Optimizing drug synergy prediction through categorical embeddings in Deep Neural Networks

Manuel González Lastre[1], Pablo González de Prado Salas[2] and Raúl Guantes[3,4,5*]

[1]Departamento de Física Teórica de la Materia Condensada, Universidad Autónoma de Madrid, Spain
[2]Foqum Analytics, Spain
[3]Departamento de Física de la Materia Condensada, Universidad Autónoma de Madrid, Spain
[4]Materials Science Institute Nicolás Cabrera, Universidad Autónoma de Madrid, Spain
[5]Condensed Matter Physics Center (IFIMAC), Universidad Autónoma de Madrid, Spain

*email: raul.guantes@uam.es

December 19, 2024

Abstract

Cancer treatments often lose effectiveness as tumors develop resistance to single–agent therapies. Combination treatments can overcome this limitation, but the overwhelming combinatorial space of drug-dose interactions makes exhaustive experimental testing impractical. Data-driven methods, such as Machine and Deep Learning, have emerged as promising tools to predict synergistic drug combinations. In this work, we benchmark the use of categorical embeddings within Deep Neural Networks to enhance drug synergy predictions. These learned and transferable encodings capture similarities between the elements of each category, demonstrating particular utility in scarce data scenarios.

Keywords: drug synergy, chemoinformatics, categorical embeddings, synergy prediction, deep learning, drug discovery

1 Introduction

Molecularly targeted anticancer drugs have proven to be a form of therapy with remarkable results in recent years [1]. However, single agent treatments lose efficacy over time as tumours develop resistance to the administered drug [1, 2]. Moreover, single drugs are not always effective at the low doses needed to tolerate side effects. In this context, drug combinations have emerged as an alternative therapy with the potential to overcome resistance and increase efficacy at small doses [3].

In the quest for effective combination therapies, high-throughput preclinical screenings play an important role [4]. They allow performing experiments in an undirected, parallelized manner, and constitute an invaluable tool for the massive interrogation of the potential effect of drug combinations. Drug combinations conferring synergy (usually quantified with respect to a null model where combined drug effects are additive or independent [5, 6]) are promising candidates for effective therapies. However, these empirical studies face several challenges, the main being the combinatorial explosion problem: the complete screening of N drugs and D doses needs D^N measurements, making exhaustive testing unfeasible. Moreover, the mechanisms of action for many drugs remain poorly understood, further complicating the prediction of synergistic or antagonistic interactions between compounds [7].

To address the combinatorial problem, many efforts have been aimed at modelling the effects of compound combinations [8]. Mathematical and statistical models [9, 10, 11, 12, 13] have been used to predict multifactorial drug responses based solely on single drug or pairwise combination data. Other approaches employed network methodology combined with biological and drug molecular information to predict drug interaction effects [14, 15]. Finally, machine learning techniques have been proven to be a useful tool in drug

discovery [16, 17, 18], as they can learn directly from the data without the need for an underlying model. In this regard, the deployment of vast amounts of molecular data informing cell attributes (gene expression, genomic mutations, copy number variations...) as well as drug features (structures, descriptors, molecular targets, fingerprints...) has boosted the application of many Machine Learning and Deep Learning (DL) methods to search for synergistic drug combinations [19, 20, 21, 22, 23, 24]. With some exceptions [21, 22], most of these approaches included a wealth of biological and molecular information combined with single drug experimental data, making it difficult to tease apart the relevance of different features in synergy prediction and thus hindering interpretation.

Dealing with complex data structures has been a challenge in Machine Learning (ML) since its inception in the mid-20th century. Vector embeddings have emerged as a transformative technique, mapping complex data structures (e.g., images, text) into a vector space more amenable to ML algorithms. These embeddings underpin many influential Deep Learning (DL) applications, such as Stable Diffusion or ChatGPT.

While certain data types, such as images, can be naturally represented as numerical arrays, embeddings extend beyond such domains. Natural language processing (NLP) exemplifies the transformative power of embeddings. Early approaches relied on simple vectorization techniques like one-hot encoding, which represent words as sparse vectors. Although sometimes effective, one-hot encoding struggles with synonyms, word order, and other subtleties of linguistic structure.

The introduction of Word2Vec marked a paradigm shift in NLP by transitioning to dense vector representations [25]. Word2Vec is also among the first applications of transfer learning in NLP—enabling models to leverage pre-trained knowledge across tasks rather than training each model from scratch. These concepts—embeddings and transfer learning—spearheaded the current golden age of NLP, which started in 2018 with the advent of the Transformer and more sophisticated forms of transfer learning [26, 27].

In recent years, categorical embedding methods have significantly advanced the ability of DL to handle categorical data in different contexts [28, 29]. During training, the neural network is forced to compress categorical information into smaller representations relevant for the task, thus inherently building meaningful relationships between the elements of the category in the embeddings. These methods can outperform traditional categorical encoding methods, like one–hot encoding, in classification and prediction problems [29].

In this study, we systematically investigate the performance of different categorical embedding methods to predict the synergy of drug combinations. First, we train three different DL models specifically designed for tabular data, comparing both performance and training time required. Later, we use the learned embeddings as input features to the most widely used machine learning methods and compare their performance relative to traditional categorical encoding techniques. To evaluate these methods, we use as a benchmark testing ground the screening dataset provided in the AstraZeneca-Sanger Drug Combination Prediction DREAM Challenge [19], using the same synergy scores, data splits and performance metric used in the competition. In order to provide a controlled and focused assessment of the suitability of categorical embeddings for synergy prediction, we used a minimal set of input features for prediction containing both numerical (single drug response features) and categorical variables, without further use of molecular or drug attributes. We show that for 10 out of the 14 benchmarked models, the learned embeddings outperform or tie to traditional encodings and in 5/14, the performance increases by more than 30%.

2 Materials and Methods

2.1 The dataset

We based our analyses on data from Sub-challenge 1 (SC1) of the AstraZeneca-Sanger Drug Combination Prediction DREAM Challenge [19]. This challenge provided a large-scale in vitro dataset, comprising 3,475 experiments involving 167 unique drug combinations tested across 85 cancer cell lines. Each experiment measured the viability of a cell line treated with a particular drug pair, from which a single synergy score was derived using the Loewe model of additive combinations[30, 19]. Positive synergy scores indicate that the combined effect is greater than expected from additivity, zero corresponds to an additive combination, and negative values indicate antagonism.

Figure 1: **Input features and output target for synergy prediction.** The dataset of input features for model training consists of: **A**. Numerical variables, corresponding to parameters of the single drug experimental dose-response curve: half-maximal inhibitory concentration (IC_{50}), slope of response (Hill coefficient $H\ S$) and drug efficacy (maximal effect E_{inf}), as well as maximum tested concentration. **B**. Categorical variables: cell line and tissue descriptor, and drug attributes (function, molecular target and pathway) as well as drug names. As output for training and prediction, we use the experimentally measured synergy scores of pairwise drug combinations (**C**).

The cancer cell lines represent six different cancer types, predominantly breast (34 cell lines), lung (22), bladder (14), and gastrointestinal (12) cancers. Each cell line is characterized by features such as the cell line name, tissue type (GDSC `tissue descriptor 2`), microsatellite instability status (`MSI`), and growth properties (adherent or suspension culture).

The drug combinations consist of pairs drawn from 118 unique compounds, including both targeted therapies and chemotherapeutic agents. For each compound (referred to as `Compound A` and `Compound B` of the pairwise combination), the dataset provides detailed information, including putative targets (`Putative target_A` and `Putative target_B`), functional annotations (`Function_A` and `Function_B`) and associated signaling pathways (`Pathway_A` and `Pathway_B`), Figure 1B. Single–drug dose–response properties are also included for each compound (Figure 1A), such as the maximum tested concentration (`Max. conc. A` and `Max. conc. B`), half-maximal inhibitory concentration (IC_{50} `A` and IC_{50} `B`), Hill coefficient (`H A` and `H B`), and maximal effect (E_{inf} `A` and E_{inf} `B`).

Our analysis focuses on utilizing the available pharmacological and cell line features without incorporating other biological and high-throughput data, such as copy-number variation, DNA methylation and transcriptomic profiles etc. The goal is to predict the synergy score of drug combinations based on this minimal set of features (Figure 1C).

2.2 Data preprocessing and feature selection

We conducted several preprocessing steps to prepare the data (available as Supplementary Data 1 in the original DreamChallenge competition paper[19]) for model training:

1. Only high quality experiments (`QA=1`) were retained, following recommendations from the original dataset to ensure data quality.

2. Drug synergy data was enriched with cell line and drug portfolio information. For the cell lines, we incorporated the categorical features: `GDSC tissue descriptor 2`, `MSI`, and cell `Growth properties`. For the drug portfolio, we included the `Putative target`, `Function` and `Pathway` for each drug.

Feature selection involved dropping unnecessary or redundant columns, including `Challenge`, `QA`, `COSMIC ID`, and columns with over 20% missing values such as H-bond acceptors (`HBA`), H-bond donors (`HBD`), `Molecular weight`, `cLogP`, `Lipinski`, and `SMILES`. Additionally, `GDSC tissue descriptor 1` and `TCGA label` were removed due to redundancy with `GDSC tissue descriptor 2`. The remaining features were grouped into categorical features (`Cell line name`, `Compound names`, `GDSC tissue descriptor 2`, `MSI`, `Growth properties`, `Putative target`, `Function` and `Pathway`) of drugs and numerical features (monotherapy dose-response parameters for each single drug as described above). The final dataset consisted of **12 categorical features and 8 numerical features**, with the synergy score as the target variable.

2.3 Evaluation metric

Due to significant experimental variability in high-throughput screenings, traditional regression metrics like mean squared error are less effective for evaluating synergy predictions. We adopted the Weighted Pearson Correlation (WPC) coefficient, as proposed in the original DREAM Challenge [19], to assess model performance. The WPC is defined as:

$$\rho_w = \frac{\sum_{i=1}^{N} \sqrt{n_i - 1}\rho_i}{\sum_{i=1}^{N} \sqrt{n_i - 1}}, \tag{1}$$

where ρ_i is the Pearson correlation coefficient between experimental and predicted synergy scores for drug combination i, n_i is the number of cell lines tested with drug combination i, and N is the total number of drug combinations. This metric emphasizes correlation across different cell lines rather than precise prediction of synergy scores. All WPC values reported in this study are calculated using the LeaderBoard (LB) dataset of the original competition, comprising 591 drug combinations for prediction. As a reference, replicate experiments in the original screening protocol achieve WPC values around 0.4, setting a practical performance upper bound [19].

2.4 Encoding Methods

2.4.1 Traditional encoding methods

We employed traditional encoding techniques such as Label Encoding and One-Hot Encoding. Label Encoding is the simplest form of encoding and consists of assigning a unique integer to each category, preserving dimensionality but potentially introducing unintended ordinal relationships between different items of the category. On the other hand, One-Hot Encoding transforms each categorical variable into binary columns representing the presence or absence of each category, which does not introduce any ordinal bias at the expense of increasing the dimensionality.

2.4.2 Embedding encodings

Categorical embeddings are proposed as a solution to the tradeoff between bias and dimensionality that traditional encodings present. Inspired by techniques from Natural Language Processing [25], categorical embeddings map item classes inside a categorical variable to dense vectors in a continuous space. Since the dimensionality of the output's vector space is smaller than the dimensionality of the input's, it forces the

Figure 2: **Training and prediction pipeline.** The processed dataset is used to train deep learning models. First, we optimize categorical embeddings for drug synergy prediction (left). These learned embeddings are subsequently employed as input features for scikit-learn models, together with the numerical features outlined in Methods. The final performance of the pipeline is benchmarked against traditional encoding methods, such as label encoding and one-hot encoding.

neural network to abstract properties from the elements inside a category.

Embeddings enable the model to learn and transfer knowledge between the categorical variables (drug and cell line information) based on the resulting network output (synergy score). The captured relationships between items of categorical variables could thus enhance predictions, specially in biological applications where data are scarce. To train and evaluate the models, we use the PyTorch Tabular library [31], which implements state–of–the–art tabular learning models, abstracts training through its *TabularModel* class and later facilitates extracting the learned embeddings with the **scikit–learn** compatible *EmbeddingTransformer* class.

We train three of the models implemented in the library: the CategoryEmbedding model, which is the simplest one and consists of a feedforward neural network utilizing embedding layers for categorical variables; AutoInt (Automatic Feature Interaction Learning via Self-Attentive Neural Networks) [32], which utilizes multihead self–attention and an interacting layer to promote interactions between different features; and TabTransformer [33], which incorporates Transformer-based attention mechanisms to learn dependencies between features. We maintain the same hyperparameters for all three models across training runs: batch size of 512, a maximum of 200 epochs, and early stopping patience of 5 epochs.

2.5   Benchmark models selection

Once the embedding vectors for our categorical features have been pre-trained with the three methods outlined above, we use them as inputs for a wide range of machine learning models commonly used for tabular data, categorized by their nature as follows:

- **Linear models:** Linear Regression, Ridge Regression, Lasso Regression, ElasticNet Regression, Bayesian Ridge Regression, and Stochastic Gradient Descent (SGD) Regressor.

- **Kernel-based and non-linear models:** Support Vector Regressor (SVR) and Gaussian Process Regressor.

- **Tree-based models:** Decision Tree Regressor, Random Forest Regressor, and Extra Trees Regressor. Additionally, boosting methods were employed, given their iterative improvement of weak learners. These models included AdaBoost Regressor, Gradient Boosting Regressor, and XGBoost Regressor

We use the **scikit–learn** [34] implementation for all models, except for XGBoost for which we employ the *dmlc/xgboost* [35] library.

To assess the performance of different encoding techniques, we also compare them with traditional label and one-hot encoding methods across the whole range of machine learning models. The computational pipeline is sketched in Figure 2.

3 Results and discussion

3.1 Performance of PyTorch Tabular Models

First, we evaluate the performance and computational cost of the PyTorch Tabular models for predicting drug synergy scores. We train three models—AutoInt, CategoryEmbedding and TabTransformer—using the dataset described in the Methods section, and compute the Weighted Pearson Correlation (WPC) for each model as a measure of prediction accuracy. Table 1 shows that, on average, AutoInt achieves the highest accuracy amongst the three, with a WPC of 0.270. In contrast, CategoryEmbedding is the fastest model, requiring an average of 4 seconds per training run but achieving a lower WPC of 0.184. TabTransformer strikes a middle ground with a WPC of 0.225, though it is the slowest to train, averaging over 9 seconds per run.

Table 1: **Performance and training time of PyTorch Tabular models.** The table summarizes the Weighted Pearson Correlation (WPC) and training times of three PyTorch Tabular models: CategoryEmbedding, AutoInt and TabTransformer. Training was performed using an NVIDIA RTX™ A1000 GPU. Results are averaged over 10 random seeds and reported as mean (standard deviation).

Model	WPC	Training time (s)
CategoryEmbedding	0.184 (0.031)	**3.996** (**0.264**)
AutoInt	**0.270** (**0.015**)	8.267 (0.118)
TabTransformer	0.225 (0.020)	9.368 (0.088)

3.2 Analysis of different embedding models

In order to gain some insight into the relationships between categorical features captured by the different embedding models, we carried out a systematic analysis of similarities among the items of a given category of drug information (`Compound, Putative target, Pathway, Function`) as illustrated in Figure 3. First, we used dimensionality reduction techniques to visualize similarities between items in the two and three main components. We employed two well established methods for non-linear dimensionality reduction: the t-Distributed Stochastic Neighbour Embedding (t-SNE)[36] and the Uniform Manifold Approximation and Projection (UMAP)[37]. Next, we applied *k-means* clustering to group items within each category. While some variability was observed across clusters, the most distinct clusters identified in the t-SNE and UMAP projections overlapped significantly (Figure S1), highlighting robust similarities between items captured by the embedding encoding.

As an example, we show in Figure 3A-C the t-SNE embedding projections of the category `Compound B`, for the three different methods employed in this work (CategoryEmbedding, AutoInt and TabTransformer) using the same number of clusters. For a controlled comparison, these embeddings correspond to trainings of the three methods initialized with the same random seed, providing a performance close to the averages shown in Table 1. Several groups of items (labels in the plots) are well separated in the two main t-SNE

dimensions. However, most of the clusters have a small overlap of labels among methods, indicating that the three embedding methods learn different relationships between variables and items. Note also that clusters do not seem to be associated to a specific functionality of the drug targets, coded by the different symbols in Figure 3A-C.

To visualize more explicitly the differences between the three embedding methods, we collect the experimental synergy scores of the training dataset and group them by their corresponding `Compound B` labels associated to each cluster, Figure 3D-F. We see that many of the clusters revealed by the embeddings display

Figure 3: **Differences in embedding vector information among methods.** Analysis of embedding vectors for the categorical variable `Compound B`, containing 47 different drug names (most of them associated to their putative molecular targets, labels in top panels). **A-C.** Embedding projections on the first two principal dimensions of t-distributed stochastic network embedding(t-SNE)[36] for the three embedding methods tested. Colors correspond to different clusters using a k-means clustering algorithm after dimensionality reduction. Symbols denote the functionality associated to the drug target. **D-F.** Boxplots with overlayed distributions (violin plots) of the z-normalized experimental synergy scores corresponding to the drug combinations containing `Compound B`, grouped by the clusters shown in the top panels. Shown with bars are the most significant differences between distribution means. Stars represent adjusted (Bonferroni) p values calculated with two-sided Wilcoxon rank-sum tests (ns: $p > 0.05$; *: $p \leq 0.05$, **: $p \leq 0.01$; ***: $p \leq 0.001$; ****: $p \leq 0.0001$). The dashed horizontal line represents the median value of the whole distribution of synergy scores. **G-I.** Boxplots of the predicted z-normalized synergy scores for the same drug combinations shown in the middle panels.

significant statistical differences among synergy scores (we show the top 4-5 most significant differences in the plots). For instance, clusters 6 and 8 in CategoryEmbedding contain synergy scores significantly below the median value, while clusters 5 and 7 include significantly higher scores. Notice that this does not mean that items in a given cluster are representing higher/lower score values. This Figure just emphasizes the fact that the embedding vectors code some meaningful (and perhaps useful) relationships among items that allow to capture trends in the data. To see how the predictions align with these trends in the experimental data, we show in Figure 3G-I the predicted synergy scores grouped by the same clusters. Notably, the biases in the experimental data are not only enhanced in the predictions (confirming that the embeddings capture the visualized trends in data), but reveal the different ways in which the trends are encoded in the embedding. The simplest method, CategoryEmbedding, shows the best overall correspondence between experimental and predicted trends, see also Figure S3. In AutoInt, predictions overemphasize the experimental trends. With this method, the biases observed in some clusters, for instance in clusters 4, 6 and 8 towards low experimental synergy scores, are pushed to lower predicted values (see the overlayed distributions in middle and bottom panels). Finally, TabTransformer reveals a net separation between low and high synergy score values, with most of the clusters showing skewed bimodal distributions of predicted synergy scores. These differences in captured data trends can also be observed in the correlations between experimental and predicted scores, Figure S2. Despite overall correlations are comparable between the different methods, TabTransformer performs worse on individual synergy predictions, as it tends to separate high and low synergy score values as much as possible.

3.3 Performance of encoding methods across machine learning models

Finally, we compare the prediction accuracy of the learned embedding encodings (AutoInt, CategoryEmbedding, and TabTransformer) against two standard methods, Label Encoding and One-Hot Encoding, by training a broad selection of machine learning models. As shown in Table 2, each model was evaluated over ten random initializations to ensure that the results are statistically significant. The Table includes both the average and the standard deviation to show that the training is robust across different seeds.

Table 2: **Performance summary (leaderboard subset) of traditional encoding methods versus learned neural network embeddings across various models.** Results are averaged over 10 random seeds and reported as mean (standard deviation). Standard deviation is omitted for deterministic training runs.

	Traditional encodings		Neural Network encodings		
Model	LabelEncoder	OneHotEncoder	CategoryEmbedding	AutoInt	TabTransformer
Linear	0.104	**0.268**	0.219 (0.021)	0.249 (0.018)	0.211 (0.021)
Ridge	0.104	0.257	0.217 (0.025)	**0.260(0.018)**	0.214 (0.016)
Lasso	0.115	0.099	**0.169(0.046)**∗	0.103 (0.017)	0.099(0.000)
ElasticNet	0.097	0.113	**0.191(0.044)**∗	0.156 (0.017)	0.105 (0.000)
Bayesian Ridge	0.090	**0.268**	0.216 (0.028)	0.263 (0.015)	0.223 (0.022)
SGD	−0.034 (0.091)	**0.268(0.004)**	0.214 (0.029)	0.259 (0.016)	0.226 (0.020)
SVR	0.101	0.194	0.207 (0.041)	**0.256(0.009)**∗	0.222 (0.010)
GP	0.112	0.118	0.016 (0.053)	**0.199(0.023)**∗	0.176 (0.011)
Decision Tree	**0.146(0.018)**	0.093 (0.029)	0.120 (0.066)	0.113 (0.050)	0.094 (0.054)
Random Forest	0.247 (0.017)	0.256 (0.021)	0.275 (0.026)	0.284 (0.016)	**0.292(0.016)**
Extra Trees	0.205 (0.023)	0.258 (0.011)	**0.280(0.017)**	0.269 (0.025)	0.278 (0.027)
AdaBoost	0.089 (0.023)	0.110 (0.018)	0.127 (0.023)	**0.206(0.045)**∗	0.145 (0.038)
Gradient Boosting	0.206 (0.005)	0.257 (0.005)	0.218 (0.036)	**0.259(0.021)**	0.250 (0.023)
XGB	0.207	0.237	**0.246(0.044)**	0.233 (0.033)	0.212 (0.042)

An asterisk (*) indicates that the embedding method achieves at least 30% better performance compared to both Label Encoding and OneHot Encoding.

For 10 of the 14 benchmarked models, embeddings either outperform or at least tie with traditional encoding methods and in 5 of them, the improvement was more than 30%. This trend holds consistently across multiple random initializations, as shown in Tables S1 and S2, where we analyze performance variability due to changes in the embedding and *sklearn* random seeds separately. Embeddings demonstrate a clear advantage in tree-based models, where they consistently outperform Label and One-Hot Encoding, with Decision Tree being the only exception. The same can be said of the kernel–based models, Support Vector Regressor and Gaussian Process, where embeddings show substantial improvements of 32% and 68% respectively (Table S3). The models with the largest observed improvements are ElasticNet (+70%) and AdaBoost (+88%) (Table S3).

When comparing the three embedding approaches, differences emerge in their effectiveness across models. CategoryEmbedding improves over traditional encodings in 7 out of 14 models, AutoInt for 8/14 and TabTransformer only for 5/14. Moreover, CategoryEmbedding and AutoInt are the best performing encoding in 4/14 and 5/14 models respectively, while TabTransformer is only the best performing method for the Random Forest model (which represents the best performing model–embedding pair in our benchmark).

These differences in performance can be better understood by analyzing the synergy score distributions across clusters represented in the embeddings, as illustrated in Figure 3G-I. Both CategoryEmbedding and AutoInt replicate more consistently the experimental synergy score distributions within their respective clusters. In contrast, TabTransformer do not reproduce these distributions accurately, often exaggerating biases. This is evident from the skewed or bimodal predicted score distributions in TabTransformer clusters, which differ markedly from the experimental ones. These discrepancies likely contribute to TabTransformer's inconsistent performance across models, as it fails to generalize well in capturing the nuanced relationships within the data.

4   Conclusions

In this work, we systematically tested the use of categorical embeddings within deep neural networks for drug synergy prediction, demonstrating their advantages over traditional encoding strategies such as Label Encoding and One-Hot Encoding. Using a minimal set of input features—focusing solely on pharmacological and cell-line properties—we systematically trained three neural network models designed for tabular data and examined the embedding representations they learned.

Our analyses showed that these embeddings capture relationships between labels included in cell-line and drug categorical variables, revealing trends in the data based on this information. This indicates that embeddings can encode meaningful patterns within categorical data for our particular task, which traditional encoding techniques may fail to capture. However, there seems to be marked differences in the type of relationships embodied by the different methods. This is highlighted both by the different clustering of drug combinations based on dimensionality reduction of the embedding vectors, and by the systematic biases in the predicted scores. These observations indicate that there is no 'one-size-fits-all' recipe for improving synergy prediction, particularly when embeddings are combined with machine learning models of different nature.

In this sense, our results demonstrate that learned embeddings either outperform or tie with traditional encoding methods in 10 out of the 14 benchmarked machine learning models, with performance improvements exceeding 30% in 5 cases. Notably, embeddings showed clear advantages in tree-based and kernel-based models, including Random Forest, Extra Trees, Support Vector Regressor, and Gaussian Process Regressor, with the latter two achieving improvements of 32% and 68%, respectively. Among the three embedding methods evaluated, AutoInt and CategoryEmbedding demonstrated broader success across models compared to TabTransformer, suggesting that explicit feature interaction mechanisms in AutoInt and the simplicity of CategoryEmbedding may generalize better in low-feature biological settings.

We emphasize that, for consistency, we used the same overall performance index (WPC) and synergy score quantification employed in the original DreamChallenge competition. Other definitions and methods to quantify synergy may represent more accurately the experimental effect of drug combinations, or improve predictions in data-driven approaches[38, 39, 40, 41, 21]. In the future, it would be interesting to explore the performance of these embedding methods with alternative synergy indicators, as well as in different drug

screenings. Moreover, we did not use available high-throughput and drug molecular information for training and prediction. We foresee that the use of this kind of biological information, combined with categorical embeddings, may significantly advance both the predictive power and the interpretability of Machine and Deep Learning tools for this task.

In summary, our study establish categorical embeddings as a scalable and data-efficient alternative to traditional encoding strategies for drug synergy prediction. These embeddings offer particular advantages in biological datasets where experiments are scarce, as they can be reused across different tasks (transfer learning).

Acknowledgments

This work was supported by the Spanish Ministry of Science and Innovation and the "ERDF A Way of Making Europe" program. M. G. L. acknowledges financial support through project PID2020-115864RB-I00 and grant PRE2021-098697. R. G. acknowledges support from project PID2021-122936NB-I00. Both M. G. L. and R. G. acknowledge additional support from the "María de Maeztu" Programme for Units of Excellence in R&D (CEX2023-001316-M).

Author contributions

All authors conceived the original idea of the work. M.G.L. wrote the pipeline for training and evaluation of the models under the supervision of R.G and P.G. R.G performed the visual analysis of the embeddings. All authors discussed the results and contributed to the writing of the manuscript.

Code and data availability

The full training and evaluation pipeline, including code and models, has been made publicly available on GitHub (edmanft/cat_drug_synergy) under an Apache License 2.0. The original dataset can be accessed in the Supplementary Information section of Menden et al. [19].

Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Competing interests

The authors declare no competing interest.

References

[1] Holohan, C., Van Schaeybroeck, S., Longley, D. B. & Johnston, P. G. Cancer drug resistance: an evolving paradigm. *Nature Reviews Cancer* **13**, 714–726 (2013).

[2] Hanahan, D. Rethinking the war on cancer. *The Lancet* **383**, 558–563 (2014). Publisher: Elsevier.

[3] Lopez, J. S. & Banerji, U. Combine and conquer: challenges for targeted therapy combinations in early phase trials. *Nature Reviews Clinical Oncology* **14**, 57–66 (2017). URL `https://www.nature.com/articles/nrclinonc.2016.96`. Publisher: Nature Publishing Group.

[4] Sun, X., Vilar, S. & Tatonetti, N. P. High-Throughput Methods for Combinatorial Drug Discovery. *Sci. Transl. Med.* **5**, 205rv1 (2013).

[5] Fitzgerald, J. B., Schoeberl, B., Nielsen, U. B. & Sorger, P. K. Systems biology and combination therapy in the quest for clinical efficacy. *Nature Chemical Biology* **2**, 458–466 (2006). URL `https://www.nature.com/articles/nchembio817`. Publisher: Nature Publishing Group.

[6] Foucquier, J. & Guedj, M. Analysis of drug combinations: current methodological landscape. *Pharmacology Research & Perspectives* **3** (2015). URL `https://onlinelibrary.wiley.com/doi/abs/10.1002/prp2.149`. _eprint: https://onlinelibrary.wiley.com/doi/pdf/10.1002/prp2.149.

[7] Chen, S.-h. & Lahav, G. Two is better than one; toward a rational design of combinatorial therapy. *Current Opinion in Structural Biology* **41**, 145–150 (2016). URL `https://www.sciencedirect.com/science/article/pii/S0959440X16301014`.

[8] Bulusu, K. C. *et al.* Modelling of compound combination effects and applications to efficacy and toxicity: state-of-the-art, challenges and perspectives. *Drug discovery today* **21**, 225–238 (2016).

[9] Zimmer, A., Katzir, I., Dekel, E., Mayo, A. E. & Alon, U. Prediction of multidimensional drug dose responses based on measurements of drug pairs. *Proceedings of the National Academy of Sciences* **113**, 10442–10447 (2016). URL `https://www.pnas.org/doi/10.1073/pnas.1606301113`. Publisher: Proceedings of the National Academy of Sciences.

[10] Wood, K. B., Wood, K. C., Nishida, S. & Cluzel, P. Uncovering Scaling Laws to Infer Multidrug Response of Resistant Microbes and Cancer Cells. *Cell Reports* **6**, 1073–1084 (2014). URL `https://www.sciencedirect.com/science/article/pii/S2211124714000862`.

[11] Wicha, S. G., Chen, C., Clewe, O. & Simonsson, U. S. H. A general pharmacodynamic interaction model identifies perpetrators and victims in drug interactions. *Nature Communications* **8**, 2129 (2017). URL `https://www.nature.com/articles/s41467-017-01929-y`. Publisher: Nature Publishing Group.

[12] Sarmah, D., Meredith, W. O., Weber, I. K., Price, M. R. & Birtwistle, M. R. Predicting anti-cancer drug combination responses with a temporal cell state network model. *PLOS Computational Biology* **19**, e1011082 (2023). URL `https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1011082`. Publisher: Public Library of Science.

[13] Comandante-Lou, N., Khaliq, M., Venkat, D., Manikkam, M. & Fallahi-Sichani, M. Phenotype-based probabilistic analysis of heterogeneous responses to cancer drugs and their combination efficacy. *PLOS Computational Biology* **16**, e1007688 (2020). URL `https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1007688`. Publisher: Public Library of Science.

[14] Cheng, F., Kovács, I. A. & Barabási, A.-L. Network-based prediction of drug combinations. *Nature Communications* **10**, 1197 (2019). URL `https://www.nature.com/articles/s41467-019-09186-x`. Publisher: Nature Publishing Group.

[15] Caldera, M. *et al.* Mapping the perturbome network of cellular perturbations. *Nature Communications* **10**, 5140 (2019). URL `https://www.nature.com/articles/s41467-019-13058-9`. Publisher: Nature Publishing Group.

[16] Lavecchia, A. Machine-learning approaches in drug discovery: methods and applications. *Drug discovery today* **20**, 318–331 (2015).

[17] Vamathevan, J. *et al.* Applications of machine learning in drug discovery and development. *Nature reviews Drug discovery* **18**, 463–477 (2019).

[18] Zhang, L., Tan, J., Han, D. & Zhu, H. From machine learning to deep learning: progress in machine intelligence for rational drug discovery. *Drug discovery today* **22**, 1680–1685 (2017).

[19] Menden, M. P. *et al.* Community assessment to advance computational prediction of cancer drug combinations in a pharmacogenomic screen - nature communications. *Nature* (2019). URL `https://doi.org/10.1038/s41467-019-09799-2`.

[20] Baptista, D., Ferreira, P. G. & Rocha, M. A systematic evaluation of deep learning methods for the prediction of drug synergy in cancer. *PLOS Computational Biology* **19**, e1010200 (2023). URL `https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1010200`. Publisher: Public Library of Science.

[21] Malyutina, A. *et al.* Drug combination sensitivity scoring facilitates the discovery of synergistic and efficacious drug combinations in cancer. *PLoS computational biology* **15**, e1006752 (2019).

[22] Gayvert, K. M. *et al.* A Computational Approach for Identifying Synergistic Drug Combinations. *PLOS Computational Biology* **13**, e1005308 (2017). URL `https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1005308`. Publisher: Public Library of Science.

[23] Kuenzi, B. M. *et al.* Predicting Drug Response and Synergy Using a Deep Learning Model of Human Cancer Cells. *Cancer Cell* **38**, 672–684.e6 (2020). URL `https://www.sciencedirect.com/science/article/pii/S1535610820304888`.

[24] Celebi, R., Bear Don't Walk, O., Movva, R., Alpsoy, S. & Dumontier, M. In-silico Prediction of Synergistic Anti-Cancer Drug Combinations Using Multi-omics Data. *Scientific Reports* **9**, 8949 (2019). Publisher: Nature Publishing Group.

[25] Mikolov, T., Chen, K., Corrado, G. & Dean, J. Efficient Estimation of Word Representations in Vector Space. *arXiv* (2013). `1301.3781`.

[26] Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *arXiv* (2018). `1810.04805`.

[27] Howard, J. & Ruder, S. Universal Language Model Fine-tuning for Text Classification. *arXiv* (2018). `1801.06146`.

[28] Guo, C. & Berkhahn, F. Entity Embeddings of Categorical Variables. *arXiv* (2016). `1604.06737`.

[29] Dahouda, M. K. & Joe, I. A deep-learned embedding technique for categorical features encoding. *IEEE Access* **9**, 114381–114391 (2021).

[30] S., L. Effect of combinations : mathematical basis of problem. *Arch. Exp. Pathol. Pharmakol.* **114**, 313–326 (1926). URL `https://cir.nii.ac.jp/crid/1571980075578237056`.

[31] Joseph, M. PyTorch Tabular: A Framework for Deep Learning with Tabular Data. *arXiv* (2021). `2104.13638`.

[32] Song, W. *et al.* AutoInt: Automatic Feature Interaction Learning via Self-Attentive Neural Networks. *arXiv* (2018). `1810.11921`.

[33] Huang, X., Khetan, A., Cvitkovic, M. & Karnin, Z. TabTransformer: Tabular Data Modeling Using Contextual Embeddings. *arXiv* (2020). `2012.06678`.

[34] Pedregosa, F. *et al.* Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research* **12**, 2825–2830 (2011).

[35] Chen, T. & Guestrin, C. XGBoost: A Scalable Tree Boosting System. *arXiv* (2016). `1603.02754`.

[36] Van der Maaten, L. & Hinton, G. Visualizing data using t-sne. *Journal of machine learning research* **9** (2008).

[37] McInnes, L., Healy, J. & Melville, J. UMAP: Uniform Manifold Approximation and Projection for Dimension Reduction (2020). URL `http://arxiv.org/abs/1802.03426`. ArXiv:1802.03426 [stat].

[38] Hafner, M., Niepel, M. & Sorger, P. K. Alternative drug sensitivity metrics improve preclinical cancer pharmacogenomics. *Nature Biotechnology* **35**, 500–502 (2017). URL `https://www.nature.com/articles/nbt.3882`. Publisher: Nature Publishing Group.

[39] Meyer, C. T. *et al.* Quantifying Drug Combination Synergy along Potency and Efficacy Axes. *Cell Systems* **8**, 97–108.e16 (2019). URL `https://www.cell.com/cell-systems/abstract/S2405-4712(19)30031-6`. Publisher: Elsevier.

[40] Wooten, D. J., Meyer, C. T., Lubbock, A. L. R., Quaranta, V. & Lopez, C. F. MuSyC is a consensus framework that unifies multi-drug synergy metrics for combinatorial drug discovery. *Nature Communications* **12**, 4607 (2021). URL https://www.nature.com/articles/s41467-021-24789-z. Publisher: Nature Publishing Group.

[41] Twarog, N. R., Connelly, M. & Shelat, A. A. A critical evaluation of methods to interpret drug combinations. *Scientific Reports* **10**, 5144 (2020). URL https://www.nature.com/articles/s41598-020-61923-1. Publisher: Nature Publishing Group.