A General Framework for Characterizing Optimal Communication in Brain Networks

Kayson Fakhar[1,2], Fatemeh Hadaeghi[2], Caio Seguin[3], Shrey Dixit[2,4,5], Arnaud Messé[2], Gorka Zamora-López[6,7], Bratislav Misic[8], Claus C. Hilgetag[2,9]

1. MRC Cognition and Brain Sciences Unit, University of Cambridge, Cambridge, United Kingdom.
2. Institute of Computational Neuroscience, University Medical Center Eppendorf-Hamburg, Hamburg University, Hamburg Center of Neuroscience, Germany.
3. Department of Psychological and Brain Sciences, Indiana University, Bloomington, IN, USA.
4. Department of Psychology, Max Planck Institute for Human Cognitive and Brain Sciences, Leipzig, Germany.
5. International Max Planck Research School on Cognitive Neuroimaging.
6. Center for Brain and Cognition, Pompeu Fabra University, 08005 Barcelona, Spain.
7. Department of Information and Communication Technologies, Pompeu Fabra University, 08018 Barcelona, Spain.
8. McConnell Brain Imaging Centre, Montréal Neurological Institute, McGill University, Montréal, Canada.
9. Department of Health Sciences, Boston University, Boston, MA, USA.
- **kayson.fakhar@mrc-cbu.cam.ac.uk**

Abstract:

Communication in brain networks is the foundation of cognitive function and behavior. A multitude of evolutionary pressures, including the minimization of metabolic costs while maximizing communication efficiency, contribute to shaping the structure and dynamics of these networks. However, how communication efficiency is characterized depends on the assumed model of communication dynamics. Traditional models include shortest path signaling, random walker navigation, broadcasting, and diffusive processes. Yet, a general and model-agnostic framework for characterizing optimal neural communication remains to be established.

Our study addresses this challenge by assigning communication efficiency through game theory, based on a combination of structural data from human cortical networks with computational models of brain dynamics. We quantified the exact influence exerted by each brain node over every other node using an exhaustive multi-site virtual lesioning scheme, creating optimal influence maps for various models of brain dynamics. These descriptions show how communication patterns unfold in the given brain network if regions maximize their influence over one another. By comparing these influence maps with a large variety of brain communication models, we found that optimal communication most closely resembles a broadcasting model in which regions leverage multiple parallel channels for information dissemination. Moreover, we show that the most influential regions within the cortex are formed by its rich-club. These regions exploit their topological vantage point by broadcasting across numerous pathways, thereby significantly enhancing their effective reach even when the anatomical connections are weak.

Our work provides a rigorous and versatile framework for characterizing optimal communication across brain networks and reveals the most influential brain regions and the topological features underlying their optimal communication.

Introduction:

In the realm of network science, the human brain represents a perfect example of a complex system. Viewing the brain as a network has uncovered key topological characteristics, including the presence of densely interconnected modules, central hubs, and hierarchical structures in information processing (Bullmore and Sporns, 2009; Sporns et al., 2004). This perspective, particularly obtained by analysis of large-scale structural brain networks — the connectome — elucidated that a range of network characteristics arise from the interplay between two conflicting evolutionary imperatives: minimizing wiring costs on one hand and maximizing signaling efficiency on the other (Betzel et al., 2016a; Gulyás et al., 2015; Kaiser and Hilgetag, 2006).

The brain is confined within a three-dimensional space, making the formation and maintenance of long-range connections metabolically expensive. Conversely, a network predominantly comprising short-range connections, although economical in wiring costs, necessitates multiple intermediate nodes for information relay to distant nodes, diminishing effective communication capacity (Bullmore and Sporns, 2012; Wang and Clandinin, 2016). It has been shown that this dichotomy leads to a compromise, where predominantly short-range connections among neighboring regions coexist with a selective set of long-range connections that function as communication shortcuts (Bassett and Bullmore, 2017; Chen et al., 2013).

In this view, signaling efficiency between nodes is graded based on the number of steps from a source to a target, presupposing information transmission *exclusively* along one path, the shortest path (Latora and Marchiori, 2001). However, it has been argued that such a conceptualization of signaling unrealistically requires brain regions to possess global knowledge of the network's connectivity (Avena-Koenigsberger et al., 2017). To address this issue, alternative **communication models (CMs)** have been developed, accommodating other conceptualizations, such as cascading dynamics and diffusive processes, where the information permeates through the network via parallel pathways. Consequently, alternative conceptualizations of how distant brain regions interact yield diverse interpretations of communication efficiency (Seguin et al., 2023). For instance, as mentioned above, the **shortest path efficiency (SPE)**, derived from the inverse of the shortest path length, reflects efficiency under the assumption that information flows along the shortest path only. In contrast, **diffusion efficiency (DE)**, defined by the inverse of the average path length of an unbiased random walker traversing from the

source to the target, assumes information to propagate along parallel pathways with no specific preference for any of them. Quantifying how much a source can effectively influence its target depends on which perspective is chosen. Given SPE, the source has optimal influence over its unconnected target, if the number of intermediate nodes along the shortest path between them is minimal. Given DE, the source has optimal influence over its unconnected target, if it has the largest number of pathways connected with it, regardless of how long they are. Thus, optimality of signaling depends on assumptions about the regime in which the information propagates in the network.

Moreover, despite this plurality of signaling conceptualizations, these models of propagation simplify communication patterns to linear, discrete interactions, thereby abstracting the complexities inherent in biological systems, such as non-linear interactions, oscillatory behaviors, and conductance delays (Seguin et al., 2023; Suárez et al., 2020). A plethora of biophysical models have been developed to address such details by modeling the behavior of regions as the average activity of biophysically grounded neuronal populations (Bettinardi et al., 2017; Breakspear, 2017). This mean-field formalization of brain activity comes with its own definitions of communication, such as communication through coherence, positing neuronal synchronization as a pivotal mechanism (Buehlmann and Deco, 2010; Fries, 2015; Vinck et al., 2023).

Therefore, while it is acknowledged that the brain's structural evolution favors optimal inter-regional communication, a consensus on the precise model of communication within brain networks and subsequently its optimality, remains missing due to conflicting assumptions about signal propagation. Addressing this issue is of particular interest, for several reasons. For example, the identification of structural features that improve information flow in brain networks elucidates their role in disease and may allow targeting them for specific therapeutic interventions. Such insights may also guide the design of neuromorphic systems that achieve a similar level of resource management as the brain (Lennie, 2003; Padamsey and Rochefort, 2023; Senn et al., 2023).

To provide a mathematically rigorous definition of optimal communication, we resort to game theory. This field analyzes interactions among agents to offer a normative account, that is, to prescribe *how they should behave* in a defined scenario, given their goals, the rules of the game, and the consequences of others' decisions (Binmore, 2007). Notably, game theoretical solutions are well established in fields where players lack 'agency'. In behavioral ecology, for example, game theoretical models are used to define normative

descriptions for how animals should behave in scenarios involving optimizing a goal, such as foraging or reproducing (Davies et al., 2012; Dugatkin and Reeve, 2000). Thus, this theoretical approach is well suited for investigating a pivotal question in neuroscience: How should brain regions interact, considering the limitations imposed by the structural connectome and the behavior of other regions, with the aim of optimizing their communication efficiency? This question is framed by two principal constraints and one overarching objective. The first constraint is imposed by the *brain's network structure*, delineating interactions between nodes. The second constraint is the *behavior of other nodes*, dictating their response to incoming signals. The objective, in this context, is to maximize signaling efficiency – conceptualized as the extent of a node's influence over others. Such a formulation gives rise to a concrete definition of optimality as an equilibrium point where no region can increase its influence on others any further. Notably, this game-theoretical approach offers a model-agnostic and data-driven toolkit to define communication within brain networks. By 'model agnostic' we mean that the game can be constructed using any model of information propagation and local dynamics incorporated into an arbitrary connectome structure. It then defines optimality in a sense that, given the defined game, how much each node can influence other nodes. Note that optimality in this framework depends on the defined game, meaning that optimal communication can differ given different network architectures and models of communication.

In the present work (summarized in Figure 1), we primarily used the human structural and functional connectomes, large-scale models of dynamics, and a game-theoretical perspective of signaling to address three questions: First, how does the communication landscape look like in the state of **optimal signal propagation (OSP)**, where nodes maximize their influence on each other given the structural and dynamical constraints? Second, which model of information propagation aligns best with the data-driven formulation of signaling? And third, which brain regions are the most influential ones and why?

To answer the first question, we used **multi-perturbation Shapley value analysis (MSA)** and approximately 7,000 million combinations of virtual lesions to precisely quantify the amount of influence exerted by each brain region (node) over every other node. We call this communication landscape the **'Optimal Influence' (OI)**. To answer the second question, we systematically compared putative models of neural

communication against the derived OI and found **Communicability (CO)** (Estrada and Hatano, 2008) to capture a substantial variation observed in OI. CO is a non-conservative cascade model that posits regions to broadcast their signals across multiple parallel pathways. However, our results indicate that CO tends to underestimate the actual influence exerted via longer pathways. Thus, we proposed complementary analytical models that better replicate the OI. Further investigations using a nonlinear model of dynamics and a **neural mass model (NMM)** allowed us to determine which of the two game constraints more strongly shape neural signaling, the global network architecture or local dynamics. We found that all models of local dynamics yielded effectively the same landscape, suggesting that network topology is a more important constraint than specific models of local dynamics. Finally, to address the third question, we revealed that areas located on the medial surface of the brain, including the precuneus, anterior cingulate cortex, and superior prefrontal cortex, exerted the strongest influence across the brain network. Notably, these regions are components of the cortical rich-club organization, which is hypothesized to act as the backbone of large-scale brain communication. Together, our results suggest that signaling in the human brain is best captured by broadcasting-like dynamics, and to optimize their influence, hub regions propagate information over multiple pathways.

Figure 1. Overview of the present work: We used the human connectome and a linear model of local node dynamics as the main network model. However, other computational models can be used, building upon different assumptions of local dynamics and other network architectures. Here, we explored Macaque and mouse connectomes, as well as nonlinear models including a neural mass model of local dynamics. These two families of variables, network structure and local dynamics, define our 'game constraints', since they dictate how information flows in the network and how nodes respond to incoming signals. For every game, i.e., computational model such as a linear model of dynamics on the human connectome, the MSA approach (cf. Figure 2) uncovered the 'optimal influence' landscape of the network. This landscape describes a game-theoretical equilibrium point at which nodes cannot unilaterally increase their influence on each other any further. We compared the optimal influence profile of nodes at this point with various communication models and analyzed the most influential nodes in such a signal propagation regime. SPE: Shortest path efficiency, NE: Navigation efficiency, SI: Search information.

Results:

Characterizing the State of Optimal Signal Propagation

To elucidate the concept of OSP, we start with an intuitive example. Consider a scenario

where an orchestra attempts to distribute funds raised from a performance. A proposal

would be to divide the funds equally among all members, a strategy that leads to the

'egalitarian value' by which every musician is paid the same amount (Algaba et al.,

2019a). However, considering discrepancies in the effort of individual players — ranging

from ensemble players to soloists and a conductor — makes this strategy *unfair* for those

who contributed more. Assuming that everyone is set to maximize their share, the

egalitarian proposal is rejected, and counterproposals follow until the *optimally fair*

solution is found that is proportional to the invested contribution of every player. One

can see this iterative process as traversing a convex solution space with a fixed point,

representing the optimal solution. Any other solution is either incorrect, e.g., the solution

results in shares that add up to a different value rather than the raised fund, or
suboptimal, meaning that a better solution exists which, given enough time, will be
selected eventually. Note that, by definition, there cannot be two equally optimal solutions
into which the payoff is divided, while it is possible for multiple players to receive the
same share, as with the egalitarian strategy.
188
This complexity mirrors the challenge we address in our study: *accurately decomposing*
the activity profile of each target node by identifying the precise contribution of each
source node. This problem and the space of all possible solutions for a network of three
nodes is depicted in (Figure.2. A and B). For every target node in a network of N nodes,
the space of all possible solutions encompasses N dimensions, with the set of potential
solutions having an arbitrarily complex structure. Consequently, finding the one optimal
solution in this space requires a systematic and extensive exploration of different
decomposition solutions. To address this issue, Shapley provided an axiomatic
framework that finds the optimal solution (called the Shapley value, see Discussion about
its distinction from SHAP values) using information from all possible ways the players
can form coalitions (Shapley, 1997). This algorithm serves as an external authority that,
instead of navigating the solution space using proposals and counterproposals,
computes the contribution of each player by systematically removing them from the
game and tracking the game outcome.

Figure 2. Visual summary of the MSA approach: A. A simple toy network with two sources and one target, in which the sources have different amounts of influence on the target. **B.** For this toy network, the space of all possible ways in which the activity of the target node can be decomposed into contributions from source nodes has two dimensions. There exists a subset of potential solutions where the activity of the target node is correctly decomposed, but the decomposition is not optimal. There exists one equilibrium point where the decomposition is correct and optimal. **C.** For every game, that is, the simulation of a whole-brain computational model, MSA performs extensive multi-site lesioning analysis to uncover the influence of every node on every other node. For every target node, MSA lesions combinations of source nodes, tracks how the activity of the target node changes given each perturbation and, for all source nodes, computes the difference between two scenarios: one with the source node included in the lesion-set, and the other where the source node is not lesioned. The difference between these two cases defines the contribution of the source to that specific coalition/combination of sources. Averaged over all contributions, the time-varying contribution of each source is then inferred. Iterating over all nodes results in the 'optimal influence' landscape that can be decomposed into two components: Direct influences, where nodes influence their connected neighbors, and indirect influences, where nodes influence distant unconnected nodes.

To do so, we used the approach of **multi-perturbation Shapley value analysis (MSA)**

(Fakhar, 2021; Keinan et al., 2004a, 2004b) that applies exhaustive multi-site virtual

lesioning across all combinations of source nodes while tracking the resultant changes

in the target node, as illustrated in (Figure 2. C.) The approach is analogous to repeatedly

performing the same musical piece while each time a subset of players is excluded,

thereby discerning each individual's contribution to the performed track (see, *e.g.,*

(Fakhar et al., 2024)). For instance, the contribution of a cello player to the song is easily distinguished by taking the difference between two pieces, once with the cello player included and once without. By evaluating all possible combinations of players, higher-order interactions are then accounted for (*e.g.,* contributions of the entire string ensemble), and thus the exact contribution of each player across all possible configurations is inferred (see section *Game-theoretical Framework* in Materials and Methods for more details). In essence, our framework reveals the unique itemized description of each player's contribution to the overall outcome. This detailed analysis allows for a precise division of payoffs, ensuring that players have no incentive to deviate from their allocated share (Gul, 1989; Pérez-Castrillo and Wettstein, 2001). The resulting game-theoretical equilibrium state, here termed the optimal signal propagation state, represents the only fair allocation of nodal influence in which no better solution can be found. Note that the 'equilibrium' here refers to the unique point in the solution space of the division problem and not the neural space (See Discussion). The MSA begins by defining a 'game.' To derive OSP, this game is formulated as a model of dynamics, such as a network of interacting nodes. These can range from abstract epidemic and excitable models (Garcia et al., 2012; Messé et al., 2015a) to detailed spiking neural networks (Pronold et al., 2024) and to mean-field models of the whole brain dynamics, as chosen here (see below). The model should ideally be fitted to reflect real data dynamics, after which MSA systematically lesions all nodes to derive the OSP. Put together, the framework is general and model-agnostic in a sense that it accommodates a wide range of network models built on different empirical datasets, from human neuroimaging and electrophysiology to invertebrate calcium imaging and anything in between. In essence, the framework is not bounded to specific modelling paradigms, which then allows direct comparison among different models (e.g., see section Global Network Topology is More Influential Than Local Node Dynamics).

Specifically, in this work, the 'game' was conceptualized as a large-scale model of the brain dynamics approximating the empirical **functional connectivity (FC)** by associating a differential equation to each node of the given **structural connectivity (SC)**. By utilizing the consensus SC and averaged FC data from 70 healthy young individuals (Griffa et al., 2019; Shafiei et al., 2019), we calibrated a linearized Wilson-Cowan model, as detailed in the 'Large-scale Computational Models of the Brain Dynamics' section under Materials and Methods. Then, MSA was used to perform

244 systematic *in-silico* lesioning of combinations of source nodes while tracking the altered

245 activity of a target node. This iterative process over all nodes elucidates the

246 comprehensive influence landscape of every node on every other node within the network

247 (illustrated in Figure 2). This landscape depicts the extent of influence one node exerts

248 over another under the state of OSP.

Figure 3. Large-scale network organization of the optimal influence landscape: Optimal influences were reorganized according to nine large-scale functional network modules and characterized by two metrics: 1. Average influence, which captures the normalized total influence of a given module within itself and to other modules. 2. Heterogeneity of influences, accounting for the normalized variation of influences within a functional module and to other modules. The egalitarian value represents a naïve strategy for assigning contributions in which all players are assumed to contribute equally, i.e., by equal division of the total influence among all nine functional modules. The bars represent how much each module deviates positively or negatively from the egalitarian assumption.

Figure 2 reveals that brain regions exert influence not only on their directly connected

neighbors, but also on distant and unconnected regions. This observation suggests that

optimal communication within the brain requires the propagation of signals beyond

immediate connections, traversing through intermediate regions to form multi-step

processing pathways. This notion is supported by evidence of significant functional

coupling between spatially distant, unconnected regions (Suárez et al., 2020). We then

reorganized the OI matrix according to established large-scale functional brain modules,

i.e., the resting-state networks, as depicted in Figure 3. We calculated two key metrics:

firstly, the average intra- and inter-module influence, which quantifies the normalized

aggregate influence that regions belonging to a module exert both internally and on other

modules. Secondly, we assessed the heterogeneity of these influences to determine the

diversity of communication patterns within and between modules. A low heterogeneity

indicates a narrow distribution of normalized total influence among nodes, measured as
the standard deviation, whereas high heterogeneity suggests a wide variation in
interaction strengths. We then asked *whether any modules exhibited deviations from the*
expected levels of influence and heterogeneity. We derived the expected level via the
egalitarian strategy where influence is uniformly distributed across all modules,
corresponding to an equal division of %100 of the flow among the nine modules. Our
analysis revealed a generally balanced communication landscape, with the largest
deviations being approximately %3. However, the default mode network stood out,
demonstrating both substantial average intra- and inter-module influence and lower
heterogeneity (Figure 3). This finding implies that nodes in the default mode network
have a large and relatively similar amount of influence over each other and the rest of
the brain. In contrast, the auditory network is characterized by a more varied and modest
level of influence, predominantly within its own module, but extending to others as well.
Together, the results presented in Figure 3 suggest that while there is a relatively
homogeneous level of influence within and between different cognitive modules, the
default mode network distinguishes itself as a key orchestrator of brain-wide
communication dynamics.
280
281 Collectively, our findings in this section indicate that manipulating a single region can
282 impact the global dynamics of the entire brain (also as shown by (Grayson et al., 2016;
283 Rabuffo et al., 2023; Young et al., 2000)), extending beyond anatomically connected
284 regions. As a result, a critical question arises: *Which poly-synaptic signaling*
285 *conceptualization most accurately encapsulates these observed indirect influences?*

Optimal Signaling via Broadcasting Over Parallel Pathways

To determine which model of signal propagation most accurately captures the indirect
influence exerted by brain regions on one another, we explored a spectrum of
communication models, spanning from routing strategies to diffusive processes (Seguin
et al., 2023, 2020). Routing strategies postulate that information travels predominantly
along, or with respect to the shortest path. As introduced before, SPE is straightforward
in its approach, focusing on the shortest path alone. **Navigation Efficiency (NE)**, on the
other hand, is a geometrically greedy routing model, aiming to minimize the physical
distance to a target node at each step. **Search Information (SI)** quantifies the amount
of information required for a random walker to find and navigate along the shortest path.

Therefore, the more the required information, the more difficult the communication
between two nodes is assumed to be. Conversely, at the opposite end of the spectrum
lie diffusion processes that envision information cascades throughout the network. This
could involve longer, even recurrent routes to the same nodes. The efficiency of signaling
under these processes is then quantified by CO and DE. CO adopts a broadcasting
strategy, whereby information spreads from the source and reaches the target through
multiple pathways, while being subjected to exponential decay with each step. This decay
inherently reduces the impact of longer pathways. DE, in contrast, does not incorporate
attenuation, focusing instead on counting the steps a random walker takes from source
to target. For detailed descriptions of these models, refer to the 'Communication Models'
section under Materials and Methods.

Figure 4. Comparison of optimal influences with other putative communication measures: Pairwise Pearson's correlation between each communication measure and optimal influences, to characterize the alignment with existing communication models. Communicability (r=0.94) and Search Information (r=-0.83) had the best alignment in this univariate setting.

A simple pairwise Pearson's correlation between OI and each CM matrices showed a
large positive correlation between OI and CO (R^2=0.88; all p-values in this work are
strictly smaller than 0.0001 unless mentioned otherwise) and a large negative
relationship with SI (R^2=0.68) while other metrics such as SPE, NE, and DE exhibited
nonlinear relationships with OI. This finding (Figure 4) suggests that, although all
conceptualizations capture a degree of OI, the one assuming an attenuating diffusion
dynamic for the signal propagation over multiple pathways most effectively mirrors OI.
This result aligns with existing studies indicating CO's efficacy in capturing the spread

of electrical stimulation to unconnected nodes (Seguin et al., 2022a), predicting large-
scale functional modules more accurately than SC (Seguin et al., 2022b), and
determining the degree of compensation by other regions following perturbation (Betzel
et al., 2016b).

However, we noticed that CO slightly underestimates the true influence of longer
pathways. To address this limitation, three alternative approaches were explored:
adjusting communicability with a scaling factor **(scaled communicability; scaled CO)**
(Zamora-López et al., 2016), using a linear instead of exponential attenuation **(Linear**
Attenuation Model; LAM), and employing the covariance structure of a **spatial**
autoregressive model (SAR) that considers linear attenuation and regional co-
fluctuation. Each of these models incorporates a single adjustable parameter: a scaling
factor for scaled CO, an attenuation factor for LAM, and a degree of spatial influence for
SAR. After fitting these parameters to replicate OI, we found that, except for SAR, the
other two models failed to rectify the issue (as shown in Figure 5. A). While scaled CO
and LAM showed marginal improvements in variance explained (R^2=0.89 and 0.9,
respectively) compared to CO (R^2=0.88), SAR achieved a near-perfect performance
(R^2=0.997). We then fitted SAR to CO instead of OI to evaluate to which extent CO
captures the real degree of spatial influence. Varying the SAR parameter indicated that
CO's positioning on the spectrum is considerably skewed towards a steep attenuation
(0.06), in contrast to OI's more moderate rate of spatial decay (0.43). This finding
supports our intuition that CO is overly strict with discounting longer pathways, since it
assumes the signal to fade almost seven times faster than it actually does. It also
indicates that a wide range of discount factors between 0.2 and 0.7 performs similarly
well (Figure 5. B), relaxing the need to search for an exact value (same applies to the
scaling factor of CO and attenuation factor of LAM; see Supplementary Figure 1).

Figure 5. Strategies to alleviate the underestimated influence of long-range pathways: A. Difference between adjacency matrices of tunable models and OI that indicates where these models underestimate (red) and overestimate (blue) the influence of nodes on each other. **B.** SAR obtains a correlation coefficient of r= 0.99 by increasing the depth by which signals can travel, however, the plot on the bottom shows that a wide range of values from 0.2 to 0.7 can be chosen with small degradation of fit. SAR: Spatial Auto-Regressive model, CO: Communicability, OI: Optimal Influence.

We subsequently explored the depth of influence in terms of the number of hops,

specifically addressing how far a signal travels before its causal impact substantially

diminishes. To this end, we used a linear regression model, fitted it to results from

progressively diffused signals in the network. Put simply, we iteratively predicted the OI

starting from walks of zero length (no spread of influence) and incrementally considered

longer walks, applying a monotonic discount to additional steps. The analysis, as

depicted in (Figure 6. A), demonstrated peak performance at the sixth step, achieving an

R^2 of 0.75. This means that the summation of only the first six steps captures %75 of the

variance in OI (also see Supplementary Figure 8 for the result from an exponential

discount instead of linear). Further, a multivariate Lasso regularized linear regression

model was trained on all walks simultaneously to identify a parsimonious combination

that most effectively predicts OI (Figure 6. B). Aligning with the result from the univariate

model, walks of length five, six, and the eighth steps (excluding seventh) were

contributing the most, allowing the model to predict OI with a high degree of accuracy

(R^2=0.96). These results imply that signal influence notably decreases after

approximately eight processing steps, despite the network's diameter being around ten

steps, meaning that the information flow between the most distant nodes is heavily

degraded (Figure 6. B). While information from the initial eight steps is sufficient to

explain %96 of the OI, the superior predictive performance of models such as SAR, LAM,

and CO suggests that incorporating all possible paths yields additional, albeit small,

information. Moreover, the real advantage of communication models lies in their relative simplicity compared to using a regularized multivariate model. Altogether, it is important to note that the longer processing pathways that are missed by CO, Scaled CO, and LAM still influence the target node, but based on comparing how much SAR gained in predictive performance, they account for about %5 of the whole communication dynamics. This finding provides a rough estimate of how much mismatch, and in which pathways, are expected when using CO, scaled CO, and LAM in human neuroimaging data. However, when these communication models were applied to mouse and macaque connectomes, a discrepancy in capturing OI in directed networks emerged (Supplementary Figure 2). SAR marginally outperformed LAM and scaled CO in the mouse connectome (r=0.21, 0.18, 0.17, respectively) but showed significantly better performance in the macaque (r=0.92, 0.24, 0.23, respectively). The enhanced performance from mouse to macaque hints at the potential influence of network size, considering the macaque network comprises 29 nodes compared to the mouse's 112. Nonetheless, the specific effects of network size, density, reciprocity, weight distribution and normalization, as well as other global characteristics on modelling OI necessitate further systematic investigation using synthetic network models. This finding delineates the limitations of current CMs in accurately depicting optimal signal propagation in large, directed networks. However, the observed inverted U-shaped fitting curves of LAM and scaled CO (detailed in Supplementary Figure 2) suggest a slower spatial decay in signal propagation than assumed by models like CO. In essence, despite the struggle of these models to precisely capture the optimal signal flow in larger directed networks, there is a consensus that the influence of regions extends further than traditionally postulated by communication models.

Figure 6. Uni-and-multivariate models of OI: A. Predictive power of a linear regression model trained on walks up to 15 broadcasting steps. **B.** A regularized multivariate model trained on all steps shows a small set of steps to be sufficient to explain %96 of OI on average. Each dot represents one cross-validation trial (N=100). **C.** Sets of regularized multivariate models were trained on network features at each degree of spatial influence for SAR and LAM to capture the impact of this parameter on the performance of the statistical model. The dashed line on the left shows a scenario when the degree of spatial influence is zero, effectively rendering SAR an identity matrix. The second dashed line indicates where the model performed the best, explaining %99 OI. **D.** Bars represent the contribution of each feature to the model, averaged over degrees of influence. Error bars indicate the %95 confidence interval. OI: Optimal influence.

In our final analysis of this section, we sought to determine if other communication

models, despite their complex relationship with OI, could surpass CO in predicting it.

Additionally, it is possible for more intuitive variables, such as the fiber length or

Euclidean distance, to provide better predictive performance. To see if OI is better

predicted using available variables, including CMs, another multivariate regularized

linear regression model was employed (illustrated in Figure 6. C). Excluding SAR, the

model successfully explained %93 of the variance in OI using just three variables: LAM,

CO, and SPE, with LAM making the most significant contribution. We then trained a set

of models with the same variables but different attenuation factors of LAM and SAR to

observe the dynamics of feature importance across different factors. To our surprise, at

its optimal parameter value, SAR emerged as the predominant predictor, effectively

simplifying the statistical model to a univariate format and once again perfectly

predicting OI (as seen in Figure 6. C). SAR maintained its dominance as the most critical variable over a range from 0.1 to 0.8, after which CO became more influential. This shift underscores the role of discounting of the signal, elucidating why DE was the least effective model in our study. The reason is that, at around $\alpha = 1$ where no discount is considered, SAR converges to DE, rendering it uninformative, whereas LAM retains its distinctiveness, surpassing both CO and SAR. Averaged over all values of α shows that SAR was the most important feature, followed by CO and LAM (Figure 6. D) which all follow broadcasting-like communication dynamics. where no discount is considered, SAR converges to DE, rendering it uninformative, whereas LAM retains its distinctiveness, surpassing both CO and SAR. Averaged over all values of α shows that SAR was the most important feature, followed by CO and LAM (Figure 6. D) which all follow broadcasting-like communication dynamics.

Collectively, our findings indicate that optimal influence in brain networks requires signal propagation across multiple pathways, akin to a broadcasting approach. The influence diminishes with each processing step, but not as quickly as it is assumed by CO. Moreover, a simple statistical model, *i.e.,* SAR, accurately predicts the network's influence structure at the optimal signal propagation regime. Importantly, previous studies indicated that SAR performs as well as many other biophysically detailed NMMs in predicting the FC (Messé et al., 2015b, 2014). Interestingly, comparing the performance of multivariate models against simple CMs suggests that little is gained from additional variables and more computationally expensive predictive models.

It is important to acknowledge that all CMs, including SAR, are predicated on a linear dynamic model, prioritizing simplicity over biophysical complexity. However, brain regions are argued to perform nonlinear operations, show oscillatory patterns of activity and show metastability by switching between multiple states to support cognition and behavior. Therefore, to affirm the notion of optimal communication in brain networks, it is essential to compare these findings with more realistic dynamics that capture such complex phenomena.

Global Network Topology is More Influential Than Local Node Dynamics

Previous research has demonstrated that linear models of local dynamics are as effective, if not more so, as nonlinear models in capturing the macroscopic dynamics of

the brain (Abdelnour et al., 2014; Messé et al., 2023, 2014; Nozari et al., 2024). This observation led us to hypothesize that optimal signal propagation in large-scale brain networks, as measured by fMRI-BOLD signal, might also be adequately represented by linear communication models. In other words, we hypothesized that *optimal signal propagation should follow the same line of reasoning and be relatively consistent across different dynamical models*. The equilibrium state in decomposing contributions should remain consistent across different dynamical models, irrespective of their complexity. This expectation would hold true unless the local dynamics — how regions process incoming signals — impose substantial constraints on information flow within the network.

To evaluate this hypothesis, we incorporated two additional models into our analysis: one using a nonlinear **tangent hyperbolic (Tanh)** transfer function, contrasting it with the linear function used in the linear model, and the other one a well-established oscillatory NMM known as the Hopf/Stuart-Landau model, operating in its critical metastable regime (Deco et al., 2017). Pearson's correlation conducted to compare these models with the linear model confirmed our hypothesis. As depicted in (Figure 7. A), both the nonlinear and Hopf models showed high correlations with the linear model (R^2=0.98 and 0.94, respectively). Further, we investigated the influence of local dynamics on OI by contrasting a model fitted to FC with one that was not, hence producing dynamics that poorly resemble the FC. The resulting scatter plot of OI for these models, as shown in (Figure 7. B), indicated another strong correlation (R^2=0.93). Collectively, these findings suggest that the equilibrium state of optimal signal propagation does not substantially vary even when employing more complex dynamical models. The reason is that, as previously found (Fakhar et al., 2024), while nonlinear transformations significantly impact the *time-varying* structure of individual contributions, they do not alter the overall amplitude of them, which in this context, is viewed as the *total* amount of influence one node exerts over another. Scaling, on the other hand, that determines the magnitude of these contributions, is inherently governed by the structural connectome across all models. Consequently, *the total influence* of one node on another is predominantly dictated by network topology rather than the specific dynamical model employed. However, *the time-resolved* pattern of fluctuations is specified by the model, which here is simply neglected as a direct consequence of collapsing the temporal information (refer to Supplementary Figure 3 for more details).

Figure 7. Correlations among linear, nonlinear, and neural mass models of local dynamics: A. OI matrices for a linear and a nonlinear model show a near-perfect correlation. Moreover, a Hopf model also has a strong correlation with the linear model, indicating that a linear model of local dynamics represents the communication in brain networks under OI as well as more complex node models **B.** Scatter plot between two settings of the same linear model, one fitted to resting-state fMRI and the other using a random value for the global coupling parameter. The finding provides evidence for the greater role of network's structure compared to nodal dynamics in shaping brain-wide optimal influence.

In summary, our findings indicate that linear models of dynamics effectively capture the degree of influence regions exert on each other under the optimal signal propagation state. Findings from this section not only corroborate previous research suggesting that macroscopic dynamics of large-scale brain networks are well approximated by linear models, but also support the hypothesis posited in the preceding section. Together, these two aspects suggest that it is the structural connectivity that shapes the landscape of optimal signaling in brain networks, rather than the models of local dynamics, since OIs are remarkably similar irrespective of the biophysical complexity embedded in models of local dynamics. The equilibrium reached in this game-theoretical framework, as demonstrated, is accurately represented by simplified abstract models of signal propagation. Thus, not only do simple communication models such as SAR perform on a par with NMMs in predicting empirical FC, but also, they represent how information optimally flows in large-scale brain networks.

Rich-Clubs Harness Parallel Pathways to Amplify Their Influence

It has been shown that a set of cortical hubs exerts a relatively large wiring cost to link with other distant regions, forming a rich-club organization (van den Heuvel and Sporns, 2011; Zamora-López et al., 2011, 2010). Thus, these topologically central nodes are argued to be the backbone of information transfer across multiple distant specialized

modules (Harriger et al., 2012; van den Heuvel et al., 2012). Previous works proposed that

these connections play a crucial role in information processing by diversifying areal

input-output connectivity (Betzel and Bassett, 2018), leading to a richer functional

repertoire (Zamora-López et al., 2016), or integrating information from the whole brain

(Goulas et al., 2015). Moreover, it was shown that the connections among adjacent

regions are stronger than those among distant areas (Beul et al., 2018; Lynn et al., 2024).

Empirical findings and modeling work have suggested an exponential distant rule by

which the strength of connections decays exponentially with spatial distance (Ercsey-

Ravasz et al., 2013; Markov et al., 2013). For instance, in our human connectome dataset,

the correlation between structural weights and fiber lengths is -0.6 (See Supplementary

Figure 4). Together, these findings pose a question, *if and how do rich-club regions keep*

their line of communication optimal given these relatively weak connection strengths of

long-distance projections?

Figure 8. Hubs, rich-club nodes, and their influence: A. Scatter plot of the influences of nodes on their connected neighbors (direct influence in Figure 2) versus the strength of the underlying connections. Despite the overall strong correlation between the total influence and the strength of structural connections, residuals (depicted by warm colors) reveal several weak connections with more influence than expected by their connection weights. **B.** The position of weak connections with strong influence in the adjacency matrix. **C.** The position of these connections in the structural brain network shows that they are mainly long-range connections among the hub regions of the cortex. **D.** shows those hub regions. **E.** The relationship between the influence of a region is and its centrality, by four centrality measures (see Material and Methods, Graph-theoretical Measures). **F.** The most indirectly influential nodes (indicated by red points in E.) that can propagate information to distant and unconnected regions. DMPFC: Dorsomedial prefrontal cortex, PCC: Posterior cingulate cortex, ACC: Anterior cingulate cortex, SFC: Superior frontal cortex, SMA: Supplementary motor area, VLPFC: Ventrolateral prefrontal cortex.

To answer this question, we first investigated the relationship between the strength of

connections between pairs of connected regions and the respective influence they assert

on each other. Intuitively, the stronger a connection is, the greater its influence, leading

to stronger communication between two regions. This relation has also been supported

experimentally by comparing the effect of optogenetics stimulation of a region over its

connected neighbors (Kim et al., 2023). Our result corroborated this finding and showed

a strong correlation between the structural weight and the amount of influence nodes

assert on their connected neighbors (r=0.95). However, several pair-wise interactions fall

well above the regression line (Figure 8. A) suggesting that some regions assert strong

influence on others despite their weak connection weights (likewise noticeable in both

mouse and macaque connectomes; Supplementary Figure 5. A). This 'bump' is also

captured by SAR, LAM, and CO (Supplementary Figure 5. B), providing further evidence

that these simple models can reproduce optimal information flow among connected

regions. As (Figure 8. B, C, and D) shows these connections mostly lie between regions

located at the medial surface of the cortex, coinciding with rich-club regions (van den

Heuvel et al., 2010; van den Heuvel and Sporns, 2011). We then computed the amount

that each node influences other *unconnected* regions (Figure 8. F) and found the same

regions to be the most influential, providing more evidence that this influence is not

related to the weak link itself, but the node's overall connectivity. To test this hypothesis,

we first computed several graph centrality measures, built both on the shortest-path and

random walk signaling conceptualization. A Spearman's rank correlation between how

influential a node is and how central it is suggests two conclusions (Figure 8. E): First, all

centrality measures show a moderate to strong positive correlation with the amount of

influence nodes assert over the rest of the network, directly and indirectly. Second, those

with the largest *indirect* influence (indicated with red) always lie on the top-right of the

data cloud, supporting the idea that they are topologically central. We further utilized null

and synthetic networks to see if we can delineate the role of connection strength and

connectivity pattern in signal propagation. Although less noticeable, the trend persisted

when the network topology was shuffled while nodal strength was preserved. It also

persisted when the weights were shuffled while the topology was held constant. The trend

only disappeared when both topology *and* weights were allocated randomly in synthetic

random networks (Supplementary Figure 5. C, D, and E).

Figure 9. Relationship between centrality of individual connections and their influence: A. Strength of individual connections versus their centrality in terms of shortest-path edge betweenness centrality. The lower panel shows the same relationship, but for the amount of influence a node has over its connected neighbor compared to the centrality of their connections. **B.** Depicts the same information for the random walk (diffusive) model of information flow. In both A and B, this relationship is compared against a null model in which the structural connectivity is shuffled while preserving the strength of each node, i.e., the weighted sum of its connections.

We then compared the edge betweenness centrality of every connection with its strength,

under both shortest-path and random walk conceptualization. **Shortest-path edge-**

betweenness centrality (SPEBC) of a link, measures how many shortest paths in the

network go through this specific connection, while **random walk edge-betweenness**

centrality (RWEBC) counts the number of times a random walker traversed this link to

move from a node to another. While the trend is missing when compared to the

connection weight, it is apparent when compared to the influence, suggesting that the

effect cannot be captured by how central *individual link*s are given these two signaling

strategies (Figure 9. A and B). Together, these findings propose that neither connectivity

nor weights *alone* are responsible for the emergence of efficient signal propagation

between weakly connected nodes. But the signature of more influence compared to the

underlying weight is only observed when central nodes are allocated with weak links.

Lastly, to further investigate this phenomenon, we systematically changed the degree of

spatial influence for a SAR model while calculating the spread of data along the second

principal component (PC). The first PC captures the main direction of variability

between the influence and connection strength, which is the observed strong

relationship. However, the second PC captures how much data points are spread

orthogonal to the main axis, indicating the amount of which weak links are influential. In

other words, this metric measures the variability around the regression line, a small

variability indicates a robust prediction of influence from the connection weight, showing

their tight coupling. In contrast, large variability approximates how much communication

between two nodes was independent of the connection strength, potentially relying on

other parallel pathways (Figure 10). We found that a steep decay factor leads to low

variability, as nodes could only influence their connected neighbors before the signal

subsides. A shallower decay rate, on the other hand, resulted in more variability since the

signal could traverse longer parallel pathways, echoing in the network and reach the

target from multiple fronts (Figure 10). This finding provides further evidence for central

nodes utilizing not only the direct path but other longer paths to compensate for the

weak direct connection strength.

Figure 10. How influence decouples from the underlying structural connections: The spread of points along the second principal component, i.e., orthogonal to the regression line, across different values of spatial influence. A very small degree of spatial influence represents a case in which the signal can only reach the neighboring nodes, while higher values indicate influences that extend over longer pathways and reverberate in the network, effectively decoupled from the underlying structural weight.

Moreover, we found that these nodes also have both larger average controllability and modal controllability (see Supplementary Figure 6), providing insight about their potential role in steering the dynamics of the brain. Average controllability measures the ability of a node to push the global dynamics into easy-to-reach states, while the modal controllability measures the power of a node to push the network towards farther and hard-to-reach states. It has been shown that the nodal strength has a strong positive correlation with average controllability and a strong negative correlation with modal controllability (Gu et al., 2015). Our results also support this finding, with the Spearman's rank correlation of nodal influence and average controllability being 0.86 and -0.63 for modal controllability. However, the influential nodes are clustered in the top-right corner of the scatter plot for modal controllability (Supplementary Figure 6). This finding suggests that these nodes steer the network to both easy-to-reach and hard-to-reach dynamical states due to their extensive local and long-range connectivity.

Altogether, results from this section propose a mechanism with which hub regions optimally communicate with their distant counterparts, given the structurally weak connections between them. These regions harness their topologically central positions to broadcast their signals not only via one (their direct) connection but other parallel indirect ones to direct the global dynamics of the brain towards different states, even

588   those that are energetically costly to reach. In other words, the weak connection between

589   two 'peripheral' nodes results in weak communication, though, this inefficiency is

590   compensated by central nodes that have access to many pathways to amplify their signal.

Discussion:

In this work, we explored the characteristics of brain communication in a state of optimal signal propagation. We employed a game-theoretical framework to uncover how nodes influence each other optimally, given a set of constraints. We defined these constraints as the network's structural topology and its functional activity, which emerged from three increasingly complex large-scale brain models. These models ranged from a linear model, where the output of each node is the weighted sum of its inputs, via a nonlinear model, in which the node modifies the incoming signals using a Tanh function, to a Hopf model that, relative to the other two models, represents more biophysical realism, such as conductance delay, metastability, and oscillatory dynamics of the brain signals, at the cost of greater computational complexity. Our results indicate that the strength by which nodes influence each other depends less on the local node model and more on the global network structure, permitting us to apply a wide range of graph theoretical metrics that fundamentally relate to the linear model. For instance, comparing putative communication models, we found that the optimal signal propagation in brain networks is better captured by frameworks that conceptualize communication to follow a broadcasting strategy. This means that, although signals travel along multiple parallel pathways, they subside after each processing step and degrade after six to eight steps. Finally, we show that topologically central brain regions, such as precuneus, prefrontal cortex, and anterior cingulate cortex, amplify their influence over remote regions by harnessing such parallel pathways. These results have several implications and caveats that are discussed below.

Interpreting Game-theoretical Solutions for Influence Decomposition

Here, we argue for developing normative formulations of brain signaling and network organization. This approach follows similar studies in synthetic brain networks, where a work also using game theory showed how nodes aiming at maximizing the network's navigability while minimizing their wiring cost organize in structures remarkably similar to empirical brain networks (Gulyás et al., 2015). Interestingly, related work (Samoylenko et al., 2022) addressed the long-standing question of why six degrees of separation exist in social networks (Travers and Milgram, 1977). Using normative modeling provided by game theory, the authors found the reason to be a trade-off between a node's aspiration to maximize its centrality, while minimizing its connection maintenance cost

(Samoylenko et al., 2022). In the present work, we also found that the first eight steps of
propagation are sufficient to reconstruct OI, with a peak on the sixth step.

As noted in the introduction, OI is model-agnostic, here, we leveraged this liberty to
compare signaling under different models of local dynamics, primarily built upon
undirected human connectome. We also included different modalities, e.g., tract tracing
in Macaque (see Structural and Functional Connectomes under Materials and Methods)
to confirm the influence of weak connections is not inflated due to imaging limitations
(Supplementary Figure 5. A). The game theoretical formulation of signaling allows for
systematic comparison among many combinations of modeling choices and data
sources. Nonetheless, in this work, we assumed full observability, i.e., complete empirical
knowledge of brain structure and function that is not necessarily practically given.
Although a detailed investigation of this issue is needed, mathematical principles behind
the method suggest that the framework can isolate the unobserved influences. In these
cases, activity of the target node is decomposed such that the influence from the
observed sources is precisely mapped, while the unobserved influences form an extra
term, capturing anything that is left unaccounted for, see (Algaba et al., 2019b; Fakhar et
al., 2024) for more technical details.

More on the mathematical principles, the Shapley value has been shown to converge to
a Nash equilibrium in some games, for instance, bargaining in which players have to
divide a sum among themselves while maximizing their payoffs, allowing us to draw a
connection between this value and the notion of the equilibrium state (Gul, 1989).
interestingly, this finding has been experimentally replicated, where subjects played a
simplified bidding game and frequently settled on division solutions very similar to their
Shapley values (Chessa et al., 2022). Thus, it is important to note that the equilibrium
discussed in the current paper is a game theoretical equilibrium in the solution space
(Figure 2. B) and not necessarily associated with the neural dynamics. Related to this
point is the notion of optimality. Here, by optimal influence, we refer to *the optimal*
solution for decomposing influences, from the cooperative game theoretical perspective,
that translates to the non-cooperative game-theoretical definition of optimality as the
largest amount of influence that a node can potentially assert on a target given the game
constraints. As depicted in (Figure 2. B.), optimality here refers to the equilibrium point
in the solution space. We call it optimal because, as shown before (Shapley, 1997), the
Shapley value is a unique solution, and in fact the only solution that satisfies three of the

four axioms related to fairness (Algaba et al., 2019a; Roth, 1988) which guarantees

stability and dominance of the solution compared to others. Lastly, the Shapley value is

being used in the context of interpretability of machine learning features by frameworks

such as **SHAP (SHapley Additive exPlanations**; see (H. Chen et al., 2022; Lundberg

and Lee, 2017)**)**. However, what is done in the present work is fundamentally different

from SHAP. Although both frameworks compute Shapley values, SHAP does it for input

features of machine learning algorithms. In contrast, here we compute the Shapley value

of each node of the network, with respect to all other nodes, at every time point. This

warrants a different interpretation of the results compared to the SHAP framework.

There is a large body of research aiming at decomposing the amount of influence

originating from a set of source nodes on a target node. Some attempts have used

information theory, such as causal information (Ay and Polani, 2008), and information

transfer (Novelli and Lizier, 2020), as well as using **Partial Information Decomposition**

(PID) (Ehrlich et al., 2022; Gutknecht et al., 2021; Luppi et al., 2024). In PID, the

information transferred can be further decomposed into synergistic, redundant and

unique contributions. In the current work, we deliberately used the wording of influence

instead of information, since a formal link between these two properties still needs to be

established (but see (Ay et al., 2019) for an example of equating them). Our framework,

however, does not measure the amount of information transferred as defined by

information theory; it also does not explicitly decompose the influence into subparts.

What it does is to characterize the amount of influence one node has over another at any

time points, given a modeling paradigm (see Supplementary Figure 3). This influence

embeds higher order interactions, such as synergistic and redundant interactions, but

eventually summarizes them into one value per time point, describing the average

contribution of a node to its targets given its contribution to all possible coalitions of

sources. Therefore, we believe that our framework complements the rich body of previous

research by providing another level of rigorous granularity, specifically, time-resolved

exact influence. Further research is needed to establish where the two perspectives of

game theory and information theory converge, and how combining them could provide

insights about communication in brain networks.

On a related note, due to its reliance on multi-site lesioning, MSA has been used to

address the complexity resulting from higher order interactions in the context of causal

inference (Fakhar et al., 2022; Fakhar and Hilgetag, 2022; Malherbe et al., 2021; Zavaglia et al., 2023). Following the well-established Woodwardian account of causality, that is, the manipulability account (Woodward, 2005), MSA at its core is a causal inference framework. The manipulability account of causality (Woodward, 2005) states that "C is a cause of E, if manipulating C results in tractable changes in E". Here we define manipulation as lesioning, as is customary in neuroscience (Adolphs, 2016; Joutsa et al., 2023; Siddiqi et al., 2022; Vaidya et al., 2019). We then address the problem of "counterfactuals" by exploring all possible ways that causes can interact at any time-point to produce an effect, leading to one of the most detailed accounts of causality. Therefore, placing our method in the large family of **effective connectivity (EC)** methods appears as a natural next step. However, here we decided to opt out of this comparison in favor of communication models, since they conceptualize brain-wide causal interactions, which involve both direct and indirect interactions, uncovering causal pathways instead (Ross, 2018). Expanding causal relationships to pathways of different lengths allows for multiple causes to interact and jointly produce an effect. Moreover, comparing our findings with those from EC approaches would involve considering a host of methods, not limited to but including spectral dynamic causal modeling (Seguin et al., 2019), partial correlation analysis, Granger causality, dynamic differential covariance (Y. Chen et al., 2022; Laasch et al., 2024), transfer entropy (Novelli and Lizier, 2020), and so forth. We believe that this worthwhile comparison calls for a separate and extensive analysis that is beyond the scope of the current work.

Finally, our framework is model-agnostic, meaning that the game and its constraints should be defined first. This approach comes with great liberty to explore different dynamical models. However, we acknowledge that this freedom can be a double-edged sword. On the one hand, it allows researchers to investigate a multitude of questions, potentially providing meaningful insight into the mechanism of communication and its role in behavior. On the other hand, it can result in ill-conceived games that lead to misinterpretations. For instance, here the time-resolved influence of all nodes over each other is a three-dimensional array. Conventionally, it would be tempting to average over the time points and produce a time-averaged influence matrix. However, since our models were stationary, the average value of the vector would be highly noisy, providing little insight into "how much" nodes modulate each other's activity. Instead, we computed the variance to capture this feature, but one might as well compute alternative

metrics, such as standard deviation, entropy, energy, where each requires careful interpretation. Moreover, variance alone might be a poor indicator of influence if the network has inhibitory connections, as both biological and **artificial neural networks (ANNs)** tend to have. By contrast, the present work focuses on conventional neuroimaging datasets with non-negative connection weights.

In sum, it is crucial to define every step of the game carefully to avoid misinterpretations. It is also important to keep in mind the provided definitions for optimality, equilibrium and influence to avoid confusion in interpreting the results of the game-theoretical analysis.

Broadcasting as an Optimal Signaling Strategy

Many previous studies in network neuroscience have relied on a graph theoretical definition of efficiency that is based on the shortest path distance (Sporns, 2018). Here, we show that the underlying signal propagation dynamics in large-scale brain networks is likely to follow a broadcasting regime. This finding implies that broadcasting goes beyond signaling along the shortest path but does not downplay its role. In other words, we show that the shortest path is critical, but not the only path along which a signal traverses. The broadcasting mechanism also circumvents a major problem of the shortest path signaling concept, that nodes would have to find the shortest path to every other node in the network without access to global information on the network organization. By broadcasting, nodes simply transmit their signal via their outgoing connections in every direction. And since the signal degrades over every step, nodes topologically closest to the source receive the signal most strongly. Put differently, navigation along the shortest path emerges naturally and without a need for centralized routing strategies, simply because the closest node receives more signal compared to the farther ones. This line of reasoning is compatible with the result depicted in (Figure 8. E) where closeness centrality predicted the influential nodes with such great accuracy compared to other centrality measures. Additionally, communication models, such as communicability, are thought to be energetically costlier than routing strategies, such as signaling exclusively along the shortest paths (Seguin et al., 2023). The reason for this argument is the fact that communicability accounts for paths of all length. However, as shown here, paths longer than seven steps are unlikely to be meaningfully contributing. Supporting this finding, Griffa and colleagues (Griffa et al., 2023) used information theory

and found that not only parallel communication is present in the human cortex, but also pathways longer than five steps are not as effective. These observations suggest that regions balance between robustness and energetic cost of signal transmission by using a handful of parallel pathways. Intriguingly, (Griffa et al., 2023) reported that the capacity for parallel communication is larger in the human cortex compared to macaque and mouse, proposing an evolutionary advantage for broadcasting over multiple pathways (Griffa et al., 2023). They also found that these pathways are more frequently placed between different functional modules, rather than within them, which aligns with our finding that hub regions harness parallel pathways to compensate for weak structural connections among them.

Another implication of this finding is that metrics such as global efficiency, representing the average shortest-path distance between all nodes, are not ideal for capturing the signaling dynamics of the brain. As Zamora-Lopez and Gilson argue (Zamora-López and Gilson, 2023), all such graph theoretical metrics assume some sort of dynamics. It is important to first establish the correct dynamics and then apply the corresponding metrics. Prompted by our findings, we would suggest that, when possible, metrics based on the shortest path distance should be replaced with others based on communicability, LAM, or SAR. For instance, instead of using the average shortest path as a measure of global network efficiency, one may compute the average communicability as *global broadcasting efficiency*. Similarly, closeness centrality may be redefined as the *broadcasting strength* by taking the average node-wise communicability instead of the average node-wise shortest-path distance.

Next, it is not yet clear whether the broadcasted signal is modified along longer chains in the network, or just relayed to boost the transmitted information. If the signal is modified, then it is likely that these pathways serve a computational role. Previous work suggests that within-module communication involves more redundant information compared to communication across modules which is mainly synergistic (Luppi et al., 2024, 2022). Interpreting our work in this perspective, information travels along fewer parallel pathways within a functional module to be processed locally, resulting in higher redundancy. However, signals are likely modified along the parallel pathways and combined with incoming signals from other modules, leading to a greater synergy.

Interestingly, the broadcasting conceptualization is argued to be a better model of information propagation in social networks compared to a random-walker-based navigation (Ghosh et al., 2011). In neuroscience, the broadcasting model of information propagation bears qualitative resemblance with concepts such as traveling waves of excitation (Muller et al., 2018), bridging a gap between communication models and communication via oscillation. Notably, we found a correlation of 0.23 between OI and FC (Supplementary Figure 9), that is close to what has been previously reported by comparing **cortico-cortical evoked potentials (CCEPs)** with FC (Keller et al., 2011). Moreover, it has been proposed that at least a subset of CCEPs propagate as traveling waves (Campbell et al., 2023). Together, these works, and our findings suggest that, first, correlation-based measures such as FC capture the propagation of information in brain networks to a limited extent, and second an approach combining CMs with traveling waves could provide biophysical mechanisms for simple signal propagation models based on broadcasting regime such as communicability. Nonetheless, our framework is grounded in game theory where its fundamental assumption is that nodes aim at maximizing their influence over each other, given the existing constraints. This assumption is well explored using various theoretical frameworks (Buehlmann and Deco, 2010; Bullmore and Sporns, 2012; Chklovskii et al., 2002; Laughlin and Sejnowski, 2003; O'Byrne and Jerbi, 2022) and remains open to further empirical investigation. Here, we used game theory to mathematically formalize a *theoretical optimum* for communication in brain networks. Our findings then provide a possible mechanism for achieving this optimality through broadcasting. Based on our results, we speculate that, there exist an optimal broadcasting strength that balances robustness of the signal against its metabolic cost. This hypothesis is reminiscent of the concept of brain criticality, which suggests the brain to be positioned in a state in which the information propagates maximally and efficiently (O'Byrne and Jerbi, 2022; Safavi et al., 2024). Together, we suggest broadcasting to be the possible mechanism with which communication is optimized in brain networks, however, further research directions include investigating whether signaling within brain networks indeed aligns with a game-theoretic definition of optimality. Additionally, if it does, subsequent studies could then examine how deviations from optimal communication contribute to or result from various brain states or neurological and psychiatric disorders.

Finally, we found that the rich-club organization of the human cortex is a major contributor to shaping brain-wide communication dynamics. An inspiring work using normative modeling suggested that hierarchies and rich-club organization are spandrels of modules and hubs (Rubinov, 2016). Spandrels are evolutionary features that evolve alongside adaptive phenotypes, while themselves serve no adaptive function. In other words, the rich-club organization is proposed to be the byproduct of modular organization while serving no adaptive function by itself (Gould and Lewontin, 1979). Our work provides evidence that, although the rich club organization could have emerged as a byproduct of modular organization, it might not be a purely ornamental spandrel, as the rich club regions represent the most influential regions of the brain (Figure 8). Previous works relating rich club regions to signaling also indicated an integrative role of these regions, which have longer temporal receptive fields compared to others, allowing them to integrate more information over time (Chaudhuri et al., 2015; Hasson et al., 2008). Interestingly, our results depicted in Figures 8 and 10 support this idea. We found that rich club regions integrate signals over longer and parallel structural pathways, enhancing their broadcasting capacity. Moreover, a recent empirical work identified disturbances in these regions and their broadcasting efficiency in patients suffering from disorders of consciousness (Panda et al., 2023). Put together, these findings suggest a causal functional role for the rich-club organization of the human cerebral cortex.

Role of Network Dynamics in Optimal Signaling

Although our work suggests a greater role for the network's structure in shaping the state of optimal signal propagation in the network compared to the specifics of the local node dynamics, this finding does not mean that the local dynamics are irrelevant. We believe that the inequality between the network's structure and dynamics in determining signal flow arises from factors such as the assumed homogeneity of nodes in our network models. Here, nodes are assumed to be identical objects with identical features and dynamics. This assumption certainly does not apply in the brain, and a growing body of network models that incorporate regional differences aim at addressing this issue (Bazinet et al., 2023; Deco et al., 2021). As mentioned before, our framework is model agnostic, so it is also possible to interrogate networks with heterogeneous models of dynamics. For applying the present approach to heterogeneous networks, we hypothesize that, firstly, how nodes influence one another further decouples from the structure (Fakhar et al., 2022), and secondly, simple communication models fail to replicate the OI

858 as well as they have done in this work. Thus, further work can shine light on the interplay
859 between the network's structure and its dynamics in shaping OI, since not only
860 heterogeneous network models are biologically more plausible, but also, they can help
861 to investigate how information optimally flows in networks where nodes respond
862 differently to incoming signals.

Limitations and Further Directions

A conceptual note is that OI, as a normative framework, describes the landscape of
communication dynamics if nodes maximize their influence. As in other game-
theoretical models, this assumption might not fully hold. The derived landscape is a
prediction that would need to be experimentally tested using *in-vivo* multi-site lesioning
experiments, which is currently not feasible. However, recent work indirectly supports our
findings by showing that propagation of electrical stimulation in the human cortex is well
captured by communicability (Seguin et al., 2022a), which we found to have one of the
largest correlations with OI. There are also technical limitations of our framework,
specifically its computational cost, since one needs potentially to simulate millions of *in-*
silico lesion combinations for each target node. For instance, in this work we performed
around half a billion lesion simulations for just one game, such as a linear model on the
human connectome (see section Game-theoretical Framework in Material and Methods).
Performing such an intensive analysis is not possible on a simple laptop. Therefore, due
to its brute-force approach, our framework provides rigorous results at the expense of
high computational effort, apart from the fact that it is yet to be used *in-vivo* (but see
(Zavaglia and Hilgetag, 2016)).

Finally, we focused on the influence of nodes on each other without relating them to
behavior or cognitive function. Moreover, we did not investigate how this influence
landscape changes due to brain disorders, aging, and other factors. Future work may take
on these challenges, for instance, by tracking the dynamics of OI during
neurodegenerative disease progression.

Material and Methods:

In this study, we used multiple Python libraries, including MSApy (Fakhar, 2021), Neurolib (Cakan et al., 2023), Netneurotools, BCTpy (Rubinov and Sporns, 2010), nctpy (Parkes et al., 2022), and Networkx (Hagberg et al., 2008). The Jupyter notebooks and Python functions to reproduce this work are available at the GitHub repository below:

https://github.com/kuffmode/OI-and-CMs

The simulation results are available at the link below:

https://zenodo.org/records/10849223

Additionally, a dedicated user-friendly Python library to compute OI and some communication models is developed and can be found at:

 https://github.com/kuffmode/YANAT

All connectomes are available as a part of the Netneurotools library:

https://github.com/netneurolab/netneurotools

Structural and Functional Connectomes

We analyzed three publicly available connectomes of human, macaque, and mouse to address differences in invasive versus non-invasive imaging modalities and reconstruction techniques.

Human Connectome

Structural and functional connectivity datasets were acquired from a cohort of 70 healthy subjects at the Lausanne University Hospital in Switzerland, and the details are described elsewhere (Griffa et al., 2019; Shafiei et al., 2020, 2019). Briefly, the group comprised individuals with an average age of 28.8 years (standard deviation 9.1 years), including 27 females, and all were scanned using a 3 Tesla MRI machine. A deterministic streamline tractography was employed to create individual SC matrices from each participant's **diffusion spectrum imaging (DSI)** data, which were recorded at five distinct levels of brain parcellation. However, here we have used only one with relatively high-resolution (219 cortical regions). The strength of each structural connection within these matrices was approximated by the density of fiber tracts.

To mitigate the size disparities between brain regions and counteract the inherent preference for longer fiber tracts in the tractography technique, a normalization

procedure was applied. This involved adjusting the streamline counts by the average
surface areas of the connected regions and the mean streamline lengths. The
culmination of this process was the formation of a unified, binary group-average SC
matrix, which was derived using a consensus strategy that ensured the individual edge
length distributions were conserved (Betzel et al., 2019; Griffa et al., 2019).

Functional brain data were gathered from the same group of subjects through **resting-**
state functional MRI (rs-fMRI) scans conducted with open eyes. The initial processing
steps of this functional data included adjustments for several physiological variables,
notably the influence of white matter, cerebrospinal fluid, and motion artifacts that
comprise three axes of translation and rotation as determined by rigid body co-
registration. Following these corrections, the **blood oxygen level-dependent (BOLD)**
time series were subjected to a low pass filtering process, utilizing a temporal Gaussian
filter set to a full width half maximum of 1.92 seconds. The analysis excluded the first
four temporal points from each scan and further data refinement was achieved through
high-motion frame censoring, a method detailed in Power and colleagues (Power et al.,
2012).

For the assessment of FC, the study calculated zero-lag Pearson correlation coefficients,
which measured the functional relationships between pairs of brain regions in each
individual's rs-fMRI time series. Lastly, the group-average FC matrix was computed as
the mean of these individual pairwise connectivity values, which includes negative values
as well.

Macaque Connectome
The connectivity matrix for the macaque was derived from retrograde tract-tracing
experiments and is provided by (Markov et al., 2013). These experiments involved the use
of fluorescent tracers in a group of 28 macaque monkeys. The projections that were
reconstructed from these experiments were mapped according to a division of 91 cortical
areas. This division was based on a combination of histological examinations and atlas-
based references. In each tract-tracing experiment, Markov and colleagues quantified
the number of neurons that were labeled in each of these 91 areas. The count of labeled
neurons was then adjusted by subtracting the number of neurons that were native to the
site of tracer injection. The outcome of this process was a 29×91 matrix, which represents

the connection weights extending from each injection site to other regions of the brain.

Here, we focused on the subset of this matrix that describes the weighted and directed

connections between 29 cortical areas, leading to a 29×29 SC matrix.

Mouse Connectome

The connectivity matrix for the mouse was compiled using tract-tracing data openly

accessible from the Allen Institute Mouse Brain Connectivity Atlas (Oh et al., 2014).

Briefly, the process involved injecting anterograde recombinant adeno-associated viral

tracers into designated areas within the right hemisphere of mouse brains. Three weeks

following the injection, during which the viral tracer projections developed, the brains

were extracted for reconstruction. These reconstructions were then standardized and

aligned with the Allen Reference Atlas' common coordinate framework.

Nodes in the network were identified based on a specialized parcellation derived from

the Allen Developing Mouse Brain Atlas. This parcellation initially included 65 areas in

each hemisphere, but 9 areas were excluded as they did not participate in any tract-

tracing experiments. Consequently, the network that was analyzed constituted 112

regions (Rubinov et al., 2015). Edges represent axonal projections between different

areas, and they were quantified as normalized connection densities. Specifically, this

measure represents the number of connections per unit volume from a source area to a

target area.

Large-scale Computational Models of the Brain Dynamics

In this work, we employed three models with increasing biological fidelity. The most

abstract and simplistic model is the linear model, where the output of a node is a

weighted sum of its inputs. The nonlinear model extends the linear model by applying a

nonlinear transformation to the input (here, tanh(•)) And lastly, the neural mass model

describes nodes as Stuart-Landau oscillators. Below are the details of each model.

Linear and nonlinear Model

The linear model we used, also known as the multivariate Ornstein-Uhlenbeck process, follows the continuous dynamical system equations described in (Fernández Galán, 2008).

$$\tau \frac{dx_i}{dt} = -x_i(t) + g \sum_{j=1}^{N} W_{ij} x_j(t) + \sigma_{in} \xi \tag{1}$$

Independent Gaussian noise ξ with mean zero and unit variance were presented to each node. Here, τ denotes the relaxation time of the node, which was set to 0.02. It should be noted that, in practice, the adjacency matrix is normalized to ensure that its largest eigenvalue $|\lambda_{max}| = 1$. Consequently, the practical decay rate aligns with the product of the relaxation time, τ, and the maximum eigenvalue, λ_{max}. σ_{in} denotes the strength of the noise and was set to 0.05 in all experiments. Given the empirical functional connectivity matrices, we optimized the coupling parameter, g, to maximize correlation between empirical and simulated FCs. With our modeling setting, $g = 0.74$ demonstrated the best fit, with a correlation of 0.23. The nonlinear model modifies the linear one simply by adding a nonlinear transformation and a larger input noise of 2 instead of 0.05 to go beyond the linear part of the function, leading to the equation below:

$$\tau \frac{dx_i}{dt} = -x_i(t) + tanh(g \sum_{j=1}^{N} W_{ij} x_j(t) + \sigma_{in} \xi) \tag{2}$$

Neural mass model

Further, we explored SC networks governed by Hopf/Stuart-Landau equations (Deco et al., 2017). This model, recognized as the canonical approach for examining the shift from noisy to oscillatory dynamics, elucidates the behavior of a nonlinear oscillating system near the Hopf bifurcation. In essence, the dynamics of each network node are captured by the following complex equation:

$$\frac{dz_i}{dt} = (a_i + j\omega_i - |z_i|^2)z_i + \sigma_{in}\xi_i \tag{3}$$

Where $z_i = x_i + jy_i$ is a complex representation of the node state, with $\xi_i(t)$ representing

Gaussian noise characterized by a standard deviation $\sigma_{in} = 0.05$. This system undergoes

a supercritical bifurcation at $a_i = 0$, where it shifts from a stable fixed point (i.e., $z_i = 0$)

to a limit cycle oscillation with frequency $f_i = \omega_i/2\pi$.

By decomposing the complex state into its Cartesian components and incorporating the

influence of other nodes in the input of each node, we derived a set of coupled equations

(Eq. 4) to govern the entire brain dynamics. This formulation enables the representation

of the influence of nodes on each other's temporal state through a diffusive interaction,

where g serves as a global coupling factor.

$$\frac{dx_i}{dt} = (a_i - x_i^2 - y_i^2)x_i - \omega_i y_i + g \sum_i W_{ij}(x_j - x_i)\sigma_{in}\xi_i$$
$$\frac{dy_i}{dt} = (a_i - x_i^2 - y_i^2)y_i + \omega_i x_i + g \sum_i W_{ij}(y_j - y_i)\sigma_{in}\xi_i$$

(4

Similar to the other two models, the global dynamics of the network are influenced by

model's parameters. Here, we precisely tuned the global coupling, g and the bifurcation

parameter, a_i, to match the empirical FC. Setting g at 5.6 and $a_i = 0.15$ for all nodes,

yields a correlation of 0.35. Other parameters, as detailed in the Neurolib library, remain

unaltered as follows. The model features a diffusive coupling type, a signal velocity of

20.0 m/s, a global coupling strength set at 5.8, a 5.0 ms Ornstein-Uhlenbeck timescale,

Ornstein-Uhlenbeck noise intensity fixed at 0.05 mV/ms/sqrt(ms), a mean value of

Ornstein-Uhlenbeck process maintained at 0.0 mV/ms, a Hopf bifurcation parameter set

to 0.15, and an oscillator frequency of 32 Hz. We collected state variable, x, representing

signals acquired from various brain regions for subsequent analyzes.

1027

Game-theoretical Framework

MSA is built upon Shapley values, which quantify a player's *fair* share of a collectively

generated outcome (see Figure 2). Generally, Shapley values are calculated by adding a

player to all possible coalitions and observing the value they bring to the coalition.

Formally, the contribution of player i to a coalition S is given by: to a coalition S is given

by: $\Delta_i(S) = v(S \cup \{i\}) - v(S)$

Where $\Delta_i(S)$ represents the value of coalition S. The Shapley value γ_i is the average of

these contributions across all permutations R of the player set:

$\gamma_i(N, v) = \frac{1}{n!} \sum_{R \in \mathcal{R}} \Delta_i(S_i(R))$

where $\mathcal{R}$ is the set of all permutations, and $S_i(R)$ is the coalition formed by ordering R

up to player i. However, due to the computational complexity of calculating Shapley

values for large sets, MSA relies on an unbiased estimator by sampling permutations. We

employed a sample size $m \ll N!$, generating N × m unique permutations for every target

region, where N is the number of source regions.

1042

In this work, we iterated this process over every node (target node) by systematically

lesioning other nodes (source nodes) and tracking the time-resolved difference between

when the sources were lesioned and when they were not. Lesioning was modeled by

setting the incoming and outgoing connections of sources to zero. For every source node,

we sampled 1,000 permutations. However, we confirmed that the algorithm converged

by comparing it against a larger sample size of 10,000, which resulted in a correlation

coefficient of 1.0 (supplementary Figure 7). We also ran the analysis for 10 repetitions

and averaged the resulting influence matrices. The final matrix has a shape of (number

of regions × number of regions × simulation time) that we reduced to a two-dimensional

matrix (number of regions × number of regions) by taking the variance of each influence

profile. Altogether, each of the experiments on the human connectome resulted in

roughly 480 million *in-silico* lesions (219 targets x 219 sources × 1,000 combination of

lesions per source for each target × 10 trials). Due to the computational implausibility of

the neural mass model, we ran the analysis only once instead of 10 repetitions, thus 48

million lesions. Together with all control analyzes, the total number of in-silico lesions

for the human connectome amounts to 7,200 million:

480m for the linear model, 480m for the nonlinear, 48m for the Hopf, 480m for the

topology-shuffled null model, 480m for the weight-shuffled null model, 4,800 for the

case where we used 10,000 lesion combinations per source for each target, and 480m

for a test case where the coupling was set to zero. All experiments were conducted on a

high-performance computing facility provided by the institute of computational

neuroscience, university hospital of Hamburg.

Communication Models and Measures

In this section, we introduce the communication models and measures employed to analyze the dynamics of information flow within the studied network. The corresponding formulas and procedures for computation are presented in Table 1.

The structural connectivity matrix $W \in \mathbb{R}^{N \times N}$ denotes the strength of pairwise connections between N brain regions. We define the connection length matrix $L = 1/W$, where L_{ij} is the travel cost between regions i and j. This conversion from connection weights to lengths is required for network communication models that optimize for minimal transmission cost of signals, e.g., shortest path efficiency.

Table 1: Communication Models and Measures

Models	Measures [*]	References
Shortest Path Efficiency Floyd-Warshall algorithm	$SPE = \dfrac{1}{\Lambda^*}$ $\Lambda_{ij}^{\Omega^*} = L_{iu_1} + \cdots + L_{u_k j}$ $\Omega_{ij}^* = \min\limits_{\Omega_{ij}=\{i,u_1,\ldots,u_k,j\}} \dfrac{1}{\Sigma_{l=1}^{k} w_{u_l u_{l+1}}}$	[10], [39]
Navigation Efficiency	$NE = \dfrac{1}{\Lambda}$ $\Lambda_{ij}^{\Omega} = L_{iu_1} + \cdots + L_{u_k j}$ $L_{st} = \min\limits_{(s,s+1)\in V} \|D_{st}\|_2^2$	[39], [115]
Diffusion Efficiency	$DE = \dfrac{\Sigma_i \Sigma_j \frac{1}{t_{ij}}}{N(N-1)}, \; i \neq j$ $t_{ij} = \dfrac{z_{jj} - z_{ij}}{\omega_j}, \; i \neq j$ $Z = [z_{ij}] = (\mathbb{I} - \hat{W} + \hat{\omega})^{-1}$ $\hat{W} = [\hat{w}_{ij}], \; \hat{w}_{ij} = \dfrac{W_{ij}}{\Sigma_{u=1}^{N} W_{iu}}$ $\omega = [\omega_1, \ldots, \omega_N]^T, \; \omega \hat{W}^T = \lambda \omega.$ $\hat{\omega} = [\omega, \ldots, \omega]$	[39], [117]
Search Information	$SI = -\log_2(\Pi)$ $\Pi_{\Omega_{ij}} = \hat{w}_{iu} \times \cdots \times \hat{w}_{ij}$	[39], [86]
Communicability	$CO = [co_{ij}]$ $co_{ij} = \Sigma_{k=0}^{\infty} \dfrac{(\hat{W})_{ij}^k}{k!} = e^{\hat{W}}$	[25]
Scaled Communicability	$SCO = [sco_{ij}]$ $sco_{ij} = \Sigma_{k=0}^{\infty} \dfrac{(\alpha\hat{W})_{ij}^k}{k!} = e^{\alpha\hat{W}}$	[44]
Linear Attenuation	$LAM = (\mathbb{I} - \alpha\hat{W})^{-1}$	[117]
Spatial Autoregressive	$SAR = (\mathbb{I} - \alpha\hat{W})^{-1}(\mathbb{I} - \alpha\hat{W})^{-T}$	[43]

[*] Throughout the table, $W \in \mathbb{R}^{N \times N}$ is the adjacency matrix corresponding to a given graph, $G = (V, E)$ with N vertices (nodes). W_{ij} signifies the connection strength from vertex i to vertex j. Anatomical connections are indicated by $W_{ij} > 0$ for connected region pairs and $W_{ij} = 0$ for unconnected pairs. L denotes the matrix of path lengths, defined as the reciprocal of W, such that $L = \frac{1}{W}$ with L_{ij} as the path length between two connected nodes, i and j. Further, $\Omega_{ij} = \{u_1, u_2, \ldots, u_k\}$ is the sequence of nodes visited along the shortest path between nodes i and j. Given the spatial organization of nodes in empirical structural connectivity, D_{st} includes the Euclidean distance between source, s, and destination, t nodes in finding optimal paths. The term $\hat{W}$ signifies the normalized adjacency matrix, where each element $\hat{w}_{ij}$ is obtained by dividing the original connection strength, w_{ij} by the sum of all connection strengths in the corresponding row of the matrix W. $\mathbb{I}$ is the identity matrix, T stands for transposed inverse matrix, and $\alpha < \frac{1}{\lambda_{max}}$ where λ_{max} is the spectral radius of the adjacency matrix, W. λ denotes the eigenvalues of a given matrix.

Shortest Path Efficiency

Shortest Path Efficiency measures the effectiveness of communication along the most direct route between two nodes in a network. Here, the Floyd-Warshall algorithm was employed to determine the sequence of regions $\Omega_{ij} = \{i, u, \ldots, v, j\}$ that minimizes the total transmission cost for signals traveling between regions i and j. This cost, denoted by Λ_{ij}^* is defined as the sum $L_{iu} + \cdots + L_{vj}$. Subsequently, the Shortest Path Efficiency (SPE)

1080 between two regions is quantified as the reciprocal of the minimum transmission cost,

1081 expressed as $SPE_{ij} = 1/\Lambda^*_{ij}$ as detailed in (Latora and Marchiori, 2001).

1082

Navigation Efficiency

Navigation within the network employs a greedy protocol that assumes signal

transmission to minimize the inter-regional Euclidean distance. The process involves

iterative progression from a source region i to a target region j. At each step, the

neighbor spatially closest to j is chosen as the next node in the path (Seguin et al., 2018).

This sequence continues until the target is reached, marking successful navigation, or a

previously visited node is encountered, indicating a failure in navigation. The cumulative

length of a successful path is denoted by $\Lambda_{ij} = L_{iu} + \cdots + L_{vj}$, where $\Omega_{ij} = \{i, u, \dots, v, j\}$

represents the sequence of nodes traversed. If navigation fails, Λ_{ij} is set to infinity.

Navigation efficiency is thus defined as the reciprocal of the traversed path length.

1093

Diffusion Efficiency

The Diffusion Efficiency (DE) model characterizes signaling through the lens of random

walks. The computation of DE involves the utilization of the transition matrix, P within a

Markov chain process unfolding on the connection weight matrix, W. Specifically, it

considers the probability p_{ij} that a simple random walker at node i will advance to node

j and the mean first passage time, t_{ij} which quantifies the expected number of

intermediate regions visited in a random walk. To elaborate on the computation

procedure, please refer to Table 1. Additionally, for a more in-depth theoretical

understanding, consult references (Goñi et al., 2013; Zhou, 2003).

1103

Search Information

Search information is a metric that evaluates the required amount of information to push

a random walker towards the shortest path, thereby reflecting the accessibility of efficient

communication routes under a diffusive model. Computing SI involves finding the above-

mentioned shortest path, Ω_{ij} between two regions, and the probability, Π_{ij}, that a random

walker will accidentally traverse from region i to region j following this path. This

probability is computed using the transition matrix, P within a Markov chain process

unfolding on the connection weight matrix. Table 1 summarizes the computation

procedure.

1113

Communicability and Scaled Communicability

1114

The measure of communicability between nodes, i and j, is expressed as the weighted

sum of the overall pathways connecting them, where each walk's contribution is weighted

proportionally to the inverse of its length—signifying the number of connections

traversed. In practice, before computing communicability, nonbinary connection weight

matrices are commonly normalized. This normalization step is employed to diminish the

impact of highly influential nodes with substantial strength. Refer to Table 1 for the

computation procedure and references (Estrada and Hatano, 2008; Zamora-López and

Gilson, 2023) for additional theoretical details. We also reported the scaled

communicability measure, which introduces the modulating parameter, α to control the

decay rate.

1125

Linear Attenuation Model

1126

The Linear attenuation model (LAM) follows the same line of reasoning as

communicability, that information propagation can be represented as a weighted sum of

all walks in the network. The difference lies in how walk-lengths are discounted. In

contrast to communicability, where the sum of walks is estimated through the

exponentiation of the adjacency matrix, Katz introduced an attenuation factor, α, to

reduce the influence over every step monotonically. Katz proposed a closed-form

expression, given by $(\mathbb{I} - \alpha W)^{-1}$ (Katz, 1953). It is important to note that the convergence

condition in this context is $0 < \alpha < 1/\lambda_{max}$, where λ_{max} represents the spectral radius

of the adjacency matrix, W. Prior to computing LAM, the adjacency matrix undergoes a

normalization process, similar to the one applied in the computation of communicability.

1137

Spatial Autoregressive Model

1138

Moreover, we incorporated the spatial autoregressive (SAR) model into our analysis. This

model, characterized as a generic representation of diffuse processes on networks, is

intricately linked to the distribution of paths within the network (Betzel and Bassett, 2018;

Messé et al., 2014; Tononi et al., 1994; Zamora-López et al., 2016). In this model, the

fluctuating signals at each node are interconnected through a system of structural

equations, expressing each signal as a linear function of others. This interconnection is

influenced by a global coupling strength factor denoted as α. Importantly, when the

network experiences input noise, the SAR model predicts that each signal follows a

multivariate normal distribution. This prediction is mathematically represented by the

covariance matrix $\left(\mathbb{I} - \alpha\widehat{W}\right)^{-1}\left(\mathbb{I} - \alpha\widehat{W}\right)^{-T}$ The term $\widehat{W}$ denotes the normalized

adjacency matrix, where each element $\widehat{w_{ij}}$ is obtained by dividing the original connection

strength, w_{ij} by the sum of all connection strengths in the corresponding row of the

matrix W. Here, $\mathbb{I}$ is the identity matrix and $-T$ stands for the transposed inverse matrix.

1152

1153 ### Null and Simulated Network Models

1154 We employed two simulated weighted networks and two null models as described below:

1155

Erdős-Rényi model

An Erdős-Rényi random graph, denoted as $G(N, P)$, was generated with 100 nodes, where

$p = 0.35$ represents the probability that any two distinct nodes are connected by an edge.

The graph was constructed by iterating over all possible pairs of nodes and connecting

them with an edge with the probability p. This resulted in a binary adjacency matrix W

where W_{ij} is 1 if nodes i and j are connected and 0 otherwise. After generating the binary

structure of the graph, weights were assigned to the edges by sampling from a log-

normal distribution. The weight W_{ij} for each edge in the graph was drawn from

$ln\mathcal{N}(\mu, \sigma^2)$ where $\mu = 1$ and $\sigma = 0.5$. The log-normal distribution was chosen for its

property of providing a multiplicative effect, appropriate for modeling local dynamical

systems coupled in a network.

1167

Barabási-Albert model

The Barabási-Albert model was used to generate synthetic scale-free networks through

a preferential attachment mechanism. As with the Erdős-Rényi model, we generated a

network with 100 nodes. Each new node added to the network creates $m = 20$ edges to

existing nodes, with a preference for nodes that already have a higher degree, thus

simulating the "rich get richer" phenomenon and producing hubs in the network. In this

Barabási-Albert model, the probability that a new node will be connected to a node i

depends on the degree k_i, according to the rule:

1176
$$\Pi(k_i) = \frac{k_i}{\Sigma_j k_i}$$

Where $\Sigma_j k_i$ is the sum of degrees of all existing nodes at the time of attachment. Similar

to the Erdős-Rényi model, the edges of the resulting binary network were weighted by

sampling from a log-normal distribution with parameters $\mu = 1$ and $\sigma = 0.5$. Moreover, to

model weakly connected hubs, all hubs in the network were fully connected with weights
assigned from a separate log-normal distribution characterized by both mean and
standard deviation equal to 0.1. This simulates the scenario where hubs have additional
connections among themselves with relatively smaller weights, representing the
observed weaker links of the rich-club in the brain.
1185

Topology-conserving null model
To investigate the impact of connection strength on network dynamics while maintaining
the underlying topology, a weight shuffling procedure was implemented. The adjacency
matrix was kept unaltered to preserve the original connectivity pattern, while the weights
were redistributed to randomize the strength of the connections. This process was
defined as follows:

Given a weighted adjacency matrix, W, with fixed topology, the set of non-zero
weights corresponding to the edges in W was permuted. The permutation was
performed in such a manner that each edge received a new weight from the set,
ensuring that the sum of the weights and the overall weight distribution remained
unchanged. This shuffling procedure was iterated 10 times, yielding 10 distinct
weighted networks with identical topologies but randomized weight
configurations.
1199

Weight-conserving null model
To study the impact of topology, we used a degree-, weight- and strength-preserving
model introduced by (Rubinov and Sporns, 2011) in which the connectivity was shuffled
while the total degree and strength of the nodes were preserved. We chose the default
parameters provided by the BCTpy toolbox, however, the correlation between the
strength sequence of pre- and post-rewired network was r=0.97 that implies a robust
rewiring. As per Rubinov and Sporns (Rubinov and Sporns, 2011), the rewiring algorithm
consists of two steps:

1. The network is randomized while maintaining each node's degree using a
connection-switching algorithm, here Maslov-Sneppen (Maslov and Sneppen,
2002). In this process, connections are adjusted by switching pairs of edges in a
way that preserves the sum of weights for the involved nodes.
2. Original network weights are then reassigned to the randomized network. This
reassignment is done by first ranking all weights by magnitude and then

associating them with the network's connections to approximate the original
distribution of weights. During this process, weights are iteratively matched and
re-ranked until all connections in the new network closely resemble the original
positive and negative strengths.

Multivariate Statistical Model

We conducted two sets of Lasso regularized multivariate regression models (Figure 6. B
and C). In one, we systematically explored the dynamics of feature importance in
predicting the optimal signal propagation and using the other set, we investigated the
number of steps needed to predict the optimal signal propagation.

1223

For the first set, we constructed a feature matrix X encompassing all communication
measures, topological and geodesic distance measures, FC, structural weights, and fiber
length between regions.
A range of 50 α (see Table 1) values from 0 to 1, delineating the degree of spatial
influence, was explored. For each α, the SAR and LAM models were computed and
subsequently integrated into the feature matrix X. A total of 25 repetition runs were
performed for each α, wherein the dataset was randomly partitioned into training and
testing subsets of proportion 0.7-0.3 using a 10-folds cross validation approach. The
training set was subjected to standard scaling before model fitting. The statistical model
was assessed through the coefficient of determination R^2 . The absolute values of the
regression coefficients obtained from the model were normalized to sum to 100,
reflecting the relative contribution of each feature to the model. These contributions were
recorded for each α and averaged over all trials to ascertain the consistent predictors.

1237

For the second set, a range of 15 steps were generated by first raising the structural
connectivity matrix to the power of 0 to 15 and then discounting the longer paths
according to the optimal discount factor of the LAM model α. For each step, 100
repetitions were performed following the same cross-validation, evaluation, and feature
importance ranking introduced above.

Graph-theoretical Measures

Several graph-theoretical measures were employed in this study that are summarized in
Table 2 and briefly explained here.

1246

Table 2: Graph-theoretical Measures

Types	Measures[*]	References
Closeness Centrality	$C_C(i) = \frac{N-1}{\Sigma_{j=1,j\neq i}^N d_{ij}}$	[122]
Eigenvector Centrality	$C_E(i) = \lvert v_i \rvert, \quad Wv = \lambda v$	[122]
Node Betweenness Centrality	$C_B(i) = \Sigma_{s\neq i\neq t}\frac{\sigma_{st}(i)}{\sigma_{st}}$	[122],[123]
Edge Betweenness Centrality	$C_{B_{edge}}(e) = \Sigma_{s\neq t}\frac{\sigma_{st}(e)}{\sigma_{st}}$	[122],[123]
Random Walk Centrality	$T = D - A, \;\; D_{ii} = \Sigma_{j=1}^N W_{ij}$ $V_{st}^i = T_{is} - T_{it}$ $I_{st}^i = \frac{1}{2}\Sigma_j W_{ij}\lvert V_{st}^i - V_{st}^j\rvert$ $C_{RW}(i) = \frac{\Sigma_{s<t}I_{st}^i}{\frac{1}{2}N(N-1)}$	[125]
Average Controllability	$W = U^*TU$ $M = (U \circ U)^T$ $v = diag(T)$ $P = diag(1 - vv^T)$ $P = [P_{\text{diag}}, \ldots, P_{\text{diag}}]$ $C_{avg} = \sum\left(\frac{\mathsf{M}}{P}\right)$	[63]
Modal Controllability	$W = U^*TU$ $v = [v_1, \ldots, v_N] = diag(T)$ $C_M(i) = \Sigma_{j=1}^N U_{ij}^2(1 - v_j^2)$	[63]

[*] Throughout the table, $W \in \mathbb{R}^{N\times N}$ is the adjacency matrix corresponding to a given graph, $G = (V, E)$ with N vertices (nodes). W_{ij} signifies the connection strength from vertex i to vertex j. Anatomical connections are indicated by $W_{ij} > 0$ for connected region pairs and $W_{ij} = 0$ for unconnected pairs. d_{st} denotes the shortest path distance between nodes s and t, and σ_{st} is the total number of shortest paths from node s to node t and $\sigma_{st}(i)$ is the number of those paths that pass through node i. In edge betweenness centrality, $\sigma_{st}(e)$ stands for the number of those paths that pass through a given edge, e. Further, v refers to the left eigenvector associated with the eigenvalue λ of maximum modulus. In computing controllability measures, we used Schur decomposition to find the unitary matrix, U, and the upper triangular matrix, T, to express the adjacency matrix, W. Further, $\circ$ denotes element-wise multiplication, * represents the conjugate transpose, and $diag(.)$ extracts the diagonal elements.

1247

Closeness Centrality

Closeness centrality is a measure reflecting the average shortest path length from a

given node to all other nodes in the network. It quantifies how "close" a node is to all

other nodes, which can indicate the node's efficiency in spreading information through

the network. As with the SPE, the shortest path distance was calculated using the Floyd–

Warshall algorithm.

1254

1255 **Eigenvector Centrality**

1256 Eigenvector centrality extends the concept of centrality by not only considering the

1257 number of connections a node has, but also the centrality of its neighbors (Oldham et al.,

2019; Zuo et al., 2012). It assigns relative scores to all nodes in the network, based on the principle that connections to high-scoring nodes contribute more to the score of the node than equal connections to low-scoring nodes. As detailed in Table 2, this quantity at the site of i-th node is calculated as the i-th component of the eigenvector of the adjacency matrix.

Shortest path Node and Edge Betweenness Centrality

Shortest path betweenness centrality measures the extent to which a node lies on the shortest paths between other nodes in the network. It captures the influence of a node over the flow of information in the network by identifying nodes that frequently act as bridges along the shortest paths between other nodes (Freeman, 1977). Subsequently, the shortest path *edge* betweenness centrality quantifies the number of times an edge acts as a bridge along the shortest path between two nodes. It reflects the importance of an edge in facilitating communication within the network. To elaborate on the computation of these metrics, please refer to Table 2.

Random-walk Node and Edge Betweenness Centrality

Random walk betweenness centrality, also known as current flow betweenness centrality, is also a measure that quantifies the node's role in facilitating information flow in the network (Newman, 2005). However, unlike shortest path betweenness centrality, which only considers the shortest paths, random walk centrality is based on the probability that a random walk starting at a source node will pass through a given node before reaching the destination node. For detailed information on the computation of Random-walk Node and Edge Betweenness Centrality based on the current flow notion, refer to Table 2.

Average and Modal Controllability

Average controllability measures the ability of a node to steer the system into many easy-to-reach states, given a discrete dynamical system. It is particularly useful in understanding the ease with which any state of the system can be reached from a given initial state. Similarly, modal controllability represents the ability of a node to steer the system into farther and hard-to-reach states. In computing the controllability measure, we used Schur decomposition to find the unitary matrix, U, and the upper triangular matrix, T, to express the adjacency matrix, W. the Computation procedure is summarized in Table 2.

Acknowledgments:

The funding is gratefully acknowledged: **K.F:** German Research Foundation (DFG)-SFB 936-178316478-A1; TRR169-A2; SPP 2041/GO 2888/2-2; and the Templeton World Charity Foundation, Inc. (funder DOI 501100011730) under grant TWCF-2022-30510. **F.H:** DFG TRR169-A2. **SD:** SFB 936-178316478-A1. **A.M:** SFB 936-178316478-A1. **B.M:** the Natural Sciences and Engineering Research Council of Canada (NSERC Discovery Grant RGPIN #017-04265). The Brain Canada Future Leaders Fund and the Canadian Institutes of Health Research (CIHR). **C.S:** N/A; **G.Z:** N/A; **C.H:** SFB 936-178316478-A1; TRR169-A2; SFB 1461/A4; SPP 2041/HI 1286/7-1, the Human Brain Project, EU (SGA2, SGA3).

Authors' Contributions:

Conceptualization: K.F., F.H., C.S., B.M., A.M., G.Z., C.H.

Data curation: K.F., C.S.

Formal analysis: K.F., F.H., A.M.

Funding acquisition: C.H.

Investigation: K.F., S.D., F.H., C.S.

Methodology: K.F., F.H., A.M., C.S.

Resources: C.H.

Supervision: A.M., B.M., G.Z., C.H.

Validation: F.H., C.H.

Visualization: K.F.

Writing—original draft: K.F., F.H.

Writing—review and editing: K.F., S.D., F.H., A.M., C.S., G.Z., B.M., C.H.

References:

Abdelnour F, Voss HU, Raj A. 2014. Network diffusion accurately models the relationship between structural and functional brain connectivity networks. *Neuroimage* **90**:335–347.

Adolphs R. 2016. Human lesion studies in the 21st century. *Neuron* **90**:1151–1153.

Algaba E, Fragnelli V, Sánchez-Soriano J. 2019a. Handbook of the Shapley value, Chapman & Hall/CRC Series in Operations Research. Philadelphia, PA: Chapman & Hall/CRC.

Algaba E, Fragnelli V, Sánchez-Soriano J. 2019b. The Shapley value, a paradigm of fairnessHandbook of the Shapley Value. Chapman and Hall/CRC. pp. 17–29.

Avena-Koenigsberger A, Misic B, Sporns O. 2017. Communication dynamics in complex brain networks. *Nat Rev Neurosci* **19**:17–33.

Ay N, Polani D. 2008. Information flows in causal networks. *Adv Complex Syst* **11**:17–41.

Ay N, Polani D, Virgo N. 2019. Information Decomposition based on Cooperative Game Theory. *arXiv [csIT]*.

Bassett DS, Bullmore ET. 2017. Small-world brain networks revisited. *Neuroscientist* **23**:499–516.

Bazinet V, Hansen JY, Misic B. 2023. Towards a biologically annotated brain connectome. *Nat Rev Neurosci* **24**:747–760.

Bettinardi RG, Deco G, Karlaftis VM, Van Hartevelt TJ, Fernandes HM, Kourtzi Z, Kringelbach ML, Zamora-López G. 2017. How structure sculpts function: Unveiling the contribution of anatomical connectivity to the brain's spontaneous correlation structure. *Chaos* **27**:047409.

Betzel RF, Avena-Koenigsberger A, Goñi J, He Y, de Reus MA, Griffa A, Vértes PE, Mišic B, Thiran J-P, Hagmann P, van den Heuvel M, Zuo X-N, Bullmore ET, Sporns O. 2016a. Generative models of the human connectome. *Neuroimage* **124**:1054–1064.

Betzel RF, Bassett DS. 2018. Specificity and robustness of long-distance connections in weighted, interareal connectomes. *Proc Natl Acad Sci U S A* **115**:E4880–E4889.

Betzel RF, Griffa A, Hagmann P, Mišić B. 2019. Distance-dependent consensus thresholds for generating group-representative structural brain networks. *Netw Neurosci* **3**:475–496.

Betzel RF, Gu S, Medaglia JD, Pasqualetti F, Bassett DS. 2016b. Optimally controlling the human connectome: the role of network topology. *Sci Rep* **6**:30770.

Beul SF, Goulas A, Hilgetag CC. 2018. Comprehensive computational modelling of the development of mammalian cortical connectivity underlying an architectonic type principle. *PLoS Comput Biol* **14**:e1006550.

Binmore K. 2007. Game theory: A very short introduction: A very short introduction, Very Short Introductions. London, England: Oxford University Press.

Breakspear M. 2017. Dynamic models of large-scale brain activity. *Nat Neurosci* **20**:340–352.

Buehlmann A, Deco G. 2010. Optimal information transfer in the cortex through synchronization. *PLoS Comput Biol* **6**:e1000934.

Bullmore E, Sporns O. 2012. The economy of brain network organization. *Nat Rev Neurosci* **13**:336–349.

Bullmore E, Sporns O. 2009. Complex brain networks: graph theoretical analysis of structural and functional systems. *Nat Rev Neurosci* **10**:186–198.

Cakan C, Jajcay N, Obermayer K. 2023. Neurolib: A simulation framework for whole-brain neural mass modeling. *Cognit Comput* **15**:1132–1152.

Campbell JM, Davis TS, Anderson DN, Arain A, Inman CS, Smith EH, Rolston JD. 2023. Subsets of cortico-cortical evoked potentials propagate as traveling waves. *bioRxivorg*. doi:10.1101/2023.03.27.534002

Chaudhuri R, Knoblauch K, Gariel M-A, Kennedy H, Wang X-J. 2015. A large-scale circuit mechanism for hierarchical dynamical processing in the primate cortex. *Neuron* **88**:419–431.

Chen H, Covert IC, Lundberg SM, Lee S-I. 2022. Algorithms to estimate Shapley value feature attributions. *arXiv [csLG]*.

Chen Y, Rosen BQ, Sejnowski TJ. 2022. Dynamical differential covariance recovers directional network structure in multiscale neural systems. *Proc Natl Acad Sci U S A* **119**:e2117234119.

Chen Y, Wang S, Hilgetag CC, Zhou C. 2013. Trade-off between multiple constraints enables

simultaneous formation of modules and hubs in neural systems. *PLoS Comput Biol* **9**:e1002937.

Chessa M, Hanaki N, Lardon A, Yamada T. 2022. Cost of complexity in implementing the Shapley value by choosing a proposer through a bidding procedure.

Chklovskii DB, Schikorski T, Stevens CF. 2002. Wiring optimization in cortical circuits. *Neuron* **34**:341–347.

Davies NB, Krebs JR, West SA. 2012. An introduction to behavioural ecology, 4th ed. Chichester, England: Wiley-Blackwell.

Deco G, Kringelbach ML, Arnatkeviciute A, Oldham S, Sabaroedin K, Rogasch NC, Aquino KM, Fornito A. 2021. Dynamical consequences of regional heterogeneity in the brain's transcriptional landscape. *Sci Adv* **7**:eabf4752.

Deco G, Kringelbach ML, Jirsa VK, Ritter P. 2017. The dynamics of resting fluctuations in the brain: metastability and its dynamical cortical core. *Sci Rep* **7**:3095.

Dugatkin LA, Reeve HK. 2000. Game theory and animal behavior. New York, NY: Oxford University Press.

Ehrlich DA, Schneider AC, Priesemann V, Wibral M, Makkeh A. 2022. A measure of the complexity of neural representations based on Partial Information Decomposition. *arXiv [csIT]*.

Ercsey-Ravasz M, Markov NT, Lamy C, Van Essen DC, Knoblauch K, Toroczkai Z, Kennedy H. 2013. A predictive network model of cerebral cortical connectivity based on a distance rule. *Neuron* **80**:184–197.

Estrada E, Hatano N. 2008. Communicability in complex networks. *Phys Rev E Stat Nonlin Soft Matter Phys* **77**:036111.

Fakhar K. 2021. MSA: A compact Python package for Multiperturbation Shapley value Analysis. Zenodo. doi:10.5281/ZENODO.5636435

Fakhar K, Dixit S, Hadaeghi F, Kording KP, Hilgetag CC. 2024. Downstream network transformations dissociate neural activity from causal functional contributions. *Sci Rep* **14**:2103.

Fakhar K, Hadaeghi F, Hilgetag CC. 2022. Causal influences decouple from their underlying network structure in echo State Networks. *arXiv [csLG]*. doi:10.1109/IJCNN55064.2022.9892782

Fakhar K, Hilgetag CC. 2022. Systematic perturbation of an artificial neural network: A step towards quantifying causal contributions in the brain. *PLoS Comput Biol* **18**:e1010250.

Fernández Galán R. 2008. On how network architecture determines the dominant patterns of spontaneous neural activity. *PLoS One* **3**:e2148.

Freeman LC. 1977. A set of measures of centrality based on betweenness. *Sociometry* **40**:35.

Fries P. 2015. Rhythms for cognition: Communication through coherence. *Neuron* **88**:220–235.

Garcia GC, Lesne A, Hütt M-T, Hilgetag CC. 2012. Building blocks of self-sustained activity in a simple deterministic model of excitable neural networks. *Front Comput Neurosci* **6**:50.

Ghosh R, Lerman K, Surachawala T, Voevodski K, Teng S-H. 2011. Non-conservative diffusion and its application to social network analysis. *arXiv [csSI]*.

Goñi J, Avena-Koenigsberger A, Velez de Mendizabal N, van den Heuvel MP, Betzel RF, Sporns O. 2013. Exploring the morphospace of communication efficiency in complex networks. *PLoS One* **8**:e58070.

Goulas A, Schaefer A, Margulies DS. 2015. The strength of weak connections in the macaque cortico-cortical network. *Brain Struct Funct* **220**:2939–2951.

Gould SJ, Lewontin RC. 1979. The spandrels of San Marco and the Panglossian paradigm: a critique of the adaptationist programme. *Proc R Soc Lond B Biol Sci* **205**:581–598.

Grayson DS, Bliss-Moreau E, Machado CJ, Bennett J, Shen K, Grant KA, Fair DA, Amaral DG. 2016. The rhesus monkey connectome predicts disrupted functional networks resulting from pharmacogenetic inactivation of the amygdala. *Neuron* **91**:453–466.

Griffa A, Alemán-Gómez Y, Hagmann P. 2019. Structural and functional connectome from 70 young healthy adults. doi:10.5281/ZENODO.2872624

Griffa A, Mach M, Dedelley J, Gutierrez-Barragan D, Gozzi A, Allali G, Grandjean J, Van De Ville D, Amico E. 2023. Evidence for increased parallel information transmission in human brain networks compared to macaques and male mice. *Nat Commun* **14**:8216.

Gu S, Pasqualetti F, Cieslak M, Telesford QK, Yu AB, Kahn AE, Medaglia JD, Vettel JM, Miller MB, Grafton ST, Bassett DS. 2015. Controllability of structural brain networks. *Nat Commun* **6**:8414.

Gul F. 1989. Bargaining foundations of shapely value. *Econometrica* **57**:81.

Gulyás A, Bíró JJ, Kőrösi A, Rétvári G, Krioukov D. 2015. Navigable networks as Nash equilibria of navigation games. *Nat Commun* **6**:7651.

Gutknecht AJ, Wibral M, Makkeh A. 2021. Bits and pieces: understanding information decomposition from part-whole relationships and formal logic. *Proc Math Phys Eng Sci* **477**:20210110.

Hagberg A, Swart PJ, Schult DA. 2008. Exploring network structure, dynamics, and function using NetworkX (No. LA-UR-08-05495; LA-UR-08-5495). Los Alamos National Laboratory (LANL), Los Alamos, NM (United States).

Harriger L, van den Heuvel MP, Sporns O. 2012. Rich club organization of macaque cerebral cortex and its role in network communication. *PLoS One* **7**:e46497.

Hasson U, Yang E, Vallines I, Heeger DJ, Rubin N. 2008. A hierarchy of temporal receptive windows in human cortex. *J Neurosci* **28**:2539–2550.

Joutsa J, Lipsman N, Horn A, Cosgrove GR, Fox MD. 2023. The return of the lesion for localization and therapy. *Brain* **146**:3146–3155.

Kaiser M, Hilgetag CC. 2006. Nonoptimal component placement, but short processing paths, due to long-distance projections in neural systems. *PLoS Comput Biol* **2**:e95.

Katz L. 1953. A new status index derived from sociometric analysis. *Psychometrika* **18**:39–43.

Keinan A, Hilgetag CC, Meilijson I, Ruppin E. 2004a. Causal localization of neural function: the Shapley value method. *Neurocomputing* **58–60**:215–222.

Keinan A, Sandbank B, Hilgetag CC, Meilijson I, Ruppin E. 2004b. Fair attribution of functional contribution in artificial and biological networks. *Neural Comput* **16**:1887–1915.

Keller CJ, Bickel S, Entz L, Ulbert I, Milham MP, Kelly C, Mehta AD. 2011. Intrinsic functional architecture predicts electrically evoked responses in the human brain. *Proc Natl Acad Sci U S A* **108**:10308–10313.

Kim S, Moon HS, Vo TT, Kim C-H, Im GH, Lee S, Choi M, Kim S-G. 2023. Whole-brain mapping of effective connectivity by fMRI with cortex-wide patterned optogenetics. *Neuron* **111**:1732-1747.e6.

Laasch N, Braun W, Knoff L, Bielecki J, Hilgetag CC. 2024. Estimating effective connectivity in neural networks: comparison of derivative-based and correlation-based methods. *bioRxiv*. doi:10.1101/2024.02.05.578871

Latora V, Marchiori M. 2001. Efficient behavior of small-world networks. *Phys Rev Lett* **87**:198701.

Laughlin SB, Sejnowski TJ. 2003. Communication in neuronal networks. *Science* **301**:1870–1874.

Lennie P. 2003. The cost of cortical computation. *Curr Biol* **13**:493–497.

Lundberg S, Lee S-I. 2017. A unified approach to interpreting model predictions. *arXiv [csAI]*.

Luppi AI, Mediano PAM, Rosas FE, Holland N, Fryer TD, O'Brien JT, Rowe JB, Menon DK, Bor D, Stamatakis EA. 2022. A synergistic core for human brain evolution and cognition. *Nat Neurosci* **25**:771–782.

Luppi AI, Rosas FE, Mediano PAM, Menon DK, Stamatakis EA. 2024. Information decomposition and the informational architecture of the brain. *Trends Cogn Sci* **28**:352–368.

Lynn CW, Holmes CM, Palmer SE. 2024. Heavy-tailed neuronal connectivity arises from Hebbian self-organization. *Nat Phys* **20**:484–491.

Malherbe C, Cheng B, Königsberg A, Cho T-H, Ebinger M, Endres M, Fiebach JB, Fiehler J, Galinovic I, Puig J, Thijs V, Lemmens R, Muir KW, Nighoghossian N, Pedraza S, Simonsen CZ, Wouters A, Gerloff C, Hilgetag CC, Thomalla G. 2021. Game-theoretical mapping of fundamental brain functions based on lesion deficits in acute stroke. *Brain Commun* **3**:fcab204.

Markov NT, Ercsey-Ravasz M, Lamy C, Ribeiro Gomes AR, Magrou L, Misery P, Giroud P, Barone P, Dehay C, Toroczkai Z, Knoblauch K, Van Essen DC, Kennedy H. 2013. The role of long-range connections on the specificity of the macaque interareal cortical network. *Proc Natl Acad Sci U S A* **110**:5187–5192.

Maslov S, Sneppen K. 2002. Specificity and stability in topology of protein networks. *Science*

296:910–913.

Messé A, Hollensteiner KJ, Delettre C, Dell-Brown L-A, Pieper F, Nentwig LJ, Galindo-Leon EE, Larrat B, Mériaux S, Mangin J-F, Reillo I, de Juan Romero C, Borrell V, Engler G, Toro R, Engel AK, Hilgetag CC. 2023. Structural basis of envelope and phase intrinsic coupling modes in the cerebral cortex. *Neuroimage* **276**:120212.

Messé A, Hütt M-T, König P, Hilgetag CC. 2015a. A closer look at the apparent correlation of structural and functional connectivity in excitable neural networks. *Sci Rep* **5**:7870.

Messé A, Rudrauf D, Benali H, Marrelec G. 2014. Relating structure and function in the human brain: relative contributions of anatomy, stationary dynamics, and non-stationarities. *PLoS Comput Biol* **10**:e1003530.

Messé A, Rudrauf D, Giron A, Marrelec G. 2015b. Predicting functional connectivity from structural connectivity via computational models using MRI: an extensive comparison study. *Neuroimage* **111**:65–75.

Muller L, Chavane F, Reynolds J, Sejnowski TJ. 2018. Cortical travelling waves: mechanisms and computational principles. *Nat Rev Neurosci* **19**:255–268.

Newman MEJ. 2005. A measure of betweenness centrality based on random walks. S*oc Networks* **27**:39–54.

Novelli L, Lizier JT. 2020. Inferring network properties from time series using transfer entropy and mutual information: validation of multivariate versus bivariate approaches. *arXiv [q-bioNC]*. doi:10.1162/netn_a_00178

Nozari E, Bertolero MA, Stiso J, Caciagli L, Cornblath EJ, He X, Mahadevan AS, Pappas GJ, Bassett DS. 2024. Macroscopic resting-state brain dynamics are best described by linear models. *Nat Biomed Eng* **8**:68–84.

O'Byrne J, Jerbi K. 2022. How critical is brain criticality? *Trends Neurosci* **45**:820–837.

Oh SW, Harris JA, Ng L, Winslow B, Cain N, Mihalas S, Wang Q, Lau C, Kuan L, Henry AM, Mortrud MT, Ouellette B, Nguyen TN, Sorensen SA, Slaughterbeck CR, Wakeman W, Li Y, Feng D, Ho A, Nicholas E, Hirokawa KE, Bohn P, Joines KM, Peng H, Hawrylycz MJ, Phillips JW, Hohmann JG, Wohnoutka P, Gerfen CR, Koch C, Bernard A, Dang C, Jones AR, Zeng H. 2014. A mesoscale connectome of the mouse brain. *Nature* **508**:207–214.

Oldham S, Fulcher B, Parkes L, Arnatkevic Iūtė A, Suo C, Fornito A. 2019. Consistency and differences between centrality measures across distinct classes of networks. *PLoS One* **14**:e0220061.

Padamsey Z, Rochefort NL. 2023. Paying the brain's energy bill. *Curr Opin Neurobiol* **78**:102668.

Panda R, López-González A, Gilson M, Gosseries O, Thibaut A, Frasso G, Cecconi B, Escrichs A, Coma Science Group Collaborators, Deco G, Laureys S, Zamora-López G, Annen J. 2023. Whole-brain analyses indicate the impairment of posterior integration and thalamo-frontotemporal broadcasting in disorders of consciousness. *Hum Brain Mapp* **44**:4352–4371.

Parkes L, Kim JZ, Stiso J. 2022. nctpy: Network Control Theory for Python. Zenodo. doi:10.5281/ZENODO.7383161

Pérez-Castrillo D, Wettstein D. 2001. Bidding for the surplus : A non-cooperative approach to the Shapley value. *J Econ Theory* **100**:274–294.

Power JD, Barnes KA, Snyder AZ, Schlaggar BL, Petersen SE. 2012. Spurious but systematic correlations in functional connectivity MRI networks arise from subject motion. *Neuroimage* **59**:2142–2154.

Pronold J, van Meegen A, Shimoura RO, Vollenbröker H, Senden M, Hilgetag CC, Bakker R, van Albada SJ. 2024. Multi-scale spiking network model of human cerebral cortex. *Cereb Cortex* **34**. doi:10.1093/cercor/bhae409

Rabuffo G, Lokossou H-A, Li Z, Ziaee-Mehr A, Hashemi M, Quilichini PP, Ghestem A, Arab O, Esclapez M, Verma P, Raj A, Gozzi A, Sorrentino P, Chuang K-H, Perles-Barbacaru T-A, Viola A, Jirsa VK, Bernard C. 2023. On global brain reconfiguration after local manipulations. *bioRxiv*. doi:10.1101/2023.09.08.556815

Ross LN. 2018. Causal selection and the pathway concept. *Philos Sci* **85**:551–572.

Roth AE. 1988. The Shapley value: Essays in honor of Lloyd S. shapley. Cambridge, England: Cambridge University Press.

Rubinov M. 2016. Constraints and spandrels of interareal connectomes. *Nat Commun* **7**:13812.

Rubinov M, Sporns O. 2011. Weight-conserving characterization of complex functional brain
networks. *Neuroimage* **56**:2068–2079.

Rubinov M, Sporns O. 2010. Complex network measures of brain connectivity: uses and
interpretations. *Neuroimage* **52**:1059–1069.

Rubinov M, Ypma RJF, Watson C, Bullmore ET. 2015. Wiring cost and topological participation of
the mouse brain connectome. *Proc Natl Acad Sci U S A* **112**:10032–10037.

Safavi S, Chalk M, Logothetis NK, Levina A. 2024. Signatures of criticality in efficient coding
networks. *Proc Natl Acad Sci U S A* **121**:e2302730121.

Samoylenko I, Aleja D, Primo E, Alfaro-Bittner K, Vasilyeva E, Kovalenko K, Musatov D, Raigorodskii
AM, Criado R, Romance M, Papo D, Perc M, Barzel B, Boccaletti S. 2022. Why are there
six degrees of separation in a social network? *arXiv [physics.soc-ph]*.

Seguin C, Jedynak M, David O, Sina ML, Sporns O, Zalesky A. 2022a. Communication dynamics in
the human connectome shape the cortex-wide propagation of direct electrical
stimulation. *bioRxiv*. doi:10.1101/2022.07.05.498875

Seguin C, Mansour L S, Sporns O, Zalesky A, Calamante F. 2022b. Network communication models
narrow the gap between the modular organization of structural and functional brain
networks. *bioRxiv*. doi:10.1101/2022.02.18.480871

Seguin C, Razi A, Zalesky A. 2019. Inferring neural signalling directionality from undirected
structural connectomes. *Nat Commun* **10**:4289.

Seguin C, Sporns O, Zalesky A. 2023. Brain network communication: concepts, models and
applications. *Nat Rev Neurosci* **24**:557–574.

Seguin C, Tian Y, Zalesky A. 2020. Network communication models improve the behavioral and
functional predictive utility of the human structural connectome. *Netw Neurosci* **4**:980–
1006.

Seguin C, van den Heuvel MP, Zalesky A. 2018. Navigation of brain networks. *Proc Natl Acad Sci
U S A* **115**:6297–6302.

Senn W, Dold D, Kungl AF, Ellenberger B, Jordan J, Bengio Y, Sacramento J, Petrovici MA. 2023.
A neuronal least-action principle for real-time learning in cortical circuits. *bioRxiv*.
doi:10.1101/2023.03.25.534198

Shafiei G, Markello R, Talpalaru T, Makowski C, Kirschner M, Devenyi GA, Hagmann P, Cashman
NR, Lepage M, Chakravarty MM, Dagher A, Mišić B. 2019. Consensus Structural and
functional connectome from 70 young healthy adults. doi:10.5281/ZENODO.3067849

Shafiei G, Markello RD, Makowski C, Talpalaru A, Kirschner M, Devenyi GA, Guma E, Hagmann P,
Cashman NR, Lepage M, Chakravarty MM, Dagher A, Mišić B. 2020. Spatial patterning of
tissue volume loss in schizophrenia reflects brain network architecture. *Biol Psychiatry*
87:727–735.

Shapley L. 1997. 7. A Value for n-Person Games. Contributions to the Theory of Games II (1953)
307-317 In: Kuhn HW, editor. Classics in Game Theory. Princeton University Press. pp.
69–79.

Siddiqi SH, Kording KP, Parvizi J, Fox MD. 2022. Causal mapping of human brain function. *Nat
Rev Neurosci* **23**:361–375.

Sporns O. 2018. Graph theory methods: applications in brain networks. *Dialogues Clin Neurosci*
20:111–121.

Sporns O, Chialvo DR, Kaiser M, Hilgetag CC. 2004. Organization, development and function of
complex brain networks. *Trends Cogn Sci* **8**:418–425.

Suárez LE, Markello RD, Betzel RF, Misic B. 2020. Linking structure and function in macroscale
brain networks. *Trends Cogn Sci* **24**:302–315.

Tononi G, Sporns O, Edelman GM. 1994. A measure for brain complexity: relating functional
segregation and integration in the nervous system. *Proc Natl Acad Sci U S A* **91**:5033–
5037.

Travers J, Milgram S. 1977. An experimental study of the small world problem In: Leinhardt S,
editor. Social Networks. Elsevier. pp. 179–197.

Vaidya AR, Pujara MS, Petrides M, Murray EA, Fellows LK. 2019. Lesion studies in contemporary
neuroscience. *Trends Cogn Sci* **23**:653–671.

van den Heuvel MP, Kahn RS, Goñi J, Sporns O. 2012. High-cost, high-capacity backbone for global
brain communication. *Proc Natl Acad Sci U S A* **109**:11372–11377.
van den Heuvel MP, Mandl RCW, Stam CJ, Kahn RS, Hulshoff Pol HE. 2010. Aberrant frontal and
temporal complex network structure in schizophrenia: a graph theoretical analysis. *J
Neurosci* **30**:15915–15926.
van den Heuvel MP, Sporns O. 2011. Rich-club organization of the human connectome. *J Neurosci*
31:15775–15786.
Vinck M, Uran C, Spyropoulos G, Onorato I, Broggini AC, Schneider M, Canales-Johnson A. 2023.
Principles of large-scale neural interactions. *Neuron* **111**:987–1002.
Wang IE, Clandinin TR. 2016. The influence of wiring economy on nervous system evolution. *Curr
Biol* **26**:R1101–R1108.
Woodward J. 2005. Making things happen: A theory of causal explanation, Oxford Studies in the
Philosophy of Science. New York, NY: Oxford University Press.
Young MP, Hilgetag CC, Scannell JW. 2000. On imputing function to structure from the
behavioural effects of brain lesions. *Philos Trans R Soc Lond B Biol Sci* **355**:147–161.
Zamora-López G, Chen Y, Deco G, Kringelbach ML, Zhou C. 2016. Functional complexity emerging
from anatomical constraints in the brain: the significance of network modularity and rich-
clubs. *Sci Rep* **6**:38424.
Zamora-López G, Gilson M. 2023. An integrative dynamical perspective for graph theory and the
study of complex networks. *arXiv [physics.soc-ph]*.
Zamora-López G, Zhou C, Kurths J. 2011. Exploring brain function from anatomical connectivity.
Front Neurosci **5**:83.
Zamora-López G, Zhou C, Kurths J. 2010. Cortical hubs form a module for multisensory integration
on top of the hierarchy of cortical networks. *Front Neuroinform* **4**:1.
Zavaglia M, Hilgetag CC. 2016. Causal functional contributions and interactions in the attention
network of the brain: an objective multi-perturbation analysis. *Brain Struct Funct*
221:2553–2568.
Zavaglia M, Malherbe C, Schlaadt S, Nachev P, Hilgetag CC. 2023. Ground-truth validation of uni-
and multivariate lesion inference approaches. *bioRxiv*. doi:10.1101/2023.03.28.534534
Zhou H. 2003. Network landscape from a Brownian particle's perspective. *Phys Rev E Stat Nonlin
Soft Matter Phys* **67**:041908.
Zuo X-N, Ehmke R, Mennes M, Imperati D, Castellanos FX, Sporns O, Milham MP. 2012. Network
centrality in the human functional connectome. *Cereb Cortex* **22**:1862–1875.
1622

Supplementary Information:

Supplementary Figure 1. Fitting curve of the scaled communicability (left) and the linear attenuation model (right) to the optimal influence matrix of the human connectome.

Supplementary Figure 2. Fitting curves of the spatial autoregressive model (top), scaled communicability (middle) and the linear attenuation model (bottom) to the optimal influence matrix of macaque (left) and mouse (right) connectomes.

Supplementary Figure 3. Temporal characteristics of optimal influence, given the Hopf model. The part above shows how the amplitude of influence between two regions relates to the structural weight and the topological distance between them. The heatmaps in the middle represent the brain-wide incoming and outgoing influence to and from the posterior cingulate cortex (PCC). Together with the column-averaged time course of these influences, the middle plot suggests that PCC receives a diverse range of incoming influences but broadcasts the same message to the rest of the network. This is also apparent from the zoomed-in view of the heatmap at the bottom.

1626

Supplementary Figure 4. The relationship between the log-normalized structural weights and the fiber length, which had a correlation of -0.6, suggesting that the longer the fiber, the weaker its strength is.

1627

A.

Macaque | Mouse

B.

Communicability | SAR | LAM

Estimated Influences

Structural Weights

C.

Human | Null

D.

Erdos-Renyi | Barabasi

Influence

Structural Weights

Influence

Structural Weights

E.

Influence

Shuffled Structural Weights

Trial 1
Trial 2
Trial 3
Trial 4
Trial 5
Trial 6
Trial 7
Trial 8
Trial 9
Trial 10

Supplementary Figure 5. Further analysis of the influence of weak connections in null, synthetic, and supplementary networks. **A.** The relationship between structural weights and the influence of two connected regions in the mouse and macaque connectome supports the results from the human connectome. There exists many weak connections that exert more influence than expected from their connection weights (the 'bump') **B.** Communication models capture the bump to different extent. **C.** The bump is also apparent in the strength-preserved null model, although localized in weaker connections. **D.** Two synthetic networks in which both the weights and the topology is randomized did not replicate the bump. **E.** Topology-preserved weight-shuffled networks replicated the bump, however, as with C. they are localized to weak connections, suggesting a complementary role for both weight distribution and topological features.

1628

Supplementary Figure 6. The relationship between influential nodes (in red) and their controllability measures.

1629

Supplementary Figure 7. Comparing the optimal influence matrices from 1,000 and 10,000 lesion samples per source node.

1630

Supplementary Figure 8. The amount of which univariate and multivariate models can predict optimal influence from summing individual walks, discounted exponentially (as with communicability).

1631

Supplementary Figure 9. Comparing optimal influence with functional connectivity.

1632