1
2   `
3   **TITLE:**
4   Miniscope Recording Calcium Signals at Hippocampus of Mice Navigating an Odor Plume.
5

6   **AUTHORS AND AFFILIATIONS:**
7   Simoes de Souza Fabio M.[1], Williamson Ryan[5], McCullough Connor[2], Teel Alec[1], Futia Gregory[2],
8   Ma Ming[1], True Aaron[4], Crimaldi John. P.[4], Gibson Emily[2,3], Restrepo Diego[1,3]
9

1 Department of Cell and Developmental Biology, University of Colorado Anschutz Medical
Campus, Aurora, CO 80045, USA
2 Department of Bioengineering, University of Colorado Anschutz Medical Campus, Aurora, CO
80045, USA,
3 Neuroscience Graduate Program, University of Colorado Anschutz Medical Campus, Aurora,
CO 80045, USA
4 Civil, Environmental & Architectural Engineering, University of Colorado, Boulder, CO 80309,
USA
5 Neurotechnology Center, University of Colorado Anschutz Medical Campus, Aurora, CO
80045, USA
20
21   fabio.simoesdesouza@cuanschutz.edu
22   diego.restrepo@cuanschutz.edu
23
24

SUMMARY:
This protocol describes how to investigate the brain-behavior relationship in hippocampal CA1
in mice navigating an odor plume. This article provides a step-by-step protocol, including the
surgery to access imaging of the hippocampus, behavioral training, miniscope GCaMP6f
recording and processing of the brain and behavioral data to decode the mouse position from
ROI neural activity.
31

ABSTRACT:
Mice navigate an odor plume with a complex spatiotemporal structure in the dark to find the
source of odorants. This article describes a protocol to monitor behavior and record Ca^{2+}
transients in dorsal CA1 stratum pyramidale neurons in hippocampus (dCA1) in mice navigating
an odor plume in a 50 cm x 50 cm x 25 cm odor arena. An epifluorescence miniscope focused
through a GRIN lens imaged Ca^{2+} transients in dCA1 neurons expressing the calcium sensor
GCaMP6f in Thy1-GCaMP6f mice. The paper describes the behavioral protocol to train the mice
to perform this odor plume navigation task in an automated odor arena. The methods include a
step-by-step procedure for the surgery for GRIN lens implantation and baseplate placement for
imaging GCaMP6f in CA1. The article provides information on real-time tracking of the mouse
position to automate the start of the trials and delivery of a sugar water reward. In addition, the
protocol includes information on using of an interface board to synchronize metadata
describing the automation of the odor navigation task and frame times for the miniscope and a

digital camera tracking mouse position. Moreover, the methods delineate the pipeline used to
process GCaMP6f fluorescence movies by motion correction using NorMCorre followed by
identification of regions of interest with EXTRACT. Finally, the paper describes an artificial
neural network approach to decode spatial paths from CA1 neural ensemble activity to predict
mouse navigation of the odor plume.
50
51
INTRODUCTION:
Although significant progress has been made understanding neural circuits involved in olfactory
navigation in head-fixed mice[1-3], and navigation strategies in freely moving mice[4-8] the role of
neural circuits in ethologically relevant freely moving navigation of turbulent odor plumes is still
unknown. This article describes how to monitor neural activity by imaging Ca^{2+} transients in
cells expressing the genetically encoded calcium sensor GCaMP6f in Thy1-GCaMP6f mice[9.] to
study whether sequential neural dynamics of dorsal CA1 stratum pyramidale neurons in the
hippocampus (dCA1) plays a role in odorant plume navigation. The methods provide
information on imaged GCaMP6f fluorescence through a miniature epifluorescence microscope
focused through a GRIN lens on dCA1[10-12]. The methods explain how to monitor simultaneously
spatial navigation and dCA1 neuron GCaMP6f calcium transients in mice performing an odor-
plume navigation task where they received a water reward when they reached the spout
delivering an odorant into an odor arena with a background laminar air flow[13, 14]. This article
describes the methods required to achieve this task (Figure 1), including the stereotaxic surgery
for the implantation of GRIN lenses, the placement of a baseplate to secure the miniscope to
the skull in a freely moving mouse, imaging with the miniature microscope and monitoring
mouse movement with a high-speed digital camera, data pre-processing for removing motion
artifacts and finding the regions of interest (ROIs), and preparation of datasets and artificial
neural network training and prediction for decoding the X and Y positions of the mouse in the
odor arena from changes in fluorescence in dCA1 ROIs[7].
Miniscope recording of calcium signals in the CA1 region of the hippocampus of mice navigating
an odor plume is relevant for understanding the computation of neural circuits involved with
olfaction and spatial information in the complex behavior task of odor-plume navigation [2, 14-16].
The CA1 region of the hippocampus plays a role in spatial navigation and is crucial for creating a
cognitive map of the environment for efficient navigation [17, 18]. Recording calcium signals with a
miniscope is a valuable way to investigate the CA1 neurons that encode spatial information
during odor plume navigation.
This technique combines the advantages of miniscope technology for recording GCaMP calcium
signals with the well-established role of the CA1 hippocampus in spatial navigation to
understand better how neural circuits drive complex behaviors [19]. Alternatively, approaches
using 2-photon microscopy can record CA1 neurons [9, 20], which requires a head-fixed mouse and
restrains the possibility of freely moving to navigate an odor plume[21]. Local-field
electrophysiological recordings of CA1 neurons allow the investigation of freely-moving mice
navigating odor plumes[22]. Still, local field electrical signals impose limitations to estimating
intracellular firing by isolating single-unit signals through spike sorting techniques. Miniscope
signals allow the identification of ROIs associated directly with intracellular calcium signals in a
reliable way [10, 11] to investigate neural computations at single-cell resolution precisely.

Miniscope technology provides a unique opportunity to better understand how the CA1 region
encodes spatial information based on odor cues.
Furthermore, this technique investigates how specific neuronal populations process odor
information for navigation and the relationship between neuronal activity patterns and
decision-making during odor plume tracking. This method can contribute to a better
understanding of how the brain processes odor and spatial information. While miniscopes offer
a single-cell resolution for recording a freely moving mouse's brain, they require specialized
surgery and data analysis expertise. In this paper, we provide a comprehensive protocol for
helping researchers go through each step to investigate the neural mechanisms of odor-plume
navigation.
99
100 The odor navigating task is a promising framework for studying neural coding and spatial odor
101 cue memory in mice. The article's findings indicate that it is possible to decode the trajectory of
102 the mouse navigating an odor plume based on neuronal ensemble calcium signals in dCA1.
103 Understanding the role of dCA1 calcium signals in odor plume navigation is a crucial step to
104 crack the neural circuit basis for odor-guided navigation in realistic environments[13, 14].
105
106
PROTOCOL:
Studies were carried in 3-to-6-month-old male and female Thy1-GCaMP6f transgenic mice[23]. All
experimental protocols were approved by the Institutional Animal Care and Use Committee of
the University of Colorado Anschutz Medical Campus, in accordance with National Institutes of
Health guidelines. The surgical procedures for GRIN lens implantation (Protocol 1) and the
baseplate placement (Protocol 2) were adapted from previous works[9, 24–29].
113
114 1. Stereotaxic surgery for implanting a GRIN lens implantation in the hippocampus.
115
116 1.1 The surgeon wears sterile gloves, a headcover, surgical mask and a lab coat.
117
118 1.2 Sterile conditions are used during all survival surgeries. Sterilize all surgical equipment by
119 autoclaving.
120
121 1.3 Place sterile drapes around the surgical area
122
123 1.4 Anesthetize the mouse by placing it in the induction chamber with 3% isoflurane for 10 min.
124
125 1.5 Check whether the mouse stops moving and is under deep anesthesia confirmed by
126 pinching the hind paw to test the hind paw reflex.
127
128 1.6 Switch the isoflurane flow to the nose cone (Supplementary File 1).
129
1.7 Make sure the low-flow isoflurane anesthesia system for mice (Jove Materials Spreadsheet)
has the temperature pad set to homeothermic settings and make sure the vapor source is set to
external compressed.

1.8 Place the anesthetized mouse in the digital stereotaxic instrument (Jove Materials
Spreadsheet). Place the front teeth of the mouse into the bite bar and place the nose cone in
front of the nose to ensure the isoflurane flow and to lock the head into place. Adjust the level
of anesthesia to between 2 to 3% according to the paw reflex after pinching (Figure 2 A).

1.9 Place the mouse ear bars into the ears and tighten. Ensure the mouse's head is horizontal
and does not move side-to-side or up and down. When the head is secure, lightly pressing
downward on the skull shouldn't cause the skull to slip out underneath the headbars.

1.10 Place the temperature probe in the rectum and tape the wire on the mouse's tail to avoid
movement. Set the temperature of the pad to maintain the rectal temperature at 37 degrees
Celsius.

1.11 Add ophthalmic ointment to the eyes to prevent harmful air drying.

1.12 The hair is shaved when head is fixed and under the isoflurane flow provided by the nose
cone to prevent movement. Shave the hair above the head with an electric shaver, then clear
any remaining hairs off with hair remover and sterile q tip (Figure 2 B).

1.13 Make the operating field sterile by swabbing the scalp with a sterile Q tip with ethanol and
betadine three times each.

1.14 Inject 0.1 mL of the local anesthetic lidocaine subcutaneously (S.Q.) under the skin
between the eyes and ears with a 29 Gauge needle. This will make a bubble. Wait for a few
minutes before cutting the skin with a scissors.

1.15 Using a tips only technique, pull the skin up carefully using forceps and use a pair of small
scissors to remove a circular portion of the skin. Absorb any blood with a sterile cotton swab.

1.16 Once the bleeding stops, clean the skull with hydrogen peroxide (5%) using a sterile cotton
swab. Bone landmarks, including where the sagittal suture and the bregmatic suture intersect
to mark bregma should be easy to identify after this procedure.

1.17 Confirm that the skull is flat relative to the stereotaxic apparatus by making sure that
bregma and lambda sutures are exactly at the same Z coordinate. This procedure is performed
by placing a needle in the manipulator arm and verifying if the tip of a needle is at the same Z
coordinate when touching both sutures. Otherwise, adjust the angle of the head by moving the
bite bar in the Z plate and repeating the procedure until the skill is in a flat position.

1.18 Attach a pipette to the micromanipulator holding a needle to apply tattoo ink. Make a
mark on the top of Bregma.

1.19 Zero the micromanipulator coordinates on Bregma and move to the coordinate above CA1

in the right hippocampus (medium-lateral +1.8 mm from Bregma, anterior-posterior -2.4 mm
from Bregma)[2]. This is the location chosen by Radvansky and Dombeck to study vitural odor
gradient navigation in mice[18, 30]. Carefully drill a small permanent dent of 1 mm diameter with a
drill at speed of 10K min[-1]-(Osada, Jove Materials Spreadsheet) to make a permanent dent on
the top of the target location (Figure 2 C).

1.20 Use the dental drill to open a circular perforation of 1.5 mm diameter to allow the
implantation of a 1 mm diameter and 4 mm length GRIN lens into the Brain (Jove Materials
Spreadsheet) (Figure 2 D).

1.21 Puncture the dura and cortex by inserting a 23 gauge needle in the middle of the hole and
move the needle into the brain slowly (~0.1 mm/min) until it reaches the depth of 1.25 mm
below dura. Remove the needle slowly from the brain (~0.1 mm/min). Use sterile cotton swabs
and saline to clean the blood.

1.22 This protocol uses a custom made UCLA's GRIN lens holder constructed with two 1ml
micropipette tips cut to fit inside each other (GRIN lens holder, Jove Materials Spreadsheet)
(Figure 2 E, F). Connect the GRIN lens holder on the micromanipulator and turn on the aspirator
connected to the pipette to hold the GRIN lens. The air pressure produced by air suction holds
the GRIN lens in place. This protocols uses a 4 mm length, 1 mm diameter GRIN lens. Implant
the GRIN lens slowly into the cortex until reaches the depth of -1.25 mm below dura.

1.23 Place a drop of liquid tissue adhesive (Jove Materials Spreadsheet) into the circular
cranium perforation to seal the hole. Wait a few minutes to dry.

1.24 Prepare quick adhesive cement -biocompatible methacrylate resin-   (Jove Materials
Spreadsheet) on the base of the GRIN lens to permanently seal it on the skull. Wait a few
minutes and let it dry.

1.25 Turn off the aspirator to release and slowly remove the GRIN lens holder from the top of
the GRIN lens that at this point is permanently attached to the skull.

1.26 Place the head bar on the top of the skull centering the hole on the GRIN lens (Figure 2 G,
H, I) (Supplementary File 2).

1.27 Carefully place quick drying adhesive cement (Jove Materials Spreadsheet) around the
base of the GRIN lens to seal the cranial window and attach the head bar to the skull. Place
drying adhesive cement (Jove Materials Spreadsheet) in the middle of the head bar and on the
sides, to keep it tightly fixed on the skull. Make sure it is completely dry. Ensure that no
adhesive cement is placed on top of the GRIN lens otherwise it will permanently degrade the
optical path and block the image.

1.28 Place a drop of low toxicity silicone adhesive (Jove Materials Spreadsheet) on top of the
GRIN lens for protection from physical damage.

1.29 Turn off the Isoflurane

1.30 Inject buprenorphine SR subcutaneously 0.001 mg/g immediately after surgery for
analgesia.

1.31 Take immediate post-operative care monitoring until the animal wakes from anesthesia.
Post-operative care is taken until the fully recovery from the surgery by monitoring the mice for
signs of pain. The animal that undergone surgery is not returned to the company of other
animals. Briefly, movement around the cage, eating and drinking and normal reaction to
handling is used to ensure that they are not under pain or stress. If the animals show signs of
severe neurological or tissue damage, which was out of the ordinary for the procedure, they
will be humanely euthanized immediately.

2. Baseplate placement for the miniscope
The procedures for head-fixing the mouse start two weeks after the animal fully recovers from
the surgery. The procedure for imaging dCA1 start three weeks after the surgery after the
animal full recovers and the GCaMP6f signal becomes strongly visible.
A baseplate is fixed on top of the GRIN lens for optical access of dCA1 GCaMP6f fluorescence
through the GRIN lens using a miniscope. This protocol utilized the miniscope version 4 -V4
(Miniscope V4, Jove Materials Spreadsheet).

2.1 Two weeks after surgery start head-fixing the mouse for 10 min by securing the head bar
with pinch clamps for acclimating the mouse to being head fixed.

2.2 Head-fix the mouse three weeks after the surgery for placement of the baseplate.

2.3 Attach a miniscope to a 3D printed holder attached in a micromanipulator (Miniscope
Holder, Jove Materials Spreadsheet) attached in a micromanipulator (Figure 3A, B).

2.4 Carefully remove the silicone adhesive (Jove Materials Spreadsheet) from the top of the
lens using fine tweezers and clean the surface of the GRIN lens using a lens wipe.

2.5 Secure the baseplate attached to the miniscope tightening the set screw on the side of the
baseplate (Miniscope baseplate V2, Jove Materials Spreadsheet) (Figure 3 C, D).

2.6 Move end of the miniscope until reaching 100 μm above the GRIN lens.

2.7 Use the sliders to configure the Miniscope settings in the Miniscope software (Miniscope
DAQ-QT Software, Jove Materials Spreadsheet) following the steps 2.8 to 2.10.

2.8 Click in the power slider in the software to control the power and keep it around 10%.

2.9 Click in the acquisition rate slider and keep it around 10 Hz.

2.10 The v4 miniscope has an electrowetting lens that can be used for fine focusing. Click in the
focus slider to set it at 50% to keep the electro-wetting-lens in the middle of the focal range.

2.11 Use the Miniscope software to view the top of the GRIN lens. It is possible to see the
circular shape of the GRIN lens on the screen.

2.12 Bring the miniscope closer to the GRIN lens by adjusting the axial position with the
micromanipulator and monitor the image with the computer. Once the top of the GRIN lens is
visible, use fine focus up and down on the micromanipulator to reach the best focal plane to
visualize cell flashes. Use the pseudo δF/F0 setting in the miniscope software to double check
the quality of the cell flashes. The focus is set to allow the maximum number of cells in the field
of view with highest attainable fluorescence intensity. At this point blood vessels should be in
focus.

2.13 It may happen that a mouse has no transient calcium signals -flashes-. In this case, it is
recommended to avoid the next steps (2.15 to 2.17) and verifying the mouse again in the next
weeks to double check whether the transient calcium signals occur. A decision can be made to
euthanize the mouse if the transient calcium signals never occur two months after the surgery.

2.14 Once the focus is optimized, carefully build a wall of quick adhesive cement between the
skull and the bottom of the baseplate. Take care not to cement the miniscope on the baseplate
and be very careful not to get any cement on the top of the GRIN lens.

2.15 Once the cement is dry, remove the set screw and carefully remove the miniscope from
the baseplate with the micromanipulator.

2.16 Use the base plate cover to protect the GRIN lens.

3. Construction of the Odor Arena
This method delineates an automated odor arena based on the design of Connor et al.[13] and
Gumaste et al.[14]. The complete assembly can be found here (Odor Arena Hardware, Jove
Materials Spreadsheet) (Supplementary File 3).

3.1 The chamber dimensions are 50 cm (L) x 50 cm (W) x 25 cm (H) with 2 acrylic walls, an
acrylic ceiling, a white expanded PVC floor, and 2 unique walls at the front and rear which
facilitate air flow (Figure 4A).

3.2 The air suction end at the rear of the arena has a tapered design with a computer fan
attached to draw air out of the chamber. A physical knob sets the fan PWM to regulate the rate
of air flow. A 3D printed honeycomb structure comprises walls for the front and rear of the
odor arena to facilitate laminar flow of air while retaining a mouse inside [10]. The honeycomb
wall at the front of the arena has an external flare for receiving large volumes of air in a non-
disruptive manner.

309
310 3.3 The water reward is delivered via simple contraptions having a Nema 17 stepper motor
311 coupled to a syringe. An A4988 microstepping driver allows precise control of the dispensed
312 volume (https://github.com/dougollerenshaw/syringe_pump, Figure 4B).
313
314 3.4 The air intake end has 4 sets of odor sources paired with water-delivery spouts, with each
315 set positioned 10 cm apart along the x axis to define the 'lanes' along which an animal will
316 navigate for a water reward (Figure 4C, D).
317
3.5 Odor delivery is managed by a system of solenoid valves connected to tubes and odorant
bottles (Figure 4D). The valves are powered using a relay board in an arrangement which
guarantees that either clean air or odorized air is flowing at all times, and that either one single
lane or zero lanes can receive odorized air at any given time. A set of five 12-volt solenoid
valves are managed using a relay board containing 4 relays. When all 4 relays are set to 'off', the
clean-air valve is open by default. When any single odor valve is opened, the clean-air valve is
automatically closed. The relay board state is managed using digital outputs from the primary
arduino controller. A consumer-grade aquarium air pump supplies air which is restricted to 20
mL/min using a manual air-flow regulator. Using a series of $1/16^{th}$ inch inner-diameter tubes
and splitters, the supply line delivers clean air each of the solenoid valves. Check-valves before
and after the odorant guarantee the direction of air flow. The clean air line merges with the
odorant lines prior to entering the arena to guarantee that odorized air is purged when the
odor lines are closed.
331
332 3.6 Animal behavior is monitored at 60 Hz using a single fast digital camera mounted above the
333 arena (Jove Materials Spreadsheet). A 3.5mm fixed focal length C-Series lens was mounted via a
334 C/CS mount adapter, capable of capturing the entire arena (Focal Lens, Jove Materials
335 Spreadsheet).
336
337 3.7 The odor arena hardware is managed using custom software developed in Python. A PC
338 connected to a Teensy 4.0 development board provides the means for computer-mediated
339 odor and water delivery. The software integrates the camera and all hardware necessary for
340 setting up experimental parameters and acquiring experimental data (Odor Arena Software,
341 Jove Materials Spreadsheet).
342
3.8 The digital camera exports a clock signal when recording video frames. The signal is used for
post-hoc synchronization with the Miniscope using an USB interface board (Jove Materials
Spreadsheet) which records the sync out signals from both systems. During an experiment, the
custom acquisition software also creates an events file which contains the important
experimental events and the camera frame on which the event occurred. A timestamps file is
also created to identify any dropped frames, a rare event.
349
4. Air speed of the plume measured with a photo-ionization detector
This method detects the time course of the odor plume through a photo-ionization detector

(PID) that exposes the gaseous odorant to a high-intensity ultraviolet light that ionizes the
odorant molecules. The device's output detects odorant molecules in the odor plume. This
technique allows the estimation of the air speed in the odor arena by comparing the delay to
detect the presence of odorants traveling through two locations using the PID.
356
357 4.1 Place a fast response miniature PID at two different distances. One location is close and
358 another location far -10 cm apart- from the odor source
359
360 4.2 Change the switch of GAIN in the front panel of the PID controller to the position x5.
361
362 4.3 Change the switch of PUMP in the front panel of the PID controller to position high.
363
364 4.4 Check the LED status light showing the sensor (voltage) output in the front panel of the
365 controller in the absence of odorants.
366
367 4.5 Switch the potentiometer OFFSET for zeroing the voltage output in the absence of odorants.
368
369 4.6 Turn on the odor valve in the odor arena.
370
371 4.7 Measure the delay to detect the odor plume with the PID at each location after opening the
372 valve. This procedure can be performed offline by recording simultaneously the output of the
373 PID and the output of the valve recorded by the odor arena (odor on) with an interface board
374 (Jove Materials Spreadsheet).
375
376 4.8 Divide the difference of the delays in each location by the difference of the distance
377 between the two PIDs to calculate the air speed of the plume.
378
5. Behavioral training mouse in the Odor Arena
This section describes a behavioral task adapted from Findley et al.[4]. The mouse is water
restricted the day before to motivate seeking a water reward. The mouse navigates the odor
plume (Figure 6B) towards a water spout located at the source of odor release to obtain water
reinforcement (3 drops of 10 μL delivered at 1Hz). During the training period the mouse is
maintained under the water restriction by having access to up to 2 mL a day. The body weight
of the mouse is monitored during the water restriction period and should not be bellow 85% of
the original body weight. The mouse receives approximately 1 mL of water per day during the
training in the odor arena and is supplemented with an additional 1 mL of water per day in the
cage after training. The mouse stays under water restriction for a maximum period of 72 hours.
Custom software (Jove Materials Spreadsheet) detects the mouse's location in real-time (60 Hz)
using a simple background-subtraction and blob-localization technique. The user manually sets
lane boundaries, the home boundary (the starting location for the mouse at the back of the
arena), and the target boundary (near the odor source at the front). Additionally, the user is can
decide how the software utilizes these boundaries. For example, the user may deliver odors
only when the mouse is behind the home boundary. For the mouse to receive a reward, the
user may require it remain within the odorized lane as it navigates to the target (the odor

source). Once the mouse crosses the target boundary, it may receive a reward. During training,
however, any of these requirements are adjusted by simply editing a 'yaml' file designed to be
self-explanatory and user-friendly.

5.1 First, train the mouse to start trials by moving to the back of the arena (defined as the
portion of the arena that is 40 cm away from the side where the air flows into the chamber).
Wait until the mouse goes to the back of the arena and then manually deliver odor and water in
one random lane and let the mouse find the source and drink the water. Repeat the procedure
many times to create the association between odor and water (Figure 6A, B). Once the mouse
learns to start trials, then use the automated software to deliver odors.

5.2 Train the mouse to do the two-lane odor navigation task using the automated custom
software. In this task one of two odor ports is randomly chosen to deliver odor and the mouse
is reinforced with water when it arrives to the water spout where odorant is delivered. This
protocol used the odorant Isoamyl Acetate diluted at 1% in mineral oil.

5.3 The mouse completes a session of about 20 trials of odor plume navigation in about 40 min.
The mouse performs one session per day.

5.4 The trained mouse achieves a percent of correct navigation above random choice in the end
of the session (> 65% correct choices). The mouse should achieve the criterion of > 65% correct
choices on the two-lane odor navigation task after 3 to 5 sessions of training.

6. Epifluorescence recording of a freely moving mouse in the odor arena
The method describes how to record the neuronal activity of stratum pyramidale (SP) cells in
dorsal CA1 by imaging the genetically encoded calcium sensor GCaMP6f expressed in Thy1
mice[9] by wide-field miniscope imaging during the two-spout odor plume navigation task
(Supplementary Movie 1, 2). A typical imaging session takes 40 min allowing the mouse to
complete approximately 20 trials of odor navigation. This technique records a mouse for several
months.

6.1 Head fix the mouse, place the miniscope on the top of the baseplate using the
micromanipulator and tighten the set screw.

6.2 Adjust the electrowetting lens to find the optimal focal plane with the largest number of
cells with highest fluorescence intensity.

6.3 Adjust the miniscope power to obtain the optimal dynamic range with a high signal to noise
ratio without saturation. This is usually attained imaging dorsal CA1 in Thy1-GCaMP6f mice with
miniscope power set around 30% at an acquisition rate of 30Hz.

6.4 Release the mouse inside of the odor arena with the miniscope attached to the baseplate.

6.5 Start acquisition with the interface board to record the TTL output of the digital camera

located at the top of the arena and the TTL signal from the miniscope for latter synchronization between behavioral and GCaMP6f video frames. The digital camera records at 60 Hz and the miniscope records at 30 Hz.

6.6 Start recording the miniscope and behavioral movies and turn on the automated software for two spout odor navigation task.

7. Data Preprocessing

This method uses a MATLAB pipeline to process the data. The code is available on GitHub (Synchronization Software, Jove Materials Spreadsheet). NoRMCorre[31] was used for motion correction, and EXTRACT[32] to find the ROIs with time-varying fluorescence signals reported as changes in fluorescence normalized by fluorescence between calcium transients (δF/F0).

7.1 Synchronize the odor arena metadata, the digital camera frames and the miniscope frames using the sync signals recorded by the interface board by running the MATLAB code Synchronize_Files_JOVE.m available on GitHub (Synchronization Software, Jove Materials Spreadsheet).

7.2 Perform motion correction of the synchronized miniscope frames using NoRMCorre (Motion Correction Software, Jove Materials Spreadsheet).

7.3 Find the ROIs with time-varying δF/F0 signals using EXTRACT (ROI Extraction Software, Jove Materials Spreadsheet).

7.4 Separate the data into trials (Synchronization Software, Jove Materials Spreadsheet).

7.5 Label each trial either as a hit or a miss based respectively on the mouse's correct or wrong navigation behavior.

7.6 Use Behavior Ensemble and Neural Trajectory Observatory (BENTO)[33] to visualize the behavior and ROIs of each separate trial (Figure 7 A, B, Supplementary Movie 3).

8. Data Analysis – Decoding Spatial Position from Brain Signals

This method uses machine learning to decode the mouse's X and Y positions in the arena from the dCA1 ROIs[7]. The MATLAB code is available (Decoding Brain Signals Software, Jove Materials Spreadsheet) in https://github.com/restrepd/drgMiniscope.

8.1 The software drgDecodeOdorArenav2.m takes as input the EXTRACT.mat output file and the odor arena metadata file. The GitHub repository provides these two files for an example (Synchronization Software, Jove Materials Spreadsheet):

  dFF_file='20220804_FCM22_withodor_miniscope_sync_L1andL4_ncorre_ext.mat';
  arena_file='20220804_FCM22withodor_odorarena_L1andL4_sync.mat';

484 8.2 drgDecodeOdorArenav2.m creates a dataset divided by within trial data containing the ROI
485 signals and metadata (X and Y positions of the mouse, odor spout location, water delivery, etc)
486 for each trial. The code also analyzes decoding for data between trials.
487
488 8.3 The code uses fitrnet to train an artificial neural network with the δF/F0 data for all ROIs for
489 all trials but one to predict x and y positions and predict the position of the trial left out using a
490 leave one out procedure.
491
492 8.4 The neural network returns the X and Y positions as output. Use the trained neural network
493 to make predictions. Input left out trials not used to train the network to make predictions of
494 the X and Y positions of the mouse in the arena from the ROIs (Figure 8A, B).
495
496
REPRESENTATIVE RESULTS:
Using this procedure, allows visualizing and recording dCA1 GCaMP6f fluorescence transients in
mice navigating the odor arena to find the source of odorants (Figure 6 A,B, Supplementary
Movie 1, 2). The fluorescence images are motion-corrected with NoRMCorre, and EXTRACT is
used to extract the ROIs. In addition, recording with an interface board allows to synchronize
the δF/F0 signals from the ROIs with odor and water delivery events in the odor arena (Figure
7A), as well as with movement of the mouse in the odor arena (Figure 7B, Supplementary
Movie 3). The representative result of the mouse navigating the odor plume includes a large
number of calcium transients during the task (Figure 7 A, B). In addition, it is possible to inspect
how the calcium responses are aligned with the presence of odor and water reward (Figure 7A).
The visualization of single trials with BENTO provides information about the calcium responses
at different stages of the trial, including trial start, deciding, navigating, drinking, and returning
to the back of the arena (Figure 7B). The method communicated valuable insights regarding the
link between CA1 calcium responses and mice behavior during an odor-oriented navigation
task.
The PID recordings can provide crucial information about the odor plume and the air speed of
the plume. The representative result shows an increase in the PID response after opening the
valve to release the odor plume inside of the odor arena (Figure 5A). Furthermore, the protocol
yields decoding of the X and Y positions of the mouse from the δF/F0 signals of the dCA1 ROIs
(Figure 8). This technique predicts the spatial location of the mouse during the odor-plume
navigation task based on the CA1 responses, which is relevant to better understanding how the
CA1 neurons process odor and spatial information. Decoding the trajectory of the mouse from
neuronal ensemble calcium signals in dCA1 is significant because it reveals how neurons in
dorsal CA1 represent a cognitive map of odorant and spatial information to perform the
complex task of odor plume navigation. The method has been expanded to   different ROIs that
behave exclusively as place cells and other cells that respond to the odor stimulus. Successful
decoding of the trajectory of the mouse from neuronal ensemble signals can be confirmed by
the strong correlation between the decoding prediction and the ground true X and Y positions
of the mouse.
526
527

FIGURE AND TABLE LEGENDS:

Figure 1. Study Pipeline.
A: The stereotaxic surgery consists of implanting a GRIN lens in the CA1 layer of hippocampus and a headplate on the skull for head fixing the mouse. B: A baseplate is placed on the top of the GRIN lens to allow accessing optically the fluorescence of the CA1 neurons with a miniscope. C: The mouse is trained on the odor plume navigation task. D: Freely moving recording of the mouse behavior and CA1 neurons navigating the odor plume.

Figure 2: Stereotaxic Surgery.
A: Place the anesthetized mouse in the stereotaxic apparatus. Adjust the level of anesthesia between 2 to 3% accordingly with the pinching paw reflex response
B: Shave the hair above the head.
C: Carefully drill a small permanent dent with drill to make a permanent dent on the top of the target location.
D: Use the dental drill to open a circular perforation of 1.5 mm diameter to allow the implantation of a 1 mm diameter and 4 mm length GRIN lens into the Brain.
E: Connect the GRIN lens holder on the micromanipulator and turn on the aspirator connected to the pipette to hold the GRIN lens.
F: Implant the GRIN lens slowly into the cortex until reaches the depth of -1.25 mm below dura matter.
G: Illustrative post-mortem fixed head showing the head-plate and base-plate cemented on the skull with the implanted GRIN lens.
H: Post-mortem CT-scan of the head illustrating the Head Bar on the top of the cranium and the GRIN lens implanted inside of the cranium.
I: Design of the head-plate to yield head-fixing the mouse.

Figure 3: Miniscope base plate placement.
A: 3D printed miniscope holder coupled to a micromanipulator.
B: Miniscope attached to the holder. C: Attaching the baseplate to the miniscope. D: Tightening the set screw for fixing the baseplate to the miniscope. The set screw is released after cementing the baseplate to the mouse skull.

Figure 4. Construction of the Odor Arena.
A: Odor arena transparent Chamber. There is a top digital camera for recording the mouse behavior. B: Step motors coupled to syringes control the water delivery to reward the mouse. C: View from the inside of the odor arena showing a honeycomb structure is used to yield a laminar flow and four odor delivery lines. D: Odor delivery system including tubes, valves and odor bottles viewed from the outside of the odor arena.

Figure 5. Odor plume recording.
A: Odor plume recorded with the photoionization detector (PID). Mean(bold blue)±Standard Deviation (light blue) of five PID traces of an odor plume propagating at 4.23 cm/s in the odor arena. Odorant source at 2cm from the odor arena floor. The sensor head of the PID provides a voltage signal for the gas concentration of the odor plume. B: Laser recording of the odor plume

with unbounded flow at 20 cm/s.

Figure 6. Mouse Behavioral Training.

A: Mouse learning to navigate toward an odor plume released on the right lane. The mouse

learns to start a trial by going to the back of the odor arena, decide a side to navigate toward

the odor plume, and drink a water reward. B: Mouse learning to navigate toward an odor

plume released on the left lane. The mouse is rewarded with odor if navigating to the correct

lane.

Figure 7. Pre-Processing the Data

A: Calcium traces synchronized with the odor arena events for many trials. Each single trial

starts with the odor delivery in red and the rewarded trials end with a water delivery pulse in

blue. The $\delta F/F0$ (unitless) calcium traces for each ROI are shown in black. Each line indicates a

ROI. An interface board is used for recording the TTL outputs of the top camera on the odor

arena and the miniscope camera for synchronizing the frames. Normcorr is used for correcting

the movement noise from the miniscope frames and Extract is used to find the ROIs and extract

the $\delta F/F0$ calcium traces. B: Representative single trial of a mouse navigating a plume. The

simultaneous visualization of the synchronized behavior (left panel) and $\delta F/F0$ calcium traces

(right panel) from each ROI of a single trial are observed with BENTO.

Figure 8. Decoding the position of the mouse from the CA1 signals.

Decoding the X and Y position of the mouse from the CA1 ROIs. The decoding prediction is

shown in blue and the mouse ground true position is shown in red. The predicted traces are

strongly correlated with the ground truth.

A: Decoding the X positions from the ROIs (Pearson Correlation Coefficient = 0.88). B: Decoding

the Y positions from the ROIs (Pearson Correlation Coefficient = 0.88).

SUPPLEMENTARY FILES:

Supplementary Movie 1:

Representative example of synchronized behavioral and miniscope frames of a mouse

navigating toward an odor plume in the left lane. A: Behavioral frames of a mouse wearing a

miniscope and navigating inside of the odor arena. B: Miniscope frames of the mouse showing

the raw calcium transients recorded through the GRIN lens.

Supplementary Movie 2:

Representative example of synchronized behavioral and miniscope frames of a mouse

navigating toward an odor plume in the right lane. A: Behavioral frames of a mouse wearing a

miniscope and navigating inside of the odor arena. B: Miniscope frames of the mouse showing

the raw calcium transients recorded through the GRIN lens.

Supplementary Movie 3:

BENTO display of the processed data of mouse behavior and brain signals. Left panel: the

mouse is navigating toward the right lane in the arena. The behavior annotations are showed in

different colors. B: δF/F0 calcium signals of the mouse navigating.
617
618   Supplementary File 1:
619   Files for the 3D printed nose cone to perform isoflurane anesthesia.
620
621   Supplementary File 2:
622   Files for the head bar for head-fixing the mouse.
623
624   Supplementary File 3:
625   Detailed layout of the odor arena.
626
DISCUSSION:
This protocol meticulously outlines the steps to record place-cells and odor-responsive cells in
the dCA1 area of the hippocampus of mice navigating an odor plume. The critical steps in the
protocol include stereotaxic surgery, placement of the miniscope baseplate, construction of the
odor area, checking the plume in the odor arena, behavioral training, miniscope recording of
the freely moving mouse, data pre-processing, and data analysis. Additionally, the protocol
explains the process of decoding the mouse trajectory from the dCA1 recordings.
A critical step in stereotaxic surgery is to follow the coordinates relative to Bregma to place the
GRIN lens at the correct location. A limitation of the method is the delay between the surgery
and the time to start observing GCaMP6f signals, which can take two to four weeks. The mouse
should be ready for use after this critical period. A difference between the current protocol and
previous protocols [24, 24–26, 26, 27] is using Thy1-GCaMP6f mice already expressing GCaMP6f in CA1
instead of injecting AAV-GCaMP6f virus in the hippocampus. It saves time during the surgery
and does not require a wait time for the expression of the AAV virus in the brain. In addition,
this protocol does not aspirate the brain and uses isoflurane instead of ketamine/xylazine,
which provides a better control of the dose to prevent overdoses. A limitation of the method is
the optical aberration of the GRIN lens, which limits the field of view. A crucial step for the
baseplate placement is to keep the electrowetting lens at the center to prevent a limitation in
adjusting the Z plate after cementing the baseplate on the head. A limitation of the
construction of the odor arena is the system's complexity, which can take several months and
may require the assistance of an engineer. A limitation of the behavioral training is that mice
may prefer one side of the odor arena against another. One way to overcome this problem is to
alternate trials rewarding the mouse for navigating toward the left and right lanes.
A critical step for checking the plume is to keep the PID needle aligned with the odor source to
detect the plume's path. A crucial step in miniscope recording a freely moving mouse is to
ensure that the mini-coax wire does not tangle during the task, which can be prevented with a
commutator. Helium balloons can be used to prevent the mini-coax wire from coming in front
of the mouse. It is critical for the data pre-processing to synchronize the TTL pulses of the digital
top camera of the odor arena and the miniscope camera. For the EXTRACT procedure, it is
recommended to use non-negative processing to extract the ROIs and δF/F0 signals better.
EXTRACT yields a visual inspection of the traces for each ROI to exclude bad ones. It is critical to
decode the X and Y positions of the mouse from the ROIs to have a large dataset with hundreds
of epochs for better training the artificial neural network.

The significance of this freely moving recording method concerning existing head-fixed methods
is studying the mouse behavior in an ethologically relevant context with the proper head
movement for navigating a complex odor plume. This method is applicable to investigate the
dynamic role of dCA1 neurons in complex odorant navigation. Furthermore, the procedure is
not restricted to hippocampus or olfaction. Other potential applications of the technique
include studying the role of different brain areas and sensory modalities, including possible
applications in visual navigation by using LEDs to indicate the rewarded lanes. In addition, this
method can be potentially applied in real-time closed-loop experiments in which decoding
neural calcium from population triggers neurostimulation or sensory feedback [20, 34–36].
669

ACKNOWLEDGMENTS:
This research was supported by the US National Institutes of Health (NIH UF1 NS116241 and
NIH R01 DC000566), and the National Science Foundation (NSF BCS-1926676). The authors
thank Andrew Scallon for helping setting up the Odor Arena chamber.

DISCLOSURES:
The authors declare no conflict of interest.
677

678 **REFERENCES:**
679

1. Adoff, M.D., Climer, J.R., Davoudi, H., Marvin, J.S., Looger, L.L., Dombeck, D.A. The functional organization of excitatory synaptic input to place cells. *Nature Communications*. **12** (1), 3558, doi: 10.1038/s41467-021-23829-y (2021).
2. Radvansky, B.A., Oh, J.Y., Climer, J.R., Dombeck, D.A. Behavior determines the hippocampal spatial mapping of a multisensory environment. *Cell Reports*. **36** (5), 109444, doi: 10.1016/j.celrep.2021.109444 (2021).
3. Lewis, S.M. *et al.* Plume Dynamics Structure the Spatiotemporal Activity of Mitral/Tufted Cell Networks in the Mouse Olfactory Bulb. *Frontiers in Cellular Neuroscience*. **15**, 633757, doi: 10.3389/fncel.2021.633757 (2021).
4. Findley, T.M. *et al.* Sniff-synchronized, gradient-guided olfactory search by freely moving mice. *eLife*. **10**, e58523, doi: 10.7554/eLife.58523 (2021).
5. Gire, D.H., Kapoor, V., Arrighi-Allisan, A., Seminara, A., Murthy, V.N. Mice Develop Efficient Strategies for Foraging and Navigation Using Complex Natural Stimuli. *Current Biology*. **26** (10), 1261–1273, doi: 10.1016/j.cub.2016.03.040 (2016).
6. Liu, A., Papale, A.E., Hengenius, J., Patel, K., Ermentrout, B., Urban, N.N. Mouse Navigation Strategies for Odor Source Localization. *Frontiers in Neuroscience*. **14**, 218, doi: 10.3389/fnins.2020.00218 (2020).
7. Tariq, M.F. *et al.* Using Head-Mounted Ethanol Sensors to Monitor Olfactory Information and Determine Behavioral Changes Associated with Ethanol-Plume Contact during Mouse Odor-Guided Navigation. *eneuro*. **8** (1), ENEURO.0285-20.2020, doi: 10.1523/ENEURO.0285-20.2020 (2021).
8. Rigolli, N., Reddy, G., Seminara, A., Vergassola, M. Alternation emerges as a multi-modal strategy for turbulent odor navigation. *eLife*. **11**, e76989, doi: 10.7554/eLife.76989 (2022).
9. Ma, M. *et al.* Sequential activity of CA1 hippocampal cells constitutes a temporal memory

map for associative learning in mice. *Current Biology*. S0960982224000216, doi: 10.1016/j.cub.2024.01.021 (2024).

10. Aharoni, D., Khakh, B.S., Silva, A.J., Golshani, P. All the light that we can see: a new era in miniaturized microscopy. *Nature Methods*. **16** (1), 11–13, doi: 10.1038/s41592-018-0266-x (2019).

11. Aharoni, D., Hoogland, T.M. Circuit Investigations With Open-Source Miniaturized Microscopes: Past, Present and Future. *Frontiers in Cellular Neuroscience*. **13**, 141, doi: 10.3389/fncel.2019.00141 (2019).

12. Flusberg, B.A. *et al*. High-speed, miniaturized fluorescence microscopy in freely moving mice. *Nature Methods*. **5** (11), 935–938, doi: 10.1038/nmeth.1256 (2008).

13. Connor, E.G., McHugh, M.K., Crimaldi, J.P. Quantification of airborne odor plumes using planar laser-induced fluorescence. *Experiments in Fluids*. **59** (9), 137, doi: 10.1007/s00348-018-2591-3 (2018).

14. Gumaste, A. *et al*. A Comparison between Mouse, In Silico, and Robot Odor Plume Navigation Reveals Advantages of Mouse Odor Tracking. *eNeuro*. **7** (1), ENEURO.0212-19.2019, doi: 10.1523/ENEURO.0212-19.2019 (2020).

15. Gumaste, A. *et al*. Behavioral discrimination and olfactory bulb encoding of odor plume intermittency. *eLife*. **13**, e85303, doi: 10.7554/eLife.85303 (2024).

16. Marin, A.C., Schaefer, A.T., Ackels, T. Spatial information from the odour environment in mammalian olfaction. *Cell and Tissue Research*. **383** (1), 473–483, doi: 10.1007/s00441-020-03395-3 (2021).

17. Eichenbaum, H. The role of the hippocampus in navigation is memory. *Journal of Neurophysiology*. **117** (4), 1785–1796, doi: 10.1152/jn.00005.2017 (2017).

18. Dombeck, D.A., Harvey, C.D., Tian, L., Looger, L.L., Tank, D.W. Functional imaging of hippocampal place cells at cellular resolution during virtual navigation. *Nature Neuroscience*. **13** (11), 1433–1440, doi: 10.1038/nn.2648 (2010).

19. Wirtshafter, H.S., Disterhoft, J.F. *In Vivo* Multi-Day Calcium Imaging of CA1 Hippocampus in Freely Moving Rats Reveals a High Preponderance of Place Cells with Consistent Place Fields. *The Journal of Neuroscience*. **42** (22), 4538–4554, doi: 10.1523/JNEUROSCI.1750-21.2022 (2022).

20. Mizuta, K., Sato, M. Multiphoton imaging of hippocampal neural circuits: techniques and biological insights into region-, cell-type-, and pathway-specific functions. *Neurophotonics*. **11** (3), 033406, doi: 10.1117/1.NPh.11.3.033406 (2024).

21. Radvansky, B.A., Dombeck, D.A. An olfactory virtual reality system for mice. *Nature Communications*. **9** (1), 839, doi: 10.1038/s41467-018-03262-4 (2018).

22. Almeida-Santos, A.F. *et al*. Social isolation impairs the persistence of social recognition memory by disturbing the glutamatergic tonus and the olfactory bulb-dorsal hippocampus coupling. *Scientific Reports*. **9** (1), 473, doi: 10.1038/s41598-018-36871-6 (2019).

23. Dana, H. *et al*. Thy1-GCaMP6 Transgenic Mice for Neuronal Population Imaging In Vivo. *PLoS ONE*. **9** (9), e108697, doi: 10.1371/journal.pone.0108697 (2014).

24. Thapa, R., Liang, B., Liu, R., Li, Y. Stereotaxic Viral Injection and Gradient-Index Lens Implantation for Deep Brain In Vivo Calcium Imaging. *Journal of Visualized Experiments*. (176), 63049, doi: 10.3791/63049 (2021).

25. Hsiao, Y.-T., Wang, A.Y.-C., Lee, T.-Y., Chang, C.-Y. Using Baseplating and a Miniscope

Preanchored with an Objective Lens for Calcium Transient Research in Mice. *Journal of Visualized Experiments*. (172), 62611, doi: 10.3791/62611 (2021).

26. Zhang, L. *et al*. Miniscope GRIN Lens System for Calcium Imaging of Neuronal Activity from Deep Brain Structures in Behaving Animals. *Current Protocols in Neuroscience*. **86** (1), e56, doi: 10.1002/cpns.56 (2019).

27. Guo, D., Gürkan Özer, A., Uusisaari, M.Y. In vivo Calcium Imaging in Mouse Inferior Olive. *Journal of Visualized Experiments: JoVE*. (172), doi: 10.3791/62222 (2021).

28. Yun, M., Shin, J., Jung, M.W. Protocol for calcium imaging of dorsal and ventral CA1 neurons in head-fixed mice. *STAR Protocols*. **4** (3), 102439, doi: 10.1016/j.xpro.2023.102439 (2023).

29. Yun, M., Hwang, J.Y., Jung, M.W. Septotemporal variations in hippocampal value and outcome processing. *Cell Reports*. **42** (2), 112094, doi: 10.1016/j.celrep.2023.112094 (2023).

30. Sheffield, M.E.J., Dombeck, D.A. Calcium transient prevalence across the dendritic arbour predicts place field properties. *Nature*. **517** (7533), 200–204, doi: 10.1038/nature13871 (2015).

31. Pnevmatikakis, E.A., Giovannucci, A. NoRMCorre: An online algorithm for piecewise rigid motion correction of calcium imaging data. *Journal of Neuroscience Methods*. **291**, 83–94, doi: 10.1016/j.jneumeth.2017.07.031 (2017).

32. Inan, H. *et al*. *Fast and statistically robust cell extraction from large-scale neural calcium imaging datasets*. doi: 10.1101/2021.03.24.436279. Neuroscience. (2021).

33. Segalin, C. *et al*. The Mouse Action Recognition System (MARS) software pipeline for automated analysis of social behaviors in mice. *eLife*. **10**, e63720, doi: 10.7554/eLife.63720 (2021).

34. Chen, Z. *et al*. A hardware system for real-time decoding of in vivo calcium imaging data. *eLife*. **12**, e78344, doi: 10.7554/eLife.78344 (2023).

35. Xue, F. *et al*. Multi-region calcium imaging in freely behaving mice with ultra-compact head-mounted fluorescence microscopes. *National Science Review*. **11** (1), nwad294, doi: 10.1093/nsr/nwad294 (2024).

36. Tabourin, L., Bretzner, F., Galstian, T. Towards a mini-endoscope design with spatially selective excitation and imaging. *Biomedical Optics Express*. **15** (3), 1750–1760, doi: 10.1364/BOE.512124 (2024).

A Stereotaxic Surgery

B Miniscope Baseplate Placement

C Behavioral Training

D

Deciding

Annotations
[s] Trial Start
[d] Deciding
[n] Navigating
[k] Drinking
[r] Returning

Edit hotkeys
Edit colors

Window (sec): 20   Trace + -   Plotting: raw (...) units areas
Chann FCM22_hit1 ▼ Add Dele.. Dup.. Behavio Add Dele. Fast..   MARS
Mouse 1 ▼   Session 1 ▼   Trial 1 ▼

dF/F0

-20   -10   0   10   20
time (sec)

Freely Moving Recording

A

B

C

D

A

B

A

Odor Lane R

Navigating   Trial Start

Drinking

Deciding

Odor Lane L

B

Trial Start

Deciding

Drinking

Navigating

A

Odor   Water

dF/F0

100 sec

B

Navigating

Mouse

ROIs

Annotations
[s] Trial Start
[d] Deciding
[n] Navigating
[k] Drinking
[r] Returning

Edit hotkeys
Edit colors

00:04.52

Window (sec): 20   Trace + −   Plotting: raw ▾ units ▾ areas ▾

Chann FCM22_hit1 ▾ Add Dele.. Dup.. Behavio Add Dele.. Fast..   MARS

Mouse 1 ▾   Session 1 ▾   Trial 1 ▾

dF/F0

-20   -10   0   10   20
time (sec)