Has AlphaFold 3 reached its success for RNAs?

Clément Bernard[1,2], **Guillaume Postic**[1], **Sahar Ghannay**[2], **and Fariza Tahi**[1]

[1]Université Paris Saclay, Univ Evry, IBISC, 91020, Evry-Courcouronnes, France

[2]LISN - CNRS/Université Paris-Saclay, France, 91400, Orsay, France

Predicting the 3D structure of RNA is a significant challenge despite ongoing advancements in the field. Although AlphaFold has successfully addressed this problem for proteins, RNA structure prediction raises difficulties due to fundamental differences between proteins and RNAs, which hinder direct adaptation. The latest release of AlphaFold, AlphaFold 3, has broadened its scope to include multiple different molecules like DNA, ligands and RNA. While the article discusses the results of the last CASP-RNA dataset, the scope of performances and the limitations for RNAs are unclear. In this article, we provide a review of the performance of AlphaFold 3 in the prediction of RNA 3D structures. Through an extensive benchmark over four different test sets, we discuss the performances and limitations of AlphaFold 3. We also compare its performances with ten existing state-of-the-art ab initio, template-based and deep-learning approaches.
Our results are freely available on the EvryRNA platform:
`https://evryrna.ibisc.univ-evry.fr/evryrna/alphafold3/`.

RNA 3D structure | AlphaFold 3 | Deep Learning | Structure evaluation
Correspondence: *fariza.tahi@univ-evry.fr*

1. Introduction

RNA molecules play a crucial role in the living. While its function is directly linked to its structure, the prediction of the latter remains an open challenge to be addressed. Knowing the structure of RNA could be of great interest for drug design or the comprehension of biological processes like cancer (1). While experimental methods like X-ray crystallography, NMR or cryo-EM (2) can determine the RNA 3D structures, their use is costly (in time and resources) and hardly scalable for the number of RNAs in the living. Computational approaches have emerged with *ab initio*, template-based and deep learning procedures. *Ab initio* methods (3–12) tend to reproduce the physics of the system, with force field applied to a coarse-grained representation (low-resolution where a nucleotide is replaced by some of its atoms). The template-based approaches (13–22) create a mapping between sequences and fragments of structure before refining the assembled structures.

Recently, with the recent success of AlphaFold for proteins (23, 24), approaches have been made to replicate its success in RNAs. Deep learning approaches like DeepFoldRNA (25), RhoFold (26), DrFold (27), NuFold (28), trRosettaRNA (29) employ strategies related to AlphaFold 2. They consider coarse-grained representation and predict Euclidean transfor-mation before reconstructing the full-atom structure. The use of torsional angles is also adapted to RNAs, with either the standard torsional angles or angles from their coarse-grained representations.

While being better than existing template-based or *ab initio* methods, deep learning approaches do not solve the prediction of RNA structures yet (30), as shown in our recent benchmark State-of-the-RNArt (31). It has also been demonstrated in the CASP-RNA challenge (32), where the top four best predictions are not deep learning-based.

The recent release of AlphaFold, AlphaFold 3, extends the prediction to ligands, DNA and RNA. It uses as inputs the sequence and multiple sequence alignment (MSA) and it also changes a part of the architecture to better adapt to the variety of its inputs. It no longer relies on torsional angles to prevent the restriction to specific molecules. It directly predicts atom coordinates with the use of a multi-cross diffusion model. Through a benchmark on CASP-RNA (32), the article mentioned good results but did not outperform human-helped methods. Nonetheless, it is not clear what the current limitations are and how well it performs compared to state-of-the-art solutions.

The aim of this article is to provide a comprehensive extension on the benchmark of AlphaFold 3 for RNAs. We first describe the main differences between RNA and proteins, before discussing the benchmark we did to evaluate AlphaFold 3. Then, we describe the results of AlphaFold 3 and the current limitations of the model. The results and the data are freely available and usable in the EvryRNA platform: `https://evryrna.ibisc.univ-evry.fr/evryrna/alphafold3/`.

2. RNA vs proteins

RNA and proteins are both molecules that play crucial roles in the living (33). They share the characteristic of having a 3D structure that directly defines their function. In this part, we discuss the differences that have prevented protein algorithms from being adaptable to RNAs.

RNAs comprise four nucleotides (A, C, G and U), whereas proteins comprise 20 amino acids. This difference has a high consequence on the adaptation of protein algorithms to RNA. The vocabulary available for RNA is limited to four unique elements, making the use of protein vocabulary not directly adaptable. The sequence length of RNA molecules also has a high variability (from a dozen to thousands of nucleotides) compared to proteins (around a hundred

amino acids).

A major difference between RNAs and proteins lies in the folding stabilisation. RNA structure is maintained by base pairing and base stacking, while protein structure is supported by hydrogen interactions in the skeleton. The protein backbone is also modelled by torsion angles (Φ and Ψ) for each amino acid because the peptide bond is planar. This is not the case for RNA, where each nucleotide can be described by six torsion angles (α, β, γ, δ, ϵ, ξ) and the sugar-pucker conformation (χ). An approximation usually involves pseudo-torsion η and θ (**?**). Protein models learn a conformational mechanism fundamentally different from the RNA folding process.

The nature of pairwise interactions of RNA 3D molecules differ from those of proteins. The Watson-Crick (WC) and non-WC interactions can be made through three different edges of the RNA base: WC edge, Hoogsten edge and sugar edge, shown in Figure 1. In addition, the orientation of the glycosidic bonds gives another property to an interaction: *cis* or *trans*. The combination of edge and orientation gives 12 possibilities of interaction between bases. The standard WC base pair corresponds to the cis WC/WC pairing. Given the orientations (*cis* or *trans*), the edges (WC-WC, WC-S, WC-H, S-WC, S-S, S-H, H-WC, H-S, H-H) and the base pairing (AA, GG, CC, UU, AG, AC, AU, GA, GC, GU, CA, CG, CU, UA, UG, UC), there are more than 200 possible base pairs. Only the standard WC pairs (cis WC/WC) of AU and CG (with GU wobble pair) are used for the 2D structure representation. Non-standard interactions play a crucial role in the overall topology of the RNA folding process. They help stabilise the structure and can not be ignored when working on RNA 3D structures.

Figure 1. Description of the three different edges of the adenine RNA base: Watson-Crick edge, Hoogsten edge and Sugar edge. The edges are similar to the other nucleotides.

The stability of the RNA and protein structures is different. Proteins tend to have a stable structure corresponding to a minimum in the energy landscape. On the other hand, RNAs can have multiple conformations depending on the environmental condition. Those foldings are of equivalent validity as they are all local minimums in the energy landscape. Ideally, finding an RNA 3D structure means finding the native foldings of RNA, and should output multiple structures with confidence scores. However, the available structures found in the PDB do not provide access to this diversity of structures.

There is a huge disparity in the protein and RNA data. Even if there is a higher proportion of RNAs than proteins in the living, this is not reflected in the available data: only a small amount of 3D RNA structures are known. Up to June 2024, 7,759 RNA structures were deposited in the Protein Data Bank (34), compared to 216,212 protein structures. The quality and diversity of data are also different: a huge proportion of RNAs come from the same families. It implies several redundant structures that could prevent a model from being generalized to other families. In addition, a huge amount of RNA families have not yet solved structures in the PDB. This means there is no balanced and representative proportion of RNA families through the known structures.

Finally, no standard dataset has been used through the community for RNAs. Each research group uses its dataset with different preprocessing associated. It prevents using deep learning methods, as a lot of work is needed for a clean dataset. While the community agrees to use RNA-Puzzles (35–39) or the newly-RNA (32) to test the generalization of proposed models, no clear training set is available. RNANet (40) has recently been developed to solve this issue. A new approach, RNA3DB (41), tries to create independent datasets to use for deep learning approaches where clustering is done based on sequence and structure disparity.

3. Materials & methods

In this section, we describe the benchmarked models, metrics, and datasets used to evaluate AlphaFold 3 performances.

A. Datasets

To evaluate the prediction of RNA structures, we considered four test sets, with three of them from our previous work (31).

- **RNA-Puzzles**: the first dataset is composed of the single-stranded structures from RNA-Puzzles (35–39), a community initiative to benchmark RNA structures. We considered only single-stranded solutions to have a fair comparison between the benchmarked models. It is composed of 22 RNAs of length between 27 and 188 nucleotides with a mean of 85 nucleotides.

- **CASP-RNA**: the second test set is CASP-RNA (32) structures, which is a collaboration between the CASP team and RNA-Puzzles. It is composed of 12 RNAs with wide-range sequences, from 30 to 720 nucleotides (with a mean of 210 nucleotides).

- **RNASolo**: the third test set is a custom test set composed of independent structures from RNAsolo (42). We downloaded the representative RNA molecules from RNAsolo (42) with a resolution below 4 Å and removed the structures with sequence identity higher than 80%. Then, we considered only the structures with a unique Rfam family ID (43), leading to 29 non-redundant RNA molecules, with a sequence between 40 and 298 nucleotides (and a mean of 96 nucleotides). It can not be ensured that the structures from this dataset were not used in the training set of

AlphaFold 3. We keep this dataset for comparison, as we already have the results for the benchmarked methods.

- **RNA3DB**: the last dataset is composed of a non-redundant set of structurally and sequentially independent structures from RNA3DB (41). It comprises the component #0, which is composed of orphan structures that are advised to be used as a test set. These structures do not have Rfam family (43) and include synthetic RNAs, small messenger RNA crystallized as part of larger complexes. After removing structures with sequences below ten nucleotides, we ended up with a dataset of 359 structures from 10 nucleotides to 339 nucleotides (with a mean of 51 nucleotides).

For the rest of the article, we mention each dataset by RNA-Puzzles, CASP-RNA, RNASolo and RNA3DB to refer them.

B. State-of-the-art methods

Existing solutions for the predictions of RNA 3D structures are based on three main types of methods: *ab initio*, template-based and deep-learning ones. As discussed previously in our work(31), *ab initio* methods (3, 5, 7) integrate the physics of the system by usually simplifying the representation of nucleotide (coarse-grained). Instead of using all the atoms for one nucleotide, they create a low-resolution representation that simplifies the computation time while losing information. They use approaches like molecular dynamics (44) or Monte Carlo (45) to perform sampling in the conformational space and use a force field to simulate real environment conditions. On the other hand, template-based methods (13, 17–19, 46) create a mapping between sequences and known motifs with, for instance, secondary structure trees (SSEs) before reconstructing the full structure from its subfragments. Finally, the recent methods tend to incorporate deep learning methods (25–29) by using attention-based architecture with self-distillation, recycling as done in AlphaFold 2 (24).

To compare the performances of AlphaFold 3 (47), we benchmarked ten different previously mentioned approaches on three of the four test sets: the ones used in our previous work (31). We used the web servers with default parameters to compare available models fairly, where each user could reproduce our experiments. For the *ab initio* methods, we benchmarked SimRNA (7), IsRNA1 (5) and RNAJP (3). Only RNAJP was used locally. For the template-based approaches, we used MC-Sym (46), Vfold3D (19), RNAComposer (18), 3dRNA (17) and Vfold-Pipeline (13). For the deep learning methods, we benchmark trRosettaRNA (29) and RhoFold (26). More details on each method are provided in our previous article (31). As me made most of the predictions using web servers, the predictions on the last test set RNA3DB were hardly applicable for all the methods. Therefore, for the RNA3DB dataset, we only benchmarked AlphaFold 3, which returns predictions very fast.

C. Evaluation metrics

To compare the predictions, we used the RNAdvisor tool (48) developed by our team, which enables the computation of a wide range of existing metrics in one command line. For the evaluation of RNA 3D structures, a general assessment of the folding of the structure can be done with either the root-mean-square deviation (RMSD) or its extension adding RNA features ϵRMSD (49). Protein-inspired metrics can also be adapted to assess structure quality like the TM-score (50, 51) of the GDT-TS (52) (counts the number of superimposed atoms). There are also the CAD-score (53) (which measures the structural similarity in a contact-area difference-based function) and the lDDT (54) (which assesses the interatomic distance differences between a reference structure and a predicted one). Finally, there are RNA-specific metrics that have been developed, like the P-VALUE (55) (which assesses the non-randomness of a given prediction). The INF and DI (56) have been developed to consider the RNA-specific interactions. The INF score incorporates canonical and non-canonical pairing with Watson-Crick (INF-WC), non-Watson-Crick (INF-NWC), and stacking (INF-STACK) interactions. The consideration of torsional angles has been developed with the mean of circular quantities (MCQ) (57). As discussed in (48), these metrics are complementary and can infer different aspects of RNA 3D structure behaviour.

4. Results

A. AlphaFold 3 compared to the state-of-the-art

We compare the predictions of ten existing methods and AlphaFold 3 on three of the four test sets. Figure 2 shows the different normalised metrics for the different models averaged over three test sets. All the metrics are normalised by the maximum values and converted to be better where near to 1 and worst when near to 0. Details of the results for each dataset are shown in Figure S1 of the Supplementary file. The results show that AlphaFold 3 has the best cumulative scores, which means it outperforms the other models when considering all the metrics. It has the highest MCQ value, indicating it returns structures which are even more physically plausible than *ab initio* methods (that use physics properties in their predictions). AlphaFold 3 does not have the best RMSD (beaten by Rhofold) but has the best lDDt and TM-score. This suggests AlphaFold does not always have the best alignment (in terms of all atoms). AlphaFold 3 has, for this benchmark, better results than the other existing approaches but does not outperform them in all existing metrics.

B. AlphaFold 3 on the different test sets

We also predicted structures from AlphaFold 3 on the last test set from RNA3DB (41). We report the TM-score, lDDT, DI and MCQ distributions for each of the four test sets in Figure 3. Distributions for other metrics are shown in Figure S2 of the Supplementary file. We observe the same behaviour for the four metrics: AlphaFold 3 has more difficulty in predicting good predictions for the dataset from RNA3DB and CASP-RNA. It has slightly better results for

Figure 2. Cumulative normalised metrics for each of the benchmark models (3, 5, 7, 13, 17–19, 26, 29, 46, 47) averaged over the three test sets (RNA-Puzzles (35–39), CASP-RNA (32) and RNAsolo (42)). Each metric is normalised by the maximum value over the four test sets, and the decreased metrics are inversed to have better values close to 1.

RNA-Puzzles, and good results for RNASolo (which makes sense as we could not ensure the structures were not leaked in the training set). These results show the difficulty of AlphaFold 3 in predicting complex structures (with either long sequences of CASP-RNA or orphan structures of RNA3DB).

We detail the two best and worst predictions for each dataset from AlphaFold 3 in Figure 4. The worst performances are for structures of long sequences for CASP-RNA and RNA-Puzzles (sequences of 71, 185, 363 and 720 nucleotides). For the RNA3DB dataset, the worst performances are for RNA with non-common structures, which might not be found in the training set of AlphaFold 3.

C. Dependance on sequence length

The prediction of long RNAs (RNAs with sequence lengths higher than 200 nucleotides) is a major issue for current approaches. Indeed, the *ab initio* methods fail to predict long interactions as the computation time highly increases with the sequence length. The template-based approaches are limited by the small amount of long RNAs, as well as the deep learning methods, as shown in (31).

To observe the relation between sequence length and AlphaFold 3 performances, we report its link with the DI and lDDT metrics in Figure 5. We considered the DI as it considers both global conformation and key RNA interactions and the lDDT as it gives a general idea of atomic distances. Links between the other metrics and the sequence length are available in Figures S3, S4 and S5 of the Supplementary file. Figure 5 indicates that the DI highly increases for the RNA3DB dataset for sequences between 0 and 100. There is also a lower slope of increase for the other test sets (except for RNAsolo), meaning that the DI slightly increases with the sequence length. Indeed, it becomes harder to predict both the folding and the canonical and non-canonical interactions when the sequence is increasing. We also observe a tendency

of decrease for the lDDT when the structures have sequences higher than 100 nucleotides.

D. Non-canonical interactions

To understand the comportment of AlphaFold 3 on RNA-specific interactions, we study the Watson-Crick (WC), non-Watson-Crick (nWC) and stacking (STACK) interactions are shown for each dataset in Table 1. All test sets have similar mean nWC interactions (except for the RNA3DB dataset). As the CASP-RNA has structures with longer sequences, it also has more stacking and WC interactions.

Table 1. Information about Watson-Crick (WC), non-Watson-Crick (nWC) and Stacking (STACK) interactions for the four test sets. The mean nWC is counted for structures with more than one nWC interaction. All test sets have more than one nWC interaction (except from RNA3DB, which has 56% of structures with at least one nWC interaction). All the datasets have at least one stacking and one WC interaction.

	RNA3DB	CASP	RNA-Puzzles	RNASolo
Mean nWC	4.7	7.6	7.5	7.8
Max. nWC	18.0	17.0	16.0	22.0
Mean STACK	31.3	160.4	65.8	73.4
Max. STACK	187.0	553.0	155.0	207.0
Mean WC	16.0	83.1	27.7	30.2
Max. WC	77.0	320.0	66.0	95.0

To evaluate the ability of AlphaFold 3 to predict non-canonical structures, we depict the scatter plots between non-Watson-Crick INF (INF-NWC) and Watson-Crick INF (INF-WC) in Figure 6. The size of the points is proportional to the RMSD of structures and, thus, to their alignment. We include the RMSD to highlight the global alignment. We observe a tendency to have a high RMSD (small points) whenever the INF-WC and INF-nWC are high. There is also a large number of structures with an INF-NWC of 0, implying that AlphaFold 3 does not predict any of the non-Watson-Crick interactions. Examples of successful and missing non-Watson-Crick interactions are shown in the Figure. For the results on stacking interactions, there are predictions where AlphaFold 3 does not predict the Watson-Crick interactions well but still predicts the stacking ones. It can be explained by good skeleton predictions while lacking the base conformations that produce the WC interactions. Secondly, there is an increased tendency between the INF-STACK and INF-WC: when AlphaFold 3 predicts the WC interactions well, it also tends to estimate the stacking well. Indeed, whenever the WC are respected, the stacking can be more easily inferred. These results show the limitations of AlphaFold 3 for predicting complex RNA interactions.

5. Conclusion

AlphaFold 2 had a huge success in the prediction of protein folding and has changed the field by the quality of its predictions. The new release of AlphaFold, named AlphaFold 3, has extended the model to predict all molecules from the PDB, like ions, ligands, DNA or RNA.

Figure 3. TM-score (58), lDDT (54), DI (56) and MCQ (57) distributions for each of the four test sets of the AlphaFold 3 (47) predictions. TM-score and lDDT are ascending: the higher, the better. DI and MCQ are descending: the lower, the better.

Through an extensive benchmark on four different robust test sets, we have evaluated the quality of prediction of AlphaFold 3 for RNA molecules. We have also compared its predictions to ten existing methods, which are easily reproducible as we considered only models with web servers.

Our results show that AlphaFold 3 has not yet reached the same success as proteins for RNAs. Its new architecture allows the prediction of wide molecules but remains limited and hardly predicts non-Watson-Crick interactions.

The predictions of AlphaFold 3 remain of competitive quality, as it outperforms most of the existing solutions and returns more physically plausible structures than *ab initio* methods. It outclasses existing deep-learning approaches but does not generalize well on orphan structures or long RNAs. It also returns predictions very quickly compared to *ab initio* or current template-based approaches.

The prediction of atom coordinates instead of base frames in AlphaFold 2 allows the extension of predictions for a wide range of molecules but prevents the generalisation of RNA-specific interactions. The lack of data is also a limitation that prevents the robustness of deep learning methods in general, and so is AlphaFold 3.

ACKNOWLEDGEMENTS
This work is supported in part by UDOPIA-ANR-20-THIA-0013, Labex DigiCosme (project ANR11LABEX0045DIGICOSME), performed using HPC resources from GENCI/IDRIS (grant AD011014250), and operated by ANR as part of the program "Investissement d'Avenir" Idex ParisSaclay (ANR11IDEX000302).
Conflict of Interest: None is declared.

Bibliography

1. Yuhua Zhu, Ling Zhu, Xinhua Wang, et al. RNA-based Therapeutics: An Overview and Prospectus. *Cell Death & Disease*, 13:644, 2022. doi: 10.1038/s41419-022-05075-2.

2. Kailong Zhang, Shuai Li, Kristina Kappel, et al. Cryo-EM Structure of a 40 kDa SAM-IV Riboswitch RNA at 3.7 Å Resolution. *Nature Communications*, 10:5511, 2019. doi: 10.1038/s41467-019-13494-7.

3. Jun Li and Shi-Jie Chen. RNAJP: enhanced RNA 3D structure predictions with non-canonical interactions and global topology sampling. *Nucleic Acids Research*, 51:3341–3356, 4 2023. ISSN 0305-1048. doi: 10.1093/nar/gkad122.

4. Andrey Krokhotin, Kevin Houlihan, and Nikolay V. Dokholyan. iFoldRNA v2: folding RNA with constraints. *Bioinformatics*, 31:2891–2893, 9 2015. ISSN 1367-4803. doi: 10.1093/bioinformatics/btv221.

5. Dong Zhang, Jun Li, and Shi-Jie Chen. IsRNA1: De Novo Prediction and Blind Screening of RNA 3D Structures. *Journal of Chemical Theory and Computation*, 17:1842–1857, 3 2021. ISSN 1549-9618. doi: 10.1021/acs.jctc.0c01148.

6. Dong Zhang, Shi jie Chen, and Ruhong Zhou. Modeling Noncanonical RNA Base Pairs by a Coarse-Grained IsRNA2 Model. *The journal of physical chemistry. B*, 2021.

7. Michal J. Boniecki, Grzegorz Lach, Wayne K. Dawson, Konrad Tomala, Pawel Lukasz, Tomasz Soltysinski, Kristian M. Rother, and Janusz M. Bujnicki. SimRNA: a coarse-grained method for RNA folding simulations and 3D structure prediction. *Nucleic Acids Research*, 44:e63–e63, 4 2016. ISSN 0305-1048. doi: 10.1093/nar/gkv1479.

8. Tristan Cragnolini, Yoann Laurin, Philippe Derreumaux, and Samuela Pasquali. Coarse-Grained HiRE-RNA Model for ab Initio RNA Folding beyond Simple Molecules, Including Noncanonical and Multiple Base Pairings. *Journal of Chemical Theory and Computation*, 11(7):3510–3522, 2015. doi: 10.1021/acs.jctc.5b00200. PMID: 26575783.

9. Peter Kerpedjiev, Christian H. Zu Siederdissen, and Ivo L. Hofacker. Predicting RNA 3D Structure Using a Coarse-Grain Helix-Centered Model. *RNA*, 21:1110–1121, 2015. doi: 10.1261/rna.047522.114.

10. Petr Šulc, Flavio Romano, Thomas E. Ouldridge, Jonathan P. K. Doye, and Ard A. Louis. A Nucleotide-Level Coarse-Grained Model of RNA. *J. Chem. Phys.*, 140:235102, 2014. doi: 10.1063/1.4881424.

11. Magdalena A. Jonikas, Randall J. Radmer, Alain Laederach, Rhiju Das, Samuel Pearlman, Daniel Herschlag, and Russ B. Altman. Coarse-grained modeling of large RNA molecules with knowledge-based potentials and structural filters. *RNA*, 15:189–199, 2 2009. ISSN 1355-8382. doi: 10.1261/rna.1270809.

12. Jes Frellsen, Ida Moltke, Martin Thiim, Kanti V. Mardia, Jesper Ferkinghoff-Borg, and Thomas Hamelryck. A Probabilistic Model of RNA Conformational Space. *PLoS Computational Biology*, 5:e1000406, 6 2009. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1000406.

13. Jiajie Li, Shanshan Zhang, Dan Zhang, and Shi-Jie Chen. Vfold-Pipeline: a web server for RNA 3D structure prediction from sequences. *Bioinformatics*, 38(16):4042–4043, 2022. doi: 10.1093/bioinformatics/btab292.

14. Li Zhou, Xunxun Wang, Shixiong Yu, Ya-Lan Tan, and Zhi-Jie Tan. FebRNA: an automated fragment-ensemble-based model for building RNA 3D structures. *Biophysical Journal*, 121: 3381–3392, 2022.

15. Andrew Martin Watkins, Ramya Rangan, and Rhiju Das. FARFAR2: Improved De Novo Rosetta Prediction of Complex Global RNA Folds. *Structure*, 28:963–976.e6, 8 2020. ISSN 09692126. doi: 10.1016/j.str.2020.05.011.

16. Xiaojun Xu and Shi-Jie Chen. Hierarchical Assembly of RNA Three-Dimensional Structures Based on Loop Templates. *Journal of Physical Chemistry B*, 122:5327–5335, 2017. doi: 10.1021/acs.jpcb.7b01933.

17. Yi Zhang, Jun Wang, and Yi Xiao. 3dRNA: 3D Structure Prediction from Linear to Circular RNAs. *Journal of Molecular Biology*, 434(11):167452, 2022. ISSN 0022-2836. doi: https://doi.org/10.1016/j.jmb.2022.167452. Computation Resources for Molecular Biology.

18. Mariusz Popenda, Marta Szachniuk, Maciej Antczak, Katarzyna J. Purzycka, Piotr Lukasiak, Natalia Bartol, Jacek Blazewicz, and Ryszard W. Adamiak. Automated 3D structure composition for large RNAs. *Nucleic Acids Research*, 40:e112–e112, 8 2012. ISSN 1362-4962. doi: 10.1093/nar/gks339.

19. Song Cao and Shi-Jie Chen. Physics-Based De Novo Prediction of RNA 3D Structures. *Journal of Physical Chemistry B*, 115:4216–4226, 2011. doi: 10.1021/jp110370s.

20. Magdalena Rother, Kristian Rother, Tomasz Puton, and Janusz M. Bujnicki. ModeRNA: a tool for comparative modeling of RNA 3D structure. *Nucleic Acids Research*, 39:4007–4022,

Figure 4. The two best and two worst predictions from AlphaFold 3 (47) for A) RNA-Puzzles (36–39), B) CASP-RNA (32), C) Test set obtained from RNASolo (42) and D) Test set from RNA3DB (41). The DI (56), lDDT (54), TM-score (50) and MCQ (57) are included for each structure. The predictions from AlphaFold 3 (in blue) are aligned with the native ones (in orange) using US-align (59).

Figure 5. Dependence of two metrics with the sequence length on the prediction of AlphaFold 3 (47) on the four test sets. Some structures are represented, with the native one (in orange) and the aligned prediction by AlphaFold 3 (in blue). A) Results of the DI (56) depending on RNA sequence length. Higher values of DI mean bad predictions, while low values mean accurate predictions. B) Results of lDDt (54) depending on RNA sequence length. Higher values of lDDT mean good predictions, while low values mean bad predictions.

Figure 6. Link between Watson-Crick (WC), non-Watson-Crick (nWC) and stacking (STACK) interactions for the predictions of AlphaFold 3 for the four test sets. The size of each point is proportional to the RMSD: the lower, the better. Only structures with at least one non-Watson-Crick interaction are shown. An INF (56) value of 1 means accurate reproduction of key RNA interactions, while a value near 0 means the structure does not reproduce the interactions. A) INF stacking (INF-STACK) depending on INF Watson-Crick (INF-WC) interactions. B) INF non-Watson-Crick (INF-nWC) depending on INF Watson-Crick (INF-WC)interactions.

5 2011. ISSN 1362-4962. doi: 10.1093/nar/gkq1320.

21. Samuel C Flores, Yaqi Wan, Rick Russell, and Russ B Altman. Predicting RNA structure by multiple template homology modeling. *Pacific Symposium on Biocomputing. Pacific Symposium on Biocomputing*, page 216—227, 2010. ISSN 2335-6928. doi: 10.1142/9789814295291_0024.

22. Rhiju Das and David Baker. Automated de novo prediction of native-like RNA tertiary structures. *Proceedings of the National Academy of Sciences of the United States of America*, 104:14664–9, 10 2007. doi: 10.1073/pnas.0703836104.

23. Andrew W. Senior, Richard Evans, John Jumper, James Kirkpatrick, Laurent Sifre, Tim Green, Chongli Qin, Augustin Žídek, Alexander W. R. Nelson, Alex Bridgland, Hugo Penedones, Stig Petersen, Karen Simonyan, Steve Crossan, Pushmeet Kohli, David T. Jones, David Silver, Koray Kavukcuoglu, and Demis Hassabis. Improved protein structure prediction using potentials from deep learning. *Nature*, 577:706–710, 1 2020. ISSN 0028-0836. doi: 10.1038/s41586-019-1923-7.

24. John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, Alex Bridgland, Clemens Meyer, Simon A. A. Kohl, Andrew J. Ballard, Andrew Cowie, Bernardino Romera-Paredes, Stanislav Nikolov, Rishub Jain, Jonas Adler, Trevor Back, Stig Petersen, David Reiman, Ellen Clancy, Michal Zielinski, Martin Steinegger, Michalina Pacholska, Tamas Berghammer, Sebastian Bodenstein, David Silver, Oriol Vinyals, Andrew W. Senior, Koray Kavukcuoglu, Pushmeet Kohli, and Demis Hassabis. Highly accurate protein structure prediction with AlphaFold. *Nature*, 596:583–589, 8 2021. ISSN 0028-0836. doi: 10.1038/s41586-021-03819-2.

25. Robin Pearce, Gilbert S. Omenn, and Yang Zhang. De Novo RNA Tertiary Structure Prediction at Atomic Resolution Using Geometric Potentials from Deep Learning. *bioRxiv*, May 2022. doi: 10.1101/2022.05.15.491755.

26. Tao Shen, Zhihang Hu, Zhangzhi Peng, Jiayang Chen, Peng Xiong, Liang Hong, Liangzhen Zheng, Yixuan Wang, Irwin King, Sheng Wang, et al. E2Efold-3D: End-to-End Deep

Learning Method for Accurate de Novo RNA 3D Structure Prediction. *arXiv preprint arXiv:2207.01586*, 2022.

27. Y. Li, C. Zhang, C. Feng, and et al. Integrating end-to-end learning with deep geometrical potentials for ab initio RNA structure prediction. *Nature Communications*, 14:5745, 2023. doi: 10.1038/s41467-023-41303-9.

28. Yuki Kagaya, Zicong Zhang, Nabil Ibtehaz, Xiao Wang, Tsukasa Nakamura, David Huang, and Daisuke Kihara. NuFold: A Novel Tertiary RNA Structure Prediction Method Using Deep Learning with Flexible Nucleobase Center Representation. *bioRxiv*, 2023. doi: 10.1101/2023.09.20.558715.

29. W. Wang, C. Feng, R. Han, and et al. trRosettaRNA: automated prediction of RNA 3D structure with transformer network. *Nat Commun*, 14:7266, 2023. doi: 10.1038/s41467-023-42528-4.

30. Bohdan Schneider, Blake Alexander Sweeney, Alex Bateman, Jiri Cerny, Tomasz Zok, and Marta Szachniuk. When will RNA get its AlphaFold moment? *Nucleic Acids Research*, page gkad726, 09 2023. ISSN 0305-1048. doi: 10.1093/nar/gkad726.

31. Clément Bernard, Guillaume Postic, Sahar Ghannay, and Fariza Tahi. State-of-the-RNArt: benchmarking current methods for RNA 3D structure prediction. *NAR Genomics and Bioinformatics*, 6(2):lqae048, June 2024. doi: 10.1093/nargab/lqae048.

32. R Das, RC Kretsch, AJ Simpkin, and et al. Assessment of three-dimensional RNA structure prediction in CASP15. *Proteins*, 91(12):1747–1770, 2023. doi: 10.1002/prot.26602.

33. Minchin, Simon and Lodge, John. Understanding biochemistry: structure and function of nucleic acids. *Essays in Biochemistry*, 63(4):433–456, 2019. doi: 10.1042/EBC20180038.

34. Helen M. Berman, John Westbrook, Zukang Feng, Gary Gilliland, T. N. Bhat, Helge Weissig, Ilya N. Shindyalov, and Philip E. Bourne. The Protein Data Bank. *Nucleic Acids Research*, 28(1):235–242, 01 2000. ISSN 0305-1048. doi: 10.1093/nar/28.1.235.

35. José Cruz, Marc-Frédérick Blanchet, Michal Boniecki, Janusz Bujnicki, Shi-Jie Chen, Song Cao, Rhiju Das, Feng Ding, Nikolay Dokholyan, Samuel Flores, Lili Huang, Christopher Lavender, Veronique Lisi, François Major, Katarzyna Mikolajczak, Dinshaw Patel, Anna Philips, Tomasz Puton, John Santalucia, and Eric Westhof. RNA-Puzzles: A CASP-like evaluation of RNA three-dimensional structure prediction. *RNA (New York, N.Y.)*, 18:610–25, 02 2012. doi: 10.1261/rna.031054.111.

36. José Almeida Cruz, Marc-Frédérick Blanchet, Michal Boniecki, Janusz M. Bujnicki, Shi-Jie Chen, Song Cao, Rhiju Das, Feng Ding, Nikolay V. Dokholyan, Samuel Coulbourn Flores, Lili Huang, Christopher A. Lavender, Véronique Lisi, François Major, Katarzyna Mikolajczak, Dinshaw J. Patel, Anna Philips, Tomasz Puton, John Santalucia, Fredrick Sijenyi, Thomas Hermann, Kristian Rother, Magdalena Rother, Alexander Serganov, Marcin Skorupski, Tomasz Soltysinski, Parin Sripakdeevong, Irina Tuszynska, Kevin M. Weeks, Christina Waldsich, Michael Wildauer, Neocles B. Leontis, and Eric Westhof. RNA-Puzzles: A CASP-like evaluation of RNA three-dimensional structure prediction. *RNA*, 18:610–625, 4 2012. ISSN 1355-8382. doi: 10.1261/rna.031054.111.

37. Zhichao Miao, Ryszard W Adamiak, Marc F Blanchet, Michal Boniecki, Janusz M Bujnicki, Shi-Jie Chen, Clarence Cheng, Grzegorz Chojnowski, Fang-Chieh Chou, Pablo Cordero, Jose Almeida Cruz, Adrian R Ferré-D'Amaré, Rhiju Das, Feng Ding, Nikolay V Dokholyan, Stanislaw Dunin-Horkawicz, Wipapat Kladwang, Andrey Krokhotin, Grzegorz Lach, Marcin Magnus, and et al. RNA-Puzzles Round II: assessment of RNA structure prediction programs applied to three large RNA structures. *RNA*, 21(6):1066–1084, 2015. doi: 10.1261/rna.049502.114.

38. Zhichao Miao, Ryszard W. Adamiak, Maciej Antczak, Robert T. Batey, Alexander J. Becka, Marcin Biesiada, Michał J. Boniecki, Janusz M. Bujnicki, Shi-Jie Chen, Clarence Yu Cheng, Fang-Chieh Chou, Adrian R. Ferré-D'Amaré, Rhiju Das, Wayne K. Dawson, Feng Ding, Nikolay V. Dokholyan, Stanisław Dunin-Horkawicz, Caleb Geniesse, Kalli Kappel, Wipapat Kladwang, Andrey Krokhotin, Grzegorz E. Łach, François Major, Thomas H. Mann, Marcin Magnus, Katarzyna Pachulska-Wieczorek, Dinshaw J. Patel, Joseph A. Piccirilli, Mariusz Popenda, Katarzyna J. Purzycka, Aiming Ren, Greggory M. Rice, John Santalucia, Joanna Sarzynska, Marta Szachniuk, Arpit Tandon, Jeremiah J. Trausch, Siqi Tian, Jian Wang, Kevin M. Weeks, Benfeard Williams, Yi Xiao, Xiaojun Xu, Dong Zhang, Tomasz Zok, and Eric Westhof. RNA-Puzzles Round III: 3D RNA structure prediction of five riboswitches and one ribozyme. *RNA*, 23:655–672, 5 2017. ISSN 1355-8382. doi: 10.1261/rna.060368.116.

39. Zhichao Miao, Ryszard W. Adamiak, Maciej Antczak, Michał J. Boniecki, Janusz Bujnicki, Shi-Jie Chen, Clarence Yu Cheng, Yi Cheng, Fang-Chieh Chou, Rhiju Das, Nikolay V. Dokholyan, Feng Ding, Caleb Geniesse, Yangwei Jiang, Astha Joshi, Andrey Krokhotin, Marcin Magnus, Olivier Mailhot, Francois Major, Thomas H. Mann, Paweł Piątkowski, Radoslaw Pluta, Mariusz Popenda, Joanna Sarzynska, Lizhen Sun, Marta Szachniuk, Siqi Tian, Jian Wang, Jun Wang, Andrew M. Watkins, Jakub Wiedemann, Yi Xiao, Xiaojun Xu, Joseph D. Yesselman, Dong Zhang, Yi Zhang, Zhenzhen Zhang, Chenhan Zhao, Peinan Zhao, Yuanzhe Zhou, Tomasz Zok, Adriana Żyła, Aiming Ren, Robert T. Batey, Barbara L. Golden, Lin Huang, David M. Lilley, Yijin Liu, Dinshaw J. Patel, and Eric Westhof. RNA-Puzzles Round IV: 3D structure predictions of four ribozymes and two aptamers. *RNA*, 26: 982–995, 8 2020. ISSN 1355-8382. doi: 10.1261/rna.075341.120.

40. Louis Becquey, Eric Angel, and Fariza Tahi. RNANet: An Automatically Built Dual-Source Dataset Integrating Homologous Sequences and RNA Structures. *Bioinformatics*, 37(9): 1218–1224, 2021. doi: 10.1093/bioinformatics/btaa944.

41. M. Szikszai, M. Magnus, S. Sanghi, S. Kadyan, N. Bouatta, and E. Rivas. RNA3DB: A structurally-dissimilar dataset split for training and benchmarking deep learning models for RNA structure prediction. *Journal of Molecular Biology*, March 2024. doi: 10.1016/j.jmb.2024.168552. Epub ahead of print.

42. B. Adamczyk, M. Antczak, and M. Szachniuk. RNAsolo: a repository of clean, experimentally determined RNA 3D structures. *Bioinformatics*, 38(14):3668–3670, 2022. doi: 10.1093/bioinformatics/btac386.

43. Ioanna Kalvari, Eric P. Nawrocki, Nancy Ontiveros-Palacios, Justyna Argasinska, Kevin Lamkiewicz, Manja Marz, Sam Griffiths-Jones, Claire Toffano-Nioche, Daniel Gautheret, Zasha Weinberg, Elena Rivas, Sean R. Eddy, Robert D. Finn, Alex Bateman, and Anton I. Petrov. Rfam 14: Expanded Coverage of Metagenomic, Viral and MicroRNA Families. *Nucleic Acids Research*, 2020. doi: 10.1093/nar/gkaa1047.

44. Xiao-Wei Qiang, Chen Zhang, Hai-Long Dong, Fu-Jia Tian, Hang Fu, Ya-Jun Yang, Liang Dai, Xing-Hua Zhang, and Zhi-Jie Tan. Multivalent Cations Reverse the Twist-Stretch Cou-

pling of RNA. *Phys. Rev. Lett.*, 128:108103, Mar 2022. doi: 10.1103/PhysRevLett.128.108103.

45. Fei Liu and Zhong-can Ou-Yang. Monte Carlo Simulation for Single RNA Unfolding by Force. *Biophysical Journal*, 88(1):76–84, 2005. ISSN 0006-3495. doi: 10.1529/biophysj.104.049239.

46. Marc Parisien and François Major. The MC-Fold and MC-Sym pipeline infers RNA structure from sequence data. *Nature*, 452:51–55, 3 2008. ISSN 0028-0836. doi: 10.1038/nature06684.

47. J. Abramson, J. Adler, J. Dunger, et al. Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature*, 2024. doi: 10.1038/s41586-024-07487-w.

48. Clement Bernard, Guillaume Postic, Sahar Ghannay, and Fariza Tahi. RNAdvisor: a comprehensive benchmarking tool for the measure and prediction of RNA structural model quality. *bioRxiv*, page 567018, 11 2023. doi: 10.1101/2023.11.14.567018.

49. Sandro Bottaro, Francesco Di Palma, and Giovanni Bussi. The Role of Nucleobase Interactions in RNA Structure and Dynamics. *Nucleic acids research*, 42, 10 2014. doi: 10.1093/nar/gku972.

50. Yang Zhang and Jeffrey Skolnick. Scoring function for automated assessment of protein structure template quality. *Proteins*, 57(4):702—710, December 2004. ISSN 0887-3585. doi: 10.1002/prot.20264.

51. Sha Gong, Chengxin Zhang, and Yang Zhang. RNA-align: quick and accurate alignment of RNA 3D structures based on size-independent TM-scoreRNA. *Bioinformatics*, 35:4459–4461, 11 2019. ISSN 1367-4803. doi: 10.1093/bioinformatics/btz282.

52. Adam Zemla, Ceslovas Venclovas, John Moult, and Krzysztof Fidelis. Processing and analysis of CASP3 protein structure predictions. *Proteins: Structure, Function, and Bioinformatics*, 37(S3):22–29, 1999. doi: https://doi.org/10.1002/(SICI)1097-0134(1999)37:3+<22::AID-PROT5>3.0.CO;2-W.

53. Kliment Olechnovic, Eleonora Kulberkyte, and Ceslovas Venclovas. CAD-score: A new contact area difference-based function for evaluation of protein structural models. *Proteins*, 81, 01 2013. doi: 10.1002/prot.24172.

54. Valerio Mariani, Marco Biasini, Alessandro Barbato, and Torsten Schwede. lDDT: a local superposition-free score for comparing protein structures and models using distance difference tests. *Bioinformatics (Oxford, England)*, 29(21):2722–2728, 2013. doi: 10.1093/bioinformatics/btt473.

55. Christine Hajdin, Feng Ding, Nikolay Dokholyan, and Kevin Weeks. On the significance of an RNA tertiary structure prediction. *RNA (New York, N.Y.)*, 16:1340–9, 07 2010. doi: 10.1261/rna.1837410.

56. Marc Parisien, José Cruz, Eric Westhof, and François Major. New metrics for comparing and assessing discrepancies between RNA 3D structures and models. *RNA (New York, N.Y.)*, 15:1875–85, 09 2009. doi: 10.1261/rna.1700409.

57. Tomasz Zok, Mariusz Popenda, and Marta Szachniuk. MCQ4Structures to compute similarity of molecule structures. *Central European Journal of Operations Research*, 22, 04 2013. doi: 10.1007/s10100-013-0296-5.

58. Shuang Gong, Chao Zhang, and Yang Zhang. RNA-align: quick and accurate alignment of RNA 3D structures based on size-independent TM-scoreRNA. *Bioinformatics (Oxford, England)*, 35(21):4459–4461, 2019. doi: 10.1093/bioinformatics/btz282.

59. Chengxin Zhang, Morgan Shine, Anna Marie Pyle, and Yang Zhang. US-align: Universal Structure Alignment of Proteins, Nucleic Acids and Macromolecular Complexes. *Nature Methods*, 19:1109–1115, 2022.