Energy-based Modelling of Single Actin Filament Polymerisation Using Bond Graphs

Peter J. Gawthrop [ID] * [1], Michael Pan [ID][2,3,4], and Vijay Rajagopal [ID] † [1,5,6]

[1] Department of Biomedical Engineering, Faculty of Engineering & Information Technology, University of Melbourne, Victoria 3010, Australia.
[2] School of Mathematics and Statistics, Faculty of Science, University of Melbourne, Victoria 3010, Australia.
[3] Equine Centre, Melbourne Veterinary School, University of Melbourne, 250 Princes Hwy, Werribee VIC 3030, Australia.
[4] ARC Centre of Excellence for the Mathematical Analysis of Cellular Systems, University of Melbourne, Parkville VIC 3010, Australia.
[5] Baker Department of Cardiometabolic Health, Melbourne Medical School, Faculty of Medical and Health Sciences, University of Melbourne, Victoria, 3010, Australia.
[6] Graeme Clark Institute for Biomedical Engineering, The University of Melbourne, Victoria, 3010, Australia.

September 2, 2024

____

*Corresponding author. **peter.gawthrop@unimelb.edu.au**
†Joint corresponding author. **vijay.rajagopal@unimelb.edu.au**

Contents

Abstract

The energy-based bond graph approach to modelling biological systems is extended to include chemomechanical transduction using actin filament polymerisation and force generation as an exemplar. It is shown that the **TF** (transformer) bond graph component provides a practical, and conceptually simple, alternative to the Brownian ratchet approach of Peskin, Odell, Oster & Mogilner. Three cases are examined: rigid filament normal to a surface; rigid filament at an angle to a surface and a flexible filament. The latter two cases correspond to incremental additions to the bond graph of the first case. In the first case, the explicit formula derived from the bond graph is identical to that derived by the Brownian ratchet approach. Energy flows are fundamental life; for this reason, the energy based approach is utilised to investigate the power transmission by the actin filament and its corresponding efficiency.

The bond graph model is fitted to experimental data by adjusting model physical parameters.

1   Introduction

"Systems Biology explores how parts of biological entities function and interact to give rise to the behaviour of the system as a whole." [1]. This Systems Biology approach is being used as the conceptual basis of understanding living entities as a system with hierarchical interacting parts, including the molecular, organelle, cellular and organ levels, within the Physiome Project [2, 3]. This endeavour requires a conceptual framework which enables models of parts to be readily integrated to model systems in a modular fashion. The concept of *energy* provides a way of integrating parts in different physical domains such as chemical, electrical, protonic and mechanical; for this reason, the energy-based *Bond Graph* approach has been suggested as a conceptual framework [3, 4].

Bond graphs were introduced (in the context of modelling engineering systems) by Paynter [5, 6] to model *energy* transduction within and between different physical domains including electrical, mechanical and hydraulic; a number of introductory texts are available [7–9]. Bond graph models of chemical reaction networks were introduced in the seminal papers of Oster et al. [10, 11], and later extended within the context of Systems Biology [12–18]. Bond graph models connecting such chemical reaction networks to the electrical domain within the Systems Biology context have been developed [19–21]; in particular, redox reactions have been modelled [22]. A recent introduction and overview of the bond graph approach to systems biology is available [23] and a short introduction to bond graph modelling is given in the Supplementary Material.

However, using the Bond Graph approach to connect the chemical and mechanical domains within the Systems Biology context is an outstanding issue; the purpose of this paper is to resolve this issue using the modelling of an Actin Filament as an exemplar.

Actin filament mechanics and dynamics govern cell and tissue physiology throughout life. Actin dynamics and organisation play an integral role in the formation of tissues at cell-cell adhesions [24], play a central role in cell division and growth [25], contribute to cell stiffness [26] and interact with myosin to generate contractile forces in motile and muscle cells [27].

The growth and breakdown of actin filaments underlies actin dynamics. The rate of actin polymerisation is tightly regulated by an interconnected network of chemical reactions, and mechanical forces. In a seminal paper on actin-based cellular motility, Peskin et al. [28] introduce the concept of a *Brownian ratchet* to "present a mechanical picture of how polymerising filaments can exert mechanical forces". The mechanism provides a physical and thermodynamically consistent explanation of how the Gibbs free energy of actin polymerisation is converted into a mechanical pushing force at the leading edge. The Brownian ratchet approach has been embellished in a number of ways to provide a better fit to experimental data and remains at the core of current understanding of how actin polymerisation exert mechanical forces [29–31]. An elegant summary of the work of Peskin, Odell, Oster & Mogilner is given by Pollard [32] who highlights three key papers: [28] which introduces the concept of the Brownian ratchet in the context of a rigid actin filament touching a membrane at a right-angle to the membrane surface; [33] which extends the theory to flexible filaments touching the membrane at an arbitrary angle; and [34] which further extends the theory to include tethered filaments and capped filaments.

The concept of *energy transduction* as a basis for modelling the interface between chemistry and mechanics has a long history [35, 36]. In this study, we present a novel formulation of single actin filament polymerisation within the bond graph modelling framework. Moreover, the bond graph derived model of actin polymerisation is compared with the Brownian ratchet model. We illustrate that following a bond graph approach produces a force-velocity relationship identical in form to that of the Brownian ratchet although the bond graph model does not assume a Brownian ratchet mechanism.

The *transformer* **TF** is the bond graph component which provides the link between different physical domains; in the context of systems biology, the **TF** component has been used to link the chemical and electrical domains [19–22] and to represent stoichiometry [23]. This paper suggests that the **TF** component can be utilised in place of the Brownian ratchet as the link between the chemical and mechanical domains. In particular, the chemomechanical behaviour of a single actin filament is analysed using the bond graph **TF** approach and the corresponding force-velocity curve is derived for rigid and flexible filaments.

§ 2 considers the rigid case normal to the surface and the result is explicitly compared with the Brownian ratchet results of Peskin et al. [28]. § 3 considers the power transfer and efficiency of the energy transduction. § 4 extends the bond graph model to the non-normal case and § 5 further extends the model to the flexible case. § 6 examines how the convexity properties of the actin filament force-velocity curve vary with the compliance of the filament. Comparison with the experimental data of Li et al. [31] (corresponding to that of Bieling et al. [30]) is presented in § 7. A short introduction to bond graph modelling is given in the Supplementary Material.

The Python/Jupyter notebook used to generate the Figures is available at: https://github.com/gawthrop/ActinRod24.

(a) Conceptual

(b) Bond graph model

Figure 1: Bond Graph model – rigid filament normal to surface.

(a) The chemical reaction A $\rightleftharpoons$ B describes the biochemistry of the growing actin filament. The reaction rate v $(\mathrm{mol\,s^{-1}})$ also provides the energy flow $(\mathrm{J\,s^{-1}})$ from the chemical to the mechanical domain – chemomechanical transduction. In this section, the actin filament is normal to the membrane. The velocity of the actin tip touching the membrane V $(\mathrm{m\,s^{-1}})$ depends on the length and number of monomers added to the polymer per second and is proportional to reaction rate v: $V = mv$. The constant m has units of $\mathrm{m\,mol^{-1}}$ and is derived in § 2.1. The growth of the filament is resisted by a force F (N) .

(b) The bond graph is a precise representation of the energy flows implied by the conceptual diagram where $\rightharpoonup$ corresponds to mechanical or chemical energy flow $(\mathrm{J\,s^{-1}})$. The bond graph **TF**:m component represents the chemomechanical transduction with modulus m $(\mathrm{m\,mol^{-1}})$. Components **Ce**:A, **Ce**:B represent *chemical complexes* (mixtures of species) [15, 37] including ATP hydrolysis; **Ce**:A includes the Actin polymer with n units and the ATP-bound G-actin monomer; **Ce**:B includes the Actin polymer with $n + 1$ units. The bond graph component **Re**:r represents the chemical reaction. The *mechanical* spring **C**:F represents the force F (N) resisting the polymerisation of Actin and the corresponding tip velocity V $(\mathrm{m\,s^{-1}})$; this can be thought of as the mechanical equivalent of a chemical chemostat. The annotation in blue is purely explanatory and is not part of the bond graph.

2 Bond Graph model of actin chemomechanical transduction

In their seminal paper, Peskin et al. [28] consider a actin filament growing by polymerisation against a membrane. The basic parameters are: a polymerisation rate of α monomers s^{-1}, a depolymerisation rate of β monomers s^{-1}, a monomer length of δ m and a force acting on the barrier of F N. Using a Brownian ratchet approach, Peskin et al. [28] (equation 3) show that the tip velocity V $\mathrm{m\,s}^{-1}$ is given by

$$V = \delta \left(\alpha e^{-\omega} - \beta \right) \tag{2.1}$$

$$\text{where } \omega = \frac{F\delta}{k_B T} \tag{2.2}$$

k_B is the Boltzmann constant and T the absolute temperature. As indicated in Figure 1(a), there are two physical domains involved: the chemical domain represented by the conceptual chemical reaction $A \leftrightarrow B$ and the mechanical domain represented by a growing actin filament.

The left and right sides of the conceptual reaction can be regarded as chemical complexes[1] where complex A includes the Actin polymer with n units and the ATP-bound G-actin monomer; complex B includes the Actin polymer with $n + 1$ units. As is shown in § 2.2, complexes A and B are related to the α and β parameters of (2.1). The growth of the actin filament against the membrane can be viewed as *chemomechanical transduction* whereby chemical energy extracted from a conceptual chemical reaction is used to drive the extension of the filament with velocity V against the membrane force F.

This paper uses a bond graph approach to represent both physical domains together with the chemomechanical transduction. As discussed in the Introduction, the motivation is to be able to include actin dynamics as one component of a modular, energy-based model of a system containing actin filaments. Furthermore, the bond graph approach of this paper yields a simple derivation of (2.1).

Figure 1(b) shows the corresponding bond graph model. The two components **Ce**:A and **Ce**:B, together with the reaction component **Re**:r represent the conceptual chemical reaction where **Ce**:A and **Ce**:B represent the complexes A and B[2]. The **C**:F component represents the force exerted by the membrane on the filament. The bond graph **TF** component is the key to the transformation between physical domains in general and the chemical and mechanical domains in particular; this is considered in § 2.1. As discussed in the Supplementary Material, the

---

[1]The notion of a chemical complex as the combination of a number of chemical species arises from Chemical Reaction Network Theory [37]) and is discussed in the Supplementary Material.

[2]Bond graph representation of complexes [12, 23] is discussed in the Supplementary Material.

1 component ensures that the reaction flux v is transduced by the **TF** component whilst ensuring energy conservation by subtracting the transduced potential $\mu_F = mF$ from the chemical potential μ_A associated with complex A.

It is shown in § 2.2 that the bond graph approach yields an identical force/velocity equation to (2.1) as derived by the Brownian ratchet approach of Peskin et al. [28].

2.1 The **TF** component and modulus

The **TF** component[3] provides the interface between two different physical domains; in the context of systems biology, the **TF** component has been used to link the chemical and electrical domains [19–22]. The **TF** component is used here to link the chemical and mechanical domains. Although the chemical and mechanical domains differ and correspond to different physical units, each has the same notion of energy measured in Joules (J). The bond graph approach assigns two key variables to each domain: an effort e and a flow f which have the property that their product is power $p = ef$ $\mathrm{J\,s^{-1}}$. The chemical domain has chemical potential μ $\mathrm{J\,mol^{-1}}$ as effort and molar flow v $\mathrm{mol\,s^{-1}}$ as flow and the mechanical domain has force F N as effort and velocity V $\mathrm{m\,s^{-1}}$ as flow.

Because the **TF** component does not store or dissipate energy, it follows that both effort and flow are related by the same modulus m:

$$V = mv \tag{2.3}$$
$$\mu_F = mF \tag{2.4}$$

where μ_F is the chemical potential corresponding to the force F.

Equation (2.3) converts molar flow into mechanical velocity. As a mole of actin subunits contains N_A molecules where N_A $(\mathrm{mol^{-1}})$ is the Avogadro Constant, and assuming that the length of the Actin subunit is δ (m), it follows that the **TF** modulus m $(\mathrm{m\,mol^{-1}})$ is given by

$$m = N_A \delta \tag{2.5}$$

Because m appears in both equations (2.3) and (2.4) it follows that the modulus m derived from considering the flows can also be used to relate the chemical and mechanical efforts μ_F and F.

2.2 Comparison with the Brownian ratchet approach

From Figure 1, the net chemical potentials acting on the reaction component **Re**:r are $\mu_A - \mu_F$ and μ_B. Hence, the net reaction flow v is given the formula [12, 23]:

---

[3]See the Supplementary material for more details

$$v = \kappa \left(e^{\frac{\mu_A - \mu_F}{RT}} - e^{\frac{\mu_B}{RT}} \right) \tag{2.6}$$

$$= \kappa \left(e^{-\frac{\mu_F}{RT}} v_0^+ - v_0^- \right) \tag{2.7}$$

$$\text{where } v_0^+ = e^{\frac{\mu_A}{RT}} \tag{2.8}$$

$$\text{and } v_0^- = e^{\frac{\mu_B}{RT}} \tag{2.9}$$

κ is the reaction rate constant associated with the reaction component **Re**:r, μ_A and μ_B are the chemical potential associated with complexes A and B. RT (J mol^{-1}) is the product of the universal gas constant R $(\text{J K}^{-1} \text{mol}^{-1})$ and the absolute temperature T (K).

Using equations (2.3) – (2.5), the mechanical velocity is:

$$V = N_A \delta \kappa \left(e^{\frac{-N_a \delta F}{RT}} v_0^+ - v_0^- \right) \tag{2.10}$$

The Bond Graph derived equations (2.10) and the Brownian ratchet equation of Peskin et al. [28, (3)] (2.1) are identical if the following substitutions are made:

$$R = N_A k_B \tag{2.11}$$

$$\alpha = N_A \kappa v_0^+ \tag{2.12}$$

$$\beta = N_A \kappa v_0^- \tag{2.13}$$

Equation (2.11) is the standard formula for the Gas Constant R; Equation (2.12) represents the polymerisation rate in monomers s^{-1} and Equation (2.13) represents the depolymerisation rate in monomers s^{-1}.

Thus the formula (2.10) obtained by bond graph arguments and the formula (2.1) obtained by statistical mechanics arguments by Peskin et al. [28] are identical.

2.3 Force-velocity curve

Using the $\alpha - \beta$ notation, Equation (2.10) becomes:

$$V = \delta \left(e^{\frac{-mF}{RT}} \alpha - \beta \right) \tag{2.14}$$

Setting $F = 0$ in equation (2.14), the velocity V_0 corresponding to no membrane force is given by:

$$V_0 = \delta \left(\alpha - \beta \right) \tag{2.15}$$

Name	Sm.	Value	Unit	Reference
Polymerisation rate	α	113	s^{-1}	Peskin et al. [28], Fig. 1
Depolymerisation rate	β	1.6	s^{-1}	Peskin et al. [28], Fig. 1
Monomer length	δ	2.7	nm	Peskin et al. [28], Fig. 1
Polymer length	L	30	nm	Mogilner and Oster [33], Fig. 2
Persistence length	λ	1	μm	Mogilner and Oster [33], Tab. 1
Contact angle	θ_0	90-54=36	degree	[31], equation (8)

Table 1: Numerical values from the literature

(a) Normalised

(b) Not normalised

Figure 2: Force-velocity curve. Using the values from Table 1, $\gamma = 4.26$ and the transformer modulus $m = 1.63 \times 10^{15} \,\mathrm{m\,mol^{-1}}$. The curves labelled $\gamma = 4.26$ are plotted for the values given in Table 1. The other two curves are for $\frac{\alpha}{4}$ ($\gamma = 2.87$) and 4α ($\gamma = 5.64$). (a) Normalised curves from Equation (2.27). (b) Without normalisation. This alternative representation emphasises that increasing the chemical potential α of the complex represented by **Ce**:**A** of Figure 1, and thus γ and the reaction potential Φ_0, increases both the stall force F_0 and the zero-force velocity V_0.

Using the values from Table 1:

$$V_0 = 0.30\,\mu\mathrm{m\,s}^{-1} \tag{2.16}$$

This value is similar to $V_0 = 0.2\,\mu\mathrm{m\,s}^{-1}$ quoted by Pollard and Borisy [38].

When the filament is stalled, $V = 0$, and the corresponding stall force F_0 is given by:

$$e^{\frac{-mF_0}{RT}}\alpha = \beta \tag{2.17}$$

$$\text{hence } F_0 = \gamma\frac{RT}{m} \tag{2.18}$$

$$\text{where } \gamma = \ln\frac{\alpha}{\beta} \tag{2.19}$$

Using the values from Table 1:

$$F_0 = 6.75\,\mathrm{pN} \tag{2.20}$$

$$\text{and } \gamma = 4.26 \tag{2.21}$$

This value for F_0 is within the range $F_0 = 7.7 \pm 1.3\mathrm{pN}$ quoted by Abraham et al. [39, Table 2].

Moreover, using Equations (2.8),(2.9),(2.12),(2.13) and (2.19) the net reaction potential Φ_C is given as:

$$\Phi_c = \mu_A - \mu_B = RT\ln\frac{\alpha}{\beta} = RT\gamma \tag{2.22}$$

it follows that the stall force F_0 can also be written as:

$$F_0 = \frac{\Phi_C}{m} \tag{2.23}$$

The force-velocity curve of Equation (2.14) can be simplified by using the expressions for V_0 and F_0 (2.15) and (2.18). In particular, equation (2.14) can be rewritten by normalising velocity V by V_0 and force F by F_0 to give:

$$\bar{V} = \frac{e^{-\gamma\bar{F}}\alpha - \beta}{\alpha - \beta} \tag{2.24}$$

$$\text{where } \bar{F} = \frac{F}{F_0} \tag{2.25}$$

$$\text{and } \bar{V} = \frac{V}{V_0} \tag{2.26}$$

Equation (2.24) can be rewritten in terms of the single parameter γ (2.19) as:

$$\boxed{\bar{V} = \frac{e^{\gamma(1-\bar{F})} - 1}{e^{\gamma} - 1}} \tag{2.27}$$

Figure 2(a) shows the variation of normalised mechanical velocity V_0 with normalised mechanical force $0 \leq F_0 \leq 1$ for three values of γ; the curve for $\gamma = 4.26$ corresponds to Figure 1 of Peskin et al. [28]. Figure 2(b) plots the same data as Figure 2(a) but in non-normalised form; this emphasises that both F_0 and V_0 increase with γ.

3 Power and efficiency

The *efficiency* of living systems in general, and actin-based transduction in particular, is of great interest [30, 31, 40]. As the bond graph approach directly exhibits energy flow, it allows the power and the efficiency of the actin filament to be directly investigated.

The mechanical power P_{mech} (flowing though the **TF**) is:

$$P_{mech} = FV \tag{3.1}$$

This is, of course equal to that part of the chemical power flowing into the **TF** . The chemical power P_{chem} into the system from the two complexes represented by **Ce**:A and **Ce**:B is the product of the molar flow v and the chemical reaction potential Φ_c (2.22):

$$P_{chem} = v\Phi_c \tag{3.2}$$
$$= vRT\gamma$$

Using the values from § 2.3, P_{mech} and P_{chem} are plotted in Figure 3(a). There are many concepts of efficiency, one possibility is to define efficiency η as:

$$\eta = \frac{P_{mech}}{P_{chem}} \tag{3.3}$$

Using Equations (3.1), (3.2) and (2.23) is follows that efficiency η is proportional to normalised force:

$$\eta = \frac{FV}{v\Phi_c} = \frac{Fmv}{vmF_0} = \frac{F}{F_0} \tag{3.4}$$

This is plotted in Figure 3(b). As expected, the efficiency is at its highest value when the system is in equilibrium: $\bar{F} = 1$ and $\bar{V} = 0$ and no energy is dissipated in the **Re** component. On the other hand, the highest power transfer occurs at $\eta \approx 20\%$; such is the tradeoff between power transfer and efficiency.

Figure 3: Power and Efficiency. (a) Using the values from Table 1 the normalised (by $P_0 = F_0 V_0 = 2.03 \, \text{aW}$) chemical power and mechanical power are plotted against normalised (by $F_0 = 6.75 \, \text{pN}$) force. The chemical power reduces as force increases; the mechanical power (PV) is zero at two points: when the force $F = 0$ and the velocity $V = 0$ (corresponding to the stall force F_0). The difference between the two powers is dissipated in the reaction component **Re**:r. (b) The *efficiency* η (3.3) is plotted against normalised force $\bar{F} = F/F_0$; as indicated in Equation (3.4), the efficiency is equal to the normalised force. The efficiency is at its highest value when the system is in equilibrium: $V = 0$ and no energy is dissipated in the **Re** component. On the other hand, the highest power transfer occurs at $\eta \approx 20\%$; such is the tradeoff between power transfer and efficiency. (c) and (d). As (a) and (b) but plotted against normalised (by $V_0 = 0.30 \, \mu\text{m}$) velocity.

4 Rigid filament not normal to surface

(a) Conceptual

(b) Bond graph model

Figure 4: Bond Graph model – rigid filament at angle $\theta \neq 0$ with normal to surface. (a) This is identical to Figure 1(a) except that the growing filament is at an angle of θrad to the membrane normal. As discussed in the text, the filament force F and velocity V are now different to the membrane force F_m and velocity V_m. (b) This is identical to Figure 1(b) except that the additional **TF** component **TF:c** is used to perform the geometric transformation between F,V and F_m,V_m imposed by the angle θ of Equations (4.1)& (4.2). It is assumed that the actin filament is in contact with a smooth surface and therefore produces no force parallel to the surface.

Mogilner and Oster [33] added two innovations to the model of Peskin et al. [28]: the actin rod impinges on the membrane at an angle θ to the normal ($\theta = 0$ corresponds to normal to the membrane, $\theta = \frac{\pi}{2}$ corresponds to parallel to the membrane); and the actin filament is flexible rather than rigid. The former is treated in this section, the latter in § 5. As discussed by Pollard [32] this work implies the existence of an optimal angle for maximum membrane velocity; this aspect is also examined in the bond graph context.

The rigid filament at an angle is shown in Figure 4(a) and the corresponding bond graph of Figure 4(b) is now derived. The bond graph approach models complex systems by incrementally adding more components. In the mechanical domain, the standard bond graph approach to modelling a coordinate rotation is to use an angle-modulated transformer **TF** component [7–9, 41]. With reference to Figure 4, the transformer **TF:c** has a modulus $\cos(\theta)$ and transforms F and V in rod coordinates to F_m and V_m in membrane coordinates. In particular:

$$V_m = V \cos(\theta) \tag{4.1}$$

$$F = F_m \cos(\theta) \tag{4.2}$$

(a) Angle-velocity (vary force)

(b) Force-velocity (vary angle)

(c) Optimum angle

(d) Effective stall force

Figure 5: Non-normal angle: $\theta \neq 0$: properties. (a) The normalised membrane velocity $\bar{V}_m = V_m/V_0$ is plotted against incidence angle θ for various values of the normalised membrane force $\bar{F}_m = \frac{F_m}{F_0}$. The optimal incidence angle for each value of force is marked. (b) The normalised membrane velocity $\bar{V}_m = V_m/V_0$ is plotted against normalised membrane force $\bar{F}_m = \frac{F_m}{F_0}$ for various values of the incidence angle θ. (c) The optimal incidence angle θ_{opt} is a function of membrane force F_m. (d) The effective stall force F_θ is a function of incidence angle θ.

Substituting Equations (4.1) and (4.2) into Equation (2.27) gives the formula giving normalised membrane velocity $\bar{V}_m$ in terms of normalised membrane force $\bar{F}_m$ with the parameters γ and θ:

$$\boxed{\bar{V}_m = \cos\theta \frac{e^{\gamma(1-\bar{F}_m\cos\theta)} - 1}{e^\gamma - 1}} \tag{4.3}$$

where

$$\bar{F}_m = \frac{F_m}{F_0} \tag{4.4}$$

$$\bar{V}_m = \frac{V_m}{V_0} \tag{4.5}$$

Using the same parameters as for Figure 2, and plotting normalised membrane velocity V_m against θ for a range of values of force F_m gives the curves of Figure 5(a); the vertical lines locate the optimal angle (giving the maximum membrane velocity) for each value of force. The optimum value of θ plotted against force is given in Figure 5(c). Note that it is possible to get forward membrane velocity for force greater than the zero stall force F_0 for $\theta > 0$. Indeed, the effective stall force is $F_0/\cos\theta$; this is plotted in Figure 5(d).

5 Flexible filament not normal to surface

If the actin filament is flexible, it will bend if a torque τ is applied; this could be analysed using standard beam theory [42]; but, as a first approximation, the flexible beam is replaced by a rigid beam of length L connected to the base by a rotational spring with compliance σ radians/Nm and angle of rotation ϵ. Figure 6(a) shows where the tip impinges on the membrane. The angle between the membrane and fixed base is θ_0 and so the angle θ between filament and membrane normal is given by:

$$\theta = \epsilon + \theta_0 \tag{5.1}$$

Substituting for θ in Equation (4.3) gives:

$$\boxed{\bar{V}_m = \cos(\theta_0 + \epsilon) \frac{e^{\gamma(1-\bar{F}_m\cos(\theta_0+\epsilon))} - 1}{e^\gamma - 1}} \tag{5.2}$$

ϵ can be computed as follows. Using the equations for a linear simple spring with compliance σ:

$$\epsilon = \sigma\tau \tag{5.3}$$

$$\text{where the torque } \tau = F_m L \sin\theta \tag{5.4}$$

Combining Equations (5.1) – (5.4):

$$\epsilon = F_m \sigma L \sin(\theta_0 + \epsilon) \tag{5.5}$$

$$= F_m \sigma L (\sin\theta_0 \cos\epsilon + \cos\theta_0 \sin\epsilon) \tag{5.6}$$

(a) Conceptual   (b) Bond graph model

Figure 6: Bond Graph model – flexible filament. (a) This is identical to Figure 4(a) except that only the growing tip is shown, the growing filament is assumed to be flexible and the flexibility approximated by a spring with compliance σ $(\mathrm{N\,m\,rad^{-1}})$ at an angle of ϵ (rad) to the base normal. The membrane is tilted by an angle θ_0 and the angle between filament and membrane normal is $\theta = \theta_0 + \epsilon$. (b) This is identical to Figure 4(b) except that the **TF** component **TF**:c is replaced by a *modulated* transformer **MTF**:c modulated by the flexibility angle ϵ as generated by Equation (5.10) from the membrane force F_m. The **0** junction ensures that the effort (force F) on the three impinging bonds is identical.

(a) Angle-velocity (vary force)

(b) Force-velocity (vary angle)

(c) Optimum angle

(d) Force-velocity (vary flexibility)

Figure 7: Flexible filament. (a) Force/velocity diagram for various values of angle θ_0 and $\chi = 0.47$ (see § 5.1, Equation (5.17)). (b) Force/velocity diagram for various values of normalised compliance χ and $\theta_0 = 60°$. (c) The optimum (maximum velocity) values of θ are plotted for the flexible ($\chi = 0.47$) and rigid ($\chi = 0$) cases. (d) The velocity force diagram for the flexible filament; this should be compared to the rigid filament result of Figure 5(a).

Hence

$$\epsilon = \bar{F}_m \chi \left(\sin \theta_0 \cos \epsilon + \cos \theta_0 \sin \epsilon \right) \tag{5.7}$$

$$\text{where the normalised compliance } \chi = \sigma L F_0 \tag{5.8}$$

and $\bar{F}_m$ is given by (4.4). Following Mogilner and Oster [33, Appendix B], it assumed that $\epsilon \ll \pi/2$ and thus Equation (5.7) becomes:

$$\epsilon \approx \bar{F}_m \chi \left(\sin \theta_0 + \cos \theta_0 \epsilon \right) \tag{5.9}$$

hence:

$$\boxed{\epsilon \approx \frac{\chi \bar{F}_m \sin \theta_0}{1 - \chi \bar{F}_m \cos \theta_0}} \tag{5.10}$$

The corresponding bond graph is given in Figure 6(b). The modulated transformer **MTF** [41] allows the **TF** component to be modulated by ϵ (5.1) generated from the membrane force F_m using Equation (5.10).

The velocity-force curve is given by Equations (4.3), (5.1) and (5.10). Figure 7 summarises solutions to these equations for $\chi = 0.47$ (see § 5.1, Equation (5.17)) which can be compared to the rigid case of § 4 and Figure 5(d).

5.1 Computation of filament normalised compliance χ

The formula (5.10) contains the normalised compliance χ a a parameter. This section computes the value of χ corresponding to the parameters listed in Table 1.

Mogilner and Oster [33] use the *persistence length* λ as a measure of filament stiffness where:

$$\lambda = \frac{B_s}{k_B T} \tag{5.11}$$

where B_s is the filament *bending stiffness* ($B_s = EI$ in beam theory), k_B is the Boltzmann constant and T the absolute temperature. Modelling the filament as an Euler cantilever beam of length L with a force F_T at the tip, the deflection δ is [42, § 21, Chapter 3]:

$$\delta = \frac{F_T L^3}{3 B_s} \tag{5.12}$$

Thus the deflection angle ϵ with respect to the root is:

$$\epsilon = \frac{\delta}{L} = \frac{F_T L^2}{3 B_s} \tag{5.13}$$

Noting that the torque $\tau = F_T L$, the equivalent compliance σ is given by:

$$\sigma = \frac{\epsilon}{T} = \frac{L}{3 B_s} \tag{5.14}$$

Using equation (5.11), the equivalent compliance σ becomes:

$$\sigma = \frac{1}{3k_B T} \frac{L}{\lambda} \tag{5.15}$$

hence, using equation (5.8):

$$\chi = \frac{L^2 F_0}{3k_B T \lambda} \tag{5.16}$$

Using the parameters from Table 1:

$$\chi = 0.47 \tag{5.17}$$

6 Curvature of the force-velocity curve

Figure 8: Curvature of the force-velocity curve. Figure 7(d) is replotted with a new range of values of normalised compliance χ. Moreover, the force is normalised by the critical force F_{crit} (6.1) instead of the stall force F_0 (2.18) to emphasise how the curvature varies with the normalised compliance χ. Although (from Figure 7(d)) the force-velocity curve is convex when the compliance is zero $\chi = 0$ part of the curve becomes concave as χ increases.

The force-velocity curves of Figure 2 are *convex* in the sense that the second derivative is positive. A number of authors [43–46] have shown that the effect of multiple filaments interacting with the properties of the membrane can lead to force velocity curves which are entirely or partially concave. This section shows that the effect of the filament compliance discussed in § 5 can lead to a similar effect.

Figure 7(d) shows force-velocity curves for varying compliance. Although when normalised compliance $\chi = 0$ the curve is convex, the curves for $\chi > 0$ become concave as force increases. Figure 8 examines this behaviour further.

Equation (5.10) exhibits a singularity at $\bar{F}_m = \bar{F}_{crit}$ where

$$\frac{F_{crit}}{F_0} = \bar{F}_{crit} = \frac{1}{\chi \cos \theta_0} \tag{6.1}$$

Figure 8 is identical to Figure 7(d) except that the force is normalised by F_{crit} rather than F_0 and it is plotted for a range of $\chi > 0$. Thus for small normalised compliance ($\chi = 0.2$) the curve is convex for small values of normalised force F_m/F_{crit}; the curve is entirely concave for large normalised compliance ($\chi = 10$).

7 Experimental comparison.

Figure 9: Experimental comparison of the formulae (5.2) & (5.10) with experimental data presented by Li et al. [31] based on results of Bieling et al. [30]. The data is extracted from the additional information in elife-73145-fig1-data1-v2.xlsx. The value of $\theta_0 = 36°$ is taken from Li et al. [31]. Using the rigid model (§ 4, dashed line), the parameter γ (2.19) (the chemical driving force) is estimated. The estimated value is $\gamma = 3.07$. Using the flexible model (§ 5, firm line), the two parameters are estimated: γ and the normalised compliance χ (5.8). The estimated values are $\gamma = 3.15$ and $\chi = 0.29$.

Li et al. [31, Fig. 1D] provide experimental values of actin growth velocity for various values of growth stress obtained from branched actin network impinging on a cantilever. As they point

out, force-feedback occurs in that the density of actin filaments increases with stress and this also appears in [31, Fig. 1D]. For the purposes of this paper, the behaviour of an average filament is obtained by normalising experimental pressure by the measured actin density[4].

This section fits the velocity-force curve for the flexible filament of § 5 given by Equations (5.2) & (5.10) to the normalised experimental data. There are 5 parameters: the angle θ_0, the chemical driving force encapsulated in γ (2.19), the normalised compliance χ (5.8), the stall force F_0 (2.18) and the unloaded velocity V_0 (2.15).

Li et al. [31] give the filament contact angle as $54°$. As the contact angle is relative to the surface (as opposed to the surface normal); this corresponds to $\theta_0 = 90 - 54 = 36°$. F_0 and V_0 were approximated by the maximum values of the normalised force and velocity respectively.

The remaining two parameters γ and χ were estimated by fitting the velocity-force curve for the flexible filament of § 5 given by Equations (5.2) & (5.10) to the normalised experimental data using the Python minimisation routine `scipy.optimize.minimize` using the default BFGS (Broyden–Fletcher–Goldfarb–Shanno) [47] method. This gives $\gamma = 3.15$ and $\chi = 0.29$; in comparison, the values of $\gamma = 4.26$ from Equation (2.21) and $\chi = 0.47$ from Equation (5.17) correspond to Table 1 and were used in Figure 7. The corresponding curve is plotted as the firm line in Figure 9 with the experimental points superimposed.

For comparison, the data was fitted with the rigid model ($\chi = 0$) by estimating the single parameter γ. This is shown as the dashed line in Figure 9. The deviation from experimental data is greater as normalised force increases; this corresponds to the greater effect of flexibility at larger forces. The deviation would increase still further for larger values of membrane force F_m.

8   Conclusion

A novel bond graph approach to the modelling of actin chemomechanical transduction has been presented and has been shown to give an identical formula to the Brownian ratchet approach presented in the seminal paper of Peskin et al. [28]. The fact that two apparently disparate approaches give the same result seems to be due to the fact that bond graphs for chemical systems are, like the Brownian ratchet, built on thermodynamic principles [10, 11]. It is of historical interest to note that Oster was involved in establishing the foundations of not only the energy-based chemical bond graph [10, 11] but also the Brownian ratchet [28, 33].

The approach in this paper is closely related to previous work [19, 21] on the bond graph representation of chemoelectrical transduction where the **TF** component is used to link chemical and electrical domains using a modulus $m = z\mathbf{F}$ where z is the number of electrical charges and $\mathbf{F}$ ($\mathrm{C\,mol^{-1}}$) the Faraday constant. Indeed, the stall force formula (2.18) relating the chemical and mechanical domains is analogous to Nernst's equation relating the chemical and electrical domains.

Although, as emphasised by Peskin et al. [28] and Pollard [32], energy-based approaches "provide no mechanistic explanation of how the free energy of polymerisation is actually trans-

---

[4]Interpolation and extrapolation using a quadratic curve fit was used to create values of actin density for the values of experimental pressure in the velocity dataset.

duced into directed mechanical force", the bond graph approach has the advantage that a model of an actin filament can be readily extended by adding additional components or modules. For example, it was shown in his paper that the basic model of actin chemomechanical transduction can be extended to non-normal incidence and flexible filaments by simply adding more components to the bond graph representation. More generally, the bond graph approach is inherently modular [13, 16, 17], and bond graph modules containing both basic bond graph components and modules can be constructed in a hierarchical fashion. In this context, future work will investigate encapsulating the bond graph of actin chemomechanical transduction as a bond graph module and using the modular bond graph approach to incrementally build models of more complex systems including networks of actin filaments, adhesion, capping, moving elastic membranes and actin recycling. The actin chemomechanical transduction is driven by ATP hydrolysis; this could be explicitly linked to bond graph models of metabolism. Using the approach of § 3, efficiency at the cellular level could then be investigated.

Understanding the flow of cellular energy is crucial to understanding life [40]; therefore energy-based bond graph modelling including the chemical, electrical and mechanical domains provides a route to this understanding.

9 Author Contributions

PJG prepared the numerical results and drafted the manuscript; PJG, MP and VR jointly developed the concepts, discussed the results and revised the manuscript. All authors approved the final version for publication.

10 Acknowledgements

PJG would like to thank the Faculty of Engineering and Information Technology, University of Melbourne, for its support via a Professorial Fellowship. The authors would like to thank the anonymous reviewers for their constructive comments which have enhanced the paper.

11 Data availability

The Python/Jupyter notebook used to generate the Figures is available at: `https://github.com/gawthrop/ActinRod24`.

References

[1] P. Kohl, E. J. Crampin, T. A. Quinn, and D. Noble. Systems biology: An approach. *Clin Pharmacol Ther*, 88:25–33, July 2010. ISSN 0009-9236. doi: 10.1038/clpt.2010.92.

[2] Peter J. Hunter and Thomas K. Borg. Integration from proteins to organs: the Physiome Project. *Nature Reviews Molecular Cell Biology*, 4(3):237–243, March 2003. ISSN 1471-0072. doi: 10.1038/nrm1054.

[3] Peter Hunter. The virtual physiological human: The physiome project aims to develop reproducible, multiscale models for clinical practice. *IEEE Pulse*, 7(4):36–42, July 2016. ISSN 2154-2287. doi: 10.1109/MPUL.2016.2563841.

[4] Vijay Rajagopal, Senthil Arumugam, Peter J. Hunter, Afshin Khadangi, Joshua Chung, and Michael Pan. The cell physiome: What do we need in a computational physiology framework for predicting single-cell biology? *Annual Review of Biomedical Data Science*, 5(1):341–366, 2022. doi: 10.1146/annurev-biodatasci-072018-021246. PMID: 35576556.

[5] H. M. Paynter. *Analysis and Design of Engineering Systems*. MIT Press, Cambridge, Mass., 1961.

[6] H.M. Paynter. An epistemic prehistory of bond graphs. In P.C. Breedveld and G. Dauphin-Tanguy, editors, *Bond Graphs for Engineers*, pages 3–17. North-Holland, Amsterdam, 1992.

[7] P. J. Gawthrop and L. P. S. Smith. *Metamodelling: Bond Graphs and Dynamic Systems*. Prentice Hall, Hemel Hempstead, Herts, England., 1996. ISBN 0-13-489824-9. doi: 10.5281/zenodo.6998395.

[8] Dean C Karnopp, Donald L Margolis, and Ronald C Rosenberg. *System Dynamics: Modeling, Simulation, and Control of Mechatronic Systems*. John Wiley & Sons, Hoboken, New Jersey, 5th edition, 2012. ISBN 978-0470889084.

[9] Peter J Gawthrop and Geraint P Bevan. Bond-graph modeling: A tutorial introduction for control engineers. *IEEE Control Systems Magazine*, 27(2):24–45, April 2007. doi: 10.1109/MCS.2007.338279.

[10] George Oster, Alan Perelson, and Aharon Katchalsky. Network thermodynamics. *Nature*, 234:393–399, December 1971. doi: 10.1038/234393a0.

[11] George F. Oster, Alan S. Perelson, and Aharon Katchalsky. Network thermodynamics: dynamic modelling of biophysical systems. *Quarterly Reviews of Biophysics*, 6(01):1–134, 1973. doi: 10.1017/S0033583500000081.

[12] Peter J. Gawthrop and Edmund J. Crampin. Energy-based analysis of biochemical cycles using bond graphs. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Science*, 470(2171):1–25, 2014. doi: 10.1098/rspa.2014.0459. Available at arXiv:1406.2447.

[13] P. J. Gawthrop and E. J. Crampin. Modular bond-graph modelling and analysis of biomolecular systems. *IET Systems Biology*, 10(5):187–201, October 2016. ISSN 1751-8849. doi: 10.1049/iet-syb.2015.0083. Available at arXiv:1511.06482.

[14] Peter J. Gawthrop and Edmund J. Crampin. Energy-based analysis of biomolecular pathways. *Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences*, 473(2202), 2017. ISSN 1364-5021. doi: 10.1098/rspa.2016.0825. Available at arXiv:1611.02332.

[15] P. Gawthrop and E. J. Crampin. Bond graph representation of chemical reaction networks. *IEEE Transactions on NanoBioscience*, 17(4):449–455, October 2018. ISSN 1536-1241. doi: 10.1109/TNB.2018.2876391. Available at arXiv:1809.00449.

[16] Michael Pan, Peter J. Gawthrop, Joseph Cursons, and Edmund J. Crampin. Modular assembly of dynamic models in systems biology. *PLOS Computational Biology*, 17(10): e1009513, Oct 2021. doi: 10.1371/journal.pcbi.1009513.

[17] Peter J. Gawthrop, Michael Pan, and Edmund J. Crampin. Modular dynamic biomolecular modelling with bond graphs: the unification of stoichiometry, thermodynamics, kinetics and data. *Journal of The Royal Society Interface*, 18(181):20210478, 2021. doi: 10.1098/rsif.2021.0478.

[18] Peter J. Gawthrop and Michael Pan. Energy-based advection modelling using bond graphs. *Journal of The Royal Society Interface*, 19(195):20220492, 2022. doi: 10.1098/rsif.2022.0492.

[19] P. J. Gawthrop, I. Siekmann, T. Kameneva, S. Saha, M. R. Ibbotson, and E. J. Crampin. Bond graph modelling of chemoelectrical energy transduction. *IET Systems Biology*, 11 (5):127–138, 2017. ISSN 1751-8849. doi: 10.1049/iet-syb.2017.0006. Available at arXiv:1512.00956.

[20] Michael Pan, Peter J. Gawthrop, Kenneth Tran, Joseph Cursons, and Edmund J. Crampin. A thermodynamic framework for modelling membrane transporters. *Journal of Theoretical Biology*, 481:10 – 23, 2019. ISSN 0022-5193. doi: 10.1016/j.jtbi.2018.09.034. Available at arXiv:1806.04341.

[21] Peter J. Gawthrop and Michael Pan. Network thermodynamical modeling of bioelectrical systems: A bond graph approach. *Bioelectricity*, 3(1):3–13, Mar 2021. ISSN 2576-3105. doi: 10.1089/bioe.2020.0042. Published Online: 18 Dec 2020.

[22] P. J. Gawthrop. Bond graph modeling of chemiosmotic biomolecular energy transduction. *IEEE Transactions on NanoBioscience*, 16(3):177–188, April 2017. ISSN 1536-1241. doi: 10.1109/TNB.2017.2674683. Available at arXiv:1611.04264.

[23] Peter J. Gawthrop and Michael Pan. Network thermodynamics of biological systems: A bond graph approach. *Mathematical Biosciences*, 352:108899, 2022. ISSN 0025-5564. doi: https://doi.org/10.1016/j.mbs.2022.108899.

[24] Qilin Yu, William R. Holmes, Jean P. Thiery, Rodney B. Luwor, and Vijay Rajagopal. Cortical tension initiates the positive feedback loop between cadherin and f-actin. *Biophysical Journal*, 121(4):596–606, Feb 2022. ISSN 0006-3495. doi: 10.1016/j.bpj.2022.01.006.

[25] Pekka Lappalainen, Tommi Kotila, Antoine Jégou, and Guillaume Romet-Lemonne. Biochemical and mechanical regulation of actin dynamics. *Nature Reviews Molecular Cell Biology*, 23(12):836–852, Dec 2022. ISSN 1471-0080. doi: 10.1038/s41580-022-00508-4.

[26] Vijay Rajagopal, William Holmes, and Peter Vee Sin Lee. Computational modeling of single-cell mechanics and cytoskeletal mechanobiology. *Wiley Interdisciplinary Reviews: Systems Biology and Medicine*, 39:e1407, November 2017. doi: https://doi.org/10.1002/wsbm.1407.

[27] Bruce Alberts, Alexander Johnson, Julian Lewis, David Morgan, Martin Raff, Keith Roberts, and Peter Walter. *Molecular Biology of the Cell*. Garland Science, Abingdon, UK, sixth edition, 2015.

[28] C.S. Peskin, G.M. Odell, and G.F. Oster. Cellular motions and thermal fluctuations: the Brownian ratchet. *Biophysical Journal*, 65(1):316–324, 1993. ISSN 0006-3495. doi: 10.1016/S0006-3495(93)81035-X.

[29] George Oster. Brownian ratchets: Darwin's motors. *Nature*, 417(6884):25–25, May 2002. ISSN 1476-4687. doi: 10.1038/417025a.

[30] Peter Bieling, Tai-De Li, Julian Weichsel, Ryan McGorty, Pamela Jreij, Bo Huang, Daniel A. Fletcher, and R. Dyche Mullins. Force feedback controls motor activity and mechanical properties of self-assembling branched actin networks. *Cell*, 164(1):115–127, Jan 2016. ISSN 0092-8674. doi: 10.1016/j.cell.2015.11.057.

[31] Tai-De Li, Peter Bieling, Julian Weichsel, R Dyche Mullins, and Daniel A Fletcher. The molecular mechanism of load adaptation by branched actin networks. *eLife*, 11:e73145, jun 2022. ISSN 2050-084X. doi: 10.7554/eLife.73145.

[32] Thomas D Pollard. Theory from the Oster laboratory leaps ahead of experiment in understanding actin-based cellular motility. *Biophysical Journal*, 111(8):1589–1592, Oct 2016. ISSN 0006-3495. doi: 10.1016/j.bpj.2016.08.044.

[33] Alex Mogilner and George Oster. Cell motility driven by actin polymerization. *Biophysical Journal*, 71(6):3030–3045, 1996. ISSN 0006-3495. doi: 10.1016/S0006-3495(96)79496-1.

[34] Alex Mogilner and George Oster. Force generation by actin polymerization II: The elastic ratchet and tethered filaments. *Biophysical Journal*, 84(3):1591–1605, 2003. ISSN 0006-3495. doi: 10.1016/S0006-3495(03)74969-8.

[35] I. Z. Steinberg, A. Oplatka, and A. Katchalsky. Mechanochemical engines. *Nature*, 210 (5036):568–571, May 1966. doi: 10.1038/210568a0.

[36] T L Hill and M W Kirschner. Subunit treadmilling of microtubules or actin in the presence of cellular barriers: possible conversion of chemical free energy into mechanical work. *Proceedings of the National Academy of Sciences*, 79(2):490–494, 1982. doi: 10.1073/pnas.79.2.490.

[37] Martin Feinberg. *Foundations of Chemical Reaction Network Theory*. Springer, 2019. ISBN 978-3-030-03857-1. doi: 10.1007/978-3-030-03858-8.

[38] Thomas D. Pollard and Gary G. Borisy. Cellular motility driven by assembly and disassembly of actin filaments. *Cell*, 112(4):453–465, Feb 2003. ISSN 0092-8674. doi: 10.1016/S0092-8674(03)00120-X.

[39] Vivek C. Abraham, Vijaykumar Krishnamurthi, D. Lansing Taylor, and Frederick Lanni. The actin-based nanomachine at the leading edge of migrating cells. *Biophysical Journal*, 77(3):1721–1732, Sep 1999. ISSN 0006-3495. doi: 10.1016/S0006-3495(99)77018-9.

[40] Nick Lane. How energy flow shapes cell evolution. *Current Biology*, 30(10):R471 – R476, 2020. ISSN 0960-9822. doi: 10.1016/j.cub.2020.03.055.

[41] D. C. Karnopp. Power-conserving transformations: Physical interpretations and applications using bond graphs. *J. Franklin Institute*, 288(3):175–201, 1969.

[42] S.P. Timoshenko and J. N. Goodier. *Theory of Elasticity*. McGraw-Hill, 1970.

[43] Jie Zhu and Alex Mogilner. Mesoscopic model of actin-based propulsion. *PLOS Computational Biology*, 8(11):1–12, 11 2012. doi: 10.1371/journal.pcbi.1002764.

[44] Deepak Kumar Hansda, Shamik Sen, and Ranjith Padinhateeri. Branching influences force-velocity curves and length fluctuations in actin networks. *Phys. Rev. E*, 90:062718, Dec 2014. doi: 10.1103/PhysRevE.90.062718.

[45] Raj Kumar Sadhu and Sakuntala Chatterjee. Actin filaments growing against a barrier with fluctuating shape. *Phys. Rev. E*, 93:062414, Jun 2016. doi: 10.1103/PhysRevE.93.062414.

[46] Raj Kumar Sadhu and Sakuntala Chatterjee. Actin filaments growing against an elastic membrane: Effect of membrane tension. *Phys. Rev. E*, 97:032408, Mar 2018. doi: 10.1103/PhysRevE.97.032408.

[47] R. Fletcher. *Practical Methods of Optimization. 2nd Edition*. Wiley, Chichester, 1987.

S1 A Short Introduction to Bond Graph Modelling

The purpose of this section is to provide the bond graph background necessary to understand the paper itself. More detail about general bond graph theory is to be found in references [7–9] and more detail about biochemical systems in references [12–18].

S1.1 Basic concepts

Bond Graph	Electrical	Mechanical	Chemical
Effort e	Voltage ϕ (V)	Force F (N)	Gibbs energy μ (J mol^{-1})
Flow f	Current I (A)	Velocity V (m s^{-1})	Molar flow v (mol s^{-1})
Quantity $q = \int^t f(\tau)d\tau$	Charge Q (C)	Displacement X (m)	Molar amount x (mol)

Table S1: Analogous variables. Systematic modelling, including the bond graph approach, uses the concept of analogous variables to bring together different physical domains. One such analogy is the effort/flow analogy displayed here: each row contains analogous variables, each column corresponds to a domain. In each case effort × flow = power. Gibbs energy is also referred to as *chemical potential*. Other physical domains such as magnetic and hydraulic can be represented in a similar fashion.

Bond graphs unify the modelling of energy within and across multiple physical domains using the concepts of *effort* (e) and *flow* (f) variables whose product is *power*. As indicated in Table S1, in the electrical domain the effort variable is voltage (electrical potential) ϕ with units of V and the flow variable is current i with units of A (or C s^{-1}) which have the product $P = \phi i$ with units of J s^{-1} or W. In the mechanical domain, the effort variable is Force F with units of N and the flow variable is velocity V with units of m s^{-1} have the product $P = FV$ with units of J s^{-1}. In the chemical domain, the effort variable is *chemical potential* μ with units of J/mol and the flow variable is reaction flow rate v with units of mol/sec; $P = \mu v$ also has units of J s^{-1}.

The bond graph **C** component is a generic potential energy *storage* component corresponding to a *capacitor* in the electrical domain, a *spring* in the mechanical domain and the accumulation of a chemical species in the chemical domain. The electrical capacitor generates voltage (electrical potential) ϕ according to the *linear* relationship: $\phi = Q/C$ where C is the capacitance in Farads (F) and Q the charge in Coulombs (C). Similarly, a linear mechanical spring generates force F according to the *linear* relationship: $F = K_s X$ where K_s is the spring constant (N m^{-1}) and X the displacement in metres.

In contrast, the chemical species generates chemical potential μJ mol^{-1} according to the *nonlinear* relationship:

$$\mu = RT \ln Kx \tag{S1.1}$$

where R is the universal gas constant with units of $\mathrm{J\,mol^{-1}\,K^{-1}}$, T absolute temperature with units of K, $x = q/q_0$ where q_0 is the reference quantity and and K a species-dependant constant which is dimensionless and depends on the reference quantity. Because of the special nonlinear relationship, the chemical version of the **C** component is given a special symbol: **Ce** .

The bond graph **R** component is a generic energy *dissipation* component corresponding to a *resistor* in the electrical domain and a damper in the mechanical domain. In the electrical domain, it generates current i according to the *linear* relationship: $i = \kappa \Delta\phi$ where κ is the conductance and $\Delta\phi$ is the net potential across the resistor. Similarly, a linear mechanical damper generates force F according to the *linear* relationship: $F = d\Delta V$ where d is the damper constant $(\mathrm{N\,m^{-1}\,s})$ and ΔV the relative velocity $(\mathrm{m\,s^{-1}})$ between the damper terminals.

The **R** component corresponds a chemical *reaction* in the chemical domain. Assuming mass-action kinetics it generates molar flow v according to the *nonlinear* relationship:

$$v = \kappa \left(\exp \frac{A^f}{RT} - \exp \frac{A^r}{RT} \right) \tag{S1.2}$$

where A^f (the *forward affinity*) and A^r (the *reverse affinity*) are the net chemical potentials (with units of $\mathrm{J\,mol^{-1}}$) of the reactants and products of the reaction respectively; κ is the reaction *rate constant* with units of $\mathrm{mol\,s^{-1}}$. Because this relationship treats the forward and reverse affinities differently, the reaction version of the **R** component is given a special symbol: **Re** .

It can be convenient to rewrite Equation (S1.2) as [12]:

$$v = \kappa \left(v_0^+ - v_0^- \right) \tag{S1.3}$$

$$\text{where } v_0^+ = \exp \frac{A^f}{RT} \tag{S1.4}$$

$$v_0^- = \exp \frac{A^r}{RT} \tag{S1.5}$$

The bond graph **I** component is a generic kinetic energy *storage* component corresponding to a *inductance* in the electrical domain, a *mass* in the mechanical domain - there is no analogue in the chemical domain. The **I** component is not used in the paper but appears in § S1.4.

Bond graphs represent the flow of energy between components by the bond symbol $\rightharpoonup$ where the direction of the harpoon corresponds to the direction of positive energy flow; this is a sign convention. The bonds connect components via *junctions* which transmit, but do not store or dissipate energy. There are two junctions: the **0** junction where all impinging bonds have the same *effort* and the **1** junction where all impinging bonds have the same *flow*. The expression for the flows associated with the **0** junction, and the efforts associated with the **1** junction, are determined by the energy conservation requirement. A further energy transmission component is the *transformer* (**TF**) component discussed in § S1.5.

S1.2   Example: an electrical system

Figure S1 illustrates bond graph modelling in the electrical domain. The four capacitors (A–D) and two resistors (r_1, r_2) are connected as in the schematic diagram of Figure 1(a). In bond

| (a) Schematic | (b) Bond Graph |

Figure S1: Modelling Electrical Systems. (a) Electrical schematic diagram. (b) Bond graph: $\Delta\phi_1 = \phi_A - \phi_B, \Delta\phi_2 = \phi_B - (\phi_C + \phi_D)$.

graph colon notation, the symbol before the colon indicates the component type and the symbol after the colon indicates the component name. Thus the bond graph of Figure 1(b) has four **C** components named A–D to represent the four capacitors and a two **R** components named r_1 & r_2 to represent the resistors. The **0** junctions impose a common potential on the attached bonds (parallel connection) The **1** junctions impose a common current (flow) on the attached bonds (series connection) Given the constitutive relations for the **C** and **R** component, the dynamical equations describing the system can be automatically generated from the bond graph of Figure 1(b).

S1.3 Example: a chemical system

Figure S2: Modelling Chemical Systems. $A \overset{r1}{\rightleftharpoons} B \overset{r2}{\rightleftharpoons} C + D$. $v_A = -v_1$, $v_B = v_1$,$v_C = v_D = v_2$.

Figure S2 illustrates bond graph modelling in the chemical domain; the corresponding reaction is $A \overset{r1}{\rightleftharpoons} B \overset{r2}{\rightleftharpoons} C + D$. In a similar manner to the electrical system of Figure S1, the bond

graph of Figure S2 has four **C** components named A–D to represent the four species and a two **Re** component named r1 and r2 to represent the two reactions. The bond graphs of the electrical and chemical system are similar; the major differences are the use of the **Ce** component in place of the **C** component and **Re** component to replace the **1** & **R** combinations of Figure 1(b). These differences are discussed in § S1.1.

The affinities (net potentials) are:

$$A_1^f = \mu_A \tag{S1.6}$$

$$A_1^r = \mu_B \tag{S1.7}$$

$$A_2^f = \mu_B \tag{S1.8}$$

$$A_2^r = \mu_C + \mu_D \tag{S1.9}$$

Using Equations (S1.1) & (S1.2):

$$v_1 = \kappa_1 \left(\exp \frac{A_1^f}{RT} - \exp \frac{A_1^r}{RT} \right) = \kappa_1 \left(K_A x_A - K_B x_B \right) \tag{S1.10}$$

$$v_2 = \kappa_2 \left(\exp \frac{A_2^f}{RT} - \exp \frac{A_2^r}{RT} \right) = \kappa_2 \left(K_B x_B - K_C K_D x_C x_D \right) \tag{S1.11}$$

S1.3.1 Complexes

Chemical Reaction Network Theory provides a means of representing a network of chemical reactions in terms of a (mathematical) graph [37]. A key to this is the notion of *complexes*. In the context of this simple introduction, complexes are exemplified by the reaction network of Figure S2: there are two reactions r_1 and r_2 and three complexes: A, B & C + D. In other words, the complexes are the species, or sum of species, appearing on one side or other of a reaction. In this case, the formulation of Equation (S1.3) is particularly useful as the definition of v_0^+ and v_0^- is not dependent on the the number of species in each complex but rather just the net affinities A^f and A^r.

Further details of the relationship between complexes and bond graphs are given by Gawthrop and Crampin [12] and by Gawthrop and Pan [23].

S1.4 Example: a mechanical system

Figure S3 illustrates bond graph modelling in the mechanical domain using the standard mass-spring-damper system of Figure 3(a). The bond graph of Figure 3(b) represents the mass, spring and damper by the **I** , **C** and **R** components described in § S1.1.

The **1** junctions impose a common velocity (flow) on the attached bonds; the **0** junction is not strictly necessary but could be used to attach further components or systems. Again, given the constitutive relations for the **I** , **C** and **R** components, the dynamical equations describing the system can be automatically generated from the bond graph of Figure 3(b).

(a) Schematic   (b) Bond Graph

Figure S3: Modelling Mechanical Systems. (a) Schematic diagram. The system comprises a mass, a spring and a damper attached to a rigid base. The three components share a common velocity $V_S = V_M = V_D = V$. (b) Bond graph. The junction structure ensures that the three velocities are equal, and that the three forces sum to zero: $F_S + F_M + F_D = 0$.

S1.5   Connecting systems: the **TF** component

The **TF** component transmits power without dissipation or storage. It has two main uses: modelling power transmission *within* a physical domain and modelling power transduction *between* domains. In the first case, for example, a mechanical lever can be modelled as the **TF** of Figure 4(a) and chemical stoichiometry can be modelled as the **TF** of Figure 4(b). In the second case, chemoelectrical transduction can be modelled as the **TF** of Figure 4(c) making use of Faraday's constant which converts molar flow $(\mathrm{mol\,s^{-1}})$ to electron flow $(\mathrm{C\,s^{-1}})$.

Figure 4(d) lies at the heart of the paper: molar flow $(\mathrm{mol\,s^{-1}})$ is converted to the filament tip velocity $(\mathrm{m\,s^{-1}})$.

$$\xrightarrow[\quad V \quad]{\quad mF \quad} \textbf{TF:m} \xrightarrow[\quad mV \quad]{\quad F \quad}$$

(a) Mechanical lever

$$\xrightarrow[\quad v \quad]{\quad m\mu \quad} \textbf{TF:m} \xrightarrow[\quad mv \quad]{\quad \mu \quad}$$

(b) Stoichiometry

$$\xrightarrow[\quad v \quad]{\quad \mu = mV \quad} \textbf{TF:m} \xrightarrow[\quad i = mv \quad]{\quad V \quad}$$

(c) Chemoelectrical transduction

$$\xrightarrow[\quad v \quad]{\quad \mu = mF \quad} \textbf{TF:m} \xrightarrow[\quad V = mv \quad]{\quad F \quad}$$

(d) Chemomechanical transduction

Figure S4: The **TF** component. In each case the power (product of effort and flow) at the two ports is the same. (a) Mechanical lever: the modulus m is the ratio of the velocities at each end of the lever [7, 8]. (b) Chemical stoichiometry: the modulus m is the ratio of the flows at the two ports; it is usually integer [23]. (c) Chemoelectrical transduction:the modulus m is Faraday's constant which has units $(\mathrm{C\,mol^{-1}})$ [19, 22]. (d) Chemomechanical transduction: the modulus m is derived in the paper for the case of an actin filament; it has units $(\mathrm{m\,mol^{-1}})$.