1 AEon: A global genetic ancestry estimation tool

2 Naomi M Warren[1] and Mark Pinese[1,2]

3 [1]Children's Cancer Institute, Lowy Cancer Research Centre, UNSW Sydney, Sydney, NSW,
4 Australia
5 [2]School of Clinical Medicine, UNSW Sydney, Sydney, NSW, Australia

7 Abstract

8 Background

Genetic ancestry is a major confounding factor in genetic association studies, and it is

essential to estimate and account for ancestry in genomic research. Despite this

importance, accurate ancestry information is difficult to obtain, and existing methods to

estimate ancestry are not designed for modern sequencing data. This methodological gap

hinders the integration of genetic ancestry information in modern research, and limits

progress in finding the genetic determinants of disease in diverse populations. To address

this gap we present AEon, a probabilistic model-based global ancestry estimation tool, ready

for use on modern genomic data.

17 Results

18 AEon predicts an individual's fractional ancestral population membership, accounting for

19 possible admixture. Unlike previous global ancestry estimation tools, AEon takes input

20 directly from a VCF/BCF, includes default training data based on the 26 reference

21 populations of the 1000 Genomes Project, and produces visualisation aids and diagnostics

22 to complement data output.

Conclusions

AEon's turnkey design significantly reduces the time taken to estimate ancestry from VCFs without compromising accuracy compared to ADMIXTURE analysis, with a 4.8-fold decrease in runtime for a file with 10,000 sites and 100 individuals. AEon is available at github.com/GenomicRisk/aeon.

Keywords

Genetic ancestry estimation, ancestry inference, WGS, admixture

Background

Genetic ancestry is a major confounding factor in genetic association studies. Current association studies are heavily biased toward European populations [1,2], limiting the application of study findings [1,2,3]. Variation in linkage disequilibrium structure between populations can disrupt linkage between causal and marker alleles [3,4], and polygenic or indirect biomarkers can be confounded by uncharacterised modifiers with enriched allele frequency in specific population groups [3,5,6]. It is therefore essential to estimate and account for genetic ancestry if we hope to translate genomic research into equitable clinical utility for ancestrally diverse populations.

Despite its critical importance for equitable genomic medicine, ancestry information is not routinely incorporated in genomic analyses. This gap exists primarily because accurate ancestry data is difficult to obtain. Self-reported ancestry is not always available, and is often conflated with ethno-cultural identity, making it an inconsistent indicator of genetic background [7]. Although ancestry can be estimated directly from an individual's genotype, and is independent of ethnic identity, such genotype-derived ancestry can be difficult to estimate in practice.

Computational methods have been developed to estimate genetic ancestry from genotype

data, but current tools suffer from significant practical limitations that hinder their adoption

in modern genomic workflows. Most existing tools either do not use the modern defacto

VCF input format (ADMIXTURE [8], iAdmix [9]), rely on external infrastructure (gnomAD's AE

tool on Hail [10], Rye [11]), require phased genotypes as input (FLARE [12], MOSAIC [13],

GNOMIX [14]), or employ difficult-to-obtain individual-level genotype data from population

reference individuals (LASER [15]). The SNVstory method [16] addresses several of these

limitations, but can only identify the major ancestral population in an individual, making it

unsuitable for admixed individuals – an increasingly common scenario in modern clinical

cohorts.

Genetic ancestry inference methods can be broadly categorized along two dimensions:

global versus local approaches, and supervised versus unsupervised methods. Global

methods model the entire genome as a homogeneous mixture of ancestral populations,

while local methods identify the ancestral origin of specific genomic segments. Supervised

methods estimate an individual's ancestry as a mixture of predefined reference populations,

whereas unsupervised approaches infer ancestral populations directly from the data. For

clinical genomics applications, global supervised approaches are ideal: they work efficiently

on unphased data (unlike local methods) and provide interpretable, consistent ancestry

estimates based on established reference populations (unlike unsupervised approaches).

Unfortunately, no existing tool provides user-friendly global supervised ancestry estimation

for modern sequencing data formats.

To address this gap, we have developed AEon, a probabilistic model-based tool for

supervised global ancestry estimation, ready for use on modern genomic

data. AEon predicts fractional population membership of input samples given allele

frequency data from known populations, accounting for possible admixture. It is simple to

install and run, implemented in Python, and utilises existing mature libraries to process

input and perform statistical modelling. AEon takes input directly from a VCF/BCF and

outputs estimates in CSV format, enabling easy integration with existing software and

pipelines. The tool also includes a default population reference file to provide turnkey

ancestry estimation with no further configuration. However, the option to modify or replace

this reference file is available should users wish to tailor the tool for their specific input data

and questions of interest.

AEon removes the barriers preventing genetic ancestry estimation from being widely

integrated into genome analysis pipelines, thereby enabling and accelerating ancestry-

informed genetic research. Here we present a high-level overview of AEon, describe its

performance and application to modern genomic sequencing data relative to the traditional

ADMIXTURE tool, and make the tool and its databases available for use.

Implementation

Approach

AEon estimates fractional population membership for individuals based on their genotype

calls and a population-specific allele frequency reference.

Briefly, AEon employs `pysam` to read input genotypes in VCF/BCF format, and converts

genotypes to dosages of pre-specified ancestry-informative alleles. These dosages are then

fit to a Gaussian mixture model by maximum likelihood using `pyro` [17], to yield a per-

individual population mixture estimate. This fit requires a reference table giving frequencies

of each allele in each population of interest. We supply a default table for GRCh38 across

the 1000 Genomes (G1K) Project populations, but AEon also supports user-supplied tables.

As output AEon produces per-individual population mixture estimates in CSV format.

Statistical Model

Following the ADMIXTURE approach [8], AEon models an individual as a mixture of

prespecified ancestral populations. Specifically, denote the count of non-reference alleles of

an individual at biallelic locus j as $G_j \in \{0, 1, 2\}$. Under the gene pool model, we suppose

each G_j is drawn independently from a categorical distribution with probabilities

$\left[(1 - r_j)^2, 2r_j(1 - r_j), r_j^2\right]$ for $G_j = [0, 1, 2]$, where r_j is the non-reference allele frequency

for the gene pool from which the individual was sampled. We model the gene pool

frequency for this individual r_j as a mixture of ancestral frequencies, $r_j = \sum_i f_{ij} p_i$ where

$p_i \in [0,1]$ is the fraction of ancestral population i contributing to this individual, and f_{ij} is

the non-reference allele frequency at locus j in ancestral population i, $\sum_i p_i = 1$. Given

prespecified f_{ij} and supplied individual G_j from genotyping, AEon estimates the full vector

of population memberships p by maximum likelihood.

Generating the Population Reference

AEon includes a default reference table of ancestry-informative allele frequencies from the

2,504 unrelated individuals in the G1K Project Phase 3 dataset [18], sampled from 26

populations grouped into 5 superpopulations. This table was based on a list of 133,872

alleles previously determined to be ancestry-informative markers across the 1000 Genomes

populations based on Hardy-Weinberg analysis [19]. The list was pruned to remove difficult

to sequence regions and closely-linked loci. We further filtered the list to remove alternate

alleles absent from GRCh38 and loci missing from the 1000 Genomes call set to yield a final

list of 128,097 alternate alleles. One sample from each of the 26 populations was set aside

to form a test set (Table S1), and the remaining samples in each population were used to

calculate allele frequencies at each locus to form the final reference table.

Testing on 1000 Genomes populations

Ancestry estimation with AEon was tested on WGS data from the 1000 Genomes Project

using the 26 samples set aside from the reference in the previous step. Genotype calls for

these 26 individuals were provided to AEon as an indexed BCF using default flags. To

evaluate the impact of number of loci on performance, AEon models were fit with either a

random subset of 1,000, 2,000, 5,000, 10,000, 20,000, 50,000 or 100,000 loci, or all 128,907

default reference loci from the reference allele frequency file. The estimated ancestry

fractions provided as output from these tests were then compared against the labelled

superpopulation assigned by the G1K database for each sample.

Testing on Simulated Admixed Individuals

Since all individuals from the G1K database are intended to be representative of specific

populations, we simulated admixture to test AEon's performance on individuals with genetic

ancestry from multiple population groups at different proportions. First, mixtures of CEPH

European Ancestry in Utah (CEU) and Sri Lankan Tamil in the UK (STU) were generated by

treating all loci as unlinked and randomly passing on one allele from each parent to the

simulated child. We chose this independent sampling strategy as loci used by AEon are

sparsely sampled to ensure they are likely unlinked. The simulated CEU50:STU50 individual

was then designated as a new 'parent' along with a Han Chinese South (CHS) individual to

generate 20 samples with CEU25:STU25:CHS50 mixed ancestry. The same number of

simulated individuals were produced with a mix of CEU12.5:STU12.5:CHS75 and

CEU37.5:STU37.5:CHS25 ancestry by combining the CEU25:STU25:CHS50 sample with either

a CEU50:STU50 or CHS100 sample respectively (Figure 1b). After preliminary testing we

found that estimated ancestry fractions were stable using at least 10,000 loci as markers;

therefore these simulated individuals were run through AEon using eight randomly sampled

subsets of 10,000 loci, and average predictions were calculated. Given that these individuals

did not belong to a single population group, their estimated ancestry fractions from each

trial were compared against the G1K labelled fractions using L2-distance between ancestry

fraction vectors.

Comparison to ADMIXTURE

Having validated AEon's results against the labelled populations, we also compared its

performance to the existing ancestry estimation tool ADMIXTURE, used in projection mode

(ADMIXTURE's supervised inference mode, selected with the -P command line flag).

First ADMIXTURE required an initial run on the reference set using --supervised mode

to generate a '.P' population reference file. To run ADMIXTURE on the test samples, a pre-

processing script that calls bcftools and plink was created to convert the initial BCF into

the required format (see Additional file 1), after which ancestry estimation for the test

samples was performed using ADMIXTURE's projection mode with the '.P' file generated

earlier from the reference set. Maximum memory usage, maximum CPU, and real time

spent were recorded for both the pre-processing step and the predictive projection-mode

ADMIXTURE run using the same selection of loci (between 1,000 and 100,000) as the AEon

trials. Tests were also conducted varying the number of samples in the input file, all with

10,000 loci. We compared these resource metrics between tools, as well as the per-sample

population mixtures predicted by each tool, on a MacBook Pro machine (Apple M2 Pro chip

with 10-core CPU (6 performance cores, 4 efficiency cores), 16GB memory). Note that the

time and memory required for the initial supervised run was not included in these

comparisons.

Extending to other reference populations

To establish AEon's performance when extending to new reference populations, we tested

its performance on Oceanian samples from the Human Genome Diversity Project [20]

(HGDP) and Simons Genome Diversity Project [21] (SGDP). The genotypes of 7 Papuan Sepik

(PAS), 7 Papuan Highlands (PAH) and 11 Bougainville (BOU) individuals were downloaded in

VCF format. 2 PAS, 2 PAH and 1 BOU individuals were reserved as test samples. The

remaining 5 PAS, 5 PAH and 10 BOU individuals were used to generate allele frequencies per

population using `bcftools`. To understand how reference sample size impacted the quality

of results, four new reference files were generated with increasing Oceanian input. The '5

OCE' reference was created by taking the default AEon G1K reference file and adding a new

'PAS' column, which contained the allele frequencies calculated from the 5 reference PAS

samples at AEon's 128,097 loci. The '10 OCE' reference took this new file and added an

additional 'BOU' column, where the allele frequencies for the BOU population were

calculated using only 5 of the reference BOU samples. PAH allele frequencies from 5

individuals were added in a new column to produce the '15 OCE' reference. Finally, the '20

OCE' reference was created by replacing the BOU column with allele frequences calculated

using all 10 reference BOU samples. The content of these allele frequency references,

testing the effect of including different numbers of Oceanian individuals in the reference

table, is summarised in Supplementary Table S2. The addition of new populations required

adding corresponding rows to the tabular 'population labels' file, which contains the

superpopulation assignment for each population. For each new reference file, AEon was run

on the 5 test samples at 10,000 loci, using the flags *-a new_reference_afs.txt --*

population_labels G1K_OCE_labels.txt.

Results

Existing global genetic ancestry estimation tools require significant hands-on time to apply

on modern sequencing data, limiting their uptake. AEon streamlines global ancestry

estimation by running directly from VCF files. This decreased complexity reduces analysis

burden and eliminates error-prone data conversion steps. Here we demonstrate that this

simplicity does not come at the expense of accuracy, and that AEon yields accurate ancestry

estimates in single-population and admixed samples, competitive with gold-standard global

approaches such as ADMXITURE.

AEon identifies the most significant superpopulation ancestry in an individual

We first evaluated AEon's ability to correctly infer the largest contributing ancestry in an

individual. We applied AEon to 26 held-out samples from the 1000 Genomes Project, and

measured the concordance between AEon's largest estimated ancestry fraction (EAF) and

the sample's labelled superpopulation.

AEon correctly identified the major contributing superpopulation in 25 out of 26 cases,

independent of the number of ancestry-informative loci supplied (Figure 1a). The remaining

sample, labelled in 1000 Genomes as Colombian (CLM), was assigned primarily European

superpopulation ancestry by Aeon, followed by the American superpopulation. While as few

as 1,000 loci could be used to assign the largest proportion of ancestry to the correct

superpopulation for most cases, this proportion and hence confidence in the prediction

increased when more loci were provided, with diminishing returns beyond 10,000 loci

(Figure 1a).

Figure 1. High accuracy of superpopulation composition can be achieved with sufficient loci, with

estimates reaching optimal accuracy from approximately 10,000 loci **(a)**. AEon predicts suitable

superpopulation ancestry fractions for admixed individuals **(c)**, the lineage of which is shown in **(b)**. EAFs

are nearly identical between ADMIXTURE and AEon, lying along the line y=x. Each point represents the

EAF assigned to a population for a given sample, with 26 points per sample **(d)**. AEon is able to

incorporate new population information, allowing samples from previously underrepresented

populations to be characterised **(e)**. Note that the colour legend for superpopulations is consistent across

all plots in this figure.

While the CLM sample was primarily assigned European ancestry at the superpopulation

level, its dominant ancestral component at the population level was CLM when 20,000 or

more loci were used for inference (Figure S1). AEon's prediction of a large fraction of

European ancestry in the CLM individual was consistent with the known admixed ancestral

composition in this group [22]. Given the potential for AEon to detect and quantify levels of

admixture, we then explicitly investigated AEon's ability to accurately estimate EAF in

individuals with defined admixture.

AEon accurately estimates ancestry of admixed individuals

To evaluate AEon's ability to estimate known admixture, we simulated offspring from

random pairings of individuals from the 1000 Genomes CEU, STU and CHS populations and

their offspring (figure 1b). This procedure generated offspring with three different

admixture patterns: 25% CEU + 25% STU + 50% CHS, 37.5% CEU + 37.5% STU + 25% CHS, or

12.5% CEU + 12.5% STU + 75% CHS. With only 10,000 loci as input, AEon accurately and

consistently predicted the known ancestral composition of these complex admixtures

(Figure 1c). These results establish AEon's ability to estimate ancestry composition in

admixed samples and supports the use of 10,000 loci for this application. To further

characterise AEon's performance, we compared its estimates and computational

performance to the gold-standard ADMIXTURE method.

AEon matches ADMIXTURE's accuracy, with enhanced performance

AEon ancestry estimates were equivalent to those from ADMIXTURE. Across the 26 held-out test samples from the 1000 Genomes Project, AEon and ADMIXTURE assigned nearly identical ancestry fractions to each population, with a mean difference of 0.00 and maximum difference of 0.027 for a single population when considering all 128,907 loci (Figure 1d).

Although AEon demonstrated equivalent accuracy to ADMIXTURE, it was more computationally efficient. AEon ancestry estimation was significantly faster than ADMIXTURE in wallclock time, both as a function of number of loci and the number of samples (Figure 2a,b). This was largely due to the costly format conversion step required for ADMIXTURE (Table S3), as well as AEon's more efficient utilisation of computational resources (Figures 2c,S2). The initial supervised ADMIXTURE run that was required to generate a reference file presented an additional one-off time cost, and was not included in these comparisons. Although AEon did require more system memory for its computation, it had superior memory scaling to ADMIXTURE, and the RAM requirements for either tool are unlikely to be limiting on modern hardware (Figure 2d). As AEon operates on samples serially, its RAM usage is effectively independent of cohort size.

Figure 2. Comparison between the resources used by AEon (orange) and ADMIXTURE (blue). AEon is

faster than ADMIXTURE, and its runtime scales better with increasing locus count **(a)** or sample count **(b)**.

AEon automatically makes use of available CPU regardless of loci count **(c)**. AEon's memory usage also

scales better with loci count **(d)**.

In summary, AEon simplifies the process of estimating ancestry, decreasing the time

required to perform analysis both in terms of wallclock time and analyst effort (Figure S3).

AEon's simplicity does not compromise accuracy, resulting in ancestry estimates that are of

the same quality as the current standard tool ADMIXTURE.

AEon readily extends to new populations with few reference individuals

AEon's underlying model relies on the data provided in its reference file, allowing the user

to interpret results within the context of predefined populations. However, this requires

that AEon's reference file contains information for all populations of interest. AEon is

designed to be extensible to accommodate new reference populations, and to demonstrate

this capability and its data requirements, we undertook a study examining AEon's ability to

quantify Oceanian ancestry.

As a baseline, we first evaluated AEon's behaviour when supplied test individuals of

Oceanian ancestry, a population group that is absent from AEon's default G1K reference

population file. As expected, applying AEon to Oceanian individuals using the default G1K

reference file led to inaccurate results, with Oceanian individuals assigned a mixture of

South Asian, East Asian, and African ancestry (Figure 1e, left bar group).

We then evaluated how rapidly AEon's ancestry estimates became accurate when it is

supplied increasing numbers of Oceanian individuals in its reference file. We generated

reference files that included varying numbers of individuals of Papuan Sepik (PAS), Papuan

Highlands (PAH), and Bougainville (BOU) ancestry, and tested AEon's performance on held-

out Oceanian samples. Inclusion of reference allele frequencies generated from only 5 PAS

samples resulted in an estimated Oceanian ancestry fraction of over 0.85 for the test PAS

samples, and a fraction above 0.8 and 0.5 for the PAH samples and BOU sample respectively

(figure 1e, 2nd bar group). This indicates that AEon is capable of accurately identifying

underrepresented ancestral populations with a minimal amount of reference data. Including

reference BOU allele frequencies significantly improved the fraction of Oceanian ancestry

assigned to the BOU sample and marginally improved the assigned Oceanian fraction for the

PAS and PAH samples (Figure 1e, 3rd bar group). Further improvement was observed with

the addition of more reference samples (Figure 1e, right two bar groups). We confirmed

that the inclusion of Oceanian populations in the reference file had minimal impact on the

assignment of ancestry fractions for G1K test samples (Figure S4).

This demonstrates that AEon can accurately identify population membership even when

given reference frequencies based on as few as five individuals, with negligible effect on

other populations. Importantly, inclusion of allele frequencies from other populations within

the same superpopulation also improved correct superpopulation assignment (Figure 1e, 2^{nd}

panel), indicating that even if a perfectly matched population reference is not available, a

reference based on an ancestrally similar group can be used to generate accurate ancestry

estimates using AEon.

Discussion

We have presented AEon, a tool to estimate global genetic ancestry from modern

sequencing data. AEon has been engineered for ease-of-use and flexibility, minimising data

handling overhead and the potential for errors. As an updated implementation of the

ADMIXTURE global ancestry model, AEon complements recent methods for ancestry

classification, and addresses the usability gap left by current ancestry mixture modelling

tools.

AEon's primary contribution is as an ancestry mixture modelling method that works natively

on modern genotype data formats. Classical methods for this modelling, such as

ADMIXTURE, were designed for genotyping microarray data. Such microarray data differ

significantly from modern genotyping-by-synthesis (GBS) in both file format and

interpretation, particularly with respect to the handling of ungenotyped loci and

homozygous reference loci [23]. Consequently, although it is possible to apply ADMIXTURE

and related methods to modern GBS data in VCF format, this comes with significant manual

(Figure S3) and computational overhead (Figure 2), leading to complex and error-prone

workflows. By working natively with VCF data, AEon circumvents these issues and provides a

highly performant, lightweight, and convenient framework to estimate ancestry from

genomic data.

A key advantage of AEon is its easy and flexible setup. AEon has straightforward single-step

execution, lightweight dependencies, and comes with a default ancestry reference table.

The inclusion of a reference ancestry table is a notable benefit of AEon, enabling new users

to generate accurate ancestry estimates for 1000 Genomes populations with minimal effort.

This simplicity of AEon does not come at the expense of flexibility, and AEon accepts custom

ancestry tables if required. Notably, we have shown that AEon provides accurate ancestry

estimates using as few as five individuals from a new reference population. To our

knowledge, this flexibility and data efficiency is unique, and supports the use of AEon to

estimate ancestry in undersampled populations. With our findings that results can be

significantly influenced by reference database mismatch (e.g. AMR admixture, Figures 1a,S1)

or incompleteness (figure 1e), this capability of AEon enables equitable genomics for

understudied human populations.

As a modern implementation of the classical ancestry mixture model, AEon complements

other new tools. For example, the SNVStory method, and the ancestry estimation module of

Hail [10], also aim to ascertain ancestry from modern GBS data. However, these methods

are designed as classification tools, which assign individuals to a single ancestry. For

populations with low admixture this is an appropriate methodology, however it is unsuitable

for characterising admixed individuals. AEon, like the classical ADMIXTURE and STRUCTURE

methods, natively fits ancestral mixtures and so naturally and accurately handles admixture,

which is commonly encountered in modern genomic cohorts.

While AEon represents a substantial improvement in usability and performance over current

approaches, it has two notable limitations. Firstly, as a supervised method, AEon can only

identify ancestry from populations represented in its reference database. Although we have

demonstrated that AEon can accurately infer ancestral composition from as few as five

population reference individuals, this need for a reference population is a crucial property

that must be considered when applying the method in practice. Secondly, as a global

ancestry estimation method, AEon cannot deduce the ancestral source of specific

haplotypes observed in an individual, which may be relevant to clinical interpretation of

genomic findings.

Conclusions

AEon accurately and rapidly estimates global genetic ancestry from WGS data, determining

the fractional ancestral populations contributing to an individual. Built on python to run

with a single command and including default reference data, it allows meaningful

information to be extracted from genotype data immediately upon installation, while also

being readily extensible to new reference populations.

Availability and requirements

Project name: AEon

Project home page: github.com/GenomicRisk/aeon

Operating systems: platform independent (can be installed from GitHub or docker images

can be accessed from https://hub.docker.com/r/naomiwren/aeon)

Programming language: Python (tested on Python 3.10)

Other requirements: Installation from the GitHub repository requires pip. Use of a virtual

environment (e.g. conda) is also recommended.

Licence: Apache-2.0 licence

List of abbreviations

AE – ancestry estimation

CPU – central processing unit

EAF – estimated ancestry fraction

GBS – genotyping-by-synthesis

G1K Project – 1000 Genomes Project

HGDP – Human Genome Diversity Project

SGDP – Simons Genome Diversity Project

For population name abbreviations, consult Supplementary Table 1.

Declarations

Ethics approval/consent to participate

367 Not applicable.

Consent for publication

369 Not applicable.

Availability of data and materials

The 1000 Genomes data analysed during the current study was downloaded from

https://ftp-

trace.ncbi.nlm.nih.gov/1000genomes/ftp/1000G_2504_high_coverage/working/20201028_

3202_raw_GT_with_annot/.

HGDP data was accessed from https://gnomad.broadinstitute.org/downloads#v3-hgdp-1kg.

SGDP data was accessed from the Seven Bridges Cancer Genomics Cloud at

https://cgc.sbgenomics.com/u/sevenbridges/simons-genome-diversity-project-sgdp.

Competing interests

379 The authors declare that they have no competing interests.

Funding

381 Mark Pinese was supported by NHMRC Investigator Grant APP1176265.

Authors' contributions

383 NMW wrote the software and wrote the manuscript. MP conceived the software and

384 contributed to the manuscript. All authors read and approved the manuscript.

Acknowledgements

386 Not applicable.

References

1. Popejoy AB, Fullerton SM. Genomics is failing on diversity. Nature. 2016;538:161–4.

2. Wong KHY, Ma W, Wei C-Y, Yeh E-C, Lin W-J, Wang EHF, et al. Towards a reference
genome that captures global genetic diversity. Nat Commun. 2020;11:5482.

3. Sirugo G, Williams SM, Tishkoff SA. The Missing Diversity in Human Genetic Studies. Cell.
2019;177:26–31.

4. Galinsky KJ, Reshef YA, Finucane HK, Loh P, Zaitlen N, Patterson NJ, et al. Estimating cross-
population genetic correlations of causal effect sizes. Genet Epidemiol. 2019;43:180–8.

5. Tahmasebi H, Trajcevski K, Higgins V, Adeli K. Influence of ethnicity on population
reference values for biochemical markers. Crit Rev Clin Lab Sci. 2018;55:359–75.

6. Martin AR, Kanai M, Kamatani Y, Okada Y, Neale BM, Daly MJ. Clinical use of current
polygenic risk scores may exacerbate health disparities. Nat Genet. 2019;51:584–91.

7. Bonham VL, Green ED, Pérez-Stable EJ. Examining How Race, Ethnicity, and Ancestry Data
Are Used in Biomedical Research. JAMA. 2018;320:1533.

8. Alexander DH, Novembre J, Lange K. Fast model-based estimation of ancestry in
unrelated individuals. Genome Res. 2009;19:1655–64.

9. Bansal V, Libiger O. Fast individual ancestry inference from DNA sequence data leveraging
allele frequencies for multiple populations. BMC Bioinformatics. 2015;16:4.

10. Karczewski KJ, Francioli LC, Tiao G, Cummings BB, Alföldi J, Wang Q, et al. The mutational
constraint spectrum quantified from variation in 141,456 humans. Nature. 2020;581:434–
43.

11. Conley AB, Rishishwar L, Ahmad M, Sharma S, Norris ET, Jordan IK, et al. Rye: genetic
ancestry inference at biobank scale. Nucleic Acids Res. 2023;51:e44–e44.

12. Browning SR, Waples RK, Browning BL. Fast, accurate local ancestry inference with
FLARE. Am J Hum Genet. 2023;110:326–35.

13. Salter-Townshend M, Myers S. Fine-Scale Inference of Ancestry Segments Without Prior
Knowledge of Admixing Groups. Genetics. 2019;212:869–89.

14. Hilmarsson H, Kumar AS, Rastogi R, Bustamante CD, Montserrat DM, Ioannidis AG. High
Resolution Ancestry Deconvolution for Next Generation Genomic Data. 2021.

15. Wang C, Zhan X, Bragg-Gresham J, Kang HM, Stambolian D, Chew EY, et al. Ancestry
estimation and control of population stratification for sequence-based association studies.
Nat Genet. 2014;46:409–15.

16. Bollas AE, Rajkovic A, Ceyhan D, Gaither JB, Mardis ER, White P. SNVstory: inferring
genetic ancestry from genome sequencing data. BMC Bioinformatics. 2024;25:76.

17. Bingham E, Chen JP, Jankowiak M, Obermeyer F, Pradhan N, Karaletsos T, et al. Pyro:
Deep Universal Probabilistic Programming. Journal of Machine Learning Research.
2019;20:1–6.

18. Byrska-Bishop M, Evani US, Zhao X, Basile AO, Abel HJ, Regier AA, et al. High-coverage
whole-genome sequencing of the expanded 1000 Genomes Project cohort including 602
trios. Cell. 2022;185:3426-3440.e19.

19. Pinese M, Lacaze P, Rath EM, Stone A, Brion M-J, Ameur A, et al. The Medical Genome
Reference Bank contains whole genome and phenotype data of 2570 healthy elderly. Nat
Commun. 2020;11:435.

20. Cavalli-Sforza LL. The Human Genome Diversity Project: past, present and future. Nat
Rev Genet. 2005;6:333–40.

21. Mallick S, Li H, Lipson M, Mathieson I, Gymrek M, Racimo F, et al. The Simons Genome
Diversity Project: 300 genomes from 142 diverse populations. Nature. 2016;538:201–6.

22. Gopalan S, Smith SP, Korunes K, Hamid I, Ramachandran S, Goldberg A. Human genetic
admixture through the lens of population genomics. Philosophical Transactions of the Royal
Society B: Biological Sciences. 2022;377.

23. Darrier B, Russell J, Milner SG, Hedley PE, Shaw PD, Macaulay M, et al. A Comparison of
Mainstream Genotyping Platforms for the Evaluation and Use of Barley Genetic Resources.
Front Plant Sci. 2019;10.

24. Salzano FM, Sans M. Interethnic admixture and the evolution of Latin American
populations. Genet Mol Biol. 2014;37:151–70.

Supplementary Data

Tables

445 **Table S1.** Selected test samples from the 1000 Genomes Project

Superpopulation	Population Code	Population Name	Sample ID
African	ACB	African Caribbean in Barbados	HG01879
	ASW	African Ancestry in South West USA	NA19625
	ESN	Esan in Nigeria	HG02922
	GWD	Gambian in Western Division - Mandinka	HG02461
	LWK	Luhya in Webuye, Kenya	NA19017
	MSL	Mende in Sierra Leone	HG03052
	YRI	Yoruba in Ibadan, Nigeria	NA18486
American	CLM	Colombian in Medellín, Colombia	HG01112

	MXL	Mexican Ancestry in Los Angeles CA, USA	NA19661
	PEL	Peruvian in Lima, Peru	HG01565
	PUR	Puerto Rican in Puerto Rico	HG00551
East Asian	CDX	Chinese Dai in Xishuangbanna, China	HG00759
	CHB	Han Chinese in Beijing, China	NA18525
	CHS	Han Chinese South	HG00403
	JPT	Japanese in Tokyo, Japan	NA18939
	KHV	Kinh in Ho Chi Minh City, Vietnam	HG01595
European	CEU	CEPH collection - Utah Residents with Northern and Western European Ancestry	NA06984
	FIN	Finnish in Finland	HG00171
	GBR	British from England and Scotland	HG00096
	IBS	Iberian Populations in Spain	HG01500
	TSI	Toscani in Italia	NA20502
South Asian	BEB	Bengali in Bangladesh	HG03006
	GIH	Gujerati Indians in Houston, Texas, USA	NA20845
	ITU	Indian Telugu in the UK	HG03713
	PJL	Punjabi in Lahore, Pakistan	HG01583
	STU	Sri Lankan Tamil in the UK	HG03642

447 **Table S2.** Composition of the reference files used to test performance for new and sparsely-
448 sampled populations.

Reference file	1000G individuals (no OCE)	OCE individuals		
		PAS	BOU	PAH

Original	2,478	0	0	0
"5 OCE"	2,478	5	0	0
"10 OCE"	2,478	5	5	0
"15 OCE"	2,478	5	5	5
"20 OCE"	2,478	5	10	5

451   **Table S3.** Real time for ADMIXTURE processing of a 30 sample file

# loci	Time (s)		
	Conversion step	Prediction step	Total
1,000	2.64	1.26	3.90
2,000	4.24	1.93	6.17
5,000	9.09	4.60	13.69
10,000	17.24	10.13	27.37
20,000	33.46	20.16	53.62
50,000	81.99	47.99	129.98
100,000	163.40	154.99	318.39
128,097	212.39	220.08	432.47

Figure S1. At 20,000 loci all samples apart from the CLM sample have the largest proportion of their ancestry assigned to the correct superpopulation (European: orange shades, American: blue shades). However, when viewed at the population level, the CLM sample is assigned a larger EAF to the CLM population than to any individual European population. We consider these proportions a reasonable estimate due to the historic movement of European peoples to this area [22,24]. The small proportion of ancestry assigned to American populations for the European test samples (CEU, GBR, IBS, TSI) likely reflects this admixed composition of American populations in the 1000 Genomes dataset used as a reference.

Average CPU usage per run across 10 trio VCFs   465

Figure S2. When run on files containing only three samples, ADMIXTURE was able to make use of the same amount of CPU as AEon with small number of loci.

475
Figure S3. Flow chart demonstrating the process required to run ADMIXTURE compared
with AEon.

Figure S4. The addition of OCE samples to the reference file does not significantly impact
the ancestry fractions assigned to samples from other populations.

Additional files

Additional file 1

The pre-processing script used to convert BCFs into the input format required by
ADMIXTURE is provided as *additional_file_1.sh*.