Hybrid spatial organization and magnitude-independent coding of linguistic information during sentence production

Adam M. Morgan[1*], Orrin Devinsky[2], Werner K. Doyle[1], Patricia Dugan[1], Daniel Friedman[1], Adeen Flinker[1,3]

[1*]Neurology Department, NYU Grossman School of Medicine, 550 1st Ave, New York, 10016, NY, USA.
[2]Neurosurgery Department, NYU Grossman School of Medicine, 550 1st Ave, New York, 10016, NY, USA.
[3]Biomedical Engineering Department, NYU Tandon School of Engineering, 6 MetroTech Center Ave, Brooklyn, 11201, NY, USA.

*Corresponding author(s). E-mail(s): adam.morgan@nyulangone.org;

Abstract

Humans are the only species with the ability to systematically combine words to convey an unbounded number of complex meanings. This process is guided by combinatorial processes thought to be unique to our species. Despite their centrality to human cognition, the neural mechanisms underlying these systems remain obscured by inherent limitations of non-invasive brain measures and a near total focus on comprehension paradigms. Here, we address these limitations with high-resolution neurosurgical recordings (electrocorticography) and a controlled sentence production experiment. We uncover distinct cortical networks encoding word-level and higher-order information. These networks exhibited a hybrid spatial organization: broadly distributed across traditional language areas, but with focal concentrations of sensitivity to semantic and structural contrasts in canonical language regions. In contrast to previous findings from comprehension studies, we find that these networks are largely non-overlapping, each processing information associated with one of three linguistic contrasts. Most strikingly, our data reveal an unexpected property of higher-order linguistic information: it is encoded independent of neural activity levels. These results show that activity magnitude and information content are dissociable, with important implications for studying the neurobiology of language.

Keywords: ECoG, language production, syntax, semantics, neural coding schemes

1 Introduction

Sentence production is the process by which the brain translates from thought to language. Despite its centrality in human cognition, daily life, and in a host of debilitating neurological disorders, it remains poorly characterized in the brain due to a number of critical gaps in the literature. For one, previous research has relied primarily on non-invasive neuroimaging and electrophysiology (e.g., fMRI, EEG, MEG), methods which make overt production very difficult to study given their susceptibility to motion and/or motor artifacts. Furthermore, these methods impose a trade-off between spatial and temporal resolution [1, 2], both of which are needed to study a dynamic, anatomically distributed system like language. Another (perhaps related) gap is that the neuroscience of language has nearly exclusively focused on either sentence comprehension or single-word production [3, 4], with only a handful of studies to date investigating the production of multi-word utterances [5–18].

One of the complexities of studying sentences is that, relative to single words, they involve higher-order constructs like combinatorial semantics and syntax. While these systems are rarely investigated with production, they have been extensively studied in the comprehension literature. However, far from elucidating, this body of work contains a number of discrepant findings, and significant disagreements persist regarding the basic facts. One such area of disagreement is localization: how these systems are spatially encoded. For semantic composition – the process of combining the meanings like "red" and "boat" into a single representation of a "red boat" – some research points toward a hub in left anterior temporal lobe [19–23], while other research points toward a broader network spanning left lateral cortex [7, 24, 25]. For syntax, there is similarly little clarity. Some research has traced syntax back to inferior frontal gyrus (IFG) [6, 26–35] with other work identifying posterior temporal areas [18, 26–33, 36–38], and other work still suggesting that it is broadly distributed rather than concentrated in any particular region(s) [34, 38–41]. Relatedly, there is significant disagreement regarding *selectivity*: the degree to which these systems overlap spatially, which may have important theoretical implications (see [41, 42] for discussion). While findings of syntax-selective regions are abundant in the literature [29–31, 38, 43–50], recent work using more targeted analytical techniques has reported extensive spatial overlap in these systems [38–41, 51–53], indicating that there may in fact be no areas of the brain that process syntax to the exclusion of words and/or meaning.

At least three factors have contributed to these discrepancies and disagreements. First, different studies define syntax differently, and may in fact be studying different phenomena. Despite often being treated as a monolith, syntax is in fact a complex system involving multiple types of representations (e.g., function words, hierarchical "tree" structures, word categories) and processes (e.g., agreement, sequencing, and binding) [30, 33, 54–56]. Some experimental designs target the depth of syntactic processing by manipulating the complexity of hierarchical structures [27, 34, 39], while

others have manipulated the presence or absence of syntactic structure [27, 51, 53, 57–63], targeting the system as a whole.

The second factor relates the difficulty of isolating a system of abstract representations. To experimentally activate abstract syntactic representations – e.g., a "rule" like *Sentence = Subject + Verb + Object* – one must use words, which often introduces confounds with properties like phonology and meaning, complicating interpretation [3, 54]. For instance, in what has become one of the most common paradigms in this area, sentences are compared to unstructured lists of words [27, 51, 53, 57–63]. The underlying assumption – a pervasive assumption that we will return to throughout this manuscript – is that elevated neural activity indicates information processing. For convenience, we will refer to this as the *Elevation-Processing Equivalence* assumption (or **EPE**). According to the EPE, a brain region that shows higher activity for sentences than lists is taken as processing information that is present in sentences but not lists. However, sentences and lists differ not only the presence of syntax and combinatorial semantics, but a number of other factors including depth of processing, ecological validity, prosody, and so on, making it difficult to uniquely attribute differences to any one particular construct. Another common approach is to vary particular syntactic structures while holding words [19, 37] and/or meaning [12, 64, 65] constant. For instance, active and passive sentences can be used to express the same meaning by arranging the same content words (e.g., Dracula, spray, chicken) in reverse orders (active: "Dracula sprayed the chicken"; passive: "The chicken was sprayed by Dracula"). This varies structure while holding constant meaning, lexical content, and sentence processing. However, comparing actives and passives comes with its own set of confounds: active and passive sentences differ in processing difficulty, and prosodic features, structural frequency, and the number and type of function words they involve (e.g., the passive *be* and *by*).

The final factor that contributes to discrepancies in the literature is the historical reliance on comprehension paradigms. Comprehension studies offer some clear benefits: they provide a high degree of experimental control, allowing the researcher to present a precise stimulus at a precise time. And to be sure, comprehension is a useful tool for studying language in general, as higher-order linguistic representations are shared across the two modalities [12, 66, 67]. However, relative to production, comprehension introduces a number of modality-specific complications. For one, it engages the language network to a lesser degree than production [13], rendering signal detection more difficult. Another (perhaps related) complication is that syntax is often ignored during comprehension in favor of less effortful strategies (e.g., context) [68–71]. In production, the act of successfully producing a grammatical sentence entails syntactic processing, mitigating such concerns. Finally, comprehension is an ongoing process of building and assessing candidate structures and meanings in response to a continually changing stream of input [29, 56, 72, 73] – a highly dynamic process that renders reasonable temporal granularity difficult to achieve, particularly when attempting to examine specific representations [12, 14, 37, 74]. In contrast, in production critical higher-order representations like the global structure and meaning of a sentence are selected by the time production begins and remain invariant over time,

providing a short, clearly defined time window – the *planning period* – during which to study these representations [7, 8, 13, 29, 73, 75, 76].

Here, we address these gaps with a controlled sentence production experiment and by sampling neural data directly from cortex in ten neurosurgical patients. Electrocorticography (ECoG), which is virtually immune to motor artifacts, provides simultaneously high spatial and temporal resolution, allowing us to precisely characterize neural activity across left lateral cortex during sentence production on a millisecond scale. Beyond just mapping activity, we aimed to characterize the spatiotemporal dynamics of higher-order linguistic processing. To avoid the types of confounds discussed above (and mitigate the risk of false positives associated with encoding models [77, 78]), we intersected two approaches to identifying such information: a sentence>list test and a active≠passive test. Together, the combination of ECoG, a controlled production paradigm, and two tests for higher-order linguistic processing afford unparalleled resolution.

2 Results

Ten neurosurgical patients with electrode coverage of left peri-Sylvian cortex (Fig. 1A) performed a sentence production task and two control tasks: list production and picture naming (Fig. 1B). During sentence production, patients overtly described cartoon vignettes depicting transitive actions (e.g., poke, scare, etc.) in response to a preceding question. Questions were manipulated to use either active ("Who poked whom?") or passive syntax ("Who was poked by whom?"), implicitly priming patients to respond with the same structure ("The chicken poked Dracula" or "Dracula was poked by the chicken") [79]. This manipulation held semantic and lexical content largely constant while varying syntactic structure and associated constructs like the number of function words, prosodic properties, and cognitive effort. During the list production control task, participants saw the same vignettes as in the sentence production trials, but preceded by an arrow indicating the direction in which participants should list the characters: left-to-right (e.g., "chicken Dracula") or right-to-left ("Dracula chicken"), mimicking the reverse order of nouns in active and passive sentences. We quantified neural activity as high gamma broadband activity ($70-150\,\mathrm{Hz}$), normalized (z-scored) to each trial's 200 ms pre-stimulus baseline, as this correlates with underlying spiking and BOLD signal [80, 81] and has been widely employed in the ECoG literature. Parallel analyses on beta-band activity, also associated with cognition [82, 83], appear in the supplemental information (see Supplemental Information A.2).

We began by comparing neural activity between sentence production and the list production control task, a contrast commonly used to isolate higher-order linguistic processing. We looked for differences specifically during the planning period – the time between the onset of the cartoon vignette and speech onset, when higher-order features of the sentence like syntax, event semantics, and prosody are planned [7, 8, 29, 73, 76, 84]. (In our stimuli, this is logically ensured by the fact that the first word of the sentence – the subject – depends on the choice of syntactic structure, making it impossible to begin speaking without a priori structure assignment.) This test identified 60 broadly distributed electrodes with significantly higher activity for

sentences ($p < .05$ for 100 ms, Wilcoxon rank sum test). Consistent with previous findings, sentences recruited higher activity than lists in the 200 to 400 ms post-stimulus window in posterior temporal areas and the inferior parietal lobule (IPL), and increasing in IFG and middle frontal gyrus (MFG) leading up to production (Fig. 1C). A region-of-interest (ROI) analysis (Fig. 1D) found four regions with significantly higher activity for sentences during the planning period: IFG, MFG, IPL, and middle temporal gyrus (MTG) ($p < .05$ for 100 ms, permutation test; see Methods Sec. 4.7) – all regions commonly associated with higher-order language processing [3, 33, 56].

While sentence>list tests are common, these behaviors differ in multiple processes [53, 57, 58, 60–62]. We therefore aimed to better isolate higher-order linguistic information by intersecting these results with those of another comparison: active vs. passive sentences, which differ in syntactic structure, number of words (the passive *be* and *by*), and the difficulty of grammatical encoding. Passive sentences had longer initiation latencies than actives (see Sec. 4.8), likely reflecting this difficulty. To remove these differences, we followed [85–87] and temporally warped the data, setting each trial's response time to the median for that task (see Supplementary Fig. S1). Such temporal warping has previously been shown to increase signal-to-noise ratio, a finding which we successfully replicated in the current dataset (Supplementary Fig. S3). Supplementary Fig. S2 shows the results of applying the same analyses from Fig. 1 to the warped data; the pattern of significant results remains unchanged. Figure 2A shows the sentence>list and active≠passive tests for three sample electrodes. Electrodes E1 and E2 showed patterns we expected to find based on previous work: E1 had significantly higher activity for sentences than lists (top plot; $p < .05$ for 100 ms, Wilcoxon rank sum test) and corresponding differences between active and passive syntax in the same time windows (bottom; $p < .05$ for 100 ms, Wilcoxon rank sum test). Electrode E2 also had significantly higher sentence activity ($p < .05$ for 100 ms, Wilcoxon rank sum task), but showed no syntax sensitivity, suggesting involvement in some other process that differs between sentences and lists such as combinatorial semantics.

However, the most prevalent pattern we observed among significant electrodes, exemplified by Electrodes E3 and E4, was unexpected. Despite no significant increase in sentence activity relative to lists, these electrodes showed significant differences between active and passive trials. These differences could in principle be due to any feature that differs between actives and passives, including syntactic structure, difficulty, utterance length, or prosody. However, all of these features are involved to a higher degree in sentences than lists, and we would therefore expect that they should all be processed in regions with higher activity during sentence than list production. The combination of sensitivity to syntactic frame without elevated sentence activity therefore seems to violate a common assumption in the field: that information processing corresponds to increased neural activity. Indeed, while 125 electrodes were identified by the active vs. passive, only 6 of these (fewer than 5%) were identified by comparing sentences to lists (Fig. 2B). Thus, whatever properties are isolated in the active/passive comparison are not well characterized by "increased neural activity."

In order to quantify and isolate sources of variance, we leveraged an analytical technique that combines Representational Similarity Analysis (RSA) and multiple regression (Fig. 2C; Methods Sec. 4.9) [88–91]. We modeled neural dissimilarity as a

Fig. 1 (A) Coverage across all 10 patients (1256 electrodes after exclusions, see Methods Sec. 4.2). (B) Experimental design: Participants completed three overt production tasks. During Sentence Production trials, they produced sentences to respond to preceding questions. Questions appeared with either active ("Who sprayed whom?") or passive syntax ("Who was sprayed by whom?"), implicitly priming patients to respond with active ("The chicken sprayed Dracula") or passive syntax ("Dracula was sprayed by the chicken"). During List Production, a control task, participants saw the same stimuli from the Sentence Production block, but preceded by an arrow indicating the direction in which to order the two characters. During Picture Naming, they produced single words. (C) Magnitude of difference in neural activity (Cohen's d) for all electrodes with a significant difference between sentences and lists, in 200 ms bins (p < .05, FDR-corrected across electrodes, Wilcoxon rank sum test). (D) Mean and standard error of high gamma activity for all three tasks, by region, locked to stimulus (i.e., picture) onset (left column) and production onset (right column). Pink bar at bottom indicates times when sentences had significantly greater activity than lists (p < .05 for at least 100 ms; one-tailed Wilcoxon rank sum test). Region abbreviations: inferior frontal gyrus (IFG), middle frontal gyrus (MFG), sensorimotor cortex (SMC), superior temporal gyrus (STG), middle temporal gyrus (MTG), inferior parietal lobule (IPL).

linear combination of event-semantic (GPT-2 sentence embeddings [92]), structural (active vs. passive), (sub)lexical (same vs. different sentence-initial word), and response

Fig. 2 (A) Four sample electrodes. Top: mean and standard error of high gamma activity by task. Pink bars denote where sentences were significantly higher than lists ($p < .05$ for 100 ms, Wilcoxon rank sum test). Bottom: mean and standard error of sentence trials split by sentence structure; bars denote significant differences between active vs. passive trials ($p < .05$ for 100 ms, Wilcoxon rank sum test). (B) 60 electrodes had significantly higher activity for sentences than lists ($p < .05$ for 100 ms, Wilcoxon rank sum test) and 125 electrodes had significant differences between active and passive trials ($p < .05$ for 100 ms, Wilcoxon rank sum test). Only 6 electrodes ($< 5\%$) had both. (C) RSA analysis pipeline: For each electrode at each time sample, we modeled the magnitude of differences in high gamma activity for each pair of sentence trials as a function of differences in structure (active/passive), event semantics, and (sub)lexical content. (D) *Representational Similarity Indices* (RSIs; derived from model coefficients) for the same four sample electrodes show sensitivity to the active/passive contrast in E1, E3, and E4 and event semantics in E2 (all $p < .05$ for 100 ms; one-tailed permutation tests). (E) Significant electrodes ($p < .05$ for 100 ms, permutation test) by RSA term. Most significant electrodes were selective for just one model term. (F-G) Two approaches to assessing the relationship between high gamma activity and RSIs for significant electrodes. In both, (sub)lexical processing was significantly correlated with the degree of neural activity, while no such evidence was found for either of the two higher-order terms. (F) Regressing activity over RSIs at the electrode- and RSI- specific time sample when RSIs peaked (structure: $p = .987$, semantics: $p = .248$, (sub)lexical: $p < .001$, linear regression). (G) Correlating across electrodes at each time sample (significant (sub)lexical RSI: $p < .05$ for 100 ms, Spearman correlation).

time dissimilarity. The (sub)lexical term accounts for variance associated with surface differences between active and passive sentences such as the presence of the word "by" – although these differences did not appear until the third or fourth word of the sentences (relatively late compared to the period prior to sentence onset, where we concentrated our analyses). Similarly, the structure term encompasses not only the syntactic structure of the utterance, but also the prosody, number of function words, and encoding difficulty. We also included response time as a covariate in the model to further account for potential differences in the frequency and/or difficulty of actives and passives. We derived *Representational Similarity Indices* (RSIs) from the model coefficients to approximate the amount of evidence for structure-related, event semantic, and (sub)lexical information in each electrode (shown for the four sample electrodes in Fig. 2D). The structure RSI accurately captured the presence of differences related to the structure of the sentence in E1, E3, and E4, and verified that E2's higher activity for sentences than lists corresponded to the presence of event semantics ($p < .05$ for 100 ms, permutation test, for all three tests). Across electrodes with any significant RSIs, the majority of electrodes processed only one of the three types of information (Fig. 2E), contradicting previous claims of a fully interwoven system [40, 51, 52].

The puzzling lack of correlation between degree of neural activity and sensitivity to the active/passive comparison observed in Electrodes E3 and E4 motivated us to further investigate this relationship. We performed a series of analyses comparing each RSI to high gamma. Note that while RSIs index differences in high gamma activity in an electrode, such differences do not require that the electrode exhibit a high overall degree of activity. This, however, is the general assumption, and predicts that RSIs should be positively correlated with the magnitude of high gamma activity. In two analyses we found no evidence that either event semantics or the various differences targeted in the active/passive comparison were related to neural activity in this way: not across electrodes at the time when each electrode's RSI reaches its maximum (Fig. 2F), nor across electrodes at each time sample (Fig. 2G). In contrast, (sub)lexical processing showed the expected result in both analyses: a positive relationship with degree of high gamma activity at the times when the (sub)lexical RSI peaked ($p < .001$, linear regression), as well as at each time sample ($p < .05$ for 100 ms, Spearman correlation). Thus, intriguingly, the independence from the magnitude of neural activity appears to correspond specifically to the two higher-order linguistic terms.

A traditional region-of-interest approach (Fig. 3A) showed above-chance concentrations of sensitivity to the active/passive contrast in IFG and MFG, event-semantics in MTG and IPL, and (sub)lexical information in SMC and STG ($p < .05$ for 100 ms, permutation test). However, none of these three types of information were limited to particular regions. Within-electrode testing (Fig. 3B) revealed that these terms were widely distributed across cortex (see also Supplementary Fig. S6 for the same tests on beta-band activity). Given that our findings were not confined to particular cortical hubs, we aimed to characterize these networks without imposing classical anatomical assumptions. We took a data-driven approach and used an unsupervised machine learning technique, Non-negative Matrix Factorization (NMF; see Methods 4.10), to

cluster electrodes according to prototypical patterns in the combined high gamma and RSI dataset (Fig. 3C). This identified five major networks of electrodes (Fig. 3D).

Fig. 3 (A) Mean and standard error of electrodes' RSIs by ROI. (B) Significant electrodes ($p < .05$ for 100 ms; one-tailed permutation test) for all three RSIs; color and size correspond to peak RSI value. (C) Non-negative Matrix Factorization (NMF), a matrix decomposition technique well-suited for identifying prototypical patterns, was used to cluster electrodes based on their concatenated high gamma activity (trial means for the three tasks) and RSIs. (D) Clusters. Top: electrode localizations; color and size correspond to NMF weight. Middle: weighted mean and standard error of high gamma for all three experimental tasks. Bottom: weighted mean and standard error of RSIs. Bars denote significance ($p < .001$ for 100 ms, permutation test).

The first three clusters were characterized by high information content (RSI) accompanied by very low high gamma activity (Clusters 1-3 in Fig. 3D), replicating the dissociation between structure-dependent information and neural activity that we observed at the electrode-level (Fig. 2B). Each of these three clusters was spatially distributed and contained above-chance levels of information for just one model term – event semantics, structure, or (sub)lexical information ($p < .05$ for 100 ms, permutation test). Temporally, these profiles aligned with theoretical and computational models of sentence production, according to which semantics is processed first, then syntax, and finally (sub)lexical representations [76, 84, 93] (see Fig. 3D, bottom).

In contrast, the last two clusters were characterized by robust high gamma activity and high regional specificity, despite the fact that our unsupervised approach did not have access to electrode locations. Cluster 4 was focused in areas associated with visual processing (occipital lobe) and attention (prefrontal cortex), with activity peaking just after stimulus onset, and it did not contain any above-chance linguistic information ($p > .05$, permutation test across all time points after correction for multiple comparisons). Cluster 5 was concentrated in regions associated with articulation (pre-central gyrus) and sensory feedback (post-central and superior temporal gyri), with activity peaking just after speech onset. It contained above-chance information only for the (sub)lexical RSI ($p < .05$ for 100 ms, permutation test) at the time when activity peaked, consistent with the correlation between (sub)lexical processing and neural activity (Figs. 2F,G).

3 Discussion

Here, we leveraged the high spatial and temporal resolution of ECoG to investigate the dynamics of sentence production. Adopting the Elevation-Processing Equivalence – the assumption that elevated activity indexes information processing – we performed a sentence>list test, a standard approach to separating (sub)lexical information from higher-order constructs like syntax and combinatorial semantics. This comparison identified a number of broadly distributed electrodes, but with focal concentrations in commonly identified regions: IFG, MFG, MTG, and IPL (Fig. 1C,D). An active≠passive test similarly identified a broadly distributed network, with focal concentrations in IFG and MFG. Given that both of these analyses were meant to identify higher-order linguistic information, we expected that identifying the electrodes significant for both should highlight higher-order language with particularly high precision, removing false positives and electrodes engaged in processes not targeted by both contrasts. Traditional region-of-interest (ROI) analyses appeared to validate this logic, identifying regions frequently associated with higher-order language like IFG and MFG. However, ECoG provides the spatial resolution to look at smaller patches of cortex – those covered by single electrodes. Among the electrodes that showed significant sensitivity to the active/passive contrast, fewer than 5% were also significant for the sentence>list test (Fig. 2B). On the hypothesis that this discrepancy might reflect the coarseness of these comparisons, both of which target a wide array of sentence-level language processes, we used an RSA-based approach to separate sources of variance in individual electrodes (Fig 2C–E). From the model results, we derived "Representational Similarity Indices" (RSIs), which characterize the degree of sensitivity to event-semantic information, (sub)lexical information, and remaining information sensitive to the active/passive distinction. In a traditional ROI-based approach, we found some regional specificity for each of the three RSIs, with MTG and IPL showing above-chance sensitivity to event semantics, IFG and MFG to the active/passive contrast, and SMC and STG to (sub)lexical information (Fig. 3B). However, as before, this only partially captured the distribution: there were significant electrodes for each of the three RSIs in every region we looked at. This suggests a hybrid organization

– networks that are broadly distributed, but with focal concentrations. To characterize these networks without imposing classical anatomical assumptions, we performed an unsupervised clustering analysis (NMF) on the joint pattern of neural activity (high gamma) and information processing (RSIs) (Fig. 3C), separating electrodes into five distinct networks (Fig. 3D). Two of these were characterized by peaks in neural activity and, despite the clustering algorithm not having access to electrodes' localizations, high spatial concentrations reflecting well-established regional-functional links: between visual processing and occipital lobe, attention and prefrontal cortex, articulation and motor cortex, and auditory feedback and STG. The remaining three clusters were defined functionally rather than by activity patterns: each uniquely encoded information related to one of the three RSIs. Intriguingly, these functional clusters recapitulated the finding of magnitude independence – originally shown at the electrode level (Fig. 2F & G) – at the network level, as, despite high information content, they were all characterized by overall low activity.

3.1 Magnitude-Independent Coding

A widespread assumption in the field holds that information processing corresponds to areas with elevated neural activity – what we have referred to as the EPE. However, we found that higher-order linguistic information was uncorrelated with the degree of neural activity measured. That is, while many electrodes showed differences in activity corresponding to higher-order linguistic distinctions, those differences did not systematically correspond to times when the overall degree of activity in the electrode was high. This "magnitude-independent coding" scheme may help account for the lack of overlap between electrodes identified by the sentence>list and active≠passive tests, as, of the two, only the sentence>list test relies on the EPE being true. If it is not, there would need to be considerable adjustments made to tests the field uses to target higher-order language.

The striking dissociation between the presence of higher-order linguistic information and degree of neural activity may not be so surprising in light of other findings. For instance, the well-established phenomenon of repetition suppression [94–97], whereby the amount of neural activity needed to process a particular representation decreases with repetition, necessitates a certain degree of independence between information processing and the overall degree of neural activity. Furthermore, multivariate analytical approaches (e.g., multivariate pattern analysis, or MVPA) are common tools in cognitive neuroscience precisely because of the increased sensitivity they offer for detecting relatively small differences in activity. However, a conceptual distinction that bears emphasis here is between overall low degree of activity and small differences in activity, the latter of which may still occur in sites with overall high levels of activity. We argue that what is relevant is not the small differences, but the fact that the cortical sites where differences occurred did not exhibit globally elevated activity.)

If higher-order linguistic information does involve a magnitude-independent code, it would require reassessing certain common assumptions about the relationship between information processing and degree of neural activity. It would also have important methodological implications: revealing a risk in relying on elevated activity as a test for the presence of information; cautioning against the common practice of a priori

excluding electrodes with low-activity responses [e.g., 77, 77, 92, 98–102]; and underscoring the importance of fine-grained analytical tools (e.g., RSA and MVPA). In terms of experimental design, an important consequence would be that sentence-list comparisons should be interpreted with caution, perhaps particularly in production. That is because the sentence>list test relies on the assumption that higher-order linguistic processing elevates neural activity. However, in our data this identified only a small fraction of electrodes sensitive to a structural manipulation, which should have homed in on many of the same cognitive constructs (Fig. 2B). The current experiment does not allow us to definitively determine which of the many differences between actives and passives (e.g., word count, difficulty, syntactic structure) drove significant effects in this comparison. However, the near total absence among the active≠passive electrodes of sentence>list electrodes indicates that in general, structure-dependent production processes like prosodic planning and grammatical encoding do not elevate activity more than list production.

As for why this might be the case, there are a number of possibilities. It may be related to the nature of production, in which case our findings would not necessarily contradict those of previous comprehension studies. One reasonable hypothesis is that list processing is fundamentally different between comprehension and production. Comprehension being more passive, it may be possible for participants to "turn off" costly higher-order processes such as attempting to identify a licit syntactic parse or extracting complex meaning from the input [51, 68, 69]. In production, on the other hand, lists may *elevate* activity with respect to sentences, as list production is more contrived and less practiced, potentially making it more difficult. If so, then it is to be expected that sentence>list comparisons would provide different results in comprehension and production. Another possibility is simply that, despite the prevalence of the sentence>list test in the literature, list comprehension may not control for syntax as intended. Previous research shows that single words engage syntactic processing [103–105] and that comprehending apparently ungrammatical sequences of words triggers syntactic analysis [106–108]. Both of these findings suggest that list comprehension might also engage syntax. Moreover, the subjective ability to recognize a list is not a sentence seems to logically entail syntactic processing. Given this, it may even be reasonable to hypothesize that lists engage syntax *more* than sentences, as the comprehension system struggles to identify a syntactic structure that fits the input. Taken together, these points suggest that more work is needed to fully understand how lists recruit language networks in comprehension and production, and indicate a need fro finer-grained manipulations (see [55] for discussion).

3.2 Localization: A hybrid spatial organization

Across analyses we observed a hybrid spatial organization: effects were broadly distributed across traditional language regions (Figs. 1C & 3B), but also showed focal concentrations – in IFG and MFG for the structure RSI; STG and SMC for the (sub)lexical RSI; and MTG and IPL for the event semantic RSI (Fig. 3A). This hybrid pattern could help reconcile ongoing debates, particularly in the syntax literature where there remains significant disagreement regarding localization. Work in this literature often considers only two possibilities: broad distribution or localized hubs. Our

data suggest the answer may instead be "both," which could explain the prevalence of both findings in the literature. One concrete implication of the present work, then, is that the field should more seriously consider such a hybrid distribution as a third possibility.

Another intriguing result is that, despite the near complete lack of overlap between the sentence>list and active≠passive tests at the electrode level, these tests were perfectly aligned at the region level. That is, the sentence>list comparison, which was meant to identify information at the sentence level, was significant in IFG, MFG, MTG, and IPL (Fig. 1D). These are exactly the same regions that were significant for the two sentence-level RSIs: event semantics (MTG & IPL) and structure (IFG & MFG) (see Fig. 3A). Conversely, the two regions that were *not* identified by tests for higher-order language – STG and SMC – were exactly those with above-chance sensitivity to (sub)lexical information. This is precisely the type of alignment we initially anticipated, a prediction which motivated intersecting the two tests. Crucially, however, the ROI-level alignment was driven by mostly distinct sets of electrodes within each region (e.g., different IFG electrodes for sentence>list vs. active≠passive). It remains unclear how and why these tests aligned in ROI analyses without overlap at the electrode level. We suspect that clarity will come from future work that carefully disentangles the many constructs targeted by each of these tests.

3.3 Information above and below the word level

Finally, our data reveal a potential distinction in how the brain processes different kinds of information. While (sub)lexical processing was strongly correlated with degree of neural activity, differences associated with sentence structure and event semantics did not show such a relationship. To end on a broader note, we offer a speculative, general hypothesis that could account for this pattern. Specifically, we suggest that this distinction may belie a deeper taxonomic generalization. Consider the fact that (sub)lexical processing is not alone: low-level sensorimotor processes in general show a similar relationship with neural activity, including vision [109, 110], audition [111, 112], and motor movement [113, 114]. We speculate that the divergence between lexical information on one hand and syntactic and event semantic information on the other may be consistent with a broader dichotomy, whereby lower-level systems encode information in a way that elevates activity, while higher-order cognition does not. Such an account may go some distance to explaining why cognitive neuroscience has progressed more slowly than sensory neuroscience. Just as low-level information shares encoding properties, higher-order processing may in general be encoded in neural populations with varying degrees of overall neural activity. Such a divergence in coding schemes could derive from any number of differences between low- and high-level cognitive systems, including their spatial distribution, evolutionary age, or informational complexity. One possibility is that because higher-level representations are generally sustained over longer periods of time, they require a metabolically efficient neural code. In contrast, lower-level representations like phonemes are relatively short-lived [115, 116], and higher firing rates may therefore be achieved without depleting resources. Taken together, our findings provide a new window into the neural

underpinnings of sentence production, using high-resolution ECoG data and a controlled production experiment to provide evidence for a hybrid spatial organization and a magnitude-independent coding scheme for higher-order linguistic processing.

4 Methods

4.1 Participants

Ten neurosurgical patients undergoing evaluation for refractory epilepsy participated in the experiment (3 female, mean age: 30 years, range: 20 to 45). All ten were implanted with electrocorticographic grids and strips and provided informed consent to participate. All consent was obtained in writing and then requested again orally prior to the beginning of the experiment. Electrode implantation and location were guided solely by clinical requirements. Eight of the participants were implanted with standard clinical electrode grid with 10 mm spaced electrodes (Ad-Tech Medical Instrument, Racine, WI). Two participants consented to a research hybrid grid implant (PMT corporation, Chanassen, MN) that included 64 additional electrodes between the standard clinical contacts (with overall 10 mm spacing and interspersed 5 mm spaced electrodes over select regions), providing denser sampling but with positioning based solely on clinical needs. The study protocol was approved by the NYU Langone Medical Center Committee on Human Research.

4.2 Data collection and preprocessing

Participants were tested while resting in their hospital bed in the epilepsy monitoring unit. Stimuli were presented on a laptop screen positioned at a comfortable distance from the participant. Participants' voice was recorded using a cardioid microphone (Shure MX424). Inaudible TTL pulses marking the onset of a stimulus were generated by the experiment computer, split, and recorded in auxiliary channels of both the clinical Neuroworks Quantum Amplifier (Natus Biomedical, Appleton, WI), which records ECoG, and the audio recorder (Zoom H1 Handy Recorder). The microphone signal was also fed to both the audio recorder and the ECoG amplifier. These redundant recordings were used to sync the speech, experiment, and neural signals.

The standard implanted ECoG arrays contained 64 macro-contacts (2 mm exposed, 10 mm spacing) in an 8×8 grid. Hybrid grids contained 128 electrode channels, including the standard 64 macro-contacts and 64 additional interspersed smaller electrodes (1 mm exposed) between the macro-contacts (providing 10 mm center-to-center spacing between macro-contacts and 5 mm center-to-center spacing between micro/macro contacts, PMT corporation, Chanassen, MN). The FDA-approved hybrid grids were manufactured for research purposes, and a member of the research team explained this to patients during consent. The ECoG arrays were implanted on the left hemisphere for all ten participants. Placement location was solely dictated by clinical care.

ECoG was recorded at 2,048 Hz, which was decimated to 512 Hz prior to processing and analysis. After rejecting electrodes with artifacts (i.e., line noise, poor contact with the cortex, and high amplitude shifts), we subtracted a common average reference (across all valid electrodes and time) from each individual electrode. Electrodes with

interictal and epileptiform activity were removed from the analysis. We then extracted the envelope of the high gamma component (the average of three log-spaced frequency bands from 70 to 150 Hz) from the raw signal with the Hilbert transform. Beta activity was quantified as the envelope of the 12 to 30 Hz band.

The signal was separately epoched locked to stimulus (i.e., cartoon images) and production onsets for each trial. The 200 ms silent period preceding stimulus onset (during which patients were not speaking and fixating on a cross in the center of the screen) was used as a baseline, and each epoch for each electrode was normalized to this baseline's mean and standard deviation (i.e., z-scored).

4.3 Experimental Design

4.3.1 Procedure

The experiment was performed in one session that lasted approximately 40 minutes. Stimuli were presented in pseudo-random order using PsychoPy [117]. All stimuli were constructed using the same 6 cartoon characters (chicken, dog, Dracula, Frankenstein, ninja, nurse), chosen to vary along many dimensions (e.g., frequency, phonology, number of syllables, animacy, proper vs. common) to facilitate identification of lexical information at analysis.

The experiment began with two familiarization blocks. In the first block (6 trials), participants saw images of each of the six cartoon characters once with labels (*chicken, dog, Dracula, Frankenstein, ninja, nurse*) written beneath the image. Participants were instructed to read the labels aloud, after which the experimenter pressed a button to go to the next trial. In the second block, participants saw the same six characters one at a time, twice each in pseudo-random order (12 trials), but without labels. They were instructed to name the characters out loud. After naming the character, the experimenter pressed a button revealing the target name to ensure learning of the correct labels. Participants then completed the picture naming block (96 trials). As before, characters were presented in the center of the screen, one at a time, but no labels were provided.

Next, participants performed a sentence production block (60 trials), starting with two practice trials. Participants were instructed that there were no right or wrong answers, we want to know what their brain does when they speak naturally. On each trial, participants saw a 1 s fixation cross followed by a written question, which they were instructed to read aloud to ensure attention. After another 1 s fixation cross, a static cartoon vignette appeared in the center of the screen depicting two of the six characters engaged in a transitive event. Participants were instructed to respond to the question by describing the vignette. The image remained on the screen until the participant completed the sentence, at which point the experimenter pressed a button to proceed. After the first 12 trials, the target sentence (i.e., an active sentence after an active question or passive sentence after a passive question) appeared in text on the screen and participants were instructed to read aloud "the sentence we expected [them] to say" to implicitly reinforce the link between the syntax of the question and the target response. If participants appeared to interpret these as corrections, the experimenter reminded them that there were no right or wrong answers.

We interleaved two picture naming trials between each sentence production trial in order to reduce task difficulty and facilitate fluent sentence production. The picture naming trials involved the two characters that would be engaged in the subsequent vignette, presented in a counterbalanced order such that on half of trials they would appear in the same order as in the expected sentence response, and in the opposite order on the other half.

Next, participants performed the listing block. List production trials were designed to parallel sentence production trials. Each trial began with a 1 s fixation cross and then an arrow pointing either left or right appeared for 1 s in the center of the screen. After another 1 s fixation cross, a cartoon vignette (the exact same stimuli) appeared on the screen. Participants named the two characters in the vignette from left to right or from right to left, according to the direction of the preceding arrow. As in sentence production trials, each list production trial was preceded by two picture naming trials with the two characters that would appear in the subsequent vignette, again in counterbalanced order.

Between each block, participants were offered the opportunity to stop the experiment if they did not wish to continue. One participant stopped before the list production block, providing only picture naming and sentence production data. The other nine participants completed all three blocks. These nine were offered the opportunity to complete another picture naming block and another sentence production block. Six consented to another picture naming block and two consented to another sentence production block.

4.3.2 Stimulus Design, Randomization, and Counterbalancing

Picture naming stimuli consisted of images of the 6 characters in pseudo-random order so that each consecutive set of 6 trials contained all 6 characters in random order. This ensured a relatively even distribution of characters across the block, and that no character appeared more than twice in a row. Characters were pseudorandomly depicted facing 8 orientations: facing forward, backward, left, right, and at the 45° angle between each of these.

Sentence production stimuli consisted of a written question and a static cartoon vignette. Questions were manipulated so half were constructed with passive syntax and half with active. All questions followed the scheme: "Who is [verb]-ing whom?" or "Who is being [verb]-ed by whom?". There were 10 verbs: *burn, hit, hypnotize, measure, poke, scare, scrub, spray, tickle, trip*. Each verb was used to create 3 vignettes involving 3 characters, counterbalanced so each character was the agent (i.e., active subject) in one vignette and the non-agent (i.e., active object) in one vignette. Each of these three vignettes was shown twice in the sentence production block, once preceded by an active question and once by a passive question to prime active and passive responses, respectively [79]. Vignettes were flipped around the vertical axis the second time they appeared so that the character that was on the left in the first appearance was on the right in the second appearance and vice versa. This was counterbalanced so that on half of the trials in each structure condition (active/passive) the subject was on the left. List production stimuli similarly consisted of the same 60 vignettes, also

presented in pseudorandom order and counterbalanced across conditions (i.e., arrow direction).

4.4 Data Coding and Inclusion

Speech was manually transcribed and word onset times were manually recorded using Audacity [118] to visualize the audio waveform and spectrogram. Picture naming trials were excluded if the first word uttered was not the target word (e.g., "Frankenstein – I mean Dracula"). Sentence trials were excluded if the first word was incorrect (i.e., "Frankenstein" instead of "Dracula," regardless of syntactic structure) or if the meaning of the sentence did not match the meaning of the depicted scene; no sentences were excluded because the structure did not match that of the prime (i.e., question). Sentences were coded as active or passive depending on the structure the patient used, not the prime structure. Listing trials were excluded if the first word was incorrect or if the order did not match that indicated by the arrow.

All patients were included in Figure 1 analyses, however three patients who produced 6 or fewer passive sentences during the sentence production block were excluded prior to any subsequent analyses that involved an active≠passive test (including the RSA and NMF analyses).

4.5 Electrode Localization

Electrode localization in subject space, as well as MNI space, was based on coregistering a preoperative (no electrodes) and postoperative (with electrodes) structural MRI (in some cases, a postoperative CT was employed depending on clinical requirements) using a rigid-body transformation. Electrodes were then projected to the surface of the cortex (preoperative segmented surface) to correct for edema-induced shifts following previous procedures [119] (registration to MNI space was based on a nonlinear DARTEL algorithm). Based on the subject's preoperative MRI, the automated FreeSurfer segmentation (Destrieux) was used for labeling within-subject anatomical locations of electrodes.

4.6 Significance testing and corrections for multiple comparisons in time series data

Statistical tests on time series data were performed independently at each time sample, resulting in the same number of p-values as there are samples in the time series. To correct for multiple comparisons we follow [120, 121] and establish a conservative criterion for significance for all time series comparisons: an uncorrected p-value that remains below .05 for at least 100 consecutive milliseconds.

4.7 Permutation tests for ROIs

To determine whether activity was significantly above chance for a given ROI (Figs. 1D and 3A), we randomized electrodes' ROI labels and re-calculated ROI means 1000 times. We derived p-values by determining what proportion of these chance means were above the real mean value at each time sample. If the p-value was less than .05

for at least 100 consecutive milliseconds (see Sec. 4.6), it was considered significant, denoted by a bar at the bottom of the plot.

4.8 Temporal warping

Our analyses focused on the planning period – the time between stimulus and speech onsets, when hierarchical syntactic structure is planned [29, 73, 76, 84]. The duration of the planning period varied considerably both across and within patients, meaning that cognitive processes become less temporally aligned across trials the farther one moves from stimulus onset in stimulus-locked epochs or speech onset in speech-locked epochs. This was potentially problematic for comparing syntactic structures, as passive trials took longer to plan (median RT: 1,424 ms) than active trials (median RT: 1,165 ms; $p < .001$, Wilcoxon rank sum test). The farther from the time lock, the more misaligned active and passive trials would be, and the more likely significant differences would be to reflect temporal misalignment rather than structure-related differences.

Temporal warping reduces such misalignments [85–87, 122, 123]. Following [85], we linearly interpolated the data in the middle of the planning period (from 150 ms post-stimulus to 150 ms pre-speech) for each trial to set all trials' planning periods to the same duration (Supplementary Fig. S1): the global median per task (1141 ms for sentences; 801 ms for lists; 758 ms for words). Specifically, for each task we started by excluding trials with outlier response times, which we defined as those in the bottom 2.5% or top 5% per participant. We then calculated the median response time per task across participants (1,142 ms for sentences, 800 ms for lists, and 758 ms for words), and for each electrode and each trial, concatenated (a) the stimulus-locked data from 150 ms post-stimulus to $\frac{1}{2}$ the median reaction time with (b) the production-locked data from $-\frac{1}{2}$ median reaction time to 150 ms pre-speech. We then linearly interpolated this time series to the number of time samples corresponding to the median reaction time minus 300 ms (i.e., the two 150 ms periods following stimulus onset and preceding speech onset). Finally, we concatenated (a) the unwarped data leading up to 150 ms post-stimulus, (b) the warped data from the previous step, and (c) the unwarped data starting 150 ms before speech onset to form the final epochs used in the analyses in Figs. 2 and 3.

Improved temporal alignment leads to better signal-to-noise ratio, which can be seen in higher trial means [87]. We leveraged this fact as a diagnostic for whether temporal warping in fact improved alignment in our data. For electrodes whose mean high gamma peaked in the warped period (between 150 ms post-stimulus and 150 ms pre-speech), we compared the peak mean values in the unwarped and the warped data. Peak values were significantly higher for the warped data than the unwarped data (Supplementary Fig. S3) for both the sentence and list production tasks ($p = .003$ and $p.008$ respectively, Wilcoxon signed rank tests), indicating that warping significantly improved temporal alignment in the data. (There was no significant difference between peak values in the picture naming data ($p = .592$). This likely reflects the fact that these trials were relatively short, with a median reaction time of just 758 ms, meaning that warping made relatively minor changes to a smaller number of time samples.)

For comparison, we reproduced Fig. 1 in Supplementary Fig. S2 using the warped data. The results of the statistical tests in these figures were qualitatively identical:

The spatial distributions of significant electrodes were nearly identical over time (Fig. 1C and Supplementary Fig. S2C) and the same ROIs (IFG, MFG, MTG, and IPL) showed significantly higher activity for sentences than lists during the planning period (Fig. 1D and Supplementary Fig. S2D).

4.9 Representational Similarity Analysis (RSA) and Representational Similarity Indices (RSIs)

To uniquely identify variance associated with event-semantics, (sub)lexical processing, and the active/passive distinction, we used multiple linear regression to model the neural activity from each electrode and at each time sample as a linear combination of event-semantic, (sub)lexical, and structural properties of the sentence the patient was planning/producing. Multiple regression is ideal in this context because it fits coefficients (slopes/betas) that can be used to derive t-values and corresponding p-values which reflect the *unique* contribution of each independent variable, effectively partitioning variance that can be unambiguously ascribed to just one term [124].

However, event semantic and (sub)lexical representations are highly complex and multidimensional, requiring a choice of which dimensions/features to use in a multiple regression model. To avoid this scenario, we leveraged a Representational Similarity Analysis-style approach and modeled pairwise differences between trials [88–91]. This resulted in just one vector per construct representing pairwise trial differences in sentence structure, event semantics, and word content.

4.9.1 Linguistic and Neural Dissimilarity Models

The structure term was binary: 1 if one trial was active and the other was passive and 0 otherwise. We modeled event-semantic representations using outputs from GPT-2's 8th hidden layer, where embeddings correlate most highly with neural activity [125]. Specifically, for each unique stimulus vignette, we fed the corresponding sentence with active syntax into GPT-2 and averaged the embeddings in layer 8 for all of the words in the sentence. By inputting only active sentences (rather than a combination of actives and passives depending on the structure of the specific trials), we ensured that the resulting vector contains just the semantic information from the trial, not the relevant structural information (i.e., whether it was active or passive).

To quantify event-semantic dissimilarity between trials, we correlated the vectors corresponding to each pair of trials' stimuli. Prior to modeling, correlation coefficients (r) were centered, scaled, and multiplied by -1 so that a value of 1 corresponded to more dissimilar meanings, and -1 meant that the two trials had the same exact stimulus. (Each stimulus appeared twice in each sentence production block, once with an active prime and once with a passive prime.)

The (sub)lexical term was also binary: 1 if the first word of the two trials' sentences were different, 0 if they were the same. This encoding scheme was meant to absorb variance associated with a host of extraneous linguistic features at the lexical and sub-lexical levels including phonetics, phonology, articulatory/motor information, auditory feedback, lemma-level representations, and lexical semantics (the meaning of individual words rather than the global event meaning).

We also included differences in response time (RT) as a covariate in the model, as this is known to index other extraneous non-linguistic features like difficulty that might be correlated with our structural manipulation. This term was quantified as the absolute value of the difference in the log of each trial's reaction times, so that higher values corresponded to bigger differences in reaction times.

We then modeled pairwise trial differences in neural activity (the magnitude of the difference between z-scored high gamma activity at a given sample for a given electrode) as a linear combination of these four dissimilarity (D) terms:

$$|\Delta\gamma| = \beta_0 + \beta_1 D_{structure} + \beta_2 D_{semantics} + \beta_3 D_{(sub)lexical} + \beta_4 D_{RT} + \epsilon \quad (1)$$

4.9.2 Electrode Significance

The data used in the RSA regression did not clearly meet the assumptions of standard linear regressions: it was not clear that the residuals should be normally distributed (high gamma activity is gamma-distributed), and imbalances in the datasets due to trial exclusions and the varying effectiveness of priming across patients were exacerbated by the implementation of pairwise trial differences. To err on the side of caution, rather than directly interpreting model statistics, we ran a permutation analysis, shuffling the neural activity with respect to linguistic features in the original datasets, reconstructing the neural dissimilarity models, and re-running the linear regression at each time sample 1000 times.

To assess whether a given electrode was significant for the structure, semantics, and (sub)lexical terms, we started by calculating the t-values corresponding to the each term's coefficient, which corresponds to the amount of evidence against the null hypothesis. Then we smoothed the real and shuffled t-values over time with a $100\,\mathrm{ms}$ boxcar function. Finally, we z-scored the real t-values by time sample and electrode with respect to the 1000 t-values from shuffled models in the same time sample and electrode. The resulting z-values reflect an estimate of evidence against the null that is standardized across patients and electrodes and independent of the number of trials. Significant electrodes for each representation were defined as those which maintained a z-value of at least 1.645 (corresponding to a 1-tailed p-value of less than .05) for at least 100 consecutive milliseconds.

4.9.3 Representational Similarity Indices (RSIs)

To derive RSIs, we performed additional transformations on these z-values to make them more interpretable and conservative. First, We scaled z-scores, dividing by 2.326, which corresponds to a p-value of .01. Consequently, values greater than 1 could be interpreted as very likely to reflect positive results, and values less than 1 were likely to reflect negative results. Next, to reduce the possibility of extremely high values having an undue influence on aggregate statistics and NMF, we applied a logarithmic penalty to values grater than 1, replacing them with $log(x) + 1$. Similarly, to reduce values more likely to correspond to negative results, we shrunk low values toward 0 by replacing values less than 1 with (e^x), and then cubing the resulting values (i.e., $(e^x)^3$) to impose an even more severe penalty on low values. Notably, this renders

all values non-negative, naturally resolving issues related to the uninterpretability of negative relationships in RSA [88, 126] and facilitating the use of NMF for subsequent clustering. Finally, we re-scaled values by multiplying them by 2.326 (undoing Step 1) so that the final RSI scale more closely matched the z scale in interpretation. Like z-scores, RSI values over 2.326 can be safely interpreted as significant at the $\alpha = .01$ threshold.

4.10 Non-negative Matrix Factorization (NMF)

We used NMF to cluster electrodes according to prototypical patterns in the data [127, 128]. In the first clustering analysis (Fig. 3), we analyzed RSIs and mean neural activity from all three tasks for all electrodes that were either "active" (non-zero neural activity; $p < .05$ for 100 ms, Wilcoxon signed rank test) or inactive, but with at least one significant RSI ($p < .05$ for 100 ms, permutation test).

High gamma activity was in units of standard deviations (i.e., z-scores), while RSIs were z-scores that had been smoothed and transformed to be non-negative, with extreme values in both directions shrunk (see Section 4.9.3). To ensure that NMF weighted the two types of information the same way, we applied the same transformation used to create the RSIs (Sec. 4.9.3) to the neural data prior to performing NMF.

We then concatenated these three time series (i.e., mean high gamma per task) and the three RSI time series (i.e., structure, event semantics, and (sub)lexical), excluding pre-stimulus time samples and those after 500 ms post-speech onset. This resulted in a matrix of dimensionality 741 (electrodes) $\times$ 4364 (time samples from 3 high gamma and 3 RSI time series).

We fed this matrix to the `nmf()` function in R (*NMF* library v0.25 [129]) using the Brunet algorithm [130] and 50 runs to mitigate the risk of converging on local minima. We tried a range of model ranks: 3 to 9. The optimal rank (5) was determined by finding the elbow in the scree plots.

Acknowledgments

This work was supported by National Institutes of Health grants F32DC019533 (A.M.), R01NS109367 (A.F.), R01NS115929 (A.F.), and R01DC018805 (A.F.).

Data and Code availability

The data set generated during the current study will be made available from the authors upon request and documentation is provided that the data will be strictly used for research purposes and will comply with the terms of our study IRB. The code is available upon publication at https://github.com/flinkerlab/low_activity_syntax.

Declarations

The authors declare that they have no competing interests.

Appendix A   Supplementary Information

A.1   Data Warping

Supplementary Figs. S1, S2, and S3 show the methods and efficacy checks for our temporal warping procedure (see Sec. 4.8). Supplementary Fig. S3 analyses were performed on the maximum values of electrodes' trial means. Prior to finding the maximum, we took the absolute value of the trial mean to capture electrodes with negative peaks (reflecting suppression) that might have been enhanced by warping. We included only those electrodes that peaked during the warped period (between 150 ms post-stimulus and 150 ms pre-speech), as other electrode's maxima remained unchanged.

Fig. S1   Warped and unwarped sentence production data from a sample electrode. The data in each trial between 150 ms post stimulus and 150 ms pre-speech were linearly interpolated to set the duration of the planning period to the global median per task (1142 ms for sentence production) [85]. (A) Sample electrode localization in MFG. (B) The mean of this electrode's warped (pink) and unwarped (grey) trials. Prior to warping, this patient's median sentence response time was 995 ms; after warping it was 1,141 ms: the median sentence production response time across patients. The peak of the warped data was higher than the unwarped peak, a sign that warping resulted in better temporal alignment and consequently higher signal-to-noise ratio. (C) Three sample trials: warped (pink) and unwarped (grey) data.

Fig. S2 Replication of Figure 1 using warped data. Results are qualitatively identical: (C) the spatial distribution of electrodes with significant differences between sentences and lists over time was nearly identical and (D) both identify IFG, MFG, MTG, and IPL as having significantly higher sentence than list activity during the planning period.

Fig. S3 Peak high gamma activity for each electrode (dot) in the warped (red) and unwarped (grey) data, by task. Warping resulted in significantly higher peaks for sentence production ($p = .003$, Wilcoxon signed rank test) and list production ($p = .008$, Wilcoxon signed rank test), evidence that it successfully improved the temporal alignment of trials [87]. No effect was found for picture naming ($p = .592$).

A.2 Analyses of Beta Activity

Supplementary Fig. S4 replicates the Figure 1 analyses but using beta activity (12-30 Hz). Beta is another important frequency band in cognition [82, 83]. In Supplementary Fig. S5, we test the hypothesis that beta activity tracks structural differences more clearly than high gamma. We present three replications of the analysis in Fig. 2F (copied in Supplementary Fig. S5A). Analyses appear in a 2×2 factorial design: regressing either beta or high gamma activity over RSIs, where RSIs were derived from RSA performed on either high gamma (left) or beta (right) activity. Across all four sets of results, the only significant finding is that reported in the main text: a positive relationship between mean sentence high gamma and (sub)lexical signal in the high gamma trial activity ($p < .001$, linear regression).

To determine whether representational encoding in beta activity might be anatomically localized more than in high gamma, we replicated the analyses in Fig. 2A,b using beta. We analyzed the resulting "beta RSIs" by region of interest (Supplementary Fig. S6A). There was significant evidence for sensitivity to structure in SMC and, as in the high gamma data, IFG ($p < .05$ for 100 ms, permutation test), but unlike high gamma there was no evidence that beta activity was sensitive to the active/passive contrast in MFG. We also plotted electrodes with significant beta RSIs on cortex (Supplementary Fig. S6B), revealing distributed networks similar to those observed in high gamma.

Fig. S4 Replication of Figure 1 using beta activity (12-30 Hz; unwarped data). (C) The distribution of electrodes that are significantly greater for sentences than lists was largely reversed from the high gamma activity. This likely reflects a well-documented phenomenon where activity in high gamma is often coupled with beta suppression, leading to effects in the reverse direction in beta [131, 132]. (D) SMC, STG, and IPL show significantly higher beta activity for sentences than lists, possibly also reflecting beta suppression corresponding to increases in high gamma during speech and auditory feedback.

Fig. S5 Four attempts at uncovering a relationship between mean neural activity during sentence production and linguistic processes. Only one significant relationship was found across all analyses: mean high gamma activity was positively related to high gamma (sub)lexical processing ($p < .001$). (A) Mean high gamma activity vs. linguistic RSIs encoded in high gamma trial activity (panel is identical to Fig. 2F). (B) Mean high gamma activity vs. linguistic RSIs encoded in beta trial activity. (C) Mean beta activity vs. linguistic RSIs encoded in high gamma trial activity. (D) Mean beta activity vs. linguistic RSIs encoded in beta trial activity.

Fig. S6 Distribution of RSIs calculated from RSA on beta activity (see parallels for high gamma in Fig. 2A,B). (A) Mean and standard error by region shows significant structure effects in IFG and SMC ($p < .05$ for 100 ms, permutation test), but there was no evidence for sensitivity to structure in MFG as there was in the high gamma activity. (B) Significant electrodes ($p < .05$ for 100 ms; one-tailed permutation test) per RSI again show a broadly distributed pattern for all three RSIs, as in high gamma.

References

[1] Flinker, A., Piai, V., Knight, R.T.: Intracranial electrophysiology in language research. In: Rueschemeyer, S.-A., Gaskell, M.G. (eds.) The Oxford Handbook of Psycholinguistics (2nd Edn) vol. 1. Oxford University Press, ??? (2018). https://doi.org/10.1093/oxfordhb/9780198786825.013.43

[2] Llorens, A., Trébuchon, A., Liégeois-Chauvel, C., Alario, F.-X.: Intra-cranial recordings of brain activity during language production. Frontiers in psychology **2**, 375 (2011) https://doi.org/10.3389/fpsyg.2011.00375

[3] Yeaton, J.D.: The neurobiology of sentence production: A narrative review and meta-analysis. Brain and Language **264**, 105549 (2025)

[4] Walenski, M., Europa, E., Caplan, D., Thompson, C.K.: Neural networks for sentence comprehension and production: An ale-based meta-analysis of neuroimaging studies. Human brain mapping **40**(8), 2275–2304 (2019)

[5] Pylkkänen, L., Bemis, D.K., Elorrieta, E.B.: Building phrases in language production: An meg study of simple composition. Cognition **133**(2), 371–384 (2014)

[6] Menenti, L., Segaert, K., Hagoort, P.: The neuronal infrastructure of speaking. Brain and language **122**(2), 71–80 (2012) https://doi.org/10.1016/j.bandl.2012.04.012

[7] Giglio, L., Hagoort, P., Ostarek, M.: Neural encoding of semantic structures during sentence production. Cerebral Cortex **34**(12), 482 (2024) https://doi.org/10.1093/cercor/bhae482

[8] Giglio, L., Ostarek, M., Weber, K., Hagoort, P.: Commonalities and asymmetries in the neurobiological infrastructure for language production and comprehension. Cerebral Cortex **32**(7), 1405–1418 (2022) https://doi.org/10.1093/cercor/bhab287

[9] Giglio, L., Ostarek, M., Sharoh, D., Hagoort, P.: Diverging neural dynamics for syntactic structure building in naturalistic speaking and listening. Proceedings of the National Academy of Sciences **121**(11), 2310766121 (2024) https://doi.org/10.1073/pnas.2310766121

[10] Sahin, N.T., Pinker, S., Cash, S.S., Schomer, D., Halgren, E.: Sequential processing of lexical, grammatical, and phonological information within broca's area. Science **326**(5951), 445–449 (2009)

[11] Braun, A.R., Guillemin, A., Hosey, L., Varga, M.: The neural organization of discourse: An h215o-pet study of narrative production in english and american sign language. Brain **124**(10), 2028–2044 (2001)

[12] Segaert, K., Menenti, L., Weber, K., Petersson, K.M., Hagoort, P.: Shared syntax in language production and language comprehension—an fmri study. Cerebral Cortex **22**(7), 1662–1670 (2012) https://doi.org/10.1093/cercor/bhr249

[13] Hu, J., Small, H., Kean, H., Takahashi, A., Zekelman, L., Kleinman, D., Ryan, E., Nieto-Castañón, A., Ferreira, V., Fedorenko, E.: Precision fmri reveals that the language-selective network supports both phrase-structure building and lexical access during language production. Cerebral Cortex **33**(8), 4384–4404 (2023) https://doi.org/10.1093/cercor/bhac350

[14] Morgan, A.M., Devinsky, O., Doyle, W.K., Dugan, P., Friedman, D., Flinker, A.: Decoding words during sentence production with ecog reveals syntactic role encoding and structure-dependent temporal dynamics. Communications Psychology **3**(1), 87 (2025)

[15] Ishkhanyan, B., Michel Lange, V., Boye, K., Mogensen, J., Karabanov, A., Hartwigsen, G., Siebner, H.R.: Anterior and posterior left inferior frontal gyrus contribute to the implementation of grammatical determiners during language production. Frontiers in psychology **11**, 685 (2020)

[16] Blanco-Elorrieta, E., Kastner, I., Emmorey, K., Pylkkänen, L.: Shared neural correlates for building phrases in signed and spoken language. Scientific reports **8**(1), 5492 (2018)

[17] Matchin, W., Wood, E.: Syntax-sensitive regions of the posterior inferior frontal gyrus and the posterior temporal lobe are differentially recruited by production and perception. Cerebral cortex communications **1**(1), 029 (2020)

[18] Takashima, A., Konopka, A., Meyer, A., Hagoort, P., Weber, K.: Speaking in the brain: the interaction between words and syntax in sentence production. Journal of Cognitive Neuroscience **32**(8), 1466–1483 (2020) https://doi.org/10.1162/jocn_a_01563

[19] Bemis, D.K., Pylkkänen, L.: Simple composition: A magnetoencephalography investigation into the comprehension of minimal linguistic phrases. Journal of Neuroscience **31**(8), 2801–2814 (2011) https://doi.org/10.1523/JNEUROSCI.5003-10.2011

[20] Westerlund, M., Pylkkänen, L.: The role of the left anterior temporal lobe in semantic composition vs. semantic memory. Neuropsychologia **57**, 59–70 (2014) https://doi.org/10.1016/j.neuropsychologia.2014.03.001

[21] Flick, G., Oseki, Y., Kaczmarek, A.R., Al Kaabi, M., Marantz, A., Pylkkänen, L.: Building words and phrases in the left temporal lobe. Cortex **106**, 213–236 (2018) https://doi.org/10.1016/j.cortex.2018.06.004

[22] Westerlund, M., Kastner, I., Al Kaabi, M., Pylkkänen, L.: The latl as locus of

composition: Meg evidence from english and arabic. Brain and Language **141**, 124–134 (2015) https://doi.org/10.1016/j.bandl.2014.12.003

[23] Graessner, A., Zaccarella, E., Friederici, A.D., Obrig, H., Hartwigsen, G.: Dissociable contributions of frontal and temporal brain regions to basic semantic composition. Brain communications **3**(2), 090 (2021) https://doi.org/10.1093/braincomms/fcab090

[24] Frankland, S.M., Greene, J.D.: Two ways to build a thought: distinct forms of compositional semantic representation across brain regions. Cerebral Cortex **30**(6), 3838–3855 (2020) https://doi.org/10.1093/cercor/bhaa001

[25] Lyu, B., Choi, H.S., Marslen-Wilson, W.D., Clarke, A., Randall, B., Tyler, L.K.: Neural dynamics of semantic composition. Proceedings of the National Academy of Sciences **116**(42), 21318–21327 (2019) https://doi.org/10.1073/pnas.1903402116

[26] Kaan, E., Swaab, T.Y.: The brain circuitry of syntactic comprehension. Trends in cognitive sciences **6**(8), 350–356 (2002) https://doi.org/10.1016/S1364-6613(02)01947-2

[27] Pallier, C., Devauchelle, A.-D., Dehaene, S.: Cortical representation of the constituent structure of sentences. Proceedings of the National Academy of Sciences **108**(6), 2522–2527 (2011) https://doi.org/10.1073/pnas.1018711108

[28] Nelson, M.J., El Karoui, I., Giber, K., Yang, X., Cohen, L., Koopman, H., Cash, S.S., Naccache, L., Hale, J.T., Pallier, C., *et al.*: Neurophysiological dynamics of phrase-structure building during sentence processing. Proceedings of the National Academy of Sciences **114**(18), 3669–3678 (2017) https://doi.org/10.1073/pnas.1701590114

[29] Hagoort, P., Indefrey, P.: The neurobiology of language beyond single words. Annual review of neuroscience **37**, 347–362 (2014) https://doi.org/10.1146/annurev-neuro-071013-013847

[30] Friederici, A.D.: The brain basis of language processing: from structure to function. Physiological Reviews **91**(4), 1357–1392 (2011) https://doi.org/10.1152/physrev.00006.2011

[31] Hickok, G., Poeppel, D.: The cortical organization of speech processing. Nature reviews neuroscience **8**(5), 393–402 (2007) https://doi.org/10.1038/nrn2113

[32] Matchin, W., Liao, C.-H., Gaston, P., Lau, E.: Same words, different structures: An fMRI investigation of argument relations and the angular gyrus. Neuropsychologia **125**, 116–128 (2019) https://doi.org/10.1016/j.neuropsychologia.2019.01.019

[33] Matchin, W., Hickok, G.: The cortical organization of syntax. Cerebral Cortex **30**(3), 1481–1498 (2020) https://doi.org/10.1093/cercor/bhz180

[34] Stromswold, K., Caplan, D., Alpert, N., Rauch, S.: Localization of syntactic comprehension by positron emission tomography. Brain and language **52**(3), 452–473 (1996) https://doi.org/10.1006/brln.1996.0024

[35] Zaccarella, E., Friederici, A.D.: Merge in the human brain: A sub-region based functional investigation in the left pars opercularis. Frontiers in psychology **6**, 1818 (2015) https://doi.org/10.3389/fpsyg.2015.01818

[36] Matchin, W., Basilakos, A., Stark, B.C., Ouden, D.-B., Fridriksson, J., Hickok, G.: Agrammatism and paragrammatism: a cortical double dissociation revealed by lesion-symptom mapping. Neurobiology of Language **1**(2), 208–225 (2020) https://doi.org/10.1162/nol_a_00010

[37] Flick, G., Pylkkänen, L.: Isolating syntax in natural language: MEG evidence for an early contribution of left posterior temporal cortex. Cortex **127**, 42–57 (2020) https://doi.org/10.1016/j.cortex.2020.01.025

[38] Shain, C., Kean, H., Casto, C., Lipkin, B., Affourtit, J., Siegelman, M., Mollica, F., Fedorenko, E.: Distributed sensitivity to syntax and semantics throughout the language network. Journal of Cognitive Neuroscience, 1–43 (2024) https://doi.org/10.1162/jocn_a_02164

[39] Ding, N., Melloni, L., Zhang, H., Tian, X., Poeppel, D.: Cortical tracking of hierarchical linguistic structures in connected speech. Nature neuroscience **19**(1), 158–164 (2016) https://doi.org/10.1038/nn.4186

[40] Blank, I., Balewski, Z., Mahowald, K., Fedorenko, E.: Syntactic processing is distributed across the language system. Neuroimage **127**, 307–323 (2016) https://doi.org/10.1016/j.neuroimage.2015.11.069

[41] Fedorenko, E., Blank, I.A., Siegelman, M., Mineroff, Z.: Lack of selectivity for syntax relative to word meanings throughout the language network. Cognition **203**, 104348 (2020) https://doi.org/10.1016/j.cognition.2020.104348

[42] Krauska, A., Lau, E.: Moving away from lexicalism in psycho-and neuro-linguistics. Frontiers in Language Sciences **2**, 1125127 (2023) https://doi.org/10.3389/flang.2023.1125127

[43] Schell, M., Zaccarella, E., Friederici, A.D.: Differential cortical contribution of syntax and semantics: An fMRI study on two-word phrasal processing. Cortex **96**, 105–120 (2017) https://doi.org/10.1016/j.cortex.2017.09.002

[44] Friederici, A.D., Kotz, S.A., Scott, S.K., Obleser, J.: Disentangling syntax and intelligibility in auditory language comprehension. Human brain mapping **31**(3),

448–457 (2010) https://doi.org/10.1002/hbm.20878

[45] Ni, W., Constable, R., Mencl, W., Pugh, K., Fulbright, R., Shaywitz, S., Shaywitz, B., Gore, J., Shankweiler, D.: An event-related neuroimaging study distinguishing form and content in sentence processing. Journal of Cognitive Neuroscience **12**(1), 120–133 (2000) https://doi.org/10.1162/08989290051137648

[46] Dapretto, M., Bookheimer, S.Y.: Form and content: dissociating syntax and semantics in sentence comprehension. Neuron **24**(2), 427–432 (1999) https://doi.org/10.1016/S0896-6273(00)80855-7

[47] Embick, D., Marantz, A., Miyashita, Y., O'Neil, W., Sakai, K.L.: A syntactic specialization for Broca's area. Proceedings of the National Academy of Sciences **97**(11), 6150–6154 (2000) https://doi.org/10.1073/pnas.100098897

[48] Kuperberg, G.R., McGuire, P.K., Bullmore, E.T., Brammer, M.J., Rabe-Hesketh, S., Wright, I.C., Lythgoe, D.J., Williams, S.C., David, A.S.: Common and distinct neural substrates for pragmatic, semantic, and syntactic processing of spoken sentences: an fMRI study. Journal of Cognitive Neuroscience **12**(2), 321–341 (2000) https://doi.org/10.1162/089892900562138

[49] Kuperberg, G.R., Holcomb, P.J., Sitnikova, T., Greve, D., Dale, A.M., Caplan, D.: Distinct patterns of neural modulation during the processing of conceptual and syntactic anomalies. Journal of Cognitive Neuroscience **15**(2), 272–293 (2003) https://doi.org/10.1162/089892903321208204

[50] Wagley, N., Hu, X., Satterfield, T., Bedore, L.M., Booth, J.R., Kovelman, I.: Neural specificity for semantic and syntactic processing in spanish-english bilingual children. Brain and Language **250**, 105380 (2024) https://doi.org/10.1016/j.bandl.2024.105380

[51] Fedorenko, E., Nieto-Castanon, A., Kanwisher, N.: Lexical and syntactic representations in the brain: an fMRI investigation with multi-voxel pattern analyses. Neuropsychologia **50**(4), 499–513 (2012) https://doi.org/10.1016/j.neuropsychologia.2011.09.014

[52] Blank, I.A., Fedorenko, E.: No evidence for differences among language regions in their temporal receptive windows. NeuroImage **219**, 116925 (2020) https://doi.org/10.1016/j.neuroimage.2020.116925

[53] Fedorenko, E., Hsieh, P.-J., Nieto-Castañón, A., Whitfield-Gabrieli, S., Kanwisher, N.: New method for fMRI investigations of language: Defining ROIs functionally in individual subjects. Journal of Neurophysiology **104**(2), 1177–1194 (2010) https://doi.org/10.1152/jn.00032.2010

[54] Sprouse, J., Lau, E.F.: Syntax and the brain. The Cambridge Handbook of Generative Syntax, 971–1005 (2013)

[55] Poeppel, D., Embick, D.: Defining the relation between linguistics and neuroscience. In: Twenty-first Century Psycholinguistics, pp. 103–118. Routledge, ??? (2017)

[56] Murphy, E.: Rose: A neurocomputational architecture for syntax. Journal of Neurolinguistics **70**, 101180 (2024) https://doi.org/10.1016/j.jneuroling.2023.101180

[57] Mazoyer, B.M., Tzourio, N., Frak, V., Syrota, A., Murayama, N., Levrier, O., Salamon, G., Dehaene, S., Cohen, L., Mehler, J.: The cortical representation of speech. Journal of cognitive neuroscience **5**(4), 467–479 (1993) https://doi.org/10.1162/jocn.1993.5.4.467

[58] Friederici, A.D., Meyer, M., Von Cramon, D.Y.: Auditory language comprehension: an event-related fMRI study on the processing of syntactic and lexical information. Brain and language **74**(2), 289–300 (2000) https://doi.org/10.1006/brln.2000.2313

[59] Matchin, W., Hammerly, C., Lau, E.: The role of the IFG and pSTS in syntactic prediction: Evidence from a parametric study of hierarchical structure in fMRI. Cortex **88**, 106–123 (2017) https://doi.org/10.1002/hbm.24403

[60] Rogalsky, C., Hickok, G.: Selective attention to semantic and syntactic features modulates sentence processing networks in anterior temporal cortex. Cerebral Cortex **19**(4), 786–796 (2009) https://doi.org/10.1093/cercor/bhn126

[61] Stowe, L.A., Broere, C.A., Paans, A.M., Wijers, A.A., Mulder, G., Vaalburg, W., Zwarts, F.: Localizing components of a complex task: sentence processing and working memory. Neuroreport **9**(13), 2995–2999 (1998)

[62] Humphries, C., Love, T., Swinney, D., Hickok, G.: Response of anterior temporal cortex to syntactic and prosodic manipulations during sentence processing. Human brain mapping **26**(2), 128–138 (2005) https://doi.org/10.1002/hbm.20148

[63] Humphries, C., Binder, J.R., Medler, D.A., Liebenthal, E.: Syntactic and semantic modulation of neural activity during auditory sentence comprehension. Journal of cognitive neuroscience **18**(4), 665–679 (2006) https://doi.org/10.1162/jocn.2006.18.4.665

[64] Feng, S., Legault, J., Yang, L., Zhu, J., Shao, K., Yang, Y.: Differences in grammatical processing strategies for active and passive sentences: An fmri study. Journal of Neurolinguistics **33**, 104–117 (2015) https://doi.org/10.1016/j.jneuroling.2014.09.002

[65] Mack, J.E., Meltzer-Asscher, A., Barbieri, E., Thompson, C.K.: Neural correlates of processing passive sentences. Brain sciences **3**(3), 1198–1214 (2013) https:

//doi.org/10.3390/brainsci3031198

[66] Indefrey, P.: The relationship between syntactic production and comprehension. In: Rueschemeyer, S.-A., Gaskell, M.G. (eds.) The Oxford Handbook of Psycholinguistics (2 Ed.), pp. 482–505. Oxford University Press, ??? (2018). https://doi.org/10.1093/oxfordhb/9780198786825.013.20

[67] Morgan, A.M., Malsburg, T., Ferreira, V.S., Wittenberg, E.: Shared syntax between comprehension and production: Multi-paradigm evidence that resumptive pronouns hinder comprehension. Cognition **205**, 104417 (2020)

[68] Ferreira, F., Bailey, K.G., Ferraro, V.: Good-enough representations in language comprehension. Current Directions in Psychological Science **11**(1), 11–15 (2002) https://doi.org/10.1111/1467-8721.0015

[69] Ferreira, F.: The misinterpretation of noncanonical sentences. Cognitive psychology **47**(2), 164–203 (2003) https://doi.org/10.1016/S0010-0285(03)00005-7

[70] Dwivedi, V.D.: Interpreting quantifier scope ambiguity: Evidence of heuristic first, algorithmic second processing. PloS one **8**(11), 81461 (2013) https://doi.org/10.1371/journal.pone.0081461

[71] Christianson, K., Hollingworth, A., Halliwell, J.F., Ferreira, F.: Thematic roles assigned along the garden path linger. Cognitive psychology **42**(4), 368–407 (2001) https://doi.org/10.1006/cogp.2001.0752

[72] Aoshima, S., Yoshida, M., Phillips, C.: Incremental processing of coreference and binding in japanese. Syntax **12**(2), 93–134 (2009) https://doi.org/10.1111/j.1467-9612.2009.00123.x

[73] Garrett, M.: Remarks on the architecture of language processing systems. Language and the brain, 31–69 (2000) https://doi.org/10.1016/B978-012304260-6/50004-9

[74] Weber, K., Indefrey, P.: Syntactic priming in german–english bilinguals during sentence comprehension. NeuroImage **46**(4), 1164–1172 (2009)

[75] Slevc, L.R.: Grammatical encoding. In: Language Production, pp. 4–31. Routledge, ??? (2023)

[76] Bock, K., Ferreira, V.S.: Syntactically speaking. The Oxford handbook of language production, 21–46 (2014)

[77] Naselaris, T., Kay, K.N., Nishimoto, S., Gallant, J.L.: Encoding and decoding in fMRI. Neuroimage **56**(2), 400–410 (2011) https://doi.org/10.1016/j.neuroimage.2010.07.073

[78] Holdgraf, C.R., Rieger, J.W., Micheli, C., Martin, S., Knight, R.T., Theunissen,

F.E.: Encoding and decoding models in cognitive electrophysiology. Frontiers in systems neuroscience **11**, 61 (2017)

[79] Bock, J.K.: Syntactic persistence in language production. Cognitive psychology **18**(3), 355–387 (1986) https://doi.org/10.1016/0010-0285(86)90004-6

[80] Mukamel, R., Gelbard, H., Arieli, A., Hasson, U., Fried, I., Malach, R.: Coupling between neuronal firing, field potentials, and fMRI in human auditory cortex. Science **309**(5736), 951–954 (2005) https://doi.org/10.1126/science.1110913

[81] Nir, Y., Fisch, L., Mukamel, R., Gelbard-Sagiv, H., Arieli, A., Fried, I., Malach, R.: Coupling between neuronal firing rate, gamma LFP, and BOLD fMRI is related to interneuronal correlations. Current biology **17**(15), 1275–1285 (2007) https://doi.org/10.1016/j.cub.2007.06.066

[82] Fries, P.: Rhythms for cognition: communication through coherence. Neuron **88**(1), 220–235 (2015) https://doi.org/10.1016/j.neuron.2015.09.034

[83] Richter, C.G., Thompson, W.H., Bosman, C.A., Fries, P.: Top-down beta enhances bottom-up gamma. Journal of Neuroscience **37**(28), 6698–6711 (2017) https://doi.org/10.1523/JNEUROSCI.3771-16.2017

[84] Ferreira, V.S., Morgan, A.M., Slevc, L.R.: Grammatical encoding. The Oxford Handbook of Psycholinguistics, 453–469 (20018)

[85] Edwards, E., Nagarajan, S.S., Dalal, S.S., Canolty, R.T., Kirsch, H.E., Barbaro, N.M., Knight, R.T.: Spatiotemporal imaging of cortical activation during verb generation and picture naming. Neuroimage **50**(1), 291–301 (2010)

[86] Picton, T.W., Lins, O.G., Scherg, M.: The recording and analysis of event-related potentials. Handbook of neuropsychology **10**, 3–3 (1995)

[87] Molina, M., Tardón, L.J., Barbancho, A.M., De-Torres, I., Barbancho, I.: Enhanced average for event-related potential analysis using dynamic time warping. Biomedical Signal Processing and Control **87**, 105531 (2024) https://doi.org/10.1016/j.bspc.2023.105531

[88] Jozwik, K.M., Kriegeskorte, N., Mur, M.: Visual features as stepping stones toward semantics: Explaining object similarity in it and perception with non-negative least squares. Neuropsychologia **83**, 201–226 (2016) https://doi.org/10.1016/j.neuropsychologia.2015.10.023

[89] Kaiser, D., Turini, J., Cichy, R.M.: A neural mechanism for contextualizing fragmented inputs during naturalistic vision. elife **8**, 48182 (2019) https://doi.org/10.7554/eLife.48182

[90] Proklova, D., Kaiser, D., Peelen, M.V.: Disentangling representations of object

shape and object category in human visual cortex: The animate–inanimate distinction. Journal of cognitive neuroscience **28**(5), 680–692 (2016) https://doi.org/10.1162/jocn_a_00924

[91] Tucciarelli, R., Wurm, M., Baccolo, E., Lingnau, A.: The representational space of observed actions. elife **8**, 47686 (2019) https://doi.org/10.7554/eLife.47686

[92] Millet, J., Caucheteux, C., Boubenec, Y., Gramfort, A., Dunbar, E., Pallier, C., King, J.-R., *et al.*: Toward a realistic model of speech processing in the brain with self-supervised learning. Advances in Neural Information Processing Systems **35**, 33428–33443 (2022)

[93] Chang, F., Dell, G.S., Bock, K.: Becoming syntactic. Psychological review **113**(2), 234 (2006) https://doi.org/10.1037/0033-295X.113.2.234

[94] Grill-Spector, K., Henson, R., Martin, A.: Repetition and the brain: Neural models of stimulus-specific effects. Trends in Cognitive Sciences **10**(1), 14–23 (2006) https://doi.org/10.1016/j.tics.2005.11.006

[95] Henson, R.N.: Neuroimaging studies of priming. Progress in Neurobiology **70**(1), 53–81 (2003) https://doi.org/10.1016/S0301-0082(03)00086-8

[96] Krekelberg, B., Boynton, G.M., Wezel, R.J.: Adaptation: from single cells to bold signals. Trends in Neurosciences **29**(5), 250–256 (2006) https://doi.org/10.1016/j.tins.2006.02.008

[97] Miller, E.K., Li, L., Desimone, R.: A neural mechanism for working and recognition memory in inferior temporal cortex. Science **254**(5036), 1377–1379 (1991) https://doi.org/10.1126/science.1962197

[98] Huth, A.G., De Heer, W.A., Griffiths, T.L., Theunissen, F.E., Gallant, J.L.: Natural speech reveals the semantic maps that tile human cerebral cortex. Nature **532**(7600), 453–458 (2016) https://doi.org/10.1038/nature17637

[99] Hamilton, L.S., Oganian, Y., Hall, J., Chang, E.F.: Parallel and distributed encoding of speech across human auditory cortex. Cell **184**(18), 4626–4639 (2021) https://doi.org/10.1016/j.cell.2021.07.019

[100] Goldstein, A., Zada, Z., Buchnik, E., Schain, M., Price, A., Aubrey, B., Nastase, S.A., Feder, A., Emanuel, D., Cohen, A., *et al.*: Shared computational principles for language processing in humans and deep language models. Nature neuroscience **25**(3), 369–380 (2022) https://doi.org/10.1038/s41593-022-01026-4

[101] Deniz, F., Tseng, C., Wehbe, L., Tour, T.D., Gallant, J.L.: Semantic representations during language comprehension are affected by context. Journal of Neuroscience **43**(17), 3144–3158 (2023) https://doi.org/10.1523/JNEUROSCI.2459-21.2023

[102] Hamilton, L.S., Huth, A.G.: The revolution will not be controlled: natural stimuli in speech neuroscience. Language, cognition and neuroscience **35**(5), 573–582 (2020) https://doi.org/10.1080/23273798.2018.1499946

[103] Trueswell, J.C., Kim, A.E.: How to prune a garden path by nipping it in the bud: Fast priming of verb argument structure. Journal of memory and language **39**(1), 102–123 (1998) https://doi.org/10.1006/jmla.1998.2565

[104] Meltzer-Asscher, A., Mack, J.E., Barbieri, E., Thompson, C.K.: How the brain processes different dimensions of argument structure complexity: Evidence from fmri. Brain and language **142**, 65–75 (2015) https://doi.org/10.1016/j.bandl.2014.12.005

[105] Berkovitch, L., Dehaene, S.: Subliminal syntactic priming. Cognitive psychology **109**, 26–46 (2019) https://doi.org/10.1016/j.cogpsych.2018.12.001

[106] Osterhout, L., Holcomb, P.J.: Event-related brain potentials elicited by syntactic anomaly. Journal of Memory and Language **31**(6), 785–806 (1992) https://doi.org/10.1016/0749-596X(92)90039-Z

[107] Kaan, E., Harris, A., Gibson, E., Holcomb, P.: The p600 as an index of syntactic integration difficulty. Language and cognitive processes **15**(2), 159–201 (2000) https://doi.org/10.1080/016909600386084

[108] Gouvea, A.C., Phillips, C., Kazanina, N., Poeppel, D.: The linguistic processes underlying the p600. Language and cognitive processes **25**(2), 149–188 (2010) https://doi.org/10.1080/01690960902965951

[109] Hubel, D.H., Wiesel, T.N.: Receptive fields of single neurones in the cat's striate cortex. The Journal of physiology **148**(3), 574 (1959)

[110] Daniel, P., Whitteridge, D.: The representation of the visual field on the cerebral cortex in monkeys. The Journal of physiology **159**(2), 203 (1961)

[111] Ades, H.W., Felder, R.E.: The acoustic projection system: a comparative study. Journal of Neurophysiology **8**(6), 463–470 (1945)

[112] Licklider, J., Kryter, K.: Frequency localization in the auditory cortex of the monkey. In: Fed. Proc, vol. 1, p. 51 (1942)

[113] Evarts, E.V.: Pyramidal tract activity associated with a conditioned hand movement in the monkey. Journal of neurophysiology **29**(6), 1011–1027 (1966) https://doi.org/10.1152/jn.1966.29.6.1011

[114] Evarts, E.V.: Relation of pyramidal tract activity to force exerted during voluntary movement. Journal of neurophysiology **31**(1), 14–27 (1968) https://doi.org/10.1152/jn.1968.31.1.14

[115] Gwilliams, L., King, J.-R., Marantz, A., Poeppel, D.: Neural dynamics of phoneme sequences reveal position-invariant code for content and order. Nature communications **13**(1), 6606 (2022) https://doi.org/10.1038/s41467-022-34326-1

[116] Gwilliams, L., Marantz, A., Poeppel, D., King, J.-R.: Hierarchical dynamic coding coordinates speech comprehension in the brain. bioRxiv, 2024–04 (2024) https://doi.org/10.1101/2024.04.19.590280

[117] Peirce, J., Gray, J.R., Simpson, S., MacAskill, M., Höchenberger, R., Sogo, H., Kastman, E., Lindeløv, J.K.: Psychopy2: Experiments in behavior made easy. Behavior research methods **51**, 195–203 (2019) https://doi.org/10.3758/s13428-018-01193-y

[118] Audacity Team: Audacity (R). http://audacity.sourceforge.net/

[119] Yang, A.I., Wang, X., Doyle, W.K., Halgren, E., Carlson, C., Belcher, T.L., Cash, S.S., Devinsky, O., Thesen, T.: Localization of dense intracranial electrode arrays using magnetic resonance imaging. Neuroimage **63**(1), 157–165 (2012) https://doi.org/10.1016/j.neuroimage.2012.06.039

[120] Maris, E., Oostenveld, R.: Nonparametric statistical testing of eeg-and meg-data. Journal of neuroscience methods **164**(1), 177–190 (2007) https://doi.org/10.1016/j.jneumeth.2007.03.024

[121] Flinker, A., Doyle, W.K., Mehta, A.D., Devinsky, O., Poeppel, D.: Spectrotemporal modulation provides a unifying framework for auditory cortical asymmetries. Nature human behaviour **3**(4), 393–405 (2019) https://doi.org/10.1038/s41562-019-0548-z

[122] Williams, A.H., Poole, B., Maheswaranathan, N., Dhawale, A.K., Fisher, T., Wilson, C.D., Brann, D.H., Trautmann, E.M., Ryu, S., Shusterman, R., *et al.*: Discovering precise temporal patterns in large-scale neural recordings through robust and interpretable time warping. Neuron **105**(2), 246–259 (2020) https://doi.org/10.1016/j.neuron.2019.10.020

[123] Wang, K., Begleiter, H., Porjesz, B.: Warp-averaging event-related potentials. Clinical Neurophysiology **112**(10), 1917–1924 (2001) https://doi.org/10.1016/S1388-2457(01)00640-X

[124] Belsley, D.A., Kuh, E., Welsch, R.E.: Regression Diagnostics: Identifying Influential Data and Sources of Collinearity. John Wiley & Sons, ??? (2005)

[125] Caucheteux, C., Gramfort, A., King, J.-R.: Deep language algorithms predict semantic comprehension from brain activity. Scientific reports **12**(1), 16327 (2022) https://doi.org/10.1038/s41598-022-20460-9

[126] Kriegeskorte, N., Mur, M., Bandettini, P.A.: Representational similarity analysis-connecting the branches of systems neuroscience. Frontiers in systems neuroscience **2**, 249 (2008) https://doi.org/10.3389/neuro.06.004.2008

[127] Lee, D.D., Seung, H.S.: Learning the parts of objects by non-negative matrix factorization. nature **401**(6755), 788–791 (1999) https://doi.org/10.1038/44565

[128] Kim, J., Park, H.: Sparse nonnegative matrix factorization for clustering. Technical report, Georgia Institute of Technology (2008)

[129] Gaujoux, R., Seoighe, C.: A flexible r package for nonnegative matrix factorization. BMC bioinformatics **11**, 1–9 (2010) https://doi.org/10.1186/1471-2105-11-367

[130] Brunet, J.-P., Tamayo, P., Golub, T.R., Mesirov, J.P.: Metagenes and molecular pattern discovery using matrix factorization. Proceedings of the national academy of sciences **101**(12), 4164–4169 (2004) https://doi.org/10.1073/pnas.0308531101

[131] Lundqvist, M., Herman, P., Warden, M.R., Brincat, S.L., Miller, E.K.: Gamma and beta bursts during working memory readout suggest roles in its volitional control. Nature communications **9**(1), 394 (2018) https://doi.org/10.1038/s41467-017-02791-8

[132] Assem, M., Hart, M.G., Coelho, P., Romero-Garcia, R., McDonald, A., Woodberry, E., Morris, R.C., Price, S.J., Suckling, J., Santarius, T., *et al.*: High gamma activity distinguishes frontal cognitive control regions from adjacent cortical networks. Cortex **159**, 286–298 (2023) https://doi.org/10.1016/j.cortex.2022.12.007