The perception of changes in visual movement feedback delay is biased by visuomotor congruence

Abbreviated title: Delay perception and visuomotor congruence

Authors: Gesche Vigh[1,2] and Jakub Limanowski[2,3]
[1]Faculty of Psychology, Technical University of Dresden, 01069 Dresden, Germany
[2]Center for Tactile Internet with Human-in-the-Loop, Technical University of Dresden, 01187 Dresden, Germany
[3]Institute of Psychology, University of Greifswald, 17486 Greifswald, Germany

Corresponding author email address: g.vigh@gmx.de

Number of pages: 19   **Number of figures:** 4   **Number of tables:** 0

Number of words: Abstract: 293, Introduction: 708, Discussion: 1138.

Conflict of interest statement: The authors declare no competing financial interests.

Acknowledgments: This work was funded by the German Research Foundation (DFG, Deutsche Forschungsgemeinschaft) as part of Germany's Excellence Strategy – EXC 2050/1 – Project ID 390696704 – Cluster of Excellence "Centre for Tactile Internet with Human-in-the-Loop" (CeTI) of Technische Universität Dresden. JL was supported by a Freigeist Fellowship of the VolkswagenStiftung (AZ 97-932).

Abstract: The Weber-Fechner Laws have been evaluated across a wide variety of modalities and tasks, but not yet in the domain of visuomotor mapping. A prominent manipulation of visuomotor mapping is temporal; i.e., delaying visual movement feedback. Yet, while visuomotor delay detection itself has been extensively studied, it is not known whether the perception of changes in delay depends on the present amount of delay. We developed a virtual reality based, continuous hand movement task, during which participants had to detect changes in visuomotor mapping (delay): Participants (N=40) performed continuous, auditory-paced grasping movements, which were measured with a data glove and transmitted to a virtual hand model. The movements of the virtual hand were periodically delayed between 0-700ms; the delay changed repeatedly in a roving oddball fashion in steps of 100-400ms. Participants had to indicate perceived delay changes by key presses, as fast as possible. This design allowed us to investigate detection accuracy and speed related to the magnitude of the delay change, and to the "baseline" delay present during movement. As expected, larger delay changes were detected more accurately than smaller ones. Surprisingly, delay changes were detected more accurately and faster when participants moved under larger delays. These results suggest that visual movement feedback delay affects the detection of changes in visuomotor mapping, but not as predicted by the Weber-Fechner Laws. Rather, smaller visual movement feedback delays likely increased the tolerance for visuomotor changes via an enhanced subjective embodiment of the virtual hand.

KEYWORDS: Action, Delay, Virtual Reality, Visuomotor Mapping, Weber-Fechner-Law

1. Introduction

For much of our usual sensory input, like sound, light and weight, the perceived magnitude of a change is proportional to the initial stimuli perceived before the change. Thus, the larger an initial stimulus is, the larger the change needs to be, so the resulting stimulus is perceived as different from the initial stimulus. This relationship is described by the Weber-Fechner Laws (Fechner, 1966), which we know hold true across different sensory modalities (Baird, 1997; Gescheider, 1997). Recent empirical evidence suggests that the Weber-Fechner Laws may also be valid for more abstract concepts like time and reward perception (Brannon et al., 2008; Namboodiri et al., 2014; Takahashi, 2005, 2006). Thus, Nieder and Miller (2003) proposed that sensory and certain cognitive representations follow the same neural coding schemes and thus hold true for all similar processes.

However, several studies investigating 'bodily' perception, e.g., concerned with self-motion and proprioception, have yielded notable violations of the Weber-Fechner Laws (Mallery et al., 2010; Nesti et al., 2015; Nouri & Karmali, 2018). Furthermore, it could be shown that the Weber-Fechner Laws are violated for visually guided grasping tasks (Ganel et al., 2008). In their study, Ganel and colleagues show that just noticeable differences depended on object size only in perceptual tasks, not in grasping tasks. Thus, the processing of stimuli related to bodily action and self-motion may follow different perceptual laws than the perception of external stimuli (Carriot et al., 2021).

The flexible control of bodily action by the brain relies on the capacity to adapt internal models for motor control to novel sensory movement feedback (Limanowski, 2022; Shadmehr et al., 2010; Wolpert & Kawato, 1998). Sensorimotor adaptation is necessary in cases where e.g. visual movement feedback is delayed, i.e., a temporal incongruence is introduced between movements and their visual feedback (Foulkes & Miall, 2000; Rohde & Ernst, 2016). Sensorimotor delays are an inherent feature of our nervous system, which the brain overcomes through internal forward modeling (Miall & Wolpert, 1996; Todorov & Jordan, 2002). But sensorimotor delays are also increasingly encountered in new technologies enabling cyber-physical interactions, such as controlling robots remotely or via virtual reality (Peters et al.,

2018; Schulze et al., 2024). In most of these scenarios, sensorimotor delays are to be expected

and, more importantly, they can vary unpredictably (Planthaber et al., 2018). Yet, it is crucial

that humans are able to experience control and, where possible, a sense of presence and

embodiment in such scenarios (Sanchez-Vives & Slater, 2005; Wen & Imamizu, 2022).

Not surprisingly, the corresponding learning and predictive processes are subject to intense

study: Many studies have investigated the perceptual thresholds for visuomotor delays, the

capacity to adapt to them, and the neuronal underpinnings of these processes (Farrer et al.,

2008; Foulkes & Miall, 2000; Krugwasser et al., 2019; Leube et al., 2003; Limanowski, 2017;

Miall et al., 1985; Miall & Jackson, 2006; Parvin et al., 2024; Rohde & Ernst, 2016; Tsakiris et

al., 2006).

One key question that, to our knowledge, has not yet been addressed is whether the perceptual

sensitivity to visuomotor delay changes depends on the amount of delay present during

movement; i.e., are identical delay changes detected differently when people currently move

under large, compared to small delays? In other words, it is unclear whether the Weber-

Fechner Laws hold for visuomotor delay perception. Not last, the aforementioned technological

developments that humans face today require this question to be answered. Therefore, here,

we tested whether people's sensitivity to *changes* in visual movement feedback delay depends

on the amount of delay already present during movement.

We addressed this question through a virtual reality based hand movement task: Participants

performed continuous right-hand grasping movements, paced by an auditory rhythm. Their

movements were fed to a photorealistic virtual hand model presented on screen, with an

experimentally added delay that changed in a roving oddball fashion (Fig. 1). Participants had

to report perceived delay changes (i.e., changes in the mapping of their real hand movements

to those executed by the virtual hand) by key presses, as fast as possible throughout the

movement task. We expected larger delay changes to be detected more accurately and faster;

following the Weber-Fechner Laws, we expected that participants would detect delays better

and quicker if they were moving under relatively smaller delays.

2. Methods

2.1 Participants:

We recruited 40 healthy, right-handed participants, with normal or corrected-to-normal vision

(15 female, mean age = 28.1, range= 22-38). We excluded three participants (one because

the data glove could not be adequately fitted and calibrated; one participant was not able to

perceive the changes in loudness of the tracking sound; and one did not perceive any delay of

the virtual hand, even for a delay of 700ms), leaving us with 37 participants whose data could

be analyzed. The experiment was approved by the ethics committee of the Technische

Universität Dresden and conducted in accordance with this approval.

2.2 Experimental Procedure

Figure 1. Experimental task and design. A-B: Participants used a data glove, worn on their right hand (occluded from view, **B**) to control a photorealistic virtual hand displayed on a screen in front of them (**A**). **C:** Participants had to execute continuous grasping (close-and-open) movements paced by an auditory cue, a tone changing loudness with a frequency of 0.5 Hz. Flexion data from the glove were fed to the virtual hand model, but with a delay; this altered the temporal congruence between the participants' hand movements and the movements of the virtual hand (i.e., the visuomotor mapping). Shown here is a schematic plot showing a full grasping cycle, i.e. the hand opening on a loud tone and closing on a quiet tone, under an exemplary delay between the virtual and real hand movements. **D:** During the continuous movement task, we repeatedly changed the amount of delay. This plot shows an example roving oddball sequence of delays between 0-700 ms as used in the experiment (i.e., one run of 4.9 min = 147 movements). Participants had to report whenever they perceived these changes, as fast as possible, by pressing the space bar of a computer keyboard (see **B**).

First, participants were briefed about the experimental procedure and completed a

demographic questionnaire. Afterwards, they put on a sanitary glove (for hygienic reasons)

and the data glove on their right hand (5Dt Data Glove Ultra, 14 sensors, 10 bit flexure

resolution per sensor, 60 Hz sampling rate, communication with the PC via USB with approx.

10 ms delay). The data glove allowed our participants to control a photorealistic virtual hand

(modelled with python 3 in blender 2.79 [(Blender Foundation, n.d.), Fig. 1B]), by measuring

the flexion of the participants' fingers and transmitting these values to the virtual hand model's

fingers (Fig. 1A-C). The virtual hand was shown on a monitor in front of the participant (1920

✕ 1080 pixels resolution, screen distance to eye about 90 cm, 18.92° of visual angle, 13 ms

Motion Picture Response Time). Participants placed their right hand on their leg, with the palm

facing upward, in a position that allowed for comfortable opening and closing of the hand (see

Fig. 1A). Their right hand was occluded from view by a barber coat. The data glove was then

calibrated; i.e., the virtual fingers' movement range was dynamically adjusted to the sensor

values until it accurately displayed the movements of the real hand.

Participants were instructed to fixate a dot presented centrally on screen, and visible at all

times, for the entirety of the experiment (Fig. 1B). The movement task was to execute simple,

continuous grasping movements: Participants opened and closed their right hand paced by a

rhythmic auditory cue; i.e., a 250 Hz tone that grew louder and quieter following a sine wave

function with 0.5 Hz frequency. When the tone was loudest, the physical hand of the participant

was supposed to be open and when the tone was quietest, the hand was supposed to be

closed (Fig. 1C).

Before the actual experiment, participants practiced to align their real hand grasping movement

with the auditory rhythm (without added delay to the virtual hand) until they felt confident that

they could open and close their hand continually throughout the main experiment, without

falling out of synchrony with the pacing signal.

In the first part of the experiment, participants had to perform 10 auditory paced grasping

movements (20 s) while fixating the dot in front of the virtual hand, at each delay level used in

the main experiment – and rate the task difficulty (see below). I.e., the virtual hand moved

either synchronously (0 ms delay) or was delayed by 100, 200, 300, 400, 500, 600 or 700 ms.

We chose relatively long delays for our experiment compared with previous single-trial delay

detection tasks (Leube et al., 2003; Limanowski, 2017; Limanowski et al., 2020), because our

pilot experiments indicated that delay perception was more difficult with our task setup, which

required simultaneously maintaining a continuous synchronization of the movements with the

pacing rhythm. Each delay level was presented three times, resulting in 24 trials in total. After

each trial, we asked our participants to indicate how difficult they felt it was to follow the auditory

cue, in comparison to the synchronous practice trial, on a 5-point Likert scale from "very easy"

to "very difficult".

In the second, main part of the experiment, participants also executed continuous, paced

grasping movements – but now with an added delay to the virtual hand movements that

changed repeatedly, following a roving oddball paradigm (Fig. 1D). Participants put their left

index finger on the space bar of a computer keyboard, and were instructed to press it as fast

as possible every time they detected a change in the visual movement delay (i.e., a change in

the mapping of the virtual hand movements to their actually executed movements).

Participants were specifically instructed, and trained to maintain stable grasping rhythm with

their real hand; i.e., to not alter their movements in response to the delays or delay changes.

During the experiment, each of 8 "baseline" delay levels (ranging from 0-700 ms in steps of

100 ms, see above) was presented for 3 to 6 movement cycles (i.e., 6-12 s), before changing

to a larger or smaller delay. The delays changed gradually between ±100-400 ms (in steps of

100 ms); i.e., over the course of 0.5 s to prevent sudden jumps in the visual movement. The

delays were presented in runs of 147 movements (4.9 mins); each run contained a predefined,

pseudorandomized sequence of 32 delay changes. Thus, we ensured that every run contained

8 delays with each length (3, 4, 5, and 6 movement cycles); and that, within each run, each

baseline delay level was presented once in combination with each absolute delay change (i.e.,

±100-400 ms; 8 delays x 4 changes = 32 delay changes). Note that, due to the nature of the

design, it was not possible to include all relative i.e., directional combinations of delay changes

with all initial delays (e.g., 700 ms was the largest delay, so there was no change of 700+100

ms, only 700-100 ms). An example of a delay sequence can be seen in Figure 1D. Overall,

eight such sequences were generated, and presented to each participant in randomized order;

resulting in 256 delay changes in total. After every run, participants could take a break until

they felt ready for the next one. After every break, the data glove was calibrated again.

2.4 Data analysis

To analyze detection performance, we defined a correct delay detection ("hit") as a button

press within two movement cycles (4 s) of a delay change. We chose to include the second

movement cycle, because each delay change was gradually introduced (see above), leaving

only a partial movement cycle for "detection" otherwise. Button presses outside of this window

were categorized as false alarms. If multiple button presses were recorded within 250 ms of a

hit or a false alarm (which we took as a proxy for 'visual' reaction time, following Jain et al.,

2015), they were counted as a single button press. To quantify the overall delay change

detection accuracy, the *False Alarm Ratio* was calculated as the number of false alarms per

number of total alarms (i.e., button presses) (Barnes et al., 2007). Note that this is different

from the often used False Alarm *Rate* (also called False Positive Rate), which is defined as

the number of false alarms per total number of "non-events". In our case, we could not clearly

define "non-events", as this would apply to any time point not corresponding to a delay change,

i.e., to most of the actual movement period. Thus, for our study we used the False Alarm Ratio.

Furthermore, we calculated a "detection score" as a more conservative index of detection

performance, punishing the percentage of hits by the False Alarm Ratio. Thus, participants

who were more hesitant and thus more accurate, but had lower hits overall, would still receive

an adequate score as compared to participants that hit the button at a near random rate. We

calculated the detection score as follows:

140
$$detection\ score\ = \frac{Percentage\ of\ Hits}{1 + FAR}$$

Detection scores were calculated for each of the 32 delay changes (see above). We then

inserted the detection scores into a 4 x 8 repeated measures ANOVA, with the factors *Delay*

Change (100, 200, 300, 400 ms) and *Baseline Delay* (0, 100, 200, 300, 400, 500, 600, 700,

800 ms). To test for non-normal properties, we used the Shapiro test. Since our data showed

non-normal properties, we used an aligned ranks transformation ANOVA for our analysis. The

degrees of freedom were calculated using the Kenward-Roger approximation. Post-hoc, we

used a linear regression model (method of least squares) to visualize the direction of the main

effects.

As an index of tracking error, we calculated the absolute phase shift in time between the

normalized mean movement of the participant and the target movement. To test whether

tracking performance (i.e., how well participants were able to maintain an accurate and stable

grasping rhythm) was influenced by detection performance, we calculated the Spearman's

rank correlation coefficients for tracking error vs. the detection score and the reaction times,

respectively, averaged over delay levels.

3. Results

A repeated measures aligned ranks transformation ANOVA on the difficulty ratings given in

the first part of the experiment (i.e., the reported difficulty of tracking the auditory target phase

with the grasping movements) showed no significant effect of delay on tracking difficulty

($F_{(7,885)}$=0.64, p=.72), the average difficulty ratings of each delay level, with associated standard

deviations, were: 2.58±1.15, 2.51±1.20, 2.44±1.08, 2.51±1.17, 2.53±1.01, 2.33±1.04,

2.50±1.17, 2.59±1.12. This means that participants found the movement task itself comparably

difficult across all delay levels.

In the main experiment, participants were well able to maintain regular and comparable

grasping across delay levels (Fig. 2). On average, they slightly lead the phase of the auditory

cue, with an average absolute tracking error of 0.24±0.15 s. Importantly, however, tracking

error did not significantly depend on the amount of visual movement feedback delay

($F_{(7,295)}$=0.23, p=.98; the average tracking errors of each delay level, in seconds, with

associated standard errors, were: 0.23±.017, 0.22±0.18, 0.24±0.18, 0.23±0.18, 0.23±0.18,

0.27±0.18, 0.27±0.18, 0.24±0.18). Together, these results suggest that our participants were

well able to comply with the task instructions; and that the delay of the virtual hand itself did

not significantly influence tracking (grasping) behavior, or the perceived task difficulty.

Figure 2. Participants' average hand movements per delay level (with standard deviations in gray shading), relative to the instructed grasping rhythm prescribed by the auditory cue. Participants tracked the auditory target rhythm comparably over all delay levels (see Results for statistical comparison of tracking errors), albeit overall leading slightly. Thus, delay per se did not bias tracking performance.

To validate the overall detection accuracy of our participants in the main experiment, we first

tested whether delay change detection was above chance level. The average False Alarm

Ratio of our participants was 0.45±0.10, which was significantly lower than the ratio that would

have resulted from random button pressing (i.e., >0.67; $t_{(36)}$=13.13, p<.001). This suggests that

the participants were able to notice the delay changes and pressed the button accordingly.

An aligned ranks transformation ANOVA on the detection scores showed a main effect of

Delay Change; i.e., the magnitude of change in lag of the visual movement feedback

($F_{(3,1116)}$=19.48, p<.001, η^2=.05). A post-hoc linear regression confirmed that these effects

could be linearly approximated (Fig.3A, R^2=.067, Slope= $2.58 \cdot 10^{-4}$, df= 35, p<.05; the average

detection scores, with standard deviations, in order from lowest to highest delay change were:

0.10±0.03, 0.11±0.03, 0.15±0.06, 0.16±0.04). However, there was no significant effect of Delay

Change on the corresponding reaction times (Fig. 3B), while the interaction effect was

significant ($F_{(21,1116)}$= 3.505, p<.001, η^2=.06). In sum, as expected, larger delay changes were

consistently detected better (albeit not faster) than smaller ones.

Secondly, there was a significant main effect of Baseline Delay on detection scores ($F_{(7,1116)}$=

11.76, p<.001, η^2=.07) and reaction times ($F_{(7,1116)}$=6.56, p<.001, η^2=.04); as well as a

significant interaction ($F_{(21,1116)}$=2.09, p<.05, η^2=.04 Fig.3B). Post-hoc linear regression

analyses showed, again, that these effects could be linearly approximated (detection scores,

Fig.3A: R^2=.55, Slope= 1.18·10^{-4}, df= 35, p<.001; reaction times, Fig.3B: R^2=.181, Slope=

4.05·10^{-4}, df= 35, p<.05, means in order from lowest to highest delay: 0.08±0.04, 0.1±0.03,

0.12±0.04, 0.12±0.06, 0.17±0.08, 0.14±0.02, 0.16±0.05, 0.17±0.04; means for reaction times:

2.14±0.18, 2.04±0.19, 2.11±0.27, 2.06±0.20, 2.02±0.14, 1.97±0.30, 1.82±0.20, 1.85±0.30). In

sum, delay change detection was overall better and faster, the higher the amount of visual

movement feedback delay present during movement at the time of the change.

Figure 3. Accuracy and speed of detecting changes in visual movement feedback delay during continuous grasping. The plots show the average detection scores (**A**, in arbitrary units) and reaction times (**B**) for each of the 32 delay change combinations; and the results of the post-hoc linear regression analyses on the respective main effects detected by ANOVA (see Results for details). Overall, larger delay changes were detected more accurately (and slightly but not significantly faster) than smaller magnitude changes; change detection was better and faster when participants were moving at larger, compared to smaller, delays.

Finally, we tested whether the participants' average detection performance covaried with how

well they were able to maintain stable tracking. With this, we aimed to detect a possible general

relationship between delay detection and tracking error; despite the fact that tracking

performance on average was comparable across delay levels (cf. Fig. 1). Indeed, we found a

negative correlation between detection accuracy and tracking error: Participants who tracked

the target rhythm overall better (i.e., had a smaller average tracking error) detected less of the

delay changes (Fig. 4, ρ=.40, p<.05). The correlation between reaction times and tracking error

showed a similar directionality, but was not significant (smaller tracking error ~ longer reaction

times to delay changes; ρ=-.05, p=.78).

Figure 4. Spearman correlation between detection score and tracking error of the individual participants. The more accurately participants tracked the auditory cue with their real hand (i.e., smaller average tracking error), the less of the delay changes they detected.

4. Discussion

Using a virtual reality based continuous hand movement task, we tested whether the detection

of changes in visuomotor temporal mapping (i.e., delay) depends on the amount of delay

currently present during movement. As expected, we found that larger delay changes were

detected significantly more accurately than smaller ones. Somewhat surprisingly, however,

delay changes were detected more accurately and faster when participants moved under

larger > smaller delays. In other words, our results suggest that the sensitivity to changes in

visual movement feedback delay is better when there already is a substantial amount of delay

present during movement. This result seems to indicate that the Weber-Fechner Laws do not

apply to the perception of (temporal) visuomotor mapping; as the laws would predict the

opposite finding, i.e., better sensitivity to changes in delay when delay itself is low.

Results inconsistent with the Weber-Fechner Laws have been reported in other domains

before, where they have been interpreted as indicating, for instance, saturation effects

(Augustin, 2008; Augustin & Tanja, 2008; Carriot et al., 2021; Doble et al., 2003). We propose

that, in our case, there is another intriguing explanation of the effect we found; which highlights

the importance of embodiment and cognitive-attentional control in settings where a conflict is

introduced between multiple sources of bodily movement feedback:

Firstly, increasing visuomotor delay reliably reduces the self-attribution of the observed

movements (also called a loss of "agency" over those movements) and reduced the subjective

embodiement of the seen moving body part (also called a loss of "ownership"; see Dummer et

al., 2009; Farrer et al., 2008; Leube et al., 2003; Tsakiris et al., 2006). Thus, it is reasonable

to assume that participants experienced more control over the virtual hand under small delays

(Krugwasser et al., 2019; Wen & Imamizu, 2022)—which could have led to a relatively stronger

subjective embodiment of the virtual limb.

Experienced embodiment can affect attentional control and task performance in virtual reality

based movement tasks, as shown e.g. by Iwasaki and colleagues (2022). In our case,

specifically, an increased embodiment of the virtual hand could have influenced our results

twofold: Firstly, an increased subjective sense of embodying the virtual hand could have

increased the tolerance for visuomotor mismatches, and thus, delay detection performance. It

is well known that the embodiment of an alternative (fake or virtual) limb biases the subjective

perception of visuoproprioceptive mismatches between real and fake limbs, resolving

intersensory conflict through updates to the corresponding neuronal representations; as

demonstrated e.g. in the 'rubber hand illusion' (Botvinick & Cohen, 1998; Limanowski, 2022).

Since visuomotor delays are, effectively, also visuoproprioceptive mismatches, we speculate

that a similar conflict attenuation could occur at smaller, compared with larger delays.

Interestingly, seven of our participants spontaneously reported, after the experiment, that they

had perceived up to half of all virtual movements as synchronous to their own movement (i.e.,

much more than actually were synchronous) – and several of those participants reported a

feeling of ownership over the virtual hand in those synchronously perceived periods. While this

were only spontaneous post-hoc reports, they tentatively support the above interpretation. An

increased embodiment of the virtual hand under small > large delays could also have distorted

the perception of movement timing (Desantis et al., 2016; Haering & Kiesel, 2015; Rohde &

Ernst, 2016). This would likely also influence the detection of delay changes.

Another possible effect of a potentially increased embodiment of the virtual hand under small

delays pertains to visuomotor interference. Visual body movements that are incongruent with

one's actual movements and movement goals can capture attention and lead to behavioral

deficits—this is sometimes also referred to as visuomotor interference (Blakemore & Frith,

2005; Brass et al., 2001; Kilner et al., 2003; Metral & Guerraz, 2019). In line with this, when

moving under visuomotor delay, visual movement feedback is processed differently depending

on whether vision is currently task-relevant or a distractor (Limanowski et al., 2020; Limanowski

& Friston, 2020). Interestingly, it has been suggested that the distracting effect of incongruent

visual stimuli may be particularly strong when they depict one's own, delayed movements

(Salomon et al., 2013). Note that our task design implied a continued focus on the real hand

movements, to track the auditory rhythm, while the virtual hand moved incongruently. Thus,

the inferior detection performance under smaller delays could hint at an increasingly distracting

effect of the virtual hand movements on the actual movements—potentially caused by a

relatively stronger embodiment of the virtual hand under small>large delays—despite tracking

performance itself not differing between delay levels. In other words, participants may have

used more cognitive-attentional resources to maintain stable tracking under small delays,

because the virtual hand was more distracting; and those resources could have been now

lacking for the detection task. This interpretation is supported by the fact that, overall,

participants who tracked the auditory rhythm better showed poorer detection performance (as

indicated by the positive correlation between overall tracking error and change detection

performance). It may also explain the relatively low overall detection performance we

observed, in contrast to other studies using single-movement designs (Farrer et al., 2008;

Leube et al., 2003).

Both effects, the increased tolerance for delays and the increased distraction by vision, are not

mutually exclusive; and both align with an increased subjective embodiment of the virtual hand

at smaller>larger delays. However, as we did not explicitly assess subjective embodiment,

both of the above interpretations have to be explicitly tested in future experiments.

Our study raised further questions that should be followed up by future work. One is whether

visuomotor delay changes are processed differently depending on whether they are task-

relevant or -irrelevant. Another question that our design cannot answer properly is whether

delay changes are perceived differently depending on whether delay is increased or

decreased. Due to the nature of our design (i.e., limiting delays between 0-700 ms), not all

directions of delay changes were presented equally often (e.g., from the 700 ms delay level,

delay was only reduced not increased). Furthermore, visuomotor temporal incongruence can

in principle also be implemented by leading, not lagging, vision; in the context of self-initiated

hand movements, however, this is associated with a number of problems related to the

predictability of the visual trajectories before actual movement. This could be an exciting

avenue for research using brain activity decoding, for example. Finally, visual feedback delay

is only one kind of visuomotor incongruence; future work should test whether other

manipulations, such as spatial offset or gain scaling, produce similar results.

In sum, we have shown that the current degree of visuomotor congruence can bias the

perception of changes in the visuomotor mapping during movement. Our results tentatively

suggest that movement under relatively small delays entails some degree of tolerance for, or

inattentiveness to delay changes; thus, they underline the general importance of embodiment

in the perception of, and movement under visuomotor conflicts.

References

Augustin, T. (2008). The parameters in the near-miss-to-Weber's law. *Journal of Mathematical Psychology*, *52*(1), 37–47. https://doi.org/10.1016/j.jmp.2007.11.001

Augustin, T., & TANJA, R. (2008). Empirical evaluation of the near-miss-to-Weber's law: A visual discrimination experiment. *Psychology Science Quarterly*, *50*.

Baird, J. C. (1997). *Sensation and judgment: Complementarity theory of psychophysics*. Lawrence Erlbaum Associates. https://search.ebscohost.com/login.aspx?direct=true&scope=site&db=nlebk&db=nlabk&AN=707812

Barnes, L. R., Gruntfest, E. C., Hayden, M. H., Schultz, D. M., & Benight, C. (2007). False Alarms and Close Calls: A Conceptual Model of Warning Accuracy. *Weather and Forecasting*, *22*(5), 1140–1147. https://doi.org/10.1175/WAF1031.1

Blakemore, S.-J., & Frith, C. (2005). The role of motor contagion in the prediction of action. *Neuropsychologia*, *43*(2), 260–267. https://doi.org/10.1016/j.neuropsychologia.2004.11.012

Blender Foundation. (n.d.). Blender.org—Home of the Blender project—Free and Open 3D Creation Software. *Blender.Org*. Retrieved 18 September 2023, from https://www.blender.org/

Botvinick, M., & Cohen, J. (1998). Rubber hands 'feel' touch that eyes see. *Nature*, *391*(6669), 756–756. https://doi.org/10.1038/35784

Brannon, E. M., Libertus, M. E., Meck, W. H., & Woldorff, M. G. (2008). Electrophysiological measures of time processing in infant and adult brains: Weber's Law holds. *Journal of Cognitive Neuroscience*, *20*(2), 193–203. https://doi.org/10.1162/jocn.2008.20016

Brass, M., Bekkering, H., & Prinz, W. (2001). Movement observation affects movement execution in a simple response task. *Acta Psychologica*, *106*(1), 3–22. https://doi.org/10.1016/S0001-6918(00)00024-X

Carriot, J., Cullen, K., & Chacron, M. (2021). The neural basis for violations of Weber's law in self-motion perception. *Proceedings of the National Academy of Sciences*, *118*, e2025061118. https://doi.org/10.1073/pnas.2025061118

Desantis, A., Waszak, F., Moutsopoulou, K., & Haggard, P. (2016). How action structures time: About the perceived temporal order of action and predicted outcomes. *Cognition*, *146*, 100–109. https://doi.org/10.1016/j.cognition.2015.08.011

Doble, C. W., Falmagne, J.-C., & Berg, B. G. (2003). Recasting (the near-miss to) Weber's law. *Psychological Review*, *110*(2), 365–375. https://doi.org/10.1037/0033-295X.110.2.365

Dummer, T., Picot-Annand, A., Neal, T., & Moore, C. (2009). Movement and the Rubber Hand Illusion. *Perception*, *38*(2), 271–280. https://doi.org/10.1068/p5921

Farrer, C., Frey, S. H., Van Horn, J. D., Tunik, E., Turk, D., Inati, S., & Grafton, S. T. (2008). The Angular Gyrus Computes Action Awareness Representations. *Cerebral Cortex*, *18*(2), 254–261. https://doi.org/10.1093/cercor/bhm050

Fechner, G. T. (1966). *Elements of psychophysics. Volume 1 / Gustav Fechner ; translated by Helmut E. Adler ; edited by David H. Howes, Edwin G. Boring ; with an introduction by Edwin G. Boring*. Holt, Rinehart and Winston, Inc.

Foulkes, A. J. McC., & Miall, R. C. (2000). Adaptation to visual feedback delays in a human manual tracking task. *Experimental Brain Research*, *131*(1), 101–110. https://doi.org/10.1007/s002219900286

Ganel, T., Chajut, E., & Algom, D. (2008). Visual coding for action violates fundamental psychophysical principles. *Current Biology*, *18*(14), R599–R601. https://doi.org/10.1016/j.cub.2008.04.052

Gescheider, G. A. (1997). *Psychophysics: The fundamentals*. Mahwah, N.J. : L. Erlbaum Associates. http://archive.org/details/psychophysicsfun0000gesc

Haering, C., & Kiesel, A. (2015). Was it me when it happened too early? Experience of delayed effects shapes sense of agency. *Cognition*, *136*, 38–42. https://doi.org/10.1016/j.cognition.2014.11.012

Iwasaki, Y., Navarro, B., Iwata, H., & Ganesh, G. (2022). Embodiment modifies attention allotment for the benefit of dual task performance. *Communications Biology*, *5*(1), 1–7. https://doi.org/10.1038/s42003-022-03603-6

Jain, A., Bansal, R., Kumar, A., & Singh, K. D. (2015). A comparative study of visual and auditory reaction times on the basis of gender and physical activity levels of medical first year students. *International Journal of Applied and Basic Medical Research*, *5*(2), 124. https://doi.org/10.4103/2229-516X.157168

Kilner, J. M., Paulignan, Y., & Blakemore, S. J. (2003). An Interference Effect of Observed Biological Movement on Action. *Current Biology*, *13*(6), 522–525. https://doi.org/10.1016/S0960-9822(03)00165-9

Krugwasser, A. R., Harel, E. V., & Salomon, R. (2019). The boundaries of the self: The sense of agency across different sensorimotor aspects. *Journal of Vision*, *19*(4), 14. https://doi.org/10.1167/19.4.14

Leube, D. T., Knoblich, G., Erb, M., & Kircher, T. T. J. (2003). Observing one's hand become anarchic: An fMRI study of action identification. *Consciousness and Cognition*, *12*(4), 597–608. https://doi.org/10.1016/S1053-8100(03)00079-5

Limanowski, J. (2017). (Dis-)Attending to the Body. In T. K. Metzinger & W. Wanja (Eds.), *PPP - Philosophy and Predictive Processing*. Open MIND. Frankfurt am Main: MIND Group. https://doi.org/10.15502/9783958573192

Limanowski, J. (2022). Precision control for a flexible body representation. *Neuroscience and Biobehavioral Reviews*, *134*. https://doi.org/10.1016/j.neubiorev.2021.10.023

Limanowski, J., & Friston, K. (2020). Attentional Modulation of Vision Versus Proprioception During Action. *Cerebral Cortex*, *30*(3), 1637–1648. https://doi.org/10.1093/cercor/bhz192

Limanowski, J., Litvak, V., & Friston, K. (2020). Cortical beta oscillations reflect the contextual gating of visual action feedback. *NeuroImage*, *222*, 117267. https://doi.org/10.1016/j.neuroimage.2020.117267

Mallery, R. M., Olomu, O. U., Uchanski, R. M., Militchin, V. A., & Hullar, T. E. (2010). Human discrimination of rotational velocities. *Experimental Brain Research*, *204*(1), 11–20. https://doi.org/10.1007/s00221-010-2288-1

Metral, M., & Guerraz, M. (2019). Fake hand in movement: Visual motion cues from the rubber hand are processed for kinesthesia. *Consciousness and Cognition*, *73*, 102761. https://doi.org/10.1016/j.concog.2019.05.009

Miall, R. C., & Jackson, J. K. (2006). Adaptation to visual feedback delays in manual tracking: Evidence against the Smith Predictor model of human visually guided action. *Experimental Brain Research*, *172*(1), 77–84. https://doi.org/10.1007/s00221-005-0306-5

Miall, R. C., Weir, D. J., & Stein, J. F. (1985). Visuomotor tracking with delayed visual feedback. *Neuroscience*, *16*(3), 511–520. https://doi.org/10.1016/0306-4522(85)90189-7

Miall, R. C., & Wolpert, D. M. (1996). Forward Models for Physiological Motor Control. *Neural Networks*, *9*(8), 1265–1279. https://doi.org/10.1016/S0893-6080(96)00035-4

Namboodiri, V. M. K., Mihalas, S., & Hussain Shuler, M. G. (2014). A temporal basis for Weber's law in value perception. *Frontiers in Integrative Neuroscience*, *8*. https://www.frontiersin.org/articles/10.3389/fnint.2014.00079

Nesti, A., Beykirch, K. A., Pretto, P., & Bülthoff, H. H. (2015). Human discrimination of head-centred visual–inertial yaw rotations. *Experimental Brain Research*, *233*(12), 3553–3564. https://doi.org/10.1007/s00221-015-4426-2

Nieder, A., & Miller, E. K. (2003). Coding of Cognitive Magnitude: Compressed Scaling of Numerical Information in the Primate Prefrontal Cortex. *Neuron*, *37*(1), 149–157. https://doi.org/10.1016/S0896-6273(02)01144-3

Nouri, S., & Karmali, F. (2018). Variability in the Vestibulo-Ocular Reflex and Vestibular Perception. *Neuroscience*, *393*, 350–365. https://doi.org/10.1016/j.neuroscience.2018.08.025

Parvin, D. E., Tsay, J., Dang, K. V., Stover, A. R., Ivry, R. B., & Morehead, J. R. (2024). *Implicit adaptation is modulated by the relevance of feedback* (p. 2022.01.19.476924). bioRxiv. https://doi.org/10.1101/2022.01.19.476924

Peters, B. S., Armijo, P. R., Krause, C., Choudhury, S. A., & Oleynikov, D. (2018). Review of emerging surgical robotic technology. *Surgical Endoscopy*, *32*(4), 1636–1655. https://doi.org/10.1007/s00464-018-6079-2

Planthaber, S., Mallwitz, M., & Kirchner, E. A. (2018). Immersive Robot Control in Virtual Reality to Command Robots in Space Missions. *Journal of Software Engineering and Applications*, *11*(7), Article 7. https://doi.org/10.4236/jsea.2018.117021

Rohde, M., & Ernst, M. O. (2016). Time, agency, and sensory feedback delays during action. *Current Opinion in Behavioral Sciences*, *8*, 193–199. https://doi.org/10.1016/j.cobeha.2016.02.029

Salomon, R., Lim, M., Kannape, O., Llobera, J., & Blanke, O. (2013). "Self pop-out": Agency enhances self-recognition in visual search. *Experimental Brain Research*, *228*(2), 173–181. https://doi.org/10.1007/s00221-013-3549-6

Sanchez-Vives, M. V., & Slater, M. (2005). From presence to consciousness through virtual reality. *Nature Reviews Neuroscience*, *6*(4), 332–339. https://doi.org/10.1038/nrn1651

Schulze, A., Bodenstedt, S., Distler, M., Weitz, J., Speidel, S., & Wagner, M. (2024). Künstliche Intelligenz in der onkologischen Chirurgie. *Die Onkologie*. https://doi.org/10.1007/s00761-024-01486-2

Shadmehr, R., Smith, M. A., & Krakauer, J. W. (2010). Error Correction, Sensory Prediction, and Adaptation in Motor Control. *Annual Review of Neuroscience*, *33*(Volume 33, 2010), 89–108. https://doi.org/10.1146/annurev-neuro-060909-153135

Takahashi, T. (2005). Loss of self-control in intertemporal choice may be attributable to logarithmic time-perception. *Medical Hypotheses*, *65*(4), 691–693. https://doi.org/10.1016/j.mehy.2005.04.040

Takahashi, T. (2006). Time-estimation error following Weber-Fechner law may explain subadditive time-discounting. *Medical Hypotheses*, *67*(6), 1372–1374. https://doi.org/10.1016/j.mehy.2006.05.056

Todorov, E., & Jordan, M. I. (2002). Optimal feedback control as a theory of motor coordination. *Nature Neuroscience*, *5*(11), 1226–1235. https://doi.org/10.1038/nn963

Tsakiris, M., Prabhu, G., & Haggard, P. (2006). Having a body *versus* moving your body: How agency structures body-ownership. *Consciousness and Cognition*, *15*(2), 423–432. https://doi.org/10.1016/j.concog.2005.09.004

Wen, W., & Imamizu, H. (2022). The sense of agency in perception, behaviour and human–machine interactions. *Nature Reviews Psychology*, *1*(4), 211–222. https://doi.org/10.1038/s44159-022-00030-6

Wolpert, D. M., & Kawato, M. (1998). Multiple paired forward and inverse models for motor control. *Neural Networks*, *11*(7), 1317–1329. https://doi.org/10.1016/S0893-6080(98)00066-5