scCancerExplorer: a comprehensive database for interactively exploring single-cell multi-omics data of human pan-cancer

Changzhi Huang[1,2,†], Zekai Liu[1,†], Yunlei Guo[1,†], Wanchu Wang[1,†], Zhen Yuan[1], Yusheng Guan[1], Deng Pan[1], Zhibin Hu[1], Linhua Sun[3]*, Zan Fu[2]*, Shuhui Bian[1,4]*

[1]State Key Laboratory of Reproductive Medicine and Offspring Health, Nanjing Medical University, Nanjing 211166, China

[2]Department of General Surgery, the First Affiliated Hospital of Nanjing Medical University, Nanjing 210029, China

[3]College of Life Sciences, Nanjing Normal University, Nanjing 210023, China

[4]Collaborative Innovation Center for Cancer Personalized Medicine, School of Public Health, Nanjing Medical University, Nanjing 211166, China

*To whom correspondence should be addressed. Email: bianshuhui@njmu.edu.cn

Correspondence may also be addressed to Zan Fu. Email: fuzan1971@njmu.edu.cn

Correspondence may also be addressed to Linhua Sun. Email: sunlh@njnu.edu.cn

[†]The authors wish it to be known that, in their opinion, the first four authors should be regarded as Joint First Authors.

ABSTRACT

Genomic, epigenomic, and transcriptomic alterations are hallmarks of cancer cells, and are closely connected. Especially, epigenetic regulation plays a critical role in tumorigenesis and progression. The growing single-cell epigenome data in cancer research provide new opportunities for data mining from a more comprehensive perspective. However, there is still a lack of databases designed for interactively exploring the single-cell multi-omics data of human pan-cancer, especially for the single-cell epigenome data. To fill in the gap, we developed scCancerExplorer, a comprehensive and user-friendly database to facilitate the exploration of the single-cell genome, epigenome (chromatin accessibility and DNA methylation), and transcriptome data of 50 cancer types. Five major modules were provided to explore those data interactively, including "integrated multi-omics analysis", "single-cell transcriptome", "single-cell epigenome", "single-cell genome", and "TCGA analysis". By simple clicking, users can easily investigate gene expression features, chromatin accessibility patterns, transcription factor activities, DNA methylation states, copy number variations, and TCGA survival analysis results. Taken together, scCancerExplorer is distinguished from previous databases with rich and interactive functions for exploring the single-cell multi-omics data of human pan-cancer. It bridges the gap between single-cell multi-omics data and the end-users, and will facilitate progress in the field of cancer research. scCancerExplorer is freely accessible via https://bianlab.cn/scCancerExplorer.

INTRODUCTION

Human cancers are characterized by molecular alterations in the genome, epigenome, and transcriptome with drastic heterogeneity, which hinder the effective clinical diagnosis and treatment (1, 2). In addition to cancer genome and transcriptome which have been extensively studied, aberrant epigenome plays a critical role in tumorigenesis and progression by affecting gene expression and genome integrity. Moreover, epigenetic modifications are potential therapeutic targets and have raised hope for developing effective cancer therapy. Several epigenetic agents have been proven for clinical treatment or in development, such as the DNA methylation inhibitors azacitidine and decitabine (3). A better understanding of the epigenetic regulation mechanism of cancer will greatly promote the development of clinical therapeutic strategies.

Single-cell multi-omics techniques have revolutionized cancer research over recent years, offering powerful tools to dissect the intricate molecular basis of human cancers. Large amounts of single-cell multi-omics data, encompassing the genome, transcriptome, and epigenome, have been continuously generated for human cancer studies (4, 5). Especially, with advanced single-cell multi-omics sequencing techniques, we and others can even simultaneously analyze the genome, epigenome, and transcriptome of the same single cell, and reveal the complicated relationships between multiple molecular layers (6–10). These studies not only provided a comprehensive atlas of human cancers but also offered a wealth of data resources for further exploration. Notably, the growing single-cell chromatin accessibility and DNA methylation data provide new opportunities for understanding human cancer from the epigenetic perspective (6, 8–16). However, analyzing and integrating the massive single-cell multi-omics data from separate studies posed significant challenges, particularly for wet-lab biologists and oncologists lacking analytical skills and adequate computing resources. Hence, integrated and user-friendly platforms are important to bridge the gap between single-cell multi-omics data and users.

Although several databases have been developed to facilitate cancer research, there is

still a lack of online databases that can meet the need to explore single-cell multi-omics

data of human pan-cancer, especially for the single-cell epigenome data (such as

chromatin accessibility and DNA methylation). For example, GEPIA2 is a great tool to

explore and visualize the gene expression profiles of TCGA data (17), which is widely

used in cancer studies, but it does not contain single-cell data. Other valuable single-

cell cancer databases, such as CancerSEA (18), TISCH2 (19), SCAR (20), and

CancerSCEM (21), focus on the single-cell transcriptome and spatial transcriptome of

cancer and lack single-cell epigenome and multi-omics integration. Although we and

other groups have published several single-cell epigenome or multi-omics databases,

such as SMARTdb (22), SCA (23), scMethBank (24), and scATAC-Ref (25), none of

them focus on human cancers. In summary, the practical needs of cancer researchers,

such as exploring single-cell ATAC-seq and DNA methylation data, and acquiring

integrated multi-omics information, cannot be met by the existing databases.

Here, we introduce scCancerExplorer (https://bianlab.cn/scCancerExplorer), an

integrated database designed to provide user-friendly functions for exploring single-

cell multi-omics data of human pan-cancer. By facilitating data mining and inspiring

novel insights into pan-cancer multi-omics data, scCancerExplorer aims to empower

researchers to decipher the complexities of human cancer and pave the way for cancer

research.

MATERIALS AND METHODS

Data collection

In total, 160 single-cell multi-omics datasets covering over 6.2 million single cells and

50 human cancer types have been collected and analyzed, involving single-cell

transcriptome, epigenome (DNA methylation and chromatin accessibility), and genome

data (copy number variation) data (Table S1). Related metadata information, such as

pathological subtype, sex, sample location, and clinical stage, was collected if available. The TCGA data from 33 cancer types, including the gene expression matrix, DNA methylation data generated using Illumina HumanMethylation450 BeadChip, mutation information, and clinical data were obtained from UCSC Xena (https://xenabrowser.net/datapages/?hub=https://gdc.xenahubs.net:443). The ATAC-seq data from TCGA project was obtained from https://gdc.cancer.gov/about-data/publications/ATACseq-AWG (26).

Data processing

Single-cell transcriptome data processing

The single-cell gene expression matrices were processed utilizing Seurat (v.4.3.0.1) (27). Briefly, quality control of the single-cell data was mainly performed according to the description in the original study. For each cell, the unique molecular identifier (UMI) count of each gene was divided by the total UMI counts of the cell and multiplied by a scale factor (default or as the original study described) before natural-log transformation. The top highly variable genes (default or as the original study described) were selected using the "FindVariableFeatures" function. The normalized data were then centered and scaled using the "ScaleData" function. Principal component analysis (PCA) was conducted on the scaled data using the highly variable genes. Subsequently, the uniform manifold approximation and projection (UMAP) was performed and employed to visualize the cell clustering result. The cell type identities were annotated based on available metadata or canonical marker genes. In principle, the cell type identity information provided by the original studies was preferentially used. Significant differentially expressed genes (DEGs) between various cell types were identified using the "FindAllMarkers" function in Seurat.

Single-cell DNA methylation data processing

For each cell, only the CpG sites (for scBS-seq data) or WCG sites (for scCOOL-seq data) with DNA methylation levels < 0.1 or > 0.9 were retained. The gene promoter

regions were defined as 1 kb upstream and 0.5 kb downstream of the transcription start

site. For each cell, only the promoter regions with at least 3 CpG or WCG sites were

retained, and the mean methylation levels within the promoter regions were calculated

to represent the methylation status of promoter regions. To plot the DNA methylation

status of each cell group, the single-cell DNA methylation data were merged by cell

group. For the CpG or WCG sites covered by multiple cells of the group, the mean

DNA methylation levels of covered cells were calculated.

Single-cell ATAC-seq data processing

To maintain maximum consistency with the original study results, only the cells present

in the metadata information provided by the original study were retained. For datasets

lacking metadata information, low-quality cells were removed mainly based on the

criteria described in the original study. For datasets that did not provide quality control

criteria in the original study, only cells with minTSS > 4 and minFrags > 1000 were

used for further analyses. Downstream data processing utilized the R package ArchR

(v.1.0.2) (28). In general, the "Arrow" file was created according to the quality control

standard and the "addDoubletScores" function of ArchR was employed to remove the

data with doublet enrichment scores > 1. The resulting "Arrow" files were used to create

the "ArchRProject". The iterative latent semantic index (LSI) dimension reduction was

performed using the "addIterativeLSI" function in ArchR. Four iterations were

executed with a clustering resolution ranging from 0.2 to 1, utilizing 15,000 to 25,000

variable features. Subsequently, the data was compressed into a two-dimensional

UMAP embedding using the "addUMAP" function from ArchR package. Peak calling

was performed on single-cell ATAC-seq data using MACS2 (v.2.2.9.1). The enrichment

of TF motifs for peaks in each cell cluster was performed using chromVAR (v.1.20.2).

The "getGroupBW" function from ArchR package was utilized to export bigwig files

with a tile size of 100 bp based on cell type. Peak-to-peak co-accessibility information

was exported using the "getCoAccessibility" function and then converted to the inter.bb

format using "bedTOBigBed" (29).

Copy number variation data processing

The single-cell copy number variation data was provided by the authors from the original studies.

TCGA survival analysis

The "lifelines" library (v.0.27.8) in Python was utilized for the survival analysis. The expression levels were categorized into "High" and "Low" groups based on the median or quantile expression value of the selected gene. The Kaplan-Meier survival curves were generated using the "KaplanMeierFitter" class in Python, and the log-rank tests were performed. Additionally, a Cox proportional hazards model was fitted using the "CoxPHFitter" class in Python to estimate the hazard ratios. The survival curves and statistical results were visualized with "matplotlib" (v.3.7.5) and "seaborn" (v.0.13.2).

TCGA DNA methylation data processing

For TCGA HumanMethylation450 data, the annotation information regarding the methylation probes was downloaded from the Illumina (https://support.illumina.com/downloads/infinium_humanmethylation450_product_fil es.html). To calculate the promoter DNA methylation levels, the gene promoter regions were defined as spanning from 1 kb upstream and 0.5 kb downstream of the transcription start site. For each sample, the DNA methylation levels for the promoter regions are calculated using the average beta values of methylation probes that fall within the gene promoter regions.

Implementation of the database

The scCancerExplorer platform is developed with Python and the Django framework (https://djangoproject.com), utilizing PostgreSQL (https://www.postgresql.org) for systematic data organization and management. The user-friendly interface is built with Angular and NG-ZORRO. The platform is hosted on an Nginx web server

(http://nginx.org) and is freely accessible without any need for registration or login. For the best user experience, scCancerExplorer is optimized for web browsers like Google Chrome, Microsoft Edge, Safari, and Mozilla Firefox, with JavaScript enabled.

DATABASE CONTENTS AND USAGE

Overall design

scCancerExplorer was designed to enable convenient exploration of single-cell multi-omics data of human pan-cancer (Figure 1) and inspire new insights into the complex landscape of human cancers. In total, multi-omics data from 160 datasets covering over 6.2 million single cells were curated and analyzed. We provided five major modules for users, including "Integrated multi-omics analysis", "Single-cell transcriptome", "Single-cell epigenome", "Single-cell genome" and "TCGA analysis". Twelve useful functions were provided, which will be described in detail below.

"Integrated multi-omics analysis" module

This module provided both single-cell multi-omics and TCGA multi-omics perspectives to learn an interested gene quickly (Figure 2). For example, users can explore the single-cell gene expression levels (Figure 2A), single-cell chromatin accessibility levels and DNA methylation levels of the promoter region of the selected gene in both normal cells and cancer cells (Figure 2B, C), the gene expression levels and promoter DNA methylation levels of both normal and cancer tissues using TCGA data (Figure 2D, E), and TCGA survival analysis results based on the expression level of the selected gene (Figure 2F) (8). If the gene being searched is a transcription factor (TF), the TF motif activity deduced from single-cell ATAC-seq data is also provided. If users want to further learn the interested gene in depth, they can use other modules that we provided for each omics below.

"Single-cell transcriptome" module

Pan-cancer analysis

With this function, a quick exploration of the integrated single-cell RNA-seq data of human pan-cancer is allowed (Figure 3A). For example, users can querying the gene expression levels of multiple interested genes in the lymphatic endothelial cells of human pan-cancer (Figure 3A) (30).

Query gene expression

In addition to the above-mentioned "Pan-cancer analysis" function, users typically need to explore a certain cancer type in depth, which can be met by the "Query gene expression" function (Figure 3B). With this function, users can easily explore the gene expression patterns of an interested gene across different cell types, and get other related information at the same time, including the cell type identification, sample locations (e.g. normal tissue, primary tumor, and metastasis), cancer stages, fractions of each cell cluster, sex information, and the differentially expressed genes (DEGs) of each cell type. Moreover, a brief introduction and links to further information for each human gene are presented.

DIY expression plot

The "DIY expression plot" function enables users to query the expression levels of multiple selected genes in multiple selected cell types and generate customized figures for visualization (Figure 3C). Multiple figure types are provided, including dot plots, heatmaps, and violin plots, which can meet most of the needs of users. Moreover, for each cell type, users can easily compare the expression levels among different sampling locations (e.g. primary tumor v.s. metastasis) different cancer stages (e.g. stage I v.s. stage III), various cancer subtypes (e.g. poorly-differentiated adenocarcinoma v.s. well-differentiated adenocarcinoma), and between male and female by simply switching options in the "Group by" select box.

Single-cell epigenome module

Focal DNA methylation plot

With this function, users can visualize the DNA methylation levels of a selected genomic region of interest (e.g. promoters) at a single CpG resolution (Figure 4A). For example, the "Tanghulu" plot displayed the demethylated region in cancer cells compared with normal cells (Figure 4A). Each row in the plot represents a cell group, with each circle denoting a CpG site.

Promoter DNA methylation plot

Users can query the DNA methylation levels of gene promoter regions at single-cell resolution, and compare them across normal tissues, primary tumors, and metastases with this module (Figure 2C).

Epigenome browser

scCancerExplorer incorporates the WashU Epigenome browser (31) to facilitate the exploration of chromatin accessibility and co-accessibility patterns (Figure 4B). Users can conveniently access specific genomic regions or genes of interest by inputting the official gene symbol or a genomic range in the search box at the top left of the browser interface. For example, we can see five potential enhancers for *LAPTM4B* (Lysosomal Protein Transmembrane 4 Beta) in ovarian cancer cells showed higher accessibility levels compared to other cell types (Figure 4B) (11). The browser interface allows users to zoom in/out, navigate to designated regions, and customize display options such as display mode (bar plot or heatmap), RGB colors, axis scales, and text labels to suit individual preferences.

TF motif activity

With this function, users can search for an interested transcription factor and obtain the motif activity score (motif deviation z-score) across different cell types calculated using single-cell ATAC-seq data (Figure 4C).

DIY ATAC-seq plot

Similar to the "DIY expression plot" module, this module enables users to easily query

the motif activities of multiple TFs across different cell types, and generate customized

figures based on their requirements (Figure 4D).

"Single-cell genome" module

This module allows users to investigate the single-cell copy number alterations (CNAs)

of human cancers. For example, users can select a cancer type (e.g. stomach cancer)

and select one or multiple patients (e.g. SC02 and SC07), and then generate the CNA

heatmap (Figure 5A) (8). The cancer cells are sorted by genetic lineage if the lineage

information is available.

"TCGA analysis" module

Survival analysis

This function provides survival analysis for 33 cancer types using TCGA data (Figure

5B). Notably, users can categorize patients based on multiple information, including

gene expression levels (e.g. above median v.s. below median), gene mutation states

(with mutation v.s. without mutation), pathological types (all types or certain subtype),

and cancer stages (all stages or certain stage). For example, users can group patients by

the expression levels of *TPM2* (Tropomyosin 2) in all colon adenocarcinoma patients

or only in patients with *APC* (APC regulator of WNT signaling pathway) mutation,

respectively (Figure 5B).

ATAC-seq browser

With the "ATAC-seq browser" function, users can explore the open chromatin regions

using TCGA ATAC-seq data. They can visualize the chromatin accessibility pattern of

a gene of interest. For example, the open chromatin peaks around the promoter region

of *MISP* (Mitotic Spindle Positioning), which are highly expressed in gastric cancer (8),

can be browsed with this function (Figure 5C).

TCGA promoter DNA methylation

Users can query the DNA methylation levels of gene promoter regions for both normal tissues and tumor tissues using the TCGA DNA methylation data in this function (Figure 5D).

DISCUSSION

The interplay between different molecular layers is critical for cancer progression and metastasis. Integrated single-cell multi-omics analyses are valuable for unraveling the complexities of cancer biology and facilitating the development of personalized therapeutic strategies. To the best of our knowledge, scCancerExplorer is the most comprehensive database for exploring single-cell multi-omics data of human pan-cancer currently.

First, by preprocessing a large number of single-cell multi-omics data and providing rich interactive tools for exploring them, we provide an important bridge between the valuable but hard-to-process resources and cancer researchers. The 5 major modules and 12 useful functions meet most of the requirements of users for exploring both single-cell genome, epigenome, and transcriptome data, and TCGA data.

Second, our featured module "Integrated multi-omics analysis" integrates multi-omics data of each gene on one web page, including TCGA bulk RNA-seq data, single-cell RNA-seq data, TCGA DNA methylation data, single-cell DNA methylation data, single-cell chromatin accessibility data, and TCGA survival analysis results. This module provides comprehensive and convenient knowledge for users to learn an interested gene from multiple perspectives, and helps users gain clues for further investigations.

Third, several customizable functions and publishing-ready figures were provided to

meet the personalized requirements of users. For example, with the "DIY expression

plot" function, users can select multiple genes and cell types and designate their order

shown in the generated figures, download the editable PDF files, and use the

publishing-level figures in their study. Additionally, by simply switching options in the

"Group by" select box, users can easily compare the expression levels between primary

tumors and metastases, pre-treatment and post-treatment tumors, and various cancer

subtypes.

Fourth, not only single-cell multi-omics data, but also TCGA multi-omics data were

collected and analyzed, including bulk RNA-seq data, DNA methylation 450K data,

and bulk ATAC-seq data. Moreover, we provide customizable TCGA survival analysis,

enabling users can not only group the patients according to the expression levels of the

selected gene, but also select patients by gene mutation states (e.g. those with TP53

mutation), pathological subtypes, and cancer stages.

In summary, scCancerExplorer is a powerful database for convenient data mining by

simple clicking, and gaining novel insights into human pan-cancer. We believe

scCancerExplorer will be one of the most useful and preferred databases for cancer

researchers. We will continually develop and maintain the database for the benefit of

broad cancer biologists and wet-lab researchers.

DATA AVAILABILITY

The database is available at https://bianlab.cn/scCancerExplorer.

ACKNOWLEDGEMENTS

We acknowledge Prof. Jingchu Luo (Peking University) for giving advices for constructing databases. We thank Prof. William Greenleaf (Stanford University) and his group for providing help when processing single-cell ATAC-seq data. All authors read and approved the final manuscript.

FUNDING

This work was supported by the National Natural Science Foundation of China (grant numbers 82173059, 82172956), the Young Elite Scientists Sponsorship Program by China Association for Science and Technology (CAST) (grant number 2020QNRC001), and research start-up funding from Nanjing Medical University (grant number KY116RC20200007).

CONFLICT OF INTEREST

The authors declare that they have no competing interests.

REFERENCES

1. Flavahan,W.A., Gaskell,E. and Bernstein,B.E. (2017) Epigenetic plasticity and the hallmarks of cancer. *Science*, **357**, eaal2380.

2. Hanahan,D. (2022) Hallmarks of cancer: new dimensions. *Cancer Discov.*, **12**, 31–46.

3. Bates,S.E. (2020) Epigenetic therapies for cancer. *N. Engl. J. Med.*, **383**, 650–663.

4. Aran,D. (2023) Single-cell RNA sequencing for studying human cancers. *Annu. Rev. Biomed. Data Sci.*, **6**, annurev-biodatasci-020722-091857.

5. Lim,B., Lin,Y. and Navin,N. (2020) Advancing cancer research and medicine with single-cell genomics. *Cancer Cell*, **37**, 456–470.

6. Bian,S., Hou,Y., Zhou,X., Li,X., Yong,J., Wang,Y., Wang,W., Yan,J., Hu,B., Guo,H., *et al.* (2018) Single-cell multiomics sequencing and analyses of human colorectal cancer. *Science*, **362**, 1060–1063.

7. Zhou,Y., Bian,S., Zhou,X., Cui,Y., Wang,W., Wen,L., Guo,L., Fu,W. and Tang,F. (2020) Single-cell multiomics sequencing reveals prevalent genomic alterations in tumor stromal cells of human colorectal cancer. *Cancer Cell*, **38**, 818-828.e5.

8. Bian,S., Wang,Y., Zhou,Y., Wang,W., Guo,L., Wen,L., Fu,W., Zhou,X. and Tang,F. (2023) Integrative single-cell multiomics analyses dissect molecular signatures of intratumoral heterogeneities and differentiation states of human gastric cancer. *Natl. Sci. Rev.*, **10**, nwad094.

9. Gaiti,F., Chaligne,R., Gu,H., Brand,R.M., Kothen-Hill,S., Schulman,R.C., Grigorev,K., Risso,D., Kim,K.-T., Pastore,A., *et al.* (2019) Epigenetic evolution and lineage histories of chronic lymphocytic leukaemia. *Nature*, **569**, 576–580.

10. Fan,X., Lu,P., Wang,H., Bian,S., Wu,X., Zhang,Y., Liu,Y., Fu,D., Wen,L., Hao,J., *et al.* (2022) Integrated single-cell multiomics analysis reveals novel candidate markers for prognosis in human pancreatic ductal adenocarcinoma. *Cell Discov.*, **8**, 13.

11. Regner,M.J., Wisniewska,K., Garcia-Recio,S., Thennavan,A., Mendez-Giraldez,R., Malladi,V.S., Hawkins,G., Parker,J.S., Perou,C.M., Bae-Jump,V.L., *et al.* (2021) A multi-omic single-cell landscape of human gynecologic malignancies. *Mol. Cell*, **81**, 4924-4941.e10.

12. Terekhanova,N.V., Karpova,A., Liang,W.-W., Strzalkowski,A., Chen,S., Li,Y., Southard-Smith,A.N., Iglesia,M.D., Wendl,M.C., Jayasinghe,R.G., *et al.* (2023) Epigenetic regulation during cancer transitions across 11 tumour types. *Nature*, **623**,

432–441.

13. Zhu,Q., Zhao,X., Zhang,Y., Li,Y., Liu,S., Han,J., Sun,Z., Wang,C., Deng,D., Wang,S., *et al.* (2023) Single cell multi-omics reveal intra-cell-line heterogeneity across human cancer cell lines. *Nat. Commun.*, **14**, 8170.

14. Becker,W.R., Nevins,S.A., Chen,D.C., Chiu,R., Horning,A.M., Guha,T.K., Laquindanum,R., Mills,M., Chaib,H., Ladabaum,U., *et al.* (2022) Single-cell analyses define a continuum of cell state and composition changes in the malignant transformation of polyps to colorectal cancer. *Nat. Genet.*, **54**, 985–995.

15. Liu,Z., Hu,Y., Xie,H., Chen,K., Wen,L., Fu,W., Zhou,X. and Tang,F. (2024) Single-cell chromatin accessibility analysis reveals the epigenetic basis and signature transcription factors for the molecular subtypes of colorectal cancers. *Cancer Discov.*, **14**, 1082–1105.

16. Granja,J.M., Klemm,S., McGinnis,L.M., Kathiria,A.S., Mezger,A., Corces,M.R., Parks,B., Gars,E., Liedtke,M., Zheng,G.X.Y., *et al.* (2019) Single-cell multiomic analysis identifies regulatory programs in mixed-phenotype acute leukemia. *Nat. Biotechnol.*, **37**, 1458–1465.

17. Tang,Z., Kang,B., Li,C., Chen,T. and Zhang,Z. (2019) GEPIA2: an enhanced web server for large-scale expression profiling and interactive analysis. *Nucleic Acids Res.*, **47**, W556–W560.

18. Yuan,H., Yan,M., Zhang,G., Liu,W., Deng,C., Liao,G., Xu,L., Luo,T., Yan,H., Long,Z., *et al.* (2019) CancerSEA: a cancer single-cell state atlas. *Nucleic Acids Res.*, **47**, D900–D908.

19. Han,Y., Wang,Y., Dong,X., Sun,D., Liu,Z., Yue,J., Wang,H., Li,T. and Wang,C. (2023) TISCH2: expanded datasets and new tools for single-cell transcriptome analyses of the tumor microenvironment. *Nucleic Acids Res.*, **51**, D1425–D1431.

20. Deng,Y., Chen,P., Xiao,J., Li,M., Shen,J., Qin,S., Jia,T., Li,C., Chang,A., Zhang,W., *et al.* (2024) SCAR: single-cell and spatially-resolved cancer resources. *Nucleic Acids Res.*, **52**, D1407–D1417.

21. Zeng,J., Zhang,Y., Shang,Y., Mai,J., Shi,S., Lu,M., Bu,C., Zhang,Z., Zhang,Z., Li,Y., *et al.* (2022) CancerSCEM: a database of single-cell expression map across various human cancers. *Nucleic Acids Res.*, **50**, D1147–D1155.

22. Liu,Z., Yuan,Z., Guo,Y., Wang,R., Guan,Y., Wang,Z., Chen,Y., Wang,T., Jiang,M. and Bian,S. (2024) SMARTdb: an integrated database for exploring single-cell multi-

omics data of reproductive medicine. *Genomics Proteomics Bioinformatics*, 10.1093/gpbjnl/qzae005.

23. Pan,L., Parini,P., Tremmel,R., Loscalzo,J., Lauschke,V.M., Maron,B.A., Paci,P., Ernberg,I., Tan,N.S., Liao,Z., *et al.* (2024) Single Cell Atlas: a single-cell multi-omics human cell encyclopedia. *Genome Biol.*, **25**, 104.

24. Zong,W., Kang,H., Xiong,Z., Ma,Y., Jin,T., Gong,Z., Yi,L., Zhang,M., Wu,S., Wang,G., *et al.* (2022) scMethBank: a database for single-cell whole genome DNA methylation maps. *Nucleic Acids Res.*, **50**, D380–D386.

25. Qian,F.-C., Zhou,L.-W., Zhu,Y.-B., Li,Y.-Y., Yu,Z.-M., Feng,C.-C., Fang,Q.-L., Zhao,Y., Cai,F.-H., Wang,Q.-Y., *et al.* (2024) scATAC-Ref: a reference of scATAC-seq with known cell labels in multiple species. *Nucleic Acids Res.*, **52**, D285–D292.

26. Corces,M.R., Granja,J.M., Shams,S., Louie,B.H., Seoane,J.A., Zhou,W., Silva,T.C., Groeneveld,C., Wong,C.K., Cho,S.W., *et al.* (2018) The chromatin accessibility landscape of primary human cancers. *Science*, **362**, eaav1898.

27. Hao,Y., Hao,S., Andersen-Nissen,E., Mauck,W.M., Zheng,S., Butler,A., Lee,M.J., Wilk,A.J., Darby,C., Zager,M., *et al.* (2021) Integrated analysis of multimodal single-cell data. *Cell*, **184**, 3573-3587.e29.

28. Granja,J.M., Corces,M.R., Pierce,S.E., Bagdatli,S.T., Choudhry,H., Chang,H.Y. and Greenleaf,W.J. (2021) ArchR is a scalable software package for integrative single-cell chromatin accessibility analysis. *Nat. Genet.*, **53**, 403–411.

29. Kent,W.J., Zweig,A.S., Barber,G., Hinrichs,A.S. and Karolchik,D. (2010) BigWig and BigBed: enabling browsing of large distributed datasets. *Bioinformatics*, **26**, 2204–2207.

30. Li,J., Wang,D., Tang,F., Ling,X., Zhang,W. and Zhang,Z. (2024) Pan-cancer integrative analyses dissect the remodeling of endothelial cells in human cancers. *Natl. Sci. Rev.*, 10.1093/nsr/nwae231.

31. Li,D., Purushotham,D., Harrison,J.K., Hsu,S., Zhuo,X., Fan,C., Liu,S., Xu,V., Chen,S., Xu,J., *et al.* (2022) WashU Epigenome Browser update 2022. *Nucleic Acids Res.*, **50**, W774–W781.

Figure 1

scCancerExplorer

Data curation

>**6.2 million**
Single cells

50
Cancer types

160
Datasets

4
Omics

>**10K**
TCGA samples

Database construction

- **Database**   PostgreSQL
- **Server**   Python
    Django
- **Front end**   Angular
    NG-ZORRO

User interface

5 major modules & 12 functions

1 **Integrated multi-omics analysis**

- Single-cell RNA-seq
- Single-cell promoter DNAme
- TF motif activity (scATAC-seq)
- TCGA RNA-seq
- TCGA survival analysis
- TCGA promoter DNAme

2 **Single-cell transcriptome**

- Pan-cancer analysis
- Query gene expression
- DIY expression plot

3 **Single-cell epigenome**

- Focal DNAme plot
- Promoter DNAme plot
- Epigenome browser
- TF motif activity
- DIY ATAC-seq plot

4 **Single-cell epigenome**

- Copy number variation

5 **TCGA analysis**

- Survival analysis
  (mutation + gene expression)
- ATAC-seq browser
- Promoter DNAme plot

467 **Figure 1. A schematic diagram illustrating the data curation, web construction,**

468 **and user interface of scCancerExplorer.** DNAme, DNA methylation.

Figure 2

A Single-cell gene expression

CMTM3 (stomach cancer)

B Single-cell promoter chromatin accessibility

CMTM3 (stomach cancer)

C Single-cell promoter DNA methylation

CMTM3 (stomach cancer)

D TCGA gene expression

CMTM3 (STAD)

*** (P value < 0.001, Wilcoxon rank-sum test)

E TCGA promoter DNA methylation

CMTM3 (STAD)

NS (Wilcoxon rank-sum test)

F TCGA survival analysis

CMTM3 (STAD, overall survival)

High (n=191)
Low (n=190)
Logrank P: 0.0123
HR(high): 1.50

Figure 2. An example for exploring an interested gene with the "Integrated multi-omics analysis" module.

(A-C) The single-cell gene expression levels (A), promoter chromatin accessibility levels (B), and promoter DNA methylation levels (C) of the selected gene across various cell types in stomach cancer (dataset ID: HRA001689).

(D-E) The gene expression levels (D) and promoter DNA methylation levels (E) of the selected gene in normal tissues and cancer tissues in TCGA stomach adenocarcinoma dataset.

(F) Overall survival analysis using TCGA stomach adenocarcinoma dataset shows that the patients with lower expression levels of the selected gene (<median value) have significantly poorer prognosis.

ADC, adenocarcinoma. NEC, neuroendocrine carcinoma. HAS, hepatoid adenocarcinoma of stomach. *CMTM3*, CKLF Like MARVEL Transmembrane Domain Containing 3. STAD, stomach adenocarcinoma. NS, non-significant.

Figure 3

Module 2: Single-cell transcriptome

A — Pan-cancer analysis

B — Query gene expression

C — DIY expression plot

Figure 3. Examples for using the "Single-cell transcriptome" module.

(A) The uniform manifold approximation and projection (UMAP) plot shows the subclusters of endothelial cells of human pan-cancer. The dot plot shows the expression levels and expressed percentages of the selected genes in the lymphatic endothelial cells (E18.lymphatics.PROX1).

(B) With "Query gene expression" function, the relative expression levels of selected gene (*EPCAM*) across various cell types in colorectal cancer (dataset ID: HRA000201) are shown in UMAP plot and violin plot. Other related information, such as cell type identities, sampling locations, cell numbers and fractions of each cell type, and tables for differentially expressed genes, were also provided.

(C) With the "DIY expression plot" function, the relative expression levels of multiple selected genes in multiple selected cell groups of colorectal cancer (dataset ID: HRA000201) are shown in three figure types, including dot plot, violin plot, and heatmap. For the dot plot, the expression levels of different cell types from different sampling locations (e.g. primary tumor v.s. metastasis) are plotted by selecting the "Cell type & location" options in the "Group by" select box.

UMAP, uniform manifold approximation and projection. PBMC, peripheral blood mononuclear cell. Cancer types: cSCC, cutaneous squamous cell carcinoma; THCA, thyroid carcinoma; TGCT, testicular germ cell tumor; STAD, stomach adenocarcinoma; SKCM, skin cutaneous melanoma; RCC, renal cell carcinoma; PRAD, prostate cancer; PAAD, pancreatic adenocarcinoma; OV, ovarian cancer; NPC, nasopharyngeal cancer; LUAD, lung adenocarcinoma; LIHC, liver hepatocellular carcinoma; HNSC, head and neck squamous cell carcinoma; GM, glioma; ESCA, esophageal carcinoma; CRC, colorectal cancer; CHOL, cholangiocarcinoma; CESC, cervical squamous cell carcinoma and endocervical adenocarcinoma; BRCA, breast carcinoma.

Figure 4

Module 3: Single-cell epigenome

A

Focal DNA methylation plot

DNA demethylation region in CRC
(chr2:155395851-155396350)

Cancer lineage
- CRC01-A0
- CRC04-A0

Normal epithelia
- CRC01-NC
- CRC04-NC

Genome

DNA methylation level
100%
80%
60%
40%
20%
0%

C

TF motif activity - LEF1

UMAP_2
UMAP_1

TF motif activity
Low   High

TF motif activity

Dysfunctional CD8+ T
Early dysfunctional CD8+ T
Effector CD8+ T (T)
Effector CD8+ T (T/B)
Effector CD8+ T (T/N)
Memory/effector CD4+ T
Naive CD4+ T
Tregs

B

Epigenome browser

Chromatin accessibility (GSE173682-Ovarian serous cystadenocarcinoma)

Tools:

chr8:9733556-97785057

◄ +5 +1 +⅓ −⅓ −1 −5 ►

System

Viewing a 51.5 Kb region in 880px, 1 pixel spans 59 bp   Metadata »

refGene   LAPTM4B

Ruler   q22.1

chr8   97740K   97750K   97760K   97770K   97780K

Cancer (epithelial)
Endothelial
Fibroblast
T cell
B cell
Coaccessibility

D

DIY ATAC-seq plot

Violin plot

Dysfunctional CD8+ T
Effector CD8+ T (T/B)
Naive CD4+ T

TBX5   RREB1   LEF1

TF motif activity
Low   High

Heatmap

TBX5
RREB1
LEF1

Naive CD4+ T   Effector CD8+ T (T/B)   Dysfunctional CD8+ T

TF motif activity
Low   High

Figure 4. Examples for using "Single-cell epigenome" module.

(A) The "Tanghulu" plot displays DNA demethylation regions in colorectal cancer cells

(dataset ID: GSE97693), with each circle representing a CpG site. White dots represent

unmethylated sites, while black dots represent methylated sites. Gray dots at the bottom

indicate covered CpG sites within selected regions in selected cells.

(B) Screenshot of the epigenome browser showing the chromatin accessibility levels

around the transcription start site of the selected gene (*LAPTM4B*, Lysosomal Protein

Transmembrane 4 Beta) of multiple cell types from ovarian cancer (dataset ID:

GSE173682). The gray regions illustrate the potential enhancers in cancer cells.

(C) Querying the motif activity of the transcription factor LEF1 across various cell

types in kidney renal clear cell carcinoma (dataset ID: GSE181062) with the "TF motif

activity" function.

(D) Querying the motif activity of multiple transcription factor in multiple cell types in

kidney renal clear cell carcinoma (dataset ID: GSE181062) with "DIY ATAC-seq plot"

function.

Figure 5

Figure 5. Examples for using "Single-cell genome" module and "TCGA analysis"

module

(A) The heatmaps showing the copy number variations of stomach cancer patients

(dataset ID: HRA001689).

(B) All patients (left) or only the patients with *APC* mutation (right) in TCGA colon

adenocarcinoma dataset were selected to perform survival analysis according to the

expression levels of the selected gene (*TPM2*, Tropomyosin 2).

(C) Browsing the chromatin accessibility pattern of the selected gene (*MISP*, Mitotic

Spindle Positioning) in TCGA stomach adenocarcinoma ATAC-seq dataset with the

"ATAC-seq browser" function.

(D) The promoter DNA methylation levels of the selected gene (*TFF3*, Trefoil Factor

3) in normal tissues and cancer tissues in TCGA colon adenocarcinoma dataset.

COAD, colon adenocarcinoma.

Table S1. The information of collected datasets.