A Message Passing Framework for Precise Cell State Identification with scClassify2

Wenze Ding[1,2,3,+] ,Yue Cao[1,2,3,4+] , Xiaohang Fu[1,2,3,4,5], Marni Torkel[1,2,3], Jean Yang[1,2,3,4*]

[1] School of Mathematics and Statistics, Faculty of Science, University of Sydney, NSW 2006, NSW, Australia
[2] Sydney Precision Data Science Centre, University of Sydney, Sydney, NSW 2006, Australia
[3] Charles Perkins Centre, University of Sydney, Sydney, NSW 2006, Australia
[4] Laboratory of Data Discovery for Health Limited (D[2]4H), Science Park, Hong Kong SAR, China
[5] School of Computer Science, The University of Sydney, NSW 2006, Australia.

[+] Contributed equally
* Corresponding author (jean.yang@sydney.edu.au)

Abstract

In single-cell analysis, the ability to accurately annotate cells is crucial for downstream exploration. To date, a wide range of approaches have been developed for cell annotation, spanning from classic statistical models to the latest large language models. However, most of the current methods focus on annotating distinct cell types and overlook the identification of sequential cell populations such as transitioning cells. Here, we propose a message passing neural network based cell annotation method, scClassify2, to specifically focus on adjacent cell state identification. By incorporating prior biological knowledge through a novel dual-layer architecture and employing ordinal regression and conditional training to differentiate adjacent cell states, scClassify2 achieves superior performance compared to other state-of-the-art methods. In addition to single-cell RNA-sequencing data, scClassify2 is generalizable to annotation from different platforms including subcellular spatial transcriptomics data. To facilitate ease of use, we provide a web server hosting over 30 human tissues.

Keywords: scRNA-seq, cell state identification, MPNN, ordinal regression, dual layer architecture

Introduction

Leveraging advancements in sequencing technologies, single-cell transcriptomics has revolutionised biological and medical research by offering unprecedented opportunities to observe gene expression across the entire transcriptome at cellular resolution[1–5]. A fundamental task in single-cell research is cell annotation, as understanding the identity of cells is key to further downstream analysis[6–8]. Current cell annotation tasks are based on two main categories of approaches, supervised and unsupervised (including some semi-supervised ones)[9–16]. Firstly, with an unsupervised approach, the process typically involves clustering the query data into groups

based on their molecular characteristics such as gene expression. This is then followed by
annotating cells from each group via marker genes analysis. The alternative approach is supervised
classification, where a set of cell expression data and their corresponding known cell type labels are
used as the training or reference data to build a model. The model can then be used to annotate cell
types in query or unseen datasets.

Although numerous approaches for cell type annotation exist, a significant portion of these focuses
on discrete and non-sequential cell subpopulations and are not designed to effectively model the
relationship of the transition between cell states. In the biological system, many processes often
involve cell transitions, such as human preimplantation embryo development[17] and T cell
differentiation during infection[18]. In contrast to non-sequential cell type annotation problems,
sequential cell states are typically more challenging due to the similar nature between adjacent cell
states. There is a gap of existing approaches specially designed to account for cell state transition
and thus effectively discriminate adjacent cell states remains a challenge in current cell
annotation[19,20].

Annotation between different single-cell expression data is subject to dataset or batch effect, where
the distribution of gene expression varies across datasets due to technical and biological differences
even after log transformation. This makes the generalizability of the single-cell classification model
for cell annotation a persistent challenge. Selected classification methods such as CHETAH[21],
scLearn[22], scMap[23] and scTyper[24] use correlation-based distance instead of Euclidean distance to
match between query cells and training cells as correlation is unit independent. Other strategies
involve using data integration strategies to find common embeddings[25,26] between the query and
reference. However, this entails additional computational expenses and needs to be repeated for
each query dataset of interest. Some machine-learning-based approaches also tried to learn the
generalised cell identity annotations from one experiment to another by semi-supervised
training[15,16]. More recently, pre-trained models, especially large language models (LLMs) have
emerged as the latest state-of-arts tools in multiple disciplines. LLMs are characterised by their
ability to generalise. Methods have applied LLMs to single cell research including Geneformer[27]
and scGPT[28]. However, these models require computationally intensive training based on a massive
number of databases and require additional adaptation to optimise for specific tasks.

Here, we proposed scClassify2, a novel framework for adjacent cell state identification with a
transferable model across platforms. This is achieved with three key innovations. Firstly, the
transferable component is achieved by adapting our recent cross-platform biomarker strategies [29]
which identifies reference-free markers by examining log-ratio of expression values in multiple
samples to capture consistent relationship between two genes. The relationship between genes is
shown to be more stable across datasets compared to individual gene expression. Secondly, we use
a dual layer architecture to enable joint learning from both the expression information and gene co-
expression pattern derived from the log-ratio of genes. Specifically, to capture the gene co-
expression pattern as well as the relationship between states, we utilised a type of graph neural
network (GNN) named message passing neural network (MPNN) for the first time in single cell
research. MPNN incorporates both node and edge information[30], unlike other types of GNN that
focus on node features while ignoring edge information. Thirdly, to identify adjacent cell state
transition, we adopt ordinal regression as the classifier of the network with a conditional training
procedure. Using eight diverse datasets, we show our transferable dual layer model out-performed

other cell annotation methods on transitional cell state identification tasks. Our framework is
generalizable for both cell type and cell states annotation including spatially resolved data. A
catalogue framework of cell state annotations containing pre-train models for various human tissues
is made available via a user-friendly web server
(https://shiny.maths.usyd.edu.au/scClassify_catalogue/) as a community resource.

Results

scClassify2 learns expression topology by integrating prior biological information through message passing network

We introduce scClassify2, which provides a generalizable cell annotation framework for sequential
cell state identification with a transferable model across platforms. With the increased number of
perturbation studies, this new extension of scClassify is specifically designed to recognise the
inherent order of cell state. In our previous study, our scClassify captures the hierarchical nature of
the cell types through a cell type tree[31]. To further increase our capacity to effectively distinguish
subtle cell types or cell states differences, we used a dual-layer design with a type of graphical
neural network called message passing neural network (MPNN). We chose MPNN as the backbone
due to its ability to capture both node and edge information as well as its flexibility and scalability
[32–35]. Based on MPNN, we encode each cell as a graph and employ a dual-layer deep learning
approach, as illustrated in Fig. 1. The dual-layer design allows the integration of two levels of
information in the network, i) log-ratio of pairwise gene expression counts modelled as edge and ii)
biological knowledge derived from gene co-expression modelled as node. This allows information
to propagate among genes across connecting edges and captures subtle gene expression topology of
different cell states including gene co-expression. We used the ratio of gene expression as it is
shown to be relatively more stable across datasets compared to individual gene expression [29].

To assess the benefit of additional gene information in enhancing cell state annotation, we
compared the single-layer mode with the dual-layer mode, where the former relies solely on
expression data. As illustrated in Fig. 2a, the integration of biological information into gene
representations via the dual-layer architecture yields higher accuracy for sequential cell state
identification compared to no information (e.g., the accuracy of using one-hot vectors versus zero
vectors is 0.63 versus 0.86). Moreover, we checked the cell embeddings captured by MPNN
correspondingly (Fig. 2b) and found dual-layer information could help the neural network recognize
and construct specific embedding patterns of subtly different cell states much better.

We further investigated model performance using various implementations to capture the gene co-
expression pattern. We found the performance of cell state identification could be further enhanced
by utilising distributed gene representations as node embeddings. For instance, as depicted in Fig.
2c, the accuracy of cell state identification increases from 0.86 when using one-hot vectors to 0.95
when employing vectors from Gene2vec. Such distributed gene representations, derived from
embedding methods like Gene2vec, scEMT, and scSpectra, estimate gene regulation networks by
capturing gene co-expression patterns from large-scale transcriptome-wide data. Gene2vec, for
example, derives the pattern using nearly 1000 datasets from GEO. Based on the performance of
these embedding methods, we implemented Gene2Vec in scClassify2 to embed each gene into a
node vector with 200 dimensions.

scClassify2 uses ordinal regression to effectively identify adjacent cell states

Given the many biological processes that involve transitional cell states it is important to capture the sequential nature between transitional cell states, scClassify2 introduced an ordinal regression layer in the model and a novel training procedure based on the conditional probability distribution of adjacent cell states.

To demonstrate its effectiveness, we compared scClassify2 with a conventional multi-classification layer on a mouse gastrulation embryonic development cell state dataset. Fig. 2d highlights the improved performance of the ordinal regression with a cell state prediction accuracy of 0.93 compared to 0.82 of the conventional multi-classification. Notably, the multi-classification model had trouble identifying E6.75. It only correctly identified ~30% of E6.75 and incorrectly predicted over 40% as E7.0. In contrast, the cell classification model based on ordinal regression in scClassify2 is able to correctly identify almost 95% of the E6.75 as E6.75 cells (Fig. 2e). Given the subtle differences in gene expression profiles along adjacent cell states, the use of ordinal regression and the conditional probability distribution between states underscores the benefits of learning the underlying relationship between the cell states.

scClassify2 outperforms other advanced approaches for sequential cell state identification

We compared the performance of scClassify2 with our previous version, as well as three other state-of-the-art classification methods sigGCN, scGCN, and scGPT, across eight datasets (Table S1) on sequential cell state (Fig.3). scClassify2 represents a significant improvement over our previous work, scClassify, evident across all eight datasets. For example, on dataset 8, scClassify2 achieves a prediction accuracy of 80.82 ± 2.14% compared to 66.44 ± 4.19% for scClassify. When compared with other state-of-the-art graph neural network based methods such as sigGCN and scGCN, scClassify2 demonstrates consistent performance advantages across all datasets. For example, as shown in Fig.3, scClassify2 achieves an accuracy of 88.91 ± 1.73%, outperforming sigGCN and scGCN with 79.32 ± 1.76% and 77.50 ± 7.17% respectively on dataset 3. Notably, scClassify2 outperforms scGPT, the latest cell embedding method using generative artificial intelligence. For example, on dataset 1, scClassify2 achieves an accuracy of 94.50 ± 0.39% compared to 93.02 ± 0.42% for scGPT. scGPT is pre-trained on thousands of information, a repository of over 33 million cells, providing it with a vast amount of prior knowledge. In contrast, scClassify2 is trained on specific tissue dataset, which provides it with the flexibility of tailoring the reference dataset than generalised models.

Broad applicability of scClassify2 including subcellular spatial transcriptomics data

To assess the applicability of scClassify2 on other biotechnology platforms, we tested it on a breast cancer dataset generated by a subcellular spatial transcriptomics (SST) platform, Xenium. SST is the latest spatial technology in the new era of spatial omics sequencing. We firstly applied BIDCell, a recently published state-of-the-art segmentation algorithm, to delineate individual cells. As illustrated in Fig. 4a-d, scClassify2 worked well even for scenarios without sequential relationships among cell types and achieved an identification precision of around 0.92 when compared to scClassify. Furthermore, we found the prediction accuracy of scClassify2 is relatively consistent across spatial regions of the breast cancer slide (Fig.4e-g), while slightly fluctuating among different cell types (Fig. 4h). Our findings prove scClassify2 as a cell type identification method with broad applicability that can be seamlessly applied to SST data.

179 scClassify2 provides catalogue for convenient single cell annotation
To provide a resource for the scientific community, we developed a user-friendly web server called
scClassify-catalogue, offering a comprehensive catalogue of scClassify2 models trained from
datasets covering almost 1,000 cell types and 30 tissue types (Fig. 5a). Traditional web portals often
present multiple non-integrated references for the same tissue and place overhead on the users with
the task of experimenting with multiple references. In contrast, scClassify-catalogue directly
delivers annotation results for the selected tissue within a relatively short time. The input of
scClassify-catalogue is flexible and allows either the direct output from 10x cell ranger software, or
a csv file or h5ad file containing the gene expression matrix (Fig. 5b). Once the job is submitted, a
job ID will be made available (Fig. 5c-d). A file containing the predicted outcome as well as an
HTML file will be emailed to the email address entered by the user once the job finishes. The
HTML file visualises the predicted cell type such that the user can easily check the prediction result
(Fig. 5e).

Discussion

In this study, we introduce scClassify2, a cell state identification method based on log-ratio values
of gene expression, a message passing framework with dual-layer architecture and ordinal
regression. scClassify2 effectively distinguishes adjacent cell states with similar gene expression
profiles. Our comprehensive evaluation demonstrates the superior performance of scClassify2
compared to other state-of-the-art methods including scGPT, sigGCN and scGCN. Moreover,
scClassify2 can be applied for cell annotation tasks on SST data. To enhance its accessibility for
researchers, we have developed a user-friendly web server equipped with pre-trained models for
over 30 tissues.
201
The integration of dual-layer learning which combines expression data with prior biological
knowledge represents an innovative strategy to incorporate prior knowledge. As intended, relevant
additional information leads to improved prediction performance. Using distributed gene
representations such as Gene2vec, scETM and scSpectra as node embedding lead to further
enhancement in performance. These representations estimate gene regulation networks by capturing
gene co-expression patterns from transcriptome-wide data and play a critical role in enabling the
network to discern subtle high-dimensional expression pattern disparities among neighbouring cell
states. Interestingly, the results suggest that MPNN is quite an effective learning model as the
simpler gene embeddings from Gene2vec is sufficient to achieve best performance compared to
more comprehensive and detailed association information from scETM and scSpectra.
212
The distinct efficacy of MPNN in comparison to other graph neural network architectures (Fig.S1)
lies in its unique message passing mechanism, enabling nodes within the graph to exchange
information along edges and influence neighbouring nodes. In contrast, Graph Convolutional
Network (GCN) rely solely on aggregated signals within each node for self-update, potentially
limiting their effectiveness. Despite attempts to augment GCN with attention mechanisms, such as
Graph Attention Network (GAT) and graph transformer, they still fall short of MPNNs due to their
inherent lack of message passing and propagation. This crucial process is indispensable for
capturing subtle gene expression differences among adjacent cell states. With genes as nodes and
pairwise log-ratio values of gene expression counts as edges, we speculate the graph itself mimics
the whole signal pathway network within a cell, where messages of different layers computed by

MPNN establish bridges facilitating gene communication akin to regulatory molecules in biological
systems.

Since gene expression profile exhibits only subtle differences along adjacent cell states (Fig.1b), the
improvement from multi-classification to ordinal regression suggests establishing a comprehensive
consistency of gene expression distributions from different cell states rather than separately
assigning them could leverage the nature of cell state evolution by using conditional probability
among them and thus results in better identification.

We have shown that besides scRNA-seq, scClassify2 is directly applicable on SST. This offers the
potential to continuously generate additional pre-trained models within the catalogue to
accommodate other forms of spatial datasets including spatial proteomics, imaging mass cytometry
(IMC) and spatial transcriptomics data. Spatial proteomics and IMC, different to transcriptomics
data, sequence selective panels of genes containing only a few hundred genes. This requires some
special adaptation strategy of the pre-trained models such as subsetting the models to the gene
panels.

In summary, we present scClassify2, a single-cell annotation tool with an emphasis to identify
sequential cell states in an ordinal manner that is applicable to both scRNA-seq and SST data. As a
resource for the community, we have constructed a dedicated web server with pre-trained
references available at (https://shiny.maths.usyd.edu.au/scClassify_catalogue/). Our work
contributes to the community by alleviating the laborious process of selecting appropriate reference
data and the requirement of computational infrastructure such as GPUs.

Material & Methods

Data collection

We included eight diverse scRNA-seq datasets (Table S1) which not only provide highly credible
cell states of certain sequential biological processes but also have been cited by other cell trajectory
research for performance evaluation. The datasets covered both human and mouse, different tissue
types and cell types, diseased and healthy. For example, mouse gastrulation embryo dataset [36] was
found at NCBI Gene Expression Omnibus (GEO: GSE171588). To control variables and focus on
cell state classification, we only collected "Epiblast" cells (13377 in total). According to embryo
development time, these cells are   naturally divided into 6 states, i.e., E6.5 (17.01%), E6.75
(6.40%), E7.0 (37.89%), E7.25 (31.06%), E7.5 (6.91%) and E7.75 (1.73%). A detailed distribution
of these cells could be found at Fig2a. We filtered cells which expressed less than 100 genes and
genes which were expressed by less than 10 cells. No additional processing was conducted after
collection and raw unnormalized expression count matrix was directly used by scClassify2.

Cell Graph construction

For each cell graph constructed by scClassify2, the input features include embedded nodes with
gene representation and encoded edges with pairwise log-ratio value of gene expression counts. In
particular, we use Gene2Vec[37], a distributed representation dictionary pretrained from
transcriptome-wide gene co-expression data, to embed gene identities into node vectors with 200
dimensions.

As for edges, we firstly pick up around 600 highly variable genes and then transfer gene expression
counts into pairwise log-ratio values. For a typical matrix X of gene expression counts with
dimension $n \times m$, where n is the number of observations (cells), and m is the number of variables
(sequenced genes). We define the "pairwise log-ratio values" for n cells as n square matrices all of
size $m \times m$. More specifically, for each cell (assume its index is i), the gene expression counts
vector would be X_i, and the j-th value $X_{i,j}$ is the expression counts of Gene j. For the $m \times m$ log-
ratio matrix, its j-th column would be enumerated by $logX_{i,j} - logX_{i,k}$ for k in the range of 1 to m,
including j. We add a Gaussian noise with mean of 0.5 to original expression counts to avoid
computational failure caused by the data sparsity.

We used radial basis functions (RBFs) with Gaussian kernels to transform these single numerical
ratio values into dense multidimensional vectors by mapping each input onto a high-dimensional
space using radial symmetry.

$$RBF(x,c) = exp\left(-\frac{(x-c)^2}{r^2}\right),$$ (1)

where x, c and r represent the log-ratio scalar needing to be vectorized, the centre point and the
variance (spreadability) of the current Gaussian kernel respectively. We have calculated the
distribution of these log-ration values and found most of them were within the range of -6 to 6. For
efficient vectorization, we used 8 kernels whose centre points were unevenly spaced in that range
according to our parameter searching process.

MPNN

After comprehensively balancing the model performance and computation consumption like
memory usage, we pruned the previous dense graph and only kept 16 outgoing edges for each node.
More specifically, for each gene (node in the graph), we chose 8 other genes with largest log-ratio
values and 8 with smallest values and kept corresponding edges. It is worth noting that log-ratio
values between two paired genes are actually the opposites, i.e., if we mark the expression count of
gene A and gene B as EA and EB, then the log-ratio of A to B would be $log(EA/EB)$ while B to A
is $log(EB/EA)$. To fully utilise the edge information, we added a perceptron layer for information
propagation. This perceptron layer effectively integrates and reweights the corresponding
neighbourhood of a certain node, serving as an attention mechanism and making the graph topology
fit expression data better.

As shown in Fig1, the MPNN model of scClassify2 has an encoder-decoder architecture. The dual-
layer encoder absorbs nodes and edges of the cell graph to gather messages from neighbourhoods
and then alternatively updates nodes and edges by these messages passing along edges. More
specifically, after aligning all input vectors, we first concatenate every two node vectors with the
edge vector connecting them and calculate the message of this edge by a perceptron. Then we
update node vectors using this message by a residual module with normalisation and dropout. With
all nodes updated, we recalculate the message via another similar perceptron and then update edge
vectors this time using new messages. The decoder is much simpler compared to the encoder. It
takes nodes and edges from the encoder and computes messages along edges. The decoder only
updates node features of the graph and tries to reconstruct the distributed representation of genes.
Before we evaluated our method, we carried out hyper-parameter searching (Supplementary Fig,
S2).

Ordinal regression

Drawing on previous work[38], we construct $n-1$ conditional training subsets $S_1, \ldots, S_j, \ldots, S_{(n-1)}$ for n sequential cell states. The first subset is the whole training set, and we conduct binary classification with regular binary cross-entropy loss to decide whether a cell belongs to the first state or following states. Meanwhile, the j^{th} subset only contains samples belonging to states following the $(j-1)^{th}$ state and we also conduct similar binary classification with cross-entropy to decide whether a cell belongs to the j^{th} state or states following the j^{th} state. After transferring the original large and complex multi-classification problem to a series of smaller and simple binary classification problems, we obtain unconditional probability through the chain rule of conditional probability. More specifically, the predicted state index q of a cell would be:

$$q = 1 + \sum_{j=1}^{n-1} I\big(\hat{P}(y > stage_j) > threshold\big), \tag{2}$$

where I is the indicator function, y represents current cell state and $\hat{P}(y > stage\, j)$ means the estimated probability of the current cell belonging to states following the j^{th} state, and the threshold is a tuneable predefined probability value. Then, the ordinal regression loss of scClassify2 would be:

$$Loss_{ord} = -\frac{1}{\sum_{j=1}^{K-1} |Sj|} \sum_{j=1}^{K=1} \sum_{i=1}^{|Sj|} [log(\sigma(z^{[i]})) \cdot I(y^{[i]} > stage_j) +$$

$$(\log(\sigma(z^{[i]})) - z^{[i]}) \cdot I(y^{[i]} \leq stage_j)] \tag{3}$$

where $z^{[i]}$ represents the predicted logits of the i^{th} training example in S_j, σ means sigmoid function and S_j means the j^{th} training subset with all cells belonging to states following the $(j-1)^{th}$ state.

Gene embedding reconstruction

Through passing messages along graph edges and self-updating, MPNN could concentrate locality into global gene expression topology, where subtle cell state information hides. To better assist in this topology capturing, we add gene representation reconstruction loss beside the cell state classification loss. The reconstruction loss measures overall distance between the distributed gene representation inputted to nodes with certain masks (mask rate 15%) in the first layer of encoder and the corresponding recovered gene representation distribution outputted by the last layer of decoder. Since these two distributions might shift unevenly by computations and operations conducted within MPNN and thus do not share the same base anymore, we choose an approximating Wasserstein distance[39–42] as our loss instead of directly using Kullback–Leibler divergence[43]. The reconstruction loss would be:

$$Loss_{rec} = inf_{\gamma \in \Pi(P,Q)} E_{(x,y)} ||x - y||, \tag{4}$$

where γ is the joint distribution of original gene representation P and reconstructed gene representation Q, Π is the set of all possible γ, inf means the infimum of the expectation.

Loss function

As described above, the loss function of scClassify2 has two main parts: an ordinal regression part to directly classify cell states according to the gene expression pattern it captures, and a gene embedding reconstruction part to implicitly guide the topology capture of MPNN and thus benefit the previous one. We use two empirical coefficients to combine them:

$$Loss = \lambda_1 Loss_{ord} + \lambda_2 Loss_{rec}. \tag{5}$$

Dual-layer implementation

We compared the single-layer network which only used expression counts with the dual-layer architecture which integrates estimated gene-gene association information with gene expression. As mentioned above, an observation or a cell is represented by a graph, where the nodes represent genes, and the edges represent log-ratio values of two connected genes' expression counts. For implementation convenience, we kept the main framework and designed the comparison of node fillers in order from simplicity (no information) to complexity (more information), where each node could be:

    (a) set to all zeros - representing no information in nodes and the network only used expression counts.

    (b) one-hot vectors - representing only unrelated gene information in nodes.

    (c) gene embeddings from Gene2vec[37] - representing gene-gene association information estimated by a machine learning approach from large-scale gene-gene co-expression data.

    (d) gene embeddings from scETM[44] and scSpectra[45] - representing gene-gene association information estimated by deep learning approaches from transcriptome-wide gene-gene co-expression data.

Evaluation framework

We mainly used accuracy and confusion matrix for our performance evaluation. A confusion matrix is a table to visualise the detailed cell state identification performance. It presents a summary of the percentages of correct and incorrect predictions made by the model, organised by the ground truth and predicted labels. We executed strict 5-fold cross validation on a collection of eight datasets (Supplementary Table S1) covering both human and mouse, different tissue types and cell types, diseased and healthy. Before the systemic evaluation, we checked the stability of our method (Supplementary Fig.S3).

To evaluate and compare the performance of scClassify2, we obtained four other publicly available methods by their default settings. These packages were installed either through their official Bioconductor website or directly from their GitHub page before December of 2023. Among them, scClassify is our previous version, which is based on traditional ensembled k-neighbours network (KNN) and cell type hierarchies. sigGCN is a multimodal end-to-end graph convolutional network combined with gene interaction information. scGCN is another graph convolution network which achieves effective knowledge transfer across disparate datasets. scGPT is a pre-trained foundation large language model with fine tuning pipeline for single-cell multi-omics.

Subcellular spatial transcriptomics (SST)

We used the Xenium Breast Cancer dataset downloaded from https://www.10xgenomics.com/products/xenium-in-situ/preview-dataset-human-breast to validate scClassify2's capability on SST data. This process needed to combine Bidcell, a cell segmentation tool developed by our group. We used its default config (details could be found at: https://github.com/SydneyBioX/BIDCell) to get the cell segmentations and applied scClassify2 on segmented expression files.

Web server

For the front-end, the interface of our web server, scClassify-catalogue
(https://shiny.maths.usyd.edu.au/scClassify_catalogue/) is based on Shiny. Shiny is an R package
facilitating the creation of interactive web applications, enabling seamless integration of data
analysis and visualisation for end users. Meanwhile, the back-end functionality was implemented
through Python, as described in our Github page (https://github.com/Wenze18/scClassify2).

Ethics statement

Not applicable.

Data Availability

Details of each dataset used in this study is listed in Supplementary Table 1.

Acknowledgments

The authors thank all their colleagues, particularly at The University of Sydney, Sydney Precision
Data Science and Charles Perkins Centre for their support and intellectual engagement. Special
thanks to Zhenghao (Chris) Chen for his contribution in our weekly discussion.

Funding

AIR@innoHK programme of the Innovation and Technology Commission of Hong Kong to all
authors. Judith and David Coffey funding and the Chan Zuckerberg Initiative Single Cell Biology
Data Insights grant (DI2-0000000197) to J.Y.H.Y and Y.C; NHMRC Investigator APP2017023 to
J.Y.H.Y. The funding source had no role in the study design; in the collection, analysis, and
interpretation of data, in the writing of the manuscript, and in the decision to submit the manuscript
for publication.

Competing Interests

The authors declare that there are no competing interests.

Author Contribution

J.Y. conceived and funded the study. J.Y., W.D., Y.C. and X.F. completed the design of study.
W.D and Y.C. completed the evaluation and analysis. The implementation of the package was done
by W.D. The construction of the web server was done by M.T. All authors wrote, reviewed, and
approved the manuscript.

References

1. Armingol, E., Officer, A., Harismendy, O. & Lewis, N. E. Deciphering cell-cell interactions

    and communication from gene expression. *Nat. Rev. Genet.* **22**, 71–88 (2021).

2. Jovic, D. *et al.* Single-cell RNA sequencing technologies and applications: A brief overview.

    Clin. Transl. Med. **12**, e694 (2022).

3. Papalexi, E. & Satija, R. Single-cell RNA sequencing to explore immune cell heterogeneity.

Nat. Rev. Immunol. **18**, 35–45 (2018).

4.   Stark, R., Grzelak, M. & Hadfield, J. RNA sequencing: the teenage years. *Nat. Rev. Genet.* **20**,

631–656 (2019).

5.   Stubbington, M. J. T., Rozenblatt-Rosen, O., Regev, A. & Teichmann, S. A. Single-cell

transcriptomics to explore the immune system in health and disease. *Science* **358**, 58–63

(2017).

6.   Lähnemann, D. *et al.* Eleven grand challenges in single-cell data science. *Genome Biol.* **21**, 31

(2020).

7.   Stegle, O., Teichmann, S. A. & Marioni, J. C. Computational and analytical challenges in

single-cell transcriptomics. *Nat. Rev. Genet.* **16**, 133–145 (2015).

8.   Zappia, L. & Theis, F. J. Over 1000 tools reveal trends in the single-cell RNA-seq analysis

landscape. *Genome Biol.* **22**, 301 (2021).

9.   Chen, J. *et al.* Transformer for one stop interpretable cell type annotation. *Nat. Commun.* **14**,

223 (2023).

10. Li, C. *et al.* SciBet as a portable and fast single cell type identifier. *Nat. Commun.* **11**, 1818

(2020).

11. Liu, Y. *et al.* TripletCell: a deep metric learning framework for accurate annotation of cell

types at the single-cell level. *Brief. Bioinform.* **24**, (2023).

12. Ma, F. & Pellegrini, M. ACTINN: automated identification of cell types in single cell RNA

sequencing. *Bioinformatics* **36**, 533–538 (2020).

13. Wang, J. *et al.* scGNN is a novel graph neural network framework for single-cell RNA-Seq

analyses. *Nat. Commun.* **12**, 1882 (2021).

14. Xie, P. *et al.* SuperCT: a supervised-learning framework for enhanced characterization of

single-cell transcriptomic profiles. *Nucleic Acids Res.* **47**, e48 (2019).

15. Xu, Z., Luo, J. & Xiong, Z. scSemiGAN: a single-cell semi-supervised annotation and

dimensionality reduction framework based on generative adversarial network. *Bioinformatics*

38, 5042–5048 (2022).

16. Kimmel, J. C. & Kelley, D. R. Semisupervised adversarial neural networks for single-cell classification. *Genome Res.* **31**, 1781–1793 (2021).

17. Petropoulos, S. *et al.* Single-Cell RNA-Seq Reveals Lineage and X Chromosome Dynamics in Human Preimplantation Embryos. *Cell* **167**, 285 (2016).

18. Fernández-García, J. *et al.* CD8+ T cell metabolic rewiring defined by scRNA-seq identifies a critical role of ASNS expression dynamics in T cell differentiation. *Cell Rep.* **41**, 111639 (2022).

19. Zhang, Y. *et al.* CellSTAR: a comprehensive resource for single-cell transcriptomic annotation. *Nucleic Acids Res.* **52**, D859–D870 (2024).

20. Zhou, P., Wang, S., Li, T. & Nie, Q. Dissecting transition cells from single-cell transcriptome data through multiscale stochastic dynamics. *Nat. Commun.* **12**, 5609 (2021).

21. de Kanter, J. K., Lijnzaad, P., Candelli, T., Margaritis, T. & Holstege, F. C. P. CHETAH: a selective, hierarchical cell type identification method for single-cell RNA sequencing. *Nucleic Acids Res.* **47**, e95 (2019).

22. Li, X. *et al.* Deep learning enables accurate clustering with batch effect removal in single-cell RNA-seq analysis. *Nat. Commun.* **11**, 2338 (2020).

23. Kiselev, V. Y., Yiu, A. & Hemberg, M. scmap: projection of single-cell RNA-seq data across data sets. *Nat. Methods* **15**, 359–362 (2018).

24. Ianevski, A., Giri, A. K. & Aittokallio, T. Fully-automated and ultra-fast cell-type identification using specific marker combinations from single-cell transcriptomic data. *Nat. Commun.* **13**, 1246 (2022).

25. Lotfollahi, M. *et al.* Mapping single-cell data to reference atlases by transfer learning. *Nat. Biotechnol.* **40**, 121–130 (2022).

26. Liu, C., Huang, H. & Yang, P. Multi-task learning from multimodal single-cell omics with Matilda. *Nucleic Acids Res.* **51**, e45 (2023).

27. Theodoris, C. V. *et al.* Transfer learning enables predictions in network biology. *Nature* **618**,

616–624 (2023).

28. Cui, H. *et al.* scgpt: Towards building a foundation model for single-cell multi-omics using

generative ai. *bioRxiv* 2023–2004 (2023).

29. Wang, K. Y. X. *et al.* Cross-Platform Omics Prediction procedure: a statistical machine

learning framework for wider implementation of precision medicine. *NPJ Digit Med* **5**, 85

(2022).

30. Zhou, Y. *et al.* Co-embedding of edges and nodes with deep graph convolutional neural

networks. *Sci. Rep.* **13**, 16966 (2023).

31. Lin, Y. *et al.* scClassify: sample size estimation and multiscale classification of cells using

single and multiple reference. *Mol. Syst. Biol.* **16**, e9389 (2020).

32. Gilmer, J., Schoenholz, S. S., Riley, P. F., Vinyals, O. & Dahl, G. E. Neural Message Passing

for Quantum Chemistry. in *Proceedings of the 34th International Conference on Machine*

Learning (eds. Precup, D. & Teh, Y. W.) vol. 70 1263–1272 (PMLR, 06--11 Aug 2017).

33. Yang, K. *et al.* Analyzing Learned Molecular Representations for Property Prediction. *J.*

Chem. Inf. Model. **59**, 3370–3388 (2019).

34. Dauparas, J. *et al.* Robust deep learning-based protein sequence design using ProteinMPNN.

Science **378**, 49–56 (2022).

35. Liu, C., Sun, Y., Davis, R., Cardona, S. T. & Hu, P. ABT-MPNN: an atom-bond transformer-

based message-passing neural network for molecular property prediction. *J. Cheminform.* **15**,

29 (2023).

36. Wang, R. *et al.* Time space and single-cell resolved tissue lineage trajectories and laterality of

body plan at gastrulation. *Nat. Commun.* **14**, 5675 (2023).

37. Du, J. *et al.* Gene2vec: distributed representation of genes based on co-expression. *BMC*

Genomics **20**, 82 (2019).

38. Shi, X., Cao, W. & Raschka, S. Deep neural networks for rank-consistent ordinal regression

based on conditional probabilities. *Pattern Anal. Appl.* **26**, 941–955 (2023).

39. Vaserstein, L. N. Markov processes over denumerable products of spaces, describing large

systems of automata. *Problemy Peredachi Informatsii* **5**, 64–72 (1969).

40. Cuturi, M. Sinkhorn distances: Lightspeed computation of optimal transport. *Adv. Neural Inf.*

Process. Syst. **26**, (2013).

41. Frogner, C., Mirzazadeh, F. & Solomon, J. Learning Embeddings into Entropic Wasserstein

Spaces. *arXiv [cs.LG]* (2019).

42. Patrini, G. *et al.* Sinkhorn AutoEncoders. in *Proceedings of The 35th Uncertainty in Artificial*

Intelligence Conference (eds. Adams, R. P. & Gogate, V.) vol. 115 733–743 (PMLR, 22--25

Jul 2020).

43. Kullback, S. & Leibler, R. A. On Information and Sufficiency. *Ann. Math. Stat.* **22**, 79–86

(1951).

44. Zhao, Y., Cai, H., Zhang, Z., Tang, J. & Li, Y. Learning interpretable cellular and gene

signature embeddings from single-cell transcriptomic data. *Nat. Commun.* **12**, 5261 (2021).

45. Kunes, R. Z., Walle, T., Land, M., Nawy, T. & Pe'er, D. Supervised discovery of interpretable

gene programs from single-cell data. *Nat. Biotechnol.* (2023) doi:10.1038/s41587-023-01940-

3.

Figures

Fig. 1. Overview of the scClassify2 framework for sequential cell state identification
(a) Linear cell state transformation is one of the most common and important phenomena in nature when external disturbance factors like signal molecules, drugs or stresses occur. (b) Conceptual illustration of expression distribution difference between distinct cell types and adjacent cell states. (c) Brief illustration of our work. scClassify2 adapts stable log-ratio values of expression data and incorporates prior gene co-expression knowledge via a dual-layer graph neural network (MPNN) to capture the expression topology of cells and then identify them accurately with a novel ordinal regression component. (d) scClassify2 could be applied to not only the traditional scRNA-seq data, but also sequencing data from subcellular spatial transcriptomics. (e) Brief illustration of the MPNN architecture adopted by scClassify2. Gene identities are encoded as nodes of the graph meanwhile the log-ratio of corresponding expression is encoded as edges. The model contains an encoder for topology capturing and a decoder for better learning.

Fig. 2. scClassify2 uses dual layer architecture based on message passing neural network
(a) tSNE plots of validation mouse gastrulation embryo dataset to show the prediction difference between single layer architecture and dual layer (with gene2vec). The left panel is annotated by ground truth. The middle and right panel are the prediction of single layer and dual layer architecture correspondingly. (b) Clustered cell embeddings captured by single layer (left panel) and dual layer (right panel) architecture correspondingly. In the heatmap, each row represents a cell, whose state is marked by the very left coloured stripes. As we can see, cell embeddings obtained from dual layer architecture show certain patterns which are highly correlated with corresponding cell state, while single layer ones do not. (c) Comparison among single layer using only gene expression data and dual layer integrating different sources of prior biological knowledge. (d) Prediction accuracy comparison between classifiers of general multi-classification and specifically designed ordinal regression across various cell states. (e) Confusion matrices of predictions from different classifiers show more details.

Fig. 3. Performance comparison for eight different datasets
Comparison of model performance for 5 advanced approaches on 8 different sequential cell state datasets. Relative ranks of these methods on each dataset are presented at the top.

Fig. 4. Applicability of scClassify2 for SST data

scClassify2 could be directly applied on subcellular spatial transcriptomics (SST) data. (a)-(d) The raw image and cell types identified by scClassify2 of human breast tissues, where (a) and (b) is replicate 1 while (c) and (d) stands for replica 2. (e)-(g) We equally divided the vision into 25 regions to observe the annotation results of scClassify2. (e) Regional cell enrichment (how many cells in one specific region compared with the whole vision). (f) scClassify2's prediction accuracy for each region. (g) The relationship between regional cell enrichment (x-axis) and scClassify2's prediction accuracy (y-axis). (h) We also checked scClassify2's precision for each cell type when applied it on SST data.

Fig. 5. Overview of scClassify-catalogue - the web server

(a) A brief overview of our web server, scClassify-catalogue. (b) Homepage of scClassify-catalogue. The window for uploading expression profiles of query data is marked by a green rectangular (Box 1). After filling all necessary information in, click the "SUBMIT" button. (c) After submission, the waiting panel would pop up. The prompt window of the waiting panel is marked by a purple rectangular (Box 2). Job ID in this window is important for us to trace the backend activity of the user's submission. Please wait enough time (usually less than 2 minutes) before clicking the "Generate result" button. (d) If the job has not been finished, another waiting panel would pop up. (e) The result page of the finished job. A UMAP of input data with annotations and a brief statistical bar plot of analysis results is available on this page. Downloadable and editable result table and analysis plot mentioned above could be reviewed by users Box 3).

Supplementary Figures

Supplementary Fig. S1.
The comparison among several graph neural network architectures. The overall prediction accuracy of MPNN and graph transformer is approximately equal, outperforming GCN and GAT. However, the graph transformer consumes significantly more training time compared with MPNN.

Embedding Approach	{	RBF: counts, mean, std
		Hidden dimension
		Number of edges connected to a node

Network Architecture	{	Whether contains decoder or not
		Which foundation graph network acrchitecture
		Number of layers for encoder and decoder
		Hidden dimension for each layer
		Which activation function

Objective Function	{	Which reconstruction loss
		Multiclassification loss or ordinal regression loss
		Threshold within ordinal regression loss
		Relative weights of losses

Supplementary Fig. S2.
The comprehensive hyperparameter search was conducted for scClassify2. Network hyperparameters of 12 aspects from 3 domains were involved to optimise its performance and robustness for real-world applications.

Supplementary Fig. S3.

The stability of model performance with respect to changes in the size of the training set.

Supplementary Table

Supplementary Table S1.
Details of eight scRNA-seq datasets of sequential cell state transformation. The columns #cells, #genes, #states denote the number of cells, the number of genes and the number of cell states respectively.

Datasets	Name of dataset	First author or organisation	Paper	#cells	#genes	#states	Species	Data accession
1	Mouse embryo	Wang et al	Nature Communications 14.1 (2023).	13377	29452	6	Mouse	https://github.com/MarioniLab/EmbryoTimecourse2018
2	T-cell development	Fernandez et al	Cell Reports 41.7 (2022).	5859	12868	5	Human	GSE211602
3	Human embryos	Petropoulos et al	Cell, 165 (2016).	1289	8772	5	Human	E-MTAB-3929
4	Mouse oligodendrocyte	Marques et al	Science,352 (2016).	3685	3534	10	Mouse	GSE75330
5	Mouse bone marrow mesenchyme erythrocyte	MCA	Cell, 172 (2018).	3105	3025	3	Mouse	GSE108097
6	Mouse dentate gyrus neurogenesis	Hochgerner et al	Nature neuroscience 21.2 (2018).	3585	2182	5	Mouse	GSE95753
7	Mouse kidney brush border	MCA	Cell, 172 (2018).	1400	2951	3	Mouse	GSE108097
8	Mouse kidney collecting duct	Park et al	Science, 360 (2018).	2701	2441	6	Mouse	GSE107585