Functional protein mining with conformal guarantees

Ron S. Boger[1,2,3,8], Seyone Chithrananda[1,3,7], Anastasios N. Angelopoulos[7], Peter H. Yoon[1,3,6,8], Michael I. Jordan[7,11], and Jennifer A. Doudna[1,3,4,5,6,8,9,10]

[1]Innovative Genomics Institute; University of California, Berkeley, CA, USA.
[2]Biophysics Graduate Group, University of California, Berkeley; Berkeley, CA, USA.
[3]Howard Hughes Medical Institute, University of California, Berkeley; Berkeley CA, USA.
[4]Molecular Biophysics and Integrated Bioimaging Division, Lawrence Berkeley National Laboratory; Berkeley, CA, USA.
[5]Department of Chemistry, University of California, Berkeley; Berkeley, CA, USA.
[6]Department of Molecular and Cell Biology, University of California, Berkeley; Berkeley, CA, USA.
[7]Department of Electrical Engineering and Computer Sciences, University of California, Berkeley; Berkeley, CA, USA.
[8]California Institute for Quantitative Biosciences, University of California, Berkeley; Berkeley, CA, USA.
[9]Gladstone Institutes; San Francisco, CA, USA.
[10]Gladstone-UCSF Institute of Genomic Immunology; San Francisco, CA, USA.
[11]Department of Statistics, University of California, Berkeley; Berkeley, CA, USA.

June 27, 2024

1 Abstract

Molecular structure prediction and homology detection provide a promising path to discovering new protein function and evolutionary relationships. However, current approaches lack statistical reliability assurances, limiting their practical utility for selecting proteins for further experimental and in-silico characterization. To address this challenge, we introduce a novel approach to protein search leveraging principles from conformal prediction, offering a framework that ensures statistical guarantees with user-specified risk on outputs from any protein search model. Our method (1) lets users select any loss metric (i.e. false discovery rate) and assigns reliable functional probabilities for annotating genes of unknown function; (2) achieves state-of-the-art performance in enzyme classification without training new models; and (3) robustly and rapidly pre-filters proteins for computationally intensive structural alignment algorithms. Our framework enhances the reliability of protein homology detection and enables the discovery of new proteins with likely desirable functional properties.

2 Introduction

In the era of protein structure prediction, there are abundant opportunities for functional annotation of proteins. However, despite the progress, there are few robust methods available to introspect and assess the quality of these annotations. This introspection is critical for selecting which proteins to characterize further through experimental or in silico methods. In this work, we address the problem of assessing which proteins to characterize by developing a practical framework for reliable and interpretable evaluations, providing essential screening methods before costly lab or structural characterization.

Identification of protein homologs provides essential insights into protein functions and evolutionary trajectories. Homology provides a valuable framework for predicting the function of newly discovered proteins and understanding the molecular mechanisms underlying various biological processes. Homology searches generate a score indicating similarity between a query protein and proteins in a lookup database, based on either primary sequence or three-dimensional structural comparison.

Traditionally, homology search has focused on sequence comparison due to its speed and the limited number of experimentally solved protein structures. BLAST [1] and Hidden Markov Models (HMMs) have long been used to search large databases of protein sequences by scoring by residue overlap and alignment-based features. Classical methods for comparing protein structures such as DALI [28] and TM-align [49] confer higher sensitivity for finding remote homologs—protein homologs with low sequence similarity. However, these methods were not widely used due to the limited number of available protein structures and their slow speeds. With the development of accurate protein structure prediction methods such as AlphaFold2 [30], the number of available (predicted) protein structures has vastly increased. Despite this, large-scale searches through these predicted structures with classical structural alignment methods remain computationally infeasible. New approaches leveraging deep learning models on sequence and structure, such as TM-Vec[25], Foldseek [42], Protein-Vec [24], and TOPH [15] have provided a promising alternative for fast and highly sensitive homology search, outperforming classical methods on speed and nearly matching their sensitivity in traditional bioinformatic benchmarks.

The practical application of protein homology models presents additional challenges. For example, a recent work Protein-Vec [24] presented state-of-the-art results across numerous benchmarks for function prediction. However, nearly all scores generated by this model fall within a range of .9995 to 1. These results are hard to interpret for a biologist, because even normalizing the scores does not indicate which proteins are worthwhile for further characterization. For instance, a biologist may want to conduct a protein search that guarantees 90% of the returned set shares biochemical function with the query protein (i.e., a 10% false discovery rate) and provides the probability of shared biochemical function within this set. The need for statistically valid "needle in a haystack" approaches to filter and retrieve a high quality set of biological systems becomes increasingly important as genomic datasets rapidly expand.

Recent work on conformal prediction offers a promising solution to validation of protein retrieval. Classical statistical techniques often rely on stringent assumptions about model structure (e.g., linearity) in order for their validity to hold; but in the era of deep-learning based black-box models, such model assumptions rarely hold. Conformal prediction provides statistical guarantees that are *black-box*—they provide uncertainty estimates about predictions without making any assumptions about the structure of the model. These techniques address the emerging challenges that have arisen with the large scale of protein data and complex deep learning architectures, which cannot

be addressed by traditional statistical methods such as e-values and likelihood thresholds. So long as there is a calibration dataset representative of future data, conformal prediction offers a framework for returning sets of predictions with calibrated risk, such as false discovery rates or partial errors in an EC annotation. By applying conformal prediction to homology search and function annotation models, we can transform raw similarity scores into interpretable confidence sets and probabilities. Thus, we allow any search model to be employed for generating candidate homologs while providing a baseline guarantee of statistical accuracy for the final sets of proteins returned. This provides adaptability and enhances the interpretability of the output, making models more accessible and useful for large-scale biological discovery.

In summary, we introduce a novel approach leveraging conformal prediction for protein retrieval, focusing on efficiently returning high-quality sets of proteins with functional similarity with statistical guarantees on their validity. Our method adaptively ensures coverage and reliability, providing robust statistical guarantees for similarity scores generated by protein search models. This enhances the interpretability and reliability of these models in identifying protein with homology and desired functional characteristics. Our approach helps determine which proteins should be further characterized in the lab or through higher resolution algorithms, such structural alignment or molecular dynamics. We demonstrate the utility of our approach across diverse protein datasets and tasks, from annotating genes of unknown function in the minimal viable genome to improving enzyme function prediction. Ultimately, our work reframes and addresses these challenges in quantitative biology as calibration and risk control problems, providing a robust approach for functional protein mining.

2.1   Motivation and relevant work

Assume we are given a set of query proteins Q of size N_Q, and a large lookup database of proteins denoted D of size $N_D \gg N_Q$, and we use some statistical model of proteins to produce a set of similarity scores between the query and lookup protein (Fig 1). Given this similarity matrix $S \in \mathcal{R}^{N_Q \times N_D}$, we aim to retrieve a subset $\hat{C} \in D$ that contains the true attribute of interest to the query (*retrieval*). Developing a selection method for this problem can be challenging, and results from selection are often model-dependent. Depending on the ability of the model to capture structural and functional similarity, the closest homologs may have lower similarity scores S_{ij} compared to more functionally distant proteins in the lookup set. Thus, we aim to create a method that can find the optimal threshold λ based on a user-specified risk tolerance α for a desired loss metric for functional homologs, such as false negative rate (FNR) or false discovery rate (FDR) (Fig 1). Given a set of query and lookup proteins, Q and D, our method returns a set $C_\lambda = \{v : S_{ij} > \lambda\}$ with statistical guarantees based on the specified risk tolerance.

The statistical techniques herein build on tools from the literature surrounding conformal prediction, as developed by [45]; for an introduction to contemporary techniques in the area, see [3]. Conformal prediction is a technique for calibrating arbitrary black-box prediction algorithms in order to satisfy statistical guarantees of marginal coverage (and notably, not conditional coverage [44, 10]). This has become especially interesting in the era of deep learning, when prediction systems may be difficult to analyze with standard analytical statistics [26, 6]. Here, we focus specifically on the use of conformal risk control techniques [14, 5, 4] for the purpose of biological retrieval algorithms. Although conformal prediction has been applied in several ways to the biomedical space (see, e.g., [39, 2, 40, 37, 7, 21, 33, 32]), we are unaware of substantial work that resembles ours. A recent work published as we were writing this manuscript, [20], leverages conformal prediction

Figure 1: **Study Design and Motivation for Protein Homology Search Using Conformal Prediction.** (a) A query sequence q is compared against a lookup database D using a protein search model (e.g., Protein-Vec). The model generates similarity scores S_{ij} , which are compared against a threshold $\hat{\lambda}$ determined through calibration. Scores above the threshold are included in the confidence set $\hat{C}$. Scores below the threshold (e.g., F98079 with 0.943) are highlighted in red to indicate their exclusion. (b) The process involves computing scores on calibration data, obtaining quantiles, and constructing prediction sets. This approach provides statistical guarantees on the validity of the returned sets, enhancing the interpretability and reliability of protein search results. (c) The distribution of Protein-Vec similarity scores for UniProt motivates the need for effective thresholds and confidence measures in protein homology searches, particularly given the high similarity scores clustering near 1. (d) Illustration of the error loss calculation for two enzymes: EC 2.1.1.13 (Methionine S-methyltransferase, Methionine synthase) and EC 4.1.1.2 (Oxalate decarboxylase). The loss function $\ell(x, C)$ assigns a value based on the maximum hierarchical loss of the enzymes in the retrieved confidence set C_λ, with 0 being every retrieved protein consisting of an exact match. The hierarchical classification tree for part of transferases (EC 2) is shown, with methionine synthase being the ground-truth EC number, and methionine s-methyltransferase being in the model-retrieved confidence set. This results in a $\ell(x, C) = 1$ hierarchical loss.

to improve a new machine learning model that the authors train, PenLight2. This is similar to section 3.2 in our work where we improve an existing machine learning model with better selection. Overall, however, our goal is not to present a new machine learning model for enzyme classification, but rather to develop a practical and rigorous methodology for experimentalists to decide what to characterize in the lab. Similarly, although some initial work has been done on conformal prediction and recommendation systems [31, 27, 8, 47], none of these recommendation system techniques have been used with biological data to our knowledge.

3 Results

3.1 Annotation of genes of unknown function with limited false discovery

Protein families are groups of evolutionarily related proteins that share a common ancestor. Members of a protein family typically have similar sequences, structures, and functions. Annotating protein families is critical in understanding their function and evolutionary history. Proteins can have multiple Pfam annotations; for instance, the bacterial immune system CRISPR-Cas9 is annotated with five Pfams for different functional domains (endonuclease, PAM interaction, etc). The Pfam database is widely used in particular to classify protein sequences into families in domains, and serves as a classic benchmark in functional annotation. We searched across Pfam-annotated proteins in Uniprot for exact and partial hits using Protein-Vec (Section 4.1.1) and demonstrated our methods in finding the optimal similarity thresholds for false negative rate (FNR) and false discovery rate (FDR) at $\alpha = 0.1$. We shuffled the data over 100 trials to generate a new calibration dataset to learn optimal thresholds for FNR and FDR.

We assign probabilities to each similarity score between query and lookup by fitting an isotonic regression. Isotonic regression is a nonparametric technique that fits a nondecreasing function to the data, allowing us to transform raw similarity scores into calibrated probabilities. This approach ensures that the assigned probabilities are monotonically increasing with respect to the similarity scores, a transformation that is a natural first step when assessing whether a given match is correct (Fig 1).

To evaluate the statistical validity of the isotonic regression, we employ Venn-Abers Predictors [46]. Venn-Abers Predictors are a type of conformal predictor that provide reliable prediction intervals, calibrated probabilities, adaptability to different loss functions, theoretical guarantees, and ease of implementation. This method helps verify that our probability assignments are statistically valid and that they maintain the desired coverage properties. By using Venn-Abers Predictors, we can ensure that the isotonic regression model produces accurate and reliable probability estimates for our similarity scores. We examine the difference in test probabilities $\hat{p}^0, \hat{p}^1$ and see that $|\hat{p}^0 - \hat{p}^1| \approx 0$, demonstrating our model's ability to assess the probability of a functional match is well calibrated (Fig 2). We also show that the expected calibration error (ECE) of the Venn-Abers predictor is low, further indicating reliability (Fig 2).

As a test case, we investigated the possibility of rigorously annotating genes identified in JCVI Syn3.0 *Mycoplasma mycoides*. JCVI Syn3.0, developed by the J. Craig Venter Institute, represents a minimal viable genome containing only the essential genes necessary for life [29]. Interestingly, despite its small genome, nearly 20% of the protein-coding genes in JCVI Syn3.0 were classified as genes of unknown function at time of publication—genes with no homology to characterized genes via BLAST and HMMSearch. Annotating the genes in this synthetic organism is crucial for understanding their functions and the minimal requirements for cellular life. Given the development

in protein structure prediction and remote homology algorithms since the initial release of JCVI Syn3.0, we hypothesized that some fraction of these genes may have remote homology (that was not found via traditional methods) to well-characterized proteins. We applied our calibrated methods to this dataset, aiming to identify functional annotations for the previously unknown genes in Syn3.0. We assigned similarity scores to each of the genes of unknown function to Uniprot using Protein-Vec, and then filtered the results by selecting only $S_{ij} \geq \hat{\lambda}$, where $\hat{\lambda}$ is a threshold fit to obtain FDR control at $\alpha = .1$. We find that 39.6% of coding genes of previously unknown function meet our criteria for an exact functional match (Fig 2) to proteins in UniProt. We demonstrate a structural alignment between a predicted structure of a gene of previously unknown function that met our criteria and a UniProt reviewed (ID Q9KAV6) exonuclease. By leveraging our approach, we provide robust and reliable annotations that could shed light on the roles of these essential genes, thereby contributing to the broader understanding of minimal genomes and synthetic biology. Our approach can be used more widely to rapidly assign high-confidence annotation to any newly discovered genome.

3.2 Robust selection strategies for enzyme function prediction

Method	Precision	Recall	F1	AUC
Calibrate on New, test on subset of New (92 proteins across 77 unique EC classes)				
Conformal ($\alpha = 1$)	**56.80 $\pm$ 1.64**	**63.71 $\pm$ 0.29**	**57.65 $\pm$ 1.45**	**81.50 $\pm$ 0.38**
Max-sep	53.05 $\pm$ 0.13	50.03 $\pm$ 1.34	50.96 $\pm$ 1.21	74.96 $\pm$ 0.66
P-Value	53.27 $\pm$ 0.51	52.01 $\pm$ 1.11	52.04 $\pm$ 0.63	75.90 $\pm$ 0.58
Generalizability test: calibrate on New, test on Price (149 Samples, 56 EC classes)				
Conformal ($\alpha = 1.5$)	55.98	**49.34**	**49.62**	**74.59**
Max-sep	58.44	46.71	49.47	73.34
P-value	**59.26**	47.74	47.77	72.34

Table 1: Comparison of CLEAN selection methods to conformal. For the first subtable relating to *New*, we calibrate on 300 data points and test on 92 from *New* (68-77 unique EC labels). We shuffle the train and test indices across 10 trials, to ensure robust performance across different partitions of the dataset. For the generalizability test, we calibrate on 380 data points from *New* and test on all 149 from *Price* (56 EC). We utilize nearly all of *New* to calibrate, as increasing the size of one's calibration set progressively increases the tightness of the loss coverage, as detailed in 5.

In addition to calibrating the Protein-Vec model for a diverse set of tasks, we also develop a novel selection method for CLEAN. CLEAN is another deep-learning approach akin to Protein-Vec that learns an embedding space of enzymes by employing a single-aspect contrastive loss function that minimizes the distance between anchor and positive enzymes, while maximizing the distance between anchor and negative enzymes. CLEAN is based on Enzyme Commission (EC) numbers, a hierarchical numerical classification scheme for enzymes in which the catalytic function of an enzyme is specified by a series of four digits in increasing specificity [48]. The hierarchical nature of this classification system, in which each enzyme sequence can be thought of as a leaf node in a tree, accorded well with our use of a hierarchical risk function. Accordingly, using the learned

Figure 2: **Robust calibration of risk and probability for Pfam domain searches. (a)** Hits represent proteins with similarity score above λ, determined by controlling the FDR at $\alpha = 0.1$. This yields hits for 39.6% of un-annotated genes in JCVI Syn3.0 *Mycoplasma mycoides*. **(b)** We control FDR on exact Pfam matches to $\alpha = .1$ and demonstrate calibration across 100 trials. **(c)** FDR control at $\alpha = .1$ retrieves roughly 25% of true positives. **(d)** We control for a false negative rate (FNR) loss at $\alpha = .1$ and demonstrate $\hat{\alpha}$ is well calibrated across 100 trials. **(e)** Using the threshold λ controlling for FNR, we are able to reduce database size by 99% on average. **(f)** Plot of false negative rates (FNR) and false discovery rates (FDR) as a function of similarity score threshold λ. As expected, FDR decreases as $\lambda \to \max(S_{ij})$ and FNR increases as $\lambda \to \max(S_{ij})$. **(g)** Structural alignment between predicted structure of functional hit of previously unannotated protein in *Mycoplasma mycoides* and characterized exonuclease. **(h)** Venn-Abers predictors assign probability of exact Pfam match given scores S_{ij}. **(i)** The difference between Venn-Abers $\hat{p}^0, \hat{p}^1$ is low, indicating that probability computations are well calibrated. **(j)** Venn-Abers predictor shows excellent reliability with Expected Calibration Error $ECE = .002$

embeddings from CLEAN, our method fits a two-component Gaussian mixture model on the raw Euclidean distances between individual enzyme sequence embeddings and different EC number cluster embeddings. These EC cluster embeddings are computed using the mean embeddings across

Figure 3: **Results for utilizing conformal prediction for enzyme function annotation, using a leading classification model.** We compare the two methods for "EC-calling" proposed by CLEAN [48], $\mathsf{max-sep}$ (max-seperation) and $\mathsf{p-value}$ p-value selection, against our conformal method. We report confidence intervals through violin plots for 10 random shuffles of the dataset to ensure coverage across *New*. **(a)** Violin plots of ROC-AUC for conformal, $\mathsf{p-value}$, and $\mathsf{max-sep}$. **(b)** Violin plots of Recall for conformal, $\mathsf{p-value}$, and $\mathsf{max-sep}$. **(c)** Distribution of similarity scores in *New, Price* datasets. We observe a slight distribution shift in similarity scores between *New* and *Price*. **(d)** Violin plots of precision for conformal, $\mathsf{p-value}$, and $\mathsf{max-sep}$. **(e)** Violin plots of F1 for conformal, $\mathsf{p-value}$, and $\mathsf{max-sep}$. **(f)** Returned EC annotations for a SARS-COV-2 antibody. Conformal selection correctly identifies SARS-CoV-2 antigen-binding fragments (Fab) as not an enzyme, whereas $\mathsf{max-sep}$ and $\mathsf{p-value}$ methods from CLEAN return possible enzyme annotations. **(g)-(i)** Intuitive overview of selection methods for EC annotation using similarity scores.

all sequences in the training dataset which have been annotated with the EC number, forming a centroid for the class. At inference time, two selection methods are used to predict, with confidence, what EC numbers an enzyme sequence belongs to. The first, $\mathsf{max-sep}$ (*max-separation*), is a greedy approach that selects EC numbers with the maximum separation that stands out from other centroid

embeddings. The second, $\mathsf{p-value}$ (*p-value selection*), identifies EC number centroid similarity scores that stand out against the background distribution of $n = 20,000$ randomly sampled training similarity scores.

CLEAN has been evaluated on two independent datasets not included in the model's development to deliver a fair and rigorous benchmark study. The first, *New-392* [48], uses a date-cutoff on Uniprot to select 392 enzyme sequences covering 177 different EC numbers, containing data from Swiss-Prot released after CLEAN was trained (April 2022). The second, *Price-149*, was a set of experimentally validated results described by Price et al [34]. First curated by ProteInfer [36], *Price-149* is considered a challenging dataset because the existing sequences have frequently been incorrectly or inconsistently labeled in databases by automated annotation methods. Given the frequent misannotation in the field and the effort devoted to selection in CLEAN, we were interested in adapting the learn-then-test procedure independently for each dataset. Additionally, we wanted to explore whether calibrating on one dataset and evaluating on the second would maintain the coverage guarantees. This approach could potentially produce a more performant selection method than the two proposed by CLEAN.

A conformal-derived similarity threshold $\hat{\lambda}_{calib}$, in contrast to query-specific annotations, would i) provide performance guarantees for divergence against the hierarchical classification for some α, and ii) enable the model to output an empty set when it is uncertain about whether the protein should be classified with an EC number at all, an issue both $\mathsf{max-sep}$ and $\mathsf{p-value}$ selection do not reconcile. We demonstrate an example of this selection pathology in Figure 3. When asking CLEAN to annotate an antigen-binding fragment of a recently-developed SARS-COV-2 antibody (a protein that is evidently not an enzyme), both $\mathsf{max-sep}$ and $\mathsf{p-value}$ return annotated sets (as $\mathsf{max-sep}$ must return at least one annotation). In contrast, conformal risk control appropriately returns an empty one. CLEAN employs a Gaussian Mixture Model to assign a level of confidence to the results. While this method can measure probability and manually determine a confidence threshold for EC annotation, it comes with limitations. For high-throughput applications like metagenomic enzyme mining, conformal guarantees implicitly resolve these model pathologies, providing a more robust solution. As a result, we calibrate on $N = 380$ of the 392 query points provided by *New*, and report test precision score, recall score, F1-score, and area under curve (AUC) in addition to the hierarchical loss coverage on *Price-149*, following the metrics reported by CLEAN. Thus, we assemble distograms for both *New-392* and *Price-148* against all 5242 EC cluster embeddings in CLEAN's training set. We then compute per-query hierarchical loss scores to calibrate with conformal risk control.

We find that the conformal selection strategy, using the same underlying embeddings produced by CLEAN, outperforms both $\mathsf{max-sep}$ and $\mathsf{p-value}$ selection. Most excitingly, we find that not only does calibrating on *New*, and evaluating on a subset of *New* outperform the CLEAN selection methods, but calibrating on *New* and testing on the more difficult *Price* benchmark containing previously hard-to-annotate enzymes of unknown function also performs well. Despite the datasets not being exchangeable, and there being a noticeable shift in the distribution of similarity scores produced by CLEAN for both datasets, the hierarchical risk calibration strategy outperforms both prior selection methods. We believe this early work raises the opportunity to use our method, conformal protein retrieval, on a withheld subset of training data as a central, large calibration dataset before extending to many, separate annotation tasks for robust selection.

3.3 DALI prefiltering of diverse folds across the proteome

In addition, we demonstrate how to do robust and fast screening prior to using high resolution in-silico algorithms. While embedding-based search methods have brought about the ability to do large-scale searches, structural alignment methods are still essential due to their ability to provide detailed biochemical and functional insights. We explored the possibility of extending calibration on a task of related function, remote homology, and extend it to a broader task that inherently relies on the same shared structural knowledge. In this section, we aim to do so by building a robust prefiltering technique for running DALI structural alignments,

Classical methods for comparing protein structures, like DALI [28] and TM-align [49] confer high sensitivity for finding remote homologs and output a structural alignment. Structural alignment is crucial for biochemists and molecular biologists because it provides insights into the functional relationships, such as the identification of active sites, binding interactions, and conformational changes, which are often not evident from sequence comparisons alone. Traditionally, these structural alignment algorithms have been limited by the number of available protein structures and slower computational runtimes. Although accurate protein structure prediction methods such as AlphaFold2 [30] have vastly increased the number of available (predicted) protein structures and structural databases broadly, these algorithms still remain computationally infeasible at scale. Computing a classical structural alignment between a set of query proteins and large databases such as the AlphaFold Database (AFDB) [43], or even the recently clustered 2.3M subset of AFDB [12], requires time and specialized compute. For instance, computing an alignment for 73 SCOPe domains against all of the clustered AFDB took ~ 1 day on our highly optimized supercomputer setup with 10 threads. As access to high-performance computational resources becomes more limited and the number of protein folds continues to expand, this problem will become more intractable. In contrast, embedding-based search methods such as Protein-Vec can perform the same task in only about ~ 30 seconds on a modern laptop. Therefore, it is valuable to select proteins efficiently prior to conducting computationally expensive in-silico analyses.

Motivated by these slow runtimes to get high-quality structural alignments and similarity scores, we choose to calibrate risk with a faster embedding-search model, Protein-Vec, on a related task of homology. We then evaluate its ability to retrieve high-ranking Z-Score hits from a DALI search as the ground-truth metric. Although new tools have been developed to quickly estimate structural alignment scores [25], computationally expensive downstream analyses such as alignment and molecular dynamics will always be relevant for biologists. As such, developing a robust methodology to prefilter large databases of proteins into smaller subsets that retain a majority of proteins with desired biochemical function remains a critical challenge in the field.

Different datasets of proteins may contain diverse genes that have varying distributions of homologous sequences, depending on their protein family, superfamily, or fold. For instance in SCOPe 2.08 [22] clustered at 40% sequence identity some families contains >100 proteins, while others contain two or only one categorized protein. When determining the threshold λ, ensuring that we account for adaptive set sizes in our retrieval set to filter large sequence and structure databases is vital. In addition, some proteins may have no known homologs, in which case a model should return an empty search set. A threshold determined with conformal risk control allows for this while providing calibrated statistical guarantees.

For developing a prefilter for DALI alignments, using a fast but perhaps less sensitive model as a surrogate with stastical guarantees enables us to quickly search large databases. With the surrogate model's predictions, we aim to infer some threshold $\hat{\lambda}$ that can obtain our subset $\hat{C} \in D$ that contains hits of structural similarity to the query. With this subset $\hat{C}$, we can then perform

	$Z \geq Z'$			$Z \geq 2$			$\frac{N(S_{ij}>\lambda)}{N}$	$\frac{N(Z<2)}{N}$	Z'
	FNR	TPR	FDR	FNR	TPR	FDR			
Mean	0.182	0.818	0.997	0.282	0.718	0.943	0.685	0.947	5.130
Std	0.174	0.174	0.004	0.236	0.236	0.070	0.246	0.067	1.670
Min	0.000	0.290	0.979	0.010	0.108	0.712	0.104	0.737	3.200
Median	0.121	0.879	0.998	0.206	0.794	0.973	0.768	0.974	5.000
Max	0.710	1.000	1.000	0.893	0.990	1.000	0.978	1.000	14.600

(a) Statistical summary of DALI search hits excluded when filtering Protein-Vec hits.

Method	Runtime	Number of threads
DALI	~ 1 day	10
Protein-Vec	~ 30 s	1

(b) Comparison of runtime between DALI and protein-vec for searching 73 SCOPe domains against the full clustered AFDB.

Table 2: **Prefiltering of clustered AFDB prior to DALI structural alignment**. We demonstrate the utility of prefiltering the clustered AFDB, showing that it is possible to discard proteins in a lookup database a priori before structural alignment. **(a)** Prefiltering of 73 SCOPe domains against clustered AFDB before DALI structural alignment with $\hat{\lambda}$ determined by FNR risk control at $\alpha = 1\%$ for up to family-level ($\ell = 1$) mismatches on a different SCOPe family dataset. We report false negative rates and false discovery rates for discretization at $Z \geq Z'$ and $Z \geq 2$ where Z' refers to the $Z - score$ elbow found with the Kneedle algorithm. We also report summary statistics on the percentage of the data which is retained at the $\hat{\lambda}$ threshold ($\frac{N(S_{ij}>\lambda)}{N}$), the percentage of hits ($\frac{N(Z<2)}{N}$) that have DALI structural alignment score $Z < 2$, and the determined elbow Z' to match biologist intuition. **(b)** Comparison of runtimes of Protein-Vec and DALI. Given the substantial speed difference between new machine learning models and prior methods for structural alignment methods, it can behoove biologists to prefilter reference databases before structural alignment.

structural alignments with DALI, thereby reducing the overall search and computation time to feasible levels. Specifically, we recognize the uniqueness of the optimization problem: we aim to significantly reduce the 2.3M proteins in clustered AFDB while maintaining as minimal of a false negative rate (FNR) calibrated through conformal risk control. In effect, we seek to select the smallest possible set which captures nearly all high Z-score homologs that would have been identified by DALI in a comprehensive clustered AFDB search.

To measure our ability to do this, we demonstrate the use of conformal risk control to prefilter DALI across diverse "multi-domain" folds from the Structural Classification of Proteins—extended database (SCOPe) [22] (see 4.1.1 for selection procedure used in SCOPe prefilter strategy). We first embed all proteins in SCOPe and the clustered AFDB using Protein-Vec, and use conformal risk control to learn a $\hat{\lambda}$ that achieves a 1% false negative rate (FNR) for SCOPe families. This calibration task is disjoint from the subsequent task, where we use the calibrated threshold to search and select proteins from the clustered AFDB. By doing so, we aim to retain nearly all high Z-score

homologs identified by DALI. Although we use Protein-Vec for ease, we note this can be done with Foldseek and other fast models that mimic structural alignment scores.

We infer a threshold that may tolerate a higher false discovery rate (FDR) for low DALI Z-scores but ensures a low false negative rate (FNR) for DALI Z-scores greater than Z'. We define the threshold Z' as the elbow-point of the descending sorted Z scores per the Kneedle algorithm [38], representing the point where the rate of decrease in Z-scores starts to slow significantly. We consider partial matches as those diverging at the family but preserving superfamily-level homology. We then use the learned threshold, $\hat{\lambda}$, as a prefilter for the DALI multi-domain search task, obtaining a subset $\hat{C} \subset D$, where D 2.3M protein clustered AFDB (see Section 4.1.4 for preprocessing steps).

We illustrate the effectiveness of our prefiltering approach in Fig 4. We display the correlation between DALI and Protein-Vec similarity scores for SCOPe domains against the clustered AFDB. When looking at the correlation between DALI and Protein-Vec similarity scores for SCOPe domains against the clustered AFDB, two distinct takeaways emerge. First, retrieved hits with higher structural similarity scores S_{ij} in Protein-Vec, corresponding to $Z - score \geq 10$ in DALI, exhibit a distinct distribution shift, indicating our method's ability to capture significant hits. In contrast, $Z - score \geq Z'$ exhibits much greater variance in Protein-Vec similarity scores. Despite this, we show that the retrieved $\hat{C}$, captures 82.8% of hits above Z' from D, while filtering out 31.5% of the clustered AFDB (Table 2a).

These results demonstrate that our prefiltering method effectively reduces the size of the lookup database while retaining a majority of homologous proteins with desired biochemical properties. By significantly cutting down the clustered AFDB set while maintaining a low FNR, our approach enables more efficient and feasible structural alignments with DALI. This strategy not only saves computational resources but also ensures that high-affinity structural homologs are not missed, providing a valuable tool for biologists and biochemists in their research.

Figure 4: **Statistically robust prefiltering can reduce the size of a lookup database for high accuracy yet computationally intensive methods like DALI.** (**a**) Correlation between DALI and Protein-Vec similarity scores for SCOPe domains against the clustered AFDB. Proteins with a DALI $Z < 2$ are reported as $Z = 0$, as they are not outputted by DALI. (**b**) Distribution of Protein-Vec scores with associated Z-scores at different Z-score values. There is an observable distribution shift as Z increases. (**c**) Histogram of Z scores below and above the learned threshold λ to ensure $\alpha = .01$ FNR for SCOPe families. We observe that most of the distribution density for Protein-Vec scores $S_{i}j < \lambda$ is contained below Z', the elbow in the Z-score distribution.

3.4 UniProt-wide retrieval of enzyme classes and SCOPe folds

In the previous section 3.3, we show a screening method for reducing the size of lookup databases while preserving high quality hits. Here, we instead wish to draw a bridge between conformal risk control and providing guarantees for precise classification tasks that are hierarchical in nature, such as that of protein structural and enzymatic specificity. In the process of doing so, we demonstrate how to improve interpretability for biologists searching through hierarchical data.

Figure 5: **Robust calibration of hierarchical risk for SCOPe and EC searches.** We demonstrate calibration at $\alpha = 1, 2$ hierarchical losses, and report test loss over 100 trials for both. We also observe, that for both the SCOPe and EC tasks, max hierarchical loss falls as a function of similarity score threshold λ, i.e., the loss is monotone and conformal guarantees apply under conformal risk control. **(a)** SCOPe: $\alpha = 1$. $\mu(\hat{\alpha}) = 0.9645$ over 100 trials. **(b)** SCOPe: $\alpha = 2$. $\mu(\hat{\alpha}) = 1.994$ over 100 trials. **(c)** Hierarchical Loss: SCOPe. **(d)** EC: $\alpha = 1$. $\mu(\hat{\alpha}) = 0.977$ across '100 trials. **(e)** EC: $\alpha = 2$. $\mu(\hat{\alpha}) = 1.980$ across 100 trials. **(f)** Hierarchical Loss: EC.

For instance, a common benchmark for remote homology methods is to examine model sensitivity on SCOPe, specifically the fraction of true positives (TPs) to a query protein q_i detected until the first incorrect family/fold/superfamily is detected. Similarly, as mentioned before for CLEAN, model sensitivity for EC calling is also often used to measure method performance. As a result of the hierarchical nature of these classification tasks, we aimed to establish that hierarchical and false negative rate (FNR) risk control could consistently provide coverage across many iterations of randomly shuffling the indices belonging to the held-out test set. Using an extended form of the *New* dataset, we designate 438 query proteins that pass a date cutoff from the Uniprot database used by

Protein-Vec, against 211720 proteins that are filtered to have a fully-characterized EC hierarchy. We choose to do so as Aspect-Vec (a single-task Protein-Vec) model, reports better performance than CLEAN, owing to the use of per-residue embeddings over mean-pooling. Thus, we decide to use the model to simulate a harder retrieval problem than CLEAN EC-calling, where classification isn't performed simply by designating 'hits' as EC cluster centers with high similarity scores, but rather other enzymes in UniProt which may or may not even belong to an EC classification that has a set size larger than 1.

We employ two different calibration losses to calibrate and find $\hat{\lambda}$, i) the hierarchical loss and ii) false negative rate control. For both, we demonstrate, across 100 trials, that the risk is controlled across arbitrary test subsets of the SCOPe and EC tasks. For SCOPe, we measure risk control across tolerance for fold-level ($\alpha = 1$) and superfamily-level ($\alpha = 2$) mismatches, demonstrating that the mean loss across trials, $\hat{\alpha}$ converges to α that aligns to the constraint set during calibration 5. We do the same for EC, measuring risk control for the same α's on the EC hierarchy, achieving similar results. We also find that calibrating on FNR = 0.1 holds coverage on both tasks, with the majority of trials reporting a test FNR $\leq \alpha$. We also observe, when measuring hierarchical loss across linearly interpolated λ thresholds from the minimum to max Protein-Vec similarity for both tasks, that the loss monotonically decreases as the similarity threshold increases (permitting fewer lookup proteins into the confidence set). This is a strong advantage for the adaptation of risk control, as a monotone loss means we have conformal guarantees on our hierarchical constraints, as defined by the upper bound intervals in Eq 4, Eq 5 .

4 Methods

In this section, we overview the mathematical tools we use in order to perform retrieval for protein homologs. In particular, the key is various methods for constructing subsets of protein space which have guarantees of retrieval, but are small enough to narrow down the search process.

Throughout this section, we will use the following notation. We will let $\mathcal{X}$ and $\mathcal{Y}$ be the query and response (lookup) proteins, respectively. In the retrieval problem, we seek to associate each query $x \in \mathcal{X}$ with a set of responses. Given a set $\mathcal{C} \subseteq \mathcal{Y}$, we measure the quality of the set $\mathcal{C}$ using a loss function:

$$\ell(x, \mathcal{C}) \in [0, B] \text{ for some } B < \infty. \tag{1}$$

As an example of a loss function, imagine that for every the query protein $x \in \mathcal{X}$ and response protein $y \in \mathcal{Y}$, we can associate a degree of SCOPe ID matching, $\mathsf{match}(x, y) \in \{0, 1, 2, 3, 4\}$. When $\mathsf{match}(x, y) = 0$, it means the proteins are an *exact match*—that they each have a site with exactly the same SCOPe family. Meanwhile, when $\mathsf{match}(x, y) = 4$, it means that the proteins are not even in the same SCOPe class. Intermediate levels of matching indicate intermediate SCOPe ID matches. With this match function in hand, we can define the loss function as, for example, the fraction of our retrieved set that is *not* exact matches. Mathematically, this loss function is

$$\ell(x, \mathcal{C}) = \frac{1}{|\mathcal{C}|} \sum_{y \in \mathcal{C}} \mathbb{1} \left\{ \mathsf{match}(x, y) \neq 0 \right\}, \tag{2}$$

where $\mathbb{1}$ is the indicator function that takes the value 1 when the argument is true and 0 otherwise. We are trying to generate retrieval sets that ensure this loss is small.

Our main tool will be to index some family of sets by a one-dimensional parameter, $\lambda \in \mathbb{R}$. We will refer to this family of sets as $\mathcal{C}_\lambda$. An example would be

$$\mathcal{C}_\lambda(x) = \{y \in \mathcal{Y} : f(x,y) \geq \lambda\}, \tag{3}$$

where f is a pre-trained machine learning model trained to predict whether x and y match. The methodologies exposed herein allow us to pick the parameter λ such that these sets have a small loss in a probabilistic sense,

$$\mathbb{E}[\ell(X, \mathcal{C}_{\hat{\lambda}}(X))] \leq \alpha. \tag{4}$$

The parameter $\hat{\lambda}$ is picked based on a calibration procedure which uses a small dataset of proteins the model has not seen during training. We will call this calibration dataset $X_1, \ldots, X_n$, and we assume we can evaluate ℓ against any of the possible responses in $\mathcal{Y}$. Then, we will deploy the $\hat{\lambda}$ that is picked using this calibration data on a new, exchangeable protein X_{test}.

The critical assumption in all the forthcoming techniques is the *exchangeability* of the calibration data and the test point. Exchangeability means that the joint distribution function of the calibration data and the test data point is invariant to permutations. As an example, i.i.d. data points are exchangeable; exchangeability is a weaker condition than this. Intuitively, this means that the calibration data must be representative of the test data, and not involve any deleterious distribution shifts.

4.0.1 Conformal risk control

Conformal risk control [5] is an extension of conformal prediction that provides an algorithm for satisfying (4) when the function $\lambda \mapsto \ell(x, \mathcal{C}_\lambda(x))$ is monotone for all x. The threshold function $\hat{\lambda}$ in the following way:

$$\hat{\lambda} = \inf\left\{\lambda : \frac{1}{n}\sum_{i=1}^{n} \ell(x, \mathcal{C}_\lambda(x)) \leq \alpha - \frac{1-\alpha}{n}\right\}. \tag{5}$$

When the data points $X_1, \ldots, X_n$ and X are exchangeable, this results in exactly the guarantee in (4).

Hierarchical risk control. Here, we explain how conformal risk control can be used to do hierarchical prediction of the SCOPe/CATH ID/EC of a protein. In other words, we will directly address the task of predicting a family for protein X. Protein families are normally classified in a hierarchy through SCOPe and CATH, with their place in the hierarchy represented as a vector:

$$h(x) = (A, B, C, D), \tag{6}$$

where A, B, C, and D are strings corresponding to the domain, superfamily, fold, and family, respectively. We let $\mathcal{C}$ take values in the space $\{A\} \cup \{A.B\} \cup \{A.B.C\} \cup \{A.B.C.D\}$, for all integers A, B, C, and D, respectively. Let our loss function be as follows:

$$\ell(x, \mathcal{C}) = c_{\min\{i \in [4] : h(x)_i = \mathcal{C}_i\}}, \tag{7}$$

where c_i are nonnegative constants. An example would be $c_1 = 3$, $c_2 = 2$, $c_3 = 1$, and $c_4 = 0$, in which case the loss function reduces to $\mathsf{match}(x, \mathcal{C})$. The key observation is that running conformal risk control at level α with the above loss results in the following property:

$$\mathbb{P}(\ell(X, \mathcal{C}_{\hat{\lambda}}(X)) = i) \leq \frac{\alpha}{c_i}, \tag{8}$$

for all i. (Here, $\alpha/0 = \infty$.) Intuitively, this means that conformal risk control can be used to simultaneously bound the probability of all mismatches, with a penalty that grows as the mismatches become more extreme. The proof of this property follows from the definition of the expected value:

$$\mathbb{E}[\ell(X, \mathcal{C}(X))] \leq \alpha \iff \sum_{i=1} c_i \mathbb{P}(\ell(X, \mathcal{C}(X)) = 4 - i) \leq \alpha \implies c_i \mathbb{P}(\ell(X, \mathcal{C}(X)) = 4 - i) \leq \alpha, \forall i. \quad (9)$$

Non-monotone risks. In this paper, we also handle non-monotone risks with an extension of conformal risk control, in high probability, called Learn then Test (LTT). The main difference between this procedure and conformal risk control are twofold. First, the space of λ, denoted Λ, must be discrete. Second, the guarantee in (4) holds in high probability over the n calibration points. However, the algorithms have a roughly similar flavor; the variant of LTT we employ in all our experiments is simply a different way of setting $\hat{\lambda}$, and takes the form

$$\hat{\lambda} = \inf \left\{ \lambda \in \Lambda : R^+(\lambda) \leq \alpha \right\}, \quad (10)$$

using any concentration bound $\mathbb{P}(R^+(\lambda) > \mathbb{E}[\ell(X, \mathcal{C}_\lambda(X))]) \leq \delta$ for all λ. We defer further detail on this procedure to [4].

4.0.2 Assigning probability to hits: isotonic regression and Venn-Abers predictors

The next method we present is geared towards a different goal: calibration. That is, given a protein x and a retrieval y, we would like to produce a probability that the retrieval is correct. We allow for any notion of correctness, parameterizing a function $\mathsf{correct}(x, y) \in \{0, 1\}$; the indicator of an exact match is one possible choice of $\mathsf{correct}$. The formal goal is to produce a probability $\hat{p}$ satisfying $\mathbb{P}(\mathsf{correct}(x, y) = 1 \mid \hat{p}) = \hat{p}$.

In this section, we develop our techniques in the setting that each protein X has a set of labeled retrieval proteins, $Y^{(1)}, \ldots, Y^{(m)}$. Then, we would like to predict the probability of $\mathsf{correct}(X, Y) = 1$ on a new, unlabeled retrieval protein Y. We also assume we have a pre-fit estimate of this quantity, such as the confidence of a retrieval system. This retrieval system estimate may not be any good, and its probabilities may be very uncalibrated. Our goal is to calibrate these probability estimates. We denote them as $\widehat{\mathsf{correct}}_i = \widehat{\mathsf{correct}}(X, Y^{(i)})$, and assume without loss of generality that they are sorted.

The canonical method for correcting these probabilities is called isotonic regression [16]. Isotonic regression solves the following optimization problem:

$$\underset{\hat{p}_1, \ldots, \hat{p}_n}{\text{minimize}} \sum_{i=1}^{n} (\hat{p}_i - \mathsf{correct}_i)^2 \quad (11)$$
$$\text{subject to } \hat{p}_1 \leq \ldots \leq \hat{p}_n.$$

This is a convex problem admitting simple $\mathcal{O}(n)$-complexity solutions (using algorithms first introduced by [17] and [9]). Once the sequence $\hat{p}_1, \ldots, \hat{p}_n$ is found, then we can set

$$\hat{p} = \sum_{i=1}^{n} \hat{p}_j \mathbb{1} \left\{ \widehat{\mathsf{correct}}(x, y) \in \left[\widehat{\mathsf{correct}}_{j-1}, \widehat{\mathsf{correct}}_j \right] \right\}, \quad (12)$$

(When $j = 0$, we set $\widehat{\mathsf{correct}}_j = 0$.)

Under normal circumstances, the isotonic regression algorithm, given n independent and identically distributed data points with (X, Y), will converge to a calibrated estimate for $\hat{p}(X, Y)$ as $n \to \infty$. The Venn-Abers predictor [46] offers an alternative calibration strategy that does not require $n \to \infty$.

The Venn-Abers predictor works by running *two* isotonic regressions with hypothetical values for $\mathsf{correct}(X, Y)$. Namely, for $b \in \{0, 1\}$, define

$$\hat{p}_1^b, \ldots, \hat{p}_n^b, \hat{p}^b = \underset{\hat{p}_1, \ldots, \hat{p}_n, \hat{p}}{\text{minimize}} \sum_{i=1}^n (\hat{p}_i - \mathsf{correct}_i)^2 + (\hat{p} - b) \tag{13}$$
$$\text{subject to } \mathsf{order}(\hat{p}_1, \ldots, \hat{p}_n, \hat{p}) = \mathsf{order}(\widehat{\mathsf{correct}}_1, \ldots, \widehat{\mathsf{correct}}_n, \widehat{\mathsf{correct}}(X, Y)),$$

where order returns the list of indexes sorting its argument.

When the data points are exchangeable, the Venn-Abers predictor gives the following guarantee:

$$\mathbb{P}(\mathsf{correct}(X, Y) = 1 \mid \hat{p}^0) = \hat{p}^0 \text{ or } \mathbb{P}(\mathsf{correct}(X, Y) = 1 \mid \hat{p}^1) = \hat{p}^1. \tag{14}$$

Thus, the interval $[\hat{p}^0, \hat{p}^1]$ is a valid interval on the probability of correctness. One can use this strategy to report to the user that the proteins X and Y are, say, $70\% - 73\%$ likely to be a match.

4.1 Dataset preparation

4.1.1 SCOPe and Pfam IDs

We select both query and lookup proteins from both UniProtKB [18] and SCOPe [22]. We use an annotated and reviewed version of UniProtKB from July 3, 2023 and select all proteins created in the database after May 25, 2022, as per [24]. The split was select to ensure there is no train-calibration leakage for the proteins used to calibrate the conformal score. This leaves $2,350$ proteins as calibration/validation, used for querying a lookup set of the remaining $540,560$ proteins. These are filtered further depending on the labels associated with the desired conformal guarantee, ie proteins annotated with Pfams. To examine guarantees across proteins with hierarchical relationships, we draw from the Astral Structural Classification of Proteins (SCOPe) [22] database version 2.08, using 40% sequence identity threshold in order to simulate the test case of remote homology. This leaves 15,177 domains in the training set across over 4693 families. For calibration, we use a test set of 400 domains, which are ensured to have $< 30\%$ sequence identity to every protein in the training set. This ensures that the model is adequately evaluated on its ability to capture features relating to remote homology. The domains in the set are filtered to have at least one other family, superfamily and fold member. For SCOPe, we calibrate on 300 proteins and test on 100 proteins

For each model and query protein q_i, we return an ordered list of lookup proteins v_j and their similarity scores to the query as $S_{ij} = f(q_i, v_j)$, along with the associated metadata (i..e. UniProt ID) of the query and list of lookup proteins (i.e.: annotated Pfams, SCOPe IDs, organism information, etc). We generate scores S_{ij} using Protein-Vec [24]; we also tested similarites derived from TOPH [15], TM-Vec [25], and Foldseek [42]. We return a rank-ordered list by similarity for each query protein q_i using FAISS.

4.1.2 Enzyme classification (EC) within UniProt

Similarly to before, we use an annotated and reviewed version of UniProtKB from July 3, 2023 and select all proteins created in the database after May 25, 2022 as our evaluation queries q_i. We filter

our lookup and query/evaluation sets Uniprot to only choose proteins with fully characterized EC numbers (ex: containing the full hierarchy $'a.b.c.d'$), returning a lookup set size of 211720 and a query set size of 438. This forms our distance matrix of size (438×211720) which we calibrate with conformal risk control using the hierarchical loss function $\mathsf{match}(x, y) = \{0, 1, 2, 3, 4\}$ as described in (Sec 4). For the EC task, we calibrate on 300 and test on the remaining 138 proteins.

4.1.3 CLEAN enzyme classification preparation

For the generalizability test, we calibrate on $N_Q = 380$ query points of the 392 provided by *New* to maximize the calibration dataset size,. We report test precision score, recall score, F1-score, and area under curve (AUC) in addition to the hierarchical loss coverage on *Price-149*, following the metrics reported by CLEAN [48]. Thus, we assemble distograms for both *New-392* and *Price-148* against all EC cluster embeddings in CLEAN's training set, forming size $(N_Q, 5242)$ matrices where N_Q represents the number of query proteins, and compute per-query hierarchical loss scores to calibrate with conformal risk control. EC numbers are normally classified in a hierarchy vector $h(x) = (A, B, C, D)$ where (A, B, C, D) refer to enzyme class, subclass, sub-subclass, and serial number respectively. It is worth noting that some enzymes may be missing labels at the lower level of the hierarchy; these are denoted as $*$ (for instance 2.3.1.$*$ or 2.3. $*$.$*$ as Acyltransferases without further characterization). We use the hierarchical loss $\mathsf{match}(x, y) = \{0, 1, 2, 3, 4\}$, where $\mathsf{match}(x, y) = 0$ if $h(x) = h(y)$ exactly (two enzymes share the same class, subclass, sub-subclass, and serial number) and $\mathsf{match}(x, y) = 4$ if $h(x)[0] \neq h(y)[0]$ (two enzymes are from different classes altogether). We note that this choice of hierarchical loss is arbitrary and can be tuned to specific application areas; for instance one may choose loss $\mathsf{match}(x, y) = \{0, 1, 2, 4, 100\}$ to significantly penalize class-level mismatches for enzyme functional annotation. We calibrate at $\alpha = 1$ for the *New* test benchmark, and $\alpha = 1.5$ for the *Price* generalizability benchmark. We chose a different loss threshold, $\alpha = 1$, primarily because in the hierarchical classification scheme provided by EC, the finest-resolution 4th digit is often a "serial number", differentiating between different enzymes having similar function, on the basis of the actual substrate in the reaction. In this regime, serial number errors may be somewhat tolerable to the experimentalist, whereas sub-subclass errors are less so. Thus, for a dataset with a distribution shift from *New*, such as *Price*, one may want to be more *tolerant* in the retrieval process and calibrate the model to consider mismatches 50% of the time at the sub-subclass level, and 50% of the time at the finest sub-subclass level (producing an expected $\alpha = 1.5$), to accurately obtain all enzymes of similar function. Additionally, many "preliminary" annotated enzymes exist with specificity only to the sub-subclass, so encouraging partial matches is important to attenuate the false negative rate (FNR), implicitly.

We note that each query protein in *New* and *Price* may have multiple possible valid EC assignments. Thus, we take the minimum hierarchical loss over retrieved train EC clusters/centroids as the final loss. i.e: for all EC labels $y_i \in \mathcal{Y}$, and k valid EC assignments for x, take:

$$\ell(x, ec_i) = \min(\mathsf{match}(x_i, y_i)), (x_i, ..., x_k), \forall y_i \in \mathcal{Y}$$

Here, if a test enzyme x has k valid EC assignments $(x_1, ..., x_k)$, we want to evaluate retrieval using the assignment that produces the minimum hierarchical loss against the returned set. We do this to not unfairly penalize the model as long as it is retrieving EC cluster centroids that are close in hierarchy to one possible assignment.

4.1.4 Preprocessing of diverse Dali folds across the proteome

We extracted all 73 entries classified as "multidomain" from the Structural Classification of Proteins—extended database (SCOPe) [22]. Each entry's corresponding Protein Data Bank (PDB) file was retrieved using its unique PDB identifier (PDBID) from the Research Collaboratory for Structural Bioinformatics (RCSB) PDB database. These files were then processed into the DALI compatible format using the built-in import function (`import.pl`) of the DALI software [28].

We utilized 73 of these chains (one was omitted as it was too short for DALI) as query structures to search against a specialized database of 2.3 million non-singleton structure representatives from the Foldseek Clustered AlphaFold database, as described in [12]. To enhance the efficiency of the DALI search process, the database was divided into multiple batches, each containing 1,000 structures. The searches were conducted in parallel across these batches using multiple threads to optimize computational resource usage and decrease total runtime.

Similarly, we constructed the equivalent query and lookup set for both Protein-Vec and TM-Vec. We embed both the entire sequence database of the 2.3M Foldseek Clustered Alphafold database, as well as the 73 "multidomain" SCOPe entries, on a single A6000 GPU. Using FAISS, we index and generate similarity scores for the entire query $\times$ lookup set.

5 Discussion

The rapid increase in genomic data and the development of new algorithms for protein search mark an exciting time for computational biology. In this study, we demonstrate a robust approach for protein search that provides statistical guarantees on the retrieval of homologous proteins, thereby enabling prioritization for further biochemical and biophysical characterization. Our method is grounded in conformal prediction, which enables the transformation of raw similarity scores into interpretable confidence sets and probabilities. Our approach for statistical guarantees in protein retrieval has meaningful applications across multiple areas in biochemistry, bioinformatics, and structural biology. Namely, we show statistically valid annotation of genes previously deemed as genes of unknown function, state of the art performance on an enzyme classification task without training a deep learning model, and robust prefiltering of the clustered AlphaFold Database to reduce computational burden for structural alignment.

Although we extensively use Protein-Vec in this work, our approach is model agnostic and can be used with any search algorithm. Indeed, protein search methods that rely on embedding pairs of proteins and computing their cosine similarity via FAISS can especially benefit with additional statistical guarantees. It is conceivable that faster structural search algorithms such as Foldseek could show an even greater improvement in prefiltering the clustered AFDB for an individual query prior to performing a more intensive structural alignment. Additionally, we could better calibrate a prefilter threshold using DALI scores for our entire SCOPe40 2.08 test vs lookup set, and calibrating to find some binned z-score threshold we wish to consistently retrieve in our confidence set. Such an approach would enable the calibration set to be truly *exchangeable* to the test DALI scores we are filtering against, and likely result in a higher filter and lower FNR rate.

Our approach is not without limitations. Conformal prediction assumes exchangeability, which may not apply to all protein homology searches. However, this is not always the case with proteins due to several factors. Organisms are sampled at different frequencies, leading to a bias where certain protein families are overrepresented, particularly those from more frequently studied organisms. When presented with new data, this may result in distribution shifts that are challenging for

the underlying conformal approach. Additionally, the quality of samples can vary significantly, with metagenomic proteins often being of lower quality compared to those from well-characterized organisms. Furthermore, some protein families may be missing altogether, as we have only sequenced a fraction of the life on Earth. Finally, these datasets often lack large individual variation; single amino acid changes can meaningfully alter a protein's active site and function, yet alignment-based methods may not fully capture these subtle but important differences. Calibration is only as good as the quantity and quality of labeled data, which underscores the importance of comprehensive and accurate datasets for achieving reliable results. There is no silver bullet to address such distribution shifts; however, there have been many recent advances in conformal prediction under distribution shift that can be brought to bear on the topic [11, 41, 13, 23]. Extending our method using these techniques would be an interesting topic for future research, although it would increase the complexity of the calibration process.

We do not produce uncertainty bounds in the underlying similarity score for a pair of proteins, but instead uncertainty between a query and lookup database. For a model such as TM-Vec which estimates the structural TM-align scores for a pair of two protein sequences, methods such as conformal quantile regression [35] could be used to provide confidence bounds around the true TM-align score. Furthermore, given that many new protein search models leverage advances in protein language models, it may be advantageous to use the sequence perplexity derived from these language models. Indeed, it has been shown that protein language models are biased by unequal sequence sampling across the tree of life [19], which can result in higher sequence perplexity for other organisms.

In summary, our work represents a significant step forward in the field to move from protein search to experimental characterization by integrating statistical guarantees through conformal prediction. The ability to annotate genes of unknown function, classify enzymes with high accuracy, and reduce computational overhead for structural alignments highlights the practical benefits of our approach. As the volume and diversity of genomic data continue to expand, the need for reliable and efficient protein search methods becomes increasingly critical. Future advancements in conformal prediction and protein language models will further enhance the robustness and applicability of these methods, driving new discoveries and innovations in biology. Our framework addresses the challenge of screening and selection proteins for deeper characterization, paving the way for more reliable and efficient discovery of proteins with valuable functional properties.

Code and data availability

Code for algorithms and figures is available at https://github.com/ronboger/conformal-protein-retrieval/. Associated data can be reproduced through executing the notebooks, but will be added in consolidated form through a Zenodo link in the Github repository shortly.

Acknowledgements

We thank members of the Doudna lab and the Innovative Genomics Institute for helpful discussions. We thank UCSF for giving us access to the high performance compute cluster Wynton to meet our compute needs. We acknowledge Dr. Daniel Bellieny Rabelo for helping run DALI on the Wynton compute cluster and Dr. Benjamin A. Adler, Dr. Jason Nomburg, Kenneth M. Loi, and Marena Trinidad for helpful feedback on the manuscript.

RSB thanks the Henry Wheeler Center for Emerging and Neglected Diseases (CEND) at UC Berkeley for the Thomas C. Alber Science & Engineering for Global Health fellowship. SC thanks the Masason Foundation, the Mercatus Center for the Emergent Ventures Fellowship, and New Science for the Computational Life Sciences micogrant.

References

[1] S. F. Altschul, W. Gish, W. Miller, E. W. Myers, and D. J. Lipman. Basic local alignment search tool. *Journal of molecular biology*, 215(3):403–410, 1990.

[2] J. Alvarsson, S. A. McShane, U. Norinder, and O. Spjuth. Predicting with confidence: using conformal prediction in drug discovery. *Journal of Pharmaceutical Sciences*, 110(1):42–49, 2021.

[3] A. N. Angelopoulos and S. Bates. A gentle introduction to conformal prediction and distribution-free uncertainty quantification. *arXiv preprint arXiv:2107.07511*, 2021.

[4] A. N. Angelopoulos, S. Bates, E. J. Candès, M. I. Jordan, and L. Lei. Learn then test: Calibrating predictive algorithms to achieve risk control. *arXiv preprint arXiv:2110.01052*, 2021.

[5] A. N. Angelopoulos, S. Bates, A. Fisch, L. Lei, and T. Schuster. Conformal risk control. *arXiv preprint arXiv:2208.02814*, 2022.

[6] A. N. Angelopoulos, S. Bates, J. Malik, and M. I. Jordan. Uncertainty sets for image classifiers using conformal prediction. In *International Conference on Learning Representations (ICLR)*, 2021.

[7] A. N. Angelopoulos, A. P. Kohli, S. Bates, M. I. Jordan, J. Malik, T. Alshaabi, S. Upadhyayula, and Y. Romano. Image-to-image regression with distribution-free uncertainty quantification and applications in imaging. *arXiv preprint arXiv:2202.05265*, 2022.

[8] A. N. Angelopoulos, K. Krauth, S. Bates, Y. Wang, and M. I. Jordan. Recommendation systems with distribution-free reliability guarantees. In *Conformal and Probabilistic Prediction with Applications*, pages 175–193. PMLR, 2023.

[9] M. Ayer, H. D. Brunk, G. M. Ewing, W. T. Reid, and E. Silverman. An empirical distribution function for sampling with incomplete information. *The annals of mathematical statistics*, pages 641–647, 1955.

[10] R. Barber, E. Candès, A. Ramdas, and R. Tibshirani. The limits of distribution-free conditional predictive inference. *Information and Inference*, 10(2):455–482, 08 2021.

[11] R. F. Barber, E. J. Candes, A. Ramdas, and R. J. Tibshirani. Conformal prediction beyond exchangeability. *The Annals of Statistics*, 51(2):816–845, 2023.

[12] I. Barrio-Hernandez, J. Yeo, J. Jänes, M. Mirdita, C. L. Gilchrist, T. Wein, M. Varadi, S. Velankar, P. Beltrao, and M. Steinegger. Clustering predicted structures at the scale of the known protein universe. *Nature*, 622(7983):637–645, 2023.

[13] O. Bastani, V. Gupta, C. Jung, G. Noarov, R. Ramalingam, and A. Roth. Practical adversarial multivalid conformal prediction. *Advances in Neural Information Processing Systems*, 35:29362–29373, 2022.

[14] S. Bates, A. Angelopoulos, L. Lei, J. Malik, and M. I. Jordan. Distribution-free, risk-controlling prediction sets. *Journal of the ACM*, 68(6), Sept. 2021.

[15] R. Boger, A. Lu, S. Chithrananda, K. Yang, P. Skopintsev, B. Adler, E. Wallace, P. Yoon, P. Abbeel, and J. Doudna. Toph (true retrieval of proteins homologs): Adapting a contrastive question-answering framework for protein search. *ICML workshop on computational biology*, 2023.

[16] H. Brunk, R. E. Barlow, D. J. Bartholomew, and J. M. Bremner. Statistical inference under order restrictions.(the theory and application of isotonic regression). *International Statistical Review*, 41:395, 1972.

[17] H. D. Brunk. Maximum likelihood estimates of monotone parameters. *The Annals of Mathematical Statistics*, pages 607–616, 1955.

[18] U. Consortium. Uniprot: a worldwide hub of protein knowledge. *Nucleic acids research*, 47(D1):D506–D515, 2019.

[19] F. Ding and J. N. Steinhardt. Protein language models are biased by unequal sequence sampling across the tree of life. *bioRxiv*, pages 2024–03, 2024.

[20] K. Ding, J. Luo, and Y. Luo. Leveraging conformal prediction to annotate enzyme function space with limited false positives. *PLOS Computational Biology*, 20(5):e1012135, 2024.

[21] C. Fannjiang, S. Bates, A. N. Angelopoulos, J. Listgarten, and M. I. Jordan. Conformal prediction under feedback covariate shift for biomolecular design. *Proceedings of the National Academy of Sciences*, 119(43):e2204569119, 2022.

[22] N. K. Fox, S. E. Brenner, and J.-M. Chandonia. SCOPe: Structural Classification of Proteins—extended, integrating SCOP and ASTRAL data and classification of new structures. *Nucleic Acids Research*, 42(D1):D304–D309, 12 2013.

[23] I. Gibbs and E. Candes. Adaptive conformal inference under distribution shift. *Advances in Neural Information Processing Systems*, 34:1660–1672, 2021.

[24] T. Hamamsy, M. Barot, J. T. Morton, M. Steinegger, R. Bonneau, and K. Cho. Learning sequence, structure, and function representations of proteins with language models. *bioRxiv*, pages 2023–11, 2023.

[25] T. Hamamsy, J. T. Morton, R. Blackwell, D. Berenberg, N. Carriero, V. Gligorijevic, C. E. Strauss, J. K. Leman, K. Cho, and R. Bonneau. Protein remote homology detection and structural alignment using deep learning. *Nature biotechnology*, pages 1–11, 2023.

[26] Y. Hechtlinger, B. Póczos, and L. Wasserman. Cautious deep learning. *arXiv preprint arXiv:1805.09460*, 2018.

[27] T. V. Himabindu, V. Padmanabhan, and A. K. Pujari. Conformal matrix factorization based recommender system. *Information Sciences*, 467:685–707, 2018.

[28] L. Holm. Using dali for protein structure comparison. *Structural Bioinformatics: Methods and Protocols*, pages 29–42, 2020.

[29] C. A. Hutchison III, R.-Y. Chuang, V. N. Noskov, N. Assad-Garcia, T. J. Deerinck, M. H. Ellisman, J. Gill, K. Kannan, B. J. Karas, L. Ma, et al. Design and synthesis of a minimal bacterial genome. *Science*, 351(6280):aad6253, 2016.

[30] J. Jumper, R. Evans, A. Pritzel, T. Green, M. Figurnov, O. Ronneberger, K. Tunyasuvunakool, R. Bates, A. Žídek, A. Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

[31] V. R. Kagita, A. K. Pujari, V. Padmanabhan, S. K. Sahu, and V. Kumar. Conformal recommender system. *Information Sciences*, 405:157–174, 2017.

[32] C. Lu, A. N. Angelopoulos, and S. Pomerantz. Improving trustworthiness of ai disease severity rating in medical imaging with ordinal conformal prediction sets. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 545–554. Springer, 2022.

[33] C. Lu, A. Lemay, K. Chang, K. Höbel, and J. Kalpathy-Cramer. Fair conformal predictors for applications in medical imaging. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 12008–12016, 2022.

[34] M. N. Price, K. M. Wetmore, R. J. Waters, M. Callaghan, J. Ray, H. Liu, J. V. Kuehl, R. A. Melnyk, J. S. Lamson, Y. Suh, et al. Mutant phenotypes for thousands of bacterial genes of unknown function. *Nature*, 557(7706):503–509, 2018.

[35] Y. Romano, E. Patterson, and E. Candes. Conformalized quantile regression. *Advances in Neural Information Processing Systems*, 32, 2019.

[36] T. Sanderson, M. L. Bileschi, D. Belanger, and L. J. Colwell. Proteinfer, deep neural networks for protein functional inference. *Elife*, 12:e80942, 2023.

[37] M. Sapounidou, U. Norinder, and P. L. Andersson. Predicting endocrine disruption using conformal prediction–a prioritization strategy to identify hazardous chemicals with confidence. *Chemical Research in Toxicology*, 36(1):53–65, 2022.

[38] V. Satopaa, J. Albrecht, D. Irwin, and B. Raghavan. Finding a "kneedle" in a haystack: Detecting knee points in system behavior. In *2011 31st International Conference on Distributed Computing Systems Workshops*, pages 166–171, 2011.

[39] J. Sun, L. Carlsson, E. Ahlberg, U. Norinder, O. Engkvist, and H. Chen. Applying mondrian cross-conformal prediction to estimate prediction confidence on large imbalanced bioactivity data sets. *Journal of chemical information and modeling*, 57(7):1591–1598, 2017.

[40] F. Svensson, N. Aniceto, U. Norinder, I. Cortes-Ciriano, O. Spjuth, L. Carlsson, and A. Bender. Conformal regression for quantitative structure–activity relationship modeling—quantifying prediction uncertainty. *Journal of Chemical Information and Modeling*, 58(5):1132–1140, 2018.

[41] R. J. Tibshirani, R. Foygel Barber, E. Candes, and A. Ramdas. Conformal prediction under covariate shift. *Advances in neural information processing systems*, 32, 2019.

[42] M. van Kempen, S. S. Kim, C. Tumescheit, M. Mirdita, J. Lee, C. L. Gilchrist, J. Söding, and M. Steinegger. Fast and accurate protein structure search with foldseek. *Nature Biotechnology*, pages 1–4, 2023.

[43] M. Varadi, S. Anyango, M. Deshpande, S. Nair, C. Natassia, G. Yordanova, D. Yuan, O. Stroe, G. Wood, A. Laydon, et al. Alphafold protein structure database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. *Nucleic acids research*, 50(D1):D439–D444, 2022.

[44] V. Vovk. Conditional validity of inductive conformal predictors. In *Proceedings of the Asian Conference on Machine Learning*, volume 25, pages 475–490, 2012.

[45] V. Vovk, A. Gammerman, and G. Shafer. *Algorithmic Learning in a Random World.* Springer, New York, NY, USA, 2005.

[46] V. Vovk and I. Petej. Venn-abers predictors. *arXiv preprint arXiv:1211.0025*, 2012.

[47] C. Wang, F. Wang, R. Guo, Y. Liang, K. Liu, and P. S. Yu. Confidence-aware fine-tuning of sequential recommendation systems via conformal prediction. *arXiv preprint arXiv:2402.08976*, 2024.

[48] T. Yu, H. Cui, J. C. Li, Y. Luo, G. Jiang, and H. Zhao. Enzyme function prediction using contrastive learning. *Science*, 379(6639):1358–1363, 2023.

[49] Y. Zhang and J. Skolnick. Tm-align: a protein structure alignment algorithm based on the tm-score. *Nucleic acids research*, 33(7):2302–2309, 2005.