PENGUIN: A rapid and efficient image preprocessing tool for multiplexed spatial proteomics

A. M. Sequeira[1,2], M. E. Ijsselsteijn[2], M. Rocha[1], Noel F.C.C. de Miranda[2]

1. Department of Informatics, School of Engineering, University of Minho, Braga, Portugal

2. Department of Pathology, Leiden University Medical Centre, Leiden, Netherlands

Abstract

Multiplex spatial proteomic methodologies can provide a unique perspective on the molecular and
cellular composition of complex biological systems. Several challenges are associated to the analysis
of imaging data, in particular regarding the normalization of signal-to-noise ratios across images and
background noise subtraction. However, straightforward and user-friendly solutions for denoising
multiplex imaging data that are applicable to large datasets are still lacking. We have developed
PENGUIN –Percentile Normalization GUI Image deNoising: a rapid and efficient image preprocessing
tool for multiplexed spatial proteomics. In comparison to existing approaches, PENGUIN stands out
by eliminating the need for manual annotation or machine learning model training. It effectively
preserves signal intensity differences and reduces noise, thereby enhancing downstream tasks like
cell segmentation and phenotyping. PENGUIN's simplicity, speed, and user-friendly interface,
deployed both as script and as a Jupyter notebook, facilitate parameter testing and image
processing. We illustrate the effectiveness of PENGUIN by comparing it with conventional image
processing techniques and solutions tailored for multiplex imaging data. This comparison
underscores PENGUIN's capability to produce high-quality imaging data efficiently and consistently.

keywords

Multiplex imaging, Immunophenotyping, Denoising, Normalization, Background subtraction, Spatial
proteomics

Introduction

In recent years, the field of multiplexed imaging technologies has grown tremendously, allowing for
spatially resolved proteomic, transcriptomic, or metabolic profiling of biological systems [1, 2].
Imaging Mass Cytometry (IMC) [3] and Multiplex Ion Beam Imaging (MIBI) [4] make use of metal-
conjugated antibodies for the detection of proteins by means of mass spectrometry. This process
involves quantifying isotopic reporter masses released from the tissue following ablation of small
tissue areas with a laser beam or ion beams. Standard immunofluorescence (IF) [5] and high
dimensional fluorescence methods, like Co-Detection by IndEXing (CODEX) [6], make use of
fluorescently labeled antibodies.

Despite the increasing application of multidimensional proteomics spatial technologies, their
resulting data poses challenges that often cannot be overcome with conventional image analysis
approaches. A common issue is the presence of noise in data, which must be removed prior to
analysis [7]. Noise sources can vary depending on which antibodies, detection channels and tissue
types are used and can be manifested in artifacts such as hot pixels or background noise [7-9].
Furthermore, some protein markers may exhibit weak signal and low signal-to-noise ratios [10].
Together, these noise sources deteriorate the image quality and complicate downstream analyses of
multiplex imaging data. Therefore, robust and stable methods for denoising have become
increasingly important with the application of these methods [7].

In this work, we propose an improved pipeline for denoising multiplexed proteomics - PENGUIN -
Percentile Normalization GUI Image deNoising. It uses scaling, thresholding, and percentile-based
filters to tackle different sources of noise in multiplex images. We demonstrate its applicability by
using an existing IMC dataset and benchmark it against existing methods for image preprocessing, as
well as methods designed specifically for analysis of multiplex imaging data. Furthermore, by also
applying PENGUIN to multiplex IF images, we demonstrate that this method can be widely applied to
different types of imaging data. The tool and the benchmarking data are available on
https://github.com/deMirandaLab/PENGUIN.

Current approaches for multiplex imaging normalization

Noise and denoising strategies

Image denoising plays a crucial role in computer vision, yet it remains a challenging task since it is
essential to reduce noise without losing relevant signals [11]. Noise can follow various probabilistic
distributions, with Gaussian noise - where noise pixel values follow a Gaussian distribution - and
impulse noise, such as salt-and-pepper noise, being the most common. In impulse noise, the noise is
random and unrelated to the image pixels. Typically, in a clean image, neighboring pixels are
correlated, as objects or surfaces often span multiple adjacent pixels, whereas noise in neighboring
pixels is usually uncorrelated. Thus, a basic and effective denoising strategy applies a predefined
operation within a local neighborhood – like a 3x3 pixel window – to produce an output value for the
center pixel, creating a processed image as the filter is applied across each pixel in the input image.
Filters, which are quick and straightforward to use, can significantly enhance image preprocessing
and noise removal. They can be linear, such as Gaussian and mean filters, or non-linear, like the
median filter [11, 12]. Linear filtering normalizes pixels by replacing them with the mean value of
their neighborhood or, in the case of Gaussian filters, a weighted mean based on the proximity of
neighboring pixels. While this approach reduces outlier pixels, it can also blur edges and significantly
diminish high-frequency image details. Moreover, with this approach, impulse noise is averaged out
but is not eliminated entirely [12, 13].

On the other end, non-linear filters operate without linear operations. The most prevalent among
these are order-statistic filters, which include median filters. In this approach, the center pixel is
substituted with the median of the ranked values from its surrounding pixels. Median filters excel in
dealing with impulse noise, as such noise usually ranks at the extreme ends of the brightness scale.
Additionally, median filtering not only significantly diminishes the spikes caused by impulse noise,
but also maintains the brightness differences across signal transitions. This leads to minimal blurring
of regional edges, thus preserving the integrity of boundary positions within the image [12].
However, median filters are primarily effective against impulse noise, requiring that the noisy pixels
constitute less than half of the neighborhood area, and their performance declines when noise is
present in more than 20% of an image's pixels. They are less successful in removing Gaussian or
random-intensity noise, as the brightness of noisy pixels does not significantly differ from that of
their neighboring pixels [12]. Percentile filters, akin to median filters, adjust pixel values based on a
range of percentiles rather than solely the median (50th percentile). Offering similar advantages to
median filters, percentile filters have the same benefits as the median filters and offer flexibility as
different markers may benefit from different values of noise reduction, as they may display more or
less shot noise [12].

Other non-linear filters include Bilateral, Non-Local Means, Adaptive Filtering, Total Variation
Denoising, Anisotropic Diffusion, and Wavelet denoising filters.

Recently, deep learning (DL) has become a powerful tool in image analysis, introducing innovative
strategies for denoising. These strategies can be categorized in two types: those that are trained
using ground truth data, and those that do not require it. In many application areas, such as spatial
omics, obtaining clean ground truth images can be challenging. Thus, denoising methods that
operate independently of a ground truth dataset are particularly valuable. Presently, Noise2Void
stands out as a widely utilized algorithm in this category [14]. It trains a neural network to eliminate
noise by leveraging information from the surrounding pixels within the same image, obviating the
need for a separate, clean reference image. Another method involves denoising autoencoders. An
autoencoder is a neural network employed in unsupervised learning, aimed at learning efficient data
representations by compressing the data into a compact internal form, and then reconstructing the
original data from this representation. When used for denoising, the autoencoder is trained to
process noisy input data and output clean data, thereby learning to ignore the noise during the
reconstruction of the original data. This training process enhances the autoencoder's ability to
identify relevant features in the presence of noise, making it a valuable tool for various image
restoration and denoising tasks [15].

Denoising imaging mass cytometry (IMC) data

With the advent of multiplex spatial phenotyping technologies, specialized approaches to address
image noise, like crosstalk and hot pixels, have been developed. Crosstalk, a phenomenon where
signals from one channel interfere with adjacent channels, can lead to the misidentification of
signals, especially for co-expressed markers [7, 10]. To mitigate this, methods like CATALYST [9]
employ pre-acquisition signal compensation matrices, while post-acquisition solutions are also
available [8, 16]. However, carefully designed antibody panels can often minimize the need for
correction by reducing low-intensity channel overlap [10, 17].

Hot pixels, another common artifact in IMC images, are identified as individual pixels exhibiting
significantly higher signal intensities compared to their surroundings and are typically modeled as a
Poisson process. This randomness, characterized by the independent occurrence of points in a
mathematical space, can be attributed to detector abnormalities and can be influenced by various
factors, including differences in metal isotope conjugation, antibody concentration, and spatial
arrangement [10, 17]. Additionally, small clusters of consecutive hot pixels, not representative of
biological structures may form due to nonspecific antibody binding, antibody aggregates, or
contamination by dust particles [8, 10].

Hot pixels are often dealt with by applying traditional image filtering methods and thresholds.
Researchers have devised numerous "homebrew" computational strategies, tailored specifically to
individual projects [16, 18, 19]. A notable method, featured in Steinbock, a Python toolkit for
processing multiplexed tissue images, addresses hot pixels by comparing each pixel's value to those
of its eight surrounding neighbors. Should the difference between the pixel and any of its neighbors
surpass a predetermined threshold, the pixel's value is reduced to match that of the highest
neighboring pixel value [20].

In addition to conventional denoising techniques, tools like Ilastik offer pixel classification in a
supervised manner, enabling the distinction between background noise and true signal pixels for
each marker [20-22]. Essentially, an experienced user trains the Ilastik Random Forest pixel classifier
by manually identifying pixels as either representing signal or background. This trained model is then
applied across all the images, resulting in a binary expression map, where non-noise pixels are
assigned a value of 1.This method has proven effective in not only eliminating background noise, but
also in standardizing and normalizing signals across different samples, thereby mitigating batch

effects [22]. However, the requirement for manual annotations across a series of images within a
cohort can be labor-intensive. This manual curation process is particularly challenging when dealing
with large datasets, making it a less desirable approach in such contexts.

Recently, Lu et al. [17] introduced IMC-Denoise, a two-step pipeline combining a Differential
Intensity Map-based Restoration (DIMR) algorithm for removing hot pixels and a self-supervised DL
algorithm for shot noise image filtering, inspired by Noise2Void, named DeepSNiF. Initially, hot pixels
are identified using Anscombe transformation differential maps. Subsequently, DeepSNiF processes
these images by randomly masking pixels through a stratified sampling approach. DL approaches,
however, tend to be time consuming, resource heavy and require rigorous tuning of parameters.

Despite the availability of various IMC denoising approaches, there is still no consensus on the
optimal approach, and the absence of a standardized strategy hinders dataset comparisons. Current
techniques either necessitate manual marking of noisy pixels across all markers – a process that is
both time-consuming and prone to inconsistency – or fail to adequately address all noise types and
nonspecific antibody signals.

In this study, we propose that the primary IMC noise sources, such as hot pixels and background
noise, can be effectively managed using straightforward classical algorithms. PENGUIN is quick,
scalable, reproducible, and does not rely on manual pixel annotation nor requires extensive
hardware resources.

Results

To mitigate noise in IMC images, the authors identified several key considerations:

1. Shot noise, characterized by random pixels exhibiting significantly higher signal intensities
compared to their surroundings (also known as salt and pepper noise), can be efficiently
addressed by filtering out very sparse signals, namely pixels that lack neighboring signals.
2. Non-specific antibody binding, when it occurs, results in signal areas that are less intense
than those from specific binding.
3. Noise tends to occur independently across different channels within the same images,
meaning it can affect one channel without necessarily impacting others. Nonetheless, within
a specific cohort, noise generally displays consistent patterns across all images from the
same channel.

To address noise in IMC images, the authors put forward a method that integrates scaling,
thresholding, and percentile-based filters. First, images undergo saturation at the 99th percentile to
remove the impact of extremely bright pixels. Following this, signal intensities across each channel
and image are normalized to a scale from 0 to 1. A thresholding technique is then applied to discard
background signals, essentially removing signals of low intensity. Subsequently, hot pixels are
pinpointed and eliminated using percentile filters. A crucial element of this strategy is the use of the
percentile filter exclusively for identifying and removing pixels without altering the image's clarity or
edges. So, after post-processing, the image retains its sharpness and edge integrity. Furthermore,
the normalization of values from 0 to 1 facilitates their direct application in subsequent analyses, like
cell segmentation. The foundational principle behind PENGUIN, the percentile-based noise
detection, is illustrated in Figure 1.

Key adjustable parameters in this pipeline include the Threshold (T) value and the Percentile (P)
value, which are both critical to its performance. A higher T will result in the removal of more signal
in the initial phase of the pipeline. If the output of a channel is predominantly background signal

with only high intensity values representing true signals, the T should be set high. In contrast, for
channels with minimal background noise, the T can be lower or even omitted. The P parameter plays
a crucial role in the pipeline, with lower values like 25 being stricter as they result in the removal of
nearly all sparse signals, while higher values such as 75 are more lenient, allowing for more sparse
signals. Tailoring these parameters for each channel is essential due to significant differences in the
behavior of markers.

Figure 2 illustrates the effects of varying T and P parameters on the IMC imaging data of β-catenin,
CD20, Vimentin, CD45, and FOXP3. For example, β-catenin showed optimal noise reduction at a
setting of T0.1 and P50, whereas CD20 required a higher threshold of T0.3 to effectively eliminate
noise. On the other hand, for Vimentin and CD45, clear images were achieved at P25, while a T
setting was not required.To simplify the visualization and deployment of the preprocessing pipeline,
we created a user-friendly Jupyter notebook. This tool enables direct observation of how thresholds
and percentiles affect different markers to help decide which thresholds are more applicable to each
marker and image. A sneak peek of the notebook can be seen in Figure 3.

The code for the preprocessing pipeline is freely available. The users can apply the functions for
direct scripting or use the notebook provided for a more user-friendly experience.

Comparison of several methods for denoising IMC

PENGUIN was evaluated against both traditional image denoising techniques and IMC-specific
approaches using a public dataset comprising 39 cellular markers evaluated by IMC on 61 samples
[24].

To improve the performance of standard image denoising methods, we applied saturation to the
99[th] percentile to remove bright outliers and normalized each channel's signal intensity between 0
and 1 [22]. We initially explored various classical filtering methods, including Gaussian, mean,
percentile, non-local means, bilateral, total variation, wavelet, anisotropic diffusion, and BM3D
filters (see supplementary figures 1 & 2). As anticipated, linear filters such as Gaussian and mean
filters tended to blur images, leading to a loss of detail and definition in tissue boundaries
(supplementary figures 1 & 2, linear filters). Although these filters did not directly eliminate hot
pixels, the pixels became less conspicuous as they were blurred. The remaining classical image filters
either failed to adequately reduce noise (for example anisotropic and bilateral filters), or distorted
the images, like the non-local mean filter, rendering them unsuitable for this type of data.

We also evaluated DL methods designed for denoising images without the need for paired ground
truth data, specifically Noise2Void [14] and denoising autoencoders [23], which were trained for 20
or 50 epochs. These approaches did not effectively denoise the images and led to image distortion,
suggesting they may not be applicable for IMC images. However, it is important to note that DL
models perform better with larger datasets. As the availability of IMC image datasets increases, the
performance of these models may improve. It is also worth mentioning that our experiments only
involved a basic convolutional denoising autoencoder configuration, and the potential for
optimization through different combinations of layers, epochs, and parameters is vast. Yet, DL
methods require significant time for development, tuning, and training, and often necessitate
specialized hardware that may not be widely accessible.

Next, we applied two IMC-specific methodologies. Firstly, we explored a hot pixel filter [20] that uses
a 3x3 kernel to assess if the difference between a pixel and its maximum neighboring value exceeds
a predefined threshold; if so, the pixel is classified as noise and is attributed the maximum
neighbor's value. This method was applied to both normalized, using thresholds ranging from 0.05 to

0.2, and to raw images with a default threshold of 50. Although this approach succeeded in
removing some hot pixels, the processed images still contained noise, and occasionally, real signals
were lost (supplementary figures 1 & 2, IMC specific strategies). Secondly, with IMC Denoise [17] we
applied both the DIMR algorithm alone and in combination with the DeepSNIF DL algorithm,
adhering to the authors' guidelines and default settings. The DIMR algorithm alone proved
inadequate for removing hot pixels. When supplemented with DeepSNIF, similar to the issues
observed with Noise2Void, some image distortions occurred. As with other DL methods, the
potential configurations for IMC Denoise are virtually limitless; however, fine-tuning the correct
parameters is a labor-intensive process. Additionally, distinct models must be trained for each
channel, further complicating the application of this approach.

Finally, we applied the methodology developed at our lab [22], where we developed a semi-
automated background removal (SABR) pipeline based on Ilastik (Figure 4). Compared to the raw
data, SABR effectively removes most noise, producing clear binary images. However, this process
also results in some loss of specific signals, noticeable for instance in the case of β-catenin
immunodetection (Figures 4 and 5).

When applying PENGUIN to the same set of images, we found that it effectively removes noise from
raw images, matching the quality achieved by the Ilastik-based SABR method. Additionally, PENGUIN
often retains more signal than SABR, as highlighted in Figure 5.

This underscores the effectiveness of PENGUIN in eliminating noise from IMC images. There are also
substantial differences between PENGUIN and the SABR pipeline. Firstly, PENGUIN necessitates
manual adjustment of thresholds and percentiles for each channel but does not require the
development of specific classifiers to distinguish between signal and noise for each marker.
Secondly, unlike the Ilastik-based method, which generates binary images indicating merely the
presence or absence of signals, PENGUIN produces images with normalized values ranging from 0 to
1, representing various signal intensities. This allows for a more nuanced analysis, as PENGUIN not
only retains more signal, but also preserves critical details of cellular structures.

Setting the thresholds and percentiles is an intuitive process, made even simpler and more efficient
with the use of the provided notebook. Processing all 61 images for each channel took less than 4
seconds on an Intel(R) Core(TM) i7-9700 CPU, which represents a significant time saving compared
to training and deploying Ilastik models for each marker. Additionally, the results are both fully
reproducible and easily achievable, marking a significant improvement over existing methods.

PENGUIN enhances downstream analysis

After confirming the effectiveness of PENGUIN for image processing, we evaluated its impact on
downstream analysis. This involved comparing raw, unprocessed images with those corrected using
the Ilastik-based SABR method and the PENGUIN pipeline in terms of cell segmentation and cell
phenotyping/clustering.

A significant advantage of PENGUIN over the previous approach is that its output can be directly
utilized in cell segmentation pipelines, eliminating the need for training an additional Ilastik model to
differentiate between membrane, nucleus, and background markers, thereby saving considerable
time. Moreover, as highlighted earlier and depicted in Figure 5, PENGUIN's normalization process
retains more signal and crucial cell structural features.

To assess the efficacy of these methods, we combined the normalized images with their
corresponding cell segmentation masks to calculate relative marker expression per cell. Cells were

then clustered using t-SNE to identify cell subsets, as shown in Figure 6. Consistent with findings by
Ijsselsteijn et al. [22], normalization and background removal are essential for accurately identifying
signals and cells, as well as normalizing IMC inter-sample variation for automated downstream
analysis. Similar to the current state-of-the-art techniques, PENGUIN adjusts for interpatient
variability, achieving well-defined cells and clusters. This represents an improvement over existing
methods because it is faster, reproducible, and allows for the preprocessed images from PENGUIN to
be directly used in cell clustering and phenotyping, bypassing the necessity for two rounds of
training Ilastik models.

PENGUIN can be applied to other image modalities

Various imaging modalities in multiplex spatial proteomics, such as MIBI, CODEX, and multiplex IF,
produce different types of images. Encouraged by the promising outcomes achieved with the
PENGUIN pipeline, and given that the signal characteristics from these modalities share similar
limitations, the authors extended the application of their developed pipeline to a set of in-house
generated IF images. The results, showcased in Figure 7, reveal high-quality denoised images,
achieved with significantly reduced time, resources, and operator-induced variations. Consequently,
PENGUIN facilitates the normalization of both IMC and IF images for downstream analysis without
compromising the specificity of the antibody signal. Additionally, its speed and scalability render it
highly effective for processing large and expanding imaging datasets.

Discussion

Spatial proteomics data, like that from IMC, provides a distinctive insight into the spatial
organization of tissues, offering broad applications. However, handling signal-to-noise ratios,
particularly with extensive antibody panels, poses significant challenges. Computational
preprocessing methods are essential for ensuring the reliability of subsequent analyses [7]. Although
various custom algorithms have previously achieved success in denoising IMC data, there is a
growing need for a standardized, efficient preprocessing pipeline to manage the increasing volume
of data. Given that pixel intensity values in spatial proteomics vary across targets, and signals for
low-abundance antigens are often sparse, it is logical that the density of positive pixels provides
more information about the presence of a signal than the intensity of individual pixels.

In this context, we introduce PENGUIN, which effectively denoises IMC images through scaling,
thresholding, and percentile filters, yielding excellent results. We evaluated this pipeline against
traditional filtering methods, DL-based approaches, and IMC-specific solutions, demonstrating that
PENGUIN delivers clear images quickly, easily, and reproducibly. A Jupyter notebook with a user-
friendly interface is provided, facilitating the testing of various thresholds and percentiles per marker
and simplifying the process of adjusting parameters, transforming, and saving images. Additionally,
the core code is available for scripting.

Compared to the recently developed Ilastik-based SABR method, PENGUIN eliminates the need for
manual annotation or training of machine learning models, preserves signal intensity differences
across tissues, reduces noise, and retains more structural details. Moreover, PENGUIN enhances
essential downstream tasks such as cell segmentation and phenotyping. Due to its simplicity, speed,
intuitiveness, high-quality results, reproducibility, and ease of deployment, we believe PENGUIN is a
valuable tool to aid in the analysis of IMC data and, eventually, of other multiplex imaging platforms.

Methods

Methods

All the tests were run in a Intel(R) Core(TM) i7-9700 CPU. The DL models were run using a GPU
Nvidia TU102 GeForce RTX 2080 Ti.

Dataset

All the results for IMC were obtained using the publicly available cohort of 61 IMC raw images with
39 markers of colorectal cancer [24].

Denoising Methods comparison

Before application of the denoising filters, images were saturated to the level of the 99th percentile
and normalized between 0 and 1. Using raw images was also tested, however, normalizing leading to
significant improvements in image quality.

The following filters were applied to each channel: Gaussian filter using sigma values of 0.7 and 1;
mean filter; percentile filter (with values of 25,50 and 75); non-local means (patch size 5, patch
distance 11 and sigma 0.2); bilateral filter; total variation (defined as proposed by Chambolle, weight
0.3); Wavelet; anisotropic diffusion and BM3D filtering(sigma 0.1, 0.2 and estimated sigma that
retrieve values between these two values were tested). Parameters not specified were set as
default. Gaussian, mean and percentile filters were based on SciPy implementation [25]. Non-local
means, bilateral filter, total variation and wavelet filtering were based on scikit-image package [26].
Bm3D was retrieved from source package [27].

The filter to remove hot pixels in IMC images was implemented as described by Windager et al. [20]
which applies a Scipy maximum filter with size 3*3. If the difference between the center pixel and its
maximum neighbor is above a defined threshold is set to the value of the maximum neighbor.
Thresholds ranging from 0.05 to 0.2 were applied with normalized images, default threshold, 50, was
used with raw images.

Noise2Void was trained as defined by Krull et al. [14] per channel with all images of the cohort with
0.2 of data used for validation. Loss was defined as MSE neighborhood radius 5 and UNET kernel size
3 for a patch size of 64. Models were trained for 20, 50, and 100 epochs.

Convolutional autoencoder for image denoising were built as defined in [23] with the encoder being
defined as 2 consecutive 2D convolution layers (32 filters kernel size (3,3), activation relu) and max
pooling (pool size (2,2) and the decoder as 2 Transpose convolutional layers (32 filters kernel size
(3,3), activation relu) and a last Convolutional operation with 1 filter, and sigmoid activation. Adam
optimizer and binary cross entropy were used. The training process was done for 20 or 50 epochs
per channel. The DL implementation was using Tensorflow [28]. All the parameters not specified
were set as default.

IMC Denoise [17] was implemented following the instructions from the tutorial notebook and
default parameters were defined. IMC Denoise has two different steps, the DIMR algithm and the
DeepSNIF. We tested only applying the DIMR algorithm per channel (4 neighbors, window size3 and
3 iterations) and DIMR algorithm followed by the DeepSNIF trained for 200 epochs.

PENGUIN implementation

PENGUIN is implemented in Python 3.10 and deployed as a code package and Jupyter Notebook. For
each image and each channel, pixels above the 99th percentile are set to that value and are

normalized from 0 to 1. After this, pixels with values below a defined threshold are removed and a
percentile filter is used to detect which pixels are considered noise or signal (window 3*3). The same
thresholds and percentiles per channel are applied to all the images in the cohort. To demonstrate
the concept we applied the percentiles of 90, 75, 50, 25, and 10 and percentile 50 after thresholding
pixels below 0.1, 0.3, and 0.5. This comparison was done for Bcatenin, CD20, Vimentin, CD45, and
FOXP3 for their importance as markers and different signal distributions. There are two Jupyter
Notebooks, one for the case where each region of interest has one TIFF file per channel, and the
other where there is a TIFF stack containing all channels.

Comparison of methods for downstream analysis

PENGUIN parameters definition

354 The raw images were analyzed by an IMC expert, using PENGUIN notebook for better visualization.
355 Parameters, namely thresholds and percentiles, were set for each channel using the Notebook tool (
356 Supplementary Table 1 - Thresholds and Percentiles values for the 39 IMC markers) and applied to
357 all images in the cohort.

Ilastik-based background removal

359 For each marker, a random forest classifier was trained in Ilastik [21] to recognize background pixels
360 and signal pixels, as described by Ijsselsteijn et al. [22]. After rigorous training on approximately 10%
361 of the dataset, the random forest classifier was applied to all images of a given marker and data was
362 exported as simple segmentation masks where all background pixels were set to zero and signal
363 pixels to one.

Cell segmentation

Cell masks were created using CellProfiler V3.0 [29]. For comparison purposes, masks were created
with raw data, as well as with PENGUIN normalized images. Using raw data, the traditional
Ilastik/CellProfiler combination was used, where first probability masks for nucleus, membrane and
background were generated in Ilastik using the DNA, Vimentin and Keratin images. Next, these were
loaded into a CellProfiler pipeline to identify primary objects (nuclei) after which membranes were
appended to those using the identify secondary objects module. Visual inspection was done to
compare the masks with the original IMC Images. After PENGUIN normalization, the normalized
images could directly be used for the creation of cell segmentation masks in Ilastik using the same
approach.

Cell type phenotyping/cluster

375 The 2 different masks from cell segmentation (Ilastik-based and PENGUIN) were loaded into ImaCytE
376 [30] combined with the raw, Ilastik-based denoised, and PENGUIN-based denoised marker profiles
377 to define relative marker expression per cell. FCS files were produced, and clustering of cells was
378 performed by t-SNE to identify cell subsets, using Cytosplore [31].

Immunofluorescence labelling and imaging

Immunofluorescence labelling was performed using the OPAL methodology. In short,
deparaffinisation, rehydration, endogenous peroxidase blocking and antigen retrieval with 10 mM
citrate buffer (pH 6.0) were performed on four μm thick FFPE tissue sections. Next, sections were
blocked using superblock solution (Thermo Fisher Scientific) and incubated for 1 hour with anti-CD4.
Opal amplification was performed by consecutive incubations with a polymeric HRP-linker antibody

conjugate (Immunologic, The Netherlands) for 10 minutes and a 10 minute incubation with OPAL650
reagent (Akoya Biosciences). The sections were boiled for 15 minutes in 10 mM citrate buffer (pH
6.0). Blocking, primary antibody incubation, followed by HRP and OPAL were then repeated for all
antibodies (CD103 – OPAL620, PD1 – OPAL570, GZMB – OPAL520, CD8 – OPAL690). Between each
step the sections were washed with PBS-tween. Finally, the sections were incubated with one µM
DAPI, washed with PBS (without tween) and mounted using Prolong® Gold Antifade Reagent (Cell
Signaling Technologies). The slides were imaged and spectrally unmixed using the Vectra 3 imaging
system and the InForm software (Akoya Biosciences) after which the component images were
normalised with PENGUIN.

Parameters, thresholds and percentiles, were set for each channel (Supplementary Table 2) and
applied to all images in the cohort.

Data and code availability

The IMC data is publicly available from Roelands et al. [24] and is accessible on BioImage Archive
(Accession number S-BIAD587, https://www.ebi.ac.uk/biostudies/bioimages/studies/S-BIAD587).

The PENGUIN pipeline is completely available and ready to use at
https://github.com/deMirandaLab/PENGUIN. The repository also contains all the code to replicate
the methods comparison, along with explainable Jupyter notebooks.

Acknowledgments

This study was supported by the Portuguese Foundation for Science and Technology-FCT and FSE
through PhD fellowship: [2020.0786BD].

References

1. Bressan, D., G. Battistoni, and G.J. Hannon, *The dawn of spatial omics.* Science, 2023.
381(6657): p. eabq4964.
2. de Vries, N.L., et al., *Unraveling the Complexity of the Cancer Microenvironment With*
Multidimensional Genomic and Cytometric Technologies. Front Oncol, 2020. **10**: p. 1254.
3. Giesen, C., et al., *Highly multiplexed imaging of tumor tissues with subcellular resolution by*
mass cytometry. Nat Methods, 2014. **11**(4): p. 417-22.
4. Keren, L., et al., *MIBI-TOF: A multiplexed imaging platform relates cellular phenotypes and*
tissue structure. Sci Adv, 2019. **5**(10): p. eaax5851.
5. Ijsselsteijn, M.E., et al., *Cancer immunophenotyping by seven-colour multispectral imaging*
without tyramide signal amplification. J Pathol Clin Res, 2019. **5**(1): p. 3-11.
6. Goltsev, Y., et al., *Deep Profiling of Mouse Splenic Architecture with CODEX Multiplexed*
Imaging. Cell, 2018. **174**(4): p. 968-981 e15.
7. Baharlou, H., et al., *Mass Cytometry Imaging for the Study of Human Diseases-Applications*
and Data Analysis Strategies. Front Immunol, 2019. **10**: p. 2657.
8. Baranski, A., et al., *MAUI (MBI Analysis User Interface)-An image processing pipeline for*
Multiplexed Mass Based Imaging. PLoS Comput Biol, 2021. **17**(4): p. e1008887.
9. Chevrier, S., et al., *Compensation of Signal Spillover in Suspension and Imaging Mass*
Cytometry. Cell Syst, 2018. **6**(5): p. 612-620 e5.
10. Milosevic, V., *Different approaches to Imaging Mass Cytometry data analysis.* Bioinformatics
Advances, 2023. **3**(1): p. vbad046.
11. Fan, L., et al., *Brief review of image denoising techniques.* Vis Comput Ind Biomed Art, 2019.
2(1): p. 7.
12. Gonzalez, R.C. and R.E. Woods, *Digital Image Processing, Global Edition.* 2018: Pearson
Education.

13.   Sreejith, S. and J. Nayak. *Study of hybrid median filter for the removal of various noises in digital image*. in *Journal of Physics: Conference Series*. 2020. IOP Publishing.
14.   Krull, A., T.-O. Buchholz, and F. Jug. *Noise2void-learning denoising from single noisy images*. in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*. 2019.
15.   Vincent, P., et al. *Extracting and composing robust features with denoising autoencoders*. in *Proceedings of the 25th international conference on Machine learning*. 2008.
16.   Wang, Y.J., et al., *Multiplexed In Situ Imaging Mass Cytometry Analysis of the Human Endocrine Pancreas and Immune System in Type 1 Diabetes*. Cell Metab, 2019. **29**(3): p. 769-783 e4.
17.   Lu, P., et al., *IMC-Denoise: a content aware denoising pipeline to enhance Imaging Mass Cytometry*. Nat Commun, 2023. **14**(1): p. 1601.
18.   Keren, L., et al., *A Structured Tumor-Immune Microenvironment in Triple Negative Breast Cancer Revealed by Multiplexed Ion Beam Imaging*. Cell, 2018. **174**(6): p. 1373-1387 e19.
19.   Rendeiro, A.F., et al., *The spatial landscape of lung pathology during COVID-19 progression*. Nature, 2021. **593**(7860): p. 564-569.
20.   Windhager, J., et al., *An end-to-end workflow for multiplexed image processing and analysis*. Nat Protoc, 2023. **18**(11): p. 3565-3613.
21.   Berg, S., et al., *ilastik: interactive machine learning for (bio)image analysis*. Nat Methods, 2019. **16**(12): p. 1226-1232.
22.   Ijsselsteijn, M.E., et al., *Semi-automated background removal limits data loss and normalizes imaging mass cytometry data*. Cytometry A, 2021. **99**(12): p. 1187-1197.
23.   Chollet, F., *Building autoencoders in keras*. The Keras Blog, 2016. **14**.
24.   Roelands, J., et al., *Transcriptomic and immunophenotypic profiling reveals molecular and immunological hallmarks of colorectal cancer tumourigenesis*. Gut, 2023. **72**(7): p. 1326-1339.
25.   Virtanen, P., et al., *SciPy 1.0: fundamental algorithms for scientific computing in Python*. Nat Methods, 2020. **17**(3): p. 261-272.
26.   van der Walt, S., et al., *scikit-image: image processing in Python*. PeerJ, 2014. **2**: p. e453.
27.   Dabov, K., et al., *Image denoising by sparse 3-D transform-domain collaborative filtering*. IEEE Trans Image Process, 2007. **16**(8): p. 2080-95.
28.   Abadi, M., et al., *Tensorflow: Large-scale machine learning on heterogeneous distributed systems*. arXiv preprint arXiv:1603.04467, 2016.
29.   McQuin, C., et al., *CellProfiler 3.0: Next-generation image processing for biology*. PLoS Biol, 2018. **16**(7): p. e2005970.
30.   Somarakis, A., et al., *ImaCytE: Visual Exploration of Cellular Micro-Environments for Imaging Mass Cytometry Data*. IEEE Trans Vis Comput Graph, 2021. **27**(1): p. 98-110.
31.   Höllt, T., et al. *Cytosplore: interactive immune cell phenotyping for large single-cell datasets*. in *Computer Graphics Forum*. 2016. Wiley Online Library.

Figure 1 - Overview of the PENGUIN pipeline. A) The original image contains noise and extreme outliers, which obscure the
rest of the signal. B) Outliers are saturated by setting values above the 99th percentile to this value, enhancing visualization.
Each channel and image are then normalized between 0 and 1. C) Pixels with values below a chosen Threshold are
removed. D) Percentile filtering is applied to detect and remove noise pixels. For each central pixel, a 3x3 window is
considered. Pixels are transformed to Boolean (0/1) and ordered ascendingly. If the percentile value is 0, the pixel is
considered noise and set to 0; if it is above 0, it is considered a real signal. For example, a 50th percentile (P50) requires that
5 out of 9 pixels to be positive, the 75th percentile requires 2 out of 9 pixels to be positive, and the 25th percentile (P25)
requires 7 out of 9 pixels to be positive. Depending on the channel characteristics, low percentile values may lead to the
removal of true signals, while high percentile values may retain noise signals.

Figure 2 - Application of different percentiles (P90,P75,P50,P25,P10) and thresholds (T0.1,T0.3,T0.5, with P50) for β-catenin,
CD20, Vimentin, CD45 and FOXP3. The optimal parameters for each channel are highlighted in green.

Figure 3 - PENGUIN Jupyter Notebook sneak peek

495 *Figure 4 - Bcatenin, CD20, Vimentin and CD45 markers for two regions of interest with raw images, PENGUIN processed and*
496 *Ilastik-based SABR approach.*

497
498 *Figure 5 - Zoom in from figure 4 for B catenin and CD45 markers. When compared to the SABR approach [22]], PENGUIN*
499 *retains more real signal and the key aspects of cell structure.*

503 *Figure 6 - t-SNE obtained by A) raw marker expression and SABR Ilastik-based cell masks, B) SABR Ilastik-denoise marker*
504 *expression and SABR Ilastik-based cell masks, C) PENGUIN-denoise marker expression and PENGUIN-based cell masks. The*
505 *t-SNE are colored by sample, CD3, CD8 and CD103 markers.*

Figure 7 – PENGUIN applied to IF images, namely, DAPI, CD4, PD1 and CD8 signal.

     Supplementary images

Supplementary Figure 1 - CD20 channel of one sample with linear filters (mean, gaussian with sigma 0.7 and 1); other traditional image filters (bilateral, non local mean, total variation, BM3D, wavelet and anisotropic); DL based strategies for denoising, namely Noise2Void and a denoise autoencoder (trained for 20 and 50 epochs) and; Strategies specific designed for IMC, namely the hot pixel filter defined by [20] and DIMR and DIMR with DeepSNIF from [17].

Supplementary Figure 2 - Bcatenin channel of one sample with linear filters (mean, gaussian with sigma 0.7 and 1); other traditional image filters (bilateral, non local mean, total variation, BM3D, wavelet and anisotropic); DL based strategies for denoising, namely Noise2Void and a denoise autoencoder (trained for 20 and 50 epochs) and; Strategies specific designed for IMC, namely the hot pixel filter defined by [20] and DIMR and DIMR with DeepSNIF from [17].

537
538
539
540

545   *Supplementary Table 1 - Thresholds and Percentiles values for the 39 IMC markers*

Marker	Percentile	Threshold	Marker	Percentile	Threshold
B catenin	60	0.2	CD8a	60	0.25
CD103	30	0.1	cleavedcaspase	40	0.3
CD11b	50	0.25	D2-40	50	0.25
CD11c	40	0	FOXP3	50	0.1
CD14	40	0.1	Granzyme B	40	0.2
CD15	40	0.25	HLA-DR	50	0.1
CD163	40	0.3	ICOS	50	0.1
CD20	50	0.1	IDO	30	0.3
CD204	50	0.1	Keratin	50	0.5
CD3	50	0.1	Ki-67	50	0.2
CD31	50	0,2	P16ink4a	50	0.2
CD38	40	0.2	PD-1	40	0.2
CD39	40	0.2	PD-L1	50	0.3
CD4	50	0.2	Tbet	60	0.1
CD45	50	0.2	TCRgd	40	0.1
CD45RO	50	0.2	TGFbeta	40	0.2
CD56	50	0.2	Vimentin	40	0.1
CD57	60	0.2	VISTA	50	0.2
CD68	40	0.2	CD7	50	0.2

547   *Supplementary Table 2 - Thresholds and Percentiles values for the IF markers*

Marker	Channel	Percentile	Threshold
DAPI	DAPI	60	0.2
CD4	Opal650	50	0.5
PD1	Opal570	40	0.7
CD8	Opal690	40	0.7