VirID: Beyond Virus Discovery - An Integrated Platform for

Comprehensive RNA Virus Characterization

Ziyue Yang [#,1,2,3], Yongtao Shan [#,1,2,3], Xue Liu [1,2,3], Guowei Chen[4], Yuanfei Pan[5], Qinyu

Gou[1,2,3], Jie Zou[1,2,3], Zilong Chang[1,2,3], Qiang Zeng[1,2,3], Chunhui Yang[1,2,3], Jianbin

Kong[1,2,3], Yanni Sun[4], Shaochuan Li[6], Xu Zhang[6], Wei-Chen Wu[1,2,3], Chunmei Li [1,2,3],

Hong Peng[1,2,3], Edward C. Holmes[7,8], Deyin Guo*[9,10], Mang Shi*[1,2,3,11]

[1]State Key Laboratory for Biocontrol, School of Medicine, Shenzhen Campus of Sun

Yat-sen University, Sun Yat-sen University, Shenzhen, China.

[2]National Key Laboratory of Intelligent Tracking and Forecasting for Infectious

Diseases, Sun Yat-sen University, Shenzhen, China.

[3]Shenzhen Key Laboratory for Systems Medicine in Inflammatory Diseases, Shenzhen

Campus of Sun Yat-sen University, Sun Yat-sen University, Shenzhen, China.

[4]Department of Electrical Engineering, City University of Hong Kong, 83 Tat Chee

Avenue, Kowloon, Hong Kong (SAR), China.

[5]Ministry of Education Key Laboratory of Biodiversity Science and Ecological

Engineering, School of Life Sciences, Fudan University, Shanghai, China.

[6]Goodwill Institute of Life Sciences, Guangzhou, China.

[7]School of Medical Sciences, The University of Sydney, Sydney, New South Wales,

Australia.

[8]Laboratory of Data Discovery for Health Limited, Hong Kong SAR, China.

[9]Guangzhou National Laboratory, Guangzhou International Bio-Island, Guangzhou,

China.

[10]State Key Laboratory of Respiratory Disease, National Clinical Research Center. for

Respiratory Disease, Guangzhou Institute of Respiratory Health, The First Affiliated

Hospital of Guangzhou Medical University, Guangzhou, Guangdong, China.

[11]Guangdong Provincial Center for Disease Control and Prevention, Guangzhou, China.

[#]These authors contributed equally to this work

Corresponding author: guodeyin@mail.sysu.edu.cn

Corresponding author: shim23@mail.sysu.edu.cn

ABSTRACT

RNA viruses exhibit vast phylogenetic diversity and can significantly impact public health and agriculture. However, current bioinformatics tools for viral discovery from metagenomic data frequently generate false positive virus results, overestimate viral diversity, and misclassify virus sequences. Additionally, current tools often fail to determine virus-host associations, which hampers investigation of the potential threat posed by a newly detected virus. To address these issues, we developed VirID, a software tool specifically designed for the discovery and characterization of RNA viruses from metagenomic data. The basis of VirID is a comprehensive RNA-dependent RNA polymerase (RdRP) database to enhance a workflow that includes RNA virus discovery, phylogenetic analysis, and phylogeny-based virus characterization. Benchmark tests on a simulated data set demonstrated that VirID had high accuracy in profiling viruses and estimating viral richness. In evaluations with real-world samples, VirID was able to identity RNA viruses of all type, but also provide accurate estimations of viral genetic diversity and virus classification, as well as comprehensive insights into associations with humans, animals, and plants. VirID therefore offers a robust tool for virus discovery and serves as a valuable resource in basic virological studies, pathogen surveillance, and early warning systems for infectious disease outbreaks.

KEYWORDS

RNA virus; Virus discovery; Phylogenetic analysis; Virome; Emerging pathogens

INTRODUCTION

RNA viruses are renowned for their genetic and phenotypic diversity and ability to infect hosts ranging from animals, plants, fungi, to microbial organisms, sometimes with devastating health and economic consequences (1). RNA viruses have caused human epidemics for millenia, with notable recent examples including human immunodeficiency virus (HIV; 1981) (2), SARS-CoV (2002) (3), pandemic H1N1 influenza (2009) (4), MERS-CoV (2012) (5), Ebola virus (Western Africa, 2013) (6), Zika virus (2015) (7) and most recently SARS-CoV-2 (2019) (8). Importantly, approximately 70% of these pandemic-causing viral pathogens originate from wildlife animals or utilize arthropod vectors (9), and many have evaded surveillance systems before their emergence in human populations (10-13). Additionally, RNA viruses pose significant threats to agriculture, particularly as epidemics in domestic animals and crops can jeopardize global food security (14-19). Understanding the diversity of RNA viruses and enhancing surveillance of those that pose threats to humans and economically important species are therefore endeavors of utmost importance (20,21).

Meta-transcriptomics (i.e., total RNA sequencing) provides a potentially unbiased survey of the genetic information from all types of organisms in biological samples and has transformed the detection and characterization of RNA viruses (22-26). This method provides efficiency and breadth in virus discovery compared to traditional cultivation techniques (27-30), which are often restricted by their reliance on cell culture growth (31), and to PCR-based approaches that depend on prior knowledge of existing viral diversity (32). As a consequence, meta-transcriptomics has become the primary tool for discovering RNA viruses (26), with the highly conserved RNA-dependent RNA polymerase (RdRP) that is essential for RNA virus replication, serving a powerful universal genetic marker (33-38).

As well as sequencing, the bioinformatics tools for detecting and characterizing virus sequences within metagenomic data sets have experienced major improvements. Initial workflow tools like ViromeScan (39) and Taxonomer (40) detected viruses in samples by analyzing sequencing reads. Subsequent tools, such as Vipie (41), ID-seq

(42), Lazypipe2 (43), and ViWrap (44), use contigs from *de novo* assemblies for virus identification, enhancing the length of query sequences and aiding the discovery of divergent viruses. With the advent of machine learning and deep learning, tools such as PhiSpy (45), VirSorter (46), VirSorter2 (47), and VIBRANT (48) were developed to differentiate viral from microbial sequences by analyzing gene and/or genomic sequences and features, although with relatively high false positive rates. Methods like VirFinder (49) and DeepVirFinder (50) utilize the frequency of consecutive nucleotides (k-mers) in known viral and cellular genomes to identify viral sequences. More recently, specialized RNA virus discovery software such as VirBot (51) have been developed. VirBot constructs databases of RNA virus protein families and employs profile Hidden Markov Models (pHMM) to identify distantly related viral sequences, exhibiting superior performance to other virus classification tools.

Despite these advancements, the bioinformatic tools for virus discovery continue to confront major challenges, such as a high false positive rate, the overestimation of viral diversity, and inaccurate virus classification (52,53). These issues are particularly problematic for RNA viruses due to their highly divergent genomes and distinct genomic structures which complicate identification using basic annotation methods (54,55). Additionally, current bioinformatic tools often lack the capability for the in-depth characterization of viruses, including the accurate identification of host associations, which impedes an understanding of their potential threat to public health and agricultural systems.

In response to these challenges, we developed VirID – a comprehensive and user-friendly software tool tailored for the discovery and characterization of RNA viruses from metagenomic data. VirID features a robust database of RdRP sequences and comprises three core modules: (i) RNA virus discovery, (ii) phylogenetic analysis, and (iii) phylogeny-based virus characterization. Benchmark tests on simulated data set revealed VirID's high accuracy in profiling and classifying RNA viruses. In practical applications with real-world data sets, VirID demonstrated its capacity for virus discovery and for conducting thorough virome analyses.

MATERIALS AND METHODS

RdRP database

We established a database of 7080 representative RdRP protein sequences for RNA virus discovery and characterization. The RdRP sequences were derived from three independent sources, including a "backbone RdRP data set" ($N = 5,384$)(28,56), the NCBI RefSeq database (viral RdRP associated, $N = 19,574$), and the NCBI GenBank database (viral RdRP associated, $N = 5,710,331$). RdRPs from the RefSeq and GenBank databases were initially identified based on key annotation terms, including "RdRP", "RNA-dependent RNA polymerase" and "polymerase" under the taxonomy "Ribovira". Highly divergent RdRPs derived from environmental samples (29,37,57) were excluded due to lack of confirmation. The RdRPs from NCBI were then compared to the backbone RdRP data set using Diamond v2.0.15.153 (58) to remove false positives. The presence of key RdRP domains, specifically the highly conserved A, B and C sequence motifs, were examined using palmscan v1.0.i86linux64 (59). The remaining sequences were clustered using CD-HIT v4.8.1 (60) at 80% amino acid identity, with a representative then selected from each cluster. This resulted in a final reference database of 7080 sequences than were then systematically organized into 24 RNA virus "superclades" based on broad phylogenetic relationships (28,56), and subsequently into 5 phyla, 20 classes, 28 orders, and 112 families based on both the phylogenetic relationships and ICTV taxonomy (Figure 1A, Supplementary Table S1).

For each of the RdRP sequences, information on host organism was initially retrieved from the Virus-Host Database (61) and confirmed by checking the original publications. Based on the host information and phylogenetic relationships, we categorized the RdRP sequences into four broad groups: (i) those infecting humans (including vector-borne viruses, $N = 188$), (ii) those infecting vertebrate animals ($N = 363$), (ii) those infecting plants ($N = 325$), and (iv) all other host associations (Figure 1B). This information, together virus phylogenetic relationships, was used to define specific host groups on phylogenetic trees (Figure 1C, Supplementary Figure S1) from

which the host-association of the newly identified RdRP sequences could be inferred

 (See below).

Figure 1. Overview of the RdRP Reference Database. (**A**) Compilation of representative RdRP sequences into 24 RNA virus superclades, categorized based on phylogenetic analysis. (**B**) Alignment of viral superclades with the ICTV taxonomic system, spanning virus class, order, and family levels. Numbers reflect the count of ICTV classifications mapped to each RdRP superclade, with specific ICTV representative mapping details provided. (**C**) The distribution of viral sequences across supergroups and ICTV taxonomy, highlighting 551 vertebrate-related and 325 plant-related sequences. Data points are color-coded to represent host associations, and bar plots show the proportions of human pathogens and plant-associated viruses in each taxonomic group. (**D**) Using the Reoviridae as a case study, the diagram presents a phylogenetic tree in which branch colors indicate taxonomy and background hues denote host association. Reference sequences are clearly annotated based on their positions within the phylogenetic tree.

Processing and assembly of sequencing reads

VirID performs an initial processing of the input read sequences. The quality control of reads was conducted using bbduk.sh (62). To remove host and microbial ribosomal RNA (rRNA) sequences, the reads were then mapped, using Bowtie2 v 2.5.1 (63), against a reference rRNA database that contained a total of 505,405 rRNA non-repetitive sequences obtained from SILVA database v138.1 (64) and the RDP-II database (65). The remaining reads were assembled *de novo* into contigs using MEGAHIT v1.2.9 (66) and under default parameters. Only contigs longer than 600bp were retained for subsequent virus discovery and characterization.

Discovery and quality control of RNA virus contigs

VirID discovers RNA viral contigs through a homology-based search approach. The assembled contigs were first compared against the RdRP reference database using the Diamond blastx program v2.0.15.153 (58) to identify potential RNA viral sequences. To remove false positives, potential viral contigs were subsequently compared against the NCBI Non-Redundant Protein Database (NR) and the hits were annotated using TaxonKit v0.14.2(67). Contigs with only non-viral hits were removed, and the top hits of the remaining contigs were used to provide an initial taxonomic annotation for the viral contigs.

In addition to the standard quality control steps described above, VirID has extra procedures to identify and remove false positives and erroneous sequences. To filter out potential endogenous virus elements (EVEs) with disrupted ORFs, we removed contigs whose RdRP-associated open reading frames (ORFs) were predicted to contain less than 200 amino acids by scanning the viral sequence in six possible reading frames. To identify and control for misassembled contigs that contained both viral and non-viral sequences, the sequence was first compared using BLASTn (68) against a "non-viral" database, specifically a sub-set of NCBI Nucleotide Sequence Database (NT) that excludes RNA viral sequences. Based on the position and length of hit, the target contigs were either partially corrected (i.e., in scenarios when "non-viral" regions

appear at either end of the contigs and were shorter than the "viral" region) or

completely removed (all other cases).

RNA virus species identification and quantification

For viral species identification, the RdRP-associated contigs were further clustered

based on 80% sequence identity and 40% sequence length to form species-level

taxonomic units. For each species, the predicted RdRPs were compared against the NR

database, and those with >90% identity and 70% coverage to existing RNA viral species

were denoted "known" viral species, whereas those below these thresholds were

considered as "new" viral species.

The sequence Reads Per Million (RPM) metric was used to evaluate the relative

abundance of virus species within the sample. Clean reads are first mapped to all contigs

associated with a virus species using Bowtie2 v2.5.1(63). The number of mapped reads

is multiplied by 10^6 and divided by the total number of reads to give the RPM value.

198
$$RPM = \frac{MappedReads * 10^6}{TotalReads}$$

Viral sequence alignment at the superclade level

For newly identified viral sequences, multiple alignment was performed before

subsequent phylogenetic placement. Viral RdRP sequences were first classified into 24

superclades for sequence alignment and phylogenetic analysis, based on BLASTx

comparisons (68) against the RdRP reference database. VirID utilizes the Amino Acid

Consistency (AAC) index to quantify the similarity between two amino acid sequences.

The AAC is calculated by dividing the number of identical, non-empty amino acids by

the total length of the amino acid sequence (Extended Data Figure 1).

To ensure the accuracy of multiple sequence alignments, we employed an iterative

approach with Mafft v7.520 (69), followed by the removal of ambiguously aligned

regions using trimAl v1.4 (70). In each iteration, for each reference sequence (R^i), its

amino acid identity r^i is determined by the highest amino acid identity value

compared to other reference sequences. For each potential viral sequence (Q^i), its

amino acid identity q^i is set as the maximum value when compared to all reference

sequences. If q^i falls below the minimum value of R across the entire reference

sequence set, the sequence Q^i is removed as a poor-quality sequence, and the alignment

process is repeated. The pseudocode for eliminating false positives through multiple

sequence alignment is provided in Supplementary Figure S2.

$$r^i = \max_{i \neq j} AAC(R^i, R^j)$$

$$q^i = \max_{k \in RefList} AAC(Q^i, R^K)$$

Phylogenetic placement

To optimize phylogenetic tree inference, we implemented an approach based on

reference trees. We first estimated reference maximum likelihood trees using the

PROTGAMMALGF model in RaxML v7 (71). Subsequently, new sequences were

integrated into these pre-built reference trees based on the alignment using the LG

model in pplacer v1.1 (72), which accurately identifies their most likely positions. The

output from pplacer, provided in JSON format, is then converted into the Newick tree

format using guppy v1.1 (72), facilitating further phylogenetic analyses.

To evaluate the reliability of our phylogenetic placement, we performed leave-one-

out cross-validation, focusing on tree recall, which measures the proportion of correctly

recovered branches. For this analysis, we only included branches supported by a

bootstrap confidence value exceeding 90%. We observed that the distribution of recall

rates varied across superclades, likely influenced by the number of reference sequences

and their similarity. In superclusters containing more than 50 sequences, recall rates for

most clusters tended to concentrate around 0.75, with few deviations (Supplementary

Figure S3). Additionally, in virus clades with a high density of sequences, such as

Picorna-Calici and Partiti-Picobirna, this placement method maintained the

fundamental stability of the tree structure, demonstrating robustness despite the

addition of numerous new sequences.

$$Tree\ recall = \frac{Edge_{both}}{Edge_{\text{reference}}}$$

Classification and host association inference based on phylogenetic analysis

The classification and host association of a query genome were inferred based on its placement within each RdRP superclade tree. We systematically annotated the evolutionary tree by traversing from the leaf nodes upwards, adhering to the principle that sibling nodes share the same labels. The labeling process for each leaf node followed the following criteria: (i) if the node corresponds to a known sequence, its label is assigned based on the existing annotation; (ii) if its sibling node is a known sequence, the leaf node inherits the label of its sibling; and (iii) if its sibling node is an internal node, we iteratively determined the label of that internal node before assigning it to the leaf node. For internal nodes, we conducted a systematic top-down traversal of all their daughter nodes. If all daughter nodes carry identical labels, the internal node adopts the same label as its descendants. However, if the daughter nodes have differing labels, the internal node is categorized under the lowest common taxonomic label for all those leaf nodes in this superclade. This structured approach ensures consistent and logical assignment of labels throughout each superclade tree.

Each potential viral sequence is assigned two types of labels: a taxonomic label that spans superclade-taxon to ICTV hierarchical classification and eventually down to the species level, and a host association label that categorizes the virus as related to humans, vertebrates, or plants. During the phylogenetic tree annotation, host association tags (represented as 0 or 1) are assigned to sequences. Specifically, if a viral sequence's sibling node is identified as a human pathogen, the sequence is considered potentially relevant to humans only if the similarity exceeds 80%. For the ICTV classification within the phylogenetic tree, the label of each internal node is determined by identifying the longest common prefix among the ICTV labels of all its daughter nodes. For sequences that remain unclassified, a default taxonomic hierarchy is assigned within the corresponding superclade. This classification system effectively categorizes potential viral sequences up to the genus level. For well-documented

viruses, species-level classification is determined using the NCBI annotation file
derived from comparisons within the NR database. This rigorous approach ensures
accurate and detailed categorization of viral sequences across various levels of
taxonomic and host associations.

Benchmarking Preliminary Viral Contig Screening on Simulated Data set

To evaluate the performance of VirID in the preliminary screening of RNA viral
sequences, we constructed a simulated short-read shotgun metagenomic data set for
benchmarking using CAMISIM (73). This data set included 15 samples from three
categories: 'known RNA viruses', 'new RNA viruses', and 'others', with each category
comprising 15 species. The 'known RNA viruses' and 'others' data sets were derived
from 463 complete RNA virus genomes and 55 complete non-RNA virus genomes
available in the NCBI RefSeq database, respectively (Supplementary Figure S4). The
'new RNA viruses' were subdivided into three levels based on their sequence similarity
to the reference database and containing five species each: 'new RNA virus L1', 'new
RNA virus L2', and 'new RNA virus L3', with similarity thresholds set at $0.70 \leq$
similarity (L1) ≤ 0.90, $0.40 \leq$ similarity (L2) < 0.70, and $0.20 \leq$ similarity (L3) < 0.40,
respectively. The sequences used to simulate 'new RNA viruses' were sourced from 299
high-quality RNA virus sequences obtained from recent publications (57,74-76),
ensuring a comprehensive and challenging test environment.

The individual simulated data samples are provided in pair-end fastq format, with
each file approximately 20 GB in size and each read 150 base pairs long. The
distribution of the three data types within each sample is maintained at a consistent ratio
of 1:1:1. Unlike other tools that require contigs, VirID accepts reads directly as input.
To ensure consistent data standards across all tools, the contigs generated from VirID's
intermediate outputs are used as input for the other tools. Additionally, for uniformity
in evaluation metrics, all tools have adopted VirID's criterion of using contigs longer
than 600bp.

We assessed the performance of six different viral detection tools—VirFinder, DeepVirFinder, VirSorter, VirSorter2, VirBot, and VirID—on a simulated data set using accuracy, precision, recall, and F1 score. These metrics focus on the number of correctly identified species in the tool's output, rather than the number of sequences. The accuracy of each tool reflects the proportion of RNA viral species correctly identified from the total number of species. Recall measures the tool's sensitivity by calculating the proportion of RNA viral species detected relative to the total number of RNA viral species in the data set. Precision indicates the specificity of the tool, defined as the proportion of RNA viral species detected out of the total number of species identified by the tool. The F1 score, the harmonic mean of precision and recall, provides a balanced measure of a tool's overall effectiveness.

Metagenomic data sets

To demonstrate VirID's visualization capabilities, we analyzed 20 SRA libraries from a large scale animal study conducted in China (76) that comprised 14 species across five provinces. In addition, we assessed the versatility of VirID through the analysis of 192 public libraries from seven studies, which included a wide range of samples from human swabs (77) and diverse animal tissues (78-80), as well as arthropod (81), plant (82), and soil samples (83). The public metagenomes utilized in this analysis were sourced from NCBI, with details provided in Supplementary Table S2, S3.

Parameters and visualizations

VirID offers three user-selectable modes: 'end to end', 'assembly and basic annotation', and 'phylogenetic analysis'. The 'end to end' mode executes both 'assembly and basic annotation' and 'phylogenetic analysis' sequentially. The 'assembly and basic annotation' mode processes sequencing data up to the point of producing annotated contigs, but it does not include phylogenetic analyses. Conversely, the 'phylogenetic analysis' mode begins with contigs and carries out subsequent processing from there.

During the 'assembly and basic annotation' stage, users can opt to remove mis-
assembled portion of a virus contig, a process that may require significant memory
resources. Additionally, an ultrasensitive mode is available for analyzing RdRP libraries
that enhances the detection of a broader range of potential viral sequences. In the
'phylogenetic analysis' phase, users can choose to eliminate redundant sequences and
customize the amino acid length thresholds for specific virus of interest.

VirID employs several tools for visualizations: sankey diagrams, stacked
histograms, and phylogenetic tree diagrams are generated using the R packages
networkD3 (84), ggtree (85), and ggplot2 (86), respectively. Further visualizations are
created using Matplotlib v3.7.4 (87) and Seaborn v0.13.0 (88), enabling comprehensive
graphical representations of the data.

RESULTS

VirID workflow

VirID is a user-friendly command-line tool designed for the detection and
detailed characterization of RNA viruses from metagenomic data. The workflow is
divided into three stages: RNA virus discovery, phylogenetic analysis, and phylogeny-
based virus characterization (Figure 2). In the first stage, putative RNA virus genomes
containing the RdRP gene are identified through a homology approach, checked for
false positives and contamination, and clustered based on sequence similarity at the
species level. This process yields high-quality genomic sequences and related
information such as sequence length, closest relatives, and abundance levels. In the
second stage, VirID conducts high-quality sequence alignment and comprehensive
evolutionary analysis across the full diversity of the RNA virosphere: this further
removes low-quality sequences and reveals the phylogenetic position of all newly
discovered viruses. In the final stage, based on these evolutionary analyses, VirID
provides precise classification information and predicts potential viral associations
with humans, vertebrates, and plants.

Figure 2. Framework for Identifying RNA Viruses from Sequencing Samples. The VirID process for automated RNA virus detection, which comprises three main stages: (**i**) RNA virus discovery, (**ii**) phylogenetic analysis, and (**iii**) phylogeny-based virus characterization. It pr oduces outputs that include viral sequences, phylogenetic trees, and comprehensive information including sequence length, best match of BLASTx comparison, virus classification, and host association.

Analysis Results Output in VirID

VirID conducts thorough data analyses and offers robust visualization tools, enabling an intuitive and comprehensive presentation of results. VirID organizes its output into three main folders: (i) ' assembly and basic annotation ' for intermediate files related to RNA virus discovery, (ii) 'phylogenetic analysis' containing well-labelled trees for various superclades, and (iii) 'results' for other figures and tables. It generates tables, fasta files, web files, and figure files (pdf format) to suit various analytical needs. We demonstrated these features here using a data set from 20 wildlife sequencing libraries that includes bats, insectivores, pangolins, pika and rodent samples (76) (Figure 3, Supplementary Table S2). In the RNA virus discovery segment, VirID estimates Reads Per Million (RPM) values for each potential viral species to assess their relative abundance. These values are displayed in a sankey plot on an HTML webpage, illustrating RPM distributions across RdRP superclades and NCBI taxonomy at multiple taxonomy levels—phylum, class, order, family, genus, and species (Figure 3A). VirID also categorizes potential viral sequences into one or two of four host-

association groups: human, vertebrate, plants, and others (Figure 3B). This information

is provided in color-coded trees that contain information on both phylogenetic

relationships and potential host associations (Figure 3C). Additionally, VirID outputs

high-quality viral genome sequences in fasta format (Figure 3D) and all other relevant

information, including sequence length, highest BLASTx match, virus classification,

association with principal hosts, in multidimensional tables (Figure 3E, Supplementary

Table S4, S5).

Figure 3. Visualization of Outputs from VirID. (**A**) Distribution of Reads Per Million (RPM) of potential viral sequences from SRA sample SRR22936818, categorized by RdRP superclade and corresponding NCBI taxonomic ranks. (**B**) The host associations of all identified virus sequences based on their placement in the phylogenetic tree. (**C**) A phylogenetic tree is used to distinguish different viral lineages and colour-coded by taxonomic group. In this case, newly identified virus sequences in the Nido superclade are highlighted in red at the end of the branches, emphasizing their significance. (**D**) Complete nucleic acid sequences for detailed analysis and verification. (**E**) Detailed information for each identified viral sequence, including host association, genomic details, and taxonomic classification.

In the example of the 20 wildlife sequencing libraries VirID identified 129 potential

RNA viral contigs belonging to 107 various species, including 87 new virus species,

spanning 26 families and 15 superclades (Supplementary Figure S5A). Overall, 54 of

these species can be assigned at the family level, with the remainder falling outside

known families. Eleven of these species are potentially relevant to humans and include

Wufeng Niviventer niviventer orthohantavirus 1, Severe acute respiratory syndrome-

related coronavirus, Rotavirus A, and Pangolin respirovirus (Supplementary Figure

S5B, Supplementary Figure S6). Additionally, several viral species associated with

vertebrate infections were identified, including those within the genera

Alphacoronavirus, *Alphainfluenzavirus*, and *Mammarenavirus*. The remaining 88 viral

species are most likely derived from diet, parasites, and other microbial cellular

organisms within the principal host, because they were identified as plant viruses (e.g.

members of the *Tombunsviridae*) or closely related to arthropod (e.g. *Iflaviridae*) or

fungal viruses (e.g. *Mitoviridae*).

Benchmarking VirID on simulated data set

We initially evaluated VirID alongside five other tools—VirBot, VirSorter2,

VirSorter, DeepVirFinder, and VirFinder—using a collection of simulated samples (N

= 15) that included a diverse mix of RNA viruses and other species. These read data

samples were generated using the CAMISIM simulator, drawing on source genomes

and sequences from both the NCBI RefSeq database and recent studies. The RNA

viruses in the CAMISIM pool were comprised of four categories: 'known RNA viruses',

'new RNA virus L1', 'new RNA virus L2', and 'new RNA virus L3', representing

different similarity levels to the reference database sequences.

Six tools were compared across 15 data samples, including the average accuracy,

precision, recall, and F1 score metrics (Figure 4A). VirID achieved the highest F1 score

of 0.9334, with a standard error of ±0.0180. Its recall, at 0.8822 with a standard error

of ±0.0301, was close to VirBot (0.8822 ± 0.0247). Notably, VirID's precision was

perfect across all 15 samples, with an absence of false positives. Of all the tools, the

three with the best performance—VirBot, VirSorter2, and VirID—and were further

evaluated for their performance on 'new RNA viruses' which shared less than 90%

amino acid identity with those described in NCBI database (Figure 4B) and 'known

RNA viruses'. VirID continued to perform well in identifying 'new RNA viruses', again

with zero false positives (Supplementary Figure S7).

We also analyzed whether the number of viral sequences or species revealed by

each tool matched that of expected species count in the simulated data (Figure 4C).

VirID's estimation of contigs (39, average) and species (27, average) were the mostly

closely aligned with the 30 true species samples, followed by VirSorter2 (average of 45

contigs and 26 species) and then VirBot (53 contigs and 27 species). VirID achieved a

ratio of 1.47 for the number of estimated sequences relative to the number of true

species. This ratio was the lowest among all tools, indicating that VirID's output most

accurately reflect the actual number of virus species.

The integrity of the RNA viral sequences revealed and processed by VirID was

assessed using the CAMISIM simulator's 'gold standard' contigs as a benchmark. These

standard contigs represent idealized assembly results of the simulated reads, providing

a baseline for evaluating the detected virus sequences. We aligned the putative viral

contigs with these 'gold standard' contigs, selecting the best matches based on coverage

and identity. The average completeness for contigs in 10 samples exceeded 90%, with

an overall average completeness of 90.80% across all 15 samples (Figure 4D). This

meets CheckV's criterion for 'high quality completeness' (89).

Figure 4. Benchmarking of Various Tools using Simulated Data. (**A**) Performance of six bioinformatic tools across
15 simulated samples, evaluating average accuracy, precision, recall, and F1 score. Error bars represent standard
errors. (**B**) Three tools – VirID, VirBot, VirSorter2 – had superior performance and were further assessed for their
specific ability to identify 'new RNA viruses' at various levels of classification. (**C**) Effectiveness of each tool in
identifying RNA virus sequences across 15 simulated samples. Yellow dots represent the number of RNA virus
sequences identified, while green dots indicate the number of corresponding species-level taxa. The inset graph in
the upper right corner adjusts the y-axis to range from 0-60 for a focused view. (**D**) Ratio of the lengths of sequences
identified by VirID in various simulated data samples compared to the length of the corresponding gold standard
sequence. Only sequences that uniquely correspond to gold standard sequences are considered.

A re-analyses of previously published data sets

We next assessed the performance of VirID by analyzing 192 meta-transcriptomic

SRA libraries from seven distinct virome studies, covering a range of sample types

including clinical (human), wild birds, Malayan pangolins, Qinghai voles, seabird ticks,

soybean fields, and peat soil samples (Supplementary Table S3). VirID significantly

improved viral discovery. From these data sets, a total of 1,283 RNA viral species were

identified, with the soil samples displaying the highest average virus species richness

at 88.5 species, followed by Qinghai vole at 2 and seabird tick at 1.9. Importantly, 1,202

novel RNA viral species were identified, among which 1,198 species were not

described in the original study. Among these, the highest number of novel viruses ($N =$

740) was found in the soil samples, with 56% of these viruses categorized within the Narna-Levi superclade. At the family level, the *Picobirnaviridae* contained the most viral species (*N = 164*), followed by the *Tombusviridae* (*N = 83*) and *Mitoviridae* (*N = 69*), although many virus species (54.5%) could not be assigned at family level (Figure 5A).

We next evaluated the number of families identified and compared these with previous studies, omitting any with incomplete classification information. Our analysis revealed an average increase of five viral families, with notable differences particularly observed in the vole and soybean data sets (Figure 5B). In addition, VirID provided a more precise classification system for the target viruses. For instance, viruses that were previously classified only at the kingdom level, such as Bulatov virus, Fennes virus, Ronne virus, and Vovk virus from the seabird tick data set, were now classified at the genus level (Supplementary Table S6).

Figure 5. Reclassification of Viruses Using VirID using Real-World Data. (**A**) Distribution of virus species across different superclades and families identified by VirID in previously published data sets, including human swabs (77), wild birds (78), Malayan pangolins (79) Qinghai voles (80), arthropods (81), plant (82), and soil samples (83). (**B**) The utility of VirID across a broader spectrum of RNA virus families. Virus families documented in the original publications are displayed on the left, while those identified in this study are shown on the right.

VirID also provides information on whether the viruses observed are associated

with vertebrates, plants, or have the potential to infect humans. For example, in the

Qinghai vole data set, we identified 180 species that were likely associated with voles,

including *Mamastrovirus* (N = 1), *Hepacivirus* ($N = 5$), *Pegivirus* ($N = 2$), *Arteriviridae*

($N = 1$), and *Picobirnaviridae* ($N = 164$). Additionally, 250 virus species were likely

associated with food sources, parasites, and symbionts within these hosts, including

Narna-Levi ($N = 163$), Partiti-Picobirna ($N = 74$) and Toti-Chryso ($N = 6$) (Figure 6A).

Overall, vertebrate-associated viruses accounted for a median of 66% of the total RNA

in host samples, ranging from 30.2-73.6%, while other viruses accounted for 23.3%,

with a range of 10.5-67.9% (Figure 6B). Notably, we identified two species,

Hepatovirus D and Rotavirus A, that are potential human pathogens. Hepatovirus D

was described in the original publication (80), while Rotavirus A was newly identified

here. These viruses were discovered because they cluster with known human pathogens

at over 80% sequence identity with these viral contigs.

Similarly, we identified 17 potential human pathogens, primarily within the clinical

sample data set. This included potential human pathogens such as Pangolin coronavirus

HKU4, Rotavirus A, and Pangolin Respirovirus identified in pangolins, as well as the

vector-borne Gadgets Gully virus, Okhotskiy virus, and Neke harbour virus from the

seabird tick samples. This is consistent with previous publications. Additionally, plant-

infecting viruses were identified in the vole ($N = 5$, likely diet-related), soybean ($N =$

6), and soil ($N = 24$) samples (Figure 6C, Supplementary Table S7). In the Soybean

field data set, we detected 79 contigs from six viral species associated with plants,

constituting about 74.5% of the total RNA, including Tobacco streak virus, Soybean

dwarf virus, Pepper mild mottle virus, Bean pod mottle virus, and Alfalfa mosaic virus

(Figure 6D).

Figure 6. Virus-Host Associations Revealed by VirID. (**A**) Number of known and unknown virus sequences related to humans, vertebrates, plants, and other hosts as identified by VirID in the Qinghai vole case study. (**B**) Count of virus sequences associated with different hosts in various tissue and fecal samples from voles identified by VirID. (**C**) Number and taxonomy of virus sequences related to different hosts in various real-world samples identified by VirID (**D**) Number of virus sequences related to different hosts in a variety of real-world samples identified by VirID.

DISCUSSION

Herein, we present VirID, an RNA virus discovery platform specifically designed for Linux servers. VirID integrates phylogenetic analysis into the identification and characterization of RNA viruses, thereby substantially improving virus discovery. The platform employs an iterative scoring strategy in its alignment processes to minimize false positives and incorporates a phylogenetic placement algorithm for the rapid and

stable phylogenetic tree inference. As a result, users can accurately estimate RNA virus

diversity, classify each identified virus with high precision, at the same time obtaining

insights into host associations which enable the potential threat to human, animal and

plant health to be evaluated. The wealth of information generated by this platform will

be invaluable for researchers involved in early warning of infectious diseases across

diverse settings.

Our results show that VirID provides the most precise estimation of viral species

composition, while other programs tend to overestimate genetic diversity. This

overestimation may occur because some methods consider all virus-associated contigs,

including those with low coverage and fragmented genomes, potentially counting them

as multiple species. To depict diversity more accurately, it is essential to focus on

regions of the genome shared by the majority of viruses, thereby minimizing

overestimation (90,91). The RdRP gene is an excellent candidate for several reasons.

First, all RNA viruses, with the exception of RNA satellite viruses, contain the RdRP

(27-29). Second, the RdRP protein is the most conserved gene in the RNA virus genome,

and often comparable across different virus classes or even phyla (92,93). Therefore,

focusing solely on RdRP contigs is key to accurately determining viral diversity within

a sample.

Compared to other virus discovery programs, the phylogenetic analysis feature of

VirID stands provides a central analytical component. In particular, it provides an

automated and reliable method for accurately classifying previously undescribed RNA

viruses, especially those that are highly divergent in sequence. Traditionally, the

approach to classifying new viruses involved BLAST analyses and assigning

taxonomic position based on the closest related hits (41,43,94). However, this method

may counter the guidelines laid down by the International Committee on Taxonomy of

Viruses (ICTV) who apply varying criteria for virus taxonomy at the species and genus

levels (24,95,96). Additionally, the lack of a clear definition of what levels of genetic

similarity differentiate higher taxonomic ranks complicates the assignment of viruses

to new families or orders when protein identity is below 40%. More importantly, some

reference sequences are incorrectly classified, which can introduce errors into the

classification process. For instance, a sequence from soil metagenomic data

(MN035928), from a divergent member within the order *Bunyavirales*, was mistakenly

labeled as belonging to the genus *Arenavirus* within the *Arenaviridae* (97). As a

consequence, subsequent discoveries of similar viruses (OQ715420)(98) were also

mislabeled as *Arenaviridae*. Such misclassifications could be avoided with robust and

reliable phylogenetic analyses.

Phylogenetic analysis is also central to the inference of host associations. Viruses

from similar host categories tend to cluster together, forming what is known as a

phylogenetic monophyly, indicative of host structure in virus phylogeny (27,28,99,100).

This pattern holds true across different types of viruses, such as vertebrate-specific

viruses, arthropod-borne viruses, and plant viruses, in which host-associated

phylogenetic monophyletic groups are identifiable at various taxonomic levels—

ranging from family level (e.g., *Picornaviridae*), to genus level (e.g., *Alphavirus*), and

even within specific genetic lineages in a genus (e.g., mosquito-borne and tick-borne

virus groups within genus *Flavivirus*). Due to the varying scales and complexity of

these host-associated groups, phylogenetic analysis serves as a valuable tool for

exploring these relationships (75,76,79). However, assigning viruses to other host

groups such as arthropods, nematodes, and even basal eukaryotes (such as parasites)

remains challenging due to the scarcity of relevant virus data on these hosts. In addition,

a limitation to all virus discovery tools, including VirID, is that they may not identify

vertebrate-associated viruses if they occupy phylogenetic positions not previously

linked to vertebrate hosts.

The ability to infer host associations is highly relevant in disease monitoring

programs in which emerging pathogens are continuously identified and evaluated

(21,101,102). Numerous viruses are discovered in sequencing efforts, but not all are

relevant to the infection of principal host or impact health. Indeed, those relevant to

disease often constitute only a small fraction (103). For example, in a survey of over

1941 game animals across China, more than 1000 viruses were identified, yet only 102

were linked to mammalian infections, and even fewer (N = 21) were considered to pose a significant risk of infecting humans or other animal species (104). Similarly, a recent meta-transcriptomics study of 2438 mosquitoes in China revealed that among the 564 RNA virus species detected, 393 were likely associated with mosquitoes, but only 7 were linked to mammalian infections (i.e., arboviruses) (105). Thus, discerning potential host associations is crucial for assessing the public health or economic impact of discovered viruses (20,106,107).

Our study is subject to several limitations. First, while the phylogenetic placement method has accelerated the estimation of evolutionary trees, the self-iterative multi-sequence alignment process remains time-consuming. Second, VirID primarily relies on the RdRP for homology evidence and is therefore unable to identify genomes that do not contain RdRP sequences or that are too divergent to be detected in homology-based searches (108,109). Consequently, for segmented viruses, the full genome assembly may be incomplete. Third, VirID does not provide strain or genotype level typing which often depend on more variable parts of viral genomes (110,111). Finally, the RdRP database is continuously expanding, particularly with the addition of data from environmental samples (29,30,37,57,112). However, since these environmental RdRP data are unverified, and this study focuses on human, animal, and plant health, they are currently excluded from our database. Nevertheless, given the flexibility of our RdRP database structure, these data can be readily incorporated to facilitate future broader scale analyses.

DATA AVAILABILITY

VirID is freely available as an open-source Python code at https://github.com/ZiyueYang01/VirID

SUPPLEMENTARY DATA

Supplementary Data are available at NAR Online.

AUTHOR CONTRIBUTIONS

Conceptualization, EC Holmes, DY Guo and M Shi; Methodology, ZY Yang, YT Shan, X Liu, GW Chen, YF Pan, DY Guo and M Shi; Investigation, ZY Yang and YT Shan; Data Collection and Processing, QY Gou, J Zou, ZL Chang, Q Zeng, CH Yang, JB Kong, WC Wu, DY Guo and M Shi; Writing – Original Draft, ZY Yang and YT Shan; Writing – Review and Editing, All authors. Funding Acquisition, CM Li, H Peng, DY Guo and M Shi; Resources (computational), SC Li, X Zhang, DY Guo and M Shi; Supervision, CM Li , H Peng, DY Guo and M Shi.

FUNDING

This study is funded by National Natural Science Foundation of China (82341118, 32270160), Natural Science Foundation of Guangdong Province of China (2022A1515011854), Shenzhen Science and Technology Program (JCYJ20210324124414040, KQTD20200820145822023), Hong Kong Innovation and Technology Fund (ITF) (MRP/071/20X), Major Project of Guangzhou National Laboratory (GZNL2023A01001), Guangdong Province "Pearl River Talent Plan" Innovation, Entrepreneurship Team Project (2019ZT08Y464), and the Fund of Shenzhen Key Laboratory (ZDSYS20220606100803007). E.C. Holmes was supported by an NHMRC (Australia) Investigator Award (GNT2017197) and by AIR@InnoHK administered by the Innovation and Technology Commission, Hong Kong Special Administrative Region, China.

REFERENCES

1. Nicaise, V. (2014) Crop immunity against viruses: outcomes and future challenges. *Frontiers in plant science*, **5**, 660.

2. Fauci, A.S. (1988) The human immunodeficiency virus: infectivity and mechanisms of pathogenesis. *Science*, **239**, 617-622.

3. Zhong, N., Zheng, B., Li, Y., Poon, L., Xie, Z., Chan, K., Li, P., Tan, S., Chang, Q. and Xie, J. (2003) Epidemiology and cause of severe acute respiratory syndrome (SARS) in Guangdong, People's Republic of China, in February, 2003. *The Lancet*, **362**, 1353-1358.

4. Smith, G.J., Vijaykrishna, D., Bahl, J., Lycett, S.J., Worobey, M., Pybus, O.G., Ma, S.K., Cheung, C.L., Raghwani, J. and Bhatt, S. (2009) Origins and evolutionary genomics of the 2009 swine-origin H1N1 influenza A epidemic. *Nature*, **459**, 1122-1125.

5.   Assiri, A., McGeer, A., Perl, T.M., Price, C.S., Al Rabeeah, A.A., Cummings, D.A.,
Alabdullatif, Z.N., Assad, M., Almulhim, A. and Makhdoom, H. (2013) Hospital outbreak
of Middle East respiratory syndrome coronavirus. *New England Journal of Medicine*,
369, 407-416.

6.   Team, W.E.R. (2014) Ebola virus disease in West Africa—the first 9 months of the
epidemic and forward projections. *New England Journal of Medicine*, **371**, 1481-1495.

7.   Musso, D. and Gubler, D.J. (2016) Zika virus. *Clinical microbiology reviews*, **29**, 487-524.

8.   Zhu, N., Zhang, D., Wang, W., Li, X., Yang, B., Song, J., Zhao, X., Huang, B., Shi, W. and
Lu, R. (2020) A novel coronavirus from patients with pneumonia in China, 2019. *New*
England journal of medicine, **382**, 727-733.

9.   Chan, J.F.-W., To, K.K.-W., Tse, H., Jin, D.-Y. and Yuen, K.-Y. (2013) Interspecies
transmission and emergence of novel viruses: lessons from bats and birds. *Trends in*
microbiology, **21**, 544-555.

10.   Claas, E.C., Osterhaus, A.D., Van Beek, R., De Jong, J.C., Rimmelzwaan, G.F., Senne, D.A.,
Krauss, S., Shortridge, K.F. and Webster, R.G. (1998) Human influenza A H5N1 virus
related to a highly pathogenic avian influenza virus. *The Lancet*, **351**, 472-477.

11.   Peiris, J.M., De Jong, M.D. and Guan, Y. (2007) Avian influenza virus (H5N1): a threat to
human health. *Clinical microbiology reviews*, **20**, 243-267.

12.   Martina, B.E., Koraka, P. and Osterhaus, A.D. (2009) Dengue virus pathogenesis: an
integrated view. *Clinical microbiology reviews*, **22**, 564-581.

13.   Ergönül, Ö. (2006) Crimean-Congo haemorrhagic fever. *The Lancet infectious diseases*,
6, 203-214.

14.   He, S. and Krainer, K.M.C. (2020) Pandemics of people and plants: which is the greater
threat to food security? *Molecular plant*, **13**, 933-934.

15.   Lee, C. (2015) Porcine epidemic diarrhea virus: an emerging and re-emerging epizootic
swine virus. *Virology journal*, **12**, 1-16.

16.   Scholthof, K.B.G., Adkins, S., Czosnek, H., Palukaitis, P., Jacquot, E., Hohn, T., Hohn, B.,
Saunders, K., Candresse, T. and Ahlquist, P. (2011) Top 10 plant viruses in molecular
plant pathology. *Molecular plant pathology*, **12**, 938-954.

17.   Untiveros, M., Fuentes, S. and Salazar, L.F. (2007) Synergistic interaction of Sweet potato
chlorotic stunt virus (Crinivirus) with carla-, cucumo-, ipomo-, and potyviruses infecting
sweet potato. *Plant disease*, **91**, 669-676.

18.   Robilotti, E., Deresinski, S. and Pinsky, B.A. (2015) Norovirus. *Clinical microbiology*
reviews, **28**, 134-164.

19.   Mackenzie, J.S., Gubler, D.J. and Petersen, L.R. (2004) Emerging flaviviruses: the spread
and resurgence of Japanese encephalitis, West Nile and dengue viruses. *Nature*
medicine, **10**, S98-S109.

20.   Lefrançois, T., Malvy, D., Atlani-Duault, L., Benamouzig, D., Druais, P.-L., Yazdanpanah,
Y., Delfraissy, J.-F. and Lina, B. (2023) After 2 years of the COVID-19 pandemic,
translating One Health into action is urgent. *The Lancet*, **401**, 789-794.

21.   Carroll, D., Daszak, P., Wolfe, N.D., Gao, G.F., Morel, C.M., Morzaria, S., Pablos-Méndez,
A., Tomori, O. and Mazet, J.A. (2018) The global virome project. *Science*, **359**, 872-874.

22.   Zhang, Y.-Z., Shi, M. and Holmes, E.C. (2018) Using metagenomics to characterize an
expanding virosphere. *Cell*, **172**, 1168-1172.

23.   Shi, M., Zhang, Y.-Z. and Holmes, E.C. (2018) Meta-transcriptomics and the evolutionary
biology of RNA viruses. *Virus research*, **243**, 83-90.

24.   Simmonds, P., Adams, M.J., Benkő, M., Breitbart, M., Brister, J.R., Carstens, E.B., Davison,
A.J., Delwart, E., Gorbalenya, A.E. and Harrach, B. (2017) Virus taxonomy in the age of
metagenomics. *Nature Reviews Microbiology*, **15**, 161-168.

25.   Zhang, Y.-Z., Chen, Y.-M., Wang, W., Qin, X.-C. and Holmes, E.C. (2019) Expanding the
RNA virosphere by unbiased metagenomics. *Annual Review of Virology*, **6**, 119-139.

26.   Greninger, A.L. (2018) A decade of RNA virus metagenomics is (not) enough. *Virus*
Research, **244**, 218-229.

27.   Shi, M., Lin, X.-D., Tian, J.-H., Chen, L.-J., Chen, X., Li, C.-X., Qin, X.-C., Li, J., Cao, J.-P.
and Eden, J.-S. (2016) Redefining the invertebrate RNA virosphere. *Nature*, **540**, 539-
543.

28.   Shi, M., Lin, X.-D., Chen, X., Tian, J.-H., Chen, L.-J., Li, K., Wang, W., Eden, J.-S., Shen, J.-J.
and Liu, L. (2018) The evolutionary history of vertebrate RNA viruses. *Nature*, **556**, 197-
202.

29.   Zayed, A.A., Wainaina, J.M., Dominguez-Huerta, G., Pelletier, E., Guo, J., Mohssen, M.,
Tian, F., Pratama, A.A., Bolduc, B. and Zablocki, O. (2022) Cryptic and abundant marine
viruses at the evolutionary origins of Earth's RNA virome. *Science*, **376**, 156-162.

30.   Chen, Y.-M., Sadiq, S., Tian, J.-H., Chen, X., Lin, X.-D., Shen, J.-J., Chen, H., Hao, Z.-Y.,
Wille, M. and Zhou, Z.-C. (2022) RNA viromes from terrestrial sites across China expand
environmental viral diversity. *Nature Microbiology*, **7**, 1312-1323.

31.   Huhtamo, E., Moureau, G., Cook, S., Julkunen, O., Putkuri, N., Kurkela, S., Uzcategui, N.Y.,
Harbach, R.E., Gould, E.A. and Vapalahti, O. (2012) Novel insect-specific flavivirus
isolated from northern Europe. *Virology*, **433**, 471-478.

32.   Culley, A.I., Lang, A.S. and Suttle, C.A. (2003) High diversity of unknown picorna-like
viruses in the sea. *Nature*, **424**, 1054-1057.

33.   Lam, T.T.-Y., Jia, N., Zhang, Y.-W., Shum, M.H.-H., Jiang, J.-F., Zhu, H.-C., Tong, Y.-G.,
Shi, Y.-X., Ni, X.-B. and Liao, Y.-S. (2020) Identifying SARS-CoV-2-related coronaviruses
in Malayan pangolins. *Nature*, **583**, 282-285.

34.   Mifsud, J.C., Gallagher, R.V., Holmes, E.C. and Geoghegan, J.L. (2022) Transcriptome
mining expands knowledge of RNA viruses across the plant kingdom. *Journal of*
Virology, **96**, e00260-00222.

35.   Li, C.-X., Shi, M., Tian, J.-H., Lin, X.-D., Kang, Y.-J., Chen, L.-J., Qin, X.-C., Xu, J., Holmes,
E.C. and Zhang, Y.-Z. (2015) Unprecedented genomic diversity of RNA viruses in
arthropods reveals the ancestry of negative-sense RNA viruses. *elife*, **4**, e05378.

36.   Holmes, E.C. (2009) *The evolution and emergence of RNA viruses*. Oxford University
Press.

37.   Edgar, R.C., Taylor, B., Lin, V., Altman, T., Barbera, P., Meleshko, D., Lohr, D., Novakovsky,
G., Buchfink, B. and Al-Shayeb, B. (2022) Petabase-scale sequence alignment catalyses
viral discovery. *Nature*, **602**, 142-147.

38.   Shi, M., Hou, X., He, Y., Fang, P., Mei, S.-Q., Xu, Z., Wu, W.-C., Tian, J.-h., Zhang, S. and
Zeng, Z.-Y. (2023) Artificial intelligence redefines RNA virus discovery.

39.   Rampelli, S., Soverini, M., Turroni, S., Quercia, S., Biagi, E., Brigidi, P. and Candela, M.
(2016) ViromeScan: a new tool for metagenomic viral community profiling. *Bmc*

Genomics, **17**, 1-9.

40.   Flygare, S., Simmon, K., Miller, C., Qiao, Y., Kennedy, B., Di Sera, T., Graf, E.H., Tardif, K.D.,
740   Kapusta, A. and Rynearson, S. (2016) Taxonomer: an interactive metagenomics analysis
741   portal for universal pathogen detection and host mRNA expression profiling. *Genome*
742   *biology*, **17**, 1-18.

743   41.   Lin, J., Kramna, L., Autio, R., Hyöty, H., Nykter, M. and Cinek, O. (2017) Vipie: web
744   pipeline for parallel characterization of viral populations from multiple NGS samples.
745   *BMC genomics*, **18**, 1-11.

746   42.   Kalantar, K.L., Carvalho, T., de Bourcy, C.F., Dimitrov, B., Dingle, G., Egger, R., Han, J.,
747   Holmes, O.B., Juan, Y.-F. and King, R. (2020) IDseq—An open source cloud-based
748   pipeline and analysis service for metagenomic pathogen detection and monitoring.
749   *Gigascience*, **9**, giaa111.

750   43.   Plyusnin, I., Vapalahti, O., Sironen, T., Kant, R. and Smura, T. (2023) Enhanced viral
751   metagenomics with lazypipe 2. *Viruses*, **15**, 431.

752   44.   Zhou, Z., Martin, C., Kosmopoulos, J.C. and Anantharaman, K. (2023) ViWrap: A modular
753   pipeline to identify, bin, classify, and predict viral–host relationships for viruses from
754   metagenomes. *Imeta*, **2**, e118.

755   45.   Akhter, S., Aziz, R.K. and Edwards, R.A. (2012) PhiSpy: a novel algorithm for finding
756   prophages in bacterial genomes that combines similarity-and composition-based
757   strategies. *Nucleic acids research*, **40**, e126-e126.

758   46.   Roux, S., Enault, F., Hurwitz, B.L. and Sullivan, M.B. (2015) VirSorter: mining viral signal
759   from microbial genomic data. *PeerJ*, **3**, e985.

760   47.   Guo, J., Bolduc, B., Zayed, A.A., Varsani, A., Dominguez-Huerta, G., Delmont, T.O.,
761   Pratama, A.A., Gazitúa, M.C., Vik, D. and Sullivan, M.B. (2021) VirSorter2: a multi-
762   classifier, expert-guided approach to detect diverse DNA and RNA viruses. *Microbiome*,
763   **9**, 1-13.

764   48.   Kieft, K., Zhou, Z. and Anantharaman, K. (2020) VIBRANT: automated recovery,
765   annotation and curation of microbial viruses, and evaluation of viral community function
766   from genomic sequences. *Microbiome*, **8**, 1-23.

767   49.   Ren, J., Ahlgren, N.A., Lu, Y.Y., Fuhrman, J.A. and Sun, F. (2017) VirFinder: a novel k-mer
768   based tool for identifying viral sequences from assembled metagenomic data.
769   *Microbiome*, **5**, 1-20.

770   50.   Ren, J., Song, K., Deng, C., Ahlgren, N.A., Fuhrman, J.A., Li, Y., Xie, X., Poplin, R. and Sun,
771   F. (2020) Identifying viruses from metagenomic data using deep learning. *Quantitative*
772   *Biology*, **8**, 64-77.

773   51.   Chen, G., Tang, X., Shi, M. and Sun, Y. (2023) VirBot: an RNA viral contig detector for
774   metagenomic data. *Bioinformatics*, **39**, btad093.

775   52.   Hegarty, B., Riddell V, J., Bastien, E., Langenfeld, K., Lindback, M., Saini, J.S., Wing, A.,
776   Zhang, J. and Duhaime, M.J.M. (2024) Benchmarking informatics approaches for virus
777   discovery: caution is needed when combining in silico identification methods. **9**,
778   e01105-01123.

779   53.   Dutilh, B.E., Varsani, A., Tong, Y., Simmonds, P., Sabanadzovic, S., Rubino, L., Roux, S.,
780   Munoz, A.R., Lood, C. and Lefkowitz, E.J.J.C.o.i.v. (2021) Perspective on taxonomic
781   classification of uncultivated viruses. **51**, 207-215.

782   54.   Simon-Loriere, E. and Holmes, E.C. (2011) Why do RNA viruses recombine? *Nature*
783   *Reviews Microbiology*, **9**, 617-626.
784   55.   Drake, J.W. (1993) Rates of spontaneous mutation among RNA viruses. *Proceedings of*
785   *the National Academy of Sciences*, **90**, 4171-4175.
786   56.   Shi, M., Lin, X.-D., Tian, J.-H., Chen, L.-J., Chen, X., Li, C.-X., Qin, X.-C., Li, J., Cao, J.-P.,
787   Eden, J.-S. *et al.* (2016) Redefining the invertebrate RNA virosphere. *Nature*, **540**, 539-+.
788   57.   Hou, X., He, Y., Fang, P., Mei, S.-Q., Xu, Z., Wu, W.-C., Tian, J.-H., Zhang, S., Zeng, Z.-Y.
789   and Gou, Q.-Y. (2023) Artificial intelligence redefines RNA virus discovery. *bioRxiv*,
790   2023.2004. 2018.537342.
791   58.   Buchfink, B., Xie, C. and Huson, D.H. (2015) Fast and sensitive protein alignment using
792   DIAMOND. *Nature methods*, **12**, 59-60.
793   59.   Babaian, A. and Edgar, R. (2022) Ribovirus classification by a polymerase barcode
794   sequence. *PeerJ*, **10**, e14055.
795   60.   Fu, L., Niu, B., Zhu, Z., Wu, S. and Li, W. (2012) CD-HIT: accelerated for clustering the
796   next-generation sequencing data. *Bioinformatics*, **28**, 3150-3152.
797   61.   Mihara, T., Nishimura, Y., Shimizu, Y., Nishiyama, H., Yoshikawa, G., Uehara, H., Hingamp,
798   P., Goto, S. and Ogata, H. (2016) Linking virus genomes with host taxonomy. *Viruses*, **8**,
799   66.
800   62.   Bushnell, B. (2014). Lawrence Berkeley National Lab.(LBNL), Berkeley, CA (United States).
801   63.   Langmead, B. and Salzberg, S.L. (2012) Fast gapped-read alignment with Bowtie 2.
802   *Nature methods*, **9**, 357-359.
803   64.   Quast, C., Pruesse, E., Yilmaz, P., Gerken, J., Schweer, T., Yarza, P., Peplies, J. and
804   Glöckner, F.O. (2012) The SILVA ribosomal RNA gene database project: improved data
805   processing and web-based tools. *Nucleic acids research*, **41**, D590-D596.
806   65.   Cole, J.R., Chai, B., Farris, R.J., Wang, Q., Kulam-Syed-Mohideen, A., McGarrell, D.M.,
807   Bandela, A., Cardenas, E., Garrity, G.M. and Tiedje, J.M. (2007) The ribosomal database
808   project (RDP-II): introducing myRDP space and quality controlled public data. *Nucleic*
809   *acids research*, **35**, D169-D172.
810   66.   Li, D., Liu, C.-M., Luo, R., Sadakane, K. and Lam, T.-W. (2015) MEGAHIT: an ultra-fast
811   single-node solution for large and complex metagenomics assembly via succinct de
812   Bruijn graph. *Bioinformatics*, **31**, 1674-1676.
813   67.   Shen, W. and Ren, H. (2021) TaxonKit: A practical and efficient NCBI taxonomy toolkit.
814   *Journal of Genetics and Genomics*, **48**, 844-850.
815   68.   Camacho, C., Coulouris, G., Avagyan, V., Ma, N., Papadopoulos, J., Bealer, K. and
816   Madden, T.L. (2009) BLAST+: architecture and applications. *BMC bioinformatics*, **10**, 1-9.
817   69.   Katoh, K. and Standley, D.M. (2013) MAFFT multiple sequence alignment software
818   version 7: improvements in performance and usability. *Molecular biology and evolution*,
819   **30**, 772-780.
820   70.   Capella-Gutiérrez, S., Silla-Martínez, J.M. and Gabaldón, T. (2009) trimAl: a tool for
821   automated alignment trimming in large-scale phylogenetic analyses. *Bioinformatics*, **25**,
822   1972-1973.
823   71.   Stamatakis, A., Hoover, P. and Rougemont, J. (2008) A rapid bootstrap algorithm for the
824   RAxML web servers. *Systematic biology*, **57**, 758-771.
72.   Matsen, F.A., Kodner, R.B. and Armbrust, E.V. (2010) pplacer: linear time maximum-

likelihood and Bayesian phylogenetic placement of sequences onto a fixed reference
tree. *BMC bioinformatics*, **11**, 1-16.

73. Fritz, A., Hofmann, P., Majda, S., Dahms, E., Dröge, J., Fiedler, J., Lesker, T.R., Belmann, P.,
DeMaere, M.Z. and Darling, A.E. (2019) CAMISIM: simulating metagenomes and
microbial communities. *Microbiome*, **7**, 1-12.

74. Feng, Y., Gou, Q.-y., Yang, W.-h., Wu, W.-c., Wang, J., Holmes, E.C., Liang, G. and Shi, M.
(2022) A time-series meta-transcriptomic analysis reveals the seasonal, host, and gender
structure of mosquito viromes. *Virus Evolution*, **8**, veac006.

75. Wang, J., Pan, Y.-f., Yang, L.-f., Yang, W.-h., Lv, K., Luo, C.-m., Wang, J., Kuang, G.-p.,
Wu, W.-c. and Gou, Q.-y. (2023) Individual bat virome analysis reveals co-infection and
spillover among bats and virus zoonotic potential. *Nature Communications*, **14**, 4079.

76. Cui, X., Fan, K., Liang, X., Gong, W., Chen, W., He, B., Chen, X., Wang, H., Wang, X. and
Zhang, P. (2023) Virus diversity, wildlife-domestic animal circulation and potential
zoonotic viruses of small mammals, pangolins and zoo animals. *Nature
Communications*, **14**, 2488.

77. Graf, E.H., Simmon, K.E., Tardif, K.D., Hymas, W., Flygare, S., Eilbeck, K., Yandell, M. and
Schlaberg, R. (2016) Unbiased detection of respiratory viruses by use of RNA
sequencing-based metagenomics: a systematic comparison to a commercial PCR panel.
Journal of clinical microbiology, **54**, 1000-1007.

78. Chang, W.-S., Eden, J.-S., Hall, J., Shi, M., Rose, K. and Holmes, E.C. (2020)
Metatranscriptomic analysis of virus diversity in urban wild birds with paretic disease.
Journal of Virology, **94**, 10.1128/jvi. 00606-00620.

79. Shi, W., Shi, M., Que, T.-C., Cui, X.-M., Ye, R.-Z., Xia, L.-Y., Hou, X., Zheng, J.-J., Jia, N.
and Xie, X. (2022) Trafficked Malayan pangolins contain viral pathogens of humans.
Nature microbiology, **7**, 1259-1269.

80. He, X., Wang, X., Fan, G., Li, F., Wu, W., Wang, Z., Fu, M., Wei, X., Ma, S. and Ma, X. (2022)
Metagenomic analysis of viromes in tissues of wild Qinghai vole from the eastern
Tibetan Plateau. *Scientific Reports*, **12**, 17239.

81. Pettersson, J.H.-O., Ellström, P., Ling, J., Nilsson, I., Bergström, S., González-Acuña, D.,
Olsen, B. and Holmes, E.C. (2020) Circumpolar diversification of the Ixodes uriae tick
virome. *PLoS Pathogens*, **16**, e1008759.

82. Elmore, M.G., Groves, C.L., Hajimorad, M., Stewart, T.P., Gaskill, M.A., Wise, K.A., Sikora,
E., Kleczewski, N.M., Smith, D.L. and Mueller, D.S. (2022) Detection and discovery of
plant viruses in soybean by metagenomic sequencing. *Virology Journal*, **19**, 149.

83. Bender, K.M., Svenning, M.M., Hu, Y., Richter, A., Schückel, J., Jørgensen, B., Liebner, S.
and Tveit, A.T. (2021) Microbial responses to herbivory-induced vegetation changes in a
high-Arctic peatland. *Polar Biology*, **44**, 899-911.

84. Allaire, J., Ellis, P., Gandrud, C., Kuo, K., Lewis, B., Owen, J., Russell, K., Rogers, J., Sese, C.
and Yetman, C. (2017) Package 'networkD3'. *D3 JavaScript network graphs from R.*

85. Yu, G., Smith, D.K., Zhu, H., Guan, Y. and Lam, T.T.Y. (2017) ggtree: an R package for
visualization and annotation of phylogenetic trees with their covariates and other
associated data. *Methods in Ecology and Evolution*, **8**, 28-36.

86. Wickham, H. (2011) ggplot2. *Wiley interdisciplinary reviews: computational statistics*, **3**,
180-185.

87. Hunter, J.D. (2007) Matplotlib: A 2D graphics environment. *Computing in science &*
engineering, **9**, 90-95.

88. Waskom, M.L. (2021) Seaborn: statistical data visualization. *Journal of Open Source*
Software, **6**, 3021.

89. Nayfach, S., Camargo, A.P., Schulz, F., Eloe-Fadrosh, E., Roux, S. and Kyrpides, N.C.
(2021) CheckV assesses the quality and completeness of metagenome-assembled viral
genomes. *Nature biotechnology*, **39**, 578-585.

90. Beerenwinkel, N., Günthard, H.F., Roth, V. and Metzner, K.J. (2012) Challenges and
opportunities in estimating viral genetic diversity from next-generation sequencing data.
Frontiers in microbiology, **3**, 31515.

91. García-López, R., Vázquez-Castellanos, J.F. and Moya, A. (2015) Fragmentation and
coverage variation in viral metagenome assemblies, and their effect in diversity
calculations. *Frontiers in bioengineering and biotechnology*, **3**, 141.

92. Venkataraman, S., Prasad, B.V. and Selvarajan, R. (2018) RNA dependent RNA
polymerases: insights from structure, function and evolution. *Viruses*, **10**, 76.

93. Mönttinen, H.A., Ravantti, J.J. and Poranen, M.M. (2021) Structure unveils relationships
between RNA virus polymerases. *Viruses*, **13**, 313.

94. Zhao, G., Wu, G., Lim, E.S., Droit, L., Krishnamurthy, S., Barouch, D.H., Virgin, H.W. and
Wang, D. (2017) VirusSeeker, a computational pipeline for virus discovery and virome
composition analysis. *Virology*, **503**, 21-30.

95. Lefkowitz, E.J., Dempsey, D.M., Hendrickson, R.C., Orton, R.J., Siddell, S.G. and Smith, D.B.
(2018) Virus taxonomy: the database of the International Committee on Taxonomy of
Viruses (ICTV). *Nucleic acids research*, **46**, D708-D717.

96. King, A.M., Adams, M.J., Carstens, E.B. and Lefkowitz, E.J. (2012) Virus taxonomy. *Ninth*
report of the International Committee on Taxonomy of Viruses, **9**.

97. Starr, E.P., Nuccio, E.E., Pett-Ridge, J., Banfield, J.F. and Firestone, M.K. (2019)
Metatranscriptomic reconstruction reveals RNA viruses with the potential to shape
carbon cycling in soil. *Proceedings of the National Academy of Sciences*, **116**, 25900-
25908.

98. Chen, Y.-M., Hu, S.-J., Lin, X.-D., Tian, J.-H., Lv, J.-X., Wang, M.-R., Luo, X.-Q., Pei, Y.-Y.,
Hu, R.-X. and Song, Z.-G. (2023) Host traits shape virome composition and virus
transmission in wild small mammals. *Cell*, **186**, 4662-4675. e4612.

99. French, R.K., Anderson, S.H., Cain, K.E., Greene, T.C., Minor, M., Miskelly, C.M., Montoya,
J.M., Wille, M., Muller, C.G. and Taylor, M.W. (2023) Host phylogeny shapes viral
transmission networks in an island ecosystem. *Nature Ecology & Evolution*, **7**, 1834-
1843.

100. Kitchen, A., Shackelton, L.A. and Holmes, E.C. (2011) Family level phylogenies reveal
modes of macroevolution in RNA viruses. *Proceedings of the National Academy of*
Sciences, **108**, 238-243.

101. Carlson, C.J., Albery, G.F., Merow, C., Trisos, C.H., Zipfel, C.M., Eskew, E.A., Olival, K.J.,
Ross, N. and Bansal, S. (2022) Climate change increases cross-species viral transmission
risk. *Nature*, **607**, 555-562.

102. Ko, K.K., Chng, K.R. and Nagarajan, N. (2022) Metagenomics-enabled microbial
surveillance. *Nature Microbiology*, **7**, 486-496.

103. Liang, G. and Bushman, F.D. (2021) The human virome: assembly, composition and host
interactions. *Nature Reviews Microbiology*, **19**, 514-527.

104. He, W.-T., Hou, X., Zhao, J., Sun, J., He, H., Si, W., Wang, J., Jiang, Z., Yan, Z. and Xing, G.
(2022) Virome characterization of game animals in China reveals a spectrum of
emerging pathogens. *Cell*, **185**, 1117-1129. e1118.

105. Pan, Y.-F., Zhao, H., Gou, Q.-Y., Shi, P.-B., Tian, J.-H., Feng, Y., Li, K., Yang, W.-H., Wu, D.
and Tang, G. (2024) Metagenomic analysis of individual mosquito viromes reveals the
geographical patterns and drivers of viral diversity. *Nature Ecology & Evolution*, **8**, 947-
959.

106. Bernstein, A.S., Ando, A.W., Loch-Temzelides, T., Vale, M.M., Li, B.V., Li, H., Busch, J.,
Chapman, C.A., Kinnaird, M. and Nowak, K. (2022) The costs and benefits of primary
prevention of zoonotic pandemics. *Science Advances*, **8**, eabl4183.

107. Rahman, M.T., Sobur, M.A., Islam, M.S., Ievy, S., Hossain, M.J., El Zowalaty, M.E., Rahman,
A.T. and Ashour, H.M. (2020) Zoonotic diseases: etiology, impact, and control.
Microorganisms, **8**, 1405.

108. Hu, W.-S. and Hughes, S.H. (2012) HIV-1 reverse transcription. *Cold Spring Harbor*
perspectives in medicine, **2**, a006882.

109. Telesnitsky, A. and Goff, S. (2011) Reverse transcriptase and the generation of retroviral
DNA.

110. Yang, C.-R., King, C.-C., Liu, L.-Y.D. and Ku, C.-C. (2020) FluConvert and IniFlu: a suite of
integrated software to identify novel signatures of emerging influenza viruses with
increasing risk. *BMC bioinformatics*, **21**, 1-14.

111. Liao, H., Cai, D. and Sun, Y. (2022) VirStrain: a strain identification tool for RNA viruses.
Genome Biology, **23**, 38.

112. Wolf, Y.I., Silas, S., Wang, Y., Wu, S., Bocek, M., Kazlauskas, D., Krupovic, M., Fire, A.,
Dolja, V.V. and Koonin, E.V. (2020) Doubling of the known set of RNA viruses by
metagenomic analysis of an aquatic virome. *Nature microbiology*, **5**, 1262-1270.

TABLE AND FIGURES LEGENDS

Figure 1. Overview of the RdRP Reference Database.

(**A**) Compilation of representative RdRP sequences into 24 RNA virus superclades,

categorized based on phylogenetic analysis.

(**B**) Alignment of viral superclades with the ICTV taxonomic system, spanning virus

class, order, and family levels. Numbers reflect the count of ICTV classifications

mapped to each RdRP superclade, with specific ICTV representative mapping details

provided.

(**C**) The distribution of viral sequences across supergroups and ICTV taxonomy, highlighting 551 vertebrate-related and 325 plant-related sequences. Data points are color-coded to represent host associations, and bar plots show the proportions of human pathogens and plant-associated viruses in each taxonomic group.

(**D**) Using the *Reoviridae* as a case study, the diagram presents a phylogenetic tree in which branch colors indicate taxonomy and background hues denote host association. Reference sequences are clearly annotated based on their positions within the phylogenetic tree.

Figure 2. Framework for Identifying RNA Viruses from Sequencing Samples.

The VirID process for automated RNA virus detection, which comprises three main stages: (i) RNA virus discovery, (ii) phylogenetic analysis, and (iii) phylogeny-based virus characterization. It produces outputs that include viral sequences, phylogenetic trees, and comprehensive information including sequence length, best match of BLASTx comparison, virus classification, and host association.

Figure 3. Visualization of Outputs from VirID.

(**A**) Distribution of Reads Per Million (RPM) of potential viral sequences from SRA sample SRR22936818, categorized by RdRP superclade and corresponding NCBI taxonomic ranks.

(**B**) The host associations of all identified virus sequences based on their placement in the phylogenetic tree.

(**C**) A phylogenetic tree is used to distinguish different viral lineages and colour-coded by taxonomic group. In this case, newly identified virus sequences in the Nido superclade are highlighted in red at the end of the branches, emphasizing their significance.

(**D**) Complete nucleic acid sequences for detailed analysis and verification.

(**E**) Detailed information for each identified viral sequence, including host association, genomic details, and taxonomic classification.

Figure 4. Benchmarking of Various Tools using Simulated Data.

(**A**) Performance of six bioinformatic tools across 15 simulated samples, evaluating average accuracy, precision, recall, and F1 score. Error bars represent standard errors.

(**B**) Three tools – VirID, VirBot, VirSorter2 – had superior performance and were further assessed for their specific ability to identify 'new RNA viruses' at various levels of classification.

(**C**) Effectiveness of each tool in identifying RNA virus sequences across 15 simulated samples. Yellow dots represent the number of RNA virus sequences identified, while green dots indicate the number of corresponding species-level taxa. The inset graph in the upper right corner adjusts the y-axis to range from 0-60 for a focused view.

(**D**) Ratio of the lengths of sequences identified by VirID in various simulated data samples compared to the length of the corresponding gold standard sequence. Only sequences that uniquely correspond to gold standard sequences are considered.

Figure 5. Reclassification of Viruses Using VirID using Real-World Data.

(**A**) Distribution of virus species across different superclades and families identified by VirID in previously published data sets, including human swabs (77), wild birds (78), Malayan pangolins (79) Qinghai voles (80), arthropods (81), plant (82), and soil samples (83).

(**B**) The utility of VirID across a broader spectrum of RNA virus families. Virus families documented in the original publications are displayed on the left, while those identified in this study are shown on the right.

1003

Figure 6. Virus-Host Associations Revealed by VirID.

(**A**) Number of known and unknown virus sequences related to humans, vertebrates, plants, and other hosts as identified by VirID in the Qinghai vole case study.

(**B**) Count of virus sequences associated with different hosts in various tissue and fecal samples from voles identified by VirID.

1009 (**C**) Number and taxonomy of virus sequences related to different hosts in various real-

1010 world samples identified by VirID.

1011 (**D**) Number of virus sequences related to different hosts in a variety of real-world

1012 samples identified by VirID.

1013

SUPPLEMENTARY INFORMATION

Supplementary Figure S1. Host Associations of Reference Viruses in 24

Superclades.

A total of 24 phylogenetic trees where background shading signifies host type (i.e.,

human, vertebrates, plants). Reference sequences are annotated according to their

phylogenetic positions within the tree.

1020

1021 **Supplementary Figure S2. Pseudocode for Eliminating False Positives.**

1022 The ACC function is used to calculate the consistency between two amino acid

1023 sequences. After each multiple sequence comparison, VirID calculates the consistency

1024 between query sequence and the reference sequence to obtain false positive sequences.

1025

1026 **Supplementary Figure S3. Accuracy of the VirID Placement Method for Different**

1027 **Superclades.**

1028 The performance of superclades performing leave-one-out cross-validation, evaluating

1029 tree recall. Each point represents one experiment.

1030

Supplementary Figure S4. Composition of the Simulation Data set Candidate Pool.

The simulated pool includes 'known RNA viruses', 'new RNA viruses', and 'others'. The

'known RNA viruses' were derived from the NCBI RefSeq database. The 'new RNA

viruses' were subdivided into three levels based on their sequence similarity to the

reference database and were sourced from recent research publications. The 'others'

includes DNA viruses, eukaryotes, bacteria, and archaea.

1037

Supplementary Figure S5. Viruses And Host Associations Revealed by VirID.

(**A**) The distribution of virus species across different superclades and families identified by VirID in 20 SRA libraries.

(**B**) The number of virus sequences related to humans, vertebrates, and other hosts as identified by VirID in 20 SRA libraries

Supplementary Figure S6. Phylogeny of Viruses Associated with Human or Vertebrates.

Phylogenetic tree shows the evolutionary relationships of the *Hantaviridae, Coronaviridae, Paramyxoviridae,* and *Sedoreoviridae* that contain potential human pathogens. Viral sequences identified by VirID. Those labelled in red are potential human pathogens, while sequences labelled in orange are viruses associated with vertebrates.

Supplementary Figure S7. Performance of Three Tools – VirBot, VirSorter2, and VirID – in Identifying 'new RNA viruses' and 'known RNA viruses'.

VirID recorded zero false positives in the identification of 'new RNA viruses'.

Supplementary Table S1. Mapping of the RdRp protein reference sequence database of RNA viruses to the ICTV taxonomic system.

Supplementary Table S2. Detailed information on 20 meta-transcriptomic from one previous study of bat, rodent, pangolin and zoo animal in China.

Supplementary Table S3. Detailed information on 192 public libraries from 7 studies retrieved from the SRA database.

Supplementary Table S4. Output information from the assembly and basic annotation phase.

1067

1068   **Supplementary Table S5.** Output information of the phylogenetic analysis section.

1069

1070   **Supplementary Table S6.** Detailed information on the classification results identified

1071   by VirID in seabird ticks.

1072

1073   **Supplementary Table S7.** Detailed information on possible host associations of viral

1074   sequences predicted by VirID in seven real-world cases.

1075