Title: Novel quantal analysis method reveals conservation of average charge injected by excitatory

synapses across cortical neurons of different sizes

Author Names and Affiliations: Martynas Dervinis[1], Guy Major[1]

[1]: Cardiff University, Cardiff, Wales, CF10 3AT, UK

Corresponding author email address: martynas.dervinis@gmail.com

Number of pages: 46

Number of figures: 9

Number of words

Abstract: 270

Body text excluding Materials and Methods: 3937

Conflict of interest statement: The authors declare no competing financial interests.

Acknowledgements: Cardiff University (GM, MD), The Medical Research Council of the UK (MD

PhD). Neural activity simulations were performed on the Cardiff School of Biosciences' Biocomputing

Hub HPC/Cloud infrastructure.

Abstract

In chemical synapses of the central nervous system (CNS), information is transmitted via the presynaptic release of a vesicle (or 'quantum') of neurotransmitter, which elicits a postsynaptic electrical response with an amplitude termed the 'quantal size'. This key determinant of neural computation is hard to measure reliably due to its small size and the multiple sources of noise within neurons and electrophysiological recordings. Measuring amplitudes of miniature postsynaptic currents (mPSCs) or potentials (mPSPs) at the cell soma is generally thought to offer a technically straightforward way to estimate quantal sizes, as each of these miniature responses (or 'minis') is generally thought to be elicited by the spontaneous release of a single neurotransmitter vesicle. However, a somatically recorded mini is typically massively attenuated compared with at its input site, and a significant fraction are indistinguishable from (or cancelled out by) background noise fluctuations. Here, as part of patch clamp data analysis software called 'minis', we describe a novel quantal analysis method that estimates the 'electrical size' of the synapse by combining somatic recordings of background physiological noise with and without minis with simulations. With the help of a genetic algorithm, simulations are successfully used to infer the combined amplitude and rise time distribution of minis that would otherwise be inaccessible due to low signal-to-noise ratios. The estimated distributions reveal a striking inverse dependence of mean minis' amplitudes on cell's total capacitance (proportional to cell size, more exactly, extracellular membrane surface area) that firmly supports the conservation of the average 'electrical size' (in terms of injected charge) of excitatory cortical synapses in rats, across neocortical pyramidal neurons of very different sizes.

Abbreviations

ABF – Axon Binary File

aCSF – artificial cerebrospinal fluid

AMPA – α-amino-3-hydroxy-5-methyl-4-isoxazolepropionic acid

AMPAR – α-amino-3-hydroxy-5-methyl-4-isoxazolepropionic acid receptor

ANN – artificial neural network

AP – action potential

CPP – (*RS*)-3-(2-carboxypiperazin-4-yl)-propyl-1-phosphonic acid

EPSC – excitatory postsynaptic current

EPSP – excitatory postsynaptic potential

GA – genetic algorithm

GABA – gamma-aminobutyric acid

IC50 – Half-maximal inhibitory concentration

IPSC – inhibitory post-synaptic current

IPSP – inhibitory post-synaptic potential

MAD – maximal absolute deviation

mEPSC– miniature excitatory post-synaptic current

mEPSP– miniature excitatory post-synaptic potential

mIPSP– miniature inhibitory post-synaptic potential

mPSC – miniature post-synaptic current

mPSP – miniature post-synaptic potential

NBQX – 2,3-dioxo-6-nitro-1,2,3,4-tetrahydrobenzo[*f*]quinoxaline-7-sulfonamide

NMDA – N-methyl-D-aspartate

NMDAR - N-methyl-D-aspartate receptor

SAD – sum of absolute deviations

SD – standard deviation

smEPSP – simulated mEPSP

SSD – sum of signed deviations

SSE – sum of squared errors

TTX – tetrodotoxin

V_m – membrane potential

Introduction

Synaptic transmission in the CNS occurs in 'quanta' (Forti et al., 1997; Hardingham et al., 2010; Isaacson and Walmsley, 1995; Jonas et al., 1993; Kraszewski and Grantyn, 1992; Kullmann and Nicoll, 1992; Kuno, 1964; Larkman et al., 1991; Sahara and Takahashi, 2001; Stern et al., 1992; Wall and Usowicz, 1998) usually thought to correspond to the release of a single neurotransmitter vesicle (Heuser et al., 1979). The amplitude of the postsynaptic response to a quantum of transmitter, the quantal size, is a key parameter defining the efficacy of synaptic transmission (Katz, 1969; Vere-Jones, 1966) and, therefore, an important determinant of neural computation.

Quantal size measurements in the CNS are difficult due to multi-synaptic contacts, limited accessibility, significant quantal variance, temporal non-stationarity of synaptic properties, and low signal-to-noise ratios of somatic electrophysiological recordings of quantal events (Bekkers, 1994; Korn and Faber, 1991). For these reasons classical quantal analysis as done at the neuromuscular junction has run into problems in central synapses. More recent methods such as noise deconvolution, Variance-Mean analysis, and optical quantal analysis have not fared much better either (Biró et al., 2005; Clamann et al., 1991; Clements, 2003; Clements and Silver, 2000; Edwards et al., 1976; Enoki et al., 2009; Jack et al., 1981; Liu et al., 2022; Oertner et al., 2002; Peled and Isacoff, 2011; Redman, 1990; Reid and Clements, 1999; Silver, 2003; Yuste et al., 1999).

A complementary method of assessing synaptic function is to measure properties of mPSCs. Miniature PSC amplitude measurements are often taken as quantal size estimates across the population of active synapses onto a neuron, as the mPSC (under voltage clamp) or mPSP (under voltage recording) likely correspond to the response to a spontaneous release of a single neurotransmitter vesicle (Brown et al., 1979; del Castillo and Katz, 1954; Fatt and Katz, 1952; Isaacson and Walmsley, 1995; Wall and Usowicz, 1998). Measurements of mPSC amplitudes are

routine in the literature. However, they are likely overestimates due to small amplitude events being

difficult to detect and largely being missed.

The use of voltage clamp can be a major reason why mPSCs "go missing". Theoretical studies (Major,

1993a; Rall and Segev, 1985; Spruston et al., 1993) predicted and experimental findings (Williams

and Mitchell, 2008) confirmed that voltage clamp fails to clamp extended dendrites, and to capture

the current flowing in at electrically remote synapses. Amplitude attenuation can also be caused if

series resistance is not compensated (Williams and Mitchell, 2008). These issues can be somewhat

sidestepped by switching to voltage recording.

However, most mPSCs go undetected because of the electrophysiology of the neuron itself. Distal

minis leak charge via the dendritic membrane, but an even more significant amplitude attenuation,

40-fold or more, is inflicted by charging the membrane capacitance of the entire dendritic arbour

(Larkum et al., 2009; Major et al., 2013a; Nevian et al., 2007; Stuart and Spruston, 1998; Williams

and Mitchell, 2008; Williams and Stuart, 2002). Such amplitudes, at the soma, are often

indistinguishable from noise fluctuations (approximately 97 μV on average in layer 5 neurons

(Nevian et al. 2007)). Recording from thin dendrites close to synaptic input sites is technically

challenging (Nevian et al. 2007). Therefore, a reliable yet widely accessible quantal analysis method,

based on somatic whole-cell patch recording, would require taking account of the background noise

component in addition to measuring putative mPSPs (or mPSCs).

Here we describe such a method based on separate recordings of excitatory mPSPs (mEPSPs) in the

presence of background physiological noise ('noise with minis' recording) and of noise alone after

blocking mEPSPs pharmacologically ('noise-alone' recording). To detect mEPSP-like events in these

recordings we used a newly developed algorithm called 'minis' which is described in our companion

article (Dervinis and Major, 2023). Because of larger minis overshadowing smaller potentials by

summating them on rise phases and reducing their amplitudes on decay phases of larger minis

(discussed in length in our companion article (Dervinis and Major, 2023)), events detected in the

'noise-alone' recording cannot be used to account for the noise component in the 'noise with minis'

recording. Instead, simulated minis must be used by superimposing them on the 'noise-alone'

recording until the 'noise with simulated minis' voltage trace closely matches the 'noise with real

minis' recording in terms of amplitude and rise time distributions of detected events. Therefore, we

augmented 'minis' software with a genetic optimisation algorithm (GA) that automatically adjusts

amplitude and rise times of simulated minis. The novel quantal analysis method produced an

unbiased quantal size estimate for excitatory synapses in the CNS which was approximately equal to

32 pC and was conserved across pyramidal cells of all sizes in cortical layers 2/3 and 5. 'Minis' thus

provides a straightforward quantal analysis method of detecting mPSPs and mPSCs in somatic

recordings and separating smaller of these events from background noise fluctuations.

Materials and Methods

Animals and electrophysiology

All experimental procedures were carried out in accordance with the UK Animals (Scientific

Procedures) Act 1986 at the Cardiff University under Home Office personal and project licenses. The

full description of electrophysiology procedures is provided in our companion article (Dervinis and

Major, 2023). Briefly, coronal somatosensory cortical slices obtained from 19- to 27-day old Wistar

rats (RRID:RGD_13508588; n = 11) of either sex were used to obtain whole-cell recordings (n = 14) of

mEPSPs in the background of physiological noise ('noise with minis' condition) by applying artificial

cerebrospinal fluid (aCSF) solution added with an action potential (AP) and inhibitory postsynaptic

potential (IPSP) blockers. Following this phase, the recordings were continued further after adding

excitatory postsynaptic potential (EPSP) blockers ('noise-alone' condition).

Passive membrane time constant, total capacitance, and cell's input resistance (the bridge balance

error) were estimated by injecting current pulses as described in (Major et al., 1993).

Experimental design

The goal of the study was to design a quantal analysis method based on somatic recordings of minis.

Due to low signal to noise ratio, simulations of minis were used to infer the signal component and to

eliminate the noise component in these recordings.

The experimental design of this study was similar to the one described in our companion article

(Dervinis and Major, 2023). As described in the previous section, whole-cell recordings were

obtained where first mEPSPs were recorded in the background of physiological noise followed by

blocking them pharmacologically to record 'pure' noise in the absence of minis. Simulated mEPSPs

(smEPSPs) were then added to the noise traces and the 'minis' algorithm was applied to this 'noise

with simulated minis' voltage trace. The resulting distribution of detected events in terms of their

amplitudes and 10-90% rise times was compared to the equivalent distribution based on 'noise with

real minis' recording. Discrepancy between the two distributions was used to inform the GA which

would then adjust the distribution of smEPSPs and generate new 'noise with simulated minis'

voltage traces and compare them again to the equivalent distribution based on 'noise with real

minis' recording. This procedure was repeated multiple times (in the order of tens to hundreds of

generations with 260 examples per generation) until the two distributions were closely matched,

within the bounds of chance statistical errors. At the end of this process the minis' distribution used

for simulating a closely matched recording was deemed to be the inference of the true minis'

distribution underlying the 'noise with real minis' recording.

Detection of miniature postsynaptic potentials

Detection of real and simulated mEPSPs was carried out using 'minis' software. The detailed

description of this detection algorithm is provided in our companion article (Dervinis and Major,

2023). We used the same detection algorithm parameters as described in that article except for the

amplitude range which was set to 0.02-10 mV.

Selection of recordings for fitting distributions of detected real minis-like events

Prior to carrying out any estimation of minis' distribution, segments of 'noise with real minis' and

'noise-alone' recordings were carefully selected. Segments containing unusual amount of noise or V_m

glitches were rejected. Parts of recording showing instability or drift of recording parameters were

also rejected to ensure that only good quality data was used. We called this a preprocessing stage

and data analyses we performed at this stage were inbuilt into 'minis' software.

As part of the preprocessing stage 'minis' produced 7 graphs showing the evolution of various

recording parameters across the entire duration of a single recording. An example is provided in

Figure 1 showing these graphs as individual panels of the figure for the longest obtained recording.

Figure 1A shows the evolution of V_m from the very beginning of the recording obtained in the regular

aCSF with APs present to the very end of the recording where APs and mIPSPs as well as mEPSPs

were blocked for some time ('noise-alone' recording phase). The data is shown, after removing V_m

segments containing responses to injected current pulses, with a total duration of 8520 s.

Throughout the entirety of this recording the baseline V_m varied between −70 and −67 mV and, thus

remained relatively stable.

There are three time markers that extend across all figure panels marking the time when the aSCF

containing TTX, gabazine, and CGP55845A was infused to block APs and IPSPs (the first marker), the

time when APs were observed to cease (the second marker), and the time when the aCSF containing

NBQX and CPP was infused to block remaining EPSPs (the third marker). The recording segment

between the second and the third markers constituted the 'noise with minis' recording, while the

segment following the third marker when mEPSPs were eventually blocked constituted the 'noise-

alone' recording. The shaded regions that also extend across all panels of Figure 1 mark files that

were selected for subsequent minis' distribution fitting analyses.

The remaining panels of Figure 1 were used to guide the data selection for subsequent analyses. The

standard deviation (SD) of the V_m (Figure 1B) was useful in determining the borders of different

recording types. Stable prolonged decreases in SD reliably indicated when APs or minis were

effectively blocked by corresponding pharmacological agents. Sudden brief increases in SD flagged

problematic recording segments containing higher levels of noise or V_m glitches. Gradual increases in

SD suggested the ensuing gradual deterioration of the recording quality.

Similar information was also provided by the evolution of amplitudes of the top 10% (amplitude-

wise) of all detected minis-like events in a single sweep (Figure 1C). Prolonged drop in the

amplitudes marked borders between recording types, while sudden jumps were indicative of V_m

instabilities. Finally, effective decay time constants of the same top 10% (by amplitude) of detected

events (Figure 1D) could be used as an indicator for the presence/absence of minis. Blocking minis

resulted in time constants becoming large and fluctuating unstably, indicating that only noise

fluctuations were being detected that did not possess typical decay dynamics common to PSPs.

Further insights into the recording quality over time were provided by impulse based measures.

Passive membrane time constant measurements over time (Figure 1E) were expected to remain

stable. Deviations from this expectation could signal a change in passive membrane properties and

the degradation in the recording quality. Total membrane capacitance (Figure 1F) was also expected

to be stable over time. Change in the capacitance could indicate tear of the membrane or loss of

part of the cell or some substantial uncontrolled destabilisation of the recording. Finally, change in

input resistance (detected from a change in the bridge balance error; Figure 1G) was not permitted

to exceed the estimate obtained at the beginning of the recording by more than twice. Violation of

this rule of thumb indicated a deterioration in the recording quality potentially resulting from debris

accumulating in the recording pipette, movement of the pipette tip or the recorded cell body, partial

formation of a membrane 'tube' (similar to what would happen in the process of producing an

outside-out patch by slowly retracting the pipette), or other reasons.

We obtained the above-discussed 7 longitudinal recording state/quality indicators for all our

recordings. Multipaneled graphs showing these indicators for each individual recording separately

are provided in Supplementary Figures 1-13.

Simulations

Simulating distributions of miniature excitatory postsynaptic potentials with a range of amplitudes

and rise times

All simulations were carried out using 'minis' software developed in Matlab (Mathworks;

RRID:SCR_001622) and performed on Cardiff School of Biosciences' Biocomputing Hub HPC/Cloud

infrastructure. Simulation of minis-like events was based on an analytical solution to the passive

cable equation for a transient current (Rall, 1977) using 100 lumped terms with a double exponential

synaptic current with τ_1= 0.15-3 ms (optimised) and τ_2 = 2 ms (Major et al., 1993). The detailed

description of how arbitrary shape PSPs were obtained is provided in our companion article (Dervinis

and Major, 2023).

A pool of simulated events was generated combining 4 bivariate (amplitude and 10-90% rise time)

normal distributions. 6 parameters described each distribution: amplitude mean μ_X and standard

deviation σ_X, 10-90% rise time mean μ_Y and standard deviation σ_Y, a correlation (or rotation) factor ρ,

and a scale factor n:

256
$$f(x,y) = \frac{n}{2\pi\sigma_X\sigma_Y\sqrt{1-\rho^2}} e^{-\frac{1}{2(1-\rho^2)}\left(\left(\frac{x-\mu_X}{\sigma_X}\right)^2 - 2\rho\left(\frac{x-\mu_X}{\sigma_X}\right)\left(\frac{y-\mu_Y}{\sigma_Y}\right) + \left(\frac{y-\mu_Y}{\sigma_Y}\right)^2\right)}.$$

All distribution parameters were controlled by the GA.

Fitting distributions of detected real minis-like events

Matlab's ga() function was used to control 24 parameters describing 4 bivariate normal distributions

(6 parameters per distribution). Additional controlled parameters were the synaptic rise time

constant τ_1 which ranged between 0.15 and 3 ms and the passive membrane time constant τ_m. The

range for the latter constant was taken to be between 0.95 times and 1.05 times the initial estimate

based on the average waveform of all minis-like events detected in the 'noise with real minis'

recording. Thus, there were 26 parameters in total controlled by the GA.

The GA would start by generating multiple distributions of smEPSPs (i.e., 'individuals'; we used 260

individuals per 'generation'). Events would be drawn pseudo-randomly from a distribution and then

simulated events of the right shape (in terms of amplitude and 10-90% rise time) would be

superimposed on the 'noise-alone' recording at time points that were chosen pseudo-randomly

(Figure 2). For generating the initial set of individuals ('population'), the GA chose parameters

pseudo-randomly within prescribed ranges. For each of the four bivariate normal distributions the

parameter ranges were as follows: μ_X (-0.1-1 mV), σ_X (0.01-1 mV), μ_Y (-1-10 ms), σ_Y (0.25-10 ms), ρ (-1

to 1), and n (0-10000 for the first distribution and −10000 to 10000 for the remaining three

distributions). Any negative count bins within the resulting final distribution were zeroed out. Any

events with amplitudes below the simulation threshold (varying positive value) or negative rise times

were excluded.

In the next step the GA assessed the fitness of each individual in the generation by using the cost

function (explained in the next subsection). The top 5% of the most fit individuals survived to the

next generation without change while individual crossover, genetic migration, and other GA

parameters were set to default values of the Matlab's ga() function except for the mutation function

type which was set to 'mutationadaptfeasible'. A new evolved generation of individuals was then

created. Which then served as the basis for yet another generation. This process was repeated until

an individual with the lowest cost (highest fitness value) possible was created, there was no

improvement in the fitness for 100 consecutive generations, or the number of generations reached

1000.

In the case when the GA terminated without attaining the highest possible fitness value, distribution

fitting procedure was reinitiated using the most fit individual as a seed. The population genetic

diversity was reset by setting the GA-controlled parameter ranges to ±5% of the original ranges

relative to the seed parameters. The rerunning of distribution fitting was repeated until the GA

generated the most fit individual possible, an acceptable level of fitness was reached (defined in the

next subsection), or there was no improvement in fitness compared to the previous run for three

consecutive repeats. In the latter case, the entire distribution fitting procedure could be repeated

starting with a high simulated amplitude lower threshold (e.g., 200 μV) with the threshold being

gradually lowered until a 'good enough' fit was attained. This 'backwards' fitting procedure was

required for several recordings due to them having large mean amplitude and, therefore, failing to

converge on an acceptable solution with a realistic minis source distribution using a low simulated

amplitude lower threshold.

If the most fit individual was within acceptable levels of fitness values, the lower threshold on

smEPSP amplitude was increased by 0.005 mV (or lowered in certain cases) and the entire fitting

procedure rerun from the beginning till the end. This procedure was repeated until the GA stopped

converging on a solution with acceptable fitness values. The reason for attempting to push up the

lower limit of the amplitudes of the smEPSPs is that GA-generated solutions are not unique.

Matching 'noise with real minis' recording can generally be achieved by using a distribution of fewer

relatively large amplitude smEPSPs or more numerous smaller amplitude smEPSPs, or some

distribution between these extremes. There is an infinite number of such distributions with ever

decreasing amplitudes of smEPSPs (in theory, all the way down to events resulting from arbitrarily

brief single AMPAR or NMDAR channel sub-conductance state openings injecting arbitrarily small

amounts of charge). Therefore, the GA with the thresholding procedure described above has no

guaranteed way of arriving at the proven true distribution of minis, only at a distribution giving an

approximate *upper limit* on the *mean* (or median) mini amplitude (the upper amplitude tail of the fit

would be more reliable though, just as with detecting those events manually).

Cost function

The goal of the minis' distribution fitting procedure was to match 'noise with simulated minis' and

'noise with real minis' recordings as close as possible in terms of the distribution of amplitudes and

10-90% rise times of detected minis-like events in the two types of V_m recording traces ('simulated'

vs. 'real' distributions), in the process 'cancelling out' any systematic errors in amplitudes or shapes

introduced by the detection algorithm or the superposition of events. This was achieved by

minimising the cost function using the GA. The cost function was composed of four types of

components: shape constraints on the simulated minis distribution, sums of absolute deviations

(SADs) between 'simulated' and 'real' distributions, sums of signed deviations (SSDs) between

'simulated' and 'real' distributions, and maximal absolute deviations (MADs) between 'simulated'

and 'real' distributions. We avoided using the sum of squared errors (SSE) because it is sensitive to

outliers.

We calculated the typical ranges of SADs and MADs for each of the 14 recordings by taking the

individual 'noise with real minis' recording and dividing it into smaller files (range was 15-606 files)

the size of the single recording sweep (a typical sweep lasted 20 s). Each file in this set was subjected

to minis detection procedure resulting in a set of 'real' distributions. They were then subtracted

from each other, and corresponding SAD (sum of absolute deviations) and MAD (maximum absolute

deviation) scores were calculated for each of the possible n*(n-1)/2 file pairings (range 105 to

183315, corresponding to 15 to 606 available files). 6 different SAD- and MAD-based scores (12

altogether) were calculated based on: distributions of (1) amplitudes of *all* detected events, (2)

amplitudes of top 50% largest detected events, (3) amplitudes of top 10% largest detected events,

(4) amplitudes of top 2% largest detected events, (5) distribution of all 10-90% rise times, and (6) a

joint amplitude and 10-90% rise time distribution. Moreover, 3 different SSD-based scores were

calculated based on: (1) amplitudes of top 50% largest detected events, (2) amplitudes of top 10%

largest detected events, and (3) amplitudes of top 2% largest detected events. These latter scores

constrained high-amplitude tails of 'simulated' distributions to have sufficient counts to avoid

negative distribution deviations in the tails. Similarly to the lower simulated amplitude limit, these

three scores served to constrain the non-uniqueness of simulated minis distributions caused by the

lower amplitude end of the distribution.

The smallest percentile that guaranteed to include half of all file combinations with all their 15

respective SAD,MAD, and SSD score values falling below this percentile threshold simultaneously

('15-score combined 50th centile'; Tables 1 and 2) was used to determine which SAD or MAD cutoff

values (*all* SAD and MAD scores for 'noise with simulated minis' traces had to fall below these

values) should be used for all 15 types of scores to construct the cost function (SSD scores had to be

simply positive; Figure 3). As described above, the centile value was estimated based on single

sweep files. The same centile value was then used to work out SAD and MAD scores for larger size

files (typically the size of 5 recording sweeps to match the size of the 'noise-alone' recording file)

that were used during the GA-controlled fitting procedure.

The cost function was constructed of 6 types of SAD scores and 6 types of MAD scores estimated

using the '15-score combined 50th centile' procedure and 3 types of positive SSD scores. These 15

scores were used to evaluate how close the 'simulated' distribution was to the single selected 'real'

distribution that was deemed to be of the best quality by a human observer. Typically, it was a file

close to the end of the 'noise with minis' recording epoch, therefore, being the most similar file, in

terms of recording quality parameters, to the 'noise-alone' recording epoch (which was generally the

first good-quality epoch after pharmacological blockade of neurotransmission was deemed

complete). Additional corresponding 15 'deviation' scores (same as SADs, MADs, and SSDs but

comparing to all available data distributions at once) were calculated assessing how much each 'real'

or 'simulated' distribution deviated from the full set consisting of all 'real' distributions and the

single 'simulated' distribution. To be designated a good enough fit, the 'simulated' distribution was

expected to have lower deviation scores than the worst performing 'real' distribution (so the

simulated distribution's histograms would not be picked as the 'worst outlier' by a double-blind

observer). 'Simulated' distributions were further penalised if their underlying 'simulated minis'

distribution violated the 10-90% rise time skewness constraint which stipulated that the mean 10-

90% rise time of simulated minis should exceed the median at least by a half of the standard

deviation. Finally, 'simulated' distributions were also penalised if their underlying 'simulated minis'

amplitude distribution had a sharp cliff at its lower end. Hence, there were 32 fitness components in

total (15 + 15 + 1 + 1 = 32).

If all amplitude SAD, MAD, SSD, and deviation scores for comparing the 'simulated' distribution to

the 'real' distribution were satisfied (≤ 15-score 50th centile SAD and MAD values and ≥ 0 SSD values)

at the end of the fitting procedure, the fit was deemed to be 'good enough'. Alternatively, the fit

could also be deemed good enough if all amplitude and 10-90% rise time 'file population' deviation

scores (all 15) were satisfied (excluding SAD, MAD, and SSD scores).

Final distribution fit acceptance

The notion of a 'good enough' fit is somewhat arbitrary. Once the fitting procedure was completed,

we set out to test whether the final fit was acceptable using statistical tests. We divided 'noise with

real minis' recordings into smaller files of the same length as the 'noise-alone' recording and

constructed a set of 'real' distributions by running 'minis' detection algorithm on these files. We

then compared these individual 'real' distributions to each other by subtracting their amplitude and

10-90% rise time distributions from each other, taking absolute value of the difference, and

summing over all bins. Finally, we selected the worst and the best performing 'real' distributions in

terms of their sums of absolute distribution bin deviations (SADs).

We also compared the 'good enough' 'noise with simulated minis' distribution to the set of

normalised 'real' distributions. The comparison yielded another set of sums of normalised absolute

distribution bin deviations (SADs). The mean of this set was then compared to the means of the

worst and best performing 'real' sets using Wilcoxon-Mann-Whitney test. If the 'simulated' set mean

was significantly larger than the worst 'real' set mean, the 'simulated' distribution was deemed to be

an underfit and, therefore, rejected and the fitting procedure was continued. In contrast, if the

'simulated' set mean was significantly smaller than the best 'real' set mean, the 'simulated'

distribution was deemed to be a likely overfit. The 'good enough' fit was accepted if the 'simulated'

set mean was not significantly larger than the worst 'real' set mean.

Statistical analyses

Parametric inferential statistics tests were used for minis' incidence rates, mean amplitudes, and

cell's total capacitance as quartile-quartile plots indicated that these measures were normally

distributed. Sums of absolute distribution bin deviations (SADs) were often not normally distributed

and, therefore, were tested using a nonparametric Wilcoxon-Mann-Whitney test.

Data accessibility

All data analysed in this study are publicly available (GIN DOI will appear in version 2 of the

manuscript). The available data include 'noise with minis' and 'noise-alone' whole-cell patch

membrane potential recordings that were used in computer simulations and minis' distribution

fitting. All electrophysiological recordings were stored in Axon Binary File (ABF) format.

Code accessibility

All analyses were carried out in Matlab and the analysis code is publicly available on GitHub (DOI will

appear in version 2 of the manuscript). The code is complete with instructions on how to reproduce

all figures reported in this study.

Software accessibility

The present study reported the use of a novel quantal analysis method that is part of 'minis'

software available on GitHub (Dervinis, 2022).

Results

Estimating quantal size by direct subtraction of noise component

We have analysed 'noise with minis' recordings and 'noise-alone' recordings with the 'minis'

detection algorithm. Detected mEPSP-like events had a particular shape amplitude and 10-90% rise

time distributions that resembled log-normal or gamma distributions (Figure 4), left skewed with a

long tail on the right. In the amplitude domain the lower end of the distribution contains a mixture

of real minis and noise fluctuations that were misidentified as real events (but missing small minis

due to them being cancelled out by noise, summating with larger minis, or failing to be detected due

to being on a decay phase of a big preceding mini – the 'overshadowing' effect).

We (naively) argued that if the noise component could be reliably estimated based on the 'noise-

alone' recording where synaptic activity has been pharmacologically blocked, it could be directly

subtracted from the 'noise with minis' distribution yielding an estimate of the pure minis'

component. Figure 4A shows both 'noise with minis' and 'noise-alone' detected event amplitude

distributions superimposed over each other. After subtracting the 'noise-alone' distribution from the

'noise with minis' distribution there appear negative low amplitude bins in the resulting distribution

(indicated by an arrowhead in Figure 4A). These missing low amplitude events are caused by a

greater number of small false positive mini-like detections in the noise-alone traces, and larger minis

overshadowing smaller minis and small amplitude noise fluctuations in the 'noise with minis'

recording (we have discussed this phenomenon in great length in our companion article (Dervinis

and Major, 2023)). Therefore, the direct subtraction approach can only provide a relatively crude

'first order' high-end upper limit on the mean of the minis' amplitude distribution.

Nevertheless, this over-estimate is more reliable than a highly subjective approach of simply

estimating the mean amplitude based on events detected using a high amplitude threshold.

Estimating quantal size by simulating excitatory postsynaptic potential source distribution

An alternative and more reliable way of estimating the quantal size in our recordings is to estimate

the minis component directly using simulations. This relies on 'minis' optimisation algorithm (GA)

being able to closely match a 'noise with simulated minis' voltage trace (Figure 2) with 'noise with

real minis' recordings in terms of amplitude and 10-90% rise time distributions of minis-like events

detected within these traces. We were able to successfully do that for all our recordings (see Figure

5 and Supplementary Figures 14-26) with one particular example shown in Figure 5. In terms of the

example shown in Figure 5, the overall amplitude SAD of the 'simulated' distribution was not

underperforming the worst-performing 'real' distribution (unidirectional 'simulated' SAD > worst-

performing 'real' SAD Wilcoxon-Mann-Whitney rank sum 'underfit' test U = 406, p = 3.4×10^{-9};

downward arrow indicates 'simulated' SAD < 'real' SAD relationship in Figure 5) and was not

outperforming the best 'real' distribution (unidirectional 'simulated' SAD < best-performing 'real'

SAD Wilcoxon-Mann-Whitney rank sum 'overfit' test U = 288, p = 0.72). Similarly, the 'simulated' 10-

90% rise time distribution was also neither an underfit (unidirectional 'simulated' SAD > worst-

performing 'real' SAD 'underfit' test U = 279, p = 0.41; upward arrow indicates 'simulated' SAD >

'real' SAD relationship in Figure 5) nor an overfit (unidirectional 'simulated' SAD < best-performing

'real' SAD 'overfit' test U = 275, p = 0.55).

All simulations produced 'good enough' matches showing amplitude and 10-90% rise time

distributions of detected minis-like events being within the range of (and thus indistinguishable

from) amplitude and 10-90% rise time count values measured in sets of 'real event' distributions

(Supplementary Figures 14-26). None of the fits were performing worse than the worst-performing

'real' distribution qualifying them as 'good enough' fits. All resulting minis source distributions are

displayed in Figure 6 and Supplementary Figures 27-39. An example in Figure 6 shows that the 'real'

minis' source distribution likely has a log-normal or gamma-like shape in both amplitude and rise

time domains.

Incidence rates (frequencies of minis per second) estimated based on simulated minis source

distributions ranged roughly between 10 and 100 minis/s (Figure 7). This estimate is an order of

magnitude higher than the one based on the literature and significantly higher than the one based

on the direct subtraction method (t(13) = 3.37, p = 0.005) and also higher than the estimate based

on amplitudes higher than a chosen 0.8 mV threshold (unrealistically high threshold; t(13) = 3.76, p =

0.002). It is precisely within the range predicted in our companion article (Dervinis and Major, 2023).

However, this range is possibly still somewhat of an underestimate as minis source distributions

were often generated using a lower limit on simulated amplitudes to constrain the distribution non-

uniqueness as discussed in the Methods subsection on the distribution fitting.

Mean amplitudes of minis derived using simulations ranged between 53 and 198.4 µV (overall mean

of 115.3 ± 5.7 µV, layer 2/3 mean of 137.3 ± 11.1 µV, and layer 5 mean of 93.4 ± 9.4 µV; Figure 8A).

When compared to capacitance estimates (or 1/capacitance), there was a strong inverse correlation

between the mean amplitude and cell's capacitance (which is proportional to the cell's size; r =

0.966, p = 2.1×10^{-8}, R^2 = 0.933, assuming capacitance per unit area is more or less a biological

constant for each cell class/type of membrane/density of channels with charged gates moving within

the membrane - increasing capacitance (Gentet et al., 2000)). That is, the larger the cell, the smaller

the amplitude of its somatically detected minis and vice-versa. This relationship is predicted by the

theory of capacitors (C = Q/V, where C stands for capacitance, Q stands for charge, and V stands for

voltage across the cell's membrane), and it is a direct demonstration of an attenuating effect of cell's

capacitance on the amplitude of somatically detected minis. If a direct line was drawn through the

data and the origin of the axes in Figure 8A, the slope of this line would provide a quantal size

estimate for excitatory synapses in the CNS in terms of 'injected' charge (Q = ΔV/ Δ(1/C)) which is

approximately equal to 32 fC in this case. The fact that the least square fitted line to the data alone

coincided with the line fitted to the data that also passed the origin and, therefore, had no intercept

term indicated that no active mechanism was in place to compensate for the attenuation of the

average minis' amplitude due to the size of the cell.

Another notable observation was that the mean amplitude estimates derived either by noise

subtraction or by minis source distribution simulation were correlated (r = 0.705, p = 0.005, R^2 =

0.498 Figure 8B). The equation of the line (1.18x – 39.3) fitted to this data provided a way to

approximate the mean amplitude of fitted minis' source distribution by subtracting the intercept

term (39 µV) from the means derived by 'naïve' noise subtraction.

Generic miniature excitatory postsynaptic potential distribution in neocortex

To construct a generic mEPSP distribution, we normalised amplitudes of simulated minis' source

distributions shown in Figure 6 and Supplementary Figures 27-39 by dividing them by their

respective means, taking the total average, smoothing the resulting distribution, and then scaling

the amplitudes to the overall mean (115.3 ± 5.7 μV). The resulting combined (amplitude and 10-90%

rise time) distribution is shown in Figures 9A and B. The corresponding marginal amplitude and 10-

90% rise time distributions are shown in Figures 9C and D, respectively. Both marginal distributions

have left-skewed log-normal-like or gamma-like distributions. This may be useful in neural network

simulations, or to potentially speed up (and constrain) fitting of simulated minis on noise to real

minis with noise, using the GA (e.g., limit the source distribution to one 2-D 'rotated' log-normal or

gamma distribution).

523   Discussion

In this article we reported two major scientific advances. First, we described a novel quantal analysis

method that is based on sequential somatic recording, from a given neuron, of a) mEPSPs (after

blockade of action potential-mediated neurotransmission, and all inhibitory neurotransmission,

including miniature IPSPs) on a background of other physiological noise, and b) recordings of noise

alone, after subsequent additional pharmacological blockade of mEPSPs (all glutamatergic ionotropic

excitatory neurotransmission). The latter type of recording provides a means to estimate the

properties of the noise component which can then be used to take into account noise fluctuations in

the combined minis and noise recording. However, this was done not by a direct subtraction of the

histogram of amplitudes (and rise times) detected from the noise component, but rather by the

simulation of the underlying minis component and repeatedly superimposing the waveforms of

simulated minis onto the noise trace until the histograms detected from the 'noise with simulated

minis' voltage trace closely matched those detected from the 'noise with real minis' recording. The

key tool to achieving this match was the genetic algorithm that optimised the parameters of the 2-

dimensional simulated minis distribution in terms of amplitudes and 10-90% rise times,

simultaneously, to best fit the experimental data distributions.

The second major advance was the use case for the novel quantal analysis method that successfully

measured the mean 'electric charge injected' size of excitatory synapses of cortical pyramidal cells

which was shown to be approximately 32 fC, across the entire sample of neocortical pyramidal

neurons recorded. This number was inferred from the slope of the line fitting minis' mean amplitude

and cell's total capacitance data in accordance with the theory of capacitors. The fact that this line

had an intercept at the origin of the axes indicated that there was no biological compensation (other

than *number* of synapses) for the amplitude attenuation of minis due to cell size (i.e., total

capacitance). Indeed, cell capacitance played a major role affecting the *voltage* amplitude of mEPSPs

resulting in a large proportion of mEPSPs being otherwise indistinguishable from noise (as

independently found in numerous other studies, e.g., (Major et al., 2013b; Nevian et al., 2007),

summarised in (Major et al., 2013b)). The number of these 'missed' minis was so high that the

estimated minis' incidence rate (frequency) was in the order of 10-100 minis/s: an order of

magnitude higher than typically reported in the synaptic physiology literature (with the notable

exception of (Nevian et al., 2007), which predicted this result, by simultaneous dual somatic and

basal dendritic whole-cell patch recordings of mEPSPs, with dendritic detection, and simultaneous

somatic measurement). Finally, both the amplitude and 10-90% rise time distributions of minis had a

log-normal- or gamma-like shape.

These findings have a few major implications. First, the method, as used for estimating the mEPSPs'

distributions in cortical layers 2/3 and 5 of cells of various size and then using these distributions to

arrive at the electrical size of excitatory synapses serves as a proof of principle that it can be

successfully used to estimate PSP distributions of various types in the CNS. The next logical step of

this method is to extend its application to the estimation of amplitude and rise time distributions of

mIPSPs generated by different types of inhibitory synapses and, as a result, the electrical sizes of

these different inhibitory synapses. Moreover, the ability to get relatively accurate quantal size

estimates unobscured by physiological noise is important for constraining synaptic parameters in

physiologically realistic simulations of neural activity. For example, now we should be able to

estimate how many active synapses are needed to generate an NMDA spike within a single dendritic

segment (Major et al., 2013b). The importance of these number estimates is not restricted to the

domain of physiologically realistic simulations but also extends to more abstract computations that

use NMDA spike-like mechanisms as coincidence detectors in the latest cortically inspired models of

artificial intelligence (Hawkins et al., 2019). It is thus imperative to arrive at accurate estimates of

synaptic transmission parameters.

These findings also draw attention to methodological issues in the field of synaptic physiology. As

discussed in our companion article (Dervinis and Major, 2023), the commonly reported incidence

rates for mEPSCs are well below 10 minis/s. Even if one is in doubt of the incidence rates that we

arrived with the help of simulations that lie in the range of 10-100 minis/s, the range of incidence

rates given by direct subtraction of the distribution of events detected in the 'noise-alone' recording

from the distribution based on the 'noise with minis' recording is still within 5.9 and 26.7 minis/s

which we know to be an underestimate. Therefore, reported minis' incidence rates below 10 minis/s

are certainly underestimates. This may have multiple causes, including lower slice temperatures in

the majority of studies (we used physiological, ca. 37 degC), and a significant temperature

dependence of synaptic release, as well as differences in slice health and slicing angle (which can

affect branch 'amputations'). Another big cause would be the use of voltage clamp, especially if the

series resistance in not compensated fully, as this low-pass filters traces and obscures smaller minis.

(e.g. trace in Supplemental?) As discussed earlier, these estimates could be improved by switching to

voltage recording instead of using the voltage clamp (Major, 1993a; Rall and Segev, 1985; Spruston

et al., 1993; Williams and Mitchell, 2008) but at the price of somewhat slower decay times of minis

(Major 1993), thus more temporal overlap and consequent difficulties detecting peaks. But more

importantly, a strong association between cell capacitance (i.e. surface area) and how much

somatically recorded minis' amplitudes are attenuated indicates that special care must be taken to

account for the effect of background noise fluctuations on the amplitude measurements as we have

done here. This association is yet another evidence supporting experimental observations of massive

mini amplitude attenuation as the PSP spreads from its dendritic source location to the soma

(Larkum et al., 2009; Major et al., 2013a; Nevian et al., 2007; Stuart and Spruston, 1998; Williams

and Mitchell, 2008; Williams and Stuart, 2002)., especially in cells with large dendritic arbours, hence

large surface areas and overall membrane capacitance. Dendritic spines and post-synaptic densities

(the specialised regions opposite release sites, containing tethered synaptic receptors) are not

grossly different between different classes of pyramidal neurons in the neocortex, although

significant differences exist between cortical layers, cortical areas, and animal species (Yuste, 2010).

It is also important to note that understanding the link between cell capacitance and somatically

recorded average mini amplitudes as well as knowing actual shapes of mini distributions in terms of

their amplitudes and rise times allows us to generate artificial data where ground truth is known.

Such labelled data could be used to train artificial neural networks (ANNs) which could then be used

develop next generation powerful quantal analysis methods allowing detection of minis directly in

mixed 'noise with minis' recordings. Perhaps such methods would not only do away with the need to

obtain relatively long voltage recordings with consecutive pharmacological phases but could

potentially fully automate the mini detection process. We are not the first to suggest the application

of ANNs to this issue (see (Pircher et al., 2022) and (Wang et al., 2024)). However, we are not aware

of attempts to use realistic mini distributions for this purpose.

Even though the novel quantal analysis method we present here is an important advance, it

nevertheless has limitations. One of them is the need for long duration recordings using different

pharmacological agents at various stages of recording. However, the somatic recording set up is not

as complicated and high-skill as an alternative multisite 2-photon targeted dendritic recording set up

would be ((Nevian et al., 2007), a heroic technique which has never been copied in another lab).

Experiments themselves could be further streamlined, as we did in some cases, by pre-blocking

action potentials before obtaining the whole-cell recordings. This is particularly useful for smaller

cells which are more prone to osmotic overloading or shrinkage and resulting recording instability

after a few tens of minutes (the pipette solution cannot exactly reproduce the cytoplasm, as it has

no proteins or macromolecules in it). Moreover, the distribution fitting procedure involving the GA

can be lengthy and computationally intensive. However, 'minis' software is parallelised at the PSP

detection level, as well as at the GA optimisation level making it particularly suitable to be executed

on multi-core computing clusters. Although 'minis' software combined with the two-stage recording

set up offers an unprecedented control for the background physiological noise, provided recording

stability is very good throughout, we understand that many researchers may not be persuaded to

adopt it themselves. The possibility of misleading fits if the recording noise became substantially

worse between 'noise with minis' and 'noise-alone' recording phases needs to be vigilantly excluded.

Therefore, the adoption of ANNs for the next generation of 'minis' software based on current

findings and future use-cases offers a way to simplify the current approach (including recording

stability quality control).

Some researchers may be critical of a method that does not rely on a direct measurement of minis

but rather on an approximation via indirect means using simulations. This is a valid criticism that

could be addressed in the future by using a method of repeatedly subjecting a voltage recording to

the minis detection procedure with an increasingly lower threshold while subtracting detected

events from the voltage recording. This approach potentially could recover most of the smaller minis

that are overshadowed by the larger ones (the so called 'negative bins' problem illustrated in Figure

4A), providing the waveforms were reasonably stereotyped in shape (not the case under voltage

clamp, (Major, 1993b)). Furthermore, other researchers may question the ability to

pharmacologically isolate the background physiological noise. Our 'noise with minis' recordings may

contain random openings of individual AMPA receptor (AMPAR) or NMDA receptor (NMDAR)

channels (possibly extra-synaptic) and our 'noise-alone' recordings may fail to fully eliminate channel

openings in the presence of quantal release of neurotransmitter (although we used high doses, well

above IC50s' (Lehmann et al., 1987; Randle et al., 1992) and rapid slice perfusion, to achieve quick

wash-in times). Background/physiological/electrical noise itself may be drifting between the two

conditions with the presence or absence of mEPSP pharmacological blockers. Although there may be

some reason to suspect that may be the case, occasionally, we rejected any recordings with such

instabilities. these factors are unlikely to have affected the results significantly due to small

amplitude nature of these membrane potential variations.

Despite some of the limitations discussed above, the method and its use case presented in this

article provide a major breakthrough in the field of synaptic physiology. Further research would

inevitably see the improvement of this method by developing the underlying algorithm in a few

promising directions with the application of ANNs being one of them. This should allow the

simplification of the minis recording procedure by eliminating the need for 'noise-alone' recording

epochs. Finally, the application of this novel quantal analysis method to describe the properties of

various types of inhibitory synapses in the neocortex would the next logical step leading to yet

another breakthrough.

References

Bekkers JM. 1994. Quantal analysis of synaptic transmission in the central nervous system. *Curr Opin Neurobiol* **4**:360–365. doi:https://doi.org/10.1016/0959-4388(94)90097-3

Biró ÁA, Holderith NB, Nusser Z. 2005. Quantal Size Is Independent of the Release Probability at Hippocampal Excitatory Synapses. *The Journal of Neuroscience* **25**:223–232. doi:10.1523/JNEUROSCI.3688-04.2005

Brown TH, Wong RKS, Prince DA. 1979. Spontaneous miniature synaptic potentials in hippocampal neurons. *Brain Res* **177**:194–199. doi:https://doi.org/10.1016/0006-8993(79)90931-4

Clamann HP, Rioult-Pedotti MS, Luscher HR. 1991. The influence of noise on quantal EPSP size obtained by deconvolution in spinal motoneurons in the cat. *J Neurophysiol* **65**:67–75. doi:10.1152/jn.1991.65.1.67

Clements JD. 2003. Variance–mean analysis: a simple and reliable approach for investigating synaptic transmission and modulation. *J Neurosci Methods* **130**:115–125. doi:https://doi.org/10.1016/j.jneumeth.2003.09.019

Clements JD, Silver RA. 2000. Unveiling synaptic plasticity: a new graphical and analytical approach. *Trends Neurosci* **23**:105–113. doi:10.1016/S0166-2236(99)01520-9

del Castillo J, Katz B. 1954. Quantal components of the end-plate potential. *J Physiol* **124**:560–573. doi:https://doi.org/10.1113/jphysiol.1954.sp005129

Dervinis M, Major G. 2023. A novel method for reliably measuring miniature and spontaneous postsynaptic potentials/currents in whole-cell patch clamp recordings in the central nervous system. *bioRxiv*. doi:10.1101/2022.03.20.485046

Edwards FR, Redman SJ, Walmsley B. 1976. Statistical fluctuations in charge transfer at Ia synapses on spinal motoneurones. *J Physiol* **259**:665–688. doi:https://doi.org/10.1113/jphysiol.1976.sp011488

Enoki R, Hu Y, Hamilton D, Fine A. 2009. Expression of Long-Term Plasticity at Individual Synapses in Hippocampus Is Graded, Bidirectional, and Mainly Presynaptic: Optical Quantal Analysis. *Neuron* **62**:242–253. doi:10.1016/j.neuron.2009.02.026

Fatt P, Katz B. 1952. Spontaneous subthreshold activity at motor nerve endings. *J Physiol* **117**:109–128.

Forti L, Bossi M, Bergamaschi A, Villa A, Malgaroli A. 1997. Loose-patch recordings of single quanta at individual hippocampal synapses. *Nature* **388**:874–878. doi:10.1038/42251

Gentet LJ, Stuart GJ, Clements JD. 2000. Direct Measurement of Specific Membrane Capacitance in Neurons. *Biophys J* **79**:314–320. doi:https://doi.org/10.1016/S0006-3495(00)76293-X

Hardingham NR, Read JCA, Trevelyan AJ, Nelson JC, Jack JJB, Bannister NJ. 2010. Quantal Analysis Reveals a Functional Correlation between Presynaptic and Postsynaptic Efficacy in Excitatory Connections from Rat Neocortex. *The Journal of Neuroscience* **30**:1441–1451. doi:10.1523/JNEUROSCI.3244-09.2010

Hawkins J, Lewis M, Klukas M, Purdy S, Ahmad S. 2019. A Framework for Intelligence and Cortical
Function Based on Grid Cells in the Neocortex. *Front Neural Circuits* **12**.
doi:10.3389/fncir.2018.00121

Heuser JE, Reese TS, Dennis MJ, Jan Y, Jan L, Evans L. 1979. Synaptic vesicle exocytosis captured by
quick freezing and correlated with quantal transmitter release. *Journal of Cell Biology* **81**:275–
300. doi:10.1083/jcb.81.2.275

Isaacson JS, Walmsley B. 1995. Counting quanta: Direct measurements of transmitter release at a
central synapse. *Neuron* **15**:875–884. doi:10.1016/0896-6273(95)90178-7

Jack JJ, Redman SJ, Wong K. 1981. The components of synaptic potentials evoked in cat spinal
motoneurones by impulses in single group Ia afferents. *J Physiol* **321**:65–96.
doi:https://doi.org/10.1113/jphysiol.1981.sp013972

Jonas P, Major G, Sakmann B. 1993. Quantal components of unitary EPSCs at the mossy fibre
synapse on CA3 pyramidal cells of rat hippocampus. *J Physiol* **472**:615–663.
doi:https://doi.org/10.1113/jphysiol.1993.sp019965

Katz B. 1969. The Release of Neural Transmitter Substances. Liverpool: Liverpool Univ. Press.

Korn H, Faber DS. 1991. Quantal analysis and synaptic efficacy in the CNS. *Trends Neurosci* **14**:439–
445. doi:https://doi.org/10.1016/0166-2236(91)90042-S

Kraszewski K, Grantyn R. 1992. Unitary, quantal and miniature gaba-activated synaptic chloride
currents in cultured neurons from the rat superior colliculus. *Neuroscience* **47**:555–570.
doi:https://doi.org/10.1016/0306-4522(92)90165-X

Kullmann DM, Nicoll RA. 1992. Long-term potentiation is associated with increases in quantal
content and quantal amplitude. *Nature* **357**:240–244. doi:10.1038/357240a0

Kuno M. 1964. Quantal components of excitatory synaptic potentials in spinal motoneurones. *J
Physiol* **175**:81–99. doi:https://doi.org/10.1113/jphysiol.1964.sp007504

Larkman A, Stratford K, Jack J. 1991. Quantal analysis of excitatory synaptic action and depression in
hippocampal slices. *Nature* **350**:344–347. doi:10.1038/350344a0

Larkum ME, Nevian T, Sandler M, Polsky A, Schiller J. 2009. Synaptic Integration in Tuft Dendrites of
Layer 5 Pyramidal Neurons: A New Unifying Principle. *Science (1979)* **325**:756–760.
doi:10.1126/science.1171958

Lehmann J, Schneider J, McPherson S, Murphy DE, Bernard P, Tsai C, Bennett DA, Pastor G, Steel DJ,
Boehm C. 1987. CPP, a selective N-methyl-D-aspartate (NMDA)-type receptor antagonist:
characterization in vitro and in vivo. *Journal of Pharmacology and Experimental Therapeutics*
240:737–746.

Liu Z, Lu X, Villette V, Gou Y, Colbert KL, Lai S, Guan S, Land MA, Lee J, Assefa T, Zollinger DR,
Korympidou MM, Vlasits AL, Pang MM, Su S, Cai C, Froudarakis E, Zhou N, Patel SS, Smith CL,
Ayon A, Bizouard P, Bradley J, Franke K, Clandinin TR, Giovannucci A, Tolias AS, Reimer J,
Dieudonné S, St-Pierre F. 2022. Sustained deep-tissue voltage recording using a fast indicator
evolved for two-photon microscopy. *Cell* **185**:3408-3425.e29. doi:10.1016/J.CELL.2022.07.013

Major G. 1993a. Solutions for transients in arbitrarily branching cables: III. Voltage clamp problems.
Biophys J **65**:469–491. doi:10.1016/S0006-3495(93)81039-7

Major G. 1993b. Solutions for transients in arbitrarily branching cables: III. Voltage clamp problems.
Biophys J **65**:469–491. doi:10.1016/S0006-3495(93)81039-7

Major G, Evans JD, Jack JJ. 1993. Solutions for transients in arbitrarily branching cables: I. Voltage
recording with a somatic shunt. *Biophys J* **65**:423–449. doi:10.1016/S0006-3495(93)81037-3

Major G, Larkum ME, Schiller J. 2013a. Active Properties of Neocortical Pyramidal Neuron Dendrites.
Annu Rev Neurosci **36**:1–24. doi:10.1146/annurev-neuro-062111-150343

Major G, Larkum ME, Schiller J. 2013b. Active Properties of Neocortical Pyramidal Neuron Dendrites.
Annu Rev Neurosci **36**:1–24. doi:10.1146/annurev-neuro-062111-150343

Nevian T, Larkum ME, Polsky A, Schiller J. 2007. Properties of basal dendrites of layer 5 pyramidal
neurons: a direct patch-clamp recording study. *Nat Neurosci* **10**:206–214. doi:10.1038/nn1826

Oertner TG, Sabatini BL, Nimchinsky EA, Svoboda K. 2002. Facilitation at single synapses probed with
optical quantal analysis. *Nat Neurosci* **5**:657–664. doi:10.1038/nn867

Peled ES, Isacoff EY. 2011. Optical quantal analysis of synaptic transmission in wild-type and rab3-
mutant Drosophila motor axons. *Nat Neurosci* **14**:519–526. doi:10.1038/nn.2767

Pircher T, Pircher B, Feigenspan A. 2022. A novel machine learning-based approach for the detection
and analysis of spontaneous synaptic currents. *PLoS One* **17**:1–16.
doi:10.1371/journal.pone.0273501

Rall W. 1977. Core Conductor Theory and Cable Properties of Neurons In: Kandel ER, Brookhardt JM,
Mountcastle VM, editors. Handbook of Physiology, Cellular Biology of Neurons. Bethesda, MD:
American Physiological Society. pp. 39–97.

Rall W, Segev I. 1985. Space-clamp problems when voltage clamping branched neurons with
intracellular microelectrodes In: T. G. Smith Jr, Lecar H, Redman SJ, Gage P, editors. Voltage and
Patch Clamping with Microelectrodes. Bethesda, MD: American Physiological Society. pp. 191–
215.

Randle JCR, Guet T, Cordi A, Lepagnol JM. 1992. Competitive inhibition by NBQX of kainate/AMPA
receptor currents and excitatory synaptic potentials: importance of 6-nitro substitution. *Eur J*
Pharmacol **215**:237–244. doi:https://doi.org/10.1016/0014-2999(92)90033-Z

Redman S. 1990. Quantal analysis of synaptic potentials in neurons of the central nervous system.
Physiol Rev **70**:165–198. doi:10.1152/physrev.1990.70.1.165

Reid CA, Clements JD. 1999. Postsynaptic expression of long-term potentiation in the rat dentate
gyrus demonstrated by variance-mean analysis. *J Physiol* **518**:121–130.
doi:https://doi.org/10.1111/j.1469-7793.1999.0121r.x

Sahara Y, Takahashi T. 2001. Quantal components of the excitatory postsynaptic currents at a rat
central auditory synapse. *J Physiol* **536**:189–197. doi:https://doi.org/10.1111/j.1469-
7793.2001.00189.x

Silver RA. 2003. Estimation of nonuniform quantal parameters with multiple-probability fluctuation
analysis: theory, application and limitations. *J Neurosci Methods* **130**:127–141.
doi:https://doi.org/10.1016/j.jneumeth.2003.09.030

Spruston N, Jaffe DB, Williams SH, Johnston D. 1993. Voltage- and space-clamp errors associated
with the measurement of electrotonically remote synaptic events. *J Neurophysiol* **70**:781–802.
doi:10.1152/jn.1993.70.2.781

Stern P, Edwards FA, Sakmann B. 1992. Fast and slow components of unitary EPSCs on stellate cells
elicited by focal stimulation in slices of rat visual cortex. *J Physiol* **449**:247–278.
doi:https://doi.org/10.1113/jphysiol.1992.sp019085

Stuart G, Spruston N. 1998. Determinants of Voltage Attenuation in Neocortical Pyramidal Neuron
Dendrites. *The Journal of Neuroscience* **18**:3501–3510. doi:10.1523/JNEUROSCI.18-10-
03501.1998

Vere-Jones D. 1966. SIMPLE STOCHASTIC MODELS FOR THE RELEASE OF QUANTA OF TRANSMITTER
FROM A NERVE TERMINAL. *Australian Journal of Statistics* **8**:53–63.
doi:https://doi.org/10.1111/j.1467-842X.1966.tb00164.x

Wall MJ, Usowicz MM. 1998. Development of the quantal properties of evoked and spontaneous
synaptic currents at a brain synapse. *Nat Neurosci* **1**:675–682. doi:10.1038/3677

Wang N-S, Marino M, Malinow R. 2024. Detecting unitary synaptic events with machine learning.
Proceedings of the National Academy of Sciences **121**:e2315804121.
doi:10.1073/pnas.2315804121

Williams SR, Mitchell SJ. 2008. Direct measurement of somatic voltage clamp errors in central
neurons. *Nat Neurosci* **11**:790–798. doi:10.1038/nn.2137

Williams SR, Stuart GJ. 2002. Dependence of EPSP Efficacy on Synapse Location in Neocortical
Pyramidal Neurons. *Science (1979)* **295**:1907–1910. doi:10.1126/science.1067903

Yuste R. 2010. Dendritic Spines. The MIT Press. doi:10.7551/mitpress/9780262013505.001.0001

Yuste R, Majewska A, Cash SS, Denk W. 1999. Mechanisms of Calcium Influx into Hippocampal
Spines: Heterogeneity among Spines, Coincidence Detection by NMDA Receptors, and Optical
Quantal Analysis. *The Journal of Neuroscience* **19**:1976–1987. doi:10.1523/JNEUROSCI.19-06-
01976.1999

Figures

Figure 1: Recording quality measures used during the data preprocessing stage to select 'noise with

minis' and 'noise-alone' recording sweeps for further data analysis for recording p103a (layer 5).

(A) Baseline V_m across the entire recording session. Stimulation pulses were excluded from the

display. The total recording duration (excluding pulse periods) was 8520 s. The first red vertical line

marks the time when pharmacological blockade of APs was initiated. The second red vertical line

marks the time when no more APs were observing in the recording. The third red vertical line marks

the time when pharmacological blockade of mEPSPs was initiated. Bright yellow periods mark 'noise

with minis' and 'noise-alone' recording segments selected as the main comparison file for the

distribution fitting. Light yellow marks all the remaining good quality 'noise with minis' recording

sweeps that were also included in the distribution fitting procedure for estimating target SAD, MAD,

and 'deviation' scores.

(B) V_m standard deviation measured over consecutive 15 ms windows over the same recording

session. The meaning of symbols is the same as in panel (A).

(C) Evolution of mean and median amplitudes of the top 10% (amplitude-wise) of all detected events

(including minis and noise events with similar rise times), averaged over single sweeps across the

entire recording session.

(D) Effective decay time constants (time to drop to 1/e of value) of the same top 10% (amplitude-

wise) of detected events as in panel (C) averaged over consecutive 20-second-long segments across

the same session. Once minis blocked pharmacologically, effective time constant of detected events

(now pure noise) increases, so this is another useful measure of when the block is complete.

(E) Evolution of passive membrane time constant over the entire recording session. Measurements

were averaged over consecutive 20-second-long segments. Measurements based on exponential

decay curve fit and on 'effective time constant' (time for V_m to drop to 1/e of a value just after

change in current (after pipette capacitance artefact and charge redistribution).

(F) Evolution of total cell membrane capacitance across the recording session. Measurements were

averaged over consecutive 20-second-long segments. Measurements based on exponential decay

curve fit and on effective time constant (time taken for V_m drop to 1/e of an initial value).

(G) Evolution of whole-cell pipette series resistance (bridge balance error) across the recording

session. Measurements were averaged over consecutive 20-second-long segments.

Figure 2: Constructing 'noise with simulated minis' voltage trace.

(A) A segment of 'noise-alone' recording that was used to produce the voltage trace in (C). The noise

recording was obtained from a cortical layer 2/3 pyramidal neuron (cell p131a).

(B) A voltage trace showing simulated mEPSPs only that were added to noise-alone recording in (A)

to produce the 'real noise with simulated mEPSPs' voltage trace in (C).

Figure 3: Amplitude and rise time scattergram (density plot) of sum of absolute deviation (SAD)

scores between histograms from all possible pairs of 'noise with minis' single sweep files from a

layer 5 pyramidal neuron (p103a) recording.

The line marking combined 50[th] centile cutoff is based on 15 different SAD, SSD, and MAD scores as

explained in Tables 1 and 2 (it extends to the remaining 13 dimensions not shown here). '15-score

combined 50[th] centile' sets a lower (more exacting) threshold for accepting distribution fits than the

mean or the median would. This is justified because distribution fits need to satisfy all 15 SAD, SSD,

and MAD scores simultaneously (e.g. to ensure that one of the tails of the distribution is not badly

fit, as well as the remaining parts of the distribution).

Figure 4: Amplitude and rise time distributions of detected minis-like events in 'noise with minis' and

'noise-alone' recordings.

(A) Amplitude distributions of detected minis-like events in 'noise with minis' and 'noise-alone'

recordings ("thick" tufted neocortical layer 5 pyramidal neuron p108b). Red arrowhead indicates

negative bins after subtracting 'noise-alone' distribution from 'noise with minis' distribution.

(B) 10-90% rise time distributions of detected minis-like events in 'noise with minis' and 'noise-

alone' recordings.

Figure 5: Distributions of minis-like events detected in a 'noise with simulated minis' voltage trace

closely matching 'noise with real minis' recordings.

Parameters of simulated minis were controlled by the Genetic Algorithm; 'noise with real minis' and

'noise-alone' recordings from neocortical layer 5 cell (p106b). Upward arrows indicate 'simulated'

SAD > 'real' SAD relationship and downward arrows indicate 'simulated' SAD < 'real' SAD

relationship. The underfit test involves a comparison with the worst-performing 'real' SAD, whereas

the overfit test involves a comparison with the best-performing 'real' SAD.

(A) Amplitude and (B) 10-90% rise time distributions (blue) of minis-like events detected in a 'noise

with simulated minis' voltage trace.

Figure 6: An example of simulated minis distribution that was used to produce a close match

between distributions of detected minis-like events in a 'noise with simulated minis' voltage trace

and a 'noise with real minis' recording for a neocortical layer 2/3 cell (p131c).

(A) Joint amplitude and 10-90% rise time distribution of simulated minis; (B) viewed from different

angle.

(C) and (D) Corresponding marginal ('one-dimensional') amplitude and 10-90% rise time

distributions.

Figure 7: Estimated minis incidence rates using various methods (grey lines are individual cells).

'Thresholded' method: an 'unreasonably high' 0.8 mV detection threshold was applied to all 14

'noise with real minis' recordings and only events with larger amplitudes were included in the

estimate.

'Subtracted' method: Distribution of minis-like events in the 'noise-alone' recording was subtracted

from the distribution of minis-like events in the 'noise with real minis' recording and the incidence

rate estimate was based on the remaining distribution.

'Fitted' method: Simulated minis distribution was used to estimate the minis' incidence rate (lowest

acceptable rate consistent with the real experimental data).

Black markers and black vertical lines correspond to means and 95% confidence intervals. Red

dotted lines mark the range of incidence rates typically reported in the literature and discussed in

the companion article (Dervinis and Major, 2023).

Figure 8: Relationship between cell's inverse total capacitance and estimated mean minis amplitude

using simulations of minis and minis' distribution fitting.

(A) Correlation between mean minis amplitudes as derived using simulated minis' distribution fitting

method and the inverse of cell's total capacitance. The blue line is the least square fit to the data

while the black line is the fit to the data that passes through the origin of the axes.

(B) Correlation between the 'subtracted' mean minis amplitude as shown in Figure 4 and the 'fitted'

mean minis amplitude.

Figure 9: Generic 'averaged' mEPSP distribution from rat (somatosensory) neocortical pyramidal

neurons.

Distributions resulting from all 14 recordings were averaged and the resulting distribution was

smoothed. All minis' amplitudes were normalised by means of their respective source distributions.

(A) A joint amplitude and 10-90% rise time distribution of simulated minis.

(B) The same distribution but viewed from a different angle.

(C) Marginal (1-dimensional) amplitude distribution of the same distribution as in (A).

(D) Marginal 10-90% rise time distribution of the same distribution as in (A).

Tables

Amp SAD ≤56th centile?	Top 50% amp SAD ≤56th centile?	Top 10% amp SAD ≤56th centile?	Top 2% amp SAD ≤56th centile?	Top 50% amp SSD ≤0?	Top 10% amp SSD ≤0?	Top 2% amp SSD ≤0?	RT SAD ≤56th centile?	Joint SAD ≤56th centile?	Amp MAD ≤56th centile?	Top 50% amp MAD ≤56th centile?	Top 10% amp MAD ≤56th centile?	Top 2% amp MAD ≤56th centile?	RT MAD ≤56th centile?	Joint MAD ≤56th centile?
...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Yes	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
No	No	No	No	Yes	No	No	Yes	Yes	Yes	No	No	No	Yes	Yes
No	Yes	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	No	No	Yes	No
Yes	Yes	Yes	Yes	No	No	No	No	Yes	Yes	Yes	Yes	Yes	No	Yes
...	...	...	...	...	...	...	...	...	...	...	...	...	...	...

Table 1: Failed hypothetical attempt to use 56th centile as a basis for the combined '15-score 50th centile'.

The table shows representative portion of a much bigger table illustrating a hypothetical scenario where the 15 SAD, SSD, and MAD scores are arranged in columns and rows correspond to different two-file combinations (many other combinations above and below those portrayed for the sake of the argument). SAD, SSD, and MAD scores are calculated by subtracting one file distribution from another (see the text for a detailed explanation). In this example only a single file combination (green; 1/6 = 16.7%; row shaded in grey) satisfies the condition of having all SAD, SSD, and MAD values that are equal or below the 56th centile value of its respective SAD, SSD, and MAD scores (unique per column) *simultaneously* in all columns. Therefore, the 56th percentile of each SAD, SSD, and MAD score would be too small to serve as the basis for the composite, joint or combined '15-score 50th centile': we need half the rows to be green, i.e. to pass the test.

Amp SAD ≤90th centile?	Top 50% amp SAD ≤90th centile?	Top 10% amp SAD ≤90th centile?	Top 2% amp SAD ≤90th centile?	Top 50% amp SSD ≤0?	Top 10% amp SSD ≤0?	Top 2% amp SSD ≤0?	RT SAD ≤90th centile?	Joint SAD ≤90th centile?	Amp MAD ≤90th centile?	Top 50% amp MAD ≤90th centile?	Top 10% amp MAD ≤90th centile?	Top 2% amp MAD ≤90th centile?	RT MAD ≤90th centile?	Joint MAD ≤90th centile?
...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	Yes
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
...	...	...	...	...	...	...	...	...	...	...	...	...	...	...

Table 2: Using 90th SAD centile as a basis for the combined '15-score 50th centile'.

The table shows an example where the 15 SAD, SSD, and MAD scores are arranged in columns and rows correspond to different 2-file combinations. SAD,

SSD, and MAD scores are calculated by subtracting one file distribution from another (see the text for a detailed explanation). Now *three* of the six file

combinations (half of them: green; rows shaded in grey) satisfy the condition of having all SAD, SSD, and MAD values that are equal or below the 90th centile

value of its respective SAD, SSD, and MAD scores (unique per column) simultaneously in all columns. Therefore the 90th percentile works as the basis for the

combined '15-score 50th centile'. Higher than 90 leads to more than half and lower than 90 leads to fewer than half of file pair combinations 'passing' all 15

tests simultaneously.

Supplementary Figures

Supplementary Figure 1: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p106b (layer 5).

(A) Baseline V_m across the entire recording session. The raw trace is very similar to the smoothed

one and, therefore, is occluded by the latter. Stimulation pulses were excluded from the display. The

total recording duration (excluding pulse periods) was 4960 s. The first red vertical line marks the

time when pharmacological blockade of APs was initiated. The second red vertical line marks the

time when no more APs were observing in the recording. The third red vertical line marks the time

when pharmacological blockade of mEPSPs was initiated. Bright yellow periods mark 'noise with

minis' and 'noise-alone' recording segments selected as the main comparison file for the distribution

fitting. Light yellow marks all the remaining good quality 'noise with minis' recording sweeps that

were also included in the distribution fitting procedure for estimating target SAD, MAD, and

'deviation' scores.

(B) V_m standard deviation measured over consecutive 15 ms windows over the same recording

session. The meaning of symbols is the same as in panel (A).

(C) Evolution of mean and median amplitudes of the top 10% (amplitude-wise) of all detected minis-

like events averaged over single sweeps across the entire recording session.

(D) Effective decay (drop to 1/e of the peak value) time constants of the same top 10% (amplitude-

wise) of detected events as in panel (C) averaged over consecutive 20-second-long segments across

the same session.

(E) Evolution of passive membrane time constant over the entire recording session. Measurements

were averaged over consecutive 20-second-long segments. Both measurements based on

exponential decay curve fit and on effective V_m drop to 1/e of the initial value were calculated and

displayed.

(F) Evolution of total cell's membrane capacitance across the recording session. Measurements were

averaged over consecutive 20-second-long segments. Both measurements based on exponential

decay curve fit and on effective V_m drop to 1/e of the initial value were calculated and displayed.

(G) Evolution of cell's input resistance (the bridge balance error) across the recording session.

Measurements were averaged over consecutive 20-second-long segments.

Supplementary Figure 2: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p108a (layer 5).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 5140 s.

Supplementary Figure 3: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p108b (layer 5).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 2400 s.

Supplementary Figure 4: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p108c (layer 5).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 2000 s.

Supplementary Figure 5: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p120b (layer 2/3).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 4000 s.

1003

1004

Supplementary Figure 6: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p122a (layer 2/3).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 4200 s.

1013

1014

Supplementary Figure 7: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p124b (layer 5).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 2400 s.

1023

1024

Supplementary Figure 8: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p125a (layer 2/3).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 3800 s.

1033

1034

Supplementary Figure 9: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p127c (layer 2/3).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 3200 s.

1043

Supplementary Figure 10: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p128c (layer 2/3).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 3800 s.

1053

Supplementary Figure 11: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p129a (layer 5).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 4000 s.

1062

1063

Supplementary Figure 12: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p131a (layer 2/3).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 2400 s.

1072

1073

Supplementary Figure 13: Recording quality measures used during the data preprocessing stage to

select 'noise with minis' and 'noise-alone' recording sweeps for further data analysis for recording

p131c (layer 2/3).

The meaning of panels A-G is explained in Supplementary figure 1 except for data being averaged

over 100-second-long windows in panels D-G. The figure shows only part of the recording following

the blockade of APs with only a single red vertical time marker visible indicating the time when

pharmacological EPSP blockers were infused. The total duration of the recording shown in the figure

was 2200 s.

1082

1083

Supplementary figure 14: Distributions of minis-like events detected in a 'noise + simulated minis'

voltage trace that closely matched 'noise + real minis' recordings.

Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

obtained in cell p103a of the cortical layer 5. Upward arrows indicate 'simulated' SAD > 'real' SAD

relationship and downward arrows indicate 'simulated' SAD < 'real' SAD relationship. The underfit

test involves a comparison with the worst-performing 'real' SAD, whereas the overfit test involves a

comparison with the best-performing 'real' SAD.

(A) Amplitude distribution of minis-like events detected in a 'noise + simulated minis' voltage trace

(the blue curve).

(B) 10-90% rise time distribution of minis-like events detected in a 'noise + simulated minis' voltage

trace (the blue curve).

1095

1096

1097 **Supplementary figure 15:** Distributions of minis-like events detected in a 'noise with simulated

1098 minis' voltage trace that closely matched 'noise with real minis' recordings.

1099 Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

1100 obtained in cell p108a of the cortical layer 5. The meanings of the upward and downward arrows are

1101 explained in Supplementary figure 14.

1102

1103

Supplementary figure 16: Distributions of minis-like events detected in a 'noise with simulated

minis' voltage trace that closely matched 'noise with real minis' recordings.

Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

obtained in cell p108b of the cortical layer 5. The meanings of the upward and downward arrows are

explained in Supplementary figure 14.

1104

1105

1106

1107

1108

1109

1110

1111 **Supplementary figure 17:** Distributions of minis-like events detected in a 'noise with simulated

1112 minis' voltage trace that closely matched 'noise with real minis' recordings.

1113 Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

1114 obtained in cell p108c of the cortical layer 5. The meanings of the upward and downward arrows are

1115 explained in Supplementary figure 14.

1116

1117

1118 **Supplementary figure 18:** Distributions of minis-like events detected in a 'noise with simulated

1119 minis' voltage trace that closely matched 'noise with real minis' recordings.

1120 Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

1121 obtained in cell p120b of the cortical layer 2/3. The meanings of the upward and downward arrows

1122 are explained in Supplementary figure 14.

1123

1124

1125 **Supplementary figure 19:** Distributions of minis-like events detected in a 'noise with simulated

1126 minis' voltage trace that closely matched 'noise with real minis' recordings.

1127 Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

1128 obtained in cell p122a of the cortical layer 2/3. The meanings of the upward and downward arrows

1129 are explained in Supplementary figure 14.

1130

1131

1132 **Supplementary figure 20:** Distributions of minis-like events detected in a 'noise with simulated

1133 minis' voltage trace that closely matched 'noise with real minis' recordings.

1134 Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

1135 obtained in cell p124b of the cortical layer 5. The meanings of the upward and downward arrows are

1136 explained in Supplementary figure 14.

1137

1138

1139 **Supplementary figure 21:** Distributions of minis-like events detected in a 'noise with simulated

1140 minis' voltage trace that closely matched 'noise with real minis' recordings.

1141 Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

1142 obtained in cell p125a of the cortical layer 2/3. The meanings of the upward and downward arrows

1143 are explained in Supplementary figure 14.

1144

1145

1146 **Supplementary figure 22:** Distributions of minis-like events detected in a 'noise with simulated

1147 minis' voltage trace that closely matched 'noise with real minis' recordings.

1148 Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

1149 obtained in cell p127c of the cortical layer 2/3. The meanings of the upward and downward arrows

1150 are explained in Supplementary figure 14.

1151

1152

Supplementary figure 23: Distributions of minis-like events detected in a 'noise with simulated

minis' voltage trace that closely matched 'noise with real minis' recordings.

Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

obtained in cell p128c of the cortical layer 2/3. The meanings of the upward and downward arrows

are explained in Supplementary figure 14.

1158

Supplementary figure 24: Distributions of minis-like events detected in a 'noise with simulated

minis' voltage trace that closely matched 'noise with real minis' recordings.

Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

obtained in cell p129a of the cortical layer 5. The meanings of the upward and downward arrows are

explained in Supplementary figure 14.

1166

Supplementary figure 25: Distributions of minis-like events detected in a 'noise with simulated

minis' voltage trace that closely matched 'noise with real minis' recordings.

Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

obtained in cell p131a of the cortical layer 2/3. The meanings of the upward and downward arrows

are explained in Supplementary figure 14.

1172

1173

Supplementary figure 26: Distributions of minis-like events detected in a 'noise with simulated

minis' voltage trace that closely matched 'noise with real minis' recordings.

Parameters of simulated minis were controlled by the GA, whereas the 'noise-alone' recording was

obtained in cell p131c of the cortical layer 2/3. The meanings of the upward and downward arrows

are explained in Supplementary figure 14.

1179

1180

Supplementary figure 27: An example of simulated minis distribution that was used to produce a

close match between distributions of detected minis-like events in a 'noise with simulated minis'

voltage trace and in a 'noise with real minis' recording for a cell p103a of cortical layer 5.

(A) A joint amplitude and 10-90% rise time distribution of simulated minis.

(B) The same distribution but viewed from a different angle.

(C) Marginal amplitude distribution of the same distribution as in (A).

(D) Marginal 10-90% rise time distribution of the same distribution as in (A).

1188

1189

1190 **Supplementary figure 28:** An example of simulated minis distribution that was used to produce a

1191 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1192 voltage trace and in a 'noise with real minis' recording for a cell p106b of cortical layer 5.

1193 The meaning of different figure panels is explained in Supplementary figure 27.

1194

1195

1196 **Supplementary figure 29:** An example of simulated minis distribution that was used to produce a

1197 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1198 voltage trace and in a 'noise with real minis' recording for a cell p108a of cortical layer 5.

1199 The meaning of different figure panels is explained in Supplementary figure 27.

1200

1201

1202 **Supplementary figure 30:** An example of simulated minis distribution that was used to produce a

1203 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1204 voltage trace and in a 'noise with real minis' recording for a cell p108b of cortical layer 5.

1205 The meaning of different figure panels is explained in Supplementary figure 27.

1206

1207

1208 **Supplementary figure 31:** An example of simulated minis distribution that was used to produce a

1209 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1210 voltage trace and in a 'noise with real minis' recording for a cell p108c of cortical layer 5.

1211 The meaning of different figure panels is explained in Supplementary figure 27.

1212

1213

1214 **Supplementary figure 32:** An example of simulated minis distribution that was used to produce a

1215 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1216 voltage trace and in a 'noise with real minis' recording for a cell p120b of cortical layer 2/3.

1217 The meaning of different figure panels is explained in Supplementary figure 27.

1218

1219

1220 **Supplementary figure 33:** An example of simulated minis distribution that was used to produce a

1221 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1222 voltage trace and in a 'noise with real minis' recording for a cell p122a of cortical layer 2/3.

1223 The meaning of different figure panels is explained in Supplementary figure 27.

1224

1225

1226 **Supplementary figure 34:** An example of simulated minis distribution that was used to produce a

1227 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1228 voltage trace and in a 'noise with real minis' recording for a cell p124b of cortical layer 5.

1229 The meaning of different figure panels is explained in Supplementary figure 27.

1230

1231

1232 **Supplementary figure 35:** An example of simulated minis distribution that was used to produce a

1233 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1234 voltage trace and in a 'noise with real minis' recording for a cell p125a of cortical layer 2/3.

1235 The meaning of different figure panels is explained in Supplementary figure 27.

1236

1237

1238 **Supplementary figure 36:** An example of simulated minis distribution that was used to produce a

1239 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1240 voltage trace and in a 'noise with real minis' recording for a cell p127c of cortical layer 2/3.

1241 The meaning of different figure panels is explained in Supplementary figure 27.

1242

1243

1244 **Supplementary figure 37:** An example of simulated minis distribution that was used to produce a

1245 close match between distributions of detected minis-like events in a 'noise with simulated minis'

1246 voltage trace and in a 'noise with real minis' recording for a cell p128c of cortical layer 2/3.

1247 The meaning of different figure panels is explained in Supplementary figure 27.

1248

1249

Supplementary figure 38: An example of simulated minis distribution that was used to produce a

close match between distributions of detected minis-like events in a 'noise with simulated minis'

voltage trace and in a 'noise with real minis' recording for a cell p129a of cortical layer 5.

The meaning of different figure panels is explained in Supplementary figure 27.

1254

Supplementary figure 39: An example of simulated minis distribution that was used to produce a close match between distributions of detected minis-like events in a 'noise with simulated minis' voltage trace and in a 'noise with real minis' recording for a cell p131a of cortical layer 2/3. The meaning of different figure panels is explained in Supplementary figure 27.