A Powered Simple Walking Model Modifies the Rate of Recovery Definition: Human Walking Deviates Drastically from Pendular Motion During the Double Support Phase

Seyed-Saleh Hosseini-Yazdi[1,2]

[1]Department of Biomedical Engineering, Schulich School of engineering, University of Calgary, AB, Canada
[2]Human Performance Laboratory, Faculty of Kinesiology, University of Calgary, AB, Canada

Conflict of Interest: None

Correspondence Address:

Seyed-Saleh Hosseini-Yazdi
Biomedical Engineering Department, Schulich School of Engineering, University of Calgary
2500 University Dr NW, Calgary AB T2N1N4

Phone: 403 402 6005
Email: seyedsaleh.hosseiniy@ucalgary.ca

Abstract:

This study proposes a modified definition of the original rate of recovery (ROR) in human walking, derived from a powered simple walking model and center of mass work. The metric captures the proportion of energy transferred from one step to the next by incorporating total step mechanical dissipation. Our simulation results show that the modified ROR decreases nearly linearly with increasing walking speed on even terrain due to collision impulses scaling with velocity ($co \sim v_{ave}$) and energy dissipation scaling quadratically ($w_{co} \sim v_{ave}^2$). For nominal even walking at 1.25 m.s^{-1}, the analytical ROR was 85%, depicting higher rates than previously proposed. Experimental data, however, reveal lower ROR values due to additional energy dissipation factors, such as soft tissue or peripheral work, which are not captured by the analytical model. In contrast to the analytical model, the experimental results also show a maximum rate of recovery occurring at 1.21 m.s^{-1}. This peak appeared when dissipation encompassed both step transition and single support phase negative work. For uneven terrains with step height variations of ±0.036 m, the average model ROR was 82%, suggesting that a completely random uneven terrain may be analytically approximated by even walking. However, the elevated energetic demands of uneven walking, primarily due to suboptimal pre-emptive push-offs (timing or magnitude), must further decrease the ROR. Similarly, other walking conditions associated with increased metabolic costs, such as aging or when vision about the coming terrain is denied (restricted lookahead), are also expected to result in reduced RORs. These findings underscore the critical role of optimal pre-emptive push-offs and proper foot placement in minimizing collision energy dissipation and enhancing walking efficiency. Therefore, having an appropriate metric for ROR also may be crucial for understanding gait mechanics, assessing mobility in populations with impairments, guiding rehabilitation, and optimizing prosthetic designs.

Word Count: 4625

Keywords: rate of recovery, walking energetics, center of mass work, step-to-step transition, push-off, collision dissipation

Introduction:

A substantial portion of walking metabolic energy is used to perform mechanical work on the Center of Mass (COM), propelling it forward and compensating for mechanical energy losses (Donelan et al., 2002a). Consequently, conserving mechanical energy during walking can also reduce the associated metabolic cost (Donelan et al., 2002a). One specific instance of mechanical energy loss occurs during the transition between steps, where the heel-strike dissipates energy by performing active negative mechanical work, referred to as "collision" (Kuo, 2002; Kuo et al., 2005). The rate of recovery (ROR), defined as the fraction of energy transferred from one step to the next (Cavagna et al., 1977). It is a key metric in walking biomechanics that measures the efficiency of energy transfer between steps, reflecting how well mechanical energy is conserved and reused during gait. A higher ROR indicates a better walking economy, reduced metabolic costs, and efficient coordination of passive (e.g., tendon elasticity) and active (e.g., muscle contractions) walking mechanisms. Since human walking is not always conservative, ROR may be redefined to account for step-to-step transition active energy dissipation. In this framework, the legs' external work compensates for the energy lost during heel-strike (Donelan et al., 2002a; Kuo, 2002). Factors such as age, state of lookahead, walking speed, and terrain conditions may also influence heel-strike energy losses, impacting the rate of recovery.

Human locomotion is hypothesized to mimic pendulum and spring-like mechanics to minimize active muscle work (Cavagna et al., 1977). Specifically, the single support phase of walking aligns with the motion of an inverted pendulum (Kuo et al., 2005). In an idealized scenario with no energy dissipation, a walker starting with sufficient initial energy would require no external energy input. Thus, human walking primarily involves converting potential and kinetic energy within a conservative system (Cavagna et al., 1977).

According to Cavagna et al. (Cavagna et al., 1976, 1977), walkers perform works against gravity (W_v) to lift

the COM and to accelerate it forward (W_f). When potential and kinetic energies are completely out of

phase, the mechanical energy transitions with no dissipation. In this state, gravitational potential energy

is converted into kinetic energy, propelling the walker forward. However, when these energies become

aligned, energy exchange is disrupted, resulting in dissipation. Humans then perform work (W_{ext}) to

compensate for this energy loss. This assumption hinges on the notion that human walking always

resembles inverted pendulum mechanics and incurs no energy waste departing from a pendular motion

(Figure 1A).

Donelan et al. (Donelan et al., 2002b), however, proposed that humans simultaneously perform positive

and negative work during step-to-step transitions. This suggests a significant deviation from the inverted

pendulum model, as the COM mechanics transition to the next stance (Figure 1B). Donelan et al. (Donelan

et al., 2002a) further argued that these simultaneous COM works are mechanically costly and serve as a

rough indicator of walking energetics. Post step transition, the human walking tends to resemble pendular

motion again (Donelan et al., 2002a; Kuo et al., 2005).

When considering the right and left legs as separate actuators exerting toe-off (push-off) and heel-strike

(collision) impulses (Kuo et al., 2005), it becomes reasonable to investigate their individual effects on the

COM. Similar to other mechanical actuators, the work of each leg is determined by the force applied and

the corresponding displacement. Thus, the mechanical work of each leg cannot mathematically cancel the

other's work. While the net effect on the COM may reflect the resultant force induced, the independent

work of each leg incurs its own metabolic cost (Griffin et al., 2003).

Both toe-off (push-off) and heel-strike (collision) impulses generate upward motions on the COM in the

frontal plane, but their sagittal plane effects differ. The toe-off (push-off) impulse propels the pelvis

forward, while the heel-strike (collision) impulse opposes the forward progression, partially wasting

momentum and mechanical energy (Figure 1C & D) (Donelan et al., 2002a, 2002b; Kuo, 2002).

Consequently, the toe-off (push-off) impulse contributes to forward momentum, whereas the heel-strike

(collision) impulse results in energy loss (Donelan et al., 2002a; Kuo, 2002).

A simple powered walking model demonstrates the independent contributions of the leading and trailing

legs during step transitions (Kuo, 2002). For a given walking speed, it predicts the active work required

(push-off work) for optimal steady-state walking, where active work matches dissipation. Pre-emptive

push-off is hypothesized to limit the magnitude of subsequent collision (Kuo, 2002; Kuo et al., 2005). When

heel-strike occurs earlier than expected (Darici et al., 2018), the pre-emptive push-off can only partially

mitigate the resulting collision (Kuo, 2001). Hence, to maintain steady walking, additional positive

mechanical energy is required during the subsequent stance phase (Darici & Kuo, 2023; Hosseini-Yazdi

Seyed-Saleh, 2024; Kuo, 2002). Suboptimal push-off ($po_{sub} < po_{opt}$) results in increased dissipation and

a reduced amount of energy transferred to the subsequent step.

Walking energetics increase with terrain complexity (Hosseini-Yazdi Seyed-Saleh, 2024; Pandolf et al.,

1976; Voloshina et al., 2013) and age (Das Gupta et al., 2019; Hosseini-Yazdi Seyed-Saleh, 2024). Restricted

lookahead might also impair the ability to select appropriate footholds, limiting the benefits of human

walking dynamics (Matthis & Fajen, 2013). It is shown that walking with a restricted lookahead also

coincides with elevated walking energetics (Hosseini-Yazdi Seyed-Saleh, 2024). Since step mechanical work

provides a rough approximation of walking energetics (Donelan et al., 2002a), it is reasonable to infer that

any walking regime requiring increased metabolic rates corresponds to higher active mechanical work

performance, and as such lower rates of recovery.

This study redefines the rate of recovery based on step energy dissipation. We develop a simulation to

derive analytical rates of recovery for nominal (optimal) walking across a range of walking speeds. The

simulation is extended to scenarios with suboptimal push-off impulses ($po_{sub} < po_{opt}$) and cases where

COM elevation changes; step-ups and step-downs (i.e. uneven walking). Without loss of generality for

uneven walking, we examine a scenario where pre-emptive push-off provides the entire step transition

energy and compensates for work against gravity. Further we compare the analytical results with ROR

derived from COM work trajectories (experimental data) for walking over smooth surfaces.

New Definition for Rate of Recovery:

According to a powered simple walking model (Kuo, 2002), the active push-off (po) is applied pre-

emptively to the COM to mechanically energize the step-to-step transition (Darici et al., 2018). This action

compensates for the dissipation caused by the heel-strike collision, which occurs after the push-off.

Consequently, the required external work (W_{ext}) is assumed to offset the energy lost during the heel-

strike (Cavagna et al., 1977). Considering 'u' as the transition impulse, its associated work is calculated as

$\frac{1}{2}u^2$ (Darici et al., 2018; Kuo, 2002). We count the total mechanical energy of the human body as the sum

of its potential and kinetic energies ($E_{tot} = E_P + E_K$). Assuming that the lowest elevation of the COM

during the stance phase as the reference for gravitational potential energy ($E_P = 0$), the total energy at

the end of the stance phase corresponds to the maximum kinetic energy ($E_{K\_max} = E_{tot}$, Figure 1E & F).

As originally defined, the rate of recovery based on the step works is given by (Cavagna et al., 1977):

$$Rate\ of\ Recovery = \frac{E_{tot} - W_{ext}}{E_{tot}} \qquad \text{Eq. 1}$$

148   This equation quantifies the proportion of mechanical energy transferred from one step to the next. Since

149   the system's total energy equals the maximum kinetic energy just before the step transition, the rate of

150   recovery becomes:

$$Rate\ of\ Recovery = \frac{E_{K\_max} - W_{ext}}{E_{K\_max}} \qquad \text{Eq. 2}$$

151   Assuming the COM velocity just before the transition approximates the average walking velocity (v_{ave} in

152   which $\vec{v}_{ave} = \vec{v}_f + \vec{v}_v$) (Kuo, 2002), and w_{ext} represents the normalized external work per unit mass, the

153   rate of recovery can be derived as:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - w_{ext}}{\frac{1}{2}v_{ave}^2} \qquad \text{Eq. 3}$$

154   To sustain a steady walk, the walker's energy must remain constant before and after the step-to-step

155   transition. Denoting the velocity before and after the transition as v^- and v^+, respectively, steady walking

156   implies, $|v^+| = |v^-| = v_{ave}$. With the kinetic energy conserved across the transition, the active work

157   energy addition (w_{ext}) equals the heel-strike energy dissipation or collision work (w_{co}). Therefore, the rate

158   of recovery can be further expressed as:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - w_{co}}{\frac{1}{2}v_{ave}^2} \qquad \text{Eq. 4}$$

159   Here, w_{co} represents the normalized energy loss due to the heel-strike collision.

Simulation based on a powered simple walking model:

161   The nominal push-off impulse for a given walking speed is expressed as $po = v_{ave} \cdot \tan \alpha$ where '2α'

162   represents the angle between the leading and trailing legs at the point of transition (Kuo, 2002).

163   Consequently, the nominal push-off work becomes $w_{po} = \frac{1}{2}v_{ave}^2 \cdot \tan^2 \alpha$ (Kuo, 2002). Assuming $w_{co} =$

164   w_{po} and $w_{ext} = w_{co}$, the rate of recovery is:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - \frac{1}{2}v_{ave}^2 \cdot \tan^2 \alpha}{\frac{1}{2}v_{ave}^2} = 1 - \tan^2 \alpha \qquad \text{Eq. 5}$$

165   For small angles, the approximation $\tan \alpha \sim \alpha$ holds, leading to $po = v_{ave} \cdot \alpha$ and $w_{po} = \frac{1}{2}v_{ave}^2 \cdot \alpha^2$.

166   Assuming a unit leg length, the step length (s) becomes proportional to 2α (Kuo, 2001, 2002). Since step

167   length follows a power law with walking speed (Kuo, 2001); $s \sim v^{0.42}$, yielding $2\alpha = c \cdot v^{0.42}$ and $\alpha =$

168     $\frac{1}{2} c \cdot v^{0.42}$. Substituting '$\alpha$' into Eq. 5 with $\tan\alpha \sim \alpha$:

$$Rate\ of\ Recovery = 1 - \alpha^2 = 1 - \frac{1}{4} c^2 \cdot v_{ave}^{0.84} \qquad \text{Eq. 6}$$

169   This analytical expression suggests that the rate of recovery decreases nearly linearly with walking speed.

170   Applying the principles of the powered simple walking model to a suboptimal push-off (po_{sub}, Figure 1G)

171   (Kuo, 2002) the mid-transition velocity (v^0) forms an angle (γ) with the COM velocity before transition

172   (v^-) which depends on the induced push-off impulse magnitude: $\gamma = \arctan(\frac{po_{sub}}{v_{ave}})$. Since $v^- \sim v_{ave}$ (Kuo,

173   2002) , the transition collision impulse (co) becomes:

$$\begin{cases} \dfrac{co}{v^0} = \sin(2\alpha - \gamma) \\ \dfrac{v_{ave}}{v^0} = \cos\gamma \end{cases} \rightarrow co = v_{ave} \dfrac{\sin(2\alpha - \gamma)}{\cos\gamma} \qquad \text{Eq. 7}$$

174   The normalized collision work is $w_{co} = 0.5 co^2$ (Darici et al., 2018; Kuo, 2002), and the modified rate of

175   recovery is:

$$Rate\ of\ Recovery = \frac{\frac{1}{2} v_{ave}^2 - w_{co}}{\frac{1}{2} v_{ave}^2} = 1 - \left(\frac{\sin(2\alpha - \gamma)}{\cos\gamma}\right)^2 \qquad \text{Eq. 8}$$

176   Using small angle approximations for 'α' and 'γ':

$$Rate\ of\ Recovery = 1 - \left(2\alpha - \frac{po_{sub}}{v_{ave}}\right)^2 = 1 - \left(c \cdot v_{ave}^{0.42} - \frac{po_{sub}}{v_{ave}}\right)^2 \qquad \text{Eq. 9}$$

177   This result shows that the rate of recovery becomes a nonlinear function of both suboptimal push-off

178   magnitude and the average walking speed. For uneven terrain with a step-up, maintaining the average

179   walking speed (v_{ave}) at mid-stance requires the post-transition COM kinetic energy to also account for the

180   work against gravity. The post-transition velocity (v^+) must therefore satisfy (Figure 1H):

$$\frac{1}{2} v^{+2} - \frac{1}{2} v_{ave}^2 = g \cdot \Delta h \rightarrow v^+ = \sqrt{v_{ave}^2 + 2g \cdot \Delta h} \qquad \text{Eq. 10}$$

A) Walking with no double support phase

Single Support   Single Support

B) Walking with double support phase

Double Support

Single Support   Single Support

C. Push-off and collision in the Frontal Plane

Push-Off   Collision

D. Push-off and collision in Sagittal Plane

Progression Direction

Push-off   Collision

E) Nominal steady walking

v^+
co_opt
α
α
po_opt
v^-
α α
Step length

F) Step-to-step transition based on powered simplest walking model

Before transition $E_P = 0$ After transition

v^- v^+

Maximum kinetic energy

G) Walking with a random (suboptimal) push-off

v^+
co_sub
$2\alpha-\gamma$
γ
po_sub
v^-
α α
Step length

H) Uneven walking (step-up)

v^+
co
$2\alpha-\gamma$ $\alpha+\delta$
v^0
γ po $\alpha-\delta$
v^0
$\alpha-\delta$ $\alpha+\delta$
δ
Step length

Figure 1: Schematics showing the step-to-step transition during even walking: (A) pendular walking model with rigid legs in which the step-to-step transition is instantaneous (no double support phase), (B) human walking demonstrates a double support phase in which humans switch from one inverted pendulum to another, (C) push-off and collision impulses have similar effects in the vertical direction, (D) push-off impulse adds to the COM mechanical energy in the progression direction while collision impulse reduces the momentum, (E and F) In nominal steady walking, the push-off and collision work, and pre (v^-) and post transition (v^+) speeds are equal, the pre transition velocity may be approximated by v_{ave}, (G) if the pre-emptive push-off is less than optimal (suboptimal), the magnitude of the subsequent collision impulse grows and the post transition speed declines, (H) when the total step transition and gravity works are provided by the pre-emptive push-off impulse, optimal uneven walking takes place.

190   If the entire uneven step energy is provided by a pre-emptive push-off, then:

$$\begin{cases} \dfrac{v^+}{v^0} = \cos(2\alpha - \gamma) \\ \dfrac{v_{ave}}{v^0} = \cos\gamma \end{cases} \rightarrow v^+ = v_{ave}\dfrac{\cos(2\alpha - \gamma)}{\cos\gamma} \rightarrow \sqrt{v_{ave}^2 + 2g.\Delta h} = v_{ave}\dfrac{\cos(2\alpha - \gamma)}{\cos\gamma} \qquad \text{Eq. 11}$$

191   The mid-transition velocity angle change (γ) must be determined numerically for a given walking

192   condition. The uneven step collision impulse becomes:

$$\dfrac{co}{v^0} = \sin(2\alpha - \gamma) \rightarrow co = v_{ave}\dfrac{\sin(2\alpha - \gamma)}{\cos\gamma} \qquad \text{Eq. 12}$$

193   Thus, the rate of recovery for an uneven step can be derived similar to even walking when a suboptimal

194   push-off is applied, yet with $\gamma > \alpha$. Using the small angle approximation, the rate of recovery for uneven

195   walking becomes: $1 - (2\alpha - \gamma)^2$. For a step-down, the process is similar, with Δh being negative. Here,

196   the potential energy converts to kinetic energy, increasing momentum, and the required push-off

197   magnitude decreases as the step-down amplitude increases.

Results:

We redefined the rate of recovery based on step mechanical work dissipation (Donelan et al., 2002a),

focusing on scenarios where the COM trajectory significantly deviates from conservative inverted

pendulum motion. Originally, the rate of recovery was defined as the percentage of total mechanical

energy carried over from one step to the next through conversion of potential and kinetic energies

(Cavagna et al., 1977). Nevertheless, we assumed that the external work equates to heel-strike energy

dissipation, enabling us to analytically estimate the rate of recovery for various walking conditions using a

simple powered walking model, whether the push-off was nominal or suboptimal (Kuo, 2002).

The step length was estimated using an empirical power law for a given velocity (Kuo, 2001)[15]. As walking

speed increased from 0.8 m. s^{-1} to 1.6 m. s^{-1}, the estimated step length increased from 0.61 m to 0.82 m

(a 34.4% increase when the leg length is 1 m). Correspondingly, the analytical total energy of walking (COM

kinetic energy just before transition) and the push-off work during the step-to-step transition increased

significantly—by 400% (from 0.32 J. kg^{-1} to 1.28 J. kg^{-1}) and 733.3% (from 0.03 J. kg^{-1} to 0.22 J. kg^{-1}),

respectively. However, the rate of recovery declined from 90.6% to 83.1% (an 8.3% decrease). The small

angle approximation yielded a rate of recovery that was, on average, only 1.5% higher than the analytical

rate (Figure 2).

For suboptimal push-offs, where push-off magnitudes varied from zero to nominal (velocity = 1.25 m. s^{-1},

$\alpha = 0.37$ rad.), the mid-transition velocity angle relative to the pre-transition velocity (γ) increased from

zero to 0.37 rad. Simultaneously, the analytical collision impulse decreased from 0.84 m. s^{-1} to 0.49 m. s^{-1}

(a 71.4% reduction), while analytical push-off work increased from zero to 0.12 J. kg^{-1} and collision work

declined from 0.36 J. kg^{-1} to 0.12 J. kg^{-1} (a 66.7% reduction). The analytical rate of recovery increased

from 54.5% to 84.9% (a 55.8% increase). The small angle approximation initially suggested a lower rate of

recovery but exceeded the analytical trajectory when the suboptimal push-off impulse reached

approximately 70% of the optimal push-off magnitude (Figure 3).

For uneven walking (step-up), we assumed that optimal walking occurred when the entire step transition

energy and the work required to overcome gravity were supplied by the pre-emptive push-off. As the step-

up amplitude increased, the optimal angle of the mid-transition COM velocity change (γ) also increased.

Simulations indicated that push-off magnitudes for step-up walking exceeded those for nominal even

walking at the same speed but were constrained by the maximum inducible analytical magnitude

($v_{ave}. \tan 2\alpha$), where analytical collision became zero (Kuo, 2002).

On average, the small angle approximation overestimated the analytical rate of recovery by only 1.3%. The

analytical rate of recovery increased from 84.9% to 99.3% as step elevation changes varied from 0 m to

0.05 m, indicating that maximum push-off eliminated dissipation, allowing full transfer of the previous

step's mechanical energy (Figure 4).

Figure 2: Summary of the analytic simulation for nominal walking across the given walking speed range: (A) As walking speed increases, the step length also increases (leg length = 1m). (B) The total mechanical energy of the walker, push-off work, and the magnitude of mechanical energy transferred from one step to the next (recovered energy or recovery) all rise. (C) While the dissipation rate increases, the rate of recovery declines. The dashed line represents the rate of recovery when a small angle approximation is employed.

Figure 3: With a suboptimal push-off exertion ($v_{ave} = 1.25 \, \mathrm{m.s^{-1}}$), as the magnitude of the induced push-off increases (A) the mid-transition velocity angle change (γ) rises, (B) resulted collision impulse declines, (C) the associated collision work dissipation decreases, and (D) the modified rate of recovery for the suboptimal push-off elevates. The vertical dashed line depicts exerting 80% of the optimal push-off. The associated transition dissipation is $0.16 \, \mathrm{J \cdot kg^{-1}}$ and the estimated rate of recovery is 80%.

For step-down, the gravitational potential energy contributed to step transition work, reducing the

required push-off as its amplitude increased. Simulations showed that for Δh = -0.036 m, no push-off was

required, as gravitational potential energy fully compensated for the step transition energy, resulting in

maximum collision energy dissipation. We terminated simulations when pre-emptive push-off reached

zero, defining this as the maximum step-down amplitude. Beyond this threshold, analytical collision could

not offset excess gravitational energy, and walkers could not sustain the average prescribed walking speed.

When pre-emptive push-off was zero, the mid-transition COM velocity equaled the pre-transition speed

($\gamma = 0$). The rate of recovery decreased with greater step-down amplitudes, declining from 85% to 54% as

collision dissipation increased from 0.12 $J.kg^{-1}$ to 0.36 $J.kg^{-1}$. For even walking, the small angle

approximation overestimated the analytical rate, but the trajectories intersected, with the approximation

underestimating recovery at the maximum step-down amplitude (Figure 5).

Rate of recovery based on experimental data:

For experimental data analysis, the collision work at heel-strike can be estimated by integrating COM

power trajectories during the collision phase (Figure 6) (Hosseini-Yazdi Seyed-Saleh, 2024; Hosseini-Yazdi

& Kuo, 2024; Kuo et al., 2005). Using this approach, the rate of recovery can be expressed as:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - \frac{W_{co\_exp}}{M}}{\frac{1}{2}v_{ave}^2} = 1 - \frac{2\ W_{co\_exp}}{M.v_{ave}^2}$$

Eq. 13

258   Here, 'M' is the subject's mass. We expect lower rates of recovery for experimental data due to additional

259   dissipation, such as soft tissue (Zelik & Kuo, 2010) or peripheral (Van Der Zee & Kuo, 2021) work that are

260   not reflected in the COM analytical work (model).

261
Figure 4: Simulation result for step up when the entire step energy and gravity work is provided by a pre-emptive push-off: with
step-up amplitude increase (A) the mid-transition velocity angle change (γ) increases, (B) as the required push-off increases from
nominal magnitude to maximum, the collision declines to zero, (C) the analytical rate of recovery increases. The increase of rate
of recovery is because of the decrease in the heel-strike collision dissipation. At maximum push-off impulse, the model predicts
no dissipation and as such the entire step's energy is transferred to the next step with the makeup needed for the gravity work.

Figure 5: Simulation result for the step down when the entire step energy and gravity work is provided by a pre-emptive push-off
and conversion of the gravity potential energy: with step-down amplitude increase (A) the mid-transition velocity angle change
(γ) declines, (B) as the required push-off decrease from nominal magnitude to zero, the collision reaches its maximum, (C) the
analytical rate of recovery also decreases. Beyond the maximum collision impulse, the model predicts the walker's speed increases
beyond the prescribed average speed.

We analyzed the COM power component trajectories derived from uneven experimental data (Hosseini-

Yazdi Seyed-Saleh, 2024) to calculate the step-averaged positive, negative, push-off, and collision work

values for walking speeds ranging from $0.8 \, \mathrm{m.s^{-1}}$ to $1.6 \, \mathrm{m.s^{-1}}$ on a smooth surface (even terrain). The

trajectories were adjusted to correct for random calibration biases, and single support phase positive

(rebound) and negative (preload) works were subsequently calculated (Hosseini-Yazdi & Bertram, 2024).

Figure 6: The COM power trajectory during a stride is illustrated, with the power contribution of the opposite leg represented by
a dashed line. Each stance begins with a heel-strike, which exerts a collision impulse on the COM. Following the initial double
support phase, gait transitions into a single support phase (rebound and preload). In the late stance phase, the trailing leg exerts
a push-off impulse during toe-off. The mechanical work for each phase can be determined by integrating the corresponding power
trajectory over time.

Based on heel-strike collision dissipation, the modified rate of recovery consistently declined from 82.5%

to 51.5%, closely mirroring model predictions but at a substantially faster rate. Analyzing the COM work

components revealed a walking speed threshold below which push-off work exceeded subsequent heel-

strike collision work. This surplus of positive energy suggests a COM speed increase beyond the prescribed

walking speed. Since total positive and negative step works were balanced and the average prescribed

speed was maintained, the extra mechanical energy post-step transition must have dissipated during the

subsequent single support phase.

Examining single support mechanical works indicated net negative work for walking speeds below the

threshold. Beyond the threshold speed, a net mechanical energy deficit was observed, which was

compensated by net positive single support work post-step transition. Consequently, we adjusted step

dissipation by incorporating net single support negative work into the step transition dissipation (collision).

This adjustment showed that the rate of recovery increased for walking speeds below the threshold, rising

from 48.6% to 59.4%, with a maximum observed at v = 1.21 m.s^{-1}. Beyond this speed, the rate of recovery

declined to 51.5% (Figure 7).

Figure 7: (A) The COM work components derived from the experimental data (Hosseini-Yazdi Seyed-Saleh, 2024) reveal walking
speeds where step transition push-off exceeds the associated step collision. This surplus mechanical energy is dissipated during
the single support phase, as indicated by the net negative single support work (Rebound – Preload). (B) When only step transition
collision dissipation work is considered for the rate of recovery calculation, the trend resembles that of the powered simple
walking model, showing a consistent decline. (C) Incorporating single support dissipation of excess step transition work (push-off)
into the rate of recovery calculation reveals an adjusted trajectory with a maximum point at v = 1.21 $m.s^{-1}$. This speed
corresponds to the point where net single support work is zero.

Discussion:

In this study, we propose a modified definition for the rate of recovery based on a powered simple walking

model (Kuo, 2002). This metric quantifies the proportion of a step's total energy that is transferred to the

subsequent step (Cavagna et al., 1977). Energy dissipated during this transition is compensated by the

active work exerted on the COM at the start of the next step (Cavagna et al., 1977; Donelan et al., 2002b).

Unlike earlier definitions, which suggests that energy dissipation stems from an incomplete conversion

between potential and kinetic energy (Cavagna et al., 1977), our approach attributes the dissipation to the

active negative work performed during the step (Donelan et al., 2002a, 2002b; Kuo, 2002). This reflects

the deviation from conservative inverted pendulum motion during the step-to-step transition or COM

modulation during the single support phase (Kuo, 2002; Kuo et al., 2005).

Contrary to the original definition, which posited a maximum rate of recovery at a specific walking velocity

(v ~ 1.2 m. s^{-1} or 4.3 km. hr^{-1})(Cavagna et al., 1977), our modified definition reveals a nearly linear

decline in rate of recovery with increasing speed for nominal walking. This decrease occurs because

collision impulse is directly proportional to walking velocity ($co{\sim}v_{ave}$) (Kuo, 2002), leading to energy

dissipation proportional to the square of velocity ($w_{co}{\sim}v_{ave}^2$). As a result, this method cannot predict

preferred walking speeds. It is because the powered simple walking model (Kuo, 2002) assumes that the

negative and positive works during step transitions are optimal and equal for a nominal gait. In contrast,

the COM work trajectories (Hosseini-Yazdi Seyed-Saleh, 2024) reveal an imbalance in step transition work,

which is regulated during the subsequent single support phase (net single support work, Figure 7A).

Consequently, we consider dissipation from both step transition and the subsequent single support phase,

when net work is negative, to calculate the rate of recovery. The walking speed associated with the

maximum rate of recovery closely aligns with the preferred or self-selected walking speed on even terrain

(Gast et al., 2019; Hosseini-Yazdi & Bertram, 2024; Ralston, 1958). The lower rates of recovery observed in

the experimental data suggest that humans face greater mechanical dissipation during real walking than

the powered simple walking model (Kuo, 2002) accounts for. Therefore, this implies that humans must

perform a greater mechanical work to maintain their gait with energetic consequences.

The original method for calculating the rate of recovery reported values ranging from approximately 50%

to 70% for walking speeds of 0.8 m. s^{-1} (2.9 km. hr^{-1}) to 1.6 m. s^{-1} (5.8 km. hr^{-1}) (Cavagna et al., 1976).

Thus, the modified model demonstrates considerably higher rates of recovery (ROR > 80%) for optimal

pre-emptive push-offs, indicating that most of the energy from the previous step is effectively transferred

to the next. This is attributed to the influence of the pre-emptive push-off, which limits heel-strike

collisions (Adamczyk & Kuo, 2009; Hosseini-Yazdi & Bertram, 2024). However, when the push-off is

suboptimal, post step transition, additional active mechanical work must be exerted, often involving hip

torque (active rebound work) (Donelan et al., 2002a; Hosseini-Yazdi & Bertram, 2024; Kuo, 2002), or

delayed push-offs (Darici et al., 2018). This increases heel-strike dissipation (Hosseini-Yazdi & Bertram,

2024), almost halving the recovery rate when heel-strike happens first. The COM push-off and collision

work trajectories indicate a non-optimal push-off, except for one speed only, which increases the total step

dissipation. This results in lower than originally proposes (Cavagna et al., 1976) rates of recovery (ROR) for

the modified model based on experimental data.

Visual information about terrain is suggested to be crucial for selecting appropriate footholds (Matthis et

al., 2018). It is proposed that vision about the coming terrain (lookahead) enables more efficient potential-

to-kinetic energy conversions and reduces the active work requirements (Hosseini-Yazdi Seyed-Saleh,

2024; Matthis et al., 2017; Matthis & Fajen, 2013). On the other hand, restricted lookahead is proposed to

lead to higher collision energy dissipations (Hosseini-Yazdi Seyed-Saleh, 2024; Matthis & Fajen, 2013).

Hence, we predict lower rates of recovery for walking with restricted lookahead. Restricted lookahead

might also increase mechanical work in the lateral direction as a function of step width (Hosseini-Yazdi

Seyed-Saleh, 2024; Voloshina et al., 2013), although this component may remain small (Bauby & Kuo,

2000; Donelan et al., 2004), it further elevates the COM active work.

The elevated metabolic costs observed in older adults' walking (Das Gupta et al., 2019) can be linked to

age-related muscular changes (Benjuya et al., 2004; Volpi et al., 2004) and altered walking patterns

(Skiadopoulos et al., 2020). Given that COM work is a proxy for walking energetics (Donelan et al., 2002a),

older adults are also expected to exhibit lower rates of recovery, consistent with their higher energy costs.

For uneven walking, the modified rate of recovery exhibits a high variability. On randomly uneven terrains,

the analytical average recovery rate (~82%) approximates that of even nominal walking (~85%) at a similar

speed ($v_{ave} = 1.25 \, \mathrm{m.s}^{-1}$). However, uneven walking is energetically more demanding (Pandolf et al.,

1976), as reflected in greater mechanical work (Hosseini-Yazdi & Kuo, 2024; Voloshina et al., 2013). During

the uneven walking, the proposed suboptimal timing of pre-emptive push-offs must increase the reliance

on the subsequent stance-phase rebound work, which leads to amplified total active mechanical work

performance and thus projects a lower rate of recovery (Darici et al., 2018, 2020).

In summary, human walking may approximate inverted pendulum motion during single support phases

(Donelan et al., 2002a; Kuo et al., 2005), but significant deviations occur during double support phases

(Donelan et al., 2002a, 2002b; Kuo et al., 2005). These deviations result in considerable mechanical costs

during step-to-step transitions (Donelan et al., 2002a). The modified rate of recovery emphasizes the

mechanical and metabolic efficiency of pre-emptive push-offs, highlighting their critical role in energy

conservation. Unlike the original definition of the rate of recovery (Cavagna et al., 1977, 1976), our

analytical model predicts a declining trend. However, based on the experimental data and our adjusted

definition, we observe a walking speed at which the rate of recovery reaches its maximum. This speed

aligns closely with reported human self-selected or optimal walking speeds (Cavagna et al., 1976; Gast et

al., 2019; Hosseini-Yazdi & Bertram, 2024; Ralston, 1958). As COM work explains the majority of walking

energetics (Donelan et al., 2002a), we anticipate that any walking conditions associated with the elevated

energetics will coincide with reduced rates of recovery. Examples include walking with restricted

lookahead or on uneven terrain. Furthermore, since the analytical COM work does not account for other

costs or dissipations, such as soft tissue or peripheral work, we also expect to observe rate of recovery

rates that are lower than those predicted by analytical models. Developing a sound metric for the rate of

recovery is particularly significant for understanding gait mechanics, assessing mobility in populations such

as the elderly or those with impairments, guiding rehabilitation, and optimizing prosthetic designs.

Additionally, ROR is influenced by factors like walking speed, terrain, and load, making it a valuable tool

for evaluating walking performance and efficiency in both clinical and everyday settings.

References:

Adamczyk, P. G., & Kuo, A. D. (2009). Redirection of center-of-mass velocity during the step-to-step

transition of human walking. *The Journal of Experimental Biology*, *212*(Pt 16), 2668–2678.

https://doi.org/10.1242/jeb.027581

Bauby, C. E., & Kuo, A. D. (2000). Active control of lateral balance in human walking. *Journal of*

Biomechanics, *33*(11), 1433–1440. https://doi.org/10.1016/s0021-9290(00)00101-9

Benjuya, N., Melzer, I., & Kaplanski, J. (2004). Aging-induced shifts from a reliance on sensory input to

muscle cocontraction during balanced standing. *The Journals of Gerontology. Series A, Biological*

Sciences and Medical Sciences, *59*(2), 166–171. https://doi.org/10.1093/gerona/59.2.m166

Cavagna, G. A., Heglund, N. C., & Taylor, C. R. (1977). Mechanical work in terrestrial locomotion: Two

basic mechanisms for minimizing energy expenditure. *The American Journal of Physiology*,

233(5), R243-261. https://doi.org/10.1152/ajpregu.1977.233.5.R243

Cavagna, G. A., Thys, H., & Zamboni, A. (1976). The sources of external work in level walking and running.

The Journal of Physiology, *262*(3), 639–657. https://doi.org/10.1113/jphysiol.1976.sp011613

Darici, O., & Kuo, A. D. (2023). Humans plan for the near future to walk economically on uneven terrain.

Proceedings of the National Academy of Sciences, *120*(19), e2211405120.

https://doi.org/10.1073/pnas.2211405120

Darici, O., Temeltas, H., & Kuo, A. D. (2018). Optimal regulation of bipedal walking speed despite an

unexpected bump in the road. *PLOS ONE*, *13*(9), e0204205.

https://doi.org/10.1371/journal.pone.0204205

Darici, O., Temeltas, H., & Kuo, A. D. (2020). Anticipatory Control of Momentum for Bipedal Walking on

Uneven Terrain. *Scientific Reports*, *10*(1), 540. https://doi.org/10.1038/s41598-019-57156-6

Das Gupta, S., Bobbert, M. F., & Kistemaker, D. A. (2019). The Metabolic Cost of Walking in healthy young

and older adults – A Systematic Review and Meta Analysis. *Scientific Reports*, *9*(1), 9956.

https://doi.org/10.1038/s41598-019-45602-4

Donelan, J. M., Kram, R., & Kuo, A. D. (2002a). Mechanical work for step-to-step transitions is a major

determinant of the metabolic cost of human walking. *The Journal of Experimental Biology*,

205(Pt 23), 3717–3727. https://doi.org/10.1242/jeb.205.23.3717

Donelan, J. M., Kram, R., & Kuo, A. D. (2002b). Simultaneous positive and negative external mechanical

work in human walking. *Journal of Biomechanics*, *35*(1), 117–124.

https://doi.org/10.1016/s0021-9290(01)00169-5

Donelan, J. M., Shipman, D. W., Kram, R., & Kuo, A. D. (2004). Mechanical and metabolic requirements

for active lateral stabilization in human walking. *Journal of Biomechanics*, *37*(6), 827–835.

https://doi.org/10.1016/j.jbiomech.2003.06.002

Gast, K., Kram, R., & Riemer, R. (2019). Preferred walking speed on rough terrain; is it all about

energetics? *Journal of Experimental Biology*, jeb.185447. https://doi.org/10.1242/jeb.185447

Griffin, T. M., Roberts, T. J., & Kram, R. (2003). Metabolic cost of generating muscular force in human

walking: Insights from load-carrying and speed experiments. *Journal of Applied Physiology*,

95(1), 172–183. https://doi.org/10.1152/japplphysiol.00944.2002

Hosseini-Yazdi Seyed-Saleh. (2024). *Energetics and Biomechanics of Uneven Walking for Young and Older*

Adults [University of Calgary]. https://prism.ucalgary.ca/server/api/core/bitstreams/be2fa66b-

26a2-4421-9d30-dfcc55dcfb35/content

Hosseini-Yazdi, S.-S., & Bertram, J. E. (2024). *Estimating the Preferred Walking Speeds Based on the*

Center of Mass Work Analysis. https://doi.org/10.1101/2024.07.16.603701

Hosseini-Yazdi, S.-S., & Kuo, A. D. (2024). *The energetic cost of human walking as a function of uneven*

terrain amplitude. https://doi.org/10.1101/2024.11.08.622353

Kuo, A. D. (2001). A simple model of bipedal walking predicts the preferred speed-step length

relationship. *Journal of Biomechanical Engineering*, *123*(3), 264–269.

https://doi.org/10.1115/1.1372322

Kuo, A. D. (2002). Energetics of Actively Powered Locomotion Using the Simplest Walking Model. *Journal*

of Biomechanical Engineering, *124*(1), 113–120. https://doi.org/10.1115/1.1427703

Kuo, A. D., Donelan, J. M., & Ruina, A. (2005). Energetic Consequences of Walking Like an Inverted

Pendulum: Step-to-Step Transitions: *Exercise and Sport Sciences Reviews*, *33*(2), 88–97.

https://doi.org/10.1097/00003677-200504000-00006

Matthis, J. S., Barton, S. L., & Fajen, B. R. (2017). The critical phase for visual control of human walking

over complex terrain. *Proceedings of the National Academy of Sciences*, *114*(32).

https://doi.org/10.1073/pnas.1611699114

Matthis, J. S., & Fajen, B. R. (2013). Humans exploit the biomechanics of bipedal gait during visually

guided walking over complex terrain. *Proceedings of the Royal Society B: Biological Sciences*,

280(1762), 20130700. https://doi.org/10.1098/rspb.2013.0700

Matthis, J. S., Yates, J. L., & Hayhoe, M. M. (2018). Gaze and the Control of Foot Placement When

Walking in Natural Terrain. *Current Biology*, *28*(8), 1224-1233.e5.

https://doi.org/10.1016/j.cub.2018.03.008

Pandolf, K. B., Haisman, M. F., & Goldman, R. F. (1976). Metabolic energy expenditure and terrain

coefficients for walking on snow. *Ergonomics*, *19*(6), 683–690.

https://doi.org/10.1080/00140137608931583

Ralston, H. J. (1958). Energy-speed relation and optimal speed during level walking. *Internationale*

Zeitschrift Für Angewandte Physiologie Einschliesslich Arbeitsphysiologie, *17*(4), 277–283.

https://doi.org/10.1007/BF00698754

Skiadopoulos, A., Moore, E. E., Sayles, H. R., Schmid, K. K., & Stergiou, N. (2020). Step width variability as

a discriminator of age-related gait changes. *Journal of NeuroEngineering and Rehabilitation*,

17(1), 41. https://doi.org/10.1186/s12984-020-00671-9

Van Der Zee, T. J., & Kuo, A. D. (2021). Soft tissue deformations explain most of the mechanical work

variations of human walking. *Journal of Experimental Biology*, *224*(18), jeb239889.

https://doi.org/10.1242/jeb.239889

Voloshina, A. S., Kuo, A. D., Daley, M. A., & Ferris, D. P. (2013). Biomechanics and energetics of walking on

uneven terrain. *Journal of Experimental Biology*, jeb.081711.

https://doi.org/10.1242/jeb.081711

Volpi, E., Nazemi, R., & Fujita, S. (2004). Muscle tissue changes with aging. *Current Opinion in Clinical*

Nutrition and Metabolic Care, *7*(4), 405–410.

https://doi.org/10.1097/01.mco.0000134362.76653.b2

Zelik, K. E., & Kuo, A. D. (2010). Human walking isn't all hard work: Evidence of soft tissue contributions

to energy dissipation and return. *Journal of Experimental Biology*, *213*(24), 4257–4264.

https://doi.org/10.1242/jeb.044297

468