A Powered Simple Walking Model Modifies the Rate of Recovery Definition: Human Walking Deviates Drastically from Pendular Motion During the Double Support Phase

Seyed-Saleh Hosseini-Yazdi[1,2]

[1]Department of Biomedical Engineering, Schulich School of engineering, University of Calgary, AB, Canada
[2]Human Performance Laboratory, Faculty of Kinesiology, University of Calgary, AB, Canada

Conflict of Interest: None

Correspondence Address:

Seyed-Saleh Hosseini-Yazdi
Biomedical Engineering Department, Schulich School of Engineering, University of Calgary
2500 University Dr NW, Calgary AB T2N1N4

Phone: 403 402 6005
Email: seyedsaleh.hosseiniy@ucalgary.ca

Abstract:

This study proposes a modified definition of the original rate of recovery (ROR) in human walking, derived from a powered simple walking model. The metric captures the proportion of energy transferred from one step to the next by incorporating step transition mechanical dissipation. Our findings show that the modified ROR decreases nearly linearly with increasing walking speed on even terrain due to collision impulses scaling with velocity ($co \sim v_{ave}$) and energy dissipation scaling quadratically ($w_{co} \sim v_{ave}^2$). For nominal even walking at $1.25 \, \mathrm{m. \, s^{-1}}$, the analytical ROR was 85%, depicting higher rates than previously proposed. Experimental data, however, is expected to show lower ROR values due to additional energy dissipation factors, such as soft tissue or peripheral work that are not reflected in the analytical model. For uneven terrains with step height variations of ±0.036 m, the average ROR was 82%, suggesting that a completely random uneven terrain may be analytically approximated by even walking. However, the elevated energetic demands of uneven walking, primarily due to suboptimal pre-emptive push-offs (timing or magnitude), must further decrease the ROR. Similarly, other walking conditions associated with increased metabolic costs, such as aging or when vision about the coming terrain is denied (restricted lookahead), are also expected to result in reduced RORs. These findings underscore the critical role of optimal pre-emptive push-offs and proper foot placement in minimizing collision energy dissipation and enhancing walking efficiency. Therefore, having an appropriate metric for ROR also may be crucial for understanding gait mechanics, assessing mobility in populations with impairments, guiding rehabilitation, and optimizing prosthetic designs.

Word Count:

Keywords: rate of recovery, walking energetics, center of mass work, step-to-step transition, push-off, collision dissipation

Introduction:

A substantial portion of walking metabolic energy is used to perform mechanical work on the Center of Mass (COM), propelling it forward and compensating for mechanical energy losses [1]. Consequently, conserving mechanical energy during walking can also reduce the associated metabolic cost [1]. One specific instance of mechanical energy loss occurs during the transition between steps, where the heel-strike dissipates energy by performing active negative mechanical work, referred to as "collision" [2], [3]. The rate of recovery (ROR), defined as the fraction of energy transferred from one step to the next [4]. It is a key metric in walking biomechanics that measures the efficiency of energy transfer between steps, reflecting how well mechanical energy is conserved and reused during gait. A higher ROR indicates a better walking economy, reduced metabolic costs, and efficient coordination of passive (e.g., tendon elasticity) and active (e.g., muscle contractions) walking mechanisms. Since human walking is not always conservative, ROR may be redefined to account for step-to-step transition active energy dissipation. In this framework, the legs' external work compensates for the energy lost during heel-strike [1], [2]. Factors such as age, state of lookahead, walking speed, and terrain conditions may also influence heel-strike energy losses, impacting the rate of recovery.

Human locomotion is hypothesized to mimic pendulum and spring-like mechanics to minimize active muscle work [4]. Specifically, the single support phase of walking aligns with the motion of an inverted pendulum [3]. In an idealized scenario with no energy dissipation, a walker starting with sufficient initial energy would require no external energy input. Thus, human walking primarily involves converting potential and kinetic energy within a conservative system [4].

According to Cavagna et al. [4], [5], walkers perform works against gravity (W_v) to lift the COM and to accelerate it forward (W_f). When potential and kinetic energies are completely out of phase, the mechanical energy transitions seamlessly, with no dissipation. In this state, gravitational potential energy

is converted into kinetic energy, propelling the walker forward. However, when these energies become aligned, energy exchange is disrupted, resulting in dissipation. Humans then perform work (W_{ext}) to compensate for this energy loss. This assumption hinges on the notion that human walking always resembles inverted pendulum mechanics and incurs no energy waste departing from a pendular motion (Figure 1A).

Donelan et al. [6], however, proposed that humans simultaneously perform positive and negative work during step-to-step transitions. This suggests a significant deviation from the inverted pendulum model, as the COM mechanics transition to the next stance (Figure 1B). Donelan et al. [1] further argued that these simultaneous COM works are mechanically costly and serve as a rough indicator of walking energetics. Post step transition, the human walking tends to resemble pendular motion again [1], [3].

When considering the right and left legs as separate actuators exerting toe-off (push-off) and heel-strike (collision) impulses [3], it becomes reasonable to investigate their individual effects on the COM. Similar to other mechanical actuators, the work of each leg is determined by the force applied and the corresponding displacement. Thus, the mechanical work of each leg cannot mathematically cancel the other's work. While the net effect on the COM may reflect the resultant force induced, the independent work of each leg incurs its own metabolic cost [7].

Both toe-off (push-off) and heel-strike (collision) impulses generate upward motions on the COM in the frontal plane, but their sagittal plane effects differ. The toe-off (push-off) impulse propels the pelvis forward, while the heel-strike (collision) impulse opposes the forward progression, partially wasting momentum and mechanical energy (Figure 1C & D) [1], [2], [6]. Consequently, the toe-off (push-off) impulse contributes to forward momentum, whereas the heel-strike (collision) impulse results in energy loss [1], [2].

A simple powered walking model demonstrates the independent contributions of the leading and trailing legs during step transitions [2]. For a given walking speed, it predicts the active work required (push-off work) for optimal steady-state walking, where active work matches dissipation. Pre-emptive push-off is hypothesized to limit the magnitude of subsequent collision [2], [3]. When heel-strike occurs earlier than expected [8], the pre-emptive push-off can only partially mitigate the resulting collision [9]. Hence, to maintain steady walking, additional positive mechanical energy is required during the subsequent stance phase [2], [10], [11]. Suboptimal push-off ($po_{sub} < po_{opt}$) results in increased dissipation and a reduced amount of energy transferred to the subsequent step.

Walking energetics increase with terrain complexity [11], [12], [13] and age [11], [14]. Restricted lookahead might also impair the ability to select appropriate footholds, limiting the benefits of human walking dynamics [15]. It is shown that walking with a restricted lookahead also coincides with elevated walking energetics [11]. Since step mechanical work provides a rough approximation of walking energetics [1], it is reasonable to infer that any walking regime requiring increased metabolic rates corresponds to higher active mechanical work performance, and as such lower rates of recovery.

This study redefines the rate of recovery based on heel-strike energy dissipation. We develop a simulation to derive analytical rates of recovery for nominal (optimal) walking across a range of walking speeds. The simulation is extended to scenarios with suboptimal push-off impulses ($po_{sub} < po_{opt}$) and cases where COM elevation changes; step-ups and step-downs (i.e. uneven walking). Without loss of generality for uneven walking, we examine a scenario where pre-emptive push-off provides the entire step transition energy and compensates for work against gravity.

New Definition for Rate of Recovery:

According to a powered simple walking model [2], the active push-off (po) is applied pre-emptively to the COM to mechanically energize the step-to-step transition [8]. This action compensates for the dissipation

caused by the heel-strike collision, which occurs after the push-off. Consequently, the required external work (W_{ext}) is assumed to offset the energy lost during the heel-strike [4]. Considering 'u' as the transition impulse, its associated work is calculated as $\frac{1}{2}u^2$ [2], [8]. We count the total mechanical energy of the human body as the sum of its potential and kinetic energies ($E_{tot} = E_P + E_K$). Assuming that the lowest elevation of the COM during the stance phase as the reference for gravitational potential energy ($E_P = 0$), the total energy at the end of the stance phase corresponds to the maximum kinetic energy ($E_{K\_max} = E_{tot}$, Figure 1E & F). As originally defined, the rate of recovery is given by [4]:

$$Rate\ of\ Recovery = \frac{E_{tot} - W_{ext}}{E_{tot}}$$

<div align="right">Eq. 1</div>

This equation quantifies the proportion of mechanical energy transferred from one step to the next. Since the system's total energy equals the maximum kinetic energy just before the step transition, the rate of recovery becomes:

$$Rate\ of\ Recovery = \frac{E_{K\_max} - W_{ext}}{E_{K\_max}}$$

<div align="right">Eq. 2</div>

Assuming the COM velocity just before the transition approximates the average walking velocity (v_{ave} in which $\vec{v}_{ave} = \vec{v}_f + \vec{v}_v$) [2], and w_{ext} represents the normalized external work per unit mass, the rate of recovery can be derived as:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - w_{ext}}{\frac{1}{2}v_{ave}^2}$$

<div align="right">Eq. 3</div>

To sustain a steady walk, the walker's energy must remain constant before and after the step-to-step transition. Denoting the velocity before and after the transition as v^- and v^+, respectively, steady walking implies, $|v^+| = |v^-| = v_{ave}$. With the kinetic energy conserved across the transition, the active work energy addition (W_{ext}) equals the heel-strike energy dissipation or collision work (W_{co}). Therefore, the rate of recovery can be further expressed as:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - w_{co}}{\frac{1}{2}v_{ave}^2}$$

<div align="right">Eq. 4</div>

Here, w_{co} represents the normalized energy loss due to the heel-strike collision.

Simulation based on a powered simple walking model:

The nominal push-off impulse for a given walking speed is expressed as $po = v_{ave} \cdot \tan \alpha$ where '2α'

represents the angle between the leading and trailing legs at the point of transition [2]. Consequently, the

nominal push-off work becomes $w_{po} = \frac{1}{2}v_{ave}^2 \cdot \tan^2 \alpha$ [2]. Assuming $w_{co} = w_{po}$ and $w_{ext} = w_{co}$, the rate

of recovery is:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - \frac{1}{2}v_{ave}^2 \cdot \tan^2 \alpha}{\frac{1}{2}v_{ave}^2} = 1 - \tan^2 \alpha$$

<div align="right">Eq. 5</div>

For small angles, the approximation $\tan \alpha \sim \alpha$ holds, leading to $po = v_{ave} \cdot \alpha$ and $w_{po} = \frac{1}{2}v_{ave}^2 \cdot \alpha^2$.

Assuming a unit leg length, the step length (s) becomes proportional to 2α [2], [9]. Since step length

follows a power law with walking speed [9]; $s \sim v^{0.42}$, yielding $2\alpha = c \cdot v^{0.42}$ and $\alpha = \frac{1}{2}c \cdot v^{0.42}$.

Substituting 'α' into Eq. 5 with $\tan \alpha \sim \alpha$:

$$Rate\ of\ Recovery = 1 - \alpha^2 = 1 - \frac{1}{4}c^2 \cdot v_{ave}^{0.84}$$

<div align="right">Eq. 6</div>

This analytical expression suggests that the rate of recovery decreases nearly linearly with walking speed.

Applying the principles of the powered simple walking model to a suboptimal push-off (po_{sub}, Figure 1G)

[2] the mid-transition velocity (v^0) forms an angle (γ) with the COM velocity before transition (v^-) which

depends on the induced push-off impulse magnitude: $\gamma = \arctan(\frac{po_{sub}}{v_{ave}})$. Since $v^- \sim v_{ave}$ [2], the

transition collision impulse (co) becomes:

$$\begin{cases} \dfrac{co}{v^0} = \sin(2\alpha - \gamma) \\ \dfrac{v_{ave}}{v^0} = \cos\gamma \end{cases} \rightarrow co = v_{ave}\,\dfrac{\sin(2\alpha - \gamma)}{\cos\gamma}$$

Eq. 7

The normalized collision work is $w_{co} = 0.5co^2$ [2], [8], and the modified rate of recovery is:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - w_{co}}{\frac{1}{2}v_{ave}^2} = 1 - \left(\frac{\sin(2\alpha - \gamma)}{\cos\gamma}\right)^2$$

Eq. 8

Using small angle approximations for 'α' and 'γ':

$$Rate\ of\ Recovery = 1 - \left(2\alpha - \frac{po_{sub}}{v_{ave}}\right)^2 = 1 - \left(c.v_{ave}^{0.42} - \frac{po_{sub}}{v_{ave}}\right)^2$$

Eq. 9

This result shows that the rate of recovery becomes a nonlinear function of both suboptimal push-off magnitude and the average walking speed.

For uneven terrain with a step-up, maintaining the average walking speed (v_{ave}) at mid-stance requires the post-transition COM kinetic energy to also account for the work against gravity. The post-transition velocity (v^+) must therefore satisfy (Figure 1H):

$$\frac{1}{2}v^{+2} - \frac{1}{2}v_{ave}^2 = g.\Delta h \rightarrow v^+ = \sqrt{v_{ave}^2 + 2g.\Delta h}$$

Eq. 10

If the entire uneven step energy is provided by a pre-emptive push-off, then:

$$\begin{cases} \dfrac{v^+}{v^0} = \cos(2\alpha - \gamma) \\ \dfrac{v_{ave}}{v^0} = \cos\gamma \end{cases} \rightarrow v^+ = v_{ave}\,\dfrac{\cos(2\alpha - \gamma)}{\cos\gamma} \rightarrow \sqrt{v_{ave}^2 + 2g.\Delta h} = v_{ave}\,\dfrac{\cos(2\alpha - \gamma)}{\cos\gamma}$$

Eq. 11

The mid-transition velocity angle change (γ) must be determined numerically for a given walking condition. The uneven step collision impulse becomes:

$$\frac{co}{v^0} = \sin(2\alpha - \gamma) \rightarrow co = v_{ave}\,\frac{\sin(2\alpha - \gamma)}{\cos\gamma}$$

Eq. 12

Figure 1: Schematics showing the step-to-step transition during even walking: (A) pendular walking model with rigid legs in which the step-to-step transition is instantaneous (no double support phase), (B) human walking demonstrates a double support phase in which humans switch from one inverted pendulum to another, (C) push-off and collision impulses have similar effects in the vertical direction, (D) push-off impulse adds to the COM mechanical energy in the progression direction while collision impulse reduces the momentum, (E and F) In nominal steady walking, the push-off and collision work, and pre (v^-) and post transition (v^+) speeds are equal, the pre transition velocity may be approximated by v_{ave}, (G) if the pre-emptive push-off is less than optimal (suboptimal), the magnitude of the subsequent collision impulse grows and the post transition speed declines, (H) when the total step transition and gravity works are provided by the pre-emptive push-off impulse, optimal uneven walking takes place.

Thus, the rate of recovery for an uneven step can be derived similar to even walking when a suboptimal push-off is applied, yet with $\gamma > \alpha$. Using the small angle approximation, the rate of recovery for uneven walking becomes: $1 - (2\alpha - \gamma)^2$. For a step-down, the process is similar, with Δh being negative. Here, the potential energy converts to kinetic energy, increasing momentum, and the required push-off magnitude decreases as the step-down amplitude increases.

Results:

We redefined the rate of recovery based on step-to-step mechanical work dissipation [1], focusing on scenarios where the COM trajectory significantly deviates from conservative inverted pendulum motion. Originally, the rate of recovery was defined as the percentage of total mechanical energy carried over from one step to the next through conversion of potential and kinetic energies [4]. Nevertheless, we assumed that the external work equates to heel-strike energy dissipation, enabling us to analytically estimate the rate of recovery for various walking conditions using a simple powered walking model, whether the push-off was nominal or suboptimal [2].

The step length was estimated using an empirical power law for a given velocity [9][15]. As walking speed increased from 0.8 m. s^{-1} to 1.6 m. s^{-1}, the estimated step length increased from 0.61 m to 0.82 m (a 34.4% increase when the leg length is 1 m). Correspondingly, the analytical total energy of walking (COM kinetic energy just before transition) and the push-off work during the step-to-step transition increased significantly—by 400% (from 0.32 J. kg^{-1} to 1.28 J. kg^{-1}) and 733.3% (from 0.03 J. kg^{-1} to 0.22 J. kg^{-1}), respectively. However, the rate of recovery declined from 90.6% to 83.1% (an 8.3% decrease). The small angle approximation yielded a rate of recovery that was, on average, only 1.5% higher than the analytical rate (Figure 2).

For suboptimal push-offs, where push-off magnitudes varied from zero to nominal (velocity = 1.25 m. s^{-1}, $\alpha = 0.37$ rad), the mid-transition velocity angle relative to the pre-transition velocity (γ) increased from

zero to 0.37 rad. Simultaneously, the analytical collision impulse decreased from $0.84\,\mathrm{m.s^{-1}}$ to $0.49\,\mathrm{m.s^{-1}}$ (a 71.4% reduction), while analytical push-off work increased from zero to $0.12\,\mathrm{J.kg^{-1}}$ and collision work declined from $0.36\,\mathrm{J.kg^{-1}}$ to $0.12\,\mathrm{J.kg^{-1}}$ (a 66.7% reduction). The analytical rate of recovery increased from 54.5% to 84.9% (a 55.8% increase). The small angle approximation initially suggested a lower rate of recovery but exceeded the analytical trajectory when the suboptimal push-off impulse reached approximately 70% of the optimal push-off magnitude (Figure 3).

Figure 2: Summary of the analytic simulation for nominal walking across the given walking speed range: (A) As walking speed increases, the step length also increases (leg length = 1m). (B) The total mechanical energy of the walker, push-off work, and the magnitude of mechanical energy transferred from one step to the next (recovered energy or recovery) all rise. (C) While the dissipation rate increases, the rate of recovery declines. The dashed line represents the rate of recovery when a small angle approximation is employed.

For uneven walking (step-up), we assumed that optimal walking occurred when the entire step transition energy and the work required to overcome gravity were supplied by the pre-emptive push-off. As the step-up amplitude increased, the optimal angle of the mid-transition COM velocity change (γ) also increased. Simulations indicated that push-off magnitudes for step-up walking exceeded those for nominal even walking at the same speed but were constrained by the maximum inducible analytical magnitude ($v_{ave}.\tan 2\alpha$), where analytical collision became zero [2].

On average, the small angle approximation overestimated the analytical rate of recovery by only 1.3%. The analytical rate of recovery increased from 84.9% to 99.3% as step elevation changes varied from 0 m to 0.05 m, indicating that maximum push-off eliminated dissipation, allowing full transfer of the previous step's mechanical energy (Figure 4).

Figure 3: With a suboptimal push-off exertion ($v_{ave} = 1.25 \text{ m.s}^{-1}$), as the magnitude of the induced push-off increases (A) the mid-transition velocity angle change (γ) rises, (B) resulted collision impulse declines, (C) the associated collision work dissipation decreases, and (D) the modified rate of recovery for the suboptimal push-off elevates. The vertical dashed line depicts exerting 80% of the optimal push-off. The associated transition dissipation is $0.16 \text{ J} \cdot \text{kg}^{-1}$ and the estimated rate of recovery is 80%.

For step-down, the gravitational potential energy contributed to step transition work, reducing the required push-off as its amplitude increased. Simulations showed that for Δh = -0.036 m, no push-off was required, as gravitational potential energy fully compensated for the step transition energy, resulting in maximum collision energy dissipation. We terminated simulations when pre-emptive push-off reached zero, defining this as the maximum step-down amplitude. Beyond this threshold, analytical collision could not offset excess gravitational energy, and walkers could not sustain the average prescribed walking speed. When pre-emptive push-off was zero, the mid-transition COM velocity equaled the pre-transition speed ($\gamma = 0$). The rate of recovery decreased with greater step-down amplitudes, declining from 85% to 54% as collision dissipation increased from 0.12 J.kg^{-1} to 0.36 J.kg^{-1}. For even walking, the small angle

approximation overestimated the analytical rate, but the trajectories intersected, with the approximation underestimating recovery at the maximum step-down amplitude (Figure 5).

Discussion:

In this study, we propose a modified definition for the rate of recovery based on a powered simple walking model [2]. This metric quantifies the proportion of a step's total energy that is transferred to the subsequent step [4]. Energy dissipated during this transition is compensated by the active work exerted on the COM at the start of the next step [4], [6]. Unlike earlier definitions, which suggests that energy dissipation stems from an incomplete conversion between potential and kinetic energy [4], our approach attributes the dissipation to negative work performed during the heel strike [1], [2], [6]. This reflects the deviation from conservative inverted pendulum motion during the step-to-step transition [2], [3].

Contrary to earlier models, which posited a maximum rate of recovery at a specific walking velocity (v ~ 1.2 m.s^{-1} or 4.3 km.hr^{-1})[4], our modified definition reveals a nearly linear decline in recovery rates with increasing walking velocity for nominal walking. This decrease occurs because collision impulse is directly proportional to walking velocity ($co \sim v_{ave}$) [2], leading to energy dissipation proportional to the square of velocity ($w_{co} \sim v_{ave}^2$). As a result, this method cannot predict preferred walking speeds.

The original method for calculating the rate of recovery reported values ranging from approximately 50% to 70% for walking speeds of 0.8 m.s^{-1} (2.9 km.hr^{-1}) to 1.6 m.s^{-1} (5.8 km.hr^{-1}) [5]. Thus, the modified model demonstrates considerably higher rates of recovery (ROR > 80%) for optimal pre-emptive push-offs, indicating that most of the energy from the previous step is effectively transferred to the next. This is attributed to the influence of the pre-emptive push-off, which limits heel-strike collisions [16], [17]. However, when the push-off is suboptimal, post step transition, additional active mechanical work must be exerted, often involving hip torque (active rebound work) [1], [2], [17], or delayed push-offs [8]. This increases heel-strike dissipation [17], almost halving the recovery rate when heel-strike happens first.

Figure 4: Simulation result for step up when the entire step energy and gravity work is provided by a pre-emptive push-off: with step-up amplitude increase (A) the mid-transition velocity angle change (γ) increases, (B) as the required push-off increases from nominal magnitude to maximum, the collision declines to zero, (C) the analytical rate of recovery increases. The increase of rate of recovery is because of the decrease in the heel-strike collision dissipation. At maximum push-off impulse, the model predicts no dissipation and as such the entire step's energy is transferred to the next step with the makeup needed for the gravity work.

Figure 5: Simulation result for the step down when the entire step energy and gravity work is provided by a pre-emptive push-off and conversion of the gravity potential energy: with step-down amplitude increase (A) the mid-transition velocity angle change (γ) declines, (B) as the required push-off decrease from nominal magnitude to zero, the collision reaches its maximum, (C) the analytical rate of recovery also decreases. Beyond the maximum collision impulse, the model predicts the walker's speed increases beyond the prescribed average speed.

For experimental data analysis, the collision work at heel-strike can be estimated by integrating COM power trajectories during the collisions phase (Figure 6) [3], [11], [18]. Using this approach, the rate of recovery can be expressed as:

$$Rate\ of\ Recovery = \frac{\frac{1}{2}v_{ave}^2 - \frac{W_{co\_exp}}{M}}{\frac{1}{2}v_{ave}^2} = 1 - \frac{2\ W_{co\_exp}}{M.v_{ave}^2} \qquad \text{Eq. 13}$$

Figure 6: The COM power trajectory during a stride is illustrated, with the power contribution of the opposite leg represented by a dashed line. Each stance begins with a heel-strike, which exerts a collision impulse on the COM. Following the initial double support phase, gait transitions into a single support phase (rebound and preload). In the late stance phase, the trailing leg exerts a push-off impulse during toe-off. The mechanical work for each phase can be determined by integrating the corresponding power trajectory over time.

Here, 'M' is the subject's mass. We expect lower rates of recovery for experimental data due to additional dissipation, such as soft tissue [19] or peripheral [20] work that are not reflected in the COM analytical works.

Visual information about terrain is suggested to be crucial for selecting appropriate footholds [21]. It is proposed that vision about the coming terrain (lookahead) enables more efficient potential-to-kinetic energy conversions and reduces the active work requirements [11], [15], [22]. On the other hand, restricted lookahead is proposed to lead to higher collision energy dissipations [11], [15]. Hence, we predict lower rates of recovery for walking with restricted lookahead. Restricted lookahead might also increase mechanical work in the lateral direction as a function of step width [11], [13], although this component may remain small [23], [24], it further elevates the COM active work.

The elevated metabolic costs observed in older adults' walking [14] can be linked to age-related muscular changes [25], [26] and altered walking patterns [27]. Given that COM work is a proxy for walking energetics [1], older adults are also expected to exhibit lower rates of recovery, consistent with their higher energy costs.

For uneven walking, the modified rate of recovery exhibits a high variability. On randomly uneven terrains, the analytical average recovery rate (~82%) approximates that of even nominal walking (~85%) at a similar speed ($v_{ave} = 1.25 \, \text{m.s}^{-1}$). However, uneven walking is energetically more demanding [12], as reflected in greater mechanical work [13], [18]. During the uneven walking, the proposed suboptimal timing of pre-emptive push-offs must increase the reliance on the subsequent stance-phase rebound work, which leads to amplified total active mechanical work performance and thus projects a lower rate of recovery [8], [28].

In summary, human walking may approximate inverted pendulum motion during single support phases [1], [3], but significant deviations occur during double support phases [1], [3], [6]. These deviations result in considerable mechanical costs during step-to-step transitions [1]. The modified rate of recovery emphasizes the mechanical and metabolic efficiency of pre-emptive push-offs, highlighting their critical role in energy conservation. As COM work explains the majority of walking energetics [1], we anticipate that any walking conditions associated with the elevated energetics will coincide with reduced rates of recovery. Examples include walking with restricted lookahead or on uneven terrain. Furthermore, since the analytical COM work does not account for other costs or dissipations, such as soft tissue or peripheral work, we also expect to observe rate of recovery rates that are lower than those predicted by analytical models. Developing a sound metric for the rate of recovery is particularly significant for understanding gait mechanics, assessing mobility in populations such as the elderly or those with impairments, guiding rehabilitation, and optimizing prosthetic designs. Additionally, ROR is influenced by factors like walking speed, terrain, and load, making it a valuable tool for evaluating walking performance and efficiency in both clinical and everyday settings.

References:

[1] J. M. Donelan, R. Kram, and A. D. Kuo, "Mechanical work for step-to-step transitions is a major determinant of the metabolic cost of human walking," *J. Exp. Biol.*, vol. 205, no. Pt 23, pp. 3717–3727, Dec. 2002, doi: 10.1242/jeb.205.23.3717.

[2] A. D. Kuo, "Energetics of Actively Powered Locomotion Using the Simplest Walking Model," *J. Biomech. Eng.*, vol. 124, no. 1, pp. 113–120, Feb. 2002, doi: 10.1115/1.1427703.

[3] A. D. Kuo, J. M. Donelan, and A. Ruina, "Energetic Consequences of Walking Like an Inverted Pendulum: Step-to-Step Transitions:," *Exerc. Sport Sci. Rev.*, vol. 33, no. 2, pp. 88–97, Apr. 2005, doi: 10.1097/00003677-200504000-00006.

[4] G. A. Cavagna, N. C. Heglund, and C. R. Taylor, "Mechanical work in terrestrial locomotion: two basic mechanisms for minimizing energy expenditure," *Am. J. Physiol.*, vol. 233, no. 5, pp. R243-261, Nov. 1977, doi: 10.1152/ajpregu.1977.233.5.R243.

[5] G. A. Cavagna, H. Thys, and A. Zamboni, "The sources of external work in level walking and running," *J. Physiol.*, vol. 262, no. 3, pp. 639–657, Nov. 1976, doi: 10.1113/jphysiol.1976.sp011613.

[6] J. M. Donelan, R. Kram, and A. D. Kuo, "Simultaneous positive and negative external mechanical work in human walking," *J. Biomech.*, vol. 35, no. 1, pp. 117–124, Jan. 2002, doi: 10.1016/s0021-9290(01)00169-5.

[7] T. M. Griffin, T. J. Roberts, and R. Kram, "Metabolic cost of generating muscular force in human walking: insights from load-carrying and speed experiments," *J. Appl. Physiol.*, vol. 95, no. 1, pp. 172–183, Jul. 2003, doi: 10.1152/japplphysiol.00944.2002.

[8] O. Darici, H. Temeltas, and A. D. Kuo, "Optimal regulation of bipedal walking speed despite an unexpected bump in the road," *PLOS ONE*, vol. 13, no. 9, p. e0204205, Sep. 2018, doi: 10.1371/journal.pone.0204205.

[9] A. D. Kuo, "A simple model of bipedal walking predicts the preferred speed-step length relationship," *J. Biomech. Eng.*, vol. 123, no. 3, pp. 264–269, Jun. 2001, doi: 10.1115/1.1372322.

[10] O. Darici and A. D. Kuo, "Humans plan for the near future to walk economically on uneven terrain," *Proc. Natl. Acad. Sci.*, vol. 120, no. 19, p. e2211405120, May 2023, doi: 10.1073/pnas.2211405120.

[11] Hosseini-Yazdi Seyed-Saleh, "Energetics and Biomechanics of Uneven Walking for Young and Older Adults," University of Calgary, Calgary, AB, Canada, 2024. [Online]. Available: https://prism.ucalgary.ca/server/api/core/bitstreams/be2fa66b-26a2-4421-9d30-dfcc55dcfb35/content

[12] K. B. Pandolf, M. F. Haisman, and R. F. Goldman, "Metabolic energy expenditure and terrain coefficients for walking on snow," *Ergonomics*, vol. 19, no. 6, pp. 683–690, Nov. 1976, doi: 10.1080/00140137608931583.

[13] A. S. Voloshina, A. D. Kuo, M. A. Daley, and D. P. Ferris, "Biomechanics and energetics of walking on uneven terrain," *J. Exp. Biol.*, p. jeb.081711, Jan. 2013, doi: 10.1242/jeb.081711.

[14] S. Das Gupta, M. F. Bobbert, and D. A. Kistemaker, "The Metabolic Cost of Walking in healthy young and older adults – A Systematic Review and Meta Analysis," *Sci. Rep.*, vol. 9, no. 1, p. 9956, Jul. 2019, doi: 10.1038/s41598-019-45602-4.

[15] J. S. Matthis and B. R. Fajen, "Humans exploit the biomechanics of bipedal gait during visually guided walking over complex terrain," *Proc. R. Soc. B Biol. Sci.*, vol. 280, no. 1762, p. 20130700, Jul. 2013, doi: 10.1098/rspb.2013.0700.

[16] P. G. Adamczyk and A. D. Kuo, "Redirection of center-of-mass velocity during the step-to-step transition of human walking," *J. Exp. Biol.*, vol. 212, no. 16, pp. 2668–2678, Aug. 2009, doi: 10.1242/jeb.027581.

[17] S.-S. Hosseini-Yazdi, "Center of Mass Work Components May Offer Estimates for Preferred Walking Speeds for Any Walking Conditions," Aug. 01, 2024. doi: 10.1101/2024.07.16.603701.

[18] S.-S. Hosseini-Yazdi and A. D. Kuo, "The energetic cost of human walking as a function of uneven terrain amplitude," Nov. 11, 2024. doi: 10.1101/2024.11.08.622353.

[19] K. E. Zelik and A. D. Kuo, "Human walking isn't all hard work: evidence of soft tissue contributions to energy dissipation and return," *J. Exp. Biol.*, vol. 213, no. 24, pp. 4257–4264, Dec. 2010, doi: 10.1242/jeb.044297.

[20] T. J. Van Der Zee and A. D. Kuo, "Soft tissue deformations explain most of the mechanical work variations of human walking," *J. Exp. Biol.*, vol. 224, no. 18, p. jeb239889, Sep. 2021, doi: 10.1242/jeb.239889.

[21] J. S. Matthis, J. L. Yates, and M. M. Hayhoe, "Gaze and the Control of Foot Placement When Walking in Natural Terrain," *Curr. Biol.*, vol. 28, no. 8, pp. 1224-1233.e5, Apr. 2018, doi: 10.1016/j.cub.2018.03.008.

[22] J. S. Matthis, S. L. Barton, and B. R. Fajen, "The critical phase for visual control of human walking over complex terrain," *Proc. Natl. Acad. Sci.*, vol. 114, no. 32, Aug. 2017, doi: 10.1073/pnas.1611699114.

[23] C. E. Bauby and A. D. Kuo, "Active control of lateral balance in human walking," *J. Biomech.*, vol. 33, no. 11, pp. 1433–1440, Nov. 2000, doi: 10.1016/s0021-9290(00)00101-9.

[24] J. M. Donelan, D. W. Shipman, R. Kram, and A. D. Kuo, "Mechanical and metabolic requirements for active lateral stabilization in human walking," *J. Biomech.*, vol. 37, no. 6, pp. 827–835, Jun. 2004, doi: 10.1016/j.jbiomech.2003.06.002.

[25] N. Benjuya, I. Melzer, and J. Kaplanski, "Aging-induced shifts from a reliance on sensory input to muscle cocontraction during balanced standing," *J. Gerontol. A. Biol. Sci. Med. Sci.*, vol. 59, no. 2, pp. 166–171, Feb. 2004, doi: 10.1093/gerona/59.2.m166.

[26] E. Volpi, R. Nazemi, and S. Fujita, "Muscle tissue changes with aging," *Curr. Opin. Clin. Nutr. Metab. Care*, vol. 7, no. 4, pp. 405–410, Jul. 2004, doi: 10.1097/01.mco.0000134362.76653.b2.

[27] A. Skiadopoulos, E. E. Moore, H. R. Sayles, K. K. Schmid, and N. Stergiou, "Step width variability as a discriminator of age-related gait changes," *J. NeuroEngineering Rehabil.*, vol. 17, no. 1, p. 41, Dec. 2020, doi: 10.1186/s12984-020-00671-9.

[28] O. Darici, H. Temeltas, and A. D. Kuo, "Anticipatory Control of Momentum for Bipedal Walking on Uneven Terrain," *Sci. Rep.*, vol. 10, no. 1, p. 540, Jan. 2020, doi: 10.1038/s41598-019-57156-6.