Center of Mass Work Analysis Estimates Preferred Walking Speeds for Varying Walking Conditions

Seyed-Saleh Hosseini-Yazdi[1,2]

[1]Department of Biomedical Engineering, Schulich School of engineering, University of Calgary, AB, Canada

[2]Human Performance Laboratory, Faculty of Kinesiology, University of Calgary, AB, Canada

Conflict of Interest: None

Correspondence Address:

Seyed-Saleh Hosseini-Yazdi

Biomedical Engineering Department, Schulich School of Engineering, University of Calgary

2500 University Dr NW, Calgary AB T2N1N4

Phone: 403 402 6005, Email: seyedsaleh.hosseiniy@ucalgary.ca

Abstract

This study investigates the role of optimal push-off impulses in minimizing the total mechanical work dissipation per step, aiming to achieve passive single support work performance for a variety of walking conditions. By optimizing push-offs to cover the entire step's energy demands, the single support work may become only storage and release of mechanical energy through tendons and tissues. Our simulations indicate that for each walking speed, there is an optimal push-off impulse that ensures energy balance without the need for additional energy input or dissipation during the subsequent single support phase in which the soft tissue dissipation is negligible, resulting in reduced total dissipation. For even terrain, the estimated preferred walking speeds align closely with literature values for young adults (~ 1.25 m. s^{-1}) and older adults (~ 1.10 m. s^{-1}) self-selected speeds, with a reduction observed for the restricted view of coming terrain (15%). For walking on uneven surfaces, terrain amplitude was shown to impact walking costs quadratically, with optimal speeds declining by approximately 20% per unit increase in terrain amplitude. Key findings include evidence that net single support work remains near zero when push-off optimally covers collision and gravity work, confirming the passive nature of single support work under this condition. We also observed that the preferred speeds for older adults tend to be 12-15% lower than for younger adults, likely due to biomechanical adaptations. Beyond certain terrain amplitudes, no preferred walking speed allowed fully passive single support work, highlighting a possible biomechanical threshold where ankle push-off alone becomes insufficient and hip torque compensation may be necessary. This approach provides a framework for estimating preferred walking speeds across different terrain amplitudes (continuous parameter), varying conditions and demographics, with potential applications in designing assistive devices and gait rehabilitation protocols that reduce metabolic cost through optimal mechanical work management.

Word Count:

Keywords: Optimal Push-Off Impulse, Passive Stance Work, Mechanical Work Minimization, Preferred Walking Speed, Uneven Terrain Locomotion

Introduction

One primary objective of walking is to minimize energy expenditure [1] while simultaneously achieving other task-specific goals [2]. Research suggests that energy expenditure is minimized when humans walk at a nominal or preferred walking speed (self-selected) [3]. The preferred walking speed is traditionally defined as the speed at which the cost of transport is minimized [4]; walking faster or slower than this speed results in increased energetic costs [5]. To determine an individual's average preferred walking speed based on energetics, subjects are often asked to walk at various velocities while their energy expenditure is measured [6]. The walking speed that coincides with the minimum of the resulting parabolic cost of transport trajectory is identified as the preferred walking speed [5]. In over ground free walking, the self-selected speed is naturally opted. This speed must reflect an optimal balance between energy expenditure and comfort for the individual [3]. Since it has been proposed that the active center of mass (COM) work during step-to-step transitions closely represents metabolic walking rates [7], a mechanical approach may also estimate preferred walking speed based on COM mechanical work.

It is hypothesized that walking economy is optimized when a pre-emptive push-off energizes gait progression [8]. The push-off redirects the COM velocity from the previous step upward, allowing the subsequent collision to adjust the COM velocity to match the new stance. In a properly timed pre-emptive push-off, the collision loss is minimized and is equal to the push-off work energy infusion (Figure 1A) [8], [9]. When the push-off is suboptimal, it only partially energizes the gait, leading to a greater collision dissipation at mid-transition to adjust the COM trajectory for the next step (Figure 1B). This leads to a reduced outcome velocity after the transition [8], necessitating additional positive mechanical work to sustain the gait. Otherwise, the COM speed will decline, and the gait may become unsustainable. This extra compensatory work likely occurs during the

single support phase positive work performance termed as rebound (Figure 1D) [9], [10].

Similarly, if push-off exceeds the subsequent heel-strike collision, the post-transition velocity

increases. Thus, to maintain the average velocity, energy dissipation during the subsequent step is

required. This dissipation must occur when the single support negative work happens (preload,

Figure 1D).

In nominal walking, it is proposed that single support work is passive, occurring through the

mechanical energy storage and release facilitated by tendons and other tissues [9], [11]. Thus, the

positive energy generated by the rebound phase must be absorbed during the preload (Figure 1D)

[9]. During the single support phase (rigid body), when the COM motion resembles an inverted

pendulum [12], The total work contributions of the leg joints have been shown to balance rebound

and preload in nominal walking with a minimal soft tissue dissipation [13]. To counteract deficits

from push-off and collision [10], if the rebound is to energize the COM progression, it must exceed

the preload; conversely, if dissipation is required, preload must exceed rebound. Hence, it is

plausible that walking deviates from the preferred regime when push-off and collision (i.e. walking

on an even surface or even walking), or rebound and preload magnitudes, are unequal.

Walking on an uneven substrate (uneven walking) presents a case where push-off may deviate

from the optimal pattern (Figure 1C). For example, heel strike may occur earlier than expected

[14], particularly in the absence of visual cues about upcoming terrain variations [15]. In such

cases, the collision occurs before the prior push-off fully adjusts the COM velocity [9], [16],

increasing the collision dissipation magnitude and demanding additional active energy input [15],

likely through hip torque [8], [17]. Age and a restrictive view of upcoming surfaces changes (here

referred to as lookahead) also influences walking biomechanics [15], [18]. Thus, we propose that

for a given walking condition, there is a walking speed at which COM mechanical work dissipation

is optimized. Based on a powered simple walking model [8], we propose that, in the mechanically

optimal speed, push-off that requires active muscle work, provides all necessary walking energy.

As such, no energy adjustment (compensation or dissipation) is required after the step transition.

Consequently, rebound serves only to straighten the stance leg and swing the limbs [9]. It is fully

absorbed by the negative preload work and remains passive [9], [11].

Since during uneven walking the COM elevation change for each step is unknown, it is challenging

to estimate the optimal push-off as the sum of step dissipation and gravitational work. We therefore

propose "rebound work equal to preload"—where single support work is suggested to be passive—

as a criterion for identifying the mechanically preferred walking speed.

Figure 1: The step-to-step transition is when the stance leg is switched. (A) During a nominal walking, the push-off work is exerted
pre-emptively and is equal to the subsequent collision. (B) If a sub-optimal push-off is exerted, the subsequent collision magnitude
grows. The reverse is true when the push-off is more than the nominal magnitude (C) Uneven walking is a deviation from nominal
even walking. In ideal case, the pre-emptive push-off must provide the mechanical energy for step change and gravity work. (D)
The human walking COM power trajectory depicts four distinct regions: collision (heel-strike), rebound, preload, and push-off
(toe-off). Since both limbs perform work on the COM during the double stance, the other leg's power trajectory is demonstrated
with a dashed line. The negative work components (collision and preload) and positive work components (rebound and push-off)
determine the work balance during contact, influencing the energetic efficiency of the gait and the compensations required.

Materials and Methods

Simulation

Building on a powered simple walking model [8], we compute the analytical collision dissipation when push-off is suboptimal (a fraction of the nominal push-off). As shown in Figure 1B, the velocity prior to transition is approximated by the average velocity (v_{ave}) and '2α' represents the leading and trailing leg angles at the point of transition [8]. The suboptimal push-off (po_{sub}) modifies the pre-transition COM velocity (v_{ave}) partially by the angle of 'γ' which is less than 'α':

$$\gamma = \text{atan}\left(\frac{po_{sub}}{v_{ave}}\right) \qquad \text{Equation 1}$$

With the mid-transition COM velocity denoted as v^0, we can estimate the collision impulse (co) as:

$$\begin{cases} v^0 = \dfrac{v_{ave}}{\cos(\gamma)} \\ \quad or \\ v^0 = \dfrac{co}{\sin(2\alpha - \gamma)} \end{cases} \rightarrow co = v_{ave}\dfrac{\sin(2\alpha - \gamma)}{\cos(\gamma)} \qquad \text{Equation 2}$$

For uneven walking, when the walker steps up by a height Δh, the post-transition velocity (v^+_{opt}) must exceed the pre-transition velocity to account for the increased potential energy. Thus:

$$0.5v^{+2}_{opt} - 0.5v^2_{ave} = g.\Delta h \rightarrow v^+_{opt} = \sqrt{v^2_{ave} + 2g.\Delta h} \qquad \text{Equation 3}$$

The step transition impulses (u) work are evaluated as $0.5u^2$ [14]. In the optimal scenario, where all transition work is provided by a pre-emptive push-off, the transition impulses are:

$$\begin{cases} po_{opt} = v_{ave}.\tan(\gamma_{opt}) \\ co_{opt} = v^+_{opt}.\tan(2\alpha - \gamma_{opt}) \end{cases} \qquad \text{Equation 4}$$

143 If PO and CO denote push-off and collision work, respectively, their difference should match the

144 gravitational work needed to maintain momentum:

$$PO - CO = g.\Delta h \rightarrow 0.5v_{ave}^2.\tan^2(\gamma_{opt}) - 0.5v_{opt}^{+2}.\tan^2(2\alpha - \gamma_{opt}) = g.\Delta h \qquad \text{Equation 5}$$

We solve Equation 6 numerically to determine γ_{opt} for given conditions. For our calculations, we

assume $v_{ave} = 1.25 \text{ m.s}^{-1}$, and its corresponding $\alpha = 0.35$ [11]. For uneven walking, $\Delta h =$

0.025m is used. We ran simulations for even and uneven walking where the push-off impulse

varied from zero to the optimal level (Figure 2). Results were normalized by the optimal push-off

work for each case.

The simulation shows that suboptimal push-off leads to an increase in collision dissipation,

creating a mechanical energy deficit post-transition. This deficit requires additional positive work

during the subsequent single support phase [10]. For even walking, if only 80% of optimal push-

off impulse is exerted, after transition, an additional 70% of nominal push-off work must be

performed, increasing total positive work to 133% of nominal. This implies 33% extra mechanical

work, with a corresponding metabolic cost.

For $\Delta h = 0.025$m, the required gravitational work is approximately 90% of nominal push-off

(magnitude of dark green arrow, Figure 2B). With only 80% of required push-off impulse, the post-

transition mechanical energy compensation would be 49% of what's needed to reach the same

speed at the subsequent midstance (optimal push-off work). The resulting total work performance

is 112% of optimal work. This indicates a need for 12% additional positive work with associated

metabolic consequences. The simulation suggests increased rebound work beyond what preload

can absorb when pre-emptive push-off fails to cover total transition energy. Thus, when PO – CO

< 0 (even walking) or PO – CO < gravity work, the push-off is suboptimal.

Conversely, when the push-off exceeds the nominal value, the post-transition speed surpasses the

average speed (speed at midstance, Figure 3), requiring dissipation to maintain steady speed. For

even walking, when push-off impulse is 125% of nominal, a mechanical energy equal to 91% of

nominal push-off work must be dissipated. Similar excess push-off raises the required dissipation

to 65% of optimal work for uneven walking. Notably, the simple powered walking model defines

a maximum pre-emptive push-off as: $po_{max} = v_{ave} \cdot \tan(2\alpha)$ [8].

Therefore, the simulation demonstrates that for any given walking speed, suboptimal or excessive

push-off, increases the magnitude of mechanical energy dissipation, leading to elevated positive

mechanical work requirements (Figure 4). Since mechanical energy largely accounts for walking

energetics [7], and energy conservation is a fundamental walking goal [1], it can be inferred that

suboptimal or excessive push-off is not favorable from an energy perspective.

Figure 2: Simulation results when suboptimal push-off is exerted: (top row) resulting collision work trajectories during the even
walking and with a known step up (uneven walking with known gravity work). The exerted push-off impulse ranges from zero to
nominal magnitudes. (Bottom row) post transition work compensation and the total positive work trajectories of suboptimal push-
off impulse for even walking and known step up (uneven walking).

COM Work Component Traces Based on Experimental Data

Using the trajectories proposed for various walking conditions—including state of lookahead,

terrain amplitudes, and walking speeds—for both young and older adults [10], [19], we developed

COM work trajectories (Figure 5 and Table 1).

Figure 3: Simulation results for excess pre-emptive push-off: (top row) resulting collision work trajectories during even walking
and known step up (uneven walking) as push-off impulse ranges from nominal magnitude to maximum analytical level (po_{max}).
For maximum analytical push-off impulse, the collision work becomes zero. (Bottom row) post transition requires work dissipation
of the excess mechanical energy of surplus push-off impulse for even walking and step up (uneven walking).

We calculated trajectories for total positive work, total negative work, push-off, and collision

across walking speeds and terrain amplitudes, ranging from 0.8 m·s⁻¹ to 1.6 m·s⁻¹ and from 0 m to

0.06 m, respectively. Trajectories were adjusted to account for random bias in instrumented

treadmill calibration. Consequently, we calculated rebound and preload values as follows: rebound

as the difference between total positive work and push-off, and preload as the difference between

total negative work and collision [9], [10].

Figure 4: The total analytical dissipation, based on the magnitude of the exerted push-off impulse, is calculated for: (A) even walking and (B) uneven walking. For suboptimal push-off, the total dissipation is equal to the amplified collision. In contrast, for excessive push-off, the total dissipation comprises both step collision losses and the excess push-off work. The minimum dissipation occurs at the nominal push-off.

Since the trajectories represented various walking conditions where the optimal push-off of each step could vary, we used the "Rebound = Preload" criterion to estimate the preferred walking speed. Additionally, we generated COM work component trajectories for even walking as a validation measure and compared the derived preferred walking speeds (for young and older adults with both normal and restricted lookahead) with values reported in the literature.

Results

We developed an analytical simulation based on a simple powered walking model [8] to analyze the mechanical energy demand after step-to-step transitions when the push-off does not fully meet the step transition energy requirements, whether for even walking or step ups (uneven walking). The simulation suggested that if push-off does not offset the subsequent collision (in either even or uneven walking) or account for gravitational work (in uneven walking), a mechanical energy

211 deficit will arise post-transition. This deficit must be compensated for during the following step

212 through positive work performance (rebound) [7], [9].

Figure 5: Uneven walking experiments setup: (A) The test terrain profiles for the uneven walking experiment. Each terrain was identified by its maximum foam height. (B) position for the normal lookahead, (C) position for the restricted lookahead. (D) Typical COM power trajectory for a walking stride. It distinctly shows four phases: collision, rebound (single support positive work), preload (single support negative work), and push-off.

Based on this observation, we inferred that when push-off is suboptimal, the subsequent rebound

requires active work, thereby increasing metabolic energy demand. Conversely, if push-off is

optimal, the subsequent rebound contributes no extra energy to COM motion, meaning the rebound

is passive and may only incur limb oscillation costs [20], [21], [22]. The simulation further

indicated that if the push-off impulse exceeds the optimal level, maintaining the prescribed average

walking speed and momentum imposes the dissipation of excess mechanical energy post-

transition. During the single support phase, this manifests a larger negative work (preload) [7], [9]

that absorbs the excess energy. When push-off exceeds optimal levels, the rebound is smaller than

the preload, suggesting that this excess energy likely converts to heat [23] rather than being stored

in limbs and tendons [9], [11]. Thus, excessive push-off results in a rebound that is not entirely

passive.

Table 1: The proposed COM work components trajectories derived by the linear mixed effect model for the experimental data. The significant parameters are identified by an asterisk (*).

Average Positive Work	Gains	P_values	Average Negative Work	Gains	P_values
Intercept*	0.0594	2.26E-02	Intercept*	-0.0649	7.77E-03
Vision*	-0.0199	2.77E-02	Vision*	0.0321	1.45E-04
Age	0.0368	3.10E-01	Age	-0.0237	4.86E-01
Velocity*	0.3182	2.38E-81	Velocity*	-0.2948	1.22E-79
Velocity-Age	-0.0085	7.17E-01	Velocity-Age	-0.0206	3.51E-01
Max_h*	60.0450	3.24E-08	Max_h*	-55.8683	3.95E-08
Max_h-Age*	30.6408	4.61E-02	Max_h-Age*	-28.4014	4.83E-02
R^2	0.6422		R^2	0.6625	
Average Push-Off			Average Collision		
Intercept*	0.0546	8.06E-05	Intercept*	0.1104	6.39E-08
Vision*	0.0137	4.22E-03	Vision*	0.0216	2.23E-03
Age	-0.0243	2.07E-01	Age	0.0346	2.24E-01
Velocity*	0.1844	4.04E-96	Velocity*	-0.2940	2.57E-112
Velocity-Age*	-0.0283	2.41E-02	Velocity-Age*	-0.0505	6.26E-03
Max_h*	-15.8506	6.10E-03	Max_h*	-54.1978	1.92E-10
Max_h-Age	4.3133	5.98E-01	Max_h-Age*	-21.8911	6.90E-02
R^2	0.4903		R^2	0.7766	

Based on experimentally derived COM work component trajectories, we observed instances where the net single support work dissipated mechanical energy, while in other cases it compensated for mechanical energy deficits. Therefore, for any given walking condition, there was only one walking speed at which rebound and preload were equal. Following simulation results, we assumed that in these cases, no additional positive compensatory work or mechanical dissipation occurred, making the associated single support mechanical work (rebound and preload) passive (storage and release). According to the simulation, we inferred that when the net single support work is zero, the magnitude of mechanical energy dissipation must be minimum. Therefore, we defined the walking speeds under these conditions—taking into account factors such as age, terrain, and visual lookahead—as the preferred walking speeds.

For uneven walking, certain terrain amplitudes within the trial ranges did not yield preferred

walking speeds, indicating that the rebound was always greater than the preload (Figure 6). We

also reported the range of terrain amplitudes where preferred walking speeds were observed,

noting that age and lookahead state decreased the estimated preferred walking speed.

Second-order polynomials were fitted to the estimated preferred walking speeds within each

category as terrain amplitude increased [24]. The preferred walking speed for young adults with

normal lookahead, based on "push-off = collision" and "rebound = collision," was 1.20 m·s⁻¹. For

young adults with normal lookahead, the preferred walking velocity ranged from 1.20 m·s⁻¹ to

0.87 m·s⁻¹ as terrain amplitudes rose from 0 m to 0.035 m (-28.1%, p = 4.4e-9, R²=0.998).

It is reported that self-selected walking speed declines with visual impairment [25], which we also

observed with restricted lookahead. For young adults with restricted lookahead, the preferred

walking velocities were estimated to vary from 1.13 m·s⁻¹ to 0.88 m·s⁻¹ (-22.1%, p = 1.3e-8,

R²=0.999) as terrain amplitude increased from 0 m to 0.3 m.

The preferred walking speed of older adults is generally lower than that of young adults, which

was consistent with our estimates. Additionally, the terrain amplitude ranges for older adults varied

based on the state of lookahead. With normal lookahead, terrain amplitudes ranged from 0 m to

0.02 m, and preferred walking speeds declined from 0.95 m·s⁻¹ to 0.85 m·s⁻¹ (-10.5%, p = 2.2e-5,

R²=0.999). With restricted lookahead, terrain amplitudes ranged only from 0 m to 0.015 m, and

preferred walking speeds declined from 0.9 m·s⁻¹ to 0.83 m·s⁻¹ (-7.78%, p = 1.7e-3, R²=0.997).

Discussion

For a given walking task or condition, the preferred walking velocity is believed to align with the

minimum cost of transport [2]. Optimal walking economy is also suggested to occur when the

push-off pre-emptively provides all the energy needed for each step [8]. Since the COM work

accounts for most walking energetics [7], the preferred walking speed may be also estimated using

COM mechanical work components over a stance phase, mainly by investigating the push-off.

However, finding optimal push-offs for varying walking conditions can be difficult. For example,

during uneven walking, where elevation changes frequently, humans must perform work against

gravity with varying intensities [26]. Studies indicate that with normal lookahead, humans tend to

spread the active work required across multiple steps [27], [28], [29]. Consequently, a specific

step's push-off may exceed the immediate energy need, prompting to explore alternatives to

directly evaluating push-off work. Here, we considered scenarios where control is exerted based

on a "just-in-time" strategy [15].

Figure 6: (A) The young adults' COM work components for even walking with normal lookahead. The crossing points at which the
collision or rebound surpasses the push-off or preload is assumed to represent the preferred walking speed at which the entire
energy of the step-to-step transition is provided pre-emptively. (B) The estimated preferred walking speed trajectories when terrain
complexities increase from zero (even) to 0.045 m. The trajectories indicate terrain amplitude thresholds for each category beyond
which the pre-emptive active energy inducement is insufficient to energize the step-to-step transition. Therefore, the rebound work
exceeds preload for the entire velocity range ($0.8 \ m \cdot s^{-1}$ to $1.6 \ m \cdot s^{-1}$). Some speed estimations are also very low to sustain
human walking. Therefore, a lower bound ($0.8 \ m \cdot s^{-1}$) is set to filter them out.

It is proposed that humans perform both positive and negative work during the single support phase

[7], [9]. Given that the single support phase mimics an inverted pendulum's motion [12], assumed

to be conservative, any work performed should theoretically cancel. Otherwise, the COM would

either accelerate or decelerate. Hence, in contrast to the pre-emptive push-off, which results from

active muscle work, it is proposed that the positive and negative work during the single support

phase are passive [7]. In other words, these single support work primarily involve energy storage

and release through tendons and tissues [7], [11]. Therefore, if the net single support work is non-

zero, it likely serves to regulate COM momentum or energy [10]. Then, identifying speeds where

rebound work is fully offset by preload could indicate optimal push-off work for a given walking

condition.

Our simulations of step transition impulses and associated work suggest an optimal push-off

impulse for each walking speed. This impulse fully supplies the energy required for step

transitions, minimizes the total collision dissipation, and eliminates the need for further energy

adjustments during the subsequent step. For a given speed, if push-off is suboptimal, additional

positive mechanical energy is required; if excessive, energy dissipation must occur post-transition.

The COM work component trajectories indicate that under varying conditions (e.g., terrain

amplitude, state of lookahead), single support work is not balanced. Hence, this imbalance

necessitates net single support mechanical work to regulate COM energy. Consequently, it is

plausible to infer that non-zero net single support work arises from increased dissipation either

before or after the transition, signaling a rise in metabolic cost. For each walking condition, there

is only one speed at which net single support work is zero (rebound = preload). This indicates a

push-off that fully offsets heel-strike and gravitational work, resulting in minimal associated

dissipation. At these speeds, our simulation suggests that no adjustment to the COM speed is

needed post-transition. As soft tissue dissipation during single support (during the rebound and

preload phases) is minimal [13], it implies that single support work is passive and incurs no

metabolic cost, aside from the potential cost of limb swing due to the frequency of force generation

[20], [21], [22].

The estimated preferred walking speeds (self-selected) for even terrain align with reported values

for young and older adults [2], [4], [30]. Similar to previous findings [2], preferred speeds for

uneven walking are slower than even walking. The estimated speed trends indicate terrain

amplitude impact aligns with the quadratic increase in walking costs due to step elevation

variations [24], [31]. Moreover, thresholds emerge where no preferred speed exists to pre-

emptively meet energy demands. This suggests a biomechanical limitation of the ankle, or

interrupted ankle work during uneven walking, making hip torque an additional energy source in

such cases. Another observation is the impact of lookahead on even walking, where visual cues

allow individuals to optimize footfall choices [15] and synchronize push-off with collisions for

energy-efficient steps, or convert maximum potential energy [14], [27], [28]. The importance of

the visual information of the coming terrains is evident by slower walking in visually impaired

individuals [25], [32], [33]. Some projected speeds are impractically low, suggesting that other

walking costs at such speeds might outweigh the benefit of fully energizing gait through push-off

[34]. Therefore, low-speed projections, such as those below $0.8 \ \mathrm{m \cdot s^{-1}}$, should be excluded.

Our method for estimating preferred speeds is based on COM mechanics when the pre-emptive

push-off is optimum that results in passive single support work. It aligns with minimizing the COM

total dissipative work of each step that closely represents the walking energetics [4]. In our

estimation we have considered the terrain amplitude as a varying continuous parameter. However,

other factors like time [35], stability, and reproducibility could refine this criterion [36]. In

conclusion, Although the simple powered model employed cannot directly determine a preferred walking speed, it can offer valuable insights into whether a particular walking regime is mechanically optimal. Since our approach estimates preferred speeds based on COM work trajectories derived from an uneven walking experimental data [10], it may potentially be extended to other conditions [7]. In extreme cases when very fast or slow speeds are estimated, biomechanical factors should be examined to ensure walking energetics remain optimal. If no preferred speed is identified, it likely indicates that additional energy regulation is required post-transition, suggesting that push-off alone does not fully energize the gait.

References

[1] A. V. Birn-Jeffery, C. M. Hubicki, Y. Blum, D. Renjewski, J. W. Hurst, and M. A. Daley, "Don't break a leg: running birds from quail to ostrich prioritise leg safety and economy on uneven terrain," *J Exp Biol*, vol. 217, no. Pt 21, pp. 3786–3796, Nov. 2014, doi: 10.1242/jeb.102640.

[2] K. Gast, R. Kram, and R. Riemer, "Preferred walking speed on rough terrain; is it all about energetics?," *Journal of Experimental Biology*, p. jeb.185447, Jan. 2019, doi: 10.1242/jeb.185447.

[3] S. M. O'Connor, H. Z. Xu, and A. D. Kuo, "Energetic cost of walking with increased step variability," *Gait Posture*, vol. 36, no. 1, pp. 102–107, May 2012, doi: 10.1016/j.gaitpost.2012.01.014.

[4] H. J. Ralston, "Energy-speed relation and optimal speed during level walking," *Int. Z. Angew. Physiol. Einschl. Arbeitsphysiol.*, vol. 17, no. 4, pp. 277–283, Oct. 1958, doi: 10.1007/BF00698754.

[5] J. S. Park and C. H. Kim, "Ground-Reaction-Force-Based Gait Analysis and Its Application to Gait Disorder Assessment: New Indices for Quantifying Walking Behavior," *Sensors (Basel)*, vol. 22, no. 19, p. 7558, Oct. 2022, doi: 10.3390/s22197558.

[6] A. D. Gidley and D. E. Lankford, "Cost of transport at preferred walking speeds are minimized while walking on moderately steep incline surfaces," *Human Movement Science*, vol. 79, p. 102849, Oct. 2021, doi: 10.1016/j.humov.2021.102849.

[7] J. M. Donelan, R. Kram, and A. D. Kuo, "Mechanical work for step-to-step transitions is a major determinant of the metabolic cost of human walking," *Journal of Experimental Biology*, vol. 205, no. 23, pp. 3717–3727, Dec. 2002, doi: 10.1242/jeb.205.23.3717.

[8] A. D. Kuo, "Energetics of Actively Powered Locomotion Using the Simplest Walking Model," *Journal of Biomechanical Engineering*, vol. 124, no. 1, pp. 113–120, Feb. 2002, doi: 10.1115/1.1427703.

[9] A. D. Kuo, J. M. Donelan, and A. Ruina, "Energetic consequences of walking like an inverted pendulum: step-to-step transitions," *Exerc Sport Sci Rev*, vol. 33, no. 2, pp. 88–97, Apr. 2005, doi: 10.1097/00003677-200504000-00006.

[10] Hosseini-Yazdi Seyed-Saleh, "Energetics and Biomechanics of Uneven Walking for Young and Older Adults," 2024. [Online]. Available: https://prism.ucalgary.ca/server/api/core/bitstreams/be2fa66b-26a2-4421-9d30-dfcc55dcfb35/content

[11] A. D. Kuo, "A Simple Model of Bipedal Walking Predicts the Preferred Speed–Step Length Relationship," *Journal of Biomechanical Engineering*, vol. 123, no. 3, pp. 264–269, Jun. 2001, doi: 10.1115/1.1372322.

[12] G. A. Cavagna, N. C. Heglund, and C. R. Taylor, "Mechanical work in terrestrial locomotion: two basic mechanisms for minimizing energy expenditure," *Am J Physiol*, vol. 233, no. 5, pp. R243-261, Nov. 1977, doi: 10.1152/ajpregu.1977.233.5.R243.

[13] T. J. Van Der Zee and A. D. Kuo, "Soft tissue deformations explain most of the mechanical work variations of human walking," *Journal of Experimental Biology*, vol. 224, no. 18, p. jeb239889, Sep. 2021, doi: 10.1242/jeb.239889.

[14] O. Darici, H. Temeltas, and A. D. Kuo, "Optimal regulation of bipedal walking speed despite an unexpected bump in the road," *PLoS ONE*, vol. 13, no. 9, p. e0204205, Sep. 2018, doi: 10.1371/journal.pone.0204205.

[15] J. S. Matthis and B. R. Fajen, "Humans exploit the biomechanics of bipedal gait during visually guided walking over complex terrain," *Proc. R. Soc. B.*, vol. 280, no. 1762, p. 20130700, Jul. 2013, doi: 10.1098/rspb.2013.0700.

[16] P. G. Adamczyk and A. D. Kuo, "Redirection of center-of-mass velocity during the step-to-step transition of human walking," *Journal of Experimental Biology*, vol. 212, no. 16, pp. 2668–2678, Aug. 2009, doi: 10.1242/jeb.027581.

[17] A. S. Voloshina, A. D. Kuo, M. A. Daley, and D. P. Ferris, "Biomechanics and energetics of walking on uneven terrain," *J Exp Biol*, vol. 216, no. Pt 21, pp. 3963–3970, Nov. 2013, doi: 10.1242/jeb.081711.

[18] J. E. Himann, D. A. Cunningham, P. A. Rechnitzer, and D. H. Paterson, "Age-related changes in speed of walking.," *Med Sci Sports Exerc*, vol. 20, no. 2, pp. 161–166, Apr. 1988.

[19] S.-S. Hosseini-Yazdi and A. D. Kuo, "A split-belt instrumented treadmill with uneven terrain," *Journal of Biomechanics*, vol. 176, p. 112376, Nov. 2024, doi: 10.1016/j.jbiomech.2024.112376.

[20] T. J. Van Der Zee and A. D. Kuo, "The high energetic cost of rapid force development in muscle," *Journal of Experimental Biology*, vol. 224, no. 9, p. jeb233965, May 2021, doi: 10.1242/jeb.233965.

[21] J. Doke and A. D. Kuo, "Energetic cost of producing cyclic muscle force, rather than work, to swing the human leg," *Journal of Experimental Biology*, vol. 210, no. 13, pp. 2390–2398, Jul. 2007, doi: 10.1242/jeb.02782.

[22] J. Doke, J. M. Donelan, and A. D. Kuo, "Mechanics and energetics of swinging the human leg," *Journal of Experimental Biology*, vol. 208, no. 3, pp. 439–445, Feb. 2005, doi: 10.1242/jeb.01408.

[23] R. McN. Alexander, "Energy-Saving Mechanisms in Walking and Running," *Journal of Experimental Biology*, vol. 160, no. 1, pp. 55–69, Oct. 1991, doi: 10.1242/jeb.160.1.55.

[24] A. S. Voloshina, A. D. Kuo, D. P. Ferris, and C. D. Remy, "A model-based analysis of the mechanical cost of walking on uneven terrain," Bioengineering, preprint, Jun. 2020. doi: 10.1101/2020.06.15.152330.

[25] Z. Kahaki, A. Safarpour, and H. Daneshmandi, "The spatiotemporal gait parameters among people with visual impairment: A literature review study," *Oman J Ophthalmol*, vol. 16, no. 3, p. 427, 2023, doi: 10.4103/ojo.ojo_24_23.

[26] D. B. Kowalsky, J. R. Rebula, L. V. Ojeda, P. G. Adamczyk, and A. D. Kuo, "Human walking in the real world: Interactions between terrain type, gait parameters, and energy expenditure," *PLoS ONE*, vol. 16, no. 1, p. e0228682, Jan. 2021, doi: 10.1371/journal.pone.0228682.

[27] O. Darici, H. Temeltas, and A. D. Kuo, "Anticipatory Control of Momentum for Bipedal Walking on Uneven Terrain," *Sci Rep*, vol. 10, no. 1, p. 540, Jan. 2020, doi: 10.1038/s41598-019-57156-6.

[28] O. Darici and A. D. Kuo, "Humans optimally anticipate and compensate for an uneven step during walking," *eLife*, vol. 11, p. e65402, Jan. 2022, doi: 10.7554/eLife.65402.

[29] O. Darici and A. D. Kuo, "Humans plan for the near future to walk economically on uneven terrain," *Proc. Natl. Acad. Sci. U.S.A.*, vol. 120, no. 19, p. e2211405120, May 2023, doi: 10.1073/pnas.2211405120.

[30] Y. Laufer, "Effect of age on characteristics of forward and backward gait at preferred and accelerated walking speed," *J Gerontol A Biol Sci Med Sci*, vol. 60, no. 5, pp. 627–632, May 2005, doi: 10.1093/gerona/60.5.627.

[31] S.-S. Hosseini-Yazdi and A. D. Kuo, "The energetic cost of human walking as a function of uneven terrain amplitude," Nov. 11, 2024. doi: 10.1101/2024.11.08.622353.

[32] M. Majlesi, N. Farahpour, and G. E. Robertson, "Comparisons of Spatiotemporal and Ground Reaction Force Components of Gait Between Individuals with Congenital Vision Loss and Sighted Individuals," *Journal of Visual Impairment & Blindness*, vol. 114, no. 4, pp. 277–288, Jul. 2020, doi: 10.1177/0145482X20940429.

[33] H. J. Bennett, K. A. Valenzuela, K. Fleenor, S. Morrison, and J. A. Haegele, "Walking biomechanics and energetics of individuals with a visual impairment: a preliminary report," *hm*, vol. 20, no. 4, pp. 8–18, 2019, doi: 10.5114/hm.2019.85094.

[34] A. N. Best and A. R. Wu, "Upper body and ankle strategies compensate for reduced lateral stability at very slow walking speeds," *Proceedings of the Royal Society B: Biological Sciences*, vol. 287, no. 1936, p. 20201685, Oct. 2020, doi: 10.1098/rspb.2020.1685.

[35] R. E. Carlisle and A. D. Kuo, "Optimization of energy and time predicts dynamic speeds for human walking," *eLife*, vol. 12, p. e81939, Feb. 2023, doi: 10.7554/eLife.81939.

[36] L. Majed, R. Ibrahim, M. J. Lock, and G. Jabbour, "Walking around the preferred speed: examination of metabolic, perceptual, spatiotemporal and stability parameters," *Front. Physiol.*, vol. 15, p. 1357172, Feb. 2024, doi: 10.3389/fphys.2024.1357172.