Center of Mass Work Components May Offer Estimates for Preferred Walking Speeds for Any Walking Conditions.

Seyed-Saleh Hosseini-Yazdi[1,2]

[1]Department of Biomedical Engineering, Schulich School of engineering, University of Calgary, AB, Canada

[2]Human Performance Laboratory, Faculty of Kinesiology, University of Calgary, AB, Canada

Conflict of Interest: None

Correspondence Address:

Seyed Saleh Hosseini Yazdi

Biomedical Engineering Department, Schulich School of Engineering, University of Calgary

2500 University Dr NW, Calgary AB T2N1N4

Phone: 403 402 6005, Email: seyedsaleh.hosseiniy@ucalgary.ca

Abstract:

It is suggested that preferred walking speeds coincide with the minimum metabolic energy expenditure. Since the positive step work performed on the center of mass (COM) broadly represents walking energetics, at the preferred walking speed, the positive step work must also be minimized. Positive step work is exerted at the beginning of the step (push-off) and during the stance phase (rebound), each followed by associated mechanical energy dissipation. A simple walking model suggests that the best walking economy is achieved when the entire step's active work is provided by the push-off, making the rebound merely the release of stored mechanical energy in tendons to swing the limbs. Accordingly, we propose a criterion where the preferred walking speed is when the rebound work does not energize COM motion and is completely absorbed by subsequent negative work (preload). We developed preferred walking speed trajectories for different terrain amplitudes, considering the influence of age and state of lookahead. We estimated that with normal lookahead, the preferred walking speed for young adults would be $1.22 \, \text{m} \cdot \text{s}^{-1}$. As walking conditions became more challenging (e.g., due to age, restricted lookahead, etc.), our estimated preferred walking speeds also declined.

Word Count: 3024

Keywords: Center of mass mechanical work, preferred walking speed, walking energetics, step-to-step transition

Introduction:

One of the main objectives of walking is to keep energy expenditures at minimum [1] while other task-specific targets are also met [2]. It is suggested that the energetic expenditure is minimized when humans walk at a nominal or preferred walking speed [3]. Traditionally, the preferred walking speed is defined when the cost of transport is minimum [4]. It means walking faster or slower than the preferred walking speed increases the energetic cost of walking [5]. To determine the average preferred walking speed based on walking energetics, subjects must walk at different velocities when their energetics are measured [6]. The walking velocity that coincides with the minimum of the derived parabolic cost of transport trajectory is introduced as the preferred walking speed [5]. Since it is proposed that the active COM works at the step-to-step transition is a close representation of the metabolic walking rate [7], there must also be a mechanical equivalent approach to estimate the preferred walking speed based on the COM mechanical work.

The walking economy is hypothesized to be maximized if a pre-emptive push-off energizes the gait progression [8]. The push-off changes the direction of the prior step's COM velocity upward, as the subsequent collision adjusts the altered COM velocity to match the new stance (Figure 1A) [9]. As such, the push-off adds mechanical energy to the system while the collision dissipates it [8].

If push-off is suboptimal, it only partially energizes the gait. Therefore, the partially adjusted COM velocity in the middle of the step-to-step transition faces a larger collision dissipation to change its trajectory for the next stance (Figure 1B). Hence, the outcome velocity is smaller after the transition [8]. Therefore, further mechanical active work inducement is necessary. Otherwise, the COM velocity drops drastically, or the gait is not sustainable.

The extra compensation is suggested to be exerted during the mid-flight at the rebound phase [10].

Donelan et al. [7] have suggested that the rebound is a passive work that is released by or stored

in tendons and tissues in nominal walking. As such, it is proposed that the positive energy of the

rebound is absorbed during the preload. If the rebound is to energize the COM progression, its

magnitude must exceed the preload [7], [8], [10]. Hence, it is plausible to assume that walking

deviates from the preferred regime when push-off is less than collision or rebound is more than

preload.

Figure 1: The step-to-step transition work exertions: (A) the optimal work exertion approach in which the push-off provides the
entire active mechanical energy needed. The following collision work equals the optimal push-off, and the system's energy stays
the same. (B) the suboptimal push-off creates a larger collision dissipation. As such, the system's power declines, and additional
energy inducement is needed after the step-to-step transition.

Uneven walking is a case in which the push-off may deviate from optimal walking. For instance,

the heel strike may happen sooner than expected [11], especially without visual information about

the coming terrain [12]. Therefore, the collision occurs when the prior push-off does not

completely adjust the COM velocity [9], [10]. As such, the collision magnitude grows and must

be canceled by an extra active energy inducement [12], most likely by the hip torque exertion [8],

[13]. Age and the state of lookahead may also affect the biomechanics of walking [12], [14].

Accordingly, we propose that for any walking condition, there is a walking velocity at which the

COM mechanical works, and thus, its energetics are minimal. We assume that the best walking

economy happens when only push-off provides all the required walking energy. Therefore, the

rebound is only to straighten the stance leg and swing the limbs completely absorbed by the

negative preload work. Since, during the uneven walking, each step's COM elevation change is

unknown, we cannot estimate the optimum push-off as the summation of step dissipation and the

work against gravity. As such, we propose "rebound work equal to preload" as the criterion for the

preferred walking velocity instead.

Materials and Methods:

We organized experiments to study uneven walking in young and older adults. For this purpose,

we modified the instrumented treadmill to use uneven terrains. We fabricated uneven terrains by

gluing construction foams to the surfaces of conventional treadmill belts [13]. We furnished the

same elevation profiles for 0.3 m to enable flat foot landing or with a small incline. Each terrain

was identified by its maximum foam height (terrain amplitude: h). The terrains were open-ended

and wrapped around the existing belts. We tightened the original and uneven terrains together

(Figure 2A).

To control the subjects' lookahead horizon, we positioned them 0.7 m and 1.2 m from the front end

of the treadmill (restricted and normal lookaheads, respectively, Figure 2B & C). To maintain

position, the subject kept gentle contact with a surgical tube mounted by two tripods.

A. Trials' terrain profiles:

3.6 m

Max_h = 0 m (or Even)

Max_h = 0.019 m

Max_h = 0.032 m

Max_h = 0.045 m

0.00 m   0.005 m   0.019 m   0.032 m   0.045 m

B. Normal Lookahead

Lookahead Horizon

Surgical tube

~ 1.2 m

~ 0.35m

Ground Reaction Forces

1.9m Distance

C. Restricted Lookahead

Lookahead Horizon

Surgical tube

~ 0.7 m

~ 0.35m

Ground Reaction Forces

1.9m Distance

Figure 2: Uneven walking experiments setups: (A) The test terrain profiles for the uneven walking experiment. Each terrain was identified by its maximum foam height. (B) position for the normal lookahead, (C) position for the restricted lookahead.

The GRF data was collected for 60 seconds at 960 Hz and converted to forces and moments using Collins et al. [15] method. We randomized the order of the walking speeds and terrain amplitudes for each subject. The trials' velocities varied from 0.8 $\mathrm{m \cdot s^{-1}}$ to 1.4 $\mathrm{m \cdot s^{-1}}$ whereas the terrain amplitudes altered from 0 m (Even) to 0.045 m. The GRFs were filtered by a third-order zero-phase Butterworth filter (cut-off 10Hz). We used the methods presented by Donelan et al. [7] and Kuo et al. [10] to calculate the COM velocity, COM power trajectory, and stance phases' works (Figure 3).

Statistical analysis was conducted using linear regression (Linear Mixed Effects Models, Statsmodels 0.15.0), with the parameters under study (COM work components) serving as the dependent variables. Trials walking velocity, terrain complexity, age, and state of lookahead (vision) were independent variables (continuous or categorical). Regression gains and associated p-values were reported to show the relationships and significance. Further, the COM work

components' statistical results were used to estimate the COM work components' trajectories for

walking velocities ranging from 0.8 m · s⁻¹ to 1.6 m · s⁻¹. We defined the mid-stance positive

and negative works (rebound and preload) as the difference of total positive work and push-off,

and difference of total negative work and collision, respectively [10]. Since it is suggested that the

energetics of walking vary $v^{3.42}$ [8], h^2 [16], we also utilized the same convention ($\dot{W} \sim v^3$ or

$W \sim v^2$ and $W \sim h^2$) to perform regression analysis.

Figure 3: Typical COM power trajectory for a walking stride. It distinctly shows four phases: collision, rebound (mid-flight positive
work), preload, and push-off.

We invited two groups of healthy adults to participate in our experiment: Young Adults (YA, age:

27.69 ± 5.21, mass: 71.0 ± 6.16 kg, six females and four males) and Older Adults (OA, age: 66.1

± 1.44, mass: 77.34 ± 12.13 kg, six males and four females). The University of Calgary Conjoint

Health Research Ethics Board approved the procedure (REB17-0761), and subjects provided

written informed consent before the experiments. The subjects were given a few short trials to

become familiar with the experimental conditions.

We defined four categories to estimate the preferred walking velocities when terrain amplitudes

ranged from zero (Even) to 0.045 m: young adults with normal lookahead, young adults with

restricted lookahead, older adults with normal lookahead, and older adults with restricted

lookahead. COM work profiles were developed for each category and terrain amplitude as walking

velocity varied from $0.8 \text{ m} \cdot \text{s}^{-1}$ to $1.6 \text{ m} \cdot \text{s}^{-1}$.

Results:

The COM work components altered significantly with parameters of interest (Table 1). The

estimated COM work trajectories for young adults with normal lookahead were generated as the

base case (Figure 4A). The estimated preferred walking velocities for young adults with normal

lookahead based on "push-off = collision" and "rebound = collision" were $1.35 \text{ m} \cdot \text{s}^{-1}$ and 1.22

$\text{m} \cdot \text{s}^{-1}$, respectively (difference = 10.7%).

There were amplitudes for the set trial ranges for which no preferred walking velocity was

estimated. For those amplitudes, this meant the rebound was always larger than the preload (Figure

4B). As such, we also reported the range of the terrain amplitudes in which preferred walking

speeds were detected.

We fitted second-order polynomials to each category's estimated preferred walking velocities with

increasing terrain amplitude. For young adults with normal lookahead, the preferred walking

velocity ranged from $1.22 \text{ m} \cdot \text{s}^{-1}$ to $0.87 \text{ m} \cdot \text{s}^{-1}$ as terrain amplitudes rose from zero to 0.035 m

(-28.1%, p = 4.4e-9, R^2=0.998). Likewise, for young adults with restricted lookahead, the preferred

walking velocities were estimated to vary from $1.13 \text{ m} \cdot \text{s}^{-1}$ to $0.88 \text{ m} \cdot \text{s}^{-1}$ (-22.1%, p = 1.3e-8,

R^2=0.999) as the terrain amplitude upper bound was 0.3 m. The older adults' terrain amplitude

ranges also differed based on the state of the lookahead. With the normal lookahead, their terrain

amplitude ranged from zero to 0.02 m as their preferred walking speeds were from $0.95\ \text{m} \cdot \text{s}^{-1}$ to

$0.85\ \text{m} \cdot \text{s}^{-1}$ (-10.5%, p = 0.999, R^2=2.2e-5). With the restricted lookaheads, their terrain

amplitudes were only from zero to 0.015 m and the associated preferred walking speed declined

from $0.9\ \text{m} \cdot \text{s}^{-1}$ to $0.83\ \text{m} \cdot \text{s}^{-1}$ (-7.78%, p = 1.7e-3, R^2=0.997).

Table 1: The statistical analysis result summary for COM work components using linear mixed effect model ($W = c_1 + c_2 \cdot v^2 +$
$c_3 \cdot h^2 + c_4 \cdot C(vision) + c_5 \cdot C(age)$). The significant parameters are identified by an asterisk (*).

	Average Positive Work Gains	P_values		Average Negative Work Gains	P_values
Intercept*	0.0594	2.26E-02	Intercept*	-0.0649	7.77E-03
Vision*	-0.0199	2.77E-02	Vision*	0.0321	1.45E-04
Age	0.0368	3.10E-01	Age	-0.0237	4.86E-01
Velocity*	0.3182	2.38E-81	Velocity*	-0.2948	1.22E-79
Velocity-Age	-0.0085	7.17E-01	Velocity-Age	-0.0206	3.51E-01
Max_h*	60.0450	3.24E-08	Max_h*	-55.8683	3.95E-08
Max_h-Age*	30.6408	4.61E-02	Max_h-Age*	-28.4014	4.83E-02
R^2	0.6422		R^2	0.6625	
	Average Push-Off			Average Collision	
Intercept*	0.0546	8.06E-05	Intercept*	0.1104	6.39E-08
Vision*	0.0137	4.22E-03	Vision*	0.0216	2.23E-03
Age	-0.0243	2.07E-01	Age	0.0346	2.24E-01
Velocity*	0.1844	4.04E-96	Velocity*	-0.2940	2.57E-112
Velocity-Age*	-0.0283	2.41E-02	Velocity-Age*	-0.0505	6.26E-03
Max_h*	-15.8506	6.10E-03	Max_h*	-54.1978	1.92E-10
Max_h-Age	4.3133	5.98E-01	Max_h-Age*	-21.8911	6.90E-02
R^2	0.4903		R^2	0.7766	

Discussion:

The preferred walking velocity is suggested to coincide with the minimum transport cost for a

given walking task or condition [2]. It is proposed that the best walking economy also happens

when the push-off provides all the walking energy pre-emptively [8]. However, estimating the

optimal push-offs for various walking conditions is impossible. An instance is uneven walking in

which humans' elevations change frequently; therefore, they need to perform work against gravity

of random magnitudes [17]. It is also reported that with normal lookahead, humans tend to

distribute the required active work among several steps [18], [19], [20]. As such, A certain step's

exerted push-off may be elevated beyond what is needed. Consequently, we have attempted to

verify the preferred walking velocity by detecting the instance where the rebound work is passive

and completely consumed by the preload phase.

During even walking as the COM elevation does not change, the two preferred walking speed

estimations ('push-off = collision' and 'rebound = preload') must yield similar results. However,

we observe that the 'push-off = collision' always yields a larger estimate (Figure 4A). If we assume

this criterion, the associated 'rebound – preload' is more than zero. Therefore, during the stance

phase, extra positive mechanical work is added to the COM. Since during the stance phase, the

COM motion resembles an inverted pendulum which is conservative, its velocity must increase. It

is contrary to treadmill walking in which the average walking velocity is constant.

For preferred walking speed estimation, if we assumed 'rebound = preload', the associated 'push-

off – collision' is greater than zero (Figure 4A). Nevertheless, this excess energy might be wasted

in another form. The simple model of walking [8] assumes that the push-off is exerted entirely pre-

emptively. However, in reality, a portion of push-off is delayed, which is exerted after the

subsequent heel strike [10] which is also true for smooth treadmill walking [9]. Since during the

double support, the stance leg is switched, the COM motion base changes [8]. As such, a portion

of the delayed push-off might be wasted by stretching the stance leg perpendicular to the COM

motion trajectory (Figure 5A & B). Most likely, the wasted push-off converts to heat [21]. This

perhaps also explains the positive difference of total positive and negative work for the examined

walking speed range. Defining the *Adjusted Push-off* by deducting the difference of total positive

and negative work from the push-off work, we observe that 'adjusted push-off = collision' also

yield estimated preferred walking speed similar to 'rebound = preload'. Hence, it might further

support using 'preload = rebound' to predict the preferred walking speeds.

Figure 4: (A) The young adults' COM work components for even walking with normal lookahead. The crossing points at which the
collision or rebound surpassed the push-off or preload was assumed to represent the preferred walking velocity at which the entire
energy of the step-to-step transition was provided pre-emptively. (B) The estimated preferred walking velocity trajectories when
terrain complexities increased from zero (even) to 0.045 m. The trajectories indicated terrain amplitude thresholds for each category
beyond which the pre-emptive active energy inducement was insufficient to energize the step-to-step transition. Therefore, the
rebound work exceeded preload for the entire velocity range ($0.8 \ m \cdot s^{-1}$ to $1.6 \ m \cdot s^{-1}$). Some speed estimations were also very
low to sustain human walking. Therefore, a lower bound must have been set to filter them out.

The estimated preferred walking velocity for even walking is comparable with the available reports

for young and older adults [4], [22]. One finding is the influence of the state of the lookahead

during the even walking. It is conceivable to assume that visual information enables humans to

select a foothold that maximizes the kinetic energy extraction [12] or regulates the relative timing

of the push-offs and collisions to exert push-offs pre-emptively [11], [18], [19]. However, it is

plausible to assume that vision's influence on even walking should be minimal. Our experimental

results, however, suggest that relying on flight time (vestibular and proprioceptive) or tactile is

less accurate than vision to regulate the gait. It aligns with reports showing that humans with

impaired sight tend to walk slower [23] and backs the effect of vision on human walking [24],

[25].

Figure 5: (A) Even during the smooth treadmill walking a portion of the trailing lead active work (push-off) is exerted when the leading leg becomes the new stance leg (delayed). (B) the delayed push-off impulse is exerted along the trailing leg. Since after the heel strike the COM trajectory changes, a portion of the delayed push-off is wasted to stretch the stance leg perpendicular to COM motion trajectory.

Similar to reported slower preferred walking speeds for older adults, our estimated trends also suggest a material difference between young and older adults [22]. Since each category's preferred walking speed trajectory is almost entirely explained by the terrain amplitude ($R^2 > 0.99$), the decline of the estimated preferred walking velocities with the second power of the terrain amplitude may also support the suggestion that walking costs increase with the step elevation height changes quadratically [16].

Another observation is the thresholds detected for each category. After a certain terrain amplitude, there is no preferred walking velocity for which all mechanical energy is provided pre-emptively. In other words, since the ankle joint exerts the push-off [10], it is plausible to assume that either the ankle's biomechanical capacity cannot keep up with the increasing demand for the necessary active work, or during uneven walking, the ankle work exertion is interrupted. If the ankle work exertion is interrupted, it means that during uneven walking, there are circumstances in which ankle work performance is more expensive than hip torque inducement mechanically.

Likewise, some of the estimated velocities are overly low to be practically sustained during human

walking. Most likely, the energetic consequences of walking at such low speeds outpace the benefit

of mechanically energizing gait entirely with push-off [26]. Therefore, a threshold must be adopted

to filter out projected speeds that are lower than the threshold. For instance, walking velocities less

than $0.8 \text{ m} \cdot \text{s}^{-1}$ must not be considered.

We proposed estimating the preferred walking speed based on the center of mass (COM), as it has

been suggested that step-to-step mechanical work determines most of the human walking

energetics [7]. This approach aligns with the energetic cost of transport, where the primary

objective of walking is to minimize metabolic cost [4]. Nevertheless, when additional factors such

as time are considered [27], the determining criterion must also be adjusted. Additionally, other

indicators such as walking stability and reproducibility may also contribute to refining the

determination of preferred walking speed [28].

In summary, we have been able to propose a method to estimate the preferred walking velocities

for the range of our experimental uneven walking study based on the COM work components. It

is plausible that the same approach might be utilized to estimate the preferred walking speeds for

any walking conditions or individuals by examining the associated COM work components [7].

For extreme cases (very fast or very slow velocities), the estimated velocities must be further

examined to ensure that other biomechanical factors do not drastically affect the energetics of

walking. If the preferred walking velocity is not detected for a specific walking condition, the

push-off does not completely energize the gait. Therefore, after the step-to-step transition, extra

energy inducement is required.

Declaration of Funding:

This work was supported by the Natural Sciences and Engineering Research Council of Canada (NSERC) Discovery and Canada Research Chair (Tier 1) programs under Grant No. 10020499.

References:

[1] A. V. Birn-Jeffery, C. M. Hubicki, Y. Blum, D. Renjewski, J. W. Hurst, and M. A. Daley, "Don't break a leg: running birds from quail to ostrich prioritise leg safety and economy on uneven terrain," *J Exp Biol*, vol. 217, no. Pt 21, pp. 3786–3796, Nov. 2014, doi: 10.1242/jeb.102640.

[2] K. Gast, R. Kram, and R. Riemer, "Preferred walking speed on rough terrain; is it all about energetics?," Evolutionary Biology, preprint, May 2018. doi: 10.1101/332106.

[3] S. M. O'Connor, H. Z. Xu, and A. D. Kuo, "Energetic cost of walking with increased step variability," *Gait Posture*, vol. 36, no. 1, pp. 102–107, May 2012, doi: 10.1016/j.gaitpost.2012.01.014.

[4] H. J. Ralston, "Energy-speed relation and optimal speed during level walking," *Int. Z. Angew. Physiol. Einschl. Arbeitsphysiol.*, vol. 17, no. 4, pp. 277–283, Oct. 1958, doi: 10.1007/BF00698754.

[5] R. E. Pimentel, J. N. Feldman, M. D. Lewek, and J. R. Franz, "Quantifying mechanical and metabolic interdependence between speed and propulsive force during walking," *Front. Sports Act. Living*, vol. 4, p. 942498, Sep. 2022, doi: 10.3389/fspor.2022.942498.

[6] A. D. Gidley and D. E. Lankford, "Cost of transport at preferred walking speeds are minimized while walking on moderately steep incline surfaces," *Human Movement Science*, vol. 79, p. 102849, Oct. 2021, doi: 10.1016/j.humov.2021.102849.

[7] J. M. Donelan, R. Kram, and A. D. Kuo, "Mechanical work for step-to-step transitions is a major determinant of the metabolic cost of human walking," *Journal of Experimental Biology*, vol. 205, no. 23, pp. 3717–3727, Dec. 2002, doi: 10.1242/jeb.205.23.3717.

[8] A. D. Kuo, "Energetics of actively powered locomotion using the simplest walking model," *J Biomech Eng*, vol. 124, no. 1, pp. 113–120, Feb. 2002, doi: 10.1115/1.1427703.

[9] P. G. Adamczyk and A. D. Kuo, "Redirection of center-of-mass velocity during the step-to-step transition of human walking," *J Exp Biol*, vol. 212, no. Pt 16, pp. 2668–2678, Aug. 2009, doi: 10.1242/jeb.027581.

[10] A. D. Kuo, J. M. Donelan, and A. Ruina, "Energetic consequences of walking like an inverted pendulum: step-to-step transitions," *Exerc Sport Sci Rev*, vol. 33, no. 2, pp. 88–97, Apr. 2005, doi: 10.1097/00003677-200504000-00006.

[11] O. Darici, H. Temeltas, and A. D. Kuo, "Optimal regulation of bipedal walking speed despite an unexpected bump in the road," *PLoS ONE*, vol. 13, no. 9, p. e0204205, Sep. 2018, doi: 10.1371/journal.pone.0204205.

[12] J. S. Matthis and B. R. Fajen, "Humans exploit the biomechanics of bipedal gait during visually guided walking over complex terrain," *Proc. R. Soc. B.*, vol. 280, no. 1762, p. 20130700, Jul. 2013, doi: 10.1098/rspb.2013.0700.

[13] A. S. Voloshina, A. D. Kuo, M. A. Daley, and D. P. Ferris, "Biomechanics and energetics of walking on uneven terrain," *J Exp Biol*, vol. 216, no. Pt 21, pp. 3963–3970, Nov. 2013, doi: 10.1242/jeb.081711.

[14] J. E. Himann, D. A. Cunningham, P. A. Rechnitzer, and D. H. Paterson, "Age-related changes in speed of walking.," *Med Sci Sports Exerc*, vol. 20, no. 2, pp. 161–166, Apr. 1988.

[15] S. H. Collins, P. G. Adamczyk, D. P. Ferris, and A. D. Kuo, "A simple method for
calibrating force plates and force treadmills using an instrumented pole," *Gait Posture*, vol.
29, no. 1, pp. 59–64, Jan. 2009, doi: 10.1016/j.gaitpost.2008.06.010.
[16] A. S. Voloshina, A. D. Kuo, D. P. Ferris, and C. D. Remy, "A model-based analysis of the
mechanical cost of walking on uneven terrain," Bioengineering, preprint, Jun. 2020. doi:
10.1101/2020.06.15.152330.
[17] D. B. Kowalsky, J. R. Rebula, L. V. Ojeda, P. G. Adamczyk, and A. D. Kuo, "Human
walking in the real world: Interactions between terrain type, gait parameters, and energy
expenditure," *PLoS ONE*, vol. 16, no. 1, p. e0228682, Jan. 2021, doi:
10.1371/journal.pone.0228682.
[18] O. Darici, H. Temeltas, and A. D. Kuo, "Anticipatory Control of Momentum for Bipedal
Walking on Uneven Terrain," Bioengineering, preprint, Sep. 2019. doi: 10.1101/769828.
[19] O. Darici and A. D. Kuo, "Humans optimally anticipate and compensate for an uneven step
during walking," *eLife*, vol. 11, p. e65402, Jan. 2022, doi: 10.7554/eLife.65402.
[20] O. Darici and A. D. Kuo, "Humans plan for the near future to walk economically on uneven
terrain," *Proc. Natl. Acad. Sci. U.S.A.*, vol. 120, no. 19, p. e2211405120, May 2023, doi:
10.1073/pnas.2211405120.
[21] R. McN. Alexander, "Energy-Saving Mechanisms in Walking and Running," *Journal of
Experimental Biology*, vol. 160, no. 1, pp. 55–69, Oct. 1991, doi: 10.1242/jeb.160.1.55.
[22] Y. Laufer, "Effect of age on characteristics of forward and backward gait at preferred and
accelerated walking speed," *J Gerontol A Biol Sci Med Sci*, vol. 60, no. 5, pp. 627–632,
May 2005, doi: 10.1093/gerona/60.5.627.
[23] Z. R. Kahaki, A. R. Safarpour, and H. Daneshmandi, "The spatiotemporal gait parameters
among people with visual impairment: A literature review study," *Oman J Ophthalmol*, vol.
16, no. 3, pp. 427–433, 2023, doi: 10.4103/ojo.ojo_24_23.
[24] M. Majlesi, N. Farahpour, and G. E. Robertson, "Comparisons of Spatiotemporal and
Ground Reaction Force Components of Gait Between Individuals with Congenital Vision
Loss and Sighted Individuals," *Journal of Visual Impairment & Blindness*, vol. 114, no. 4,
pp. 277–288, Jul. 2020, doi: 10.1177/0145482X20940429.
[25] H. J. Bennett, K. A. Valenzuela, K. Fleenor, S. Morrison, and J. A. Haegele, "Walking
biomechanics and energetics of individuals with a visual impairment: a preliminary report,"
hm, vol. 20, no. 4, pp. 8–18, 2019, doi: 10.5114/hm.2019.85094.
[26] A. R. Wu, C. S. Simpson, E. H. F. Van Asseldonk, H. Van Der Kooij, and A. J. Ijspeert,
"Mechanics of very slow human walking," *Sci Rep*, vol. 9, no. 1, p. 18079, Dec. 2019, doi:
10.1038/s41598-019-54271-2.
[27] R. E. Carlisle and A. D. Kuo, "Optimization of energy and time predicts dynamic speeds for
human walking," *eLife*, vol. 12, p. e81939, Feb. 2023, doi: 10.7554/eLife.81939.
[28] L. Majed, R. Ibrahim, M. J. Lock, and G. Jabbour, "Walking around the preferred speed:
examination of metabolic, perceptual, spatiotemporal and stability parameters," *Front.
Physiol.*, vol. 15, p. 1357172, Feb. 2024, doi: 10.3389/fphys.2024.1357172.
344