The Powered Simplest Walking Model Explains the Different Vertical Ground Reaction Force Amplitudes at Elevated Walking Speeds

Seyed-Saleh Hosseini-Yazdi [1,2], John EA Bertram [1,3]

[1]Department of Biomedical Engineering, Schulich School of Engineering, University of Calgary, AB, Canada

[2]Human Performance Laboratory, Faculty of Kinesiology, University of Calgary, AB, Canada

[3]Cumming School of Medicine, University of Calgary, AB, Canada

Conflict of Interest: None

Correspondence Address:

John EA Bertram

Biomedical Engineering Department, Schulich School of Engineering, University of Calgary

2500 University Dr NW, Calgary AB T2N1N4

Phone: (403) 210 9857

Email : jbertram@ucalgary.ca

Word count : 2980

Abstract:

Understanding the vertical ground reaction force (vGRF) profile offers important insight into how humans regulate mechanical work during walking. Although the characteristic double-hump vGRF pattern is well documented, the mechanical factors underlying asymmetry in peak amplitudes and midstance trough timing remain unclear. Using a simple powered walking model and an inverted pendulum simulation with constant hip torque, we examined how step-transition work—collision and push-off—shapes the vGRF trajectory. We further compared these predictions to empirical data spanning walking speeds from 0.8–1.4 $\mathrm{m.s^{-1}}$. The simple walking model predicted symmetric vGRF profiles across speeds because collision and push-off impulses were equal, resulting in passive single-support motion. In contrast, adding hip torque within the pendular model produced stance-phase asymmetries, shifting the vGRF trough earlier when torque added energy and later when torque dissipated energy. Empirical analysis revealed that collision and push-off impulses were generally unequal except at one speed, producing asymmetric vGRF peaks. At low speeds, push-off exceeded collision; at high speeds, the reverse occurred, consistent with a need for compensatory single-support positive work. These mechanical imbalances predicted systematic shifts in trough timing toward the dominant impulse. Therefore, we propose the Vertical GRF Trough Timing Index (vGRF-TTI), combined with collision and push-off peak amplitudes, as a clinically meaningful outcome capturing the balance of step-transition work. Earlier troughs with elevated collision peaks indicate impaired push-off or constrained gait conditions, whereas later troughs with larger push-off peaks reflect compensatory or enhanced propulsion. These metrics provide sensitive, mechanism-based indicators of gait efficiency and neuromotor control.

Introduction:

Walking is performed by exerting forces on the terrain. The reaction of the induced forces (Ground Reaction Forces: GRF) accelerates the walkers' Center of Mass (COM) in the direction of progression (Muller 2018). The vertical direction component is the largest since the legs support body weight (Masani, Kouzaki, and Fukunaga 2002) as a result, the analysis of vertical GRF has attracted much attention (Libera, Streamer, and Queen 2025; Schwartz, Rozumalski, and Trost 2008). Triaxial GRF can be collected on instrumented treadmills (Hosseini-Yazdi and Kuo 2024) in the lab setting but requires considerable upfront capital expenditure. Thus, many researchers may utilize inexpensive uniaxial force plates (Voloshina et al. 2013) or shoe insoles (Libera, Streamer, and Queen 2025) to avoid lab space and cost limitations. Vertical GRF profiles are affected by several factors, such as terrain complexity (Aminiaghdam and Rode 2017; Hosseini-Yazdi and Kuo 2025), view of approaching substrate irregularities (Hosseini-Yazdi Seyed-Saleh 2024; Majlesi, Farahpour, and Robertson 2020), age (Laufer 2005), etc. However, a limited mechanical explanation has been provided for those circumstances when the two vertical GRF peaks amplitudes are different and midstance trough is skewed, i.e. when the vertical GRF profile is asymmetric (Figure 1).

It is suggested that the first peak of the vertical ground reaction force is due to weight acceptance (Aminiaghdam et al. 2017; Libera, Streamer, and Queen 2025), i.e. a collision as the heel strike of the next stance limb affects the COM velocity vector (Adamczyk and Kuo 2009), and the second is due to ankle-generated force to accelerate the COM forward and upward (Adamczyk and Kuo 2009; Muller 2018). Various factors may affect the magnitude of vertical GRF peaks.

For example, carrying extra load distorts the vertical GRF profile (Aminiaghdam and Rode 2017;

Huang and Kuo 2014). Aminiaghdam et al. (Aminiaghdam and Rode 2017) have suggested that

greater loads and loading rates or lower unloading rates alter the vertical GRF peaks. It is also

proposed that walking with a crouched posture leads to higher vertical GRFs and loading rates

during early stance and lower vertical GRFs during the pre-swing phase (Aminiaghdam et al.

2017). It is further suggested that, modeling the human leg as a spring and damper, the damper

shifts the vertical GRF later in stance by increasing forces after the heel strike and decreasing

forces at toe-off, resulting in an early lift-off (Aminiaghdam et al. 2017).

Figure 1: Vertical ground reaction force (GRF) of walking changes when walking conditions are altered: (A) when walking speed
is varied (adopted from (Schwartz, Rozumalski, and Trost 2008)), (B) when the truck forward angle is raised (adopted from
(Aminiaghdam et al. 2017)). The solid black line represents free normal walking. While the vertical GRF for nominal walking
demonstrates a fairly symmetrical profile, deviations lead to asymmetrical trajectories.

In addition to load support, GRF represents the work performed by the legs on the COM to

sustain progression. It has been shown that human walking involves a step-to-step transition

during double stance over which the direction of COM velocity changes (Adamczyk and Kuo

2009). This velocity change requires energy dissipation (Kuo 2002). Therefore, if the kinetic

energy is to be preserved, the lost energy must be compensated. Such energy dissipation and

restoration are observed during the step transition (Donelan, Kram, and Kuo 2002a, 2002b) by

force application of leading and trailing legs generating the characteristic double hump shape

(Adamczyk and Kuo 2009). The two limbs work in concert to manage the transition where the

toe-off (push-off) force peak of the trailing leg is followed by the leading leg's heel-strike peak.

Such sequence is hypothesized to minimize step transition energy dissipation (Kuo 2002) and as

such the walking energetics (Donelan, Kram, and Kuo 2002a) (Figure 2).

Figure 2: A simple model of powered walking that explain the step-to-step transition required work performance. (A) in nominal walking, the energy compensation and energy dissipation are equal. (B) An example of deviation from nominal walking is when for a given speed, the magnitude of pre-emptive push-off that compensates step transition dissipation is less than required.

Limited studies explain vertical GRF peak amplitude asymmetry where the factors involved are

backed by experimental data. We hypothesize that the amplitude of vertical GRF peaks at heel-

strike and toe-off are determined by the performed walking speed collision and push-off

magnitudes. Hence, when walking speed deviates from the mechanically optimal speed

(Hosseini-Yazdi and Bertram 2025a), the two vertical GRF peak amplitudes become unequal

resulting in asymmetry in the GRF profile. Due to its relative magnitude, understanding the

vertical GRF profile may provide substantial insight into human locomotion (Fineberg et al.

2013). In this study, we first attempt to understand its variation using a simple walking and

pendular model for different conditions. Further, we compare the simulation results with analysis

of empirical data available in the literature.

Materials and Methods:

Since the vertical GRF magnitude of walking is relatively larger than other components, the step-

to-step transition work are often associated with it application (Adamczyk and Kuo 2009)(Figure

3). As a result, we focus on its role evaluation through a simple walking model simulation (Kuo

2002) and pendular model (R. McN. Alexander 1995; R.McNeill Alexander 1992) to examine its

finding against empirical data analysis (Hosseini-Yazdi Seyed-Saleh 2024).

Figure 3: Walking step-to-step transition involves a simultaneous positive and negative work performance to adjust the COM
velocity for the new stance while minimizing required mechanical work and as such metabolic cost of walking. (A) step
transition mechanical work by leading and trailing legs, (B) step transition impulses to perform step transition (adopted from
(Adamczyk and Kuo 2009).

Simulation:

138 We utilize a simple powered walking model that assumes concentrated mass in the pelvis with

139 rigid massless legs (Kuo 2002). It assumes that the entire step work, positive and negative,

140 occurs during the step transition when the previous stance leg push-off is followed by the

141 collision of the next stance leg. For a given walking speed (   ), the push-off impulse is

142        in which ' ' represents half the angle between leading and trailing legs at the

143 point of transition (Figure 2).

144 We break down the stance phase into three sub-phases; first double support representing the heel-

145 strike collision impulse, single support with no active work as an inverted pendulum, and the

146 second double support demonstrating the toe-off push-off impulse. Therefore, transition impulses

147 (co: for heel-strike or collision and po: for toe-off or push-off) can be represented as the area

148 under the force trajectory of the associated region. Thus, the step transition impulses can be

149 proxies for the amplitude of collision and push-off peaks, since the model assumes a very short

150 duration for impulse application (Kuo 2002) (Figure 4). We assume that the collision ends at the

151 first vertical GRF whereas push-off starts at the second peak (Adamczyk and Kuo 2009) (Figure

152 3).

Figure 4: A vertical GRF during a walking stance may be described by heel-strike weight acceptance collision, single support motion like an inverted pendulum, and the push-off. According to the model, the durations for active force applications are very short, therefore, for the sake of representation vertical force trajectories depicting active impulses are plotted close to vertical direction. (A) when vertical GRF is symmetrical, (B) when vertical GRF is asymmetrical.

During the single support phase, the motion of COM is proposed to closely resemble an inverted pendulum (Cavagna, Heglund, and Taylor 1977; Kuo, Donelan, and Ruina 2005a). Having short double support durations (R. McN. Alexander 1995; Kuo 2002), it is fair to consider pendular motion for the entire stance (Figure *5*). As such, the pendulum normalized tension can be represented as (Renjewski 2025):

$$\frac{T}{m.\,g} = \cos\theta - \frac{l}{g}\dot{\theta}^2 \qquad \text{Equation 1}$$

Therefore, the vertical component of the ground reaction forces is:

$$F_z = \frac{T}{m.\,g}\cos\theta \qquad \text{Equation 2}$$

For the sake of this analysis, we assume that the pendular motion starts at $\theta = +0.3\,rad.$, ends at $\theta = -0.3\,rad.$, and the angular velocity is $\dot{\theta} = -1\,rad/sec$. We assume that single support active work is exerted by a constant hip torque (Hosseini-Yazdi and Bertram 2025b; Kuo, Donelan, and Ruina 2005a; Voloshina et al. 2020). We consider three hip torque magnitudes ($\tau(t) \sim cte.$): -0.15, 0, and 0.15 to evaluate the effect of single support work on the profile of the vertical GRF. Therefore, the equation of motion for inverted pendulum becomes (Kuo 2002):

$$\ddot{\theta} = \frac{g}{l}\sin\theta + \frac{\tau(t)}{m.\,l^2} \qquad \text{Equation 3}$$

Since, the COM motion based on the right-hand rule is in negative direction, the positive torque reduces the energy of pendulum while the negative torque increases it. We also check if the vertical reaction force is symmetrical or is skewed to a particular direction using a Parabola Skewness Index: (PSI) in which if vertex is shifted to the right PSI > 0, if vertex is shifted to the left PSI < 0, for complete symmetry PSI is zero (|PSI| < 0.001). Here, the 'l' stands for the leg length (here 1 m) whereas the 'g' represents the gravitational acceleration.

Empirical Data Analysis:

During the stance, four distinct phases in the COM power profile can be recognized (Kuo, Donelan, and Ruina 2005a). While collision and push-off are the negative and positive work during the double support, the rebound and preload are the positive and negative work during single support (Hosseini-Yazdi and Bertram 2025a) (Figure 6). We consider collision and push-off as the result of associated impulses (Adamczyk and Kuo 2009; Kuo 2002). Similar to the simulation, we assume that the collision ends at the first vertical GRF while push-off starts at the second peak (Adamczyk and Kuo 2009) (Figure 3 and Figure 4). Therefore, collision and push-off impulse magnitudes define the vertical GRF first and second peak amplitudes.

Figure 5: the simulation of single support with inverted pendulum motion in which all the mass is concentrated and legs are rigid. A constant torque is applied to the COM to modulate its motion. It is to represent the hip work.

We utilize the presented empirical data suggesting trajectories for collision and push-off when walking speed varies (0.8   to 1.4   ) (Hosseini-Yazdi Seyed-Saleh 2024). We remove the random effect of treadmill calibration (Hosseini-Yazdi and Bertram 2025b, 2025a). For any speed, the step transition impulses are calculated by   , where ' ' and ' ' are work and its associated impulse, respectively (Darici, Temeltas, and Kuo 2018).

194 Figure 6: During stance phase, the COM power depicts four distinct sub-phases. It starts with a collision of the heel-strike during
195 the first double support. It is followed by the positive and negative work of single support, i.e. rebound and preload. It ends with
196 the push-off that infuses positive work to COM (adopted from *(Hosseini-Yazdi and Bertram 2025a)*)

Results:

Based on the simulation, we observed that with walking speed increase (0.8   to 1.4

), the step transition impulses grew from 0.20   to 0.57   . The step transition

collision and push-off also rose from 0.02   to 0.16   As such, the simulation

demonstrated that the mechanical energy dissipation of collision and the active work of push-off

were equal for any speed of the utilized range (Figure 7). Thus, the single support after the step-

transition did not demand any regulatory active work. In other words, the simulation predicted

symmetrical profiles for walking GRF.

The simulation suggested close profile for total pendular tension and the vertical reaction force.

Without hip torque, the duration of stance was 1.09 sec while normalized pendular tension and

vertical reaction were 0.99 and 0.98, respectively. With a hip torque that resisted the pendular

motion (positive direction), the stance duration increased to 1.51 sec (+%38.5) while the

changes in tension (1.00, or +%1.0), and vertical rection (0.99, or +%1.0) were

relatively small. On the other hand, with a hip torque enhancing motion (in negative direction),

the stance duration decline to 0.93 sec (-%17.2) while the tension (0.98, or -%1.0) and

vertical reaction (0.97, or -%1.0) reduced slightly. We also observed asymmetries when

pendular motions were performed along with hip torque. When there was no hip torque, the start

and finish vertical reaction forces were 0.82 with PSI of 0.000 while with supporting (in negative

direction) and opposing (in positive direction) torques the finishing vertical reaction forces were

0.79 (PSI = -0.013, skewness to left or earlier stance) and 0.83 (PSI = 0.012, skewness to right

or later stance), respectively. In other words, supporting hip torque, skewed the pendular force

peak toward early stance, whereas an opposing torque pushed it towards the later stance. This

further represented asymmetries when a hip torque was applied during the pendular motion

(Figure 8).

Figure 7: Simple walking model simulation prediction for (A) the step transition impulses, (B) step transition work for given
walking speed range. For any speed, the model assumes equal dissipation and energy compensation to maintain the walker's
mechanical energy during the step transition, as such the single support may be done passively. Therefore, it predicts a
symmetrical vertical GRF profile for any given speed.

In contrast to simple walking model, the empirical data analysis predicted asymmetrical GRF

peaks except for one particular walking speed. As walking speed increased, the associated push-

off and collision varied from 0.16   to 0.38   , while the collision dissipation

magnitude varied from 0.06   to 0.44   . As a result, the associated heel-strike and toe-

off impulses ranged from 0.41   to 0.61   , and from 0.24   to 0.67   ,

respectively (Figure 9). Therefore, at lower walking speeds, the push-off peaks were to be higher

than collisions', whereas at elevated speeds the order was reversed. Therefore, single support

needed regulating active work. At   , the collision and push-off impulses were

equal, and thus single support did not require active work performance. In other words, the heel-

strike and push-off peaks were dissimilar except at the designated speed where the magnitudes of

collision and push-off were equal.

Figure 8: The simulation of single support motion with an inverted pendulum when hip torque is present. The
simulation suggests that the presence of hip torque changes the magnitude of peak force and trajectory, yet the
influence on the duration of stance, i.e. force profile is more pronounced. (A) Total pendulum tension, (B) vertical
reaction force of pendulum.

Discussion:

GRF analysis is the simplest approach to study human walking (Park and Kim 2022) and is

utilized for clinical biomechanic evaluations (Campanelli 2023). The GRF indicates the

instantaneous acceleration of COM. The GRF profiles are affected by walking conditions since

humans modulate their walking by exerting forces and performing mechanical work (Kuo,

Donelan, and Ruina 2005b). Since vertical GRF is the dominant force during human walking

(Libera, Streamer, and Queen 2025), we have attempted to provide a mechanistic view to explain

its trajectory as walking conditions are altered.

Figure 9: The analysis of empirical data for step transition (A) work, (B) derived impulses. The analysis suggests that there is
only one walking speed (designated at   ) for which the magnitudes of energy dissipation and compensation are
equal. As such, the associated vertical GRF must have a symmetrical profile with inverted pendulum like motion for the single
support phase in which no active muscle work is performed. Therefore, for speeds less than the designated value, the push-off
peak is predicted to be larger than collision peak. The order is predicted to be reverse for speeds higher than the designated value.

In this study we have used a simple walking model focusing on step-to-step transition (Kuo

2002). Then, we have utilized a pendular model (R. McN. Alexander 1995; Cavagna, Heglund,

and Taylor 1977). Although pendular model is able to predict the horizontal force of walking

fairly correctly, it does not show the "M" shape for the vertical force component. The pendular

model presents a concavity that is opposite of what is observed experimentally (Campanelli

2023). However, it provides valuable insights about human walking. Pendular model suggests

that single support phase is performed with minimal torque, i.e. free or passive motion

(R.McNeill Alexander 1992; Cavagna, Heglund, and Taylor 1977; Kuo, Donelan, and Ruina

2005a). Nevertheless, there are studies that highlight the role of single support work to regulated

COM mechanical energy throughout the stance (Hosseini-Yazdi and Bertram 2025a, 2025b,

2025c). Therefore, we have evaluated the impact of constant torque (Voloshina et al. 2020) for a

pendular model, whether opposing or supporting the COM motion, with the passive motion.

Finally, we have utilized the available empirical data to predict the symmetry or asymmetry of

vertical GRF based on the step transition work and subsequent mechanical energy imbalance.

The simulation based on the simplest walking model (Kuo 2002) suggests a symmetrical force

profile for any adopted walking speed. Since this model assumes that entire step active work

occurs during a short duration at step-to-step transition (Donelan, Kram, and Kuo 2002a), it

accepts a complete passive motion for the single support phase (Cavagna, Heglund, and Taylor

1977). Thus, this model suggests nominal walking for any adopted speed. Since it is shown that

active work performance is not limited to the step-transition only (Hosseini-Yazdi and Bertram

2025a, 2025c), we may consider this as a modification approach to enhance the simple walking

model capabilities despite its current strength (Darici and Kuo 2022; Darici, Temeltas, and Kuo

2018, 2020).

To consider the single support active work regulation, the utilized constant hip torque leads to

changes in vertical reaction force. We observe that torque application mainly affects the time

duration of single support and as such the magnitude of applied impulses. The amplitudes of

peak forces also change and the force profiles become asymmetric. Based on this simulation, we

expect vertical GRF trough to shift to later stance when applied torque dissipates COM energy

whereas when hip torque adds to COM energy, it shifts the GRF trough toward the early stance.

Based on empirical data analysis, for a given walking speed, we observe imbalance in step-

transition work. At elevated walking speeds when the collision exceeds the push-off, there must

be a mechanical energy addition during the single support phase (Hosseini-Yazdi and Bertram

2025a). Since with walking speed increase, the duration of double support declines (Williams

and Martin 2019), the step-transition work must happen in shorter time frame. As such, we

expect dominant heel-strike peaks compared to push-off. We also expect that the vertical GRF

trough to be skewed towards the collision peak. Such prediction is supported by examining

associated vertical GRF profiles (Nilsson and Thorstensson 1989; Schwartz, Rozumalski, and

Trost 2008).

On the contrary when the push-off is greater than collision at reduced walking speeds, there must

be energy dissipation during the single support phase. Hence, we expect a dominant push-off

peak versus collision with single support GRF trough being skewed toward push-off. Although

experimental data supports the skewness of trough toward later stance (Nilsson and Thorstensson

1989), it is hard to recognize a dominant push-off peak (Schwartz, Rozumalski, and Trost 2008).

The extension of double support phase with reduced speed (Williams and Martin 2019) may

spread push-off impulse application over expanded time frame. Therefore, the push-off peak

amplitude is reduced.

When step transition work is balanced, i.e. collision = push-off, the vertical GRF must be

symmetrical. As such, not only are the amplitudes of push-off and collision peaks equal, but also

the single support phase must closely resemble an inverted pendulum with passive motion (zero

hip torque). Therefore, the single support force must be symmetrical with the trough at

midstance. It is suggested that the free walking coincides with mechanically preferred walking

speed (Hosseini-Yazdi and Bertram 2025a) during which step-transition work is balance, and

there is no active work within the single support phase (Hosseini-Yazdi and Bertram 2025b). The

vertical GRF of free walking depicts a fairly symmetrical profile (Schwartz, Rozumalski, and

Trost 2008).

Humans modulate their gaits to adjust to the imposed walking conditions (Hosseini-Yazdi Seyed-

Saleh 2024). One method might be to adjust the force generated to perform active work,

although not all the modulation happens with force exertion, nor the ability and capability of

force generation, especially in short time intervals, can contribute to gait control. Nonetheless,

GRF analysis is a powerful tool that enables us to search for other gait compensation methods,

recognize possible deficits, that possibly could be used for rehabilitation or conditioning. The

magnitude and ease of measurement (Libera, Streamer, and Queen 2025), makes vertical

components the first target for gait analysis.

We suggest that the vertical GRF profile is affected by the step-transition and subsequent single

support active work. Only when walking is mechanically preferred (Hosseini-Yazdi and Bertram

2025a), the vertical GRF is symmetrical. Any walking condition that prohibits or disrupts push-

off performance, must lead to collision dissipation growth (Hosseini-Yazdi and Bertram 2025b).

Therefore, the active work of single support shifts the vertical GRF trough closer to heel-strike

(early stance). Such vertical GRF trajectories may be observed during challenging walking

conditions like uneven walking (Hosseini-Yazdi and Kuo 2025), restricted lookahead or with age

(Hosseini-Yazdi Seyed-Saleh 2024). On the contrary, when push-off is more than collision, the

midstance trough is shifted toward toe-off (later stance).

A clinically meaningful outcome from our study is the Vertical GRF Trough Timing Index

(vGRF-TTI)—the percentage of stance at which the minimum vertical GRF occurs—combined

with the amplitude of the early (collision) and late (push-off) vertical GRF peaks. Together, these

features capture the mechanical balance of step-to-step transition. When push-off is reduced or

disrupted—such as with aging, pathology, uneven terrain, or restricted lookahead—the trough

shifts earlier toward heel-strike and the collision peak increases while the push-off peak

diminishes, indicating elevated collision energy loss and insufficient single-support active work.

Conversely, when push-off exceeds collision, the trough shifts later toward toe-off and the push-

off peak becomes larger relative to the collision peak, reflecting enhanced or compensatory late-

stance power generation. Because symmetrical vertical GRF profiles only arise during

mechanically preferred walking, deviations in trough timing and peak amplitudes provide

sensitive, clinically accessible indicators of gait inefficiency, impaired neuromotor control, and

altered mechanical work strategies.

References:

Adamczyk, Peter G., and Arthur D. Kuo. 2009. "Redirection of Center-of-Mass Velocity during
the Step-to-Step Transition of Human Walking." *The Journal of Experimental Biology*
212(Pt 16): 2668–78. doi:10.1242/jeb.027581.

Alexander, R. McN. 1995. "Simple Models of Human Movement." *Applied Mechanics Reviews*
48(8): 461–70. doi:10.1115/1.3005107.

Alexander, R.McNeill. 1992. "Simple Models of Walking and Jumping." *Human Movement*
Science 11(1–2): 3–9. doi:10.1016/0167-9457(92)90045-D.

Aminiaghdam, Soran, and Christian Rode. 2017. "Effects of Altered Sagittal Trunk Orientation
on Kinetic Pattern in Able-Bodied Walking on Uneven Ground." *Biology Open*:
bio.025239. doi:10.1242/bio.025239.

Aminiaghdam, Soran, Christian Rode, Roy Müller, and Reinhard Blickhan. 2017. "Increasing
Trunk Flexion Transforms Human Leg Function into That of Birds despite Different Leg
Morphology." *The Journal of Experimental Biology* 220(Pt 3): 478–86.
doi:10.1242/jeb.148312.

Campanelli, Leonardo. 2023. "A Simple Model of Human Walking." *Journal of Medical Science*
92(1): e817. doi:10.20883/medical.e817.

Cavagna, G. A., N. C. Heglund, and C. R. Taylor. 1977. "Mechanical Work in Terrestrial
Locomotion: Two Basic Mechanisms for Minimizing Energy Expenditure." *The*
American Journal of Physiology 233(5): R243-261.
doi:10.1152/ajpregu.1977.233.5.R243.

Darici, Osman, and Arthur D Kuo. 2022. "Humans Optimally Anticipate and Compensate for an
Uneven Step during Walking." *eLife* 11: e65402. doi:10.7554/eLife.65402.

Darici, Osman, Hakan Temeltas, and Arthur D. Kuo. 2018. "Optimal Regulation of Bipedal Walking Speed despite an Unexpected Bump in the Road" ed. Jeffrey M Haddad. *PLOS ONE* 13(9): e0204205. doi:10.1371/journal.pone.0204205.

Darici, Osman, Hakan Temeltas, and Arthur D. Kuo. 2020. "Anticipatory Control of Momentum for Bipedal Walking on Uneven Terrain." *Scientific Reports* 10(1): 540. doi:10.1038/s41598-019-57156-6.

Donelan, J. Maxwell, Rodger Kram, and Arthur D. Kuo. 2002a. "Mechanical Work for Step-to-Step Transitions Is a Major Determinant of the Metabolic Cost of Human Walking." *The Journal of Experimental Biology* 205(Pt 23): 3717–27. doi:10.1242/jeb.205.23.3717.

Donelan, J. Maxwell, Rodger Kram, and Arthur D. Kuo. 2002b. "Simultaneous Positive and Negative External Mechanical Work in Human Walking." *Journal of Biomechanics* 35(1): 117–24. doi:10.1016/s0021-9290(01)00169-5.

Fineberg, Drew B., Pierre Asselin, Noam Y. Harel, Irina Agranova-Breyter, Stephen D. Kornfeld, William A. Bauman, and Ann M. Spungen. 2013. "Vertical Ground Reaction Force-Based Analysis of Powered Exoskeleton-Assisted Walking in Persons with Motor-Complete Paraplegia." *The Journal of Spinal Cord Medicine* 36(4): 313–21. doi:10.1179/2045772313Y.0000000126.

Hosseini-Yazdi Seyed-Saleh. 2024. "Energetics and Biomechanics of Uneven Walking for Young and Older Adults." University of Calgary. https://prism.ucalgary.ca/server/api/core/bitstreams/be2fa66b-26a2-4421-9d30-dfcc55dcfb35/content.

Hosseini-Yazdi, Seyed-Saleh, and John E.A. Bertram. 2025a. "Center of Mass Work Analysis Predicts Preferred Walking Speeds for Varying Walking Conditions." *Journal of Biomechanics* 185: 112682. doi:10.1016/j.jbiomech.2025.112682.

Hosseini-Yazdi, Seyed-Saleh, and John E.A. Bertram. 2025b. "Optimum Push-off for Uneven Walking Based on the Just-in-Time Strategy: Walking with Interrupted Push-Off Is Mechanically Costly." *Journal of Biomechanical Engineering*: 1–20. doi:10.1115/1.4069666.

Hosseini-Yazdi, Seyed-Saleh, and John Ea Bertram. 2025c. "The Consequence of Uneven Walking Transitory Modulation Strategies: A Simulation-Based Approach." *Journal of Theoretical Biology* 614: 112234. doi:10.1016/j.jtbi.2025.112234.

Hosseini-Yazdi, Seyed-Saleh, and Arthur D. Kuo. 2024. "A Split-Belt Instrumented Treadmill with Uneven Terrain." *Journal of Biomechanics* 176: 112376. doi:10.1016/j.jbiomech.2024.112376.

Hosseini-Yazdi, Seyed-Saleh, and Arthur D. Kuo. 2025. "The Energetic Cost of Human Walking as a Function of Uneven Terrain Amplitude." *Journal of Experimental Biology*: jeb.249840. doi:10.1242/jeb.249840.

Huang, Tzu-Wei P., and Arthur D. Kuo. 2014. "Mechanics and Energetics of Load Carriage during Human Walking." *The Journal of Experimental Biology* 217(Pt 4): 605–13. doi:10.1242/jeb.091587.

Kuo, Arthur D. 2002. "Energetics of Actively Powered Locomotion Using the Simplest Walking Model." *Journal of Biomechanical Engineering* 124(1): 113–20. doi:10.1115/1.1427703.

Kuo, Arthur D., J Maxwell Donelan, and Andy Ruina. 2005a. "Energetic Consequences of Walking Like an Inverted Pendulum: Step-to-Step Transitions:" *Exercise and Sport Sciences Reviews* 33(2): 88–97. doi:10.1097/00003677-200504000-00006.

Kuo, Arthur D., J. Maxwell Donelan, and Andy Ruina. 2005b. "Energetic Consequences of Walking like an Inverted Pendulum: Step-to-Step Transitions." *Exercise and Sport Sciences Reviews* 33(2): 88–97. doi:10.1097/00003677-200504000-00006.

Laufer, Yocheved. 2005. "Effect of Age on Characteristics of Forward and Backward Gait at Preferred and Accelerated Walking Speed." *The Journals of Gerontology. Series A, Biological Sciences and Medical Sciences* 60(5): 627–32. doi:10.1093/gerona/60.5.627.

Libera, Theresa L., Jill Streamer, and Robin M. Queen. 2025. "Peak Weight Acceptance, Mid Stance Trough, and Peak Push-Off Force Symmetry Are Decreased in Older Adults Compared With Young Adults." *Journal of Applied Biomechanics* 41(2): 117–23. doi:10.1123/jab.2024-0027.

Majlesi, Mahdi, Nader Farahpour, and Gordon E. Robertson. 2020. "Comparisons of Spatiotemporal and Ground Reaction Force Components of Gait Between Individuals with Congenital Vision Loss and Sighted Individuals." *Journal of Visual Impairment & Blindness* 114(4): 277–88. doi:10.1177/0145482X20940429.

Masani, Kei, Motoki Kouzaki, and Tetsuo Fukunaga. 2002. "Variability of Ground Reaction Forces during Treadmill Walking." *Journal of Applied Physiology (Bethesda, Md.: 1985)* 92(5): 1885–90. doi:10.1152/japplphysiol.00969.2000.

Muller, Bertram. 2018. *Handbook of Human Motion*. New York, NY: Springer Berlin Heidelberg.

Nilsson, J., and A. Thorstensson. 1989. "Ground Reaction Forces at Different Speeds of Human Walking and Running." *Acta Physiologica Scandinavica* 136(2): 217–27. doi:10.1111/j.1748-1716.1989.tb08655.x.

Park, Ji Su, and Choong Hyun Kim. 2022. "Ground-Reaction-Force-Based Gait Analysis and Its Application to Gait Disorder Assessment: New Indices for Quantifying Walking Behavior." *Sensors (Basel, Switzerland)* 22(19): 7558. doi:10.3390/s22197558.

Renjewski, Daniel. 2025. *Knees, Ankles, Feet, and Toes: The Biomechanics of Bipedal Human Walking*. Technical University of Munich. doi:10.14459/2025MD1767337.

Schwartz, Michael H., Adam Rozumalski, and Joyce P. Trost. 2008. "The Effect of Walking
Speed on the Gait of Typically Developing Children." *Journal of Biomechanics* 41(8):
1639–50. doi:10.1016/j.jbiomech.2008.03.015.

Voloshina, Alexandra S., Arthur D. Kuo, Monica A. Daley, and Daniel P. Ferris. 2013.
"Biomechanics and Energetics of Walking on Uneven Terrain." *The Journal of
Experimental Biology* 216(Pt 21): 3963–70. doi:10.1242/jeb.081711.

Voloshina, Alexandra S., Arthur D. Kuo, Daniel P. Ferris, and C. David Remy. 2020. *A Model-
Based Analysis of the Mechanical Cost of Walking on Uneven Terrain*. Bioengineering.
preprint. doi:10.1101/2020.06.15.152330.

Williams, Daniel S., and Anne E. Martin. 2019. "Gait Modification When Decreasing Double
Support Percentage." *Journal of Biomechanics* 92: 76–83.
doi:10.1016/j.jbiomech.2019.05.028.

448