Oscillations create groove: A reservoir model for learning complex drumming performances

Yuji Kawai[1*], Shinya Fujii[2], Minoru Asada[1,3,4,5],

1 Symbiotic Intelligent Systems Research Center, Institute for Open and Transdisciplinary Research Initiatives, Osaka University, Suita, Osaka, Japan
2 Faculty of Environment and Information Studies, Keio University, Fujisawa, Kanagawa, Japan
3 International Professional University of Technology in Osaka, Kita-ku, Osaka, Japan
4 Academy of Emerging Sciences, Chubu University, Kasugai, Aichi, Japan
5 Center for Information and Neural Networks, National Institute of Information and Communications Technology, Suita, Osaka, Japan

* kawai@otri.osaka-u.ac.jp

Abstract

Musical performances, particularly drumming, intricately balance rhythmic patterns and creative expression, all heavily influenced by the concept of "groove." This study explored how the brain learns and internalizes complex rhythms and grooves from a computational perspective. The cerebellum and basal ganglia play key roles in rhythm perception, production, and timing. We utilized an oscillation-driven reservoir computing model, which is a simplified recurrent neural network designed for timing learning, to acquire complex rhythms. The model was trained to replicate the drumming style of Jeff Porcaro by learning his hi-hat patterns. Analyses revealed that the model's outputs, including fluctuations in interbeat timings and amplitudes, were similar to the original drumming. Next, it was trained to generate multidimensional drum kit performances for various genres (funk, jazz, samba, and rock). Model outputs had timing deviation and audio features related to a sense of groove, similar to the original performances. By incorporating the oscillations of multiple frequencies into the reservoir, the model reproduced fluctuations of timing intervals (microtiming) and amplitudes, as well as audio features of each musical genre. Our results indicated that oscillation-driven reservoir computing can successfully replicate the timing and rhythmic complexity of professional drumming, suggesting that it is a common computational principle for motor timing and rhythm generation. Furthermore, this approach offers insights into the neural underpinnings of musical groove, shedding light on how the brain processes and reproduces intricate rhythmic patterns.

Author summary

Drumming is a sophisticated art form combining rhythmic precision and creative flair, encapsulated by the elusive quality of "groove." Understanding how the brain generates these complex rhythms can provide insights into both musical and neural functions. In this study, we employed oscillation-driven reservoir computing to model the principal neural processes involved in learning and generating complex drum rhythms in the cerebellum and basal ganglia. We trained the model using the

renowned drummer Jeff Porcaro's hi-hat patterns and expanded its capabilities to produce multi-instrument drum performances. By introducing oscillations of different frequencies to reservoir computing, we enhanced the reservoir's complex dynamics to create dynamic, non-repetitive, fluctuating time intervals and amplitudes of skilled drumming perfromances. Our findings demonstrate that this computational approach can emulate the nuanced microtiming and audio features essential for skilled drumming, shedding light on the potential neural mechanisms underlying skilled musical performances.

Introduction

Music performance, particularly drumming, involves a complex interplay between rhythmic patterns and creative expressions. The process of acquiring these rhythms and embodying the elusive quality of "groove" is a quest that has fascinated musicians and researchers alike [1–10]. How does our brain learn and internalize the intricate rhythms and grooves that define musical artistry?

The term "groove" is primarily defined as a pleasurable desire to move in response to music [1–4]. Such pleasurable and emotional responses to music have been associated with anticipation and predictability [5–8, 11]. Witek et al. [4] created drum rhythm patterns of varying rhythmic complexities (degree of syncopation) and investigated rhythmic patterns that induced a strong groove. They found that participants experienced groove when listening to rhythms with a medium level of complexity or medium degree of syncopation. By contrast, simple and complex rhythms were rated as having a weaker sense of groove. This suggests that medium levels of prediction errors in music are most pleasurable and rewarding [6–8].

In addition to the complexity of beats like syncopation, some studies have examined what musical characteristics related to a groove sensation (for a review, see Ref. [9]). The timing and velocity of beats in the performances of professional musicians include fluctuations [10, 12–14], which create pleasurable emotional and behavioral responses [15, 16]. Such a slight timing deviation is termed as "microtiming," which usually less than 50 ms [17, 18]. Räsänen et al. [13] extracted Jeff Porcaro's hi-hat playing sound from Michael McDonald's "I Keep Forgettin' " [19] and analyzed the hi-hat amplitudes and interbeat intervals, i.e., times between percussion strokes or hits. The intervals drift from the 16th note pattern and follow a Gaussian-type distribution, indicating expressive microtiming. Furthermore, detrended fluctuation analysis (DFA) [20] revealed that, like $1/f$ fluctuations, the fluctuations of the intervals and amplitudes have persistent correlations over long time scales, i.e., data points separated by long time intervals are not independent but exhibit correlated dependence. In addition to microtiming, other audio features related to a groove sensation have also been investigated. Madison et al. [2] found that beat salience (a measure of rhythmic periodicity) and event density (a measure of the variability in the event onset velocity signal) correlate with groove ratings. Stupacher et al. [21] corroborated Madison et al. [2]'s result and reported that audio signal intensity, its variability, and attack slope of onsets increase groove ratings.

There is considerable evidence that auditory-motor brain regions activate when listening to music and rhythm [9, 22–28]. Kasdan et al. [28] conducted a meta-analysis of 30 functional magnetic resonance imaging studies that investigated musical rhythm processing. They revealed a large network involving the auditory and motor regions, including the bilateral superior temporal cortices, supplementary motor area, basal ganglia, and cerebellum. In particular, cerebellar activity is greater when the rhythm is more complex. It has been suggested that there is a close relationship between the perception and production of rhythms and that there is overlapped neural

circuits [26, 29]. The subcortical areas, basal ganglia, and cerebellum respond to auditory time perception and production [24, 26, 30], and patients with focal lesions in these areas show reduced tracking at the beat frequency [31]. Furthermore, it has been reported that musical training induces plastic changes in the cortical auditory-motor regions, as well as in the cerebellum and basal ganglia [32]. From a broader perspective, these areas play important roles in learning and control [33–36]. The basal ganglia perform reward-based learning with dopaminergic modifications, while the cerebellum learns by adjusting its connections (long-term depression: LTD) based on feedback (error signals) from climbing fibers. These signals help fine-tune motor skills and coordination [34]. Through these learning mechanisms, these regions can also learn single-interval timing [37–39]. Although the functional segregation of the cerebellum and basal ganglia in timing perception has been debated [24, 40–42], these regions should share computational principles that underlie the learning of timing and rhythm.

Reservoir computing, a type of recurrent neural network (RNN), was used to model the cerebellum [43–45] and basal ganglia (striatum) [46–48]. Standard reservoir computing consists of a fixed randomly connected RNN, termed a reservoir [49, 50]. The input to the reservoir network induces complex reservoir dynamics, and its network states are integrated using a weighted sum (readout). The readout weights are modified to obtain the desired output, for which the least-squares method is often used. In cerebellar models, granule cells perceive cortical inputs and form an RNN with the Golgi cells. Readout training is realized through Purkinje cell plasticity (LTD). In the basal ganglia models, the striatum receives cortical inputs and dopamine modification in the striatum is regarded as readout training. Reservoir computing, which enables temporal information processing based on neural dynamics, has been utilized as a model to explain motor timing learning [48, 51–55]. In the motor timing task, there was a stimulus-free interval between stimuli. Therefore, the neural (reservoir) activity elicited by the initial onset signal must be sustained for an interval without any input. Vincent-Lamarre et al. [52] demonstrated that providing a reservoir with sinusoidal oscillations allows the reservoir to sustain their activity during an interval, allowing timing to be successfully learned. Kawai et al. [55] improved performance by adding output feedback to the model and showed that it could learn and predict complex time series. To date, however, reservoir models have not learned and generated real-world rhythms.

In this study, we applied the reservoir model proposed by Kawai et al. [55] as a timing-learning machine to learn and generate complex drum rhythms. The readout was trained with the desired target time series from the encoded performances of professional drummers. By feeding back the output of a reservoir to its input, the reservoir learns the next output from the current output; i.e., it predicts one time ahead. When generating rhythms, the reservoir repeats this one-time-ahead prediction and provides feedback to generate a time series. In standard reservoir models, the generated time series tends to be simple and periodic. To represent fluctuating time intervals and amplitudes of skilled drumming performances, we input oscillations with multiple frequencies to the reservoir. It is expected that the input of oscillation superimposition produces more complex dynamics than the network-inherent dynamics, which facilitates the learning of acyclic drumming. This model suggests that oscillation-driven reservoir computing is a common computational principle used for timing and rhythm generation. Model outputs are then analyzed to determine to what extent they mimic the original performances with respect to microtiming and audio features that related to a groove sensation.

First, the model learns the one-dimensional hi-hat rhythm pattern by Jeff Porcaro [13]. We tested the models with oscillations in different frequency bands and

considered the nature of the generated time series. Using the same analyses as Räsänen et al. [13], we examined whether the rhythms generated after learning were similar to the original performance. Next, the model was trained to perform as a multidimensional drum kit. Microtiming and audio features of the outputs were analyzed and compared with those of the original performances. We present examples of the generated time series to demonstrate that the reservoir model can copy and generalize the performances in different genres.

Related studies

Entrainment [56–58] and error-correction [59–62] models have been proposed to explain the ability to perceive a beat from a computational perspective (for a review, see Ref. [63]). The entrainment models rely on oscillators that resonate and entrain their inputs. Entrainment refers to the synchronization of two or more oscillating systems as a result of an external forces or interactions between them. Beat perception is regarded as synchronizing an external rhythmic input with a preprepared oscillators. Classical error-correction models adjust the timing of the next finger tap to reduce the error between the current tap and the stimulus [59]. Bose et al. [60] proposed an error-correction model in which a beat-generation oscillator learned the spiking phase and period of a stimulus neuron receiving an isochronous stimulus sequence. A comparator counts the number of spikes in the oscillator and stimulus neuron and adjusts the oscillator frequency according to the error between their counts. Egger et al. [61] derived an error-correction model using a firing-rate neuron model. The neurons build an oscillator that activates a ramp function, and its value is reset when a certain threshold is exceeded. The ramping speed depends on an input parameter that control the oscillator frequency. The input value was adjusted at each reset such that the oscillator frequency matched the time between successive stimuli. These models represent isochronous rhythms by tuning the frequency of an oscillator or the frequencies of oscillators. Simple oscillators can only represent simple beats and do not generate complex rhythms. The reservoir model used in this study is an error-correction model because it adjusts the readout based on errors. However, the reservoir network transforms the oscillation inputs into complex dynamics with large dimensions, which generates complex rhythms.

Machine learning methods for generating music and complex rhythms are being actively developed [64, 65]. From reviewing the generation of drum performances, Hutchings [66] proposed a method for generating a full drum kit part for a provided kick-drum sequence using an RNN sequence-to-sequence method. Makris [67] combined a long short-term memory- (LSTM) based architecture with a feedforward neural network module. The former module learns the sequences of successive drum events, whereas the latter deals with musical information on the guitar, bass, beat structure, and tempo. Thus, it can generate rhythms conditioned by musical information. Variational autoencoders (VAEs) learn to compress the input data into a latent distribution and reconstruct their input data [68]. The decoder network generates a novel output from the latent space. GrooVAE [69] automatically composes drum performances using a VAE, which generates and controls expressive drum performances. Furthermore, Transformers [70], which are a type of a deep learning model, have been applied in the field of music generations (e.g., [71–73]). The learning algorithms of these machine learning systems [64–73] are based on error back-propagation and do not aim to understand the brain processing. Their learning costs are very high, and they require large computational resources and training data. In contrast, reservoir computing is more biologically plausible because its learning algorithm does not rely on backpropagation and can be realized by simple rules, including LTD and dopaminergic modification in readout. Reservoir computing has

Fig 1. Oscillation-driven reservoir computing. Sinusoidal oscillators drive a reservoir, which is a randomly connected recurrent neural network with fixed connection weights. The output is given as a linear summation of the reservoir states (readout, shown as orange arrows), which is fed back into the reservoir. Only the readout weights are modulated using recursive least-squares. Adapted from Ref. [55].

fewer training parameters and can, therefore, learn from a small amount of data. This study is the first to use reservoir computing to generate drum performances.

Results

Reservoir model

The reservoir is a randomly connected RNN with firing-rate neural units that receive multiple sinusoidal oscillator inputs (Fig. 1). We used ten oscillators with different $[f_{\min}, f_{\max}]$ Hz random frequency ranges and random initial phases, which were fixed between trials. The initial states of the reservoirs were randomly determined. To reduce the initial state dependency, an onset signal was fed into the reservoir at time zero. This signal is a short, strong single pulse that resets the reservoir activity [51, 53]. The output was obtained by the linear summation (readout) of the reservoir activity. The output was then fed back into the reservoir at the next time step. The readout weights were trained to minimize the errors between the outputs and target time series using recursive least squares [74], which is an online learning method. The other connection weights for the oscillator inputs, onset signal input, reservoir RNN, and output feedback were determined randomly and fixed through learning.

Learning the hi-hat performance

The target time series was encoded from the hi-hat performance by Jeff Porcaro [75] in "I Keep Forgettin' " [19] by Michael McDonald. We used the dataset of hi-hat hit timings and their amplitudes available in Ref. [13]. We encoded these data into a target time series (see the Methods section, Fig. 2). These hi-hat performance data, which consist of 16th notes, have six 16th rests after 4 s, and bar breaks after these rests. The relevant audio file is attached as Audio S1.

Fig 2. Target 20-s time series obtained from the hi-hat performance.

The reservoir computing model was trained with the target 20-s time series and generated 40-s outputs. During the generation, the model was not given the target and generated outputs autonomously. The latter 20 s, in particular, are an inexperienced period during which the model is expected to produce outputs analogous to the target; that is, it generalizes the target. Fig. 3A shows an example of the output generated by reservoir computing without oscillation inputs. The output fell into a completely periodic orbit and did not have the rests and fluctuations characteristic of the original performance. The audio file of the example output shown in Fig. 3A is attached as Audio S2.

In contrast to its periodic output, oscillations in the reservoir enabled it to reproduce and generalize the target (Fig. 3B–D). The behavior of the outputs depended on the frequency bands of the oscillations. When oscillations of $[10, 25]$ Hz were given to the reservoir (Fig. 3B), the model reproduced the target during the first 20 s whereas the output was disturbed and lacked generalization ability in the second half. Fig. 3C shows the output of the model with $[25, 50]$ Hz oscillators. In the first half, the model followed the target; in the second half, the output was analogous to the target. When further high-frequency oscillations ($[50, 100]$ Hz) were applied to the reservoir, the model did not replicate the target perfectly but produced an output similar to that of the target (Fig. 3D). The respective audio files are attached as Audios S3 to S5.

We quantified the similarity between the model-generated outputs and the original data regarding fluctuations and patterns of interbeat timing intervals and amplitudes. In the analyses, the original data for all times of one song were used. While all the amplitude data were analyzed, only the 16th note intervals were analyzed. Therefore, only the interval data between 100 ms and 200 ms were analyzed. The model with $[50, 100]$ Hz oscillators generated a 200-s output, the first 20 s of which were discarded, and the remaining 180-s portion was included in the analyses. The results of these analyses were averaged among the outputs of 20 models with different random seeds. Histograms of the timing intervals and amplitudes of the hi-hat hits are shown in Fig. 4. The timing intervals of both the original and model followed Gaussian-type distributions with means of 156.6 ms and 155.4 ms and standard deviations of 8.7 ms and 10.2 ms, respectively. This indicates that the model reproduced the original distribution of timing fluctuations, termed microtiming. For the amplitude histograms, the original data had two peaks, while the model data had one peak. Nevertheless, the distribution of the model amplitudes was biased to the right, with large amplitudes representing accentuation.

Second, DFA, a method of studying long-range correlations in time-series data, particularly $1/f$ noise [20], was applied to the timings and amplitudes. Long-range correlations refer to the persistence of dependencies between values that are far apart in a sequence. These correlations indicate that values separated by a long time period

Fig 3. Example outputs of the reservoir model trained with the hi-hat time series. The solid blue and dashed green curves represent the model output and target respectively. A. Output of the reservoir model without oscillation inputs. B–D. Outputs of the reservoir models respectively with $[10, 25]$ Hz, $[25, 50]$ Hz, and $[50, 100]$ Hz, oscillation input ranges.

are still statistically related, which can indicate the underlying processes or structures driving the data. See the Methods section for a detailed description of DFA. The scaling exponent α indicates the nature of the correlations; when $\alpha = 0.5$: the series is uncorrelated, e.g., for white noise; when $0.5 < \alpha < 1$: the series has long-range positive correlations; when $0 < \alpha < 0.5$: the series has long-range negative correlations. The results from DFA for the fluctuations of the intervals and amplitudes are shown in Fig. 5. For the intervals, the results of the original data can be approximated by two lines bordered by a scale of 40, with exponents respetively of 0.31 (anticorrelations) and 0.72 (correlations). Results of the analysis of the model outputs are similarly approximated by two lines, and in Fig. 5B the exponents are 0.25 and 0.37; the means (standard deviations) of the 20 runs were 0.29 (0.068) and 0.39 (0.13). In Fig. 5D, for the amplitudes, the results of both the original data and model outputs were approximated by a single straight line with respective exponents of 0.63 and 0.40. The averaged exponent was 0.41 (0.085). These results suggests that the series of intervals and amplitudes generated by the model had long-range negative correlations, which means that increases in the series were likely to be followed by decreases and that

Fig 4. Histograms of the timing intervals and amplitudes of hi-hat hits. A, C: timing intervals and amplitudes of the original hi-hat performance data, respectively. B, D: timing intervals and amplitudes of the model outputs, respectively.

decreases were likely to be followed by increases. This pattern creates a zig-zag or oscillating behavior in the data.

Third, Fig. 6 shows the Poincaré plots or return maps of the timing intervals, which are scatter graphs created by plotting each data point in a time series against the next one in the sequence. The plots of the original and model data show negative correlations, with correlation coefficients were -0.48 and -0.55, respectively. The average (standard deviation) of the correlation exponents for the 20 model outputs was -0.48 (0.14). These negative correlations mean that the interval following a beat with a shorter interval tends to be longer, and vice versa.

Finally, we analyzed the short-scale patterns of variations in the intervals and amplitudes for bars consisting of 16 hits. Fig. 7A shows 16th note intervals during the first 10 bars of the original data, i.e., the intro part of the song. Short, long, and short patterns are observed at the beginning of the bars. Because the model outputs had no bar representation, 16 hits after the 16th rests were analyzed. There were 417 cases of 16th rest, followed by 15 16th notes in the 20 trials, which were averaged. Fig. 7B shows the short-long-short-long pattern of intervals after the 16th rests. Similar analyses were performed for the amplitude series (Fig. 7C and D). A high-low-high-low pattern was observed in both the original and modeled amplitude data. However, although the amplitudes of the 1st, 5th, 9th, and 13th hits were higher than those in the original pattern, no accent patterns were observed in the model outputs.

Fig 5. Results from DFA. A, C: Timing intervals and amplitudes of the original hi-hat performance data, respectively. B, D: Timing intervals and amplitudes of the model outputs, respectively.

Learning drum-kit performances

Next, the reservoir computing model with $[50, 100]$-Hz oscillators was trained using the target encoded from the multidimensional drum-kit performances. From the Groove MIDI Dataset [69], funk, jazz, samba, and rock files were selected and the first 20 s of each was used as a target. The hit onset timings' and their amplitudes' data were extracted from the MIDI files and encoded into time-series data, as in the case of the hi-hat detailed above. A readout layer was provided for each multiple-drum instrument. The audio files of the targets are attached as Audios S6 to S9.

Figs. 8–11 respectively show example outputs of the model trained with the funk, jazz, samba, and rock performances. Their audio files are attached as Audios S10 to S13. In each case, a performance similar to the target was generated. In the case of funk (Fig. 8), a series of snare hits emerged, which was not present. The jazz-learned model reproduced its characteristic fill-in (tom, snare, and kick patterns in that order), indicating the model learned such spatiotemporal pattern (Fig. 9). The samba output was relatively periodic, but the snare patterns dynamically transitioned. In the case of rock (Fig. 11), a clear inter-modality rule was acquired that a snare (rim) was not struck when a snare (head) was hit with a large amplitude. These results demonstrate that the model could learn the coordination between drums to create dynamic, complex rhythmic patterns.

We investigated whether microtiming of the hi-hat performances in the model outputs reproduced that of the originals. The hi-hat rhythm was better suited for this microtiming analysis because it was more periodic than those of other drum parts. Twenty models with different random seeds each output 60 seconds, and their hi-hat

Fig 6. Poincaré plot (return map) of the timing intervals. A, B: Results of the original data and model output, respectively.

Table 1. Means and standard deviations of microtiming

Genre	Source	Mean (s)	Standard deviation (s)
Funk	Original	0.186	0.0108
	Model	0.188	0.0207
Jazz	Original	0.519	0.0115
	Model	0.518	0.0219
Samba	Original	0.517	0.0144
	Model	0.517	0.0187
Rock	Original	0.240	0.0194
	Model	0.241	0.0199

hit timing intervals were calculated. The hi-hat intervals for the entire original performances were also calculated. Fig. 12 shows histograms of the hi-hat interbeat intervals of the four original performances and model outputs. Histograms of the original performances showed bimodal peaks because the original hi-hat rhythm changed in the middle of the performances; therefore, in Fig. 12, the original histograms were cut out at the same intervals as the histograms of the model outputs. The means and standard deviations of those histograms are listed in Table 1. These results indicate that the average timing intervals matched between the original and model, whereas the microtiming variability of the model outputs was greater than that of the original. This increased variability is a property of the model, as it was also observed in the previous hi-hat performance analysis (see Fig. 4).

The similarity of the audio features between the model outputs and original performances was quantified. We calculated six audio features related to groove feel [21] from the audio files of the original performances and the 20 model outputs. The six features are as follows.

- Root mean square (RMS) energy: global signal intensity (RMS of the amplitude).

- Spectral flux: changes in the spectrum of an audio signal.

- Attack: mean attack (amplitude) slope of all hit onsets.

- Pulse clarity: clarity of rhythmic or metrical pulsation.

- Event density: the number of events per second.

- RMS standard deviation (SD): variability of the signal intensity.

Fig 7. Short-scale patterns. A. 16th note intervals during the first 10 bars of the original data. B. 16th note intervals after a 16th rest in the model outputs. C. Amplitudes of 16th notes during the first 10 bars of the original data. D. Amplitudes of 16th notes after a 16th rest in the model outputs. Error bars indicate the standard deviation of the 10 bars (A and C) or 417 cases (B and D).

The values of these audio features are shown in Fig. 13. This figure shows that most of the audio features of the original and model were consistent, indicating their acoustical similarity. For pulse clarity (Fig. 13D), the values of the model outputs were smaller than those of the original. Since pulse clarity quantifies the periodicity of a rhythm, this result indicates that the periodicity or metric-structural components of the model outputs was reduced.

Discussion

We developed a model that learns complex drum performances using the oscillation-driven reservoir computing. This model learned real-world drum performances and replicated the fluctuations of interbeat timings (microtiming) and audio features, which relate to a sense of groove. Furthermore, it could generalize the short target data samples to generate rhythms that were close to but different from the target, which could be called improvisation based on an example. In the learning task of playing a multidimensional drum kit, the model could learn the spatiotemporal patterns between the instruments, resulting in dynamic and consistent performances, including fill-ins. Most existing models of beat perception and generation directly adjust the frequencies of neural oscillators to fit isochronous target rhythms [59–62]. This approach allows only a simple rhythm to be generated. In the present model, the oscillator frequencies are fixed, and the network dynamics are tuned via readout training, which enables the model to learn complex real-world rhythms.

Oscillation-driven reservoir computing was designed for learning timings [55]. Time

Fig 8. Example outputs of the reservoir model trained with the funk performance. The solid-blue and dashed-green curves respectively represent the model's output and the target.

can be measured by reservoir activity driven by oscillator inputs, even during periods of no external stimulus. In this study, oscillators were used to generate complex reservoir activity. Conventional reservoir computing without oscillator inputs produces simple periodic outputs. In contrast, oscillator inputs enable the reservoirs to generate complex rhythmic patterns. Therefore, we suggest this as a unified model for learning timings and rhythms. In the human brains, the cerebellum and basal ganglia are thought to be responsible for such learning [9, 22–28]. Indeed, the fact that previous computational models in these areas also used a reservoir computing framework [43–48] further supports our model.

The model's performance depended on the given frequency bands. Low-frequency ([10, 25] Hz) inputs contributed to the accurate reproductions of the targets, whereas high-frequency ([50, 100] Hz) inputs contributed to generalizing the target to generate target-like performances. This tendency is similar to that observed in a previous study on chaotic time-series prediction [55]. We hypothesize that the low-frequency inputs acted as "time stamps" for the targets. That is, the model learned the relationship between the specific dynamics induced by the oscillator inputs, which represented time, and the targets. However, the model that overfitted the relationship between specific reservoir states and the target was unable to generalize it to unlearned states. In contrast, high-frequency inputs did not affect the reservoir states because the neuron model had a time constant and did not change states at high speed. Therefore, the model somewhat preserved the network-inherent dynamics, and thus prevented overfitting.

This suggests that different neural mechanisms are involved in for copying and improvising musical performances. High-frequency (beta- and gamma-band) oscillations were observed in magnetoencephalography (MEG) during music beat perception, imagery, and timing prediction [76, 77]. An electroencephalogram (EEG) study by Rosen et al. [78] found clusters of beta- and gamma-band activity when higher-quality and lower-quality improvisations were compared in jazz performances.

Fig 9. Example outputs of the reservoir model trained with the jazz performance. The solid-blue and dashed-green curves respectively represent the model's output and the target.

Subsequently, a group of the authors [79] recorded jazz guitarists' EEGs while improvising to provide chord sequences. They found that high-flow (effortless attention to the task) was associated with high-frequency (gamma-band) clusters in the left opercula and in the left temporal gyri. Such high-frequency cortical activity may facilitate the generalization of musical performances. Using EEGs to detect further high-frequency (high-gamma-band) signals is difficult, but studies using electrocorticography (ECoG) have revealed that rhythmic information is contained in the high-gamma signals in the auditory cortex [80–82]. This confirms that listening to music induces high-frequency signals, and it would be interesting to study how this relates to improvising performances.

Whatever frequency bands were used, these were not directly related to the tasks of the rhythm learning. For example, the average interbeat intervals for the hi-hat performance is 0.156 s, which corresponds to approximately 6.4 Hz. The frequencies of the input oscillators were much higher than those and were randomly determined. Even though the model did not have an external "metronome," it acquired an internal representation of a metronome as a result of training, resulting in stable performances.

In learning the hi-hat rhythm, the model generated performances with fluctuations

Fig 10. Example outputs of the reservoir model trained with the samba performance. The solid-blue and dashed-green curves respectively represent the model's output and the target.

in the intervals and amplitudes. These fluctuations are not random but exhibited the same distributions and patterns (e.g., the high-low-high-low pattern) as the original fluctuations. Such repetitive timing deviation is called *systematic* microtiming [2, 83], and microtiming within the same instrument is considered *horizontal*. Therefore, the model could copy *systematic horizontal* microtiming of the professional hi-hat performance. However, the long-range correlations of the model fluctuations were negative, showing an inverse relationship to those of the original fluctuations. This means that the model outputs were stable; that is, an increase at one time point tended to be followed by a decrease, and vice versa. In addition, this model could not learn the concepts of bars and meters. The 16th rests, which marks the end of the bars in the original performance, was randomly placed in the model's outputs. Therefore, this model fails to learn the long-term rhythmic patterns. A solution may conceivably be to include meter information in the oscillators. An EEG study revealed that gamma-band signals in the auditory cortex reflect the metric structure [84]. Other studies have also shown that brain oscillations in various frequency bands contain information about the meters of rhythms being heard [76, 85, 86]. By including meter information in the oscillations, it may be possible to learn long-term rhythmic

Fig 11. Example outputs of the reservoir model trained with the rock performance. The solid-blue and dashed-green curves respectively represent the model's output and the target.

patterns.

In learning the drum-kit performances of various genres, the model generated outputs similar to the original performances. The microtiming analysis of the hi-hat performances showed that the model outputs had horizontal microtiming with greater variability than the originals. This might be due to the variability in neural dynamics of the model. Nevertheless, their standard deviations were less than 20 ms, which are considered as microtiming, defined as timing deviation of 50 ms or less. The audio feature analysis showed that with except for the pulse clarity feature, the model outputs copied the features that correlate with a sense of groove, indicating that the model can copy groovy performances. The pulse clarity values for periodicity were reduced because the model did not represent long-term structures, including meter and bar, as discussed earlier.

This model uses professional performance as a target and copies it in just ten training sessions. Therefore, it does not explain how the drumming performance improves. In reality, performance skills are acquired gradually during numerous practice routines designed and arranged by teachers and coaches [87, 88]. Performing music involves more than a single neural circuit but a variety of sensorimotor and

Fig 12. Histograms of the timing intervals of hi-hat hits in the four original performances (left panels) and model outputs (right panels). A–D: timing intervals for the funk, jazz, samba, and rock performances, respectively.

cognitive functions [89], such as motor control [90,91], planning and temporal control [92], and feedback monitoring [93]. An important future research direction is to investigate the processes for acquiring such complex skills to construct their computational models.

Methods

Oscillation-driven reservoir computing [55]

The reservoir is a network with N neural units whose state vector is represented as $\mathbf{x}(t) = (x_1, x_2, \ldots, x_N)^\top$ at time t. The initial values of $\mathbf{x}(t)$ were randomly drawn

Fig 13. Audio features of the original performances (blue) and the model outputs (green). A–F: bar plots for RMS energy, spectral flux, attack, pulse clarity, event density, RMS SD, respectively. In model outputs, the error bars indicate the standard deviations among 20 models.

from a uniform distribution of $[-1, 1]$. Its network dynamics follows

$$\tau_{\mathrm{tc}} \frac{\mathrm{d}\mathbf{x}(t)}{\mathrm{d}t} = -\mathbf{x}(t) + \mathbf{W}\mathbf{r}(t) + \mathbf{W}_{\mathrm{os}}\mathbf{o}(t) + \mathbf{W}_{\mathrm{in}}s(t) + \mathbf{W}_{\mathrm{fb}}\mathbf{y}_{\mathrm{fb}}(t), \tag{1}$$

$$\mathbf{r}(t) = \tanh(\mathbf{x}(t)), \tag{2}$$

where τ_{tc} denotes the time constant, and $\mathbf{W}$, $\mathbf{W}_{\mathrm{os}}$, $\mathbf{W}_{\mathrm{in}}$, and $\mathbf{W}_{\mathrm{fb}}$ respectively denote the reservoir recurrent weight matrix, oscillator input weight matrix, onset signal input weight vector, and feedback weight matrix. The variables $\mathbf{o}(t)$, $s(t)$, and $\mathbf{y}_{\mathrm{fb}}(t)$ respectively denote the oscillation inputs, an onset signal, and the output feedback signals.

$\mathbf{W}$ is an $N \times N$ weight matrix, each component of which has a non-zero value with a probability p. The non-zero values were drawn from a Gaussian distribution with a mean of zero and a standard deviationn of $g/\sqrt{pN}$, where g is the gain of the reservoir weights. The oscillators are N_{os} sinusoids. The vector of the oscillator input is represented as $\mathbf{o}(t) = (\sin(2\pi f_1 t + \phi_1), \sin(2\pi f_2 t + \phi_2), \ldots, \sin(2\pi f_{N_{\mathrm{os}}} t + \phi_{N_{\mathrm{os}}}))^{\top}$, where f_i and ϕ_i respectively denote the frequency and the random initial phase. The frequencies are randomly determined from a uniform $[f_{\min}, f_{\max}]$ distribution range. Parameters f_i and ϕ_i are fixed during learning and testing. $\mathbf{W}_{\mathrm{os}}$ is an $N_{\mathrm{os}} \times N$ matrix for the oscillator input to the reservoir. The scalar onset signal $s(t)$ from -50 ms to 0 ms, is 1 and at other times, 0. $\mathbf{W}_{\mathrm{in}}$ is the weight vector of size N for the onset signal inputs into the reservoir. The output is fed back into all reservoir units as $\mathbf{y}_{\mathrm{fb}}(t)$. The feedback weights $\mathbf{W}_{\mathrm{fb}}$ is an $N_{\mathrm{ro}} \times N$ matrix. The components of $\mathbf{W}_{\mathrm{os}}$, $\mathbf{W}_{\mathrm{in}}$, and $\mathbf{W}_{\mathrm{fb}}$ are drawn from Gaussian distributions with a mean of zero and standard deviation of $g_{\mathrm{os}}/\sqrt{N_{\mathrm{os}}}$, g_{in}, $g_{\mathrm{fb}}/\sqrt{N_{\mathrm{ro}}}$, where g_{os}, g_{in}, g_{fb} denote the gains of the oscillation input weights, onset signal input weights, and feedback weights, respectively.

To obtain N_{ro}-dimensional output $\mathbf{y}(t) = (y_1, y_2, \ldots, y_{N_{\mathrm{ro}}})$, $\mathbf{r}(t)$ is weighted as

$$\mathbf{y}(t) = \mathbf{W}_{\mathrm{ro}}(t)\tilde{\mathbf{r}}(t), \tag{3}$$

where $\mathbf{W}_{\mathrm{ro}}(t)$ denotes a $(3/2 * N) \times N_{\mathrm{ro}}$ readout weight matrix, and $\tilde{\mathbf{r}}(t)$ is the concatenation of $\mathbf{r}(t)$ and a vector of half components of $\mathbf{r}(t)$ squared. This has been

empirically shown to improve forecasting efficiency [94–96]. $\mathbf{W}_{\mathrm{ro}}(t)$ has an initial value for the zero matrix and is modulated by recursive least-squares, which is an online learning method. At time t, $\mathbf{W}_{\mathrm{ro}}(t)$ is updated as follows:

$$
\begin{aligned}
\mathbf{W}_{\mathrm{ro}}(t + \Delta t) &= \mathbf{W}_{\mathrm{ro}}(t) - \mathbf{e}(t)\mathbf{P}(t)\mathbf{r}(t), & (4) \\
\mathbf{e}(t) &= \mathbf{y}(t) - \mathbf{d}(t), & (5)
\end{aligned}
$$

where $\mathbf{d}(t)$, $\mathbf{e}(t)$, and $\mathbf{P}(t)$ respectively denote a target, error, and $(3/2 * N) \times (3/2 * N)$ matrix. $\mathbf{P}(t)$ is updated as

$$
\mathbf{P}(t + \Delta t) = \mathbf{P}(t) - \frac{\mathbf{P}(t)\mathbf{r}(t)\mathbf{r}^{\top}(t)\mathbf{P}(t)}{1 + \mathbf{r}^{\top}(t)\mathbf{P}(t)\mathbf{r}(t)}. \tag{6}
$$

The initial value of $\mathbf{P}(t)$ is given as $(1/a)\mathbf{I}$, where $\mathbf{I}$ denotes the identity matrix, and a is a constant.

In the simulations, the numerical solutions to Eq. (1) were obtained using the Euler method, where the simulation step size Δt was set to 1 ms. The recursive least-squares (Eqs. (4)–(6)) was applied once every two steps, and Δt was set to 2 ms. The simulation started at -250 ms, and the training period was from 1 ms to 20,000 ms. The training was repeated ten times, and the performance was evaluated during the untrained testing period.

We used the parameter values listed in Table 2 in all the simulations. These parameters follow those in Ref. [55]. To learn the hi-hat-only performance, we set $N_{\mathrm{ro}} = 1$; to learn the funk performance, $N_{\mathrm{ro}} = 3$; and to learn other drum-kit performances, $N_{\mathrm{ro}} = 5$.

Table 2. Parameter settings

Parameter	Description	Value
N	Reservoir network size	5000
N_{os}	Number of oscillators	10
g	Gain of reservoir weights	1.0
g_{os}	Gain of oscillation input weights	0.5
g_{in}	Gain of onset signal input weights	5
g_{fb}	Gain of feedback weights	3
p	Connection probability	0.1
τ	Time constant	10 ms
a	Initial value for recursive least squares	1

Detrended fluctuation analysis

DFA is a statistical method widely used to analyze the presence of long-range correlations in time-series data, particularly for non-stationary data, such as heartbeat time series [20], brain oscillations [97,98], and human musical rhythm [13,99]. We applied DFA to the interbeat intervals and amplitudes. Let $u(i)$ be the ith hit time, and the ith interbeat interval be denoted by $\tau(i) = u(i+1) - u(i)$. Then, we calculate the fluctuation of the interval from the mean $\langle \tau \rangle$, i.e., $\Delta\tau(i) = \tau(i) - \langle \tau \rangle$. The fluctuations were integrated as

$$
z(i) = \sum_{j=1}^{i} \Delta\tau(j) \ \text{ for } i = 1, 2, \ldots, M, \tag{7}
$$

where M is the number of data points. Next, the integrated time series was divided into boxes of equal length s. Within each box, a least-squares line $(z_s(i))$ was fitted to

the data points $(y(i))$ to capture the linear trend. The trend represented by $z_s(i)$ was subtracted from the original data $(z(i))$ within the box, resulting in the detrended fluctuation: $(z_{\text{detrended}}(i) = z(i) - z_s(i))$. Finally, the root-mean-square fluctuations were calculated for each box by the following

$$F_k(s) = \sqrt{\frac{1}{s}\sum_{i=ks+1}^{ks+s}\left[z_{\text{denrended}}(i)\right]^2}\ \text{ for } k = 1, 2, \ldots, \frac{M}{s} - 1. \tag{8}$$

Finally, $F_k(s)$ was averaged over all M/s elements to obtain $F(s) = \langle F_k(s)\rangle$. This procedure was repeated for different box size s. In the presence of scaling, the relationship between $F(s)$ and s may be described by $F(s) \propto s^\alpha$, where the scaling exponent α is the slope of the line relating $\log F(s)$ and $\log s$. Eq. (7) and below applied similarly to the amplitude data series.

Encoding and decoding of drum performances

To learn the hi-hat performance, we used a dataset of hi-hat hit timings and their amplitudes [13]. This data was obtained by applying a 100th-order FIR filter with a cutoff frequency of 8 kHz to the original sound source to extract only the hi-hat sound and then applying an onset detection algorithm [13]. To encode this data into the target time series, we first added 0.2 to all amplitudes to emphasize small amplitude hits. Single Gaussian pulses centered on the hit timing were then placed on a time series. The Gaussian amplitudes were the combined amplitudes of the hits, and their standard deviations were set to 30 ms. We cut out the first 20 s of the beginning and normalized it for the maximum and minimum to be 1 and 0 (see Fig. 2).

To convert the model output into sound data, a moving average filter was first applied to the output time series and a maximum value detection was performed to obtain hit timings and their amplitudes. The amplitudes were renormalized such that the maximum and minimum amplitudes were those of the original. Hits with amplitudes below 0.1 were ignored. We then placed hi-hat audio data at the timing points, and their intensity (loudness) was linearly modulated by the amplitudes.

We used the Groove MIDI Dataset [69] which is a large dataset comprising 1150 MIDI files of drum performances by ten professional drummers in various genres. From this dataset, we selected four performances.

- Funk: drummer1/session1/1_funk_80_beat_4-4.mid,

- Jazz: drummer1/session1/4_jazz-funk_116_beat_4-4.mid,

- Samba: drummer1/session1/28_latin-samba_116_beat_4-4.mid,

- Rock: drummer1/session3/1_rock-prog_125_beat_4-4.mid.

Their MIDI files distinguishes between different types of drumming, e.g., between an open or closed hi-hat; however, hi-hats, snares, toms, and cymbals were grouped into one dimension each owing to the infrequency of hits. This procedure reduced the numbers of dimensions (pitches) of funk, jazz, samba, and rock respectively from seven to three, from 12 to five, from six to five, and from six to five. Similar to above, the model outputs were converted to data of peak timings and their amplitudes. Fluctuation in the peaks resulted in small hits with small timing intervals to appear. Therefore, hits with timing intervals of 5 ms or less were removed as noise. The data were converted to the MIDI format and then converted to audio data.

In the audio analysis, we used Musical Information Retrieval (MIR) Toolbox for MATLAB [100]. The MIR Toolbox functions we used for the analysis of the six features are listed below.

- RMS energy: *mirrms*.

- Spectral flux: Averaged over the entire period of a spectral flux time series as the output of *mirflux*.

- Attack: *mirpulseclarity* using 'Attack' option.

- Pulse clarity: *mirpulseclarity* using 'MaxAutocor' option.

- Event density: *mireventdensity*.

- RMS SD: Standard deviation over the entire period of an RMS time series as the output of *mirrms*.

Supporting information

- Audio S1. Audio file of the hi-hat learning target.

- Audio S2. Audio file of an output of the model without oscillations.

- Audio S3. Audio file of an output of the model with $[10, 25]$ Hz oscillators.

- Audio S4. Audio file of an output of the model with $[25, 50]$ Hz oscillators.

- Audio S5. Audio file of an output of the model with $[50, 100]$ Hz oscillators.

- Audio S6. Audio file of the funk learning target.

- Audio S7. Audio file of the jazz learning target.

- Audio S8. Audio file of the samba learning target.

- Audio S9. Audio file of the rock learning target.

- Audio S10. Audio file of a model output trained with the funk.

- Audio S11. Audio file of a model output trained with the jazz.

- Audio S12. Audio file of a model output trained with the samba.

- Audio S13. Audio file of a model output trained with the rock.

Acknowledgments

This work was supported by JST PRESTO (JPMJPR23S5 and JPMJPR23S9), JSPS KAKENHI (23K25750 and 24H02199), and the project, JPNP16007, commissioned by the New Energy and Industrial Technology Development Organization (NEDO).

References

1. Madison G. Experiencing groove induced by music: consistency and phenomenology. Music Perception. 2006;24(2):201–208.

2. Madison G, Gouyon F, Ullén F, Hörnström K. Modeling the tendency for music to induce movement in humans: first correlations with low-level audio descriptors across music genres. Journal of Experimental Psychology: Human Perception and Performance. 2011;37(5):1578–1594.

3. Janata P, Tomic ST, Haberman JM. Sensorimotor coupling in music and the psychology of the groove. Journal of Experimental Psychology: General. 2012;141(1):54.

4. Witek MAG, Clarke EF, Wallentin M, Kringelbach ML, Vuust P. Syncopation, body-movement and pleasure in groove music. PLOS ONE. 2014;9(4):e94446.

5. Vuust P, Frith CD. Anticipation is the key to understanding music and the effects of music on emotion. Behavioral and Brain Sciences. 2008;31(5):599–600.

6. Vuust P, Dietz MJ, Witek M, Kringelbach ML. Now you hear it: A predictive coding model for understanding rhythmic incongruity. Annals of the New York Academy of Sciences. 2018;1423(1):19–29.

7. Koelsch S, Vuust P, Friston KJ. Predictive processes and the peculiar case of music. Trends in Cognitive Sciences. 2019;23(1):63–77.

8. Vuust P, Heggli OA, Friston KJ, Kringelbach ML. Music in the brain. Nature Reviews Neuroscience. 2022;23(5):287–305.

9. Etani T, Miura A, Kawase S, Fujii S, Keller PE, Vuust P, et al. A review of psychological and neuroscientific research on musical groove. Neuroscience & Biobehavioral Reviews. 2023;158:105522.

10. Iyer V. Embodied mind, situated cognition, and expressive microtiming in African-American music. Music perception. 2002;19(3):387–414.

11. Gebauer L, Kringelbach ML, Vuust P. Ever-changing cycles of musical pleasure: the role of dopamine and anticipation. Psychomusicology: Music, Mind, and Brain. 2012;22(2):152–167.

12. Fujii S, Hirashima M, Kudo K, Ohtsuki T, Nakamura Y, Oda S. Synchronization error of drum kit playing with a metronome at different tempi by professional drummers. Music Perception: An Interdisciplinary Journal. 2011;28(5):491–503.

13. Räsänen E, Pulkkinen O, Virtanen T, Zollner M, Hennig H. Fluctuations of hi-hat timing and dynamics in a virtuoso drum track of a popular music recording. PLoS One. 2015;10(6):e0127902.

14. Câmara GS, Nymoen K, Lartillot O, Danielsen A. Timing is everything··· or is it? Effects of instructed timing style, reference, and pattern on drum kit sound in groove-based performance. Music Perception: An Interdisciplinary Journal. 2020;38(1):1–26.

15. Nelias C, Sturm EM, Albrecht T, Hagmayer Y, Geisel T. Downbeat delays are a key component of swing in jazz. Communications Physics. 2022;5(1):237.

16. Kilchenmann L, Senn O. Microtiming in swing and funk affects the body movement behavior of music expert listeners. Frontiers in psychology. 2015;6:1232.

17. Iyer VS. Microstructures of feel, macrostructures of sound: Embodied cognition in West African and African-American musics. University of California, Berkeley; 1998.

18. Butterfield MW. The Power of Anacrusis: Engendered Feeling in Groove-Based Musics. Music Theory Online. 2006;12(4).

19. McDonald M. In: I Keep Forgettin'. Warner Bros; 1982.

20. Peng CK, Havlin S, Stanley HE, Goldberger AL. Quantification of scaling exponents and crossover phenomena in nonstationary heartbeat time series. Chaos: An Interdisciplinary Journal of Nonlinear Science. 1995;5(1):82–87.

21. Stupacher J, Hove MJ, Janata P. Audio features underlying perceived groove and sensorimotor synchronization in music. Music Perception: An Interdisciplinary Journal. 2016;33(5):571–589.

22. Zatorre RJ, Chen JL, Penhune VB. When the brain plays music: auditory–motor interactions in music perception and production. Nature Reviews Neuroscience. 2007;8(7):547–558.

23. Grahn JA, Rowe JB. Feeling the beat: premotor and striatal interactions in musicians and nonmusicians during beat perception. Journal of Neuroscience. 2009;29(23):7540–7548.

24. Teki S, Grube M, Griffiths TD. A unified model of time perception accounts for duration-based and beat-based timing mechanisms. Frontiers in Integrative Neuroscience. 2012;5:90.

25. Grahn JA. Neural mechanisms of rhythm perception: current findings and future perspectives. Topics in Cognitive Science. 2012;4(4):585–606.

26. Fujii S, Wan CY. The role of rhythm in speech and language rehabilitation: The SEP hypothesis. Frontiers in Human Neuroscience. 2014;8:777.

27. Merchant H, Grahn J, Trainor L, Rohrmeier M, Fitch WT. Finding the beat: a neural perspective across humans and non-human primates. Philosophical Transactions of the Royal Society B: Biological Sciences. 2015;370(1664):20140093.

28. Kasdan AV, Burgess AN, Pizzagalli F, Scartozzi A, Chern A, Kotz SA, et al. Identifying a brain network for musical rhythm: A functional neuroimaging meta-analysis and systematic review. Neuroscience & Biobehavioral Reviews. 2022;136:104588.

29. Konoike N, Nakamura K. Cerebral substrates for controlling rhythmic movements. Brain Sciences. 2020;10(8):514.

30. Mayville JM, Jantzen KJ, Fuchs A, Steinberg FL, Kelso JAS. Cortical and subcortical networks underlying syncopated and synchronized coordination revealed using fMRI. Human Brain Mapping. 2002;17(4):214–229.

31. Nozaradan S, Schwartze M, Obermeier C, Kotz SA. Specific contributions of basal ganglia and cerebellum to the neural tracking of rhythm. Cortex. 2017;95:156–168.

32. Penhune VB. In: Thaut MH, Hodges D, editors. Musical expertise and brain structure: the causes and consequences of training. Oxford University Press; 2019. p. 419–438.

33. Jueptner M, Weiller C. A review of differences between basal ganglia and cerebellar control of movements as revealed by functional imaging studies. Brain: A Journal of Neurology. 1998;121(8):1437–1449.

34. Doya K. Complementary roles of basal ganglia and cerebellum in learning and motor control. Current Opinion in Neurobiology. 2000;10(6):732–739.

35. Ito M. Mechanisms of motor learning in the cerebellum. Brain Research. 2000;886(1-2):237–245.

36. Groenewegen HJ. The basal ganglia and motor control. Neural Plasticity. 2003;10(1-2):107–120.

37. Buhusi CV, Meck WH. What makes us tick? Functional and neural mechanisms of interval timing. Nature Reviews Neuroscience. 2005;6(10):755–765.

38. Grondin S. Timing and time perception: A review of recent behavioral and neuroscience findings and theoretical directions. Attention, Perception, & Psychophysics. 2010;72(3):561–582.

39. Coull JT, Cheng RK, Meck WH. Neuroanatomical and neurochemical substrates of timing. Neuropsychopharmacology. 2011;36(1):3–25.

40. Dreher JC, Grafman J. The roles of the cerebellum and basal ganglia in timing and error prediction. European Journal of Neuroscience. 2002;16(8):1609–1619.

41. Teki S, Grube M, Kumar S, Griffiths TD. Distinct neural substrates of duration-based and beat-based auditory timing. Journal of Neuroscience. 2011;31(10):3805–3812.

42. Kameda M, Niikawa K, Uematsu A, Tanaka M. Sensory and motor representations of internalized rhythms in the cerebellum and basal ganglia. Proceedings of the National Academy of Sciences. 2023;120(24):e2221641120.

43. Yamazaki T, Tanaka S. The cerebellum as a liquid state machine. Neural Networks. 2007;20(3):290–297.

44. Rössert C, Dean P, Porrill J. At the edge of chaos: how cerebellar granular layer network dynamics can provide the basis for temporal filters. PLOS Computational Biology. 2015;11(10):e1004515.

45. Tokuda K, Fujiwara N, Sudo A, Katori Y. Chaos may enhance expressivity in cerebellar granular layer. Neural Networks. 2021;136:72–86.

46. Dominey PF. Complex sensory-motor sequence learning based on recurrent state representation and reinforcement learning. Biological Cybernetics. 1995;73(3):265–274.

47. Hinaut X, Dominey PF. Real-time parallel processing of grammatical structure in the fronto-striatal system: A recurrent network simulation study using reservoir computing. PLOS ONE. 2013;8(2):e52946.

48. Kawai Y, Asada M. Spatiotemporal motor learning with reward-modulated Hebbian plasticity in modular reservoir computing. Neurocomputing. 2023;558:126740.

49. Jaeger H. The "echo state" approach to analysing and training recurrent neural networks. GMD-148, German National Research Center for Information Technology. 2001;.

50. Jaeger H, Haas H. Harnessing nonlinearity: predicting chaotic systems and saving energy in wireless communication. Science. 2004;304(5667):78–80.

51. Laje R, Buonomano DV. Robust timing and motor patterns by taming chaos in recurrent neural networks. Nature Neuroscience. 2013;16(7):925–933.

52. Vincent-Lamarre P, Lajoie G, Thivierge JP. Driving reservoir models with oscillations: a solution to the extreme structural sensitivity of chaotic networks. Journal of Computational Neuroscience. 2016;41:305–322.

53. Kawai Y, Park J, Tsuda I, Asada M. Learning long-term motor timing/patterns on an orthogonal basis in random neural networks. Neural Networks. 2023;163:298–311.

54. Kawai Y, Park J, Asada M. Reservoir computing using self-sustained oscillations in a locally connected neural network. Scientific Reports. 2023;13(1):15532.

55. Kawai Y, Morita T, Park J, Asada M. Oscillations enhance time-series prediction in reservoir computing with feedback. arXiv preprint arXiv:240200236. 2024;.

56. Large EW, Jones MR. The dynamics of attending: How people track time-varying events. Psychological Review. 1999;106(1):119–159.

57. Large EW, Almonte FV, Velasco MJ. A canonical model for gradient frequency neural networks. Physica D: Nonlinear Phenomena. 2010;239(12):905–911.

58. Large EW, Herrera JA, Velasco MJ. Neural networks for beat perception in musical rhythm. Frontiers in Systems Neuroscience. 2015;9:00159.

59. Mates J. A model of synchronization of motor acts to a stimulus sequence: II. Stability analysis, error estimation and simulations. Biological Cybernetics. 1994;70(5):475–484.

60. Bose A, Byrne Á, Rinzel J. A neuromechanistic model for rhythmic beat generation. PLoS Computational Biology. 2019;15(5):e1006450.

61. Egger SW, Le NM, Jazayeri M. A neural circuit model for human sensorimotor timing. Nature Communications. 2020;11(1):3933.

62. Zemlianova K, Bose A, Rinzel J. A biophysical counting mechanism for keeping time. Biological Cybernetics. 2022;116:205–218.

63. Large EW, Roman I, Kim JC, Cannon J, Pazdera JK, Trainor LJ, et al. Dynamic models for musical rhythm perception and coordination. Frontiers in Computational Neuroscience. 2023;17:1151895.

64. Briot JP, Pachet F. Deep learning for music generation: challenges and directions. Neural Computing and Applications. 2020;32(4):981–993.

65. Ji S, Yang X, Luo J. A survey on deep learning for symbolic music generation: Representations, algorithms, evaluations, and challenges. ACM Computing Surveys. 2023;56(1):1–39.

66. Hutchings P. Talking Drums: Generating drum grooves with neural networks. In: Proceedings of the First International Workshop on Deep Learning and Music joint with IJCNN; 2017. p. 43–47.

67. Makris D, Kaliakatsos-Papakostas M, Karydis I, Kermanidis KL. Conditional neural sequence learners for generating drums' rhythms. Neural Computing and Applications. 2019;31(6):1793–1804.

68. Kingma DP, Welling M. Auto-encoding variational bayes. In: Proceedings of the International Conference on Learning Representations; 2014.

69. Gillick J, Roberts A, Engel J, Eck D, Bamman D. Learning to groove with inverse sequence transformations. In: Proceedings of the 36th International Conference on Machine Learning; 2019.

70. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention is all you need. Advances in Neural Information Processing Systems. 2017;30.

71. Jin C, Wang T, Liu S, Tie Y, Li J, Li X, et al. A transformer-based model for multi-track music generation. International Journal of Multimedia Data Engineering and Management. 2020;11(3):36–54.

72. Huang YS, Yang YH. Pop music transformer: Beat-based modeling and generation of expressive pop piano compositions. In: Proceedings of the 28th ACM International Conference on Multimedia; 2020. p. 1180–1188.

73. Nuttall T, Haki B, Jorda S. Transformer neural networks for automated rhythm generation. In: Proceedings of the International Conference on New Interfaces for Musical Expression; 2021.

74. Haykin S. Neural Networks and Learning Machines. 3rd ed. Upper Saddle River, NJ, USA: Pearson; 2009.

75. Jeff Porcaro;. `https://en.wikipedia.org/wiki/Jeff_Porcaro`.

76. Fujioka T, Trainor LJ, Large EW, Ross B. Beta and gamma rhythms in human auditory cortex during musical beat processing. Annals of the New York Academy of Sciences. 2009;1169(1):89–92.

77. Fujioka T, Ross B, Trainor LJ. Beta-band oscillations represent auditory beat and its metrical hierarchy in perception and imagery. Journal of Neuroscience. 2015;35(45):15187–15198.

78. Rosen DS, Oh Y, Erickson B, Zhang FZ, Kim YE, Kounios J. Dual-process contributions to creativity in jazz improvisations: An SPM-EEG study. NeuroImage. 2020;213:116632.

79. Rosen D, Oh Y, Chesebrough C, Zhang FZ, Kounios J. Creative flow as optimized processing: Evidence from brain oscillations during jazz improvisations by expert and non-expert musicians. Neuropsychologia. 2024; p. 108824.

80. Sturm I, Blankertz B, Potes C, Schalk G, Curio G. ECoG high gamma activity reveals distinct cortical representations of lyrics passages, harmonic and timbre-related changes in a rock song. Frontiers in Human Neuroscience. 2014;8:798.

81. Ding Y, Zhang Y, Zhou W, Ling Z, Huang J, Hong B, et al. Neural correlates of music listening and recall in the human brain. Journal of Neuroscience. 2019;39(41):8112–8123.

82. Herff SA, Herff C, Milne AJ, Johnson GD, Shih JJ, Krusienski DJ. Prefrontal High Gamma in ECoG tags periodicity of musical rhythms in perception and imagination. eNeuro. 2020;7(4).

83. Madison G, Sioros G. What musicians do to induce the sensation of groove in simple and complex melodies, and how listeners perceive it. Frontiers in Psychology. 2014;5:894.

84. Snyder JS, Large EW. Gamma-band activity reflects the metric structure of rhythmic tone sequences. Cognitive Brain Research. 2005;24(1):117–126.

85. Iversen JR, Repp BH, Patel AD. Top-down control of rhythm perception modulates early auditory responses. Annals of the New York Academy of Sciences. 2009;1169(1):58–73.

86. Nozaradan S, Peretz I, Missal M, Mouraux A. Tagging the neuronal entrainment to beat and meter. Journal of Neuroscience. 2011;31(28):10234–10240.

87. Ericsson KA, Krampe RT, Tesch-Römer C. The role of deliberate practice in the acquisition of expert performance. Psychological review. 1993;100(3):363–406.

88. Anders E K. Deliberate practice and acquisition of expert performance: a general overview. Academic Emergency Eedicine. 2008;15(11):988–994.

89. Brown RM, Zatorre RJ, Penhune VB. Expert music performance: cognitive, neural, and developmental bases. Progress in Brain Research. 2015;217:57–86.

90. Aoki T, Furuya S, Kinoshita H. Finger-tapping ability in male and female pianists and nonmusician controls. Motor Control. 2005;9(1):23–39.

91. Fujii S, Kudo K, Ohtsuki T, Oda S. Tapping performance and underlying wrist muscle activity of non-drummers, drummers, and the world's fastest drummer. Neuroscience Letters. 2009;459(2):69–73.

92. Drake C, Palmer C. Skill acquisition in music performance: relations between planning and temporal control. Cognition. 2000;74(1):1–32.

93. Repp BH. Effects of auditory feedback deprivation on expressive piano performance. Music Perception. 1999;16(4):409–438.

94. Pathak J, Hunt B, Girvan M, Lu Z, Ott E. Model-free prediction of large spatiotemporally chaotic systems from data: A reservoir computing approach. Physical Review Letters. 2018;120(2):024102.

95. Chattopadhyay A, Hassanzadeh P, Subramanian D. Data-driven predictions of a multiscale Lorenz 96 chaotic system using machine-learning methods: Reservoir computing, artificial neural network, and long short-term memory network. Nonlinear Processes in Geophysics. 2020;27(3):373–389.

96. Vlachas PR, Pathak J, Hunt BR, Sapsis TP, Girvan M, Ott E, et al. Backpropagation algorithms and reservoir computing in recurrent neural networks for the forecasting of complex spatiotemporal dynamics. Neural Networks. 2020;126:191–217.

97. Linkenkaer-Hansen K, Nikouline VV, Palva JM, Ilmoniemi RJ. Long-range temporal correlations and scaling behavior in human brain oscillations. Journal of Neuroscience. 2001;21(4):1370–1377.

98. Parish LM, Worrell GA, Cranstoun SD, Stead SM, Pennell P, Litt B. Long-range temporal correlations in epileptogenic and non-epileptogenic human hippocampus. Neuroscience. 2004;125(4):1069–1076.

99. Hennig H, Fleischmann R, Fredebohm A, Hagmayer Y, Nagler J, Witt A, et al. The nature and perception of fluctuations in human musical rhythms. PLOS ONE. 2011;6(10):e26457.

100. Lartillot O, Toiviainen P. A Matlab toolbox for musical feature extraction from audio. In: the 10th International Conference on Digital Audio Effects; 2007. p. 237–244.