1 **FuncFetch: An LLM-assisted workflow enables mining thousands of enzyme-substrate**
2 **interactions from published manuscripts**
3

4 Nathaniel Smith[1], Xinyu Yuan[1], Chesney Melissinos[1], Gaurav Moghe[1]*
5 [1] Plant Biology Section, School of Integrative Plant Science, Cornell University, Ithaca, NY, USA
6 14853
7 * Corresponding author: gdm67@cornell.edu
8
9 ORCIDs:
10 NS: 0009-0004-5672-8081
11 CM: 0009-0005-4443-8797
12 XY: 0009-0006-9199-7652
13 GM: 0000-0002-8761-064X

Abstract

Motivation

Thousands of genomes are publicly available, however, most genes in those genomes have poorly defined functions. This is partly due to a gap between previously published, experimentally-characterized protein activities and activities deposited in databases. This activity deposition is bottlenecked by the time-consuming biocuration process. The emergence of large language models (LLMs) presents an opportunity to speed up text-mining of protein activities for biocuration.

Results

We developed FuncFetch — a workflow that integrates NCBI E-Utilities, OpenAI's GPT-4 and Zotero — to screen thousands of manuscripts and extract enzyme activities. Extensive validation revealed high precision and recall of GPT-4 in determining whether the abstract of a given paper indicates presence of a characterized enzyme activity in that paper. Provided the manuscript, FuncFetch extracted data such as species information, enzyme names, sequence identifiers, substrates and products, which were subjected to extensive quality analyses. Comparison of this workflow against a manually curated dataset of BAHD acyltransferase activities demonstrated a precision/recall of 0.86/0.64 in extracting substrates. We further deployed FuncFetch on nine large plant enzyme families. Screening 27,120 papers, FuncFetch retrieved 32,605 entries from 5547 selected papers. We also identified multiple extraction errors including incorrect associations, non-target enzymes, and hallucinations, which highlight the need for further manual curation. The BAHD activities were verified, resulting in a comprehensive functional fingerprint of this family and revealing that ~70% of the experimentally characterized enzymes are uncurated in the public domain. FuncFetch represents an advance in biocuration and lays the groundwork for predicting functions of uncharacterized enzymes.

Availability and Implementation

Code and minimally-curated activities available at: https://github.com/moghelab/funcfetch and https://tools.moghelab.org/funczymedb

Introduction

Introduction
The last decade has witnessed a rapid rise in the number of high-quality sequenced plant genomes.
However, most genes in these genomes are insufficiently annotated at the functional level. For
example, there are 101 annotated BAHD acyltransferase enzyme-encoding genes in the cultivated
tomato genome, out of which <15 have acceptor substrate classes associated with them (Kruse
et al., 2022). While traditionally performed using sequence similarity searches across species
using software such as PAINT (Gaudet *et al.*, 2011) and TreeGrafter (H. Tang *et al.*, 2019), in recent
years, several methods employing artificial intelligence/machine learning (AI/ML) have also been
developed for predicting gene function attributes such as Gene Ontology (GO) categories, Enzyme
Commission (EC) numbers or enzyme-substrate information (Boadu *et al.*, 2023; Pan *et al.*, 2023;
Kim *et al.*, 2023). These algorithms typically utilize large public protein function databases such as
UniProt, BRENDA and KEGG for their training data. Unfortunately, experimentally verified gene
functions — mostly from a limited number of reference species — have been curated into these
databases. Some model species such as *Escherichia coli* (Karp *et al.*, 2023) , *Saccharomyces*
cerevisiae (Engel *et al.*, 2022) , *Schizosaccaromyces pombe* (Rutherford *et al.*, 2024) , *Drosophila*
melanogaster (Antonazzo *et al.*, 2020) , *Arabidopsis thaliana* (Reiser *et al.*, 2024), *Mus musculus*
and *Homo sapiens* have strong curation communities, leading to prioritized deposition of
experimentally characterized activities from these species into databases (de Crécy-lagard *et al.*,
2022). However, despite a large corpus of experiments in other species, these characterized
functions remain undeposited in function databases.

A major bottleneck for this deposition is biocuration (de Crécy-lagard *et al.*, 2022). For
example, of the >16 million entries in UniProt under Viridiplantae taxonomy class, only ~43,000
have been curated in SwissProt (half of which are from Arabidopsis and rice), and only ~12,000
entries have functions or catalytic activities defined based on literature evidence. This biocuration
process involves — among a multitude of steps (Y. A. Tang *et al.*, 2019) — searching for relevant
papers, reading through them carefully, extracting relevant information into a structured database
format, and validating the extraction. This is an invaluable but labor-intensive process. By one
report, *"there are fewer than 100 full-time equivalents biocurators extracting gene-specific*
functional information from the literature into ~40 public databases
(functional/phenotypes/interactions/pathways) and fewer than 10% of these focusing on bacteria
and plants" (de Crécy-lagard *et al.*, 2022). The small number of biocurators — especially in the
plant domain — has resulted in a significant backlog of published manuscripts whose data is not
available in structured databases.

In this context, large language models (LLMs) such as GPT, Gemini and Claude have
emerged as promising tools for the automatic identification and extraction of scientific information
from literature. General purpose models without domain-specific pretraining have been evaluated
on a variety of tasks. For example, researchers have demonstrated that Claude 2 can extract
structured information for medical evidence synthesis, highlighting its potential in therapeutic

research (Gartlehner *et al.*, 2024). A comprehensive assessment of GPT-3.5 revealed that while it
falls short of state-of-the-art models for tasks such as named entity recognition and sentence
similarity, it still nears human performance on the PubMedQA evaluation (Chen *et al.*, 2023).

Additional work has evaluated the performance of LLMs that are fine-tuned or pretrained
on domain-specific text. One study demonstrated that an older model, GPT-3, could perform
similarly or outperform dedicated models on a variety of evaluations including questions on
molecule properties and chemical reaction yields (Jablonka *et al.*, 2024). Similarly, LLMs enhanced
with explicit chemistry knowledge outperformed others in chemistry-related tasks, including
organic synthesis and the discovery of novel chromophores (Bran *et al.*, 2023). GPT-4 and BERT-
based models have also shown strong performance in establishing protein-protein interactions
despite the lack of domain specific text training for GPT-4 (Rehana *et al.*, 2023). A comparative
study of ML models indicated that a fine-tuned PubMedBERT based model was superior in
identifying gene-disease relationships when compared to rule-based systems and T5-based
models (Milošević and Thielemann, 2023). This growing body of knowledge establishes LLMs as
valid tools for interacting and gleaning valuable data from corpuses of biomedical text.

While ongoing work continues in development of models, evaluation frameworks, and
benchmark performance, there are opportunities to deploy readily-accessible LLMs for useful
information retrieval tasks. One workflow demonstrated success in phylochemical mapping of
specific natural products to plant phylogenies (Busta *et al.*, 2024). The PATHAK method
successfully elucidated gene function relationships in *Arabidopsis thaliana* from ~5000 journal
articles (Kumar and Mukhtar, 2024). These efforts suggest that current generation of LLMs already
have sufficient utility for information retrieval applications. Despite these successes, to our
knowledge, the large corpus of literature on plant enzyme function and enzyme-substrate
relationships going back four decades has still not been parsed. Furthermore, the challenges
associated with the quality of such extractions have not been adequately explored.

In this research, we evaluated the capability of GPT-4 for extracting enzyme-substrate
information and related metadata from published papers. We developed FuncFetch, a multi-step
workflow to generate such an enzyme-substrate dataset. We demonstrated the utility of this
workflow by controlled testing and iterative development and compared its performance relative
to a high-quality, manually curated enzyme-substrate database of a large enzyme family.
FuncFetch is adaptable to other gene families with a few prompt changes. We demonstrate this
extensibility by producing a first-pass curation dataset of >30,000 characterized enzyme-
substrate interactions from nine plant enzyme families, which together constitute ~5% of the
diploid plant genomes. Further manual curation of this dataset can enable better annotation of
thousands of enzyme-encoding genes across the plant kingdom.

117
118

Methods

Dependencies

The multi-step FuncFetch workflow **(Fig. 1A)** was developed using Python v3.10.13 and requires installation of specific additional packages **(Supp. File 1A)**. Additionally, it requires OpenAI and NCBI accounts and Application Programming Interface (API) keys. All configuration files and code can be found on our GitHub page (see Data Accessibility).

FuncFetch overview

This workflow comprises of five steps as follows:

- **Step 1:** With API calls to NCBI E-Utilities (Sayers, 2018), PubMed was queried using a user-supplied list of journals and keywords **(Supp. File 1B-D)**. The keywords must first be decided by the user based on domain-specific knowledge using the PubMed web interface. Given our focus on plants, the journal list included 199 plant, biochemistry and general interest journals. By default, all review articles and all only-review journals were excluded from further consideration but the users have the ability to include these article types. The articles were filtered by a list of 156 keywords related to biochemistry. Given limitations of the NCBI efetch pipeline, if there were >10,000 hits, multiple queries were made with publication-year limits, enabling download of all hits systematically. These settings can be adjusted using a configuration file.

- **Step 2:** Abstracts of articles selected from Step 1 hits (Set 1) were passed on to GPT-4 Turbo (gpt-4-turbo-2024-04-09), which was given the abstract text, title and a family-specific query. The model returned a yes or no response of whether the paper likely described the biochemical activity for the given enzymatic activity. For papers classified as yes, the software output a set of Digital Object Identifiers (DOIs) and other citation information in RIS format (Set 2).

- **Step 3:** This step was performed in a semi-automatic fashion. The RIS file was imported into the open-source program Zotero 6.0.32 or v7 beta, which automatically downloaded PDFs of the manuscripts locally. Manual download was needed for some articles.

- **Step 4:** The PDFs in the Zotero storage folder were passed to GPT-4 directly as well as after text extraction using pdfminer.six v.20231228. Specific prompts **(Supp. File 4)** were sent to GPT-4 using API calls to extract the enzyme-substrate pairs as well as other annotation information such as enzyme common name, species name, GenBank/UniProt ID if any, and product information. The API calls were made with an associated vector store containing a single PDF file for the PDF method. The text method sent extracted text to the model as a string in the API request. Information parsed from both approaches was merged via another GPT-4 API call. This API call was made using a third prompt along with the string outputs of both previous methods. The prompts instruct the model to output data in JSON format, which was then converted to a tab-delimited file. We evaluated both GPT-4 Turbo and GPT-4o models (gpt-4-turbo-2024-04-09 and gpt-4o-2024-05-13, respectively). This step produced a set of extracted enzyme activities (Set 4, uncurated set).

- **Step 5:** Manual verification of Set 4 activities is essential because Set 4 can contain plant enzymes tested in bacteria/yeast via heterologous expression, actual non-plant enzymes that need to be removed, or enzyme activities from a different family. We did not test the ability of GPT-4 to identify these complex scenarios. In this step, for each row of extracted Set 4

activities, if a species name was available, its taxonomic information namely the family and
kingdom were attached using a custom Python script. Using Microsoft Excel and custom
Python scripts, subsequent curation involved selecting enzymes with species information,
removing activities from non-target families, adding UniProt and GenBank IDs based on
extracted ID information, and prioritizing enzymes with available gene IDs for further curation
(Set 5, minimally curated set).

• **Step 6:** This step involved reading each prioritized paper manually and verifying extracted data
in each column, resulting in Set 6, a Verified Set. In this research, Step 6 was performed only
for BAHD acyltransferase enzymes.

Validation of Step 2
A test dataset of 347 abstracts was manually constructed to equally represent papers with
reported enzyme activities (positives) and no reported enzyme activities (negatives) **(Supp. File**
2A,B). Positives were sourced from UniProt citations for catalytic activity annotations, with
additional papers identified through manual searches to ensure equal representation across five
enzyme families. We included these enzyme families — BAHD acyltransferases, cytochrome
P450s, O-methyltransferases, UDP-glycosyltransferases, peroxidases — to reduce bias and
overfitting of prompts to any one family or activity. The abstract and title of each paper were
assessed by an API call to GPT-4 along with a predetermined prompt embedded with the enzyme
family name **(Supp. File 2B)**. The model parameters were: *seed = 1, logit_bias = {'15':100,*
'16':100}, max_tokens = 1. The seed was set to increase reproducibility of model outputs during
validation. The logit_bias and max_tokens parameters limit the model's output options to a single
token response of "1" or "0", corresponding to yes or no respectively. Model temperatures were
tested at 0.1, 0.2, and 0.5 based on OpenAI's recommendation for tasks that require consistent
outputs (OpenAI Docs, 2024). Based on the output of the model, each paper was established as
true positive, false positive, true negative, or false negative enabling calculation of precision, recall,
and F1 scores for each prompt across the entire dataset. Thirteen unique prompts were developed
throughout testing **(Supp. File 2B)**. This began with an initial prompt developed by interacting with
ChatGPT and asking it to extract biochemical information from pdfs of journal articles. Prompts
were developed by reading through the output of previous prompts and making hypotheses about
the most relevant language in the prompt that influenced the false positives/negatives. The system
content of the chat completion model was also iterated upon, but seemed to make little difference
in performance, so evaluation of this parameter was stopped. Whenever a new prompt resulted in
a better F1 or Recall score than a previous attempt, that prompt would then be iterated upon via
the same process.

Validation of Step 4
A test set of 10 papers was established to evaluate the output and performance of FuncFetch Step
4 **(Supp. File 3A, Supp. File 4)**. This test set was made up of 5 papers each from two enzyme
families in the positive paper set detailed in the previous section (BAHD acyltransferases [BAHDs]
and UDP glycosyltransferases [UGTs]), containing 71 and 38 BAHD and UGT activities from 16 and
18 enzymes, respectively. These ten papers were selected to represent the diversity of BAHD
activities and contexts in which they were reported (e.g. single enzyme discoveries, complete

biosynthetic pathway studies, heterologous expression). The UGT papers were used as the negative test with the query set as "BAHD acyltransferase" in the Step 4 configuration. This ensured that there were enzyme activities present in the paper that could be extracted successfully, but that would not be of the correct enzyme family. We included this set of papers as the negative test set to evaluate the model's ability to discriminate enzyme families and exclude irrelevant activities. Step 4 was run on these 10 papers and the outputs of text, pdf, and merge extraction techniques were graded for precision and recall.

All extraction methods output multiple activities in the same line of tabular output, but especially the merge method. Given this model behavior, evaluating each line of output underestimates the number of correct activity relationships. Therefore, we developed a manual procedure that splits a line of output into multiple entries. A grading procedure was developed to score entries of Step 4 output as correct, unknown correct, incorrect, or incomplete **(Supp. File 5B,C)**. These procedures also detail enzyme, substrate, and product naming standards. Graded entry counts were used to calculate evaluation metrics.

Assessment of workflow using curated BAHD acyltransferase database

After validation of the entire pipeline, FuncFetch was used to extract information about the BAHD family, resulting in Set 4 enzyme-substrate association entries. The tabular output of Step 4 was evaluated against a high-quality dataset (HQD) of BAHD activities **(Supp. File. 5D)** from 129 papers updated from our previously published study (Kruse *et al.*, 2022). Every entry in this dataset was manually reviewed at least twice. This HQD represents the best comparison to the performance of FuncFetch Step 4 because there are no comparable datasets available and because FuncFetch aims to complement family-wide manual curation efforts. For each paper appearing in the evaluation set and the HQD, the Step 4 output was manually graded and compared to the HQD according to the same grading procedure described in the previous section.

Semi-automatic curation to generate the minimally curated set

Set 4 entries were processed in a multi-step fashion. First, we flagged and manually reviewed a small subset of entries in the tabular output for which the activity extractions came only from the PDF method or text method or none. Second, we identified records of plant proteins either directly ascribed to plants or tested in bacterial or fungal systems. This was accomplished by tagging each row of the Set 4 result with the Family and Kingdom name using NCBI Taxonomy hierarchy. Third, we identified records of the targeted enzyme family using the extracted enzyme names, abbreviations and if needed, reading the papers. Non-specific extractions (e.g. cytochrome P450s or hydroxylases or acyltransferases when the target family was methyltransferases) were removed. Fourth, we used sequence IDs and enzyme names to match entries with UniProt accessions. Finally, entries with sequence ID information available were prioritized, given the ability to identify their enzyme families with certainty using protein sequence information. These entries with sequence ID information constituted the Minimally Curated Set (Set 5). Only BAHD acyltransferases were processed to Verified Set (Set 6), which involved a detailed reading of the associated literature and adding/deleting activities as needed **(Supp. File 6)**. We note that there are substantial similarities in activities extracted for the CYP450 and dioxygenase/oxygenase queries, given significant overlap and promiscuity in functions of these families.

Development of a web resource and data availability

All scripts used in this work are available on GitHub (https://github.com/moghelab/funcfetch) along with the demo files, while relevant output files were deposited on GitHub and the project website (https://tools.moghelab.org/funczymedb/). For developing the website, rapid prototyping of page layouts and functionality was initially performed in Webflow (2024) before development was moved and completed in VSCode v1.87. Node.js v20.12.0 was used to generate and launch the pages as a web app. This Node.js app is dependent only on the Express module v4.18.3. The website was run in a Docker v20.10.17 container built from a Node.js base image: *node:16.17.0-bullseye-slim*. The base image acts as the parent of the image, and has heritable capabilities.

Results and Discussion

FuncFetch enables first-pass extraction of enzyme-substrate interactions from manuscripts

FuncFetch Step 1 queries the NCBI PubMed database using the user-provided search term and identifies manuscripts containing or associated with the query as keywords or MeSH terms. Preliminary assessments revealed that many of these hits are not relevant e.g. a query for BAHD acyltransferase also retrieved articles on Bone-Anchored Hearing Devices, or on topics related to plant development. Hence, we instituted filters based on journals and keywords **(Supp. File 1B,C)**. Considering hundreds of irrelevant manuscripts and manuscripts with only mention of the enzyme but no detailed *in vitro* investigation still passed these filters, we explored whether GPT-4 can predict whether a given paper might describe an enzyme assay for the family of interest, based on the title and abstract text. We manually generated a corpus of 347 manuscripts belonging to five enzyme families to test GPT-4's performance.

Our first prompt **(Q1; Fig. 1B)** resulted in recall, precision, and F1 scores of 0.88, 0.95 and 0.91, respectively, at temperature 0.5 **(Fig. 1C)**, indicating an acceptable level of performance. To optimize it further, we sequentially iterated through 11 questions and 2 system inputs in 13 combinations **(Fig. 1B; Supp. File 2B,C)** revealing an expected tradeoff between precision and recall. We selected Q11 as it had the highest recall (0.94), enabling us to cast a wide net for the next step. We also saw that introducing "likely" (Q1 to Q2) and "describes" rather than "directly tests" (Q9 to Q11) resulted in increased papers classified as relevant, from 156 to 170 and 154 to 190 respectively. The density of "yes" responses increased for prompts with more inclusive language **(Fig. 1D)**, highlighting the relationship between the model's confidence in assertions and the specificity or flexibility of prompt language.

Having demonstrated the validity of the Abstract Filter, the next step required parsing the entire manuscript. We assessed that the best solution to accessing the PDFs is to export a citation exchange RIS file and download papers automatically using the Zotero reference manager. This step was successful for a majority of the cases — using Zotero v6, 74.8% of BAHD papers could be automatically downloaded. Remaining papers were downloaded mostly one-by-one and attached to Zotero records manually.

Initially we tested two approaches for accurate retrieval of enzyme activities from downloaded manuscripts **(Supp. File 4)**: 1) directly feeding in a PDF to GPT-4 (Approach 1), and 2) embedding PDF data in a text format, followed by feeding the text to GPT-4 (Approach 2). Comparative testing of these two approaches revealed that Approach 1 had better recall than

291 Approach 2, with precision being better for the latter **(Supp. File 3B)**. Combining the outputs of
292 both approaches again using an LLM instruction (Approach 3; "merge method") resulted in
293 improved performance **(Supp. File 3B; Supp. File 4).**
294
Performance of the FuncFetch pipeline on the BAHD acyltransferase dataset
We next implemented the entire pipeline on the BAHD acyltransferase enzyme family
dataset. We previously compiled a dataset of 567 activities of 164 BAHDs from 75 species (Kruse
et al., 2022), which we updated in this study. The final HQD comprised 1114 activities of 209
BAHDs from 87 species **(Supp. File 5D)**. We estimated precision and recall of the FuncFetch
pipeline by comparing its output with the HQD. The total PubMed articles returned by Step 1 were
1038 with elink and 461 without elink **(Fig. 2D).** Of the 129 papers in the HQD, 113 (87.6%) and 78
(60.5%) were retrieved, with and without elink respectively. Of these, Step 2 classified 101 and 76
as relevant (Recall: 0.89 and 0.97). Seventy additional papers with 137 novel characterized
BAHDs were found by this workflow and missed by our manual search.
From the 76 papers passed on to Step 4, we estimated reaction-level and substrate-level
performance metrics using the HQD as the comparison. The precision/recall was 0.81/0.49 and
0.87/0.65 respectively **(Fig. 2B)**, indicating that while GPT-4 was correctly able to extract the
substrates most of the time, it faced challenges linking the substrates and/or substrate-product
pairs together. We also found that the performance of both reaction and substrate-level extraction
increased with a model update from GPT-4T to 4o **(Fig. 2B)**.
The most common cause of an incorrect entry in the output were cases of incorrect enzyme
families. Of 65 false positive entries, 20 (30.8%) were BAHD family enzymes with incorrect
activities not supported by the text. The other 45 (69.2%) incorrect entries were enzymes of non-
target families. These other families included acetyltransferases, decarboxylases, carboxylases,
UDP-glycosyltransferases, O-methyltransferases, ligases, and various synthases. Papers
resulting in these entries discuss entire biosynthetic pathways or otherwise report on a variety of
enzymes and reactions. Despite some confusion on enzyme families, the model displayed an
ability to understand domain-specific nomenclature. For example, the model parsed and
associated CoA thioester naming conventions (e.g. aiC4, iC5, aiC5) with products and other
substrates effectively **(Supp. File 5J)**.
In our evaluation, 191 (24.0%) of the 795 entries were marked as incomplete. These
generally tended to be incomplete donor substrates rather than acceptors. Of 96 incomplete
entries with one substrate, 74 (77.1%) were missing a donor and 22 (22.9%) were missing an
acceptor. These omitted data may result from additional attention paid to acceptors due to similar
naming of acceptors and products, and the separation of donor information in the text from
discussion of acceptor substrates and products.
Of the relevant entries, ~58% of entries with extracted IDs/names could be associated with
at least one UniProt entry. These entries can be considered priority entries for more detailed
verification **(Table 1).** We sampled 10 papers with verified activities that were missing sequence
IDs to understand why these IDs were omitted. In four papers, enzymes lacked IDs, though
sequences were available in supplementary files or external references. Three papers described
enzymes not mapped to genes, so no sequence information was available. In the final three, IDs

were present but missed during retrieval. These findings highlight areas where our ID retrieval could
be improved, though some IDs may remain unavailable with our current method.

Out of 795 Step 4 output entries, we found 237 correct entries that were not found in the
manual curation process **(Supp. File 5J)**. These 237 entries could be associated with 29 UniProt
accessions. These data include activities inferred from enzyme names, references to previous
assays performed in the references section of the manuscript, and activities assayed but entirely
missed by the manual review process. When we evaluated Step 4 output including these entries,
precision/recall increased at the reaction-level and substrate-level, to 0.87/0.60 and 0.90/0.73,
respectively **(Fig. 2A,B; Supp. File 5A).** This finding highlights the value of a complementary LLM
screening of manuscripts along with manual curation, as a human reviewer may overlook
information the model detects.

We also evaluated the proportion of our retrieved entries that are already present and
curated in UniProt i.e. in the SwissProt and RHEA databases. This provided a sense of the "curation
gap" that is addressable by FuncFetch. From the 841 verified BAHD entries with extracted UniProt
IDs, we found 187 unique IDs **(Table 1)**. Of these unique IDs, 49 (26.2%) were reviewed (Swiss-
Prot) and 44 (23.5%) had catalytic activity (RHEA) annotations **(Supp. File 6A,B)**. We also missed
20 BAHDs already catalogued in SwissProt and RHEA **(Supp. File 6B-D)**. Considering these
numbers, we estimate that at least 69.1% of the Verified Set lacks catalytic activity
annotations. This represents the current estimated curation gap for this enzyme family, which is
likely an underestimate given 588 extracted entries could not be automatically assigned a UniProt
ID and were not included in this calculation. This analysis demonstrated that our workflow is
capable of finding enzyme activities that are already well-represented in public databases.
However, most entries retrieved by this workflow remain uncurated in the public domain, validating
the utility of our approach.

First-pass automatic curation of thousands of manuscripts for eight plant enzyme families

To extend our analysis further and generate a valuable resource for the plant biochemistry
community, we used FuncFetch to identify relevant papers for eight additional enzyme
families/activities that constitute ~4-5% of the gene content in diploid plant genomes **(Fig. 2C-E)**.
This process was an order of magnitude faster than manual review **(Fig. 2C; Supp. File 7)**. At a cost
of ~$65, we screened >27,000 paper abstracts and identified a conservative set of 5547
manuscripts that may contain enzyme-substrate information **(Fig. 2D)**. Performance of Steps 3-5
produced a Minimally Curated Set for each family **(Fig. 2E)**. Overall, across all 9 enzyme family
activities, 32,605 entries were extracted and minimally curated from 5547 papers, which will need
to be verified further. Detailed Step 6 curation was performed only for BAHD acyltransferases
(Supp. File 6).

Curation performed in Step 5 to produce this Minimally Curated Set revealed several issues
with LLM-extracted data that needed to be carefully assessed manually. First, we found that 10-
30% entries for each family included non-target enzymes from other families or non-plant
enzymes. Without manual curation, it is not straightforward to identify plant enzymes, since some
papers may contain plant enzymes heterologously expressed in bacteria or yeast. In several cases,
the model listed the host species name (e.g. *Escherichia coli, Saccharomyces cerevisiae*) rather
than the name of the original plant species. Second, if multiple enzymes are characterized in the

same study, multiple enzyme entries could be extracted, and need to be filtered out. Third, we
observed a consistent gap in retrieved enzyme sequence information across all families **(Table 1)**.
On average, ~42% of entries have no associated sequence identifier after we map them to UniProt
accessions based on enzyme names. This presents a roadblock to eventual manual curation.
In addition to extraction issues, we detected several instances of hallucinations **(Supp. File**
8). For plant papers and enzymes, the model listed human, mouse or rat as species and listed their
enzymes and substrates despite these species never being mentioned in the paper. While there
were 0-1% hallucinations detected for plant-enriched families such as BAHDs, PKSs, GDSLs and
UDPGTs, the proportion was between 3-7% for ubiquitously present families such as peroxidases,
CYP450s and (di)oxygenases. The actual number of hallucinations of this type could be higher but
is irrelevant given they would be filtered out using the taxonomic filter. The tabular organization of
the data in the Step 4 output and association of paper titles with species and kingdom names in
Step 5 allows for efficient detection and removal of many such hallucinations. Nonetheless,
detailed curation needs to be performed for all entries before their release on protein function
databases. Minimally Curated Sets for all enzyme families can be accessed and downloaded from
the project website and GitHub.
392
393 **Table 1: Extracted entries that could be mapped to one or more UniProt IDs**

Enzyme family name	Total extracted entries	Number of entries with ID hits	% with ID hits	Number of entries without ID hits
GDSL lipase	166	97	58.4	69
UDPGT	3630	2089	57.5	1541
BAHD acyltransferase	1429	841	58.6	588
Peroxidase	5502	2820	51.3	2682
OMT	2938	1401	47.7	1537
CYP450	5680	3558	62.6	2122
Aminotransferase	1419	740	52.1	679
Dioxygenase	10957	6668	60.9	4289
PKS	884	624	70.6	260
TOTAL	32605	18838	57.8	13767

394
395
Conclusions
Since the introduction of transformers in 2017 (Vaswani *et al.*, 2017, 2023), the field of
LLMs has grown by leaps and bounds as witnessed by the numerous commercial LLMs existing
today including GPT, Llama, Mistral, Gemini, and Claude. Biological research has made significant
use of these LLMs just in the last two years in fields as diverse as predictions of protein-protein
interactions (Jin *et al.*, 2024), single-cell multiomics clusters (Cui *et al.*, 2024), summarizing
literature for non-coding RNAs (Green *et al.*, 2024), predicting disease specific knowledge graphs
(Li *et al.*, 2024), and in eco-evolutionary research (Gougherty and Clipp, 2024). Here, we explore
the use of the GPT-4 LLMs in extracting enzyme-substrate interactions and related metadata,
highlight the limitations of this application, and generate a resource of such interactions for

community annotation and use. Such an application has been explored recently e.g. with ChatGPT
and Bard/Gemini in a microbiological context (Caspi and Karp, 2024) and for general entity-relation
pairing in PubTator3 (Wei *et al.*, 2024). Kumar and Mukhtar developed a method named PATHAK
for associating genes with biological process GO terms (Kumar and Mukhtar, 2024). However, this
is a dynamic field and a state-of-the-art application, as highlighted by the fact that many of the
cited approaches were still preprints at the time of this writing. To our knowledge, at the time of
writing, no existing workflow exists for extracting plant enzyme activities from biochemistry
literature. In addition to describing a workflow, this work also makes a list of hundreds of relevant
papers and thousands of partly curated activities available to the scientific community for
community curation/analyses. Given over two-thirds of the experimentally characterized enzymes
are still uncurated in the public domain, development of workflows such as FuncFetch is a need of
the hour.
The FuncFetch workflow integrates three platforms — NCBI E-Utilities, OpenAI GPT-4 and
Zotero — enabling screening of thousands of published papers and extraction of information from
a select few. This workflow can be flexibly configured as needed for other purposes. We expect
that the overall sequence of steps will remain constant, although the questions as well as the
precision/recall for different tasks may change based on task complexity. For example, identifying
chemical and enzyme names — both of which have a unique, defined vocabulary — may be a
simpler task for an LLM than extracting mutant phenotype data, which could range from change in
cellular morphology or membrane fluidity to change in growth rate or interaction with
pests/pathogens. Therefore, query engineering may need to be conducted for every untested
application of FuncFetch. Over the course of this research, we also found that Step 4 performance
and especially cost-effectiveness significantly improved with GPT-4 model updates **(Fig. 2B)**. We
note that FuncFetch is flexible enough to accommodate future model upgrades. Assuming that
models will keep improving over time, the cost-effectiveness and performance of the FuncFetch
pipeline can be expected to improve.
The advantage of the stepwise approach is evident. It took ~14 minutes to download
>27,000 paper metadata from PubMed, ~$65 to screen these abstracts overnight using GPT-4
batch submission and ~$1400 to extract ~40,000 entries. The initial screening step significantly
reduced the cost of data extraction from PDFs, and the pre-selection of papers mitigates the
chances of citation hallucinations. One major bottleneck in our pipeline is downloading PDFs of
screened papers using Zotero (Step 3). This is not the best option; however, it is the most optimal
option that circumvents manually downloading thousands of papers while still retaining
comprehensiveness. We expect that individual institutions' access to publisher libraries may
affect the outcome of this step. For Step 4, we compared the cost of manual curation vs. GPT-4
extraction from papers. The differences in cost and time savings were drastic **(Fig. 2C; Supp. File
7).** We believe these are gross underestimates since the effect of human attention span and
engagement over long periods of time are not accounted for here. Nonetheless, given the quality
issues of GPT-4 extraction highlighted above, manual validation of extracted activities is still
necessary.
We decided to use the GPT-4 LLM for this analysis given its widespread use, however, other
LLMs listed above may offer better performance. In validating Step 4 methods we found some
output variation between identical API calls, despite the inclusion of a seed parameter. These

variations generally consisted of recombination of substrates, products, and enzymes across
different entries. It may be worthwhile to explore these variations and leverage model information
on probable alternative token responses to extend the breadth of extracted information.
Furthermore, we observed that GPT-4o performed better than GPT-4T **(Fig. 2B).** The choice of the
LLM model and parameter changes may therefore significantly affect curation results. Recently,
EnzChemRED emerged as a chemistry relation extraction dataset comprised of curated PubMed
abstracts. Finetuning on such a dataset appears to improve model performance on relation
extraction metrics (Lai *et al.*, 2024). Taken as a whole, optimization of finetuning, model choice,
and parameters will likely improve performance on similar information retrieval tasks.

Despite our initial concern, we found zero instances of hallucinations (Jin *et al.*, 2023) in
our full curation of BAHD activities, which we define here as making up substrates and products
that are not mentioned in the paper. While the LLM made incorrect associations between
substrates and enzymes, either from the main text or the references, completely un-mentioned
substrates were not observed in Set 5 entries for BAHDs and PKSs. Nonetheless, for more
ubiquitous families, dozens to hundreds of instances were detected. Hallucinations are known to
occur when using LLMs, especially public-facing versions such as ChatGPT and Bard (Caspi and
Karp, 2024). Our results suggest that in some cases, the model outputs information from the
training vector space **(Supp. File 8)**. Such hallucinations tended to be highly repetitive and near
identical, listed biomedical species instead of plant, bacteria or yeast, or had human enzyme
names when the paper title clearly indicated investigation of a plant enzyme. This finding also
raises a potential concern for chemistry or protein-function specific LLMs built on foundation
models — the taxonomic breadth of the training data used may significantly affect their
performance.

In FuncFetch, we employed several measures that potentially mitigate hallucinations.
Firstly, our questions were highly specific in the enzymatic function as well as the taxonomic
space. We also focused on single enzyme families, significantly constrained the outputs to 1/0
(Step 2) or a controlled JSON vocabulary (Step 4), and set low temperatures for retrieval (0.5
instead of default 1 on ChatGPT) thereby reducing model "creativity". For each query in Step 4, we
also initiated a new API call removing all memory of previous uploaded papers/text. Third, we
employed extensive semi-automatic curation steps (Step 5) that lead to detection of obvious
instances of such hallucinations. Finally, we matched the extracted species name with the species
name of the sequence identifier obtained via NCBI Taxonomy, enabling us to select higher-
confidence entries rapidly (Step 5). Nonetheless, it is possible that full curation of the Set 5
activities of the non-BAHD enzyme families may reveal additional instances of hallucinations.
Future development of the FuncFetch workflow may require integration of techniques such as
Retrieval Augmented Generation (RAG) (Béchard and Ayala, 2024; Wei *et al.*, 2024), Knowledge
Retrieval (Varshney *et al.*, 2023) or LLM-finetuning for genomics-focused tasks. Mitigating
hallucinations in a high-throughput manner is a dynamically evolving field at the time of this writing
(Tonmoy *et al.*, 2024).

ML has been used for predicting genes and gene functions for over two decades (Mahood
et al., 2020). Over the last few years, however, the advent of AlphaFold and AI innovations have
significantly revolutionized this field. For example, Google's ProtNLM recently provided functional
descriptors for 50 million uncharacterized proteins in the UniProt database (Hatch, 2022). ESP —

a generalized machine learning model — was found to predict enzyme-substrate pairs with >91%
accuracy for the tested datasets (Kroll *et al.*, 2023). In-house transformers have also been used to
predict enzyme-substrate promiscuity — AlphaFold's EvoFormer model was used to predict the
strength of protein-ligand interactions, with additions from orthogonal cheminformatic techniques
(Xing *et al.*, 2024). While these innovations are useful in covering the vast, unannotated protein
space, our previous research on BAHDs demonstrates that simply cataloguing activities of
published, well-characterized BAHDs increased the proportion of uncharacterized enzymes
annotated with their putative substrate classes from ~10% to 40-45% (Kruse *et al.*, 2022).
Furthermore, such a catalog allows more rational selection of substrates for downstream
validation experiments as well as improves the training data for generation of more unbiased
models. The FuncFetch workflow and database are steps in that direction.
503
Acknowledgements

505 We thank Drs. Qi Sun and Jaroslaw Pillardy at the Cornell BioHPC core and Vishwa Jyoti Baruah for
506 their assistance in implementing the pipeline and the website Docker container. We thank Venus
507 Kajangu for assisting with verifying GenBank sequence IDs in Set 6 for BAHDs. We also thank the
508 reviewers for helpful comments that helped improve this manuscript.

509
Author Contributions
511 This research was conceived by NS and GM. NS, CM and GM wrote code and performed all
512 bioinformatic analyses. NS, XY and GM validated results and performed curation. NS and GM
513 wrote the manuscript. All authors reviewed the manuscript.
514
Supplementary Data
Supplementary File 1: Description of packages and filters used for FuncFetch workflow. (1A)
Version information for all software used to develop and test FuncFetch pipeline. (1B) PubMed
indexed journals included by FuncFetch when running Step 1 with Journal Filter. (1C) PubMed
indexed keywords included by FuncFetch when running Step 1 with keyword filter. Keywords
marked with "fil" in the second column were not used for most families but are kept in the list in
case needed. (1D) Queries used for PubMed searches.
Supplementary File 2: Details of Step 2 testing & results. (2A) PubMed IDs and titles of 347 papers
included in evaluation of Step 2, and whether in positive or negative test group. (2B) Text of all
prompts and system input evaluated for Step 2. (2C) Metrics of every prompt and system tested
across temperatures (Descending F1 score order).
Supplementary File 3: Details of Step 4 validation. (3A) List of 10 papers included in Step 4
method validation. Papers in the positive set have BAHD acyltransferase activities. Papers in the
negative set have UDP-glycosyltransferase activities, but the model was asked to extract BAHD
acyltransferase activities. (3B) Metrics for each tested method using the 4T or 4o models.
Supplementary File 4: Details of Step 4 prompts and code examples.
Supplementary File 5: Details of Step 4 Evaluation. (5A) Analysis and results of Step 4 of
FuncFetch workflow. Counts of unknown correct (dark blue), known correct (green), incorrect
(red), and incomplete (yellow) entries for each evaluation method. Additionally, counts for entries
that differ in grading between evaluation methods denoted in a separate section as dark blue, light

blue, and orange. Recall and precision scores for each evaluation method, and formulas used to calculate each. (5B) Protocols for grading Step 4 output entries. This includes definitions and examples of what constitutes correct and incorrect entries and substrates/products. (5C) Protocol for splitting Step 4 output entries. This process splits an entry with multiple combinations of substrates (activities) to align Step 4 output with the structure of the high-quality dataset [HQD]. (5D) HQD of BAHD acyltransferase activities. (5E) Tabular output file of Step 4 (merge method) run with model gpt-4-turbo-2024-04-09 (4T). (5F) Tabular output file of Step 4 (merge method) run with model gpt-4o-2024-05-13 (4o). (5G) HQD entries from papers that appear in output of 4T Step 4. (5H) HQD entries from papers that appear in output of 4o Step 4. (5I) 4T Step 4 output entries from papers that appear in the HQD. (5J) 4o Step 4 output entries from papers that appear in the HQD. (5K) 4T Step 4 output substrate grading. (5L) 4o Step 4 output substrate grading.

Supplementary File 6: Verified Set of BAHD acyltransferase activities. (A) The Manual Check column differentiates entries where the species of the FuncFetch extracted ID is the same as the one extracted through NCBI Taxonomy using the enzyme names by our inhouse Python script. If the tag is "Same Species", the UniProtID column names apply. If the tag is "Different_species" or "Multiple_species", then none of the NCBI Taxonomy IDs extracted are correct, and we consider them incorrect mappings to be dealt with manually. If the tag is "No_ID", then No ID could be extracted. In total, out of the 1429 entries, IDs of 841 entries could be extracted, only 53 of which are incorrectly mapped after Manual_Check. (B) Analysis of IDs for determining Curation gap. (C) All SwissProt BAHDs (D) Overlaps between different sets.

Supplementary File 7: Time comparison of human readers and Step 4. (7A) Time totals, analysis, and methods. Human readers recorded the time it took them to read and extract enzyme-substrate interactions. The final product of this extraction is presented in 6B-D. The same 10 papers were run through Step 4 of the FuncFetch timeline. Code modifications were made to provide timestamps for the beginning and end of processing for each paper. The resulting time intervals were then compared to the human readers. (7B) Reader-1 extracted information. (7C) Reader-2 extracted information. (7D) Reader-3 extracted information. (7B) FuncFetch Step 4 extracted information.

Supplementary File 8: Analysis of hallucinations. (8A) First example of messages presenting information from model weights. The pdf method describes searching the document for mentions of the target enzyme families, but only returns entries with the target names and no additional information. In this case, the text method returns a set of correct enzyme activities, but with no relation to information in the text. The information presented is similar to the output when the same model is asked about the enzyme family in question with no added context (see 8C). (8B) Second example of messages presenting information from model weights. In this case, both pdf and text methods present similar information to the output when the same model is asked about the enzyme family in question with no added context (see 8C). (8C) Screenshot of ChatGPT response with GPT-4o model when prompted to describe UDP-glycosyltransferases and their substrates.

Conflict of Interest

No competing interests exist.

Funding

This research was funded by NSF-IOS-Plant Genome Research Program award #2310395 to GM.

References

Antonazzo,G. *et al.* (2020) Building a pipeline to solicit expert knowledge from the community to aid gene summary curation. *Database*, **2020**, baz152.

Béchard,P. and Ayala,O.M. (2024) Reducing hallucination in structured outputs via Retrieval-Augmented Generation.

Boadu,F. *et al.* (2023) Combining protein sequences and structures with transformers and equivariant graph neural networks to predict protein function. *Bioinformatics*, **39**, i318–i325.

Bran,A.M. *et al.* (2023) ChemCrow: Augmenting large-language models with chemistry tools.

Busta,L. *et al.* (2024) Mapping of specialized metabolite terms onto a plant phylogeny using text mining and large language models. *Plant J.*, **n/a**.

Caspi,R. and Karp,P.D. (2024) An Evaluation of ChatGPT and Bard (Gemini) in the Context of Biological Knowledge Retrieval. *Access Microbiol.*

Chen,Q. *et al.* (2023) An extensive benchmark study on biomedical text generation and mining with ChatGPT. *Bioinformatics*, **39**, btad557.

de Crécy-lagard,V. *et al.* (2022) A roadmap for the functional annotation of protein families: a community perspective. *Database*, **2022**, baac062.

Cui,H. *et al.* (2024) scGPT: toward building a foundation model for single-cell multi-omics using generative AI. *Nat. Methods*, 1–11.

Engel,S.R. *et al.* (2022) New data and collaborations at the Saccharomyces Genome Database: updated reference genome, alleles, and the Alliance of Genome Resources. *Genetics*, **220**, iyab224.

Gartlehner,G. *et al.* (2024) Data extraction for evidence synthesis using a large language model: A proof-of-concept study. *Res. Synth. Methods*, **15**, 576–589.

Gaudet,P. *et al.* (2011) Phylogenetic-based propagation of functional annotations within the Gene Ontology consortium. *Brief. Bioinform.*, **12**, 449–462.

Gougherty,A.V. and Clipp,H.L. (2024) Testing the reliability of an AI-based large language model to extract ecological information from the scientific literature. *Npj Biodivers.*, **3**, 1–5.

Green,A. *et al.* (2024) LitSumm: Large language models for literature summarisation of non-coding RNAs.

Hatch,V. (2022) Natural language processing for rapid protein annotation.

Jablonka,K.M. *et al.* (2024) Leveraging large language models for predictive chemistry. *Nat. Mach. Intell.*, **6**, 161–169.

Jin,M. *et al.* (2024) ProLLM: Protein Chain-of-Thoughts Enhanced LLM for Protein-Protein Interaction Prediction. 2024.04.18.590025.

Jin,Q. *et al.* (2023) Retrieve, Summarize, and Verify: How Will ChatGPT Affect Information Seeking from the Medical Literature? *J. Am. Soc. Nephrol.*, **34**, 1302.

Karp,P.D. *et al.* (2023) The EcoCyc Database (2023). *EcoSal Plus*, **11**, eesp-0002-2023.

Kim,G.B. *et al.* (2023) Functional annotation of enzyme-encoding genes using deep learning with transformer layers. *Nat. Commun.*, **14**, 7370.

Kroll,A. *et al.* (2023) A general model to predict small molecule substrates of enzymes based on machine and deep learning. *Nat. Commun.*, **14**, 2787.

Kruse,L.H. *et al.* (2022) Orthology-based analysis helps map evolutionary diversification and predict substrate class use of BAHD acyltransferases. *Plant J.*

Kumar,N. and Mukhtar,M.S. (2024) PATHAK: An NLP-Based Method to Mine Gene and Function Relationships from Published Articles.

Lai,P.-T. *et al.* (2024) EnzChemRED, a rich enzyme chemistry relation extraction dataset. *Sci. Data*, **11**, 982.

Li,D. *et al.* (2024) DALK: Dynamic Co-Augmentation of LLMs and KG to answer Alzheimer's Disease Questions with Scientific Literature.

630 Mahood,E.H. *et al.* (2020) Machine learning: A powerful tool for gene function prediction in plants.
631    *Appl. Plant Sci.*, **8**, e11376.
632 Milošević,N. and Thielemann,W. (2023) Comparison of biomedical relationship extraction
633    methods and models for knowledge graph creation. *J. Web Semant.*, **75**, 100756.
634 OpenAI Docs (2024) OpenAI Platform: How should I set the temperature parameter?
635 Pan,T. *et al.* (2023) PFresGO: an attention mechanism-based deep-learning approach for protein
636    annotation by integrating gene ontology inter-relationships. *Bioinformatics*, **39**, btad094.
637 Rehana,H. *et al.* (2023) Evaluation of GPT and BERT-based models on identifying protein-protein
638    interactions in biomedical text.
639 Reiser,L. *et al.* (2024) The Arabidopsis Information Resource in 2024. *Genetics*, **227**, iyae027.
640 Rutherford,K.M. *et al.* (2024) PomBase: a Global Core Biodata Resource—growth, collaboration,
641    and sustainability. *Genetics*, **227**, iyae007.
642 Sayers,E. (2018) E-utilities Quick Start. In, *Entrez Programming Utilities Help [Internet]*. National
643    Center for Biotechnology Information (US).
644 Tang,H. *et al.* (2019) TreeGrafter: phylogenetic tree-based annotation of proteins with Gene
645    Ontology terms and other annotations. *Bioinformatics*, **35**, 518–520.
646 Tang,Y.A. *et al.* (2019) Ten quick tips for biocuration. *PLoS Comput. Biol.*, **15**, e1006906.
647 Tonmoy,S.M.T.I. *et al.* (2024) A Comprehensive Survey of Hallucination Mitigation Techniques in
648    Large Language Models.
649 Varshney,N. *et al.* (2023) A Stitch in Time Saves Nine: Detecting and Mitigating Hallucinations of
650    LLMs by Validating Low-Confidence Generation.
651 Vaswani,A. *et al.* (2017) Attention Is All You Need.
652 Vaswani,A. *et al.* (2023) Attention Is All You Need.
653 Wei,C.-H. *et al.* (2024) PubTator 3.0: an AI-powered literature resource for unlocking biomedical
654    knowledge. *Nucleic Acids Res.*, gkae235.
655 Xing,H. *et al.* (2024) High-throughput prediction of enzyme promiscuity based on substrate–
656    product pairs. *Brief. Bioinform.*, **25**, bbae089.
657

Figure 1

Figure 1: Overview of pipeline and performance assessment. (A) Pipeline overview. Boxes in yellow show steps not requiring GPT-4, those in salmon require GPT-4, and those in blue are executed manually or using local specialized Python scripts. (B) Representative questions for Step 2. Yellow highlight indicates altered text relative to the above question. Full list of questions available in Supplementary materials. (C) Performance assessment of query engineering. Q11 question with the highest recall at temperature 0.5 and was chosen for downstream steps. Q11 provided more flexibility for the model in predicting target papers. (D) Density estimation of probability value distribution indicating increased model confidence in "yes" ("1") responses. Boundary-corrected kernel density estimates computed using biweight kernel and simple boundary correction method (fbckden function from evmix R package). Note that the Y-axes for no and yes response plots have different scales.

Figure 2

Figure 2: FuncFetch results. (A) Schema for Step 4 grading procedure. Red and green colors depict wrong and correct entries, respectively. (B) Precision-Recall of Step 4 output. *Activities* are entries correct on 2/3 compounds present in a reaction. *Substrates* are counted as correct or incorrect independently from activity grading. (+) denotes entries regraded with unknown correct substrates or product counts added to the high-quality dataset (HQD). (C) Average time taken by three human reviewers [R1, R2, R3] and FuncFetch Step 4 [FF] to extract information from 1 manuscript. (D) Number of papers obtained at different steps for each family. The keywords used for initial extraction are described in Supplementary File 1. Costs were calculated by noting the difference between API credits used before and after each code run. (E) Number of extracted and minimally curated enzyme-substrate entries. Entries with sequence IDs can further assist in verifying the domain family of the extracted enzyme. Significant overlap was seen between entries extracted for dioxygenases and CYP450s.