Biom3d, a modular framework to host and develop 3D segmentation methods

Guillaume Mougeot (1), Sami Safarbati (2), Hervé Alégot (2), Pierre Pouchin (2), Nadine Field (4), Sébastien Almagro (5), Émilie Pery (3), Aline Probst (2), Christophe Tatout (2), David E. Evans (4), Katja Graumann (4), Frédéric Chausse (3), Sophie Desset (2)

(1) Aarhus University (Department of Ecoscience, Biodiversity and Conservation, C.F. Møllers Allé 8, Building 1110, 8000 Aarhus C, Denmark)

(2) iGReD - Génétique, Reproduction et Développement, UCA - Université Clermont Auvergne, CNRS - Centre National de la Recherche Scientifique UMR6293, INSERM - Institut National de la Santé et de la Recherche Médicale U1103, (Facultés de Médecine et de Pharmacie, TSA 50400, 28 Place Henri Dunant, 63001 Clermont-Ferrand - France)

(3) IP - Institut Pascal, UCA - Université Clermont Auvergne, CNRS - Centre National de la Recherche Scientifique UMR6602 (Campus Universitaire des Cézeaux, 4 avenue Blaise Pascal, TSA 60026 / CS 60026, 63178 Aubière Cedex - France)

(4) Oxford Brookes University, (Department for Biological and Medical Sciences, Headington Campus, Gipsy Lane, Oxford OX3 0BP, UK - Royaume-Uni)

(5) Université de Reims Champagne-Ardenne, CNRS, MEDYC, Reims, France

U-Net is a convolutional neural network model developed in 2015 and has proven to be one of the most inspiring deep-learning models for image segmentation. Numerous U-Net-based applications have since emerged, constituting a heterogeneous set of tools that illustrate the current reproducibility crisis in the deep-learning field. Here we propose a solution in the form of Biom3d, a modular framework for deep learning facilitating the integration and development of novel models, metrics, or training schemes for 3D image segmentation. The new development philosophy of Biom3D provides an improved code sustainability and reproducibility in line with the FAIR principles and is available as a graphical user interface and an open-source deep-learning framework to target a large community of users, from end users to deep learning developers.

Introduction

The biomedical field produces many three-dimensional images (3D), whether to follow the fate of a tumor in an organ or to measure shape properties of cells, nuclei or other organelles. Such properties can be extracted using a method in image analysis called semantic segmentation. Semantic segmentation classifies each pixel from an image as belonging to the object of interest or to the background and thus produces a binary mask of the image. The increased massification of data has led to the development of innovative solutions to automate segmentation. While these solutions present some challenges, especially when it comes to 3D biomedical images, they offer great potential. The variability in imaging modalities, noise-to-signal ratio, size, voxel spacing or volume distribution of the objects to segment presents exciting opportunities for further development. This is where deep learning methods come into play, being both performant and flexible on a broad range of applications, from denoising[1] to image segmentation[2], and of modalities, from microscopy to medical imaging, both for 2D and 3D images.

U-Net, a convolutional neural network model developed in 2015[3], has been demonstrated to be one of the most effective deep-learning models for 3D semantic segmentation. Numerous U-Net-based applications[2] have since emerged but are still not routinely used for biomedical image analysis. This can be attributed, in part, to the difficulty encountered by non-programmers in mastering such tools. Furthermore, there is a lack of evidence to demonstrate the superiority of deep learning methods in comparison with conventional ones. Some methods, such as CellPose[4,5], StarDist[6] and DeepImageJ[7], are ready to use, with the necessary code, documentation, and information about the computing environment[2]. Unfortunately, they have lost some of their flexibility, and adaptation to other datasets. Their possibility of new training, especially for 3D images, is not always straightforward or even possible. On the other hand, nnU-Net[8], with its ability to auto-configure itself on training sets, performs well for many image acquisition modalities, but is not accessible to users without programming experience. At the other end of the skills spectrum, deep learning developers have at their disposal a bank of perfectly documented and up-to-date functions thanks to MONAI[9], but without an assembly plan, such as proposed for 2D images by OpenMMLab[10], development of any innovation is a time-consuming process, and there is currently no available method for evaluating them in a timely manner. The objective of this article is to present the development of a deep learning segmentation framework that combines the ease of use of DeepImageJ with the flexibility of

nnU-Net, while also serving as a development base for improving methods for developers in
the style of OpenMMLab.

In this work, in addition to performance, flexibility and reusability, we propose a new prism
through which to evaluate a deep learning method: **sustainability**. Our definition of method
sustainability encapsulates two main objectives: method accessibility and adaptability. Method
accessibility relates to the range of users concerned with the tool. Increasing this range would
not only result in an enlarged user community, but would also facilitate the emergence of
multidisciplinary interactions, a goal that is shared by numerous researchers[11]. This is
particularly true for software inherited from fundamental research, which attempts to reach
applied research. Involving end-users will ensure that the software meets the needs of an
external community and has concrete applications, giving it both meaning and feedback for
improvements. Involving external developers will attract novel ideas while strengthening a
community of maintainers. Method adaptability relates to this last community of developers
and is the ability of a tool to quickly evolve, especially in the fast-moving world of deep
learning. It can be reasonably assumed that the more adaptable a tool is, and the broader its user
community, the longer it should last.

Following this, we defined a new code development philosophy. To reach a wider audience, our
aim is to create a series of tools that bridge the gap between end-users and developers in a gentle
way, meaning that end-users wishing to deepen their understanding of the method right down
to the lines of code need to be able to do this in small steps only. For each user profile, the
objective is thus to substantially reduce the time required to invest in using a deep learning
method, while simultaneously expanding the scope of accessible functions (Figure 1). The
intention is to prioritize usability to the same extent as functionality. Current state-of-the-art
methods usually target only one of these user profiles: nnU-Net[8], Cellpose[5] or StarDist[6] target
Python Programmers, while ZeroCostDL4Mic[12] or DeepImageJ[7] are mainly addressed to Non-
Programmers (Figure 1). Moreover, during the code implementation, the emphasis should be
made on code clarity, which implies that the code should remain comprehensible from its
overall architecture to its individual lines by, for example, being presented in a hierarchical,
tree-like structure. This approach starts with high-level, general functions and progressively
delves into more granular details and functionalities, facilitating a gradual and systematic
comprehension of the code.
Such a method can also be made adaptive to novel innovations by incorporating an additional
objective into the development process: code modularity. Code modularity means that

components should be as self-contained and independent as possible (Figure 1). In computer

science, this concept is also known as code cohesion and is opposed to code coupling[13]. This

approach allows programmers to seamlessly incorporate or remove specific code components

without causing undue disruptions to the overall system.

Following all these sustainability constraints, we developed a series of open-access tools called

Biom3d. By default, it is optimized to segment 3D images potentially having multiple channels

or simultaneously presenting objects from different classes. These volumetric images can

originate from CT-scan, MRI, confocal, X-ray or electron microscope. Biom3d integrates

offline and online interfaces (GUI, CLI, and API), automated configuration processes, editable

configuration files and a modular deep learning framework facilitating the choice of models,

metrics, data loaders or training routines.

Results

Biom3D flexibility and performance. Biom3d was first benchmarked with medical datasets using part of the Medical Segmentation Decathlon (MSD)[14] and the Multi-organ Abdominal challenge (often called BTCV)[15]. These datasets have served to develop the flexibility of nnU-Net and constitutes thus the primary goal of Biom3d performance (Figure 2). On both datasets, Biom3d automatically adjusts its training configuration, resulting in Dice scores on the test sets exceeding those of nnU-Net (Figure 3). To demonstrate its performance against conventional methods, Biom3d was compared with NucleusJ[16], a method specialized in 3D segmentation of individual nuclei. A custom dataset of 93 images of individual plant nuclei of various shapes and fluorescence intensity captured with a structured illumination microscope was created[17]. In this case, in addition to nnU-Net and NucleusJ, Biom3d could also be compared to methods designed for 3D nucleus segmentation in fluorescent images like DeepCell[18], QCANet[19], Cellpose[5] and StarDist[6] (Figure 3). While being slightly better than nnU-Net, Biom3d significantly outperforms the other methods, even the conventional method NucleusJ. Our hypothesis is that the pretraining of Cellpose, DeepCell and QCANet and the star-convex polyhedron constraint of StarDist introduce strong biases and prevent the model from appropriately fitting to the strong variation of intensity within the nuclei. To further assess its capabilities, Biom3d was also evaluated with other modalities (Figure 2). For electron microscope (EM) images, Biom3d achieved a Dice score of 92% when evaluated with the two 3D images from EPFL public database[20] (Figure 3). Finally, Biom3d was applied to an EM image of plant root nuclei, to synchrotron images of aortic lamellae and to segment nonconvex objects such as membranes of epithelial cells. In all these cases, Biom3d successfully segmented the objects of interest (Figure 2).

A modular architecture. During Biom3d development, a significant amount of effort was dedicated to ensuring code modularity. It would be beneficial for programmers to have the opportunity to experiment with a broad degree of freedom in the deep learning hyper-parameters by altering the type of deep learning model, the learning rate, or the data loading process. These challenges are tackled with the modular structure of Biom3d, which first core components are Configuration Files. The Configuration Files of Biom3d depart from those of OpenMMLab being both simplified and completed. They include the definition of two types of hyper-parameters. First, stand-alone hyper-parameters can be integers, float numbers, or lists. They include parameters defined in the Graphical User Interface (patch size, number of epochs etc.) as well as many additional stand-alone hyper-parameters such as the initial learning rate

or whether to use half-precision float-point format or not. Second, module hyper-parameters
are key-value dictionaries. In this dictionary, the first key-value pair precises the name of the
module being used, and the second key-value pair defines the parameters of this module. For
example, "UNet3DVGGDeep" is the name of the 3D U-Net model in Biom3d, and its set of
parameters is the number of pooling layers of the model and the number of classes of objects
in the images (Figure 4).

The second modularity component of Biom3d is the Module Register. Modules are code
components classified in eight categories (Figure 4): Preprocessors, preparing the datasets
before training, Datasets, loading the datasets during training, Models, defining the deep
learning models, Metrics, defining the loss functions for model performance assessment,
Trainers, defining the training and validation loops, Predictors, defining the prediction loops,
Postprocessors, processing the model output before saving and Callbacks, decoupling all
recurrent events such as model saving, learning rate updates, logs printing and saving, or loss
updates from the training loop (Figure 4). We expect that such a paradigm will simulate a
significant number of deep learning methods, with a broader application spectrum than just
image segmentation. Except for Callbacks which are defined in the Builder (see below), all
available Modules in Biom3d are named and listed in the Module Register. While editing the
Configuration File, a user can thus select from the Register the modules that fit the most to the
expected task. As modules are Python classes or functions, if the user does not find the
appropriate modules, new modules can be easily integrated into Biom3d by importing them and
adding a new entry to the Register. It must be noticed that Biom3d accepts Pytorch modules
from any origin if they respect the expected inputs and outputs of the surrounding modules. For
example, if intending to add a new Metric to the default Biom3d configuration, the user must
only make sure that it includes a few arguments like a name, a value and an average value. Once
added to the Register, the new Module can directly be incorporated in Biom3d workflow by
simply editing the Configuration File.

If Modules are the organs of Biom3d, the Builder is its skeleton, providing a general structure
for the Module to properly work together. The Builder reads the Configuration File, retrieves
and instantiates the selected modules from the Register, and prepares them for training or
prediction. Once a Builder is instantiated with a Configuration File, the user can then easily
start the training or prediction process by calling a single function. The Builder stores its
configuration and the training status (training curves, etc.) which can then be reused to carry on
interrupted training or to fine-tune models with a new Configuration File.

An easy-to-use tool. Biom3d integrates one local Graphical User Interface (GUI) and one
online GUI in the form of a Google Colab notebook. An important innovation with Biom3d
interfaces is the "auto-configuration" button. Once the dataset folders path has been entered and
this button pressed, Biom3d proceeds to a cascade of hidden operations (Supplementary Figure
1). The dataset is first scanned to check its quality and to retrieve its characteristics, such as the
median image size or the median sampling. Biom3d is flexible on the input image format, as it
works with most medical formats (Nifti, DICOM etc.) and works with TIFF format, largely
used for microscopy data. Biom3d data scanning process is equipped with many safeguards to
automatically correct most user annotator mistakes, which seems to be decisive in avoiding the
"first-click abandonment" phenomenon. These data characteristics are then used to normalize
the images and to automatically configure the training process of the deep learning model.

The result of this automated training configuration, including the definition of the patch size or
the batch size, is stored in a YAML file, is partially displayed in the interface, and is left editable
in its entirety if needed. Finally, pressing on "start" initiates the training process. The local
interface can also be employed in conjunction with a remote server, where computing resources
are installed, and with OMERO[21], a hosting platform for microscopy images. While the training
proceeds, all relevant information, such as the training curves or the trained model, is
periodically stored. Once trained, a model can be either fine-tuned on another dataset, or used
for prediction. The prediction process is straightforward for the end user (Supplementary Figure
1): the training configuration file is used to load the pretrained model, to normalize the new
dataset, and to execute the prediction workflow.

A toolbox for bioimage analysts. Biom3d has been packaged as an easy-to-use Python library
that can serve as an Application Programming Interface (API) and integrates a Command Line
Interface (CLI). Exploiting the CLI enlarges Biom3d potentialities. Users may for instance
execute Biom3d on a High-Performance Computing (HPC) resource in a batch process while
applying it on a large variety of datasets. They could also isolate individual processes such as
data preprocessing, auto-configuration, or model training. Moreover, to fuse capabilities of
multiple models trained on different datasets or with different configurations, Biom3d allows
multi-model predictions. This last capability is particularly important to assemble the work of
different teams across the world, working under different conditions. All these CLI options are
directly accessible after installation of Biom3d Package, referenced in the Python Package
Index (PyPI).

Python programmers may also be interested in exploiting the potential of the Configuration File

and the eight types of modules. Configuration Files of Biom3d allows fine-tuning of more

hyper-parameter settings more precisely than is feasible through the GUI alone, without the

need to delve into Biom3d code. Biom3d modularity allows for rapid experimentation with

different configurations to identify the optimal setup for specific tasks or datasets. For example,

the default deep learning model of Biom3d, which corresponds to the dynamic 3D U-Net

available in nnU-Net framework, can easily be changed for another one. As a result, we

demonstrated that a 3D EfficientU-Net model can outperform the 3D U-Net on the Pancreas

dataset (Figure 3). Additionally, Biom3d is compatible with MONAI[9], public library integrating

the latest biomedical models for multidimensional images, which enable quick use cutting-edge

models.

A framework for developers. Biom3d has also been meticulously crafted at a granular code

level, allowing deep learning programmers, well-versed in working with libraries like PyTorch

or TensorFlow, to easily understand, edit, remove, or add code components. It is also worth

noting that Biom3d plays an important role in the process of comparing old and new code

segments when creating new code based on existing works. This development strategy was, for

instance, exploited to entirely redesign the original Dataset Module of nnU-Net. As Biom3d

easily accepts alien code incorporation, the entire and original "Dataset Module" of nnU-Net

was integrated as a Biom3d Module. Following this integration, a series of intermediate and

hybrid Dataset Modules were developed and tested. Comparisons between old and new Dataset

Modules could easily be done by editing a single line in the Configuration File. The weak points

of the prototype Dataset Module were rapidly spotted and improved. The final Dataset Module,

which relies on the TorchIO library[22], is likely the reason why Biom3d outperforms nnU-Net

on multiple tasks (Figure 3). This development strategy can be followed for all Biom3d

Modules. Last, as each piece of Biom3d code can be isolated from the others, they can easily

be extracted and reused for another independent project. This is particularly true not only for

Biom3d Modules but even for individual functions such as the auto-configuration or the image

loading and saving.

Discussion

Biom3d is a new, high-performing, and flexible set of tools applicable to various 3D

segmentation problems, with numerous biological and medical applications. It surpasses in

accuracy specialized tools, such as NucleusJ, while demonstrating state-of-the-art results on a

wide variety of new problems, such as plant chromocenter segmentation or aorta lamella
segmentation. It responds to the needs of end users through easy to install and easy to use
interfaces, enabling auto-configuration of the deep learning model training, and compatible
with several image formats and with OMERO software[21]. To make Biom3d an even bigger part
of the landscape of tools now available to biologist users, it will be made compatible with
Napari[23], ZeroCostDL4Mic[12,24] and DeepImageJ[7]. In line with FAIR principles for AI[25], future
models will then be shared online in Open Neural Network Exchange (ONNX)[26] format, on
website such as HuggingFace.co or Bioimage.io, and future developments streamlined on
MLflow (https://mlflow.org). To broaden Biom3d's spectrum of applications, further
developments should include instance segmentation, object tracking, image denoising as well
as processing images in proprietary formats or with large N-dimension such as light sheet
images and to offer the possibility of using images stored with the next generation file formats
(NGFF) such as OME-Zarr[28].

The implementation of all these developments will be facilitated by the modular code
architecture of Biom3d. Biom3d has been designed as a sandbox, within which developers are
strongly encouraged to integrate new code elements. It is coded in the Python programming
language and based primarily on the Pytorch[29] deep learning framework. This language and
framework were chosen for their current popularity in the field of deep learning, so code
implemented with them, such as MONAI, can be added to Biom3d with little to no effort. These
constraints may yet pose some integration challenges for developers using other programming
languages or deep learning libraries, such as TensorFlow[30], with which StarDist was created, or
JAX[31], an emerging framework. While being highly modular, Biom3d code remains coupled to
some extent. This occurs because it is needed in some instances to improve efficiency, by using
shared internal functions across different components. It is minimized however to keep the
advantages of modularity as interconnection can make the codebase more sensitive to changes
as alterations to one section of the code might unintentionally impact other areas, complicating
maintenance, and updates. The development of Biom3d represents a significant advance in the
modularity of deep learning code, while maintaining performance and avoiding code
redundancy. While further increases in modularity are possible, they may necessitate a
significant additional investment of time and resources.

Finally, through the benchmarking performed on nucleus images in this article, we have
pinpointed one of the main remaining limitations of deep learning methods: they depend on
large, manually annotated datasets. While conventional image analysis tools can help provide

partial annotations, manual interventions are inevitable, which also impedes the spread of deep learning methods. The modular code of Biom3d could be exploited to reduce this time-consuming process, by including methods such as active learning[32], generative methods[33], weakly supervised learning[34], and self-supervised learning[35,36]. Biom3d has, for instance, successfully performed self-supervision for 3D images, which involved both image classification and image segmentation.

Most importantly, we hope that the intuitive design of Biom3d, from its graphical interfaces to its modular code architecture, will foster collaboration among diverse communities, including biologists, radiologists, microscopists, image analysts and developers, and will render it both reusable and sustainable.

Online content

Biom3d is available at https://github.com/GuillaumeMougeot/biom3d and as a notebook at https://colab.research.google.com/github/GuillaumeMougeot/biom3d/blob/master/docs/biom3d_colab.ipynb.

References

1. Buchholz, T. O. *et al.* Content-aware image restoration for electron microscopy. *Methods Cell Biol.* **152,** 277–289 (2019).

2. Mougeot, G. *et al.* Deep learning -– promises for 3D nuclear imaging: a guide for biologists. *J. Cell Sci.* **135,** jcs258986 (2022).

3. Ronneberger, O., Fischer, P. & Brox, T. U-net: Convolutional networks for biomedical image segmentation. *Lect. Notes Comput. Sci. (including Subser. Lect. Notes Artif. Intell. Lect. Notes Bioinformatics)* **9351,** 234–241 (2015).

4. Stringer, C., Wang, T., Michaelos, M. & Pachitariu, M. Cellpose: a generalist algorithm for cellular segmentation. *Nat. Methods* **18,** 100–106 (2021).

5. Pachitariu, M. & Stringer, C. Cellpose 2.0: how to train your own model. *Nat. Methods* **19,** 1634–1641 (2022).

6. Weigert, M., Schmidt, U., Haase, R., Sugawara, K. & Myers, G. Star-convex polyhedra for 3D object detection and segmentation in microscopy. *Proc. - 2020 IEEE Winter Conf. Appl. Comput. Vision, WACV 2020* 3655–3662 (2020).

299   doi:10.1109/WACV45572.2020.9093435

300   7.   Gómez-de-Mariscal, E. *et al.* DeepImageJ: A user-friendly environment to run deep
301   learning models in ImageJ. *Nat. Methods* **18,** 1192–1195 (2021).

302   8.   Isensee, F., Jaeger, P. F., Kohl, S. A. A., Petersen, J. & Maier-Hein, K. H. nnU-Net: a
303   self-configuring method for deep learning-based biomedical image segmentation. *Nat.*
304   *Methods* **18,** 203–211 (2021).

305   9.   MONAI Consortium. MONAI: Medical Open Network for AI. (2023).
306   doi:https://doi.org/10.5281/zenodo.4323058

307   10.   MMSegmentation. Available at: https://github.com/open-mmlab/mmsegmentation.

308   11.   Nogare, D. D., Hartley, M., Deschamps, J., Ellenberg, J. & Jug, F. Using AI in
309   bioimage analysis to elevate the rate of scientific discovery as a community. *Nat.*
310   *Methods* **20,** 973–975 (2023).

311   12.   Chamier, L. von *et al.* ZeroCostDL4Mic: An open platform to use deep-learning in
312   microscopy. *bioRxiv* 2020.03.20.000133 (2020). doi:10.1101/2020.03.20.000133

313   13.   Gamma, E., Helm, R., Johnson, R. & Vlissides, J. *Design Patterns: Elements of*
314   *Reusable Software*. *Addison-Wesley Professional Computing Series* (Addison-Wesley
315   Longman Publishing Co., Inc., 1996).

316   14.   Antonelli, M. *et al.* The Medical Segmentation Decathlon. *Nat. Commun.* **13,** 4128
317   (2022).

318   15.   Gibson, E. *et al.* Multi-organ Abdominal CT Reference Standard Segmentations.
319   *Zenodo, 22-Feb-2018* **26,** 1–7 (2018).

320   16.   Dubos, T. *et al.* Automated 3D bio-imaging analysis of nuclear organization by
321   NucleusJ 2.0. *Nucleus* **11,** 315–329 (2020).

322   17.   iGReD, U. C. A. Dataset of individual plant nuclei. Available at:
323   https://omero.bio.fsu.edu/webclient/?show=project-5001.

324   18.   Greenwald, N. F. *et al.* Whole-cell segmentation of tissue images with human-level
325   performance using large-scale data annotation and deep learning. *Nat. Biotechnol.*
326   2021.03.01.431313 (2021). doi:10.1038/s41587-021-01094-0

327   19.   Tokuoka, Y. *et al.* 3D convolutional neural networks-based segmentation to acquire

328   quantitative criteria of the nucleus during mouse embryogenesis. *npj Syst. Biol. Appl.* **6,**
329   1–12 (2020).

330 20. Lucchi, A., Li, Y. & Fua, P. Learning for structured prediction using approximate
331   subgradient descent with working sets. *Proc. IEEE Comput. Soc. Conf. Comput. Vis.*
332   *Pattern Recognit.* 1987–1994 (2013). doi:10.1109/CVPR.2013.259

333 21. Allan, C. *et al.* OMERO: Flexible, model-driven data management for experimental
334   biology. *Nat. Methods* **9,** 245–253 (2012).

335 22. Pérez-García, F., Sparks, R. & Ourselin, S. TorchIO: A Python library for efficient
336   loading, preprocessing, augmentation and patch-based sampling of medical images in
337   deep learning. *Comput. Methods Programs Biomed.* **208,** 106236 (2021).

338 23. Sofroniew, N. *et al.* napari. (2022). doi:10.5281/zenodo.5848842

339 24. Hidalgo-Cenalmor, I. *et al.* DL4MicEverywhere: Deep learning for microscopy made
340   flexible, shareable, and reproducible. *bioRxiv* (2023). doi:10.1101/2023.11.19.567606

341 25. Huerta, E. A. *et al.* FAIR for AI: An interdisciplinary and international community
342   building perspective. *Sci. Data* **10,** 487 (2023).

343 26. Bai, J., Lu, F. & Zhang, K. ONNX: Open Neural Network Exchange. *GitHub*
344   *repository* (2019).

345 27. MLflow: An Open Source Platform for Machine Learning. (2024).

346 28. Miles, A. *et al.* zarr-developers/zarr-python: v2.17.1. (2024).
347   doi:10.5281/zenodo.10790679

348 29. Paszke, A. *et al.* PyTorch: An imperative style, high-performance deep learning library.
349   *arXiv* **32,** (2019).

350 30. Abadi, M. *et al.* TensorFlow: Large-Scale Machine Learning on Heterogeneous
351   Distributed Systems. (2016).

352 31. Bradbury, J., Frostig, R., Hawkins, P., Johnson, M., Leary, C., Maclaurin, D., Necula,
353   G., Paszke, A., Vanderplas, J., WandermanMilne, S., Zhang, Q. JAX: composable
354   transformations of Python + NumPy programs. 1–8 (2018).

355 32. Budd, S., Robinson, E. C. & Kainz, B. A survey on active learning and human-in-the-
356   loop deep learning for medical image analysis. *Medical Image Analysis* **71,** 102062

(2021).

33.   Fu, C. *et al.* Three dimensional fluorescence microscopy image synthesis and

segmentation. *IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit. Work.* **2018–**

June, 2302–2310 (2018).

34.   Zhao, Z. *et al.* Deep Learning Based Instance Segmentation in 3D Biomedical Images

Using Weak Annotation BT - Medical Image Computing and Computer Assisted

Intervention – MICCAI 2018. in (eds. Frangi, A. F., Schnabel, J. A., Davatzikos, C.,

Alberola-López, C. & Fichtinger, G.) 352–360 (Springer International Publishing,

2018).

35.   Sahasrabudhe, M. *et al.* Self-supervised Nuclei Segmentation in Histopathological

Images Using Attention BT - Medical Image Computing and Computer Assisted

Intervention – MICCAI 2020. in (eds. Martel, A. L. et al.) 393–402 (Springer

International Publishing, 2020).

36.   Kirillov, A. *et al.* Segment Anything. (2023).

Figure 1 – **Method accessibility for different user profiles. a**, Fulfilling the needs of a
continuum of user profiles. In the abscissa are conjointly represented the skills and needs of
deep learning users while in the ordinate is represented the estimated time required for them to
use the method and fulfil their needs. On the left, non-programmers may expect easy-to-use
software with graphical user interfaces and better segmentation results than with non-deep
learning methods, without the need for delving into deep learning theory. In the middle, Python
programmers may look for a command line interface or a Python package as well as a
performant, flexible and easily reconfigurable deep learning tool. On the right, deep learning
developers may be interested in a well-documented and modular deep learning framework,
where pieces of code can easily be changed, removed, or added. Most of the state-of-the-art
methods are only targeting one user profile, noticeably omitting deep learning developers. **b**,
Difference between a modular code and a coupled code. Each piece of code represents a node
in these graphs. Each edge is an interaction between two distinct pieces of code. A modular
code (*top*) means that the few code components are clearly isolated and have few clearly defined
links. A coupled code (*bottom*) has code components with a low internal cohesion and are
strongly intertwined.

Figure 2 – **Samples of Biom3d predictions over medical datasets (*top row*) and biological datasets (*bottom row*).** All views originate from testing images, unseen during the training of Biom3d default model. **a-d** and **f** originate from public datasets while the rest are custom datasets. For each example, a 3D view is depicted on top of a 2D z-slice, both representing an overlay of the segmentation result and the raw image. The rendering was done by Napari. **a**, Multi-organ abdominal challenge (BTCV) representing thirteen segmented organs in CT-scan. **b**, Three brain tumor sub-regions in MRI. **c**, A pancreas (red) and a tumor (blue) in CT-scan. **d**, A lung tumor in CT-scan. **e**, An aortic lamella in a synchrotron microscope. **f**, EPFL dataset of mitochondria in an electron microscope. **g**, Plants cell nuclei in an electron microscope. **h**, A plant cell nucleus and its chromocenters in a structured illumination microscope. **i**, Nuclei of a mouse embryo in a confocal microscope. To help the model separate nuclei clusters, frontier regions between nuclei have been segmented (blue). **j**, An epithelial cell of a Drosophila embryo. Both the inner cell and cell membranes have been segmented.

Figure 3 – **Biom3d performances. a**, Biom3d reaches similar Dice scores as nnU-Net on various 3D segmentation datasets. The Dice score, when applied to 3D segmentations, measures similarity by calculating twice the volume of intersection divided by the total volume of both the ground truth mask and the prediction. The higher the Dice score is, the better. The images in these datasets were captured with CT-scan (BTCV, Lung tumor, Pancreas tumor), MRI (Brain tumor), fluorescent microscope (Nuclei), and electron microscope (EPFL mitochondria). Public datasets from medical segmentation challenges (BTCV, Brain tumor, Lung tumor, and Pancreas tumor) were selected for their diversity in the number of object classes to segment. These datasets were split in two, with the first half of the images and masks used for training and the second half for testing. For the custom dataset Nuclei, 65 images and masks were used for training, while the remaining 28 were used for testing. The EPFL dataset has only one publicly available training image and one testing image. Training and testing images were identically chosen for Biom3d and nnU-Net. **b**, Benchmark of 7 segmentation methods on a custom dataset of 3D plant nuclei. NucleusJ is a non-deep learning method specialized in 3D nucleus segmentation. Only Biom3d, nnU-Net and StarDist provided the requirement to train a new 3D segmentation model. Without a way to retrain them, Cellpose, QCANet and DeepCell could only be tested with their pretrained models. Only Biom3d and nnU-Net exceeded the average Dice score obtained with NucleusJ. **c**, Example of Biom3d application to obtain biological insights. The volume of relative heterochromatin fraction (RHF) refers to the ratio between the

volume of voxels located in chromocenter regions and of voxels located elsewhere in the

nucleus. The box plots represent samples of *A. thaliana* nuclei sorted between guard cells (*top*)

and pavement cells (*bottom*). Biom3d is compared to NODeJ, a non-deep learning add-on of

NucleusJ, on the task of segmenting chromocenters in Col0 and in H1 mutant nuclei. While

obtaining similar results on pavement cells, Biom3d predicted a shift in the volume distribution

inverse to that predicted by NODeJ. The validity of this prediction was manually verified by

experts. This result illustrates the importance of precise segmentations when assessing a

biological hypothesis.

Figure 4 – **Configuration File, Builder and Module Register. (*Left*)** The Configuration File lists the names of existing Modules appearing in the Module Register and defines their parameters (*Greek letters*). **(*Middle*)** The Builder reads parameters and Module names in the Configuration File. It then retrieves the corresponding modules from the Module Register and builds them with their parameters. The Builder can then be used to train a Model with a Dataset, a Trainer, and a Metric. Once trained, the Model can be used by the Builder to predict the segmentation masks of some raw images using a Preprocessor, a Predictor, and a Postprocessor. **(*Right*)** The Module Register lists all existing modules of Biom3d, except for Callbacks which are built in the Builder. There are currently seven different types of modules in the Register, and each type has different variants (*colour shades*).

Figure 5 – **Code modularity of Biom3d. a**, Representation of Biom3d code architecture. Each node in this directed acyclic graph is one Python script in Biom3d. Each directed edge is one call of one script by another. This graph was automatically generated by *pydeps*, a Python dependency visualizer, and by calling the default training workflow of Biom3d (*bottom left node*). The training process instantiates a Builder which then consults the Register to instantiate requested modules from the Configuration file. **b**, Representation of nnU-Net code architecture. For comparison with Biom3d, this graph was also generated by *pydeps* and depicts the nnU-Net training workflow. This graph is more coupled than Biom3d graph, indicating that nnU-Net code will probably be harder to understand or modify. **c**, Exploiting modularity to benchmark model architectures. Once new model architectures have been added to Biom3d, a benchmark experiment can be conducted by only changing the model's name in the configuration files, while leaving the rest of the training hyper-parameters untouched. The default U-Net model in Biom3d is here compared to an EfficientU-Net and a HRNet, both being integrated into Biom3d. These model architectures are trained and tested on the Pancreas tumor dataset. The results of this experiment indicate that, despite being slower, the EfficientU-Net model is more appropriate for this dataset than the others.

Methods

Requirements. Biom3d is a Python3 package essentially relying on numpy and Pytorch packages. Image reading and saving is ensured via scikit-image, SimpleITK and tifffile. Deep learning computation can be either executed on a CPU or a GPU. GPU execution requires the installation of CUDA and CuDNN libraries compatible with the Pytorch library as well as a GPU having at least 10 Gb of VRAM for training and 4 Gb for prediction.

Graphical User Interfaces. The online interface is based on Google Colab and thus does not require accessing a local GPU. Its use requires the connection to a Google account. The training and prediction datasets must be uploaded to a Google Drive accessible via the interface. The code of the online interface is hidden for ergonomic reasons, but is accessible, and it has been made as simple as possible, exclusively using Biom3d framework. The online interface allows to preprocess a training dataset, to auto-configure a training process, to execute the training and to make prediction with a trained model. To take advantage of Biom3d modularity, the Configuration file is directly editable in Google Colab. While requiring access to a computing GPU, the local interface allows a higher degree of flexibility (Supplementary Figure 1 and Supplementary Figure 2). The user can start training or predicting on a local computer or on a private remote Linux server. In both cases, the interface is dynamic depending on user choices. If the user has a trained model and intends to fine-tune it, the interface displays a field for the path of the trained model and a field for the new dataset. If the user has a preprocessed dataset, only the configuration path will be asked. During prediction, if the user has access to an OMERO server (Supplementary Figure 3), the interface will ask for the user credentials and the OMERO dataset number. The OMERO dataset is then downloaded on the computing server, used for prediction, and the resulting images are eventually uploaded to a new OMERO dataset. For the remote interface, the user is additionally asked to provide a name to the training dataset which will automatically be sent to the computing server. After prediction, resulting images can either be downloaded locally or sent to an OMERO server.

Preprocessing. Preprocessing consists in adapting a dataset to the training workflow and, inversely, adapting the training workflow to the dataset. The default preprocessing methodology has been designed and tested for 3D image segmentation. In the following explanation, masks are manually segmented images. The default preprocessing in Biom3d is a four-step process: (1) data reading and scanning to extract the data characteristics, (2) auto-configuration to create

a Configuration file adapted to the data characteristics, (3) data normalization to uniformize

image and mask dimensions and intensities, and (4) data splitting to separate training and

validation sets. Preprocessing is illustrated in Supplementary Figure 4.

Data scanning. For any processing requiring image reading (data-scanning, data-loading,

preprocessing, etc.), Biom3d adaptively reads 3D images stored in NumPy format (.npy), in

TIFF format (.tif or .tiff) or in any other medical formats read by SimpleITK library (see list of

available format on https://simpleitk.readthedocs.io/en/master/IO.html), such as Nifti format.

After preprocessing or prediction, Biom3d saves 3D images or masks along with necessary

meta-data. While compressed formats are appropriate for long term storage (such as Nifti or

TIFF format), fast reading formats are preferred for deep learning applications (such as NumPy

format). After preprocessing, training images and masks are thus stored in NumPy format. After

prediction, Biom3d stores the resulting masks using the input image format and meta-data. As

TIFF tagging system is unrestrictive regarding meta-data formatting, Biom3d image reader

might not properly read meta-data originating from some proprietary formats, except if TIFF

images have successfully been processed with Bio-format. The current image reader of Biom3d

does not support proprietary formats, such as CZI. Once read, Biom3d extracts the dataset

fingerprint from the images. This fingerprint includes the median image size, the mean and

standard deviation of the image voxel intensities within the mask, the 5% and 95% percentiles

of these intensities, and, if available, the median sampling, which represents the voxel

dimensions in meters.

Auto-configuration. The auto-configuration process of Biom3d mainly consists in finding the

best patch size and batch size to provide to the deep learning model, as well as the number and

dimensions of the successive pooling layers occurring in the U-Net model. Biom3d heuristics

produce similar results as nnU-Net ones, yet they have been simplified. Biom3d auto-

configuration process only uses the median size of the input images. The ideal patch size is set

to respect the median size proportions, while the product of its dimensions is smaller than a

maximum patch size, by default defined as $(128,128,128) = (d_1^*, d_2^*, d_3^*)$, a value chosen for

being adapted to GPUs with less than 10 Gb of VRAM. More formally, the goal is to find the

exponents α_i in $\prod_{i=1}^n \frac{D_i}{(1+\epsilon)^{\alpha_i}} = \prod_{i=1}^n d_i^*$, where $n = 3$ is the number of dimensions, D_i, $d_i =$

$\frac{D_i}{(1+\epsilon)^{\alpha_i}}$ and d_i^* are the i-th dimension of the median size, the patch size and the maximum patch

size respectively, and ϵ is a small number typically equal to 10^{-3}. If all exponents α_i were

assumed to be identical, their ideal value is $\alpha^* = \frac{1}{n\log(1+\epsilon)} \sum_{i=1}^{n} \log\left(\frac{D_i}{d_i^*}\right)$. This value would

ensure the preservation of the median size proportions. Yet, for large and strongly anisotropic

images, this may cause some dimensions of the ideal patch size to be set smaller than 1. To

prevent this, an upper bound u_i on α_i's values is set to be $d_i = \frac{D_i}{(1+\epsilon)^{\alpha_i}} \geq 1 \Leftrightarrow \alpha_i \leq \frac{\log(D_i)}{\log(1+\epsilon)} =$

u_i. If $S = \{i \in [\![1,n]\!], \alpha_i > u_i\} \neq \emptyset$, then $\forall i \in S, \alpha_i = u_i$, and $\forall i \notin S, \alpha_i = \frac{1}{n-|S|}(n\alpha^* -$

$\sum_{i \in S} u_i)$, so to preserve $\sum \alpha_i = n\alpha^*$. This process is reiterated until $S = \emptyset$. The final values of

α_i can then be used to obtain $d_i = \frac{D_i}{(1+\epsilon)^{\alpha_i}}$, the patch size. For each dimension, the number of

the 2-pooling in the U-Net model is then defined by $p_i = \max\left(0, min\left(\left\lfloor \log_2\left(\frac{d_i}{\max_i(d_i^*)}\right) + \right.\right.\right.$

$\left.\left.\left. p^* \right\rfloor, p^* \right)\right)$, where p^* is the user-defined maximum number of 2-pooling, by default set to 5. To

prevent features maps having non-integer dimensions after dimension reduction during 2-

pooling, the patch size dimensions d_i are readjusted one last time to the closest multiple of 2^{p_i}.

The batch is set to 2 and eventually increased if the GPU VRAM allows it. The auto-

configuration results are stored in a new Configuration file in Python format, based on the

default Configuration file included in Biom3d.

Data normalization. Data normalization encompasses image reshaping and resizing and voxel

intensity normalizing (Supplementary Figure 5). Images are automatically reshaped to conform

to the standard (channel, height, width, depth) dimensions. Biom3d accepts a wide range of

dimension variants, even within the same dataset. If not specified by the user, Biom3d

automatically detects the location of the channel dimension in 4-dimensional images. For each

mask, a series of check-ups are performed to automatically spot and, eventually, correct

annotation mistakes. For instance, within the same dataset, it can be found manual annotations

with an inconsistent number or order of dimensions. If annotating with levels of grey, users

could also mistakenly decide to use inconsistent levels of grey or more levels of grey than

existing classes of objects. Depending on the mistake, Biom3d either corrects or warns the user.

For instance, if two classes of object are expected and more than two were found in the mask,

Biom3d automatically applies a threshold by considering as background the most recurrent

class. In case where three or more classes are expected and even more classes are found in the

mask, Biom3d displays an error. Biom3d is compatible with masks having 4 or 3 dimensions.

Image intensities are then Z-normalized using either the mean and standard deviation of the

image voxel intensities, or, if available, using the median mean and standard deviation of the

dataset voxel intensities retrieved during data scanning. If the median sampling could be retrieved, images and masks are resized to all match the media sampling. Images are resized with trilinear interpolation while masks with nearest neighborhood. Finally, for each object class in mask, a random sampling is performed to extract some foreground locations. These values will be used during data loading to rapidly locate foreground regions during image patch cropping. Once preprocessed, the images, masks and foreground location are stored in automatically created output folders. The output folder paths are added to the Configuration file.

Data splitting. Following the cross-validation strategy, the dataset is by default split into 5 subsets called folds (Supplementary Figure 5). More formally, each image filename is associated with a random integer between 0 and 4. During training, if fold 0 is selected, images associated with 0 will be considered as validation images while remaining images will be considered as training images. If less than 10 images are present in the dataset, Biom3d reduces the number of folds to $\max\left(\left\lfloor\frac{N}{2}\right\rfloor, 2\right)$, where N is the number of images in the dataset. If only one image is found in the dataset, Biom3d split the image and mask in two along the largest image dimension – 80% of the image will be used for training and 20% for validation. Filenames with associated fold indices are stored in a CSV file that will be loaded during training. The CSV file path is added to the Configuration file.

Data loading. Data loading consists in loading a batch of preprocessed data into computer memory and eventually performing data augmentation, for it to be prepared for the training workflow (Supplementary Figure 6). Several data loading modules for 3D image segmentation are available in Biom3d: one based on nnU-Net batchgenerators package, one based on TorchIO SubjectsDataset, and one based on Pytorch Dataset. The latter one is the default and will be detailed here (Supplementary Figure 6). The data loading module initialization first loads the image and mask filenames of training and validation sets using the CSV file created during data splitting. To fasten data loading, images and masks can be, on demand, loaded into computer memory. The initialization then creates the data augmentation transformations used during training with TorchIO package: random cropping, random affine transform, random anisotropy, random flipping, random intensity variation, random blurring, random noise, random patch swapping, and random contrast variation. The axes of the rotation in the random affine transform and of the random anisotropy depends on the patch size anisotropy. By default, anisotropy transforms, and rotation transforms are applied to every axis. If any patch size dimensions are bigger than three times the smallest patch size dimension, then only these

dimensions are considered as valid axes to apply random anisotropy. In this scenario, only the
smallest dimension is considered a valid axis for rotation transforms. Once this initialization is
completed, the data loader is ready to use. During training data loading, a batch of foreground
locations, images and masks are loaded into computer memory. The image and mask are then
randomly cropped using the patch size. To do so, several constraints are considered. First, if
rotation transforms are applied, the patch size is temporally enlarged beforehand to avoid empty
corners appearing in images and masks once rotated. The enlarged patch size is set to be cubic
and its dimensions equal to the largest diagonal of the patch. Second, foreground locations are
used to crop one image and mask pair out of three in the batch. Among the list of possible
foreground locations, one is selected to be the location of the center of the patch. Third, if the
cropped image and mask are smaller than the patch size, then they are padded with zeros equally
in all three dimensions. Once cropped, the images and masks are transformed with the rest of
the data augmentations before being output. During validation data loading, only the random
cropping is performed without any other form of data augmentation.

Dynamic models. Biom3d includes several deep learning model definitions. The default deep
learning model is a standard 3D U-Net model for semantic segmentation[1]. It has been
implemented in a modular fashion, meaning that the encoder, the decoder and the
c[1]onvolutional blocks can work independently. More specifically, the default VGG encoder[2]
can straightforwardly serve as an independent classification model or can be replaced by any
other encoder in the 3D U-Net model, such as the 3D EfficientNet[3] included in Biom3d, the
MONAI models, or any Pytorch model compatible with 3D images. The default 3D U-Net
model architecture is dynamic and depends on the number p_i of successive pooling layers found
for each dimension during the auto-configuration. The maximum number of 2-pooling along a
given dimension k is determined by $\min(p_k, \max_i p_i)$. For each case where $p_k < \max_i p_i$, there
will be $\max_i p_i - p_k$ 1-pooling layers, evenly distributed between the head and tail of the
encoder. For instance, if the auto-configuration sets the ideal number of successive pooling
layers to be $(3,5,5)$, the pooling layers of the 3D U-Net will have the following list of kernel
dimensions: $((1,2,2), (2,2,2), (2,2,2), (2,2,2), (1,2,2))$. The definition of the rest of the model
layers follows the original U-Net architecture.

Training. Losses, metrics, callbacks as well as training and validation routines are all
independent modules in Biom3d, the default ones being designed for 3D semantic
segmentation. The default training loss is the sum of the class Dice score and the cross-entropy

between the predicted and annotated masks. Default validation metrics include the Dice score

and the intersection over union between the predicted and annotated masks. Even if the default

behavior of these metrics requires the 3D annotated masks to be formatted such that each pixel

value of the mask represent a single object class (0, 1, 2, etc.), Biom3d metrics are also

compatible with 4D annotated masks formatted with an additional channel dimension

representing each individual object class. In such setup, Biom3d metrics accept input pixel to

be associated with multiple object classes. The default optimizer is the stochastic gradient

descent with a Nesterov momentum of 0.99 and a weight decay of 3e-5. The default training

routine uses the data loader to get a batch of data, passes it to the model then to the loss,

computes the gradients and clips their norms, before updating the model parameters using the

optimizer. The training routine periodically calls the callbacks (Supplementary Figure 7) to

update the learning rate with cosine annealing, to print and store information about the training

and validation, and to store the model parameters of the best performing model. Training and

validation stored information includes the training and validation losses per epoch and

prediction snapshot on the validation set. After loading the Configuration file, the Builder

oversees the instantiation of the losses, metrics, callbacks and optimizer before executing the

training and validation routines. This execution can be done using mixed precision and in

parallel on multiple GPUs. For reproducibility reasons, once the training is finished, the output

folder includes the Configuration file and the data splitting file, in addition to all the other

information stored by the training callbacks. If interrupted, training can thus be restarted by

solely using this output folder. Biom3d also allows to perform model finetuning or retraining

by instantiating a new Builder using both an output folder and a new Configuration file.

Predicting. Predicting with Biom3d encompasses three steps: (1) pre-processing, by default

including image reading and normalization, (2) predicting, by default involving tiling the

images and passing the tiles to the model, and (3) post-processing, by default implying

discretizing model outputs, removing noise and saving the predicted masks. Each of these steps

is an isolated Biom3d module. The modularity of Biom3d allows to reuse the exact same

function for pre-processing as the one used to normalize training data. Before being passed to

the deep learning model, input images are tiled with TorchIO grid sampler. For one input image,

this function creates a series of patches equally distributed and overlapping by an overlap equal

to half of the patch dimensions. To respect these two tiling constraints, the input image is

eventually padded with zeros. Batch of patches are constituted and given to the model. To

increase the prediction accuracy, each batch is augmented by flipping along the seven possible

combinations of (x, y, z)-axis. Augmented predictions are then flipped back before being averaged. Predicted tiles are then aggregated using Hann filtering to reduce edge artefacts in patch overlapping regions. As data pre-processing involved data resampling, the aggregated prediction is finally resized back to the original image dimensions. As Biom3d framework is compatible with ensemble learning, it is also possible to aggregate predictions coming from different models. If such case, model outputs are simply averaged before being post-processed. Post-processing then starts by discretizing the prediction. For 4D masks, discretizing means to apply a threshold of 0.5 to the output of the sigmoid function applied to the model output. For 3D masks, discretizing means to retrieve the argmax of the output of the SoftMax function applied to the model output. On user request, two distinct noise removal strategies can then be applied to remove too small, segmented regions. Connected components can thus be computed to retrieve either the biggest segmented object or objects which volumes are higher than an Otsu threshold determined using the volume distribution of all connected components. Finally, the post-processed prediction is automatically saved along with input image metadata.

Evaluation. Controlling the quality of a trained model can be done with Biom3d by either using the local graphical user interface or the application programming interface. For 3D segmentation, one folder containing 3D ground truth masks of images different from the training set and another folder with the corresponding predictions can be passed to Biom3d to retrieve the average Dice score on this set. To fasten experiments and benchmarking, Biom3d also includes scripts that allow the preprocessing, training, prediction, and evaluation of a new deep learning model on a new dataset to be executed with a single command

Data availability

All public datasets displayed on Figure 2 or used to benchmark Biom3d in Figure 3 can be accessed via their respective website: Beyond The Cranial Vault (BTCV)-Abdomen, https://www.synapse.org/Synapse:syn3193805; the Medical Segmentation Decathlon (Brain tumor, Lung tumor and Pancreas tumor), http://medicaldecathlon.com; EPFL electron microscopy dataset, https://www.epfl.ch/labs/cvlab/data/data-em. The rest of the data created in the frame of this work is hosted by Mésocentre UCA on a public OMERO server https://omero.mesocentre.uca.fr/webclient/userdata/?experimenter=352. Trained models and predictions created by Biom3d on the public datasets can be found in the following OMERO project: https://omero.mesocentre.uca.fr/webclient/?show=project-2005. Trained models and custom training datasets used to create the illustration in Figure 2 for the X-ray microscopy

image of aorta, for the electron microscopy image of plant root nuclei, for the confocal microscopy images of the mouse embryo and the Drosophila embryo can be found in the following OMERO project: https://omero.mesocentre.uca.fr/webclient/?show=project-2007. For all custom datasets, the specific images and predictions represented on Figure 2 have been set aside in the following OMERO project: https://omero.mesocentre.uca.fr/webclient/?show=project-2006. The plant nucleus dataset used to benchmark the nucleus segmentation methods in Figure 3 can be found in the following OMERO project: https://omero.mesocentre.uca.fr/webclient/?show=project-2002. For the previous dataset, the training data and the trained model of Biom3d can be found in the following OMERO project: https://omero.mesocentre.uca.fr/webclient/?show=project-2001. The plant chromocenter dataset used to benchmark Biom3d and NODeJ in Figure 3 can be found in the following OMERO project: https://omero.mesocentre.uca.fr/webclient/?show=project-2004. For the previous dataset, the training data and the trained model of Biom3d can be found in the following OMERO project: https://omero.mesocentre.uca.fr/webclient/?show=project-2003.

Code availability

Biom3d is a public python package referenced in the Python Package Index (https://pypi.org/project/biom3d/). The latest version of the code and documentation of Biom3d can be found on GitHub (https://github.com/GuillaumeMougeot/biom3d).

References

1. Ronneberger, O., Fischer, P. & Brox, T. U-net: Convolutional networks for biomedical image segmentation. *Lect. Notes Comput. Sci. (including Subser. Lect. Notes Artif. Intell. Lect. Notes Bioinformatics)* **9351,** 234–241 (2015).

2. Simonyan, K. & Zisserman, A. Very Deep Convolutional Networks for Large-Scale Image Recognition. *CoRR* **abs/1409.1,** (2014).

3. Tan, M. & Le, Q. V. EfficientNet: Rethinking model scaling for convolutional neural networks. *36th Int. Conf. Mach. Learn. ICML 2019* **2019–June,** 10691–10700 (2019).

Acknowledgements

We would like to thank Adama Nana for his support with benchmarking nucleus segmentation methods, the bioinformatics core facility of the Au-Bi (Mesocentre UCA) and the iGReD CLIC

microscopy facilities. This work was partially achieved using HPC resources from GENCI–
IDRIS (Grant 2022-AD011013709) on the supercomputer Jean Zay's A100 partition. We thank
Dr. Fredy Barneche (CNRS, IPBS Sorbonne) and Sara Farrona (University of Galway, Ireland)
for providing us with seeds; Xiaowen Liang (Université de Reims Champagne Ardenne) for
providing us with annotated images of rat aorta; Cynthia Dennis (iGReD) for providing us with
an annotated dataset of epithelial cells of drosophila ovaries and Nicolas Allègre (iGReD) for
stained mouse embryos. Students in the Master 1 Bioinformatics program (UCA) have
contributed to the annotation of nuclei images and the drafting of documentation for biologists
(graduating classes 2023-2024 and 2025).

This work was supported by Agence Nationale de la Recherche of the French government
through the programme 'Investissements d'Avenir' (16-IDEX-0001 CAP 20-25), 'Dynam'Het'
ANR-11 JSV2 009 01 and 'SINUDYN' ANR-12 ISV6 000; Oxford Brookes University,
Université Clermont Auvergne, Centre National de la Recherche Scientifique, Institut National
de la Recherche et de la Santé, the Université Reims Champagne Ardenne, the European
Regional Development Fund (FEDER), EMERGENCE (16-IDEX-0001 CAP 20-25) and the
trainee grants funding GDR IMABIO (France). A.P., C.T., D.E.E., K.G. and S.D. are part of the
International Plant Nucleus Consortium (IPNC; https://radar.brookes.ac.uk) and the European
Cooperation in Science and Technology COST-Action CA16212 (INDEPTH;
https://indepth.brookes.ac.uk/). The authors acknowledge Synchrotron SOLEIL to have
provided beamtime for Figure 2 under project no. 20211303. ANATOMIX is an Equipment of
Excellence (EQUIPEX) funded by the Investments for the Future program of the French
National Research Agency (ANR), project NanoimagesX, grant no. ANR-11-EQPX-0031.

Author contributions

G.M. conceptualized the coding philosophy and undertook most of the programming work and
experiments. D.E.E., F.C., C.T., E.P. and S.D. provided ideas for the project and obtained
funding. S.S. helped debug and improve the user interface. G.M. and S.D. wrote the manuscript
with input from C.T., F.C., D.E.E. and E.P.
G.M. and S.D. performed data analysis and prepared the figures. A.P., H.A., P.P., S.D., S.A. and
N.F. provided annotated images and were beta testers of Biom3d.

Competing interests

747   The authors declare no competing or financial interests.

Supplementary Figure 1 – **Training workflow of Biom3d in the local graphical interface. (*Left*) Training tab of the local graphical interface.** The user specifies the path to the folders containing training images and annotations, then defines a name for the Configuration file and the future trained model, and the auto-configuration can start. Automatically defined parameters can be adjusted manually, if needed, before starting the training. **(*Right*) Backend workflow.** Once the "Auto-configuration" button is pressed, the data-preprocessing starts. The dataset key elements (median shape etc.) are extracted and used to normalize all the images and to define training configuration (patch size etc.). If the "Start" button is pressed, a deep learning model will be trained and saved along with the pre-processing methodology (data-fingerprint).

Supplementary Figure 2 – **Prediction workflow. (*Left*) Prediction tab of the graphical interface.** The user chooses a folder containing raw images, the path to a trained model and a folder for the future predictions. The predictions start when the "Start" button is pressed. **(*Right*) Backend workflow.** The raw images are normalized using the data-fingerprint of the training dataset. The trained model is then loaded and used to compute predictions.

Supplementary Figure 3 – **Remote access and OMERO access to Biom3d.** Remote access

and OMERO access can work together or independently. A combined use case is represented.

The local interface (*left*) allows the access to a remote server remote (*middle*) running Biom3d

training or prediction workflows. If used in combination with an OMERO server (right), the

remote server will download raw images from an OMERO dataset and upload them back in a

new OMERO dataset.

Supplementary Figure 4 – **Auto-configuration and Preprocessing of training dataset for 3D segmentation.** Image and mask folders (*red, left*) are scanned to extract their data-fingerprint. The data-fingerprint is used to preprocess the images and masks and to automatically configure the future training (*yellow, centre*). The outputs of these two steps (*green, right*) are: a CSV file (*folds.csv*) describing which files will be used for training or validation, a Configuration file, the pre-processed images (*images_out*) and masks (*masks_out*), and the location of the foreground voxels (*fg_out*).

Supplementary Figure 5 – **Training data normalization and splitting for 3D segmentation.**
The preprocessing starts (*purple box*, *initialization*) by (1) creating the three output folders
(*fg_out*, *images_out*, *masks_out*), (2) optionally splitting single image/mask and (3) splitting
the dataset into training and validation folds (*folds.csv*). Afterwards, each image and mask
(*blue box*) are read (*Read File*), independently of their format, reshaped (*Reshape*) so to have
exactly 4 dimensions in (*channel, depth, heigh, width*) format, z-normalized for images and
uniformized for masks (*Normalize*), and resized (*Resize*) so all images and masks have the
same sampling. Finally, the locations of foreground voxels are extracted and stored in the
appropriate output folder (*fg_out*).

Supplementary Figure 6 – **Biom3d default Dataset Module for 3D segmentation.** In the

`__init__` class function (*purple*), the CSV file is used to sort training images from validation

images and the patch size is used to determine the parameters of the rotation transformation

(rotation angle and rotation patch size, *yellow*). In the `__getitem__` class function (*blue*), one

image and one mask are loaded into computer memory from their local folder. Those are then

cropped in regions where foreground objects are located. If rotation augmentation is active,

then the foreground crop is performed with a larger patch size before being cropped a second

time to discard unwanted empty regions in the image corners. Another series of

augmentations is finally applied to obtain a ready to use pair of image and mask patches.

Supplementary Figure 7 – **Callback Module principle.** The whole training (top row, orange)

is divided into epochs (green) themselves divided into batches (red). Callbacks are Python

classes that can have one or more class-functions, each representing one of 6 different time

points (middle row). Biom3d currently has 7 types of Callback Modules (bottom row).

812