Protein Set Transformer: A protein-based genome language model to power high diversity viromics

Cody Martin[1,2], Anthony Gitter[3,4,5], and Karthik Anantharaman[1,6, 7,*]

[1] Department of Bacteriology, University of Wisconsin-Madison, Madison, WI, USA
[2] Microbiology Doctoral Training Program, University of Wisconsin-Madison, Madison, WI, USA
[3] Department of Biostatistics and Medical Informatics, University of Wisconsin-Madison, Madison, WI, USA
[4] Morgridge Institute for Research, Madison, WI, USA
[5] Department of Computer Sciences, University of Wisconsin-Madison, Madison, WI, USA
[6] Department of Integrative Biology, University of Wisconsin-Madison, Madison, WI, USA
[7] Department of Data Science and AI, Wadhwani School of Data Science and AI, Indian Institute of Technology Madras, Chennai, TN, India

* Correspondence: karthik@bact.wisc.edu (Karthik Anantharaman)

Keywords: viromics, viral metagenomics, genome language model, protein language model, transformer

Abstract

Exponential increases in microbial and viral genomic data demand transformational advances in scalable, generalizable frameworks for their interpretation. Standard homology-based functional analyses are hindered by the rapid divergence of microbial and especially viral genomes and proteins that significantly decreases the volume of usable data. Here, we present Protein Set Transformer (PST), a protein-based genome language model that models genomes as sets of proteins without considering sparsely available functional labels. Trained on >100k viruses, PST outperformed other homology- and language model-based approaches for relating viral genomes based on shared protein content. Further, PST demonstrated protein structural and functional awareness by clustering capsid-fold-containing proteins with known capsid proteins and uniquely clustering late gene proteins within related viruses. Our data establish PST as a valuable method for diverse viral genomics, ecology, and evolutionary applications. We posit that the PST framework can be a foundation model for microbial genomics when trained on suitable data.

Introduction

Viruses are the most abundant biological entity on the planet and inhabit every ecosystem. Understanding how viruses modulate microbiome community dynamics and functional outputs is an active area of research that spans various scales from global biogeochemistry[1] to human health and disease[2]. Despite the sheer abundance and influence of viruses, comprehensive large-scale viral metagenomics (viromics) studies are severely hindered by the enormous genetic diversity of viruses as most genomics tools rely on sequence similarity to existing reference databases. These problems are compounded by the lack of universal genes in viruses, complicating phylogenetic and comparative analyses across diverse groups of viruses. Overall, these challenges have impeded the development of viromics software that is both accurate and scalable to increasingly diverse viral datasets. Thus, there is a clear need to develop data-driven frameworks to study viruses at-scale using generalizable genomic principles instead of simple sequence homology-based methods.

Protein language models (pLMs) are promising deep learning frameworks for generalizable genomics. Trained on corpuses of millions of proteins[3–5], pLMs have been shown to model amino acids patterns in protein sequences akin to reading words in sentences, capturing biochemical, functional, and structural features of proteins using contextual information of the amino acids within a protein[4,5]. Applications of pLMs to viral datasets have demonstrated increased capacity for protein function annotation[6,7] and host prediction[8]. However, these studies only focused on specific tasks without considering that pLMs could be universally beneficial for a variety of viromics tasks[9], thus missing out on the true potential of foundation pLMs. An additional shortcoming of pLMs themselves is that they do not account for evolution-driven genome organization. Recent work has addressed this issue by contextualizing pLM embeddings across short genomic fragments[10] and even representing the entire genome as an aggregation of the pLM embeddings[8]. However, each of these models only targets one specific kind of representation: the former represents proteins with added genome context, while the latter represents genomes as a weighted sum of protein embeddings subject to a specific classification task. Further, similar work used similar protein-based genome modeling to classify plasmid proteins ontologically[11]. Again, the supervised training of that study causes a lack of generality when considering that other related tasks could benefit from the same contextualization approach. Thus, none of these approaches are truly generalizable to a variety of viromics tasks that require both protein- and genome-level reasoning.

Here, we present Protein Set Transformer (PST), a protein-based genome language model that uses an encoder-decoder paradigm to simultaneously produce both genome-contextualized protein embeddings and genome-level embeddings within a single end-to-end model. We developed several novel algorithmic advances for the PST architecture and implemented more memory-efficient data handling compared to similar methods[8,10,11]. We additionally pretrained foundation PST models on >100k high-quality dereplicated viral genomes encoding >6M proteins using a self-supervised objective. Then, PST was evaluated on two distinct test datasets, one consisting of >150k high-

quality viral genomes encoding >7M proteins from IMG/VR v4[12] and another of >12k viruses encoding >141k proteins detected from soil metagenomes deposited in MGnify[13]. We demonstrate that PST better relates viral genome-genome relationships based on shared protein content and is highly sensitive to remote relationships. Further, we observe that only PST can consistently cluster functionally related proteins like late gene proteins, indicating the importance of genome context-aware training. Additionally, PST protein embeddings are associated with protein structure relationships, as demonstrated by clustering proteins with capsid folds that could not be detected by sequence similarity with annotated capsid proteins. Notably, neither the genome-contextualized PST protein embeddings nor the genome embeddings were learned with respect to any external labels, meaning that they will be useful for a wide range of applications. Due to this flexibility of PST, we propose that our foundation model can be used for transfer learning to model other viral-centric tasks such as viral gene and genome identification, genome quality control, genome binning, taxonomy, and host prediction, which are major components of viromics research[9]. For example, we show that PST substantially improves viral-host prediction compared to existing prediction tools. Thus, we expect that PST will be integral to future viromics studies. Further, we posit that the PST architecture can be a general-purpose model for microbial genomics when trained on microbial instead of, or in addition to, viral genomes.

Results

Developing the Protein Set Transformer genome language model

109
Figure 1. The Protein Set Transformer (PST) architecture and training regime. A) General overview of
the graph-based PST for learning genome representations from contextualized protein embeddings. Each
protein is represented by an ESM2 protein embedding. PST internally represents each genome as a graph,
consisting of multiple subgraphs of fully connected, locally adjacent proteins. The size of each subgraph is
a tuned hyperparameter. PST uses multi-head attention both to contextualize protein embeddings within
each genome and to learn per-protein weights for a weighted averaged over each genome. See
Supplementary Fig. 1 for a modeling-centric view of PST. Both protein and genome representations can
be used for an appropriate downstream task. **B**) Triplet mining workflow that includes the data augmentation
technique **C**) PointSwap sampling. For each training genome, a positive genome is identified from the
ESM2 embedding space defined as the minimum Chamfer distance. Then, a negative, less related, genome
is chosen from the PST embedding space that is the next farther genome after the positive. We augment
our training data by creating hybrid genomes that swap similar protein vectors between each genome and
its positive genome. **D**) Pictorial representation of the triplet loss objective function used to train PST on
viral genomes. The operational objective of triplet loss is to embed each genome and its positive genome
closer in embedding space than each genome and its negative genome, within a tunable distance margin.

PST (**Fig. 1A, Supplementary Fig. 1**) models genomes as sets of proteins using
principles from the natural language processing and set[14] and pointset[15] transformer[16]
fields. We thus refer to PST as a protein-based genome language model, since it
contextualizes protein information at genome-scale. In PST, all proteins from each
genome are embedded using the well-established ESM2 pLM[3,4]. Unlike Set
Transformer[14], PST concatenates small vectors onto the pLM embeddings to model both
the protein genome position and coding strand. This set of updated protein embeddings
from each genome are fed to the PST encoder, which uses multi-head attention[16] to
contextualize the protein representations within each genome (referred to as simply "PST
protein embeddings" afterward). These PST protein embeddings can be used for protein-
level tasks like protein classification and functional annotation. In an end-to-end PST, the
PST protein embeddings are further passed to the PST decoder, which also uses multi-
head attention to weigh the relative importance of each protein in a genome. These
weights are used for a weighted average of the contextualized proteins to produce a
genome representation.

A common training objective for language models that is used by a similar protein-
based genome language model[10] is masked language modeling (MLM)[17], which involves
predicting masked tokens (words) in sentences from the rest of the sentence as a
classification task. In the case of genome sentences composed of protein words
represented as dense vectors, masked language modeling is less intuitive and likely
overcomplicates training. For example, the number of distinct proteins massively
outnumbers the number of unique words in natural languages. These differences in
vocabulary size are exacerbated by the initial representation of proteins as d-dimensional
embeddings, which impedes traditional classification-based objective functions and
requires customized regression objectives to tailor these domain differences to fit MLM[10].

We instead opt to mirror relationship-guided genomics to better understand patterns
of genetic diversity using the triplet loss (TL) function[15,18] (**Fig. 1B, 1D**). During self-
supervised pretraining of the PST foundation model, TL uses the distance in PST
embedding space as a measure of genome-genome relatedness, which are implicitly
conditioned on protein-protein relatedness in PST. Briefly, TL involves the formation of
genome triplets, consisting of one as an anchor, the genome most related to the anchor
as a positive example, and a genome less similar than the positive genome as a negative
example[15,18] (**Fig. 1B, 1D**). Positive examples are defined using the Chamfer distance in
the input embedding space among genomes within a training minibatch. Chamfer
distance is computed as the average minimum of protein-protein embedding distances
for pairs of genomes, meaning that the positive genome has the most similar proteins to
the anchor genome. Meanwhile, negative examples are sampled in the PST embedding
space using a semi-hard negative sampling strategy to select negative genomes that are
closest to but slightly farther than the positive genome. Since PST is trained with a self-
supervised objective, there are no obvious choices of negative examples, so the chosen
negative example is weighted based on the Chamfer distance between the anchor and
negative genomes. This notably reduces the contribution to the loss for negative genomes
that are actually similar to the anchor based on Chamfer distance (see **Methods**). Overall,

the objective of TL is to embed the positive genome closer to the anchor than the negative
within a tunable margin (**Fig. 1D**).
173
To help PST learn more generalizable representations, we used the data
augmentation technique PointSwap[15] (**Fig. 1C**) for each genome and its most related
genome defined by Chamfer distance above (**Fig. 1B**). Each genome pair swaps protein
vectors that are most similar at a defined, tunable rate, analogous to homologous
recombination. We then update the TL objective to include maximizing the similarity
between the anchor genome and its corresponding augmented hybrid genome produced
by PointSwap.
181
We additionally trained an encoder-only PST (**Supplementary Fig. 1**) with a MLM-
style objective to compare the choice of objective for viral genome and protein
representation learning. During training, proteins are masked at a tunable rate in each
genome as targets. In traditional MLM, masked word predictions are scored using a
classification-based objective. Here, however, protein words are represented as dense
vectors in genome sentences, which does not easily allow for simple classification. We,
therefore, adapted a previous approach[10] that uses a mean squared error loss function
to consider the distance between the predicted protein embeddings and the masked
target embeddings. Notably, this also enables a more direct comparison against a
previously published genome language model that is similar to PST[10]. Further, to model
real genetic diversity and the fact that different types of proteins can occur in the same
genomic contexts, we further augment the MLM objective by positively sampling the
nearest protein embedding in ESM2 space to create positive examples. Our MLM
objective, thus, considers the distance between the predicted protein embedding and the
masked targets as well as the distance between the predicted positive protein embedding
and the masked targets. We refer to the full encoder-decoder PST trained with TL as
"PST-TL" and the encoder-only PST trained with MLM as "PST-MLM". However, we note
that references to a generic "PST" indicate a full encoder-decoder PST (i.e. PST-TL),
unless otherwise specified.
201
202   *Tuning PST using two cross validation strategies*
203
To train PST foundation models, we collected 103,589 viruses from 12 different
publicly available sources[1,19–29] as a training dataset (**Supplementary Fig. 2A**). We
evaluated PSTs on two distinct test datasets: 151,255 viruses from IMG/VR v4[12] and
12,857 viruses detected from soil metagenomes deposited in MGnify[13]. The viruses from
each test set were chosen since they were distinct at the nucleotide level (<95% average
nucleotide identity over 85% of either genome) from the training viruses. The MGnify test
viruses were further dereplicated with the IMG/VR v4 test viruses using the same
nucleotide similarity criteria as above. Dereplication at the nucleotide level was sufficient
to reduce train-test genome similarity at the protein level (**Supplementary Fig. 3**). Most
viruses in each set were predicted to encode between 2–100 proteins (**Supplementary
Fig. 2B**) and to be Duplodnaviria, Monodnaviria, or Riboviria (**Supplementary Fig. 2C**).
Additionally, most were from environmental sources not associated with a holobiont

(**Supplementary Fig. 2C**), especially marine systems. Among the viruses with a known
or predictable host, most were bacterial viruses (**Supplementary Fig. 2C**).
218
We tuned eight different PSTs starting with small (6-layer, 8M param) or large (30-
layer, 150M param) ESM2 protein embeddings, respectively, using the TL and MLM
objectives. Four models were tuned using a variant of leave-one-group-out cross
validation (CV), where the group is the viral taxonomic realm. In our variation, the
Duplodnaviria group is always included as a CV training fold since this group composes
a significant fraction of our training set (65.4%, **Supplementary Fig. 2C**). This CV setup
notably helps choose model hyperparameters optimal for all viruses rather than just the
most abundant, since the validation groups never include this substantially large viral
taxonomic realm. These models have a "T" appended to the model name (i.e. PST-TL-
T).
229
The other four models were tuned using CV groups based on protein diversity, such
that there was minimal overlap of shared protein content between these groups
(**Supplementary Fig. 26C**). We considered this alternate approach because viral
taxonomy may not necessarily correlate with the protein diversity and evolution found in
viral genomes. For example, the amount of protein diversity within the Duplodnaviria may
be far greater than other viral realms simply because it is a much larger group, meaning
that these taxonomic groups are not very homogeneous. These models have a "P"
appended to the model name (i.e. PST-TL-P).
238
The best models were chosen based on the lowest loss averaged among all folds at
the end of tuning. Using this strategy, we tuned training-specific (dropout, layer dropout,
learning rate, weight decay, batch size), model-specific (number of attention heads and
encoder layers), PST-specific (chunk size), PointSwap-specific (rate), and TL-specific
(distance margin, scale factor) hyperparameters (**Supplementary Fig. 4–5**). We
additionally tuned a masking rate for PST-MLM (**Supplementary Fig. 5**). For PST-TL-
T__small, fewer attention heads and encoder layers led to optimal performance, while the
reverse is true for PST-TL-T__large, likely reflecting the increased information capacity
of larger pLM embeddings. There were no striking differences between the PST-TL-P
models concerning model complexity. Increasing values of the PointSwap rate generally
led to decreased loss for all PST-TL models. Notably, increasing values of the TL distance
margin led to greater performance for PST-TL-T, while decreasing this resulted in
somewhat better performance for PST-TL-P. For PST-MLM models, there were not many
major trends. However, the lack of global trends even holding objectives and CV
strategies constant highlighted the need for CV hyperparameter tuning.
254
After hyperparameter tuning, we trained a final model for each model size, CV
strategy, and objective using the best hyperparameters (**Supplementary Fig. 6**). The
remaining results are based on these models that we refer to using the following format:
"PST-OBJECTIVE-CV__SIZE", i.e. PST-TL-T__small indicates a full encoder-decoder
PST trained with TL, tuned with the taxonomic CV strategy, and using the ESM__small
protein embeddings as input. The model sizes are both 5.4M for both small PST-TL

models, 21.3–177.9M for large PST-TL models, 23.8–93.0M for small PST-MLM models,
and 93.6–185.8M for large PST-MLM models (**Supplementary Table 11**).
263
264 *PST captures viral genome-genome evolutionary relationships*
265
To evaluate if PST learned biologically meaningful representations of viral genomes,
we compared the genome embeddings produced by PST against other protein- and
nucleotide-based methods with a quantitative clustering assessment on the PST test
datasets. For protein-based methods, we performed an ablation study comparing
unweighted averages of the input ESM2 embeddings and of the PST protein embeddings
over each genome ("PST-CTX" methods). We additionally compared the choice of TL or
MLM training objectives. For nucleotide-based methods, we used 4-mer nucleotide
frequency vectors, GenSLM[30] embeddings, and HyenaDNA[31] embeddings. The latter
methods were chosen for both their availability relative to the course of this study and
their relevance to genome language modeling, as there have been several recently
described nucleotide-based models[32,33]. Notably, both GenSLM and HyenaDNA have
also been referred to as genome language models, so we explicitly refer to these as
nucleotide language models to distinguish them from our protein-based genome
language model. GenSLM was trained to focus on codon-level words in a genome
sentence. Thus, to produce GenSLM genome embeddings, we embedded each
nucleotide open reading frame (ORF) and then averaged these over each genome.
Meanwhile, HyenaDNA is a long-context nucleotide language model that can
contextualize up to 1Mb fragments, which is well above the size of most viral genomes.
Protein-based methods and HyenaDNA appeared to better reflect the evolutionary
relationships among viruses in both the PST training and IMG/VR v4 test datasets in a
qualitative analysis of the genome embeddings in which there are visually distinct clusters
of the four viral taxonomic realms (**Fig. 2A**).
288

289
Figure 2. PST learns biologically meaningful genome representations for diverse sets of viruses. A)
UMAP dimensionality reduction plots for the genome embeddings produced by each method, color coded
by the viral realm. "Kmer" represents 4-mer nucleotide frequency vectors. "PST-CTX-TL" methods are
simple averages of the PST-TL protein embeddings over each genome. **B, C**) Pearson correlation
coefficients between the similarity in embedding space of the corresponding embedding and genome-
genome similarity for the IMG/VR v4 (top) and MGnify (bottom) test datasets. Embedding similarity was
calculated as angular similarity of L2-normalized embeddings. Genome-genome similarity is the harmonic
mean of Average Structural Identity (ASI; see **Methods**) and the proportion of shared genes between each
pair of genomes based on structural information. ASI was only computed between genomes that clustered
together based on the corresponding embedding. Genome pairs were considered **B**) "closely related" if
there were *any* protein sequence alignments between any of the proteins from each genome. Inversely,
genome pairs were considered **C**) "distantly related" if there were *no* protein sequence alignments and only
protein structural alignments between any of the proteins from each genome. The actual scatterplots can
be found in **Supplementary Fig. 8–11**.

To quantitatively evaluate each genome representation, a similarity-weighted *k*-
nearest neighbor (*k*NN) graph was constructed from each of the genome embeddings
from each test dataset with 15 neighbors and then clustered using the Leiden algorithm[34]
with a similarity threshold of 0.9. This led to 20-30k clusters for the IMG/VR v4 test set
(**Supplementary Fig. 7A**) and 1.5-2.5k clusters for the MGnify test set (**Supplementary
Fig. 7B**). For both datasets, the average cluster size ranged from 4-8 genomes depending
on the genome embedding (**Supplementary Fig. 7**). Notably, this led to ≥75% of all viral
genomes in each dataset being clustered with at least 1 other genome (**Supplementary
Fig. 7**).

For pairs of genomes in each genome cluster, we computed the average amino acid
identity (AAI) and average structural identity (ASI; see **Methods**). Since AAI is based on
protein sequence alignments and ASI is based on protein structure alignments, these two
metrics allow us to distinguish between genomes that are closely related and remotely
related. This is because AAI relies on protein sequence alignments, which are not as
sensitive as structural alignments. Likewise, genomes where AAI cannot be detected but
ASI can be detected are considered distantly related, since there are protein structure
alignments but no protein sequence alignments.

We then plotted a score aggregating ASI with the proportion of shared protein
structures against the embedding angular similarity (**Supplementary Fig. 8–11**) and
computed the Pearson correlation coefficient for each genome embedding and set of
closely and distantly related genomes (**Fig. 2BC**). Only PST-TL methods, regardless of
CV strategy or test dataset, displayed a positive correlation for both closely and distantly
related genomes (**Fig. 2BC**, **Supplementary Fig. 8–11**). Notably, PST-TL were also the
only embeddings to show an increased correlation for the distantly related genomes
compared to the similar genomes. This highlights the greater sensitivity in detecting
genome-genome relationships for PST-TL models, especially for remote relationships.
Inversely, kmer and HyenaDNA showed a positive correlation only for closely related
genomes (**Fig. 2B**, **Supplementary Fig. 8**, **Supplementary Fig. 10**), which likely reflects
the limited search range of nucleotide-based methods. This is further supported by the
sharp decrease in correlation for these two methods when evaluating the distant genomes
(**Fig. 2C**, **Supplementary Fig. 9**, **Supplementary Fig. 11**). Interestingly, all other protein-
based genome embeddings showed a negative correlation between the embedding
similarity and ASI score, suggesting that these genome embeddings do not accurately
capture genome-genome relationships (**Fig. 2BC**, **Supplementary Fig. 8–11**). PST-CTX-
TL genome embeddings, which are simple averages of PST protein embeddings
compared to the learned weighted averages of PST-TL genomes embeddings, showed
slightly less negative correlations but still performed poorly. Additionally, there was
potentially representation collapse in the genome embeddings from PST-MLM models,
most notably for PST-MLM-T, since there was little variation in embedding similarity
(**Supplementary Fig. 8–11**). This arises even though PST-MLM models are not directly
trained to produce genome embeddings (see **Methods**), unlike PST-TL models. Overall,
these analyses suggest that full encoder-decoder PSTs are superior for genome
representation learning.

We also evaluated the taxonomic purity of both the viruses and their hosts across the
genome clusters, which did not strongly separate any method for either test dataset
(**Supplementary Fig. 12–13**). This may suggest that current viral taxonomy is not as
informative for understanding viral-viral relationships across diverse sets of viruses
compared to AAI and ASI, which are based on information more intrinsic to viral genomes.
Further, the proportion of viruses with a known or predicted host is low (**Supplementary
Fig. 2C**), which may also skew this analysis.

PST detects important viral protein functions

PST genome representations are produced as a function of the input protein
embeddings that get contextualized by the intermediate PST encoder. Thus, we expected
that biologically meaningful genome embeddings should be generated from meaningful
protein representations. We first analyzed the attention scores of each protein per
genome from the large PST-TL models, which are used as importance scores when
pooling the PST protein embeddings for the final genome representation. We considered
that the general function of each protein was likely associated with high attention. Indeed,
structural proteins (head, packaging, tail) and replication or nucleotide metabolism
proteins were generally most attended to by the model, regardless of PST model or
annotation database (**Fig. 3A**, **Supplementary Fig. 14**). This is intuitive since these
proteins are essential to viruses and likely reflects their relatively greater abundance in
the dataset (**Supplementary Fig. 15**). Further, we found a subtle association between
the attention scores with the number of proteins belonging to the same sequence identity-
based cluster (**Supplementary Fig. 16**). This reflects the model assigning a higher weight
to proteins seen more frequently.

377
Figure 3. PST leverages genomic context to learn protein function relationships. A) Relative scaled
attention from large PST-TL models for proteins belonging to different PHROG functional categories for
IMG/VR v4 (top) and MGnify (bottom) test datasets. The per-protein attention scores from each model were

normalized by the number of proteins encoded per scaffold (see Methods). For each model, these
normalized attention values were then rescaled so that the maximum value was 1. Then the top 1,000
proteins based on the rescaled normalized attention were chosen for each functional category. The bar
height represents the mean of those attention values, and the bars indicate ±1 standard deviation. **B**)
Summary of functional co-clustering based on PHROG annotations of the IMG/VR v4 test set. Each
connected component was clustered in a co-occurrence graph using the Leiden algorithm with resolution
of 1.25. The edges indicate pairs of functional categories that were more enriched in protein clusters defined
by clustering the *k*-nearest neighbor graph of the corresponding protein/ORF embeddings relative to the
background distribution of annotation profiles. The length of the edges reflects the degree of enrichment
since the networks were visualized using a spring force algorithm. Dotted gray lines indicate connections
that were less enriched than or equal to expected, while solid lines were more enriched than expected. **C–**
F) The proportion of protein clusters that correspond to Late Gene (top, **C, D**) or DNA-interacting (bottom,
E, F) modules for the IMG/VR v4 (left, **C, E**) and MGnify (right, **D, F**) test datasets. A protein cluster was
considered to represent a functional module if all proteins annotated by PHROG in the cluster belonged to
the subcategories that composed each module (Late Genes: Head and Packaging, Tail, Connector, Lysis;
DNA-interacting: Nucleotide Metabolism, Lysogeny, Gene Expression). Each protein cluster was also
required to have annotated proteins belonging to at least 2 of the subcategories. The dashed lines mark
the method that has the greatest proportion of protein clusters corresponding to the indicated functional
module.

To quantitatively assess the ability of PST to detect protein relationships, we
conducted a similar analysis as with the genome clusters. The embedding-based protein
clusters were generated using the Leiden algorithm on a similarity-weighted *k*NN graph
with 15 neighbors and a similarity threshold of 0.9. This approach led to 1.5-2M protein
clusters for the IMG/VR v4 test set and 20-35k protein clusters for the MGnify test set with
average cluster sizes ranging from 2-6 proteins (**Supplementary Fig. 17**). For each
dataset, ≥75% of proteins were clustered (**Supplementary Fig. 17**). We then performed
a similar purity analysis of the protein clusters with respect to VOG and PHROG functional
categories that did not strongly indicate which protein embeddings produced the most
functionally pure protein clusters (**Supplementary Fig. 18**), although PST-TL-T__small,
PST-TL-P__small, PST-TL-P__large, and GenSLM were consistently the best. The PST-
MLM models tended to perform on par with ESM2 for this task.

PST clusters related protein functions into function modules

To identify cases where PST outperforms the input ESM2 for protein tasks, we
considered that genome context could impart a greater sensitivity for detecting evolution-
driven genome organization. More specifically, we suspected that PST would be capable
of identifying groups of associated protein functions that reflect this underlying genome
organization. For example, the late genes encoding for structural, packaging, and lysis
proteins are adjacent and transcribed by a single promoter in the Lambda genome[35]. We,
therefore, assessed protein function co-clustering patterns. For each protein cluster, we
calculated the number of times pairs of proteins belonging to different PHROG functional
categories co-clustered against the number of times each pair of categories would be
expected to co-cluster based on the underlying distribution of the PHROG database
categories. The resulting enrichment networks showed that PST-TL could group proteins
based on broader function modules in the IMG/VR v4 test set (**Fig. 3B**, **Supplementary
Fig. 19**). For example, tail, head and packaging, connector, and lysis proteins, which are
notably late gene proteins, consistently co-clustered above background in PST-TL protein
clusters. Additionally, DNA-interacting (nucleotide metabolism, lysogeny, and gene

expression) function modules were enriched in PST-TL-P and GenSLM protein clusters.
Interestingly, using ESM2 protein embeddings to cluster the proteins did not lead to
interpretable functional modules emerging (**Fig. 3B**, **Supplementary Fig. 19**). Moreover,
only PST-MLM-T__large detected the late gene and DNA-interacting modules. Since all
PST-TL models and only one PST-MLM model were able to detect these modules, this
suggests that the capacity to identify functional modules is specific to PST-TL and not
PST-MLM. Notably, these functional modules were not detected by any method in the
MGnify test set (**Supplementary Fig. 20**). This could be due to the ~20x reduction in the
total number of annotated proteins in the MGnify set relative to the IMG/VR v4 set that
prevent accurately identifying these co-clustering relationships. However, this could also
reflect evolutionary differences of soil viruses compared to viruses from other
ecosystems.

These results were also consistent with the proportion of protein clusters from the
IMG/VR v4 test set that we considered as belonging to these function modules, as PST-
TL showed the highest proportions (**Fig. 3CE**, **Supplementary Fig. 21**). For late genes
and when using VOG annotations, there were not significant differences between the
protein embeddings with the MGnify test set (**Fig. 3D**, **Supplementary Fig. 21**). However,
PST-TL showed a higher proportion of DNA-interacting clusters (**Fig. 3F**), despite this
module not being detected in the co-clustering networks (**Supplementary Fig. 20**). This
difference is likely because this approach only considered "pure" clusters that represent
these functional modules, while the previous strategy quantified all clusters without
considering an overall cluster summary. Nonetheless, these data demonstrate that
considering genome context better enables PST to detect broader functional associations
implicitly encoded in viral genome organization.

PST expands annotation for proteins of unknown function

Interestingly, hypothetical proteins unable to be annotated by either the VOG or
PHROG databases were generally considered the most important by PST-TL models
(**Fig. 3A**). One explanation is that since proteins of unknown function make up 70-90% of
all proteins in the PST test datasets (**Supplementary Fig. 15**, **Supplementary Table 2**),
it is likely that there are true viral hallmark structural and replication proteins that have
diverged at the sequence level among the unannotated proteins. Since PST-TL
embeddings showed positive correlation with a structure-based genome-genome
similarity metric (**Fig. 2BC**, **Supplementary Fig. 8–11**), we investigated if PST could be
used to identify structural similarity more directly. To test this, we selected unannotated
proteins that cluster with detectable capsid proteins to check if these unannotated
proteins contained conserved capsid-like structural folds that were missed by sequence
similarity searches. We filtered the proteins from the test viruses to maintain proteins
belonging to protein clusters that contained only annotated capsid proteins or hypothetical
proteins. We then used foldseek[36] and ProstT5[37] to translate this protein set into a
structural alphabet for searching against Protein Data Bank[38] structures for structural
homology. To validate the structural reasoning of this approach that does not directly infer
a protein structure, we independently aligned the structures of the reference HK97 major
capsid protein[39] with two different AlphaFold 3-predicted[40] structures using the most

structurally similar proteins from our dataset: one that was detected by a VOG profile with
unknown function (**Fig. 4A**) and one undetected entirely (**Fig. 4B**). The strong alignments
indicate that our workflow can accurately identify capsid-fold-containing proteins from the
protein sequence alone. Using this approach, the PST-TL models generally showed the
greatest proportion of unannotated proteins with structural homology to known capsid
proteins, regardless of CV strategy (**Fig. 4CD**). GenSLM ORF embeddings were also
better than other protein embeddings for this task, likely due to being pretrained on
microbial genomes, which would contain some viral sequences, and finetuned on SARS-
CoV-2 genomes. The proportion of unannotated proteins clustering with capsid proteins
was consistently the lowest with ESM2, PST-MLM, and, surprisingly, PST-TL-T__large
protein embeddings.
488

A Annotated unknown by VOG

TM-score: 0.95
rmsd: 1.6

B Undetected by VOG

TM-score: 0.69
rmsd: 3.49

Identifying capsid proteins based on structure

C IMG/VR v4

D MGnify

Protein/ORF Embedding

Embedding Type:
Protein
Nucleotide

E Embedding-based Annotation Transfer

Any labeled | All have same function

Protein/ORF Embedding
ESM__large
ESM__small
PST-MLM-P__large
PST-MLM-P__small
PST-MLM-T__large
PST-MLM-T__small
PST-TL-P__large
PST-TL-P__small
PST-TL-T__large
PST-TL-T__small
genslm

Model

Embedding Type:
Protein
Nucleotide

Number of nearest neighbors

489
Figure 4. PST expands functional annotation of hypothetical proteins. A, B) Structural alignments with
the HK97 major capsid protein (PDB: 2FS3, gray) for a protein annotated by VOG as unknown (**A**,
"IMGVR_UViG_3300038749_000016|3300038749|Ga0423190_00012|260998-304157_27") and another

undetected by VOG (**B**, "IMGVR_UViG_2687453601_000002|2687453601|2687454426|1161639-
1205965_50"). The red cartoon diagrams are the query proteins from our dataset and were chosen due to
being the most similar to the HK97 capsid protein from each category. **C, D**) The proportion of proteins from
the **C**) IMG/VR v4 and **D**) MGnify (right) test datasets unannotated by VOG clustering with annotated capsid
proteins that have detectable structural homology with known capsid folds. Structural homology was
detected using foldseek searching against the Protein Data Bank database. **E**) The proportion of proteins
unannotated by VOG whose nearest neighbors in embedding space are annotated. The colors indicate the
protein/ORF embedding. Nearest neighbors were searched using angular similarity after L2-normalizing
the protein embeddings. *Left*: A hit was considered for each unannotated protein if any of the neighbors
less than or equal to the current number of nearest neighbors were annotated. *Right*: A hit was considered
similarly to the left side with the additional constraint that all of the current set of nearest neighbors must
belong to the same VOG functional category. Unannotated proteins were not used to penalize the score.
505
We next considered that similarity in embedding space could be used to propagate
functional labels from annotated to unannotated proteins. To evaluate the annotation
transfer ability of PST, we checked if any of the nearest neighbors in embedding space
were annotated (**Fig. 4E** left). We then further constrained this search to require all
neighbors belong to the same VOG functional category as an additional source of
confidence for annotation transfer (**Fig. 4E** right). These results showed little difference
for most methods, except for GenSLM, PST-TL-P__small, and PST-TL-T__small
consistently being the worst. It is possible that the smaller embedding sizes for PST-TL-
P__small and PST-TL-T__small may have decreased the performance since the larger
models perform better. Notably, as additional neighbors are searched, the improvement
proportion for all protein-based methods tended to decrease after >6 neighbors were
evaluated and required to have the same functional category (**Supplementary Fig. 22**
right). Meanwhile, GenSLM showed plateauing improvement when requiring congruent
functions among the nearest neighbors (**Supplementary Fig. 22**). This is consistent with
nucleotide sequences having a lower evolutionary range compared to protein sequences
and structures, as GenSLM ORF embeddings could not generally identify any additional
annotated proteins (**Supplementary Fig. 22**). Further, we already demonstrated that
broader functional relationships can be detected by PST-TL protein embeddings, which
explains why protein-based representations would decrease in performance as more
neighbors are considered. This, however, may indicate an initial grasp of both specific
and broad protein function that could be tuned for different downstream tasks. Overall,
these results indicate that protein embeddings could be better for annotation transfer.
528
529 *PST can be applied toward viral-host prediction*
530

Figure 5. PST improves host prediction. A) Graph neural network approach for host prediction developed by CHERRY. The node representations are swapped out to the corresponding data type. **B**) The proportion of iPHoP test viruses whose true host species is predicted above the indicated confidence threshold. None of the 1636 iPHoP test viruses were filtered for similarity to those in the PST training set. The graph-based models were trained in this study, while "iPHoP" represents the output of running the iPHoP tool on the same test set. All PST and ESM models use the "large" versions for genome embeddings. PST-MLM-T did not have any predictions above the indicated confidence thresholds.

Since we expect that PST can be used as a general-purpose model for downstream viromics tasks, we used the large PST genome embeddings for viral-host prediction as a proof-of-concept. We adopted and modified a graph framework described previously[41] that models this scenario as a link prediction task in a virus-host interaction network. Briefly, the objective is to predict for any pair of virus and host whether there should be a link, indicating a prediction for infection of that host by the corresponding virus (**Fig. 5A**). This task can be performed by a Graph Neural Network (GNN), which uses a form of convolutions to aggregate local (more related) parts of the graph to improve link prediction.

We implemented a variant of the GNN-based CHERRY algorithm[41] (**Fig. 5A**), swapping out the node (genome) embeddings of both viruses and hosts with either ESM2, various PSTs, or the tetranucleotide frequency (kmer) vectors that CHERRY uses. Although this design is likely suboptimal for PST models, which have embeddings

specialized for viruses but not hosts, it enables a direct comparison of the choice of
genome embedding instead of various virus-host genome embedding combinations. We
then trained these models using the training dataset of the host prediction tool iPHoP[42] to
compare with previously published work (**Supplementary Fig. 23**). Then, each trained
model and iPHoP were evaluated using the same iPHoP test dataset. We assessed
whether the true host species for each test virus could be identified with high confidence
(**Fig. 5B**). The model using PST-TL-T genome embeddings significantly outperformed all
other methods at the host species level, even previously published tools (**Fig. 5B**).
Notably, PST-TL-P did not perform as well as PST-TL-T, despite generally performing as
well as or equal to PST-TL-T in previous tasks. Conversely, PST-MLM-P outperformed
PST-TL-P moderately at the highest confidence threshold and substantially at the lower
threshold (**Fig. 5B**), which is surprising since PST-MLM-P has not performed well in the
prior evaluations. This could be explained by PST-MLM-P and PST-TL-T having 10x more
trainable parameters compared to PST-TL-P (**Supplementary Table 11**). PST-MLM-T, in
contrast, did not make any correct predictions that met the confidence requirements and
has 50% fewer parameters. Another potential source of bias that could skew the results
generally in favor of PST embeddings is that there are viruses in the iPHoP test set that
are similar to those in the PST training set (**Supplementary Fig. 24A**). However,
excluding these viruses did not change the overall results (**Supplementary Fig. 25**).

Discussion

Here, we present the PST framework for modeling genomes as sets of proteins, where
each protein is initially represented by information-rich ESM2 protein embeddings. PST
contextualizes the input protein embeddings and subsequently yields genome
representations as weighted averages of contextualized protein embeddings, which can
be targeted toward either protein-level or genome-level downstream tasks. When
pretrained on a large, diverse dataset of viral genomes, PST-TL demonstrated superior
ability in understanding evolutionary relationships among viral genomes (**Fig. 2BC**).
Notably, encoder-only PSTs like PST-MLM and PST-CTX-TL did not show any correlation
between genome embedding similarity and ASI (**Fig. 2BC**). This suggests that a trainable
decoder that learns a weighted average of protein embeddings is required for optimal
genome representation. Further, our PST-MLM models were trained in a similar way to a
previous genome language model[10]. The poor performance of PST-MLM models in both
genome and protein tasks indicates that MLM is possibly not the best training regime for
genome language modeling, especially for highly diverse genomes like viral genomes.

At the protein level, the PST-TL protein embeddings demonstrated patterns of broad
function grouping, consistently clustering late gene proteins together (**Fig. 3B–F**).
Additionally, PST-TL often clustered capsid-fold-containing proteins that could not be
annotated by VOG with annotated capsid proteins (**Fig. 4CD**). This suggested, alongside
a positive correlation between embedding similarity and protein structure-based genome-
genome similarity (**Fig. 2BC**, **Supplementary Fig. 8–11**), that PST-TL uses inferred
structural information for relating proteins and, subsequently, genomes. PST-TL further
showed high sensitivity for annotation transfer (**Fig. 4E**). Performance for these protein-
level tasks could be further improved by finetuning the ESM2 pLM with viral sequences

and by training a PST with a dual objective that more directly considers protein-protein
and genome-genome relationships. The performance of PST-TL-P__large, specifically,
across these tasks is notable since this model has ~10% the number of parameters
compared to the other large PST models (**Supplementary 11**).
604
Finally, when applied toward a viral host prediction task, the PST-TL-T genome
embeddings were able to detect the true host species for the greatest number of viruses
when compared against two previously published host prediction tools (**Fig. 5B**). We
notably refrained from overanalyzing the subtle differences in performance in the proof-
of-concept host prediction task since there are numerous training techniques beyond the
scope of our work that could have resulted in a superior PST-based host prediction model.
For example, the PST genome embeddings are likely not well-suited for host genome
representation. It is, therefore, important to emphasize that the PST-based host prediction
model performed on par with (and sometimes better than) existing host prediction tools
without PST being initially tasked with host prediction and without significant training time.
615

Figure 6. PST can be a general-purpose microbial and viral genome language model. A) Potential downstream tasks of the pretrained PST that represent commonly desired steps of a typical computational viromics pipeline. **B**) Example workflow of a genome language model based on PST that could incorporate both microbial and viral input genome datasets.

It is imperative to reiterate that this superior performance in a variety of viromics tasks emerged despite not training PST with these objectives. Taken together, our results indicate that PST is suitable as a foundation model for common viromics tasks, such as virus identification, taxonomy, host prediction, protein annotation, genome binning, etc. (**Fig. 6A**). We anticipate that more thorough studies for downstream viromics problems will benefit from starting from our pretrained PST models. Additionally, finetuning PST can bring even greater performance for these downstream tasks. For example, finetuning an end-to-end host prediction model with a virus-host dataset would likely significantly improve predictive power compared to what we observed. Further, the iPHoP training dataset has limited diversity (**Supplementary Fig. 24B**), which could suggest that the results here are not representative of true performance on less represented viruses. Nonetheless, our work has provided a preliminary framework for a standalone PST-based host prediction tool.

There has been increasing discussion around the biosecurity risks posed by biological foundation models due to potential biosecurity threats such as generating novel pathogenic viruses or guiding gain-of-function viral mutations[43,44]. For example, the AlphaFold 3 web server does not allow predictions for certain viral proteins[40], Evo excluded viruses with eukaryotic hosts from its pretraining data[45], and ESM3-open filtered viral sequences and select agents from its training sets[46]. While developing PST, we have assessed the ethical implications of this viral foundation model and perceived it to have a low biosecurity risk, in particular with respect to human pandemics. First, only 0.2% of the PST training viruses infect humans. Of these, only 4 are on the CDC's list of bioterrorism agents (https://emergency.cdc.gov/agent/agentlist-category.asp; Filoviridae viruses: Ebolavirus and Marburgvirus), and 10 more are under surveillance by the National Respiratory and Enteric Virus Surveillance System (https://www.cdc.gov/nrevss/php/dashboard). Further, only 1% of the training viruses infect mammals, which would be the most likely viral reservoirs that could spillover into human populations. Since our model was not trained considering host identity, the low abundance of these viruses in the training dataset likely minimizes their influence on the learned PST embeddings. Second, the lowest resolution of PST is at the protein level, meaning that it would be difficult to reverse engineer a *de novo* viral genome using PST. While a nucleotide language model reported the ability to generate *de novo* bacterial virus genomes[33], the similarity of these genomes to the training dataset was not investigated. One pitfall is that the model could have been generating trivially *de novo* genomes that do not differ substantially from the training data. Reverse engineering genomes from our protein-based work is further complicated by the complexities of how human viruses tend to encode and express genes (overlaps, alternative starts, alternative splicing, post-translational processing, etc.). These molecular biology issues likely mean that achieving *in vivo* activity of a generated viral genome would be challenging as previously discussed[47].

We additionally consulted with three experts in biological machine learning and data
science to assess the potential biosecurity risk of our work before releasing the PST code
and model weights. There was unanimous agreement that PST offered potential benefits
for virology and other biological fields, leading to full support for publicly releasing the
source code and trained models. Two reviewers did not perceive a relatively greater threat
by PST compared to the ESM2 model used as input. The other had no general concerns
but acknowledged that there could be unforeseen issues. Therefore, the external
evaluation is consistent with our internal assessment that the demonstrated and potential
future benefits (**Fig. 6A**) of our work to advance our understanding of viruses outweigh
any hypothetical threats that would require significant resources to unleash.
674
Finally, our PST architecture, while trained on viral proteins and genomes for this
study, is agnostic to the source of the proteins and type of genomes. The only
requirements of our framework are the ordered protein sequences and genome strand of
each ORF. These requirements are more easily satisfied by microbial genomes, where
computational ORF calling is both accurate and common. However, PST could
theoretically work with large enough datasets of experimentally determined ORFs from
eukaryotes as well. Nonetheless, we propose that our PST implementation is equally
appropriate for developing a microbial foundation model to solve similar challenges in
microbial genomics (**Fig. 6B**), which notably also include poor protein annotation rates
and high sequence divergence. In fact, our foundation PST-TL-T model was still useful
for host genome representations in the virus-host prediction task (**Fig. 5**), despite only
being trained on viruses.

Data Availability
Sources for publicly available viral genomes are listed in Supplementary Table 1. Supplementary data specific to this manuscript, including protein FASTA files, protein and genome embeddings, trained PST model weights, and virus-host interaction graphs, were deposited at DRYAD: (doi: 10.5061/dryad.d7wm37q8w). Data can be downloaded via the DRYAD web interface, and we have also provided command line access to download files with instructions in the PST GitHub repository.

Code Availability
All code for the PST model architecture and analyses specific to this manuscript is available at: https://github.com/AnantharamanLab/protein_set_transformer. Specifically for manuscript-associated analyses, Jupyter notebooks are provided for each method section that uses code. We provided additional repositories for generating the ESM2 protein embeddings, GenSLM ORF and genome embeddings, and HyenaDNA genome embeddings that can be found in the main model repository above.

Author contributions
All authors (CM, AG, KA) conceived the project. CM conducted model and software development, all analyses, results visualization, and content organization. AG and KA provided project feedback. CM and KA wrote the manuscript draft. All authors (CM, AG, KA) reviewed the results and edited and approved the manuscript.

Acknowledgements
This research was supported by a National Institute of General Medical Sciences of the National Institutes of Health award (R35GM143024) and by a National Science Foundation award (2226451). CM was supported by a National Science Foundation Graduate Research Fellowship and a University of Wisconsin-Madison SciMed GRS Fellowship. AG acknowledges support from Jeanne M. Rowe. We thank members of the Anantharaman lab for project discussion and feedback on the manuscript. Model training and inference was performed using the resources and assistance of the University of Wisconsin-Madison Center for High Throughput Computing[48]. We thank Drs. Yunha Hwang, Jeffrey Ruffolo, and Mark Craven, experts in biological machine learning and data science, for their assessment of potential biosecurity risks of this study.

Competing interests
The authors declare no competing interests.

Methods

Viral genome datasets

We acquired viral genomes from 12 different publicly available sources[1,19–29] as a training dataset. For GTDB (r202), we used PhageBoost[49] (v0.1.7) with default settings to identify integrated proviruses, filtering predictions that did not encode at least 20 proteins. We then filtered genomes that were not considered complete or high-quality as defined by CheckV[50] (v1.0.1). We then dereplicated this set of genomes using a custom workflow. We first used skani[51] (v0.1.0 sketch: --fast) to compute pairwise average nucleotide identity (ANI) between all pairs of viruses. We constructed a graph where edges connected viruses with ≥95% ANI and ≥50% genome coverage of the alignment for both genomes. The edge weights were the product of ANI and coverage. We then used the Markov clustering algorithm[52] (mcl v14-137 -I 2.0) to cluster this graph, taking one genome from each cluster at random as a representative genome. This resulted in 103,589 viral genomes for training.

We then chose the most complete, least contaminated, and longest genome for each viral operational taxonomic unit in IMG/VR v4[12], ensuring that each representative was considered high-quality by CheckV, as one test dataset. We then dereplicated this putative test dataset with the training dataset using a similar approach as above with skani (--slow, ≥95% ANI, ≥85% coverage) and mcl. We kept all viruses that did not cluster with training viruses. For both datasets, we filtered out viruses predicted to encode only 1 protein. This resulted in 151,255 genomes spanning 182,906 scaffolds.

We curated a second test dataset composed solely of soil viruses, which are significantly less represented in the IMG/VR v4 test dataset (15.3% compared to 49.7% aquatic viruses), identified from soil metagenomes deposited in MGnify[13]. We downloaded 145 soil metagenomes with assemblies available up to January 10, 2025, filtered for contigs ≥2.5kb in length, and used geNomad[53] (v1.7.4) to identify viral scaffolds from the assemblies. This resulted in an initial set of 17,802 viruses. Then, we dereplicated these viruses using the same skani-mcl workflow with both the training and IMG/VR v4 test datasets. This led to a final total of 12,857 MGnify test viruses.

For all viruses, we predicted protein open reading frames (ORFs) using the Python bindings of prodigal called pyrodigal[54] (v2.3.0) for single-contig viruses and prodigal-gv (v2.11.0) for viral metagenome-assembled genomes (vMAGs). We did not consider the updates made by prodigal-gv[53] (added gene models for giant viruses and viruses using alternative genetic codes) to be substantial enough to apply to the entire dataset given the scale and distribution of the data. With these protein predictions, we filtered out viruses predicted to encode only 1 protein (the final number of genomes listed above reflects this final filtering step). The total number of proteins encoded in each dataset were 6,391,562 for the training dataset, 7,182,220 for the IMG/VR v4 test dataset, and 141,643 for the MGnify test dataset.

For the training viruses and MGnify test viruses, viral taxonomy not provided by
IMG/VR v3 was assigned using geNomad[53] (v1.7.2) to get labels that were consistent
with the current standards. For the IMG/VR v4 test viruses, we used the provided
taxonomic labels since they were consistent with current standards, and most were
predicted using geNomad also. We did not perform host prediction on the training or
IMG/VR v4 viruses, since that was already provided by the viral-centric source databases.
For the MGnify test viruses, however, we used iPHoP (v1.3.3) to predict hosts, since we
detected these viruses in this study. The summary of information for the training and test
viruses can be found in **Supplementary Table 1**.
777
778   **ESM2 protein language model embeddings**
779
PyTorch (v2.1.0)[55] and fair-esm[3] (v2.0.0) were used to obtain protein embeddings. We
refer to the ESM2 models "esm2_t6_8M_UR50D" (6 layers, 8M parameters, 320-
dimensional embedding) and "esm2_t30_150M_UR50D" (30 layers, 150M parameters,
640-dimensional embedding) as "ESM__small" and "ESM__large", respectively. The
amino acid embeddings in each protein were averaged for a single d-dimensional vector.
For proteins longer than 20,000 amino acids, the sequence was split in half, and the
embeddings for each half were then averaged for the final embedding. This only affected
1 bacterial protein in the host prediction analysis.
788
Generating the fixed ESM2 embeddings is the most computationally expensive step
for the entire PST model, but this only needs to be done once. The approximate inference
rate across each dataset used here was 614.28 proteins/second for ESM__small and
130.80 proteins/second for ESM__large using 1 A100 GPU. This led to the following
inference times for ESM__small (training set: 2.89h, IMG/VR v4 test set: 3.25h, and
MGnify test set: 3.84 min) and for ESM__large (training set: 13.57h, IMG/VR v4 test set:
15.25h, and MGnify test set: 18.05 min). Notably, this step can scaled up to the number
of available GPUs since the ESM2 embeddings are independent for each protein,
meaning that input files can be split evenly and assigned to each GPU for parallelized
inference.
799
800   **Protein Set Transformer model architecture**
801
Protein Set Transformer (PST) was built using PyTorch (v2.0.0), PyTorch Geometric[56]
(v2.3.1), and PyTorch-Lightning (v2.0.7). PST draws inspiration from deep learning of set-
structured data like the Set Transformer[14] while using modifications that are specific to
pointsets[15], which are sets whose items are d-dimensional vectors. PST, thus, models
genomes as a set of proteins G_i where $g_{ij} \in G_i$ is the jth protein in the ith genome. Each
protein is initially represented by its d-dimensional ESM2 protein embedding, with $G_i \in$
$R^{n_i \times d}$ where n_i is the number of proteins encoded in genome G_i. We did not finetune the
ESM2 models, so the ESM2 embeddings were used as frozen inputs. For each protein
g_{ij}, learnable embeddings for both the position in the genome and for the encoding strand
were concatenated to the ESM2 embeddings. The positional embeddings for proteins
were relative to the positions of the proteins in each genome and are used so the model
learns relative ordering of proteins. For fragmented genomes such as viral metagenome-

assembled genomes (vMAGs), the protein ordering was only done relative to each
scaffold instead of the entire set of scaffolds that compose a fragmented genome.
816
To account for the large variation in the number of proteins encoded by each genome,
we used a memory-efficient graph-based implementation that considers each genome as
a graph and each protein as nodes in the genome graph. Notably, each individual genome
matrix G_i is stacked for each minibatch, so there is no padding. Then, an indexing pointer
keeps track of the offsets (number of rows/proteins) for each genome for efficient access.
For memory efficiency and to model real fragmented genomic data, we break each
genome graph into subgraphs whose node sets include 15-50 mutually exclusive,
contiguously located proteins. The size of each subgraph was tuned and is, thus, fixed.
These nodes are all fully connected in each subgraph such that all proteins in each
genome subgraph attend to each other in the PST encoder. We prevent subgraphs with
1 node by adding possible singleton node cases to the previous subgraph. The subgraph
size ("chunk size") hyperparameter is constant for all genomes. Thus, a minibatch of N
genomes is represented by a single graph $\mathcal{G} = (X, E) = \text{Stack}(G_i)$ where X is the total
number of proteins encoded by the N genomes. E is the total number of protein-protein
edges and is a function of the subgraph size and number of proteins per genome.
832
PST uses an encoder-decoder paradigm previously described with the Set
Transformer[14]. The encoder uses multi-head self-attention to contextualize each protein
by the other proteins within the same scaffold (i.e. a single contiguous nucleotide
sequence). Then, the decoder uses multi-head attention pooling to summarize the
genome as a weighted average of contextualized protein embeddings. To contextualize
the proteins in each genome, we used a graph-based implementation of multi-head
scaled-dot product self-attention[16] in each layer of the PST encoder:

$$\alpha_{ij} = \text{GraphSoftmax}\left(\frac{(W^Q x_i)(W^K x_j)}{\sqrt{d}}\right)$$

$$\text{MultiHeadAttn}(\mathcal{G}) : x_i^{(l+1)} = W^{Q,(l)} x_i^{(l)} + \sum_{j \in \mathcal{N}(i) \cup \{i\}} \alpha_{ij}^{(l)} W^{V,(l)} x_j^{(l)}$$

where $x_i^{(l)}$ is the embedding vector for the ith protein at the lth encoder layer, d is the
protein embedding dimension. Likewise, $W^{\cdot,(l)}$ is the weight matrix for the query, key, and
value at the lth encoder layer. $\mathcal{N}(i)$ is the set of protein neighbors for the ith protein in
the same genome subgraph. A_{ij} is the scaled-dot product attention calculation.
GraphSoftmax is a modified softmax function that only normalizes the attention values
within the set of subgraphs that belong to the same genome. Thus, only proteins in the
same subgraph attend to each other, but the attention values are normalized by all
proteins in the genome. To enable multi-head attention, we split the input protein
embeddings in the same number of chunks as the number of attention heads along the
embedding dimension. After the self-attention calculation, we concatenate the outputs
from each head back together. Further, we followed a pre-normalization strategy in which
we normalized the input protein embeddings before the linear layers. Specifically, we
used the GraphNorm (implemented in PyTorch-Geometric) normalization operator that
normalizes the protein embeddings only within each genome. Additionally, we used the

corresponding skip connections in which untransformed inputs are added to values post-
attention. A full PST encoder layer can thus be mathematically represented as the
following set of equations (1):

$$
\begin{aligned}
X^1 &= \text{GraphNorm}(X^0) \\
X^2 &= \text{MultiHeadAttn}(\mathcal{G}) \\
X^3 &= X^0 + X^2 \\
X^4 &= \text{GraphNorm}(X^3) \\
X^5 &= \text{FF}(X^4) \\
X^6 &= X^3 + X^5
\end{aligned}
\tag{1}
$$

861 where X represents the intermediate protein representations and X^0 is the input protein
862 embeddings in the stacked batch. FF represents a 2-layer feedforward network with GELU
863 (Gaussian error linear unit[57]) activation and dropout after each layer. After the full PST
864 encoder, a final GraphNorm operation was applied.
865
The PST decoder uses multi-head attention to compute a per-protein attention score
to be used as the weights for a weighted average of protein embeddings over each
genome. As described previously[14], multi-head attention pooling uses a learnable d-
dimensional seed vector S as the query when computing attention. During the attention
calculation, the contextualized protein embeddings X^C output from the PST encoder are
projected onto S:

$$
872 \quad \text{Attn}(X^C, S) = \text{GraphSoftmax}\left(\frac{(W^Q S)(W^K X^C)}{\sqrt{d}}\right) \times (W^V X^C)
$$

873 The attention values from this projection are used to weight X^C. After re-weighting, X^C is
874 averaged over each genome to produce the final genome outputs. The full set of PST
875 decoder equations is similar to the encoder (**Equation 1**):

$$
\begin{aligned}
X^0 &= \text{GELU}(W X^C) \\
X^1 &= \text{GraphNorm}(X^0) \\
X^2 &= \text{Attn}(X^1, S) \\
X^3 &= X^0 + X^2 \\
X^4 &= \text{GraphNorm}(X^3) \\
X^5 &= \text{FF}(X^4) \\
X^6 &= X^3 + X^5 \\
X^7 &= \text{GraphPool}(X^6) \\
X^G &= \text{FF}(X^7)
\end{aligned}
$$

877 where W is the weights of a linear layer. GraphPool is a pooling (mean) operator over
878 each genome graph that averages the contextualized weighted protein embeddings for
879 each genome. Each FF is a different 2-layer feedforward network with GELU activation
880 and dropout after each layer. X^G is the final genome embeddings. See **Supplementary**
881 **Fig. 1** for a pictorial representation of the PST architecture.
882
883 For fragmented genomes like vMAGs, there is an additional step. Here, X^G instead
884 represents a scaffold-level embedding over the proteins encoded on that scaffold. This
885 arises since PST contextualization and decoding only happen over contiguous

886 sequences. To then produce a genome-level embedding, we use mean pooling over
887 scaffold embeddings for all scaffolds composing a fragmented genome.
888
Inference using 1 A100 GPU takes between 7e-4–0.027 seconds/genome or 0.018–
0.159 seconds/genome using 128 CPUs (AMD EPYC 7H12). When using 1 GPU, the
total inference time for each dataset ranges from 30s–1.13h depending on the number of
genomes and proteins encoded per genome. For 128 CPUs, the total inference time takes
significantly longer but is still reasonably between 40 seconds for the smaller MGnify
dataset (12,857 genomes encoding 141,643 proteins) with ESM__small embeddings up
to 6.68h for the larger IMG/VR v4 dataset (151,255 genomes encoding 7,182,220
proteins) with ESM__large embeddings. PST loads datasets entirely into memory, so
memory usage during inference will include the size of the dataset plus processing.
However, there is an option to lazily load data from disk, which would increase processing
times slightly. For the MGnify test set, which is more reminiscent of a typical dataset, this
would be 170–339MB for loading the dataset and an additional 942MB–2.98GB from the
model (total of 1.1–3.3GB). For larger datasets like the training and IMG/VR v4 test sets,
the primary spike in memory usage would be from loading the dataset into memory (7.8–
17GB).
904
905 **Training the PST foundation models with triplet loss**
906
907   The foundation viral Protein Set Transformer (PST) models were trained using a self-
908 supervised triplet loss objective $\mathcal{L}(\mathcal{G})$ as described previously[15]:

$$D(G^a, G^p, G^n) \quad = \quad [\|f(G^a) - f(G^p)\|_2^2 - \omega_i\|f(G^a) - f(G^n)\|_2^2 + \alpha]_+$$

909
$$\mathcal{L}(\mathcal{G}) \quad = \quad \frac{1}{2N}\sum_{i=1}^{N} C_i\big[D\big(G_i^a, G_i^p, G_i^n\big) + D\big(G_i^a, G_i'^p, G_i'^n\big)\big]$$

where G_i^a is the ith genome treated as an anchor point, G_i^p is the positive genome for the
ith genome, G_i^n is the negative genome for the ith genome, and G_i' is the augmented
genome for the ith genome created using the PointSwap sampling method[15]. $f(\cdot)$ is the
function modeled by the full PST neural network, and $\|x - y\|_2^2$ is the squared L2
(Euclidean) distance between the vectors x and y. C_i is an optional class weight to amplify
the contribution to the loss for classes that are less abundant than others. When we
considered the viral taxonomic realm for cross validation groups (see "**Cross validation**
and hyperparameter tuning"), we additionally used the viral realm to compute class
frequency labels for each virus. Specifically, we compute C_i as an inverse abundance
frequency. Suppose that the ith genome belongs to viral realm k, then the class weight is
computed as:

$$F_k = \frac{n_k}{N}$$

$$C_i = \frac{1}{F_k}$$

923 where n_k is the number of genomes in the training dataset belonging to viral realm k out
924 of N total genomes. When the taxonomy of the viruses was not considered, such as when
925 using protein diversity for cross validation (see "**Cross validation and hyperparameter**

926 **tuning**"), C_i was equal to a 1-vector, meaning that each virus contributed equally to the
927 loss. These PST models trained with triplet loss are referred to as "PST-TL".
928

929 We implemented an easy positive semi-hard negative triplet mining strategy as
930 described previously[15]. To account for the self-supervised choice of the negative genome,
931 the scale factor ω_i reweights the anchor-negative distance according to the following
932 exponential decay equation:

$$\omega_i = \exp\left(-\frac{CD(G_i^a, G_i^n)}{2(c\sigma)^2}\right) \tag{2}$$

where $CD(X, Y)$ is the Chamfer distance between the genomes X and Y, c is a scaling
factor, and σ is the standard deviation of all Chamfer distances in a minibatch. $[\cdot]_+ = $
$\max(0, \cdot)$, which means that there is no contribution to the loss function for cases where
the positive genome is already closer to the anchor genome than the negative by a margin
of α. Thus, α is the farthest distance the negative genome needs to be from the anchor
compared to the positive genome. This restraint notably prevents representation collapse
that could occur in the naïve case of embedding the anchor and positive genomes in the
same position.
942

For a training minibatch, positive mining occurs in the input ESM2 embedding space
using Chamfer distance, before the PST forward pass and before concatenating
positional and strand embeddings. Thus, the positive genomes are sampled online during
training, and the candidates will differ each epoch as minibatches are formed. The
Chamfer distance $CD(X, Y)$ between genomes X and Y always uses the input ESM2
embeddings and is defined as follows:

$$CD(X, Y) = \frac{1}{|X|}\sum_{x \in X} \min_{y \in Y}\|x - y\|_2^2 + \frac{1}{|Y|}\sum_{y \in Y} \min_{x \in X}\|x - y\|_2^2 \tag{3}$$

950 where $x \in X$ are the proteins from genome X and $y \in Y$ are the proteins from genome Y.
951 Intuitively, this means that the positive genome is defined as the most similar genome
952 based on cumulative distance of ESM2 protein embeddings, which should choose a
953 positive genome that encodes the most similar proteins.
954

Negative mining requires the positive genome for a semi-hard sampling scenario,
which is important for forming triplets that will lead to fast and efficient updates to the
model parameters. Notably, negative mining also happens online and is affected by model
updates because negative genomes are sampled in the learned PST embedding space.
The only candidates for a negative genome are those that are farther than the positive
genome in the PST embedding space using Euclidean distance, and we choose the first
genome that is farther than the positive as the negative in the semi-hard case. In cases
where there are no genomes farther than the positive genome in the PST embedding
space, such as at the beginning of training when the model weights have not been well-
optimized, we loosen the semi-hard sampling requirement and choose the genome
closest to the positive genome as the negative genome. Since negative mining is self-
supervised, we use the exponential decay reweighting factor ω_i to down-weight poor
choices of a negative genome that are actually very similar to the anchor genome.
Notably, the ω_i reweighting factor depends on the Chamfer distance (**Equation 2**) and,

subsequently, the input ESM2 embeddings. Thus, we implicitly consider the ESM2
embeddings as a ground truth for protein representation when mining both the positive
and negative genomes.

PointSwap sampling

When training PST-TL models, we used the data augmentation technique PointSwap
sampling[15]. During positive mining, we keep track of the most similar protein from the
positive genome X^p for each protein in the anchor genome $x \in X$ (**Equation 3**) as the
flow $x_i \rightarrow x_j^p$. We create the augmented genome X' as follows:

979
$$X' = \text{PointSwap}(X, X^p) = \{x'_0, \dots, x'_{n_i}\}, \text{where}$$

980
$$x'_i = \begin{cases} x_j^p & \text{if } u_i < p \\ x_i & \text{otherwise} \end{cases}$$

where u_i is a set of samples from a standard uniform distribution $[0,1]$ and p is a rate of
protein swapping between genomes. This means that the augmented genome X' differs
from the anchor genome by swapping related proteins with the most related positive
genome, which intuitively mimics genetic variation. To form an augmented triplet with the
augmented genome as the positive genome, the negative genome is selected from the
set of augmented genomes in a minibatch using the procedure described above in
"**Training the PST foundation models with triplet loss**".

A masked language modeling PST variant

To compare different self-supervised objective functions, we implemented a masked
language modeling (MLM) loss objective using only the PST encoder. A tunable fixed
proportion of proteins are masked per genome, where masked protein embeddings are
set to 0-vectors. We allow these 0-vector masked embeddings to be concatenated with
the current positional and strand embeddings, rather than equally sized 0-vectors, since
the position and strand are not unknown. In traditional large language models, only the
word identity, and not position, is masked, since the contextual information of neighboring
words is used to predict the identity of the masked word.

The PST encoder contextualizes protein embeddings according to the configuration
of genome subgraphs (see "**Protein Set Transformer model architecture**" and
Equation 1). We adapted a similar approach for genome language modeling with proteins
represented as embeddings using MLM[10]. Briefly, we use a mean squared error function
to mirror a MLM objective, since the protein words are d-dimensional vectors and not
scalars:

1006
$$\mathcal{L} = \frac{1}{n_m} \sum_{i=1}^{n_m} \|Y_{pred} - Y_{target}\|_2^2$$

where n_m is the total number of masked proteins per minibatch, Y_{target} is the target
masked embeddings concatenated with positional and strand embeddings, and Y_{pred} is
the contextualized protein embeddings. We further considered that multiple proteins could
occur in the same genomic contexts, such as homologs or reordering of grouped sets of

proteins. To account for this, we positively sampled the nearest neighbor for each input
protein embedding in ESM2 space using Euclidean distance and computed the PST-MLM
protein embeddings, denoted as Y_{pos}. The mean squared error between Y_{pos} and Y_{target}
was computed similarly and averaged with the $Y_{pred} - Y_{target}$ loss:

$$\mathcal{L} = \frac{1}{2n_m} \sum_{i=1}^{n_m} \left\| Y_{pred} - Y_{target} \right\|_2^2 + \left\| Y_{pos} - Y_{target} \right\|_2^2$$

1015

1016
1017   Finally, to produce genome embeddings, which PST-MLM models do not directly
1018 produce, the contextualized protein embeddings are averaged over each genome.
1019

Cross validation and hyperparameter tuning

1021
1022   To optimize the model hyperparameters (**Supplementary Table 3**), we used Optuna[58]
1023 (v3.3.0) to iteratively sample hyperparameters in a direction that optimizes the objective
1024 function using a Bayesian Tree-structured Parzen Estimator method. Model performance
1025 was evaluated using one of two different cross validation (CV) strategies each based on
1026 a Leave-One-Group-Out (LOGO) approach.
1027
The first CV strategy involved a modified LOGO implementation. Here, we considered
the viral taxonomic realm to be the group with 5 total groups: Duplodnaviria,
Monodnaviria, Riboviria, Varidnaviria, and Unknown / Other. We adapted the LOGO
strategy to always include Duplodnaviria in each training fold, since this group of viruses
accounted for 65.4% of the training dataset. This resulted in training 4 separate models
validated on the remaining viral realms. This notably helped to ensure that the best model
is chosen based on the relatively lower abundance viral taxa in the training dataset. Each
of the 4 folds were synchronized during training to enable overall performance monitoring
as the average of each fold. This enabled real-time monitoring of each tuning trial's
performance. Thus, we were able to stop trials early depending on several criteria using
the average validation loss of each fold: (1) if the loss plateaued (standard deviation of
change less than 1e-6) after having trained 3 epochs, (2) if the loss did not decrease by
0.05 within 5 epochs, (3) if the current performance was worse than the median
performance of previous trials at the same training epoch, (4) if the model was trained for
20 epochs, (5) if 24 hours passed, (6) or if the loss was not finite. For number 3, this was
tracked by the Optuna framework, and we required at least 1 complete trial before this
was enabled. In the case of early stopping due to reasons 1, 2, 3, and 6, these trials were
marked as pruned and not used by Optuna's median performance calculation. Models
tuned with this taxonomic approach have "-T" in the model name (i.e. PST-TL-**T**__small).
1047
The second LOGO CV strategy used groups based on protein diversity. We
constructed 5 groups with relatively evenly distributed protein diversity using a greedy
heuristic. First, we clustered the training proteins using mmseqs2 (v13.45111, cluster -s
7.5 -c 0.5 --cluster-mode 1) into remotely related groups of proteins. We then constructed
a presence/absence binary matrix V, where the rows were each training virus genome
and the columns were the remote protein clusters. We then computed the dice similarity

scores S between all pairs of viruses that shared any protein clusters to compute which
viruses shared the same sets of proteins:

1056
$$S_{ij} = \frac{2|v_i \cdot v_j|}{|v_i| + |v_j|} \qquad (4)$$

We then filtered S to retain only genome-genome connections with a dice similarity ≥0.5,
which resulted in 25,733 connected components of genomes that had similar protein
content profiles. We computed the average dice score of all pairs of genomes within the
same connected components and across connected components, which showed that
there was not significantly shared protein content between connected components
(**Supplementary Fig. 26A**). We then constructed 4 groups with minimally overlapping
protein diversity using a greedy algorithm. First, the 4 largest connected components
were taken as seeds for each of the 4 groups. To confirm that there was minimal overlap
in protein diversity between these seeding connected components, we compared their
average intra- and inter-connected-component dice similarity (**Supplementary Fig. 26B**).
Then, for each of the 4 seeding connected components, we constructed 4 independent
priority heaps based on the average dice similarity between genomes in each of the
seeding components and genomes in all other connected components. Each of the 4
broad groups were expanded in round-robin fashion by popping off the most similar
connected component from the heap and adding this to the current group if it had not
already been taken. We further confirmed that there was greater internal similarity than
inter-group similarity with an average maximum dice score, where the maximum non-self
dice score was computed for each genome searching against all other genomes from
each of the final 4 groups (**Supplementary Fig. 26C**). Finally, there were 1,734 genomes
that did not share any protein clusters with any other genomes and were, thus, not
included in the above greedy search algorithms. Since these genomes do not share any
protein similarity with any of the other genomes, we added all of these to the smallest
group, since this would not affect the overlap in protein diversity of any groups. This
resulted in 4 relatively balanced groups consisting of 31,778, 25,119, 24,650, 22,042
training genomes, respectively, with minimal overlap in shared protein content
(**Supplementary Fig. 26C**). Models tuned with this protein diversity approach have "-P"
in the model name (i.e. PST-TL-**P**__small).

1084
The summary for the number of CV trials for each combination of training objectives
(MLM vs TL), ESM2 input size (ESM__small vs ESM__large), and CV strategies can be
found in **Supplementary Table 10**. Briefly, each of the 8 model setups had 7-45 complete
trials, 5-78 trials that got pruned due to poor performance, and 1-16 failed trials. The only
reason for failing was due to out-of-memory errors on A100 80GB vRAM GPUs hosted
by the University of Madison-Wisconsin Center for High Throughput Computing[48]. All trials
were tuned using 1 GPU since Optuna has limited support for GPU parallelism.

1092
The final performance for each training trial was the average validation loss from each
of the models trained in each CV fold. For PST-TL-T models, once the TL of the best
model setup decreased below 20.0, we chose the best hyperparameter configuration. All
other models approached loss values below 1.0 without needing to arbitrarily stop. The
summary of final training can be found in **Supplementary Table 11**, including the time
needed to train on the full training set using 1 A100 GPU. The final models took between

4.5-33.7h to train with early stopping once the training loss plateaued and did not
decrease by 0.05 within 5 epochs. During training of the final models, a learning rate
scheduler was used that linearly decreased the learning each epoch. Further, we tested
batch accumulation sizes of 1, 25, 50, 100, and 250, and the best model among these 5
accumulation sizes was chosen based on the minimum loss at the end of training. The
selected batch accumulation size for each model is also reported in **Supplementary**
Table 11.
1106
For both tuning and training the final models, gradients were clipped to keep all values
below a magnitude of 1.0, and we used mixed precision training, using bfloat-16 data
when available. These choices helped stabilize training. Our fold training synchronization
strategy and modified LOGO CV approach were implemented in a custom package called
"lightning-cv" available from the main model repository. This package heavily relies upon
and extends functionality in the lightning-fabric sub-library of PyTorch-Lightning (v2.0.7).
For the protein diversity CV groups, we used the "LeaveOneGroupOut" implementation
in scikit-learn (v1.4.2) that is integrated into "lightning-cv".
1115
1116 **GenSLM open reading frame (ORF) and genome embeddings**
1117
We used the 25M parameter GenSLM[30] foundation model ("genslm_25M_patric",
downloaded September 2023) for our analyses since the output embedding dimension
(512) was on par with other protein and genome embeddings used. The GenSLM
foundation model is pretrained only on bacterial and archaeal nucleotide genes where the
gene sequences were broken into codons as input. The authors then finetuned the
foundation models on a dataset of SARS-CoV-2 genomes. However, it is not clear if only
the open reading frames (ORFs) from SARS-CoV-2 were included or if entire viral
genomes were used as input during finetuning. This is further complicated by the fact that
the protein-coding density of the SARS-CoV-2 genome is 71.2% (based on the NCBI
RefSeq reference sequence NC_045512.2). We chose to mimic the pretraining setup
and input the protein-coding ORFs for each virus in our datasets. Notably, we used
GenSLM as a nucleotide analog of ESM2, producing ORF embeddings akin to the ESM2
protein embeddings. We used these ORF embeddings for protein/ORF analyses and the
average of these over each genome as genome embeddings for genome analyses.
1132
1133 **HyenaDNA genome embeddings**
1134
We used the HyenaDNA[31] model with the longest context size (1M nucleotides, "large-
1m", downloaded from HuggingFace in November 2023) that has 6.5M parameters. We
converted all non-ACGTN nucleotides to Ns. Genomes larger than 1M nucleotides were
split into non-overlapping fragments of 1M nucleotides at most. Then each fragment was
tokenized and fed to the "large-1m" HyenaDNA model. The embedding of each genomic
fragment was averaged to produce the final genome embedding. We also used this same
averaging approach for fragmented genomes (i.e. vMAGs), where the final genome
embedding was the average of each fragment.
1143
Tetranucleotide frequency vectors as genome embeddings

For each genome, we computed tetranucleotide frequency vectors
($[AAAA \quad \cdots \quad TTTT]$) using the bionumpy[59] package (v1.0.8). We filtered all nucleotides
not in the canonical ACGT alphabet before calculation. For RNA viruses, U nucleotides
were represented by T for simplicity. For multi-scaffold viruses, these frequency vectors
were computed for each scaffold and then averaged over each scaffold. Throughout the
paper, these are referred to as "kmer".

1152
1153   **Clustering genome and protein embeddings**

1154
We constructed a similarity-weighted *k*-nearest neighbors (*k*NN) graph. The set of
*k*NN was computed using the faiss[60] (v1.8.0) Python bindings. We used the divide-and-
conquer IndexIVFFlat search index that splits the input embeddings into n_{cells} Voronoi
cells for faster retrieval. The number of Voronoi cells was $n_{cells} = 3878$ for clustering
IMG/VR v4 genomes, $n_{cells} = 4096$ for clustering IMG/VR v4 proteins, $n_{cells} = 329$ for
clustering MGnify genomes, and $n_{cells} = 2048$ for clustering MGnify proteins.

1161
Genome or protein clusters were then detected in the similarity-weighted *k*NN graph
using the Leiden[34] algorithm Python implementation of iGraph (v0.11.3) with a resolution
of 0.9 to only cluster embeddings with a high angular similarity. Lowering the similarity
threshold to 0.6, which is a very relaxed threshold as this value indicates nearly
perpendicular vectors, did not substantially change the number of clusters or average
cluster size for any embedding. This likely reflected the vast diversity of the viral genomes
and proteins, so we opted to keep a high embedding similarity threshold of 0.9 for
clustering. For each clustering iteration, the random number generator was reset and
seeded using the same random seed, so all clustering results are exactly reproducible.
We do not include singletons as clusters for downstream analyses.

1172
1173   **Genome and protein clustering purity**

1174
To compute the overall purity of clusters produced by different genome and protein
embeddings, we computed viral and host taxonomic purity for each set of genome
clusters and functional purity for each set of protein clusters using the information gain
ratio I as a proxy for purity. For taxonomic purity, we considered the case of clustering all
genomes into a single cluster as the background. For functional purity using curated
functional categories from VOG or PHROG, we used the distribution of functional
categories from the annotation databases as the background. In either case, unlabeled
proteins and genomes were excluded during the entropy computation but included for the
cluster size weighting. Then we computed I as follows:

1184
$$I = \frac{H_{background} - \sum_{i=1}^{n_{clusters}} H_i w_i}{H_{background}} \in [-h, 1]$$

1185   where h is the information gain of the background compared to a uniform distribution and
1186 H is the information entropy of each cluster with respect to a set of labels related to viral
1187   taxonomy, host taxonomy, or protein function. The calculation of I is weighted by the size
1188   of each cluster, including unlabeled members, where:

$$w_i = \frac{n_i}{\sum_{i=1}^{n_{\text{clusters}}} n_i}$$

Values of I close to 0 indicate clustering patterns with no improvement above background, while values of I close to 1 suggest maximal purity since there are few clusters with multiple labels. It is possible to interpret I as a purity score since the backgrounds are not pure with respect to the labels. Thus, a maximum I means that there is only a single label for each cluster.

Average amino acid identity (AAI)

We used mmseqs2[61] (v13.45111) and polars (v1.24) to compute the AAI between pairs of viruses at scale. Given the large number of viruses in this study (>250k), we did not exhaustively compute the AAI between all pairs of viruses (~32.5B). Instead, we used heuristics implemented by mmseqs2 to only consider the AAI between viruses that had any protein sequence similarity detectable when using the mmseqs2 search settings: -s 7.5 -c 0.3 -e 1e-3. For each pair of viral genomes, we only retained the best hit for each protein from each genome. Then, AAI was computed as the mean of protein-protein sequence similarities computed by mmseqs2. Since we did not exhaustively compute all possible protein-protein sequence alignments, some AAI scores were only based small fractions of the total number of proteins encoded in each genome. To account for this, we took the harmonic mean of AAI and the minimum proportion of shared genes to use as a final AAI-based score when necessary.

Average structural identity (ASI)

We compiled foldseek[36] (v284d732b9a801c642213a396286cae3344a11d2c) from source to enable CUDA support. We used foldseek to download the ProstT5 model to translate protein sequences to 3Di structural sequences for all proteins in both test datasets using A100 GPUs. We split all datasets into subsets of 100,000 proteins per file to parallelize this translation on a computing cluster and then concatenated the output files into a single foldseek database. We then computed ASI analogously to AAI, except using foldseek to search our 3Di structure sequence databases with the following settings: -c 0.3 -e 1e-2 -s 4.0. The 3Di searches were performed on CPU.

Protein functional annotation

We used VOG (r219) and PHROG[62] (v4) databases for the annotation of viral proteins. For VOG, which supplies profile Hidden Markov models (HMMs), we used pyhmmer (v0.9.0) with a bit score cutoff of 40. For PHROG, we used mmseqs2 (v13.45111) with the recommended search settings (https://phrogs.lmge.uca.fr/READMORE.php). In both cases, we kept the best hit for each protein with the max bit score. For each database, we curated the functional categories of each annotation that we describe below.

For PHROG, which already provides an extensive set of 10 categories (including unknown function), we manually readjusted certain categories. Our manual curation of the PHROG database affected 1,937 out of 38,880 profiles. We renamed the following

categories for better intuition of the functional category: "DNA, RNA and nucleotide
metabolism" to "nucleotide metabolism", "integration and excision" to "lysogeny", and
"transcription regulation" to "gene expression". We then dissolved the "moron, auxiliary
metabolic gene and host takeover" category for being too broad and relatively unrelated.
These 461 profiles were split into the already existing "other"; the newly created "host
takeover", "lysogenic conversion", "metabolic gene"; and the renamed "gene expression",
"lysogeny", and "nucleotide metabolism" categories. Generic annotations like "membrane
associated protein" and "ABC transporter" were put in the "other" category. We considered
proteins involved in host replication and cell division inhibition, superinfection exclusion,
anti-sigma factors, and defense against host antiviral proteins to be "host takeover".
Proteins that encoded toxins or antitoxins/resistance proteins were categorized as
"lysogenic conversion." Proteins directly involved in specific metabolic transformations
were put in "metabolic gene," while accessory or generic proteins like "nicotinamide
mononucleotide transporter" were considered as "other". These changes can be found in
Supplementary Table 5.
1249
VOG provides very broad categories: "Xr" for replication, "Xs" for structural, "Xh" for
host-benefitting, "Xp" for virus-benefitting, and "Xu" for hypothetical proteins. The "Xh"
and "Xp" categories are also ambiguous on what specific function the protein may
perform. We, therefore, used text pattern matching on the specific HMM annotation
descriptions to subdivide all HMMs into 9 categories: anti-host defense, exit, gene
expression, integration, packaging, replication, structural, other, and unknown. Briefly, we
separated terminases, portal proteins, and head packaging proteins from other structural
proteins into a "packaging" category. Lysis, virion export, and budding HMMs were
considered collectively as the "exit" group. "Integration" includes both integrases and
excisionases as well as transposases. We considered all nucleotide metabolism and
genome replication to be part of "replication". To account for overlap in text matching, we
enforced the following hierarchy: structural > packaging > exit > integration > gene
expression > anti-host defense > replication > unknown > "RNA polymerases" > other.
The final category for each HMM was, therefore, the highest in the hierarchy. We added
RNA polymerases that did not indicate if they were replicative RNA-directed or
transcriptive DNA-directed at the bottom to put these specific RNA polymerases in the
"gene expression" category. Additionally, HMMs without matches were thus considered in
the "other" category. The category for each VOG r219 HMM can be found in
Supplementary Table 6, and the regex patterns used to categorize each HMM can be
found in **Supplementary Table 7**.
1270
1271 **Protein attention scaling and analysis**
1272
1273 We computed the attention values as follows: Let $A_{ij} \in A_i$ be the mean attention score
1274 across all attention heads for the jth protein from the ith genome:

$$A_{ij} = \frac{1}{n_{\text{heads}}} \sum_{k=1}^{n_{\text{heads}}} A_{ijk}$$

1275

1276 The sum of per-protein attention values for each genome is 1.0:

$$\sum_{A_{ij} \in A_i} A_{ij} = 1.0$$

Given n_i, the number of proteins in the ith genome, and n_k, the number of proteins in the kth genome, and $n_i \neq n_k$, it follows that A_i and A_k are not directly comparable since the number of proteins each genome is not the same. More explicitly stated, consider $n_i = 2$ and $n_k = 4$, and $A_i = [0.5 \quad 0.5]$ and $A_k = [0.5 \quad 0.3 \quad 0.05 \quad 0.15]$. For the genome i, the model has randomly split attention to both proteins, while for genome k, the model clearly has attended to the first protein more than the others, despite the numerical values being equivalent.

Therefore, to compare the PST-TL attention values per protein for each scaffold, we normalized the attention scores. We considered the background case for the attention distribution A_i to be a uniform distribution, ie $A_i \sim U(0,1; n_i)$ where $U(0,1; n_i)$ is a standard uniform distribution with probability $\frac{1}{n_i}$ of attending any of the n_i proteins. We then computed the distance between A_i and $U(0,1; n_i)$ using the normalized Kullbach-Leibler (KL) divergence:

$$D_i = \frac{H_i^{U(0,1;n_i)} - H_i^{A_i}}{H_i^{U(0,1;n_i)}} \in [0,1]$$

H^X is the entropy of the probability distribution X:

$$H(X) = -\sum_{x \in X} p(x) \log_2 p(x)$$

We then rescale all per-protein attention values in A_i by the KL-divergence D_i to down-weight misleadingly large attention values that are uniformly (randomly) distributed:

$$A'_{ij} = A_{ij} \times D_i$$

Thus, for cross-genome comparisons, we use the normalized attention scores $A'_{ij} = \{A_{i1} \quad \cdots \quad A_{in_i}\}$. In our above example, $A'_i = [0.0 \quad 0.0]$ and $A'_k = [0.0881 \quad 0.0528 \quad 0.0088 \quad 0.0264]$.

To associate PST-TL attention with protein function, we first chose the top 1,000 proteins for each VOG and PHROG category based on the rescaled attention values A'. We normalized the values from the PST-TL-T models and PST-TL-P models by dividing by the maximum scaled attention for each model. This allowed us to focus on relative differences in attention, rather than compare absolute differences between these two sets of models. To compare attention values with abundance in the training and test datasets, we then clustered the proteins using sequence identity (mmseqs2 v13.45111 -e 1e-3 -c 0.5 -s 7.5). We computed the max scaled attention A'_{ij} for all proteins in the same cluster, excluding singletons.

Protein annotation improvement

We considered all proteins unable to be annotated using the VOG r219 databases as hypothetical proteins, where N_H is the number of hypothetical proteins. N_H includes both proteins detectable by VOG profiles but assigned a hypothetical function and proteins

undetectable entirely. We computed the annotation improvement as a function of a
protein/ORF embedding. We used the same protein search settings described in the
Methods section "**Clustering genome and protein embeddings**": angular similarity on
the unit-normalized protein embeddings. For each protein, we searched for k nearest
neighbors, scoring this as an improvement if any neighbor proteins in that set were
annotated:

1323
$$T_k = \sum_{i=1}^{N_H} \begin{cases} \text{if ANY of the } k \text{ Nearest Neighbors of } i \text{ is annotated} & 1 \\ \text{else} & 0 \end{cases}$$

1324 Then, we computed the overall annotation improvement AP_k as the proportion of
1325 hypothetical proteins whose nearest neighbors had any annotations:

1326
$$AP_k = \frac{T_k}{N_H}$$

1327
To enforce a greater degree of confidence beyond any neighbors being annotated, we
further required that all k nearest neighbors belong to the same VOG functional category.
For example, this functional category set of 2 neighbors {structural, replication} would not
be counted as an annotation improvement, since the 2 nearest neighbors have broadly
different functions. We excluded nearest neighbors that were unannotated from this
penalty (i.e. {unknown, structural, unknown, structural} counts as a hit). The updated
scoring function can be described as:

1335
$$T_k = \sum_{i=1}^{N_H} \begin{cases} \text{if ALL of the } k \text{ Nearest Neighbors of } i \text{ have the same VOG category} & 1 \\ \text{else} & 0 \end{cases}$$

1336
1337 **Protein function co-clustering**
1338
1339   We used curated PHROG functional categories (**Supplementary Table 5**) to compute
1340 functional co-clustering, excluding the category for proteins of unknown function. Given a
1341 protein clustering configuration, for each protein cluster $P_i \in P$, we count the co-
1342 occurrence between pairs of functional categories u and v as the product of the number
1343 of proteins belonging to each category in the cluster:

1344
$$C_i^{uv} = n_i^u \times n_i^v$$

1345 where n_i^u is the number of proteins in the ith protein cluster that belongs to category u.
1346 The observed co-occurrence C^{uv} between the functional categories u and v is defined as
1347 the sum of cluster-level co-occurrences:

1348
$$C^{uv} = \sum_{i=1}^{|P|} C_i^{uv}$$

1349 To account for the distribution of PHROG annotation profiles, we computed an enrichment
1350 score against the background of the distribution of the 38,800 PHROG profiles:

1351
$$E^{uv} = \frac{C^{uv}}{C_{background}^{uv}} \in [0, \infty]$$

where $C_{background}^{uv}$ is computed analogously to C^{uv} except using relative abundances of
the annotation profiles themselves instead of annotated proteins. To identify functional

categories that co-occur frequently, we constructed a fully-connected graph with all
PHROG functional categories as nodes and the corresponding edge weights E^{uv}
between categories u and v. We then applied the Leiden algorithm with resolution 1.25
to identify sub-communities of co-occurring functions enriched above background.

1358

Protein functional module detection
1359

1360

We defined the following protein functional modules based on curated functional
categories (**Supplementary Tables 5 and 6**) and annotation text searches. For PHROG
DNA-interacting modules, we included all hits that belonged to either "nucleotide
metabolism", "lysogeny", or "gene expression" categories. For VOG, all hits belonging to
"replication", "integration", "packaging", and "gene expression" were included. For
PHROG late genes, annotations in the categories "tail", "head and packaging",
"connector", and "lysis" were retained. Likewise, for VOG, the categories "structural",
"exit", and "packaging" were included.

1369

We considered protein clusters to correspond to a specific functional module if they
met the following module-specific criteria: (1) We required at least 2 categories to be
represented by the annotated proteins in each cluster. (2) We excluded protein clusters
that had any annotated proteins outside the indicated functional categories to focus on
protein clusters that most strongly fit our definition of functional modules, i.e. were "pure"
relative to the definition of the functional module. We ignored proteins of unknown function
when considering functional purity.

1377

Capsid structure searches
1378

1379

1380 To quantify the frequency at which embedding-based protein clusters co-cluster VOG-
1381 detectable capsid proteins with proteins unable to be assigned function by VOG, we
1382 excluded all embedding-based protein clusters that did not solely consist of annotated
1383 capsids and hypothetical proteins. This led to a total of 462,141 IMG/VR v4 test proteins
1384 and 7,448 MGnify test proteins for this analysis.

1385

We used foldseek[36] (v284d732b9a801c642213a396286cae3344a11d2c) to convert
our protein sequence database into a 3Di-structure database using the ProstT5[37] model
(downloaded February 2025; foldseek createdb with "--prostt5-model" option; see
"**Average Structural Identity (ASI)**"), which uses language tokens to represent structural
features. We searched our 3Di-structure database against 295k structures from the
Protein Data Bank[38] (PDB; downloaded using foldseek in July 2024) using default
settings. We selected only alignments with bit scores ≥100 and alignment identities ≥10%.
To select PDB structures corresponding to capsid proteins, we chose only PDB structures
from the foldseek PDB database whose description contained either "capsid" or "virion".
We validated this approach by aligning AlphaFold 3-modeled[40]
(https://alphafoldserver.com) monomer structures with the HK97 major capsid protein
(2FS3) using TM-align[63] implemented in the PDB web server[64]. We choose 2 proteins
with the highest scoring structural alignment as determined by foldseek, each from either

proteins annotated with a VOG profile of unknown function or proteins undetected by
VOG, for this analysis.
1401

1402   We then scored the proportion of unannotated proteins from each cluster that had a
1403   structural alignment with a PDB capsid protein out of all the searched proteins from each
1404   test set.
1405

1406 **Embedding UMAP visualization**
1407

We used the Python implementation of the UMAP algorithm[65] (umap-learn v0.5.3) for
embedding visualization only. For genome embeddings, we used the default 15 nearest
neighbors defined using Euclidean distance. When computing the reduced embeddings,
we jointly embed the genome embeddings of both the training and test datasets for each
type of genome embedding into the same space. We did not reduce the dimensionality
before visualization, so the embeddings themselves were directly used as inputs to the
UMAP algorithm.
1415

1416 **Graph-based host prediction framework**
1417

For the virus host prediction proof-of-concept, we modeled our framework off
CHERRY[41], which applies graph learning on a virus-host interaction network $G = (X, E)$.
Our implementation uses PyTorch (v2.2.2), PyTorch-Geometric (v2.5.2) and PyTorch-
Lightning (v2.2.4). The interaction network is bipartite, meaning that there are 2 types of
nodes: viral nodes $v_i \in V$ and host nodes $h_i \in H$. The total node set X is thus $X = V \cup H$.
The edges E represent known virus-host pairs and may also include confident virus-host
predictions that come from virus-host genome alignments (see "**Host prediction training**
and test datasets" for more detail). Given G, the objective is a link prediction task to infer
for any virus-host pair (v_i, h_i) the probability of an edge existing in the interaction
network.
1428

1429   For the most comparable analyses, we designed our neural network architecture
1430   based on CHERRY: an encoder consisting of multiple Graph Convolution[66] (GCN) layers
1431   and a decoder that performs the link prediction. The encoder propagates information in
1432   the genome embeddings among local neighborhoods. Specifically, the GCN encoder
1433   layers $e^{(l+1)}$ can mathematically be represented as:

1434
$$e^{(l+1)} = \phi\left(\widetilde{D}^{-\frac{1}{2}}\tilde{A}\widetilde{D}^{\frac{1}{2}}e^{(l)}W^{(l)}\right) \tag{5}$$

where l is the layer index, $\tilde{A}$ is the adjacency matrix with self-connections ($\tilde{A} = A + I$, I is
the identity matrix,), and $\widetilde{D}$ is the diagonal matrix where $\widetilde{D}_{ii} = \sum_j \tilde{A}_{ij}$. ϕ is the activation
function, and $W^{(l)}$ is the l-layer model weights. $e^{(0)} \in \mathbb{R}^{|X| \times N}$ is the input genome
embedding where N is the size of the embedding. To compare our work to CHERRY,
which uses tetranucleotide frequency genome embeddings, we substitute the genome
embedding with either the PST genome embeddings or the simple average of the ESM2
protein embeddings over each genome for both the viruses and hosts.
1442

1443   The decoder is a 2-layer feedforward neural network that takes the outputs from the
1444 encoder as input. We consider all possible virus-host pairs $(v_i, h_j) \in X$ as a query set Q
1445 where each pair is represented by the difference in encoder embedding:

$$q_{ij} = \text{encoder}(v_i) - \text{encoder}(h_j)$$

1447 The decoder, therefore, is mathematically written as:

$$\begin{cases} q_{ij}^{(l+1)} = \phi\left(q_{ij}^{(l)}\theta^{(l)}\right) \\ \text{decoder}(q_{ij}) = \text{sigmoid}\left(q_{ij}^{L-1}\right) \end{cases}$$

1449 where $q_{ij}^{(l)}$ is the hidden feature in the lth layer out of L total decoder layers, and $q_{ij}^{(0)} =$
1450 q_{ij}. ϕ is the activation function, and $\theta^{(l)}$ represents the weights of the lth fully connected
1451 layer.

1452
1453 **Host prediction training and test datasets**
1454
For the virus host prediction proof-of-concept, we modeled our framework off
CHERRY[41], which applies graph learning on a virus-host interaction network. To construct
the network of known virus-host pairs, we used the train and test datasets from iPHoP[42].
Specifically, the train dataset included 3628 complete bacterial and archaeal viruses from
NCBI RefSeq prior to 2021. The iPHoP test dataset consisted of 1636 complete bacterial
and archaeal viruses from NCBI GenBank, distinct from the training dataset. Although
both datasets indicate the taxonomy of the host, they do not provide specific genome
accessions to link the viruses, which are necessary to construct the interaction network.

1463
For the training dataset, we used the Virus-Host Database[67] (accessed April 2024) to
determine the full host taxonomy. We then selected either the NCBI RefSeq
representative sequence associated with the host taxonomy, if one existed, or the most
complete (longest and assembly_level == "Complete Genome") genome from NCBI
GenBank (accessed May 2024). We included all hosts in the Virus-Host Database if there
were multiple such as in the case of viruses with a relatively broad host range. The set of
hosts notably includes multiple strains of the same species or species of the same genus
as indicated in the Virus-Host Database. Then, any strain information was ignored, so the
lowest level of evaluation was at the host species.

1473
We performed a similar search for the test dataset using the information provided in
Supplementary Table 2 of iPHoP[42]. We divided the test virus hosts whose species ranks
were unknown (ie "Wolbachia sp.") into 2 different sets. If these hosts were already in the
set of hosts for the training dataset, we did not retrieve any new host genomes. Instead,
we considered all hosts currently in the set of hosts with the same genus as potential
hosts for these viruses. For new hosts, we used the same search criteria as above to add
a single new host for each of these viruses. This resulted in a total of 805 host genomes,
corresponding to 594 unique host species.

1482
1483 **Constructing the virus-host interaction network**
1484

To construct the virus-host interaction network, we constructed the heterogeneous
graph G that has 2 node types (virus, host) and 2 edge types (virus-related to-virus, virus-
infects-host). For the virus-host edges, we included all virus-host pairs identified above,
meaning that G includes both training and test viruses. We notably deviated from the
CHERRY implementation by excluding confident host predictions that would have come
from virus-host BLASTn genome alignments (proviruses) or CRISPR spacers. This
deviation is not concerning since we focused on the relative performance of our PST
genome embeddings compared to other tools and genome embeddings, rather than
absolute predictive ability.
1494
To select virus-virus edges representing pairs of similar viruses, we used a protein
sharing network clustering approach when using tetranucleotide frequency genome
vectors, since this is the same approach CHERRY uses[41]. We first excluded all singleton
proteins since these do not inform about genome-genome relatedness and only serve to
account for the proportion of gene sharing relative to the total number of proteins/protein
clusters in each genome. After protein clustering using mmseqs2 (v13.45111 -s 7.5 -e 1e-
3 -c 0.5) and filtering singleton proteins, we constructed a sparse $(|V| \times n_{pc})$ presence-
absence matrix where n_{pc} is the total number of protein clusters in the dataset. Each row
represents what protein clusters are encoded in the indicated genome. We then
computed the dice similarity S_{ij} for each pair of genomes using **Equation 4**. We then
constructed a graph with all viruses where the edges are $S_{ij} \mid S_{ij} > 0$. To understand which
viruses were considered related, we clustered this graph with the Leiden algorithm with a
resolution of 0.1. Edges were created in the interaction graph between all viruses in the
same gene-sharing clusters. For the other genome embeddings we tested, we considered
pairs of viruses to be related if their genome embeddings were at least 75% similar based
on angular similarity of unit-normalized embeddings. This ensured that each virus had at
least 1 neighbor and was, therefore, included in the interaction graph. We then pruned
these embedding-based virus-virus connections to maintain up to the top 15 neighboring
viruses for each virus.
1514
1515 **Host prediction model training**
1516
1517   We trained new graph-based host prediction models using the iPHoP training dataset,
1518 swapping the genome representations for PST genome embeddings or the simple
1519 average of the ESM2 protein embeddings over each genome. Our implementation used
1520 PyTorch (v2.1.2) and PyTorch-Geometric (v2.4.0). We used a binary cross entropy loss
1521 objective for the link prediction task to classify the edge E_{ij} as existing (1) or not (0):

$$\mathcal{L} = -\frac{1}{N} \sum_{k=1}^{N} y_k \log\big(p(y_k)\big) + (1 - y_k)\log\big(1 - p(y_k)\big)$$

1522

1523 where y_k is the discretized final output for the *kth* virus-host pair from the model decoder,
1524 given a probability threshold for whether an edge E_{ij} is predicted to exist.
1525
During training, we randomly split all virus-host edges $E = \{E^{(T)}, E^{(V)}\}$ into disjoint
training $E^{(T)}$ and validation $E^{(V)}$ sets at an 80:20 ratio. We additionally randomly sampled

negative edges $E' = \{E'^{(T)}, E'^{(V)}\}$ that do not exist in the virus-host interaction network G
to provide the model with negative examples (implemented by PyTorch-Geometric). The
negative edge sets $E'^{(T)}$ and $E'^{(V)}$ are also disjoint, and $|E| = |E'|$ so that there was not
label imbalance. During the message-passing stage of the model encoder, only the real
edges E are used. After message passing updates the node representations, we used
$E \cup E'$ for decoding and inference with both real and negative edges. Therefore, $N =$
$|E^{(\cdot)} \cup E'^{(\cdot)}|$ for either the training or validation edges. Since the prediction task does not
depend on virus-virus edges, these edges were not split or negatively sampled. This
means that the graph structure and message passing consider all viruses, not just training
viruses. Thus, during training, we masked any virus-host edges that contain test viruses
in the loss computation to prevent data leakage.
1539
1540 Although we strived to implement a nearly 1:1 model with the original CHERRY
1541 implementation, our implementation and training deviates in 3 ways. (1) We allowed
1542 separate learnable weights for each type of edge (virus-virus, virus-host, and host-virus)
1543 in the message-passing encoder layers by updating **Equation 5**:

1544
$$W^{(l)} = \begin{cases} W_{vv}^{(l)} & \text{virus-virus edges} \\ W_{vh}^{(l)} & \text{virus-host edges} \\ W_{hv}^{(l)} & \text{host-virus edges} \end{cases}$$

1545 $W_{hv}^{(l)}$ and subsequently host-virus edges are required to ensure reciprocal message
1546 passing between virus and host nodes despite the intuitive way of representing virus-host
1547 edges as directed. The native CHERRY implementation does not allow for edge type-
1548 specific weights, instead sharing weights for all edge types.
1549
(2) Due to modeling G as a heterogeneous graph, the message passing layer is not a
true Graph Convolution (GCN) layer, which is not implemented for heterogeneous graphs
in PyTorch-Geometric. Specifically, we use a generalization of the GCN layer[68] that allows
for heterogeneous graph learning with multiple node and edge types. For this layer,
however, the node update equations for this layer and the GCN layer are identical, but
there may be PyTorch-Geometric implementation-specific differences beyond changing
node representations.
1557
(3) We explored a more sophisticated technique for handling the training and
validation splits for link-level tasks that we refer to as "disjoint training". Specifically, we
divided the real training edges $E^{(T)}$ into 2 disjoint sets $E^{(T)} = \{E^{(MP)}, E^{(D)}\}$ where $E^{(MP)}$
are edges only used for message passing (node updates) and $E^{(D)} \cup E'^{(T)}$ are edges only
used for supervision (decoding and inference). Specifically, $E^{(D)} \cup E'^{(T)}$ are the edges
used for link prediction. We only considered a 70:30 split for $E^{(MP)}$ and $E^{(D)}$ for this study
when this was enabled. This modification is analogous to splitting training data into
separate training and validation sets to prevent data leakage but only for training edges.
1566
To decouple the effect of these 3 differences from the choice of node embeddings, we
trained a model that is nearly faithful to the CHERRY implementation without these
changes (barring the required change #2), and then we trained a separate model using

tetranucleotide frequency genome embeddings (kmer) that enables our changes. Thus,
the CHERRY and "kmer" model use the same virus-host interaction graph as input, but
the "kmer" models explored the effects of changes #1 and #3.
1573
To lightly optimize hyperparameters, we sampled from sets of intuitive values for the
number of encoder layers, decoder hidden dimensions, learning rate, whether to enable
disjoint training (at a 70:30 split), and whether to allow edge specific-weights in the
encoder or not. We did not dilate the input embedding dimension in the encoder layers.
For the 2-layer feedforward decoder network, we only chose values smaller or equal to
the input embedding dimension for the first layer. The second layer dimensions were then
required to be strictly less than the first layer dimensions. See **Supplementary Table 9**
for the values sampled for each hyperparameter. We applied the same random seed
when training each iteration and chose the best model based good overall performance
and lowest validation loss at the end of 150 training epochs. We defined "good" overall
performance as a validation loss curve that was monotonically decreasing over or
constant at the end of training time. We selected a total of 7 models that were the best:
CHERRY without the above changes and 6 that allowed the above implementation
changes and used different genome embeddings. All models were trained with a dropout
of 0.25 after the encoder and after each decoder feedforward layer. We used the ReLU
activation function after each layer.
1590
1591 **Host prediction model evaluation**
1592
iPHoP (v1.3.3) and the models trained in this study were evaluated using the iPHoP
test dataset (see "**Host prediction training and test datasets**"). For the graph-based
models, we considered all test virus-host pairs for link prediction and retained only those
≥75% confidence, which is the minimum for iPHoP, or ≥90% confidence. All virus-host
pairs were considered to enable resolution at each host taxonomic rank. However, we
only evaluated if the true host taxon was among the predictions above the confidence
threshold, so not all predictions were analyzed. Specifically, we computed the proportion
of the iPHoP test viruses whose true host taxon was confidently predicted among all
hosts.
1602
Since there were notably a nontrivial number of viruses in the iPHoP test dataset that
were similar to those in the PST training dataset based on AAI (see "**Average amino acid**
identity (AAI)"), we filtered these viruses out using several similarity cutoffs to evaluate
their effects on our interpretation of the host prediction results. More specifically, the
similarity of each iPHoP test virus to the closest PST training virus was computed as the
harmonic mean of the AAI and the minimum proportion of genes used to compute AAI
relative to each genome.

References

1. Roux, S. *et al.* Ecogenomics and potential biogeochemical impacts of globally abundant ocean viruses. *Nature* **537**, 689–693 (2016).

2. Kieft, K. *et al.* Virus-associated organosulfur metabolism in human and environmental systems. *Cell Rep* **36**, 109471 (2021).

3. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science* **379**, 1123–1130 (2023).

4. Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences* **118**, e2016239118 (2021).

5. Chandra, A., Tünnermann, L., Löfstedt, T. & Gratz, R. Transformer-based deep learning for predicting protein properties in the life sciences. *eLife* **12**, e82819 (2023).

6. Flamholz, Z. N., Biller, S. J. & Kelly, L. Large language models improve annotation of prokaryotic viral proteins. *Nat Microbiol* **9**, 537–549 (2024).

7. Li, B. & Liang, G. ESM-PVP: Identification and classification of phage virion proteins with a large pretrained protein language model and an MLP neural network. 2023.12.29.573676 Preprint at https://doi.org/10.1101/2023.12.29.573676 (2023).

8. Liu, D., Young, F., Robertson, D. L. & Yuan, K. Prediction of virus-host association using protein language models and multiple instance learning. 2023.04.07.536023 Preprint at https://doi.org/10.1101/2023.04.07.536023 (2023).

9. Andrade-Martínez, J. S. *et al.* Computational Tools for the Analysis of Uncultivated Phage Genomes. *Microbiol Mol Biol Rev* **86**, e00004-21.

10. Hwang, Y., Cornman, A. L., Kellogg, E. H., Ovchinnikov, S. & Girguis, P. R. Genomic language model predicts protein co-regulation and function. *Nat Commun* **15**, 2880 (2024).

11. Ji, Y. *et al.* PlasGO: enhancing GO-based function prediction for plasmid-encoded proteins based on genetic structure. 2024.07.03.602011 Preprint at https://doi.org/10.1101/2024.07.03.602011 (2024).

12. Camargo, A. P. *et al.* IMG/VR v4: an expanded database of uncultivated virus genomes within a framework of extensive functional, taxonomic, and ecological metadata. *Nucleic Acids Res* **51**, D733–D743 (2023).

13. Richardson, L. *et al.* MGnify: the microbiome sequence data analysis resource in 2023. *Nucleic Acids Research* **51**, D753–D759 (2023).

14. Lee, J. *et al.* Set Transformer: A Framework for Attention-based Permutation-
Invariant Neural Networks. in *Proceedings of the 36th International Conference on*
Machine Learning 3744–3753 (PMLR, 2019).

15. Arsomngern, P., Long, C., Suwajanakorn, S. & Nutanong, S. Towards Pointsets
Representation Learning via Self-Supervised Learning and Set Augmentation. *IEEE*
Transactions on Pattern Analysis and Machine Intelligence **45**, 1201–1216 (2023).

16. Vaswani, A. *et al.* Attention is All you Need. in *Advances in Neural Information*
Processing Systems vol. 30 (Curran Associates, Inc., 2017).

17. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep
Bidirectional Transformers for Language Understanding. Preprint at
http://arxiv.org/abs/1810.04805 (2019).

18. Schroff, F., Kalenichenko, D. & Philbin, J. FaceNet: A Unified Embedding for Face
Recognition and Clustering. in *2015 IEEE Conference on Computer Vision and*
Pattern Recognition (CVPR) 815–823 (2015). doi:10.1109/CVPR.2015.7298682.

19. Tisza, M. J. & Buck, C. B. A catalog of tens of thousands of viruses from human
metagenomes reveals hidden associations with chronic diseases. *Proceedings of the*
National Academy of Sciences **118**, e2023202118 (2021).

20. Cook, R. *et al.* Hybrid assembly of an agricultural slurry virome reveals a diverse and
stable community with the potential to alter the metabolism and virulence of
veterinary pathogens. *Microbiome* **9**, 65 (2021).

21. Gazitúa, M. C. *et al.* Potential virus-mediated nitrogen cycling in oxygen-depleted
oceanic waters. *ISME J* **15**, 981–998 (2021).

22. Gregory, A. C. *et al.* Marine DNA Viral Macro- and Microdiversity from Pole to Pole.
Cell **177**, 1109-1123.e14 (2019).

23. Parks, D. H. *et al.* GTDB: an ongoing census of bacterial and archaeal diversity
through a phylogenetically consistent, rank normalized and complete genome-based
taxonomy. *Nucleic Acids Research* **50**, D785–D794 (2022).

24. Camarillo-Guerrero, L. F., Almeida, A., Rangel-Pineros, G., Finn, R. D. & Lawley, T.
D. Massive expansion of human gut bacteriophage diversity. *Cell* **184**, 1098-1109.e9
(2021).

25. Gregory, A. C. *et al.* The Gut Virome Database Reveals Age-Dependent Patterns of
Virome Diversity in the Human Gut. *Cell Host Microbe* **28**, 724-740.e8 (2020).

26. Roux, S. *et al.* IMG/VR v3: an integrated ecological and evolutionary framework for
interrogating genomes of uncultivated viruses. *Nucleic Acids Research* **49**, D764–
D775 (2021).

27. Michniewski, S. *et al.* A new family of "megaphages" abundant in the marine environment. *ISME COMMUN.* **1**, 1–4 (2021).

28. ter Horst, A. M. *et al.* Minnesota peat viromes reveal terrestrial and aquatic niche partitioning for local and global viral populations. *Microbiome* **9**, 233 (2021).

29. Brum, J. R. *et al.* Patterns and ecological drivers of ocean viral communities. *Science* **348**, 1261498 (2015).

30. Zvyagin, M. *et al.* GenSLMs: Genome-scale language models reveal SARS-CoV-2 evolutionary dynamics. *The International Journal of High Performance Computing Applications* **37**, 683–705 (2023).

31. Nguyen, E. *et al.* HyenaDNA: Long-Range Genomic Sequence Modeling at Single Nucleotide Resolution. in *Advances in Neural Information Processing Systems* vol. 36 43177–201 (Curran Associates, Inc., 2023).

32. Peng, C., Shang, J., Guan, J., Wang, D. & Sun, Y. ViraLM: Empowering Virus Discovery through the Genome Foundation Model. 2024.01.30.577935 Preprint at https://doi.org/10.1101/2024.01.30.577935 (2024).

33. Shao, B. A long-context language model for deciphering and generating bacteriophage genomes. 2023.12.18.572218 Preprint at https://doi.org/10.1101/2023.12.18.572218 (2024).

34. Traag, V. A., Waltman, L. & van Eck, N. J. From Louvain to Leiden: guaranteeing well-connected communities. *Sci Rep* **9**, 5233 (2019).

35. Liu, X., Jiang, H., Gu, Z. & Roberts, J. W. High-resolution view of bacteriophage lambda gene expression by ribosome profiling. *Proceedings of the National Academy of Sciences* **110**, 11928–11933 (2013).

36. Barrio-Hernandez, I. *et al.* Clustering predicted structures at the scale of the known protein universe. *Nature* **622**, 637–645 (2023).

37. Heinzinger, M. *et al.* Bilingual Language Model for Protein Sequence and Structure. 2023.07.23.550085 Preprint at https://doi.org/10.1101/2023.07.23.550085 (2024).

38. Varadi, M. *et al.* PDBe and PDBe-KB: Providing high-quality, up-to-date and integrated resources of macromolecular structures to support basic and applied research and education. *Protein Science* **31**, e4439 (2022).

39. Gan, L. *et al.* Capsid Conformational Sampling in HK97 Maturation Visualized by X-Ray Crystallography and Cryo-EM. *Structure* **14**, 1655–1665 (2006).

40. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* **630**, 493–500 (2024).

41. Shang, J. & Sun, Y. CHERRY: a Computational metHod for accuratE pRediction of
virus–pRokarYotic interactions using a graph encoder–decoder model. *Briefings in*
Bioinformatics **23**, bbac182 (2022).

42. Roux, S. *et al.* iPHoP: An integrated machine learning framework to maximize host
prediction for metagenome-derived viruses of archaea and bacteria. *PLOS Biology*
21, e3002083 (2023).

43. Pannu, J., Gebauer, S., McKelvey Jr, G., Cicero, A. & Inglesby, T. AI could pose
pandemic-scale biosecurity risks. Here's how to make it safer. *Nature* **635**, 808–811
(2024).

44. Pannu, J. *et al.* Dual-use capabilities of concern of biological AI models. *PLoS*
Comput Biol **21**, e1012975 (2025).

45. Nguyen, E. *et al.* Sequence modeling and design from molecular to genome scale
with Evo. 2024.02.27.582234 Preprint at https://doi.org/10.1101/2024.02.27.582234
(2024).

46. Hayes, T. *et al.* Simulating 500 million years of evolution with a language model.
2024.07.01.600583 Preprint at https://doi.org/10.1101/2024.07.01.600583 (2024).

47. National Academies of Sciences, E., and Medicine. *The Age of AI in the Life*
Sciences: Benefits and Biosecurity Considerations. (The National Academies Press,
2025). doi:10.17226/28868.

48. Center for High Throughput Computing. Center for High Throughput Computing.
(2006) doi:10.21231/gnt1-hw21.

49. Sirén, K. *et al.* Rapid discovery of novel prophages using biological feature
engineering and machine learning. *NAR Genomics and Bioinformatics* **3**, lqaa109
(2021).

50. Nayfach, S. *et al.* CheckV assesses the quality and completeness of metagenome-
assembled viral genomes. *Nat Biotechnol* **39**, 578–585 (2021).

51. Skani enables accurate and efficient genome comparison for modern metagenomic
datasets. *Nat Methods* **20**, 1633–1634 (2023).

52. Van Dongen, S. Graph Clustering Via a Discrete Uncoupling Process. *SIAM J.*
Matrix Anal. Appl. **30**, 121–141 (2008).

53. Camargo, A. P. *et al.* Identification of mobile genetic elements with geNomad. *Nat*
Biotechnol 1–10 (2023) doi:10.1038/s41587-023-01953-y.

54. Larralde, M. Pyrodigal: Python bindings and interface to Prodigal, an efficient
method for gene prediction in prokaryotes. *Journal of Open Source Software* **7**, 4296
(2022).

55. Paszke, A. *et al.* Automatic differentiation in PyTorch. (2017).

56. Fey, M. & Lenssen, J. E. Fast Graph Representation Learning with PyTorch
Geometric. Preprint at http://arxiv.org/abs/1903.02428 (2019).

57. Hendrycks, D. & Gimpel, K. Gaussian Error Linear Units (GELUs). Preprint at
https://doi.org/10.48550/arXiv.1606.08415 (2023).

58. Akiba, T., Sano, S., Yanase, T., Ohta, T. & Koyama, M. Optuna: A Next-generation
Hyperparameter Optimization Framework. in *Proceedings of the 25th ACM SIGKDD*
International Conference on Knowledge Discovery & Data Mining 2623–2631
(Association for Computing Machinery, 2019). doi:10.1145/3292500.3330701.

59. Rand, K., Grytten, I., Pavlovic, M., Kanduri, C. & Sandve, G. K. BioNumPy: Fast and
easy analysis of biological data with Python. 2022.12.21.521373 Preprint at
https://doi.org/10.1101/2022.12.21.521373 (2022).

60. Douze, M. *et al.* The Faiss library. Preprint at
https://doi.org/10.48550/arXiv.2401.08281 (2024).

61. Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence searching
for the analysis of massive data sets. *Nat Biotechnol* **35**, 1026–1028 (2017).

62. Terzian, P. *et al.* PHROG: families of prokaryotic virus proteins clustered using
remote homology. *NAR Genomics and Bioinformatics* **3**, lqab067 (2021).

63. Zhang, Y. & Skolnick, J. TM-align: a protein structure alignment algorithm based on
the TM-score. *Nucleic Acids Res* **33**, 2302–2309 (2005).

64. Bittrich, S., Segura, J., Duarte, J. M., Burley, S. K. & Rose, Y. RCSB protein Data
Bank: exploring protein 3D similarities via comprehensive structural alignments.
Bioinformatics **40**, btae370 (2024).

65. McInnes, L., Healy, J. & Melville, J. UMAP: Uniform Manifold Approximation and
Projection for Dimension Reduction. Preprint at http://arxiv.org/abs/1802.03426
(2020).

66. Kipf, T. N. & Welling, M. Semi-Supervised Classification with Graph Convolutional
Networks. Preprint at http://arxiv.org/abs/1609.02907 (2017).

67. Mihara, T. *et al.* Linking Virus Genomes with Host Taxonomy. *Viruses* **8**, 66 (2016).

68. Morris, C. *et al.* Weisfeiler and Leman Go Neural: Higher-order Graph Neural
Networks. Preprint at http://arxiv.org/abs/1810.02244 (2021).

1778