Title: Dopamine tracks adaptive learning of action representations

Authors: Maxime Come[1,2*], Arnaud Lespart[1*], Aylin Gulmez[1], Loussineh Keshishian[1,2], Joachim Jehl[1,2],

Elise Bousseyrol[1,2], Steve Didienne[1,2], Eleonore Vicq[1,2], Tinaïg Le Borgne[1,2], Alexandre Mourot[1,2],

Philippe Faure[1,2**]

Affiliations:

1. Brain Plasticity Laboratory, CNRS UMR 8249, ESPCI Paris, PSL Research University, Paris, France.

2. Sorbonne Université, Inserm, CNRS, Neuroscience Paris Seine - Institut de Biologie Paris Seine (NPS

- IBPS), 75005 Paris, France.

*These authors contributed equally

** Corresponding author: phfaure@gmail.com

Abstract: (~150 word, here 146)

Flexible decision-making requires not only updating values, but redefining which features constitute an

action in a given context. We recorded nucleus accumbens (NAc) dopamine release while mice navigated

a three-target intracranial self-stimulation foraging task in which outcomes were evaluated under three

distinct reward delivery rules. Despite a constant motor repertoire, dopamine transients reorganized

across contingencies and generalized linear models revealed context-dependent dopamine signal

reflecting action direction, recent outcome-history, or target identity. Reinforcement-learning model

comparison showed that these signatures are best explained by distinct reward prediction errors (RPEs)

defined over different state–action representations, rather than a single fixed model-free scheme. A single

deep reinforcement-learning agent trained by temporal-difference learning, recapitulated both the rule-

specific policies and the corresponding dopamine signature. These results identify NAc dopamine as a

dynamic readout of representation learning, remapping prediction errors onto the task features that define

successful action as contingencies change.

Main text

Introduction

Solving a puzzle often requires more than simply learning from outcomes—it also demands selecting which features matter depending on the context: A toddler might learn to sort objects by color in one game and by shape in another. This ability to flexibly reconfigure which environmental features are used to guide learning is fundamental to intelligent behavior. In computational terms, it requires not only the ability to learn action values from outcomes (reinforcement learning) but also to identify the relevant state space, i.e., the internal representation of the environment from which these values are derived. This process, known as representation learning, is increasingly recognized as a central challenge for neuroscience [1–4]. While reinforcement learning theories formalize how agents update value expectations through reward prediction errors (RPEs), such mechanisms only operate effectively when the agent has selected an appropriate set of task-relevant variables. Critically, selecting the appropriate state representation allows animals to overcome a fundamental computational bottleneck known as the *curse of dimensionality* [5,6]. In natural settings, choices often involve multiple features (e.g., spatial location, action history, outcome probability) that vary across contexts and time. Learning values for all feature combinations becomes intractable for standard reinforcement learning mechanisms, both because of the combinatorial explosion in possible states and because the mapping between features and reward can itself change [7]. Flexible behavior therefore requires a mechanism to extract and update low-dimensional, task-relevant representations—effectively, learning *what counts as an action* in a given context—so that values can be learned efficiently.

Understanding how animals form and update such internal representations is essential for describing flexible behavior, particularly in environments with changing or ambiguous task structures [3]. This issue has gained increasing importance as researchers shift their focus from experiments with a simple task structure to more elaborate tasks [8–12] that more closely resemble natural decision-making, with multiple (and possibly overlapping or competing) features that animals may use as state representations, as well as potentially abrupt changes over time in the state representations being used. Capturing the dynamics of representation change requires dedicated experimental and analytical approaches. While theoretical and behavioral studies have highlighted strategies to cope with high-dimensional environments[7], identifying neural signals that reflect the internal representations used to guide learning and decision-making remains a major challenge. This identification can provide critical insight into which features are effectively used by animals to build a relevant internal model of the world — to predict values, compute errors, and guide goal-directed actions.

Dopamine (DA) is a very well-established substrate to signal value and compute reward prediction error (RPE) [13–24], integrating outcome-related dimensions in a common currency [25–27], and driving reinforcement learning and decision making [19,25,26,28–31]. Because RPEs are necessarily computed within

a specific state and action space, variation of DA transients may reveal which representation the animal

is currently using to compute value. Recent work shows that DA can reflect inference over latent task

states and context dependent expectation [8,32], as well as probability distributions over hidden causes [33],

suggesting sensitivity to abstract structure beyond raw sensory features. However, direct evidence that

DA dynamically reconfigures to track qualitatively different representations as animals shift between

fundamentally distinct task contingencies remains lacking.

Here, we address this gap using a spatial decision-making task in freely moving mice. We imposed three

reward rules [9,10,34,35] *i.e.,* deterministic, sequence-complexity and probabilistic, while keeping the same

physical actions and outcomes, isolating changes in the computational structure of the problem from

changes in motor demands. We combined this behavioral assay with fiber photometry recordings of DA

release in the nucleus accumbens (NAc) and a two-level computational modeling approach. First, we

used interpretable reinforcement learning models with hand-specified state and action features to formally

compare alternative candidate representations and identify which features best explain NAc DA dynamics

in each rule. Second, we trained a deep reinforcement learning (deep RL) agent with a simple feedforward

architecture that learns its own internal representations from minimal inputs, and asked whether a single

network can reproduce both the rule-specific behavioral policies and the rule-dependent modulation of

RPE-like signals. This approach tests whether representation learning—extracting task-relevant features

through error-driven plasticity—provides a parsimonious mechanism for the adaptive structure observed

in DA signals. Together, these analyses show that DA signals dynamically reflect RPEs computed from

context-specific features, revealing the internal model used by the animal in each condition, and that a

deep RL agent trained by temporal-difference learning naturally recapitulates these rule-specific patterns

under a fixed exploration policy. These findings position NAc DA as a real-time indicator of representation

learning, providing a window into how the brain adaptively constructs and updates action-relevant

structure in complex environments.

Each reward context is associated with a specific reward-seeking strategy

Using different versions of a spatial bandit task adapted for mice [9,10,34,35], we aimed to obtain rule-specific

and feature-dependent strategies. In this task, animals learned to navigate between three marked

locations in an open field, each associated with an intracranial self-stimulation (ICSS) of the medial

forebrain bundle (MFB). Mice could not receive two consecutive ICSS at the same location; and therefore,

had to alternate between rewarding locations, resulting in a sequence of movements and binary choices

(i.e., trials) **(Fig. 1A)**. Despite the apparent simplicity of this self-generated, goal-oriented behavior, mice

can use different features of the environment to guide their actions and obtain rewards (**Fig. 1B**). Mice

were initially trained in a deterministic context (*Det*) where all locations consistently delivered ICSS.

Although reward delivery was guaranteed at every location, this context nonetheless required animals to

learn and internalize a simple structural rule: no two consecutive rewards could be obtained at the same

location. As a result, mice had to alternate between the three available targets, producing sequences of

choices constrained by spatial foraging dynamics. Initially, animals explored the environment with irregular

trajectories and variable speeds. With training, they progressively optimized their behavior, developing

stereotyped circular trajectories with minimal U-turns and ballistic movement profiles **(Fig. 2A)**. These

behavioral adaptations reflect the acquisition of a minimal internal model of the task structure, allowing

animals to predict that remaining at the same location would not yield further reward. This is further

supported by the progressive increase in the number of trials **(Fig. S1A)**, reflecting improved efficiency in

task execution throughout learning. Thus, although the Det context does not require complex credit

assignment or value updating, it provides an essential baseline for evaluating the subsequent emergence

of more sophisticated decision strategies when the reward structure becomes ambiguous or non-

deterministic **(Fig 2B, Fig S1B-C)**.

In the complex context (Cplx) **(Fig 2B** middle**)**, reward delivery was determined by the variability in recent

choice patterns **(**see methods and **Fig S2A)**[10], computed relative to the last nine decisions using a

complexity algorithm. This rule requires animals to overcome a key limitation of model-free learning

strategies. In contrast to the Det and Proba rules, where individual actions or spatial locations could be

associated with consistent reward outcomes, the Cplx rule imposes no such direct contingency. Instead,

animals must maximize variability in their behavior over time, independently of any fixed spatial preference

or repeated motor strategy. This configuration renders previously learned policies a priori ineffective, and

creates a setting in which trial identity loses its predictive power **(Fig S2B)**. Importantly, solving the task

does not require tracking a large set of state-action pairs, which would be computationally costly, but

rather adopting a *compressed representation* of the task, in which increasing sequence variability

becomes the feature associated with reward [10]. As such, the Cplx rule constitutes a strong test of

representation learning, assessing whether animals can adapt their internal model when the structure of

reward contingencies is non-trivial and abstract.

In the probabilistic context (Proba), each location was associated with a fixed probability of reward delivery

(p100, p50, or p25) **(Fig. 2B** right**)**. Unlike the Cplx rule, this setting involves stochastic outcomes and

requires animals to integrate probabilistic feedback over time to optimize their choices. Successful

performance relies on estimating expected values for each location and adapting spatial preferences

accordingly. This context thus engages value-based decision-making based on feature-specific learning,

with spatial location becoming the task-relevant dimension. In contrast to Cplx, where individual outcomes

are largely uninformative without reference to prior behavior, the Proba condition allows a more classical

reinforcement learning strategy to emerge — but still requires flexible updating of value representations

as animals recover from the behavioral variability induced by the previous rule [35].

These three distinct reward structures resulted in distinct trajectory patterns **(Fig 2B)**, success rates **(Fig**

2C), and decision-making strategies **(Fig 2D-G)**. In *Det*, animals tended to adopt circular trajectories with

minimal U-turns (~20%) **(Fig 2D)**. In contrast, the *Cplx* rule resulted in random trajectory patterns

characterized by high sequence complexity (**Fig 2E, Fig S2B**). In *Proba*, mice exhibited a bias toward

locations with higher probability of reward delivery **(Fig 2G)**, resulting in a high percentage of U-turns (**Fig**

2D) and a preference for p100 and p50 (**Fig 2F**). We ensured that those differences in decision strategy

were not due to motivation or vigor to perform the three versions of the task **(Fig S3A-B)**. Overall, while

the basic design of the task remained constant, each rule instantiated a distinct causal relationship

between actions and rewards. The evolution of behavior across contexts demonstrates that mice are

capable of extracting and adapting to these contingencies, dynamically modifying their decision

strategies. This makes the task well-suited to track both behavioral flexibility and its neural correlates over

time, in particular through the lens of DA dynamics and internal representation learning.

Nac Dopamine dynamics reveal expectations built upon rule-specific features

We next examined DA release dynamics during the task, across the three rules, using the fluorescent

sensor $GRAB_{DA2m}$ [36] expressed in the lateral shell of the nucleus accumbens (NAc) in a new cohort of

wild-type male mice (**Fig 3A, Fig S4A**). Positive events in DA release occurred upon receiving expected

rewards, whereas negative events were observed when expected rewards were omitted (**Fig 3B-C, Fig**

S4B), indicative of a negative RPE (for simplicity, these events, whether positive or negative, are referred

to as transients). Similar responses were observed while recording Ventral Tegmental Area (VTA) DA

neurons activity with GCaMP in DAT-iCre mice, ensuring consistency in the interpretation of DA dynamics

between release and somatic processes **(Fig S4C-D)**. Analysis of the amplitude distribution of DA

transients (positive and negative) across the different rules showed greater variability compared to

unexpected random stimulation in a rest cage, suggesting an active mechanism related to reward

expectation modulating the DA response, rather than being a mere response to the ICSS (**Fig 3D**). This

modulation is particularly important given that the ICSS directly activates MFB fibers, raising the possibility

of DA release being directly driven by stimulation. The observed variability across task contexts thus

strongly supports a dynamic, expectation-dependent component in DA signaling that add to the electrical

stimulation signal. Additional experiments with unexpected rewards delivered either during the task but

off-target (i.e. when the animal was in-between rewarded locations, **Fig 3E**) or in a rest cage (**Fig S5A-**

D) demonstrated a larger response compared to expected rewards during the task, yet only after

conditioning, further supporting the role of expectation in modulating DA release. We also controlled for a

potential impact of sensor fatigue and found no effect on DA signal when stimulations were given in the

rest cage with varying durations in-between stimulation (matching those observed in the task, typically

from 2s to 7s) **(Fig S5E-F)**. Altogether, these findings confirm that DA positive transients during the task

are not merely driven by the delivery of MFB stimulation, but are modulated by reward expectation. The

amplitude of DA signals varied depending on whether outcomes were expected or not, and this

modulation differed across contexts and over time. These results are consistent with the notion that DA

release reflects reward prediction error (RPE) signals, with positive transients following unexpected

rewards and negative transients after unexpected omissions. Notably, similar ICSS pulses evoked

different responses depending on behavioral context—highlighting that DA signals are influenced by

ongoing task engagement and learning history, rather than being reflexive responses to stimulation alone.

These observations support the use of DA transients as dynamic markers of outcome expectation. To

better understand the basis of these expectations, we next asked: what task features are DA signals

sensitive to, and how does this sensitivity vary across rules? To do this, we applied generalized linear

models (GLMs) to analyze fluctuations in DA transients amplitudes across trials, running separate

regression analyses for each individual mouse at the end of each rule (last two sessions) **(Fig 4A)**. The

predictors included current and previous trial outcomes (P: reward or omission), the specific target where

outcomes occurred (T: locations pA, pB, and pC; or p100, p50 and p25 in Proba), the direction taken (UT:

Forward movement or U-turn) and side (RL: left or right choice). These variables were selected based on

their relevance to the specific constraints of each task rule, and their potential to capture the different

features that mice could use to build internal models of the environment. In the *Det* setting, where all trials

were rewarded, we observed that the key predictor for differentiating trials was direction (UT) but not side

nor target **(Fig 4B).** In the *Cplx* setting, trial outcome accounted for the biggest part of DA variation

(positive for rewards, negative for omissions, **Fig 4C**), with an additional positive effect of previous

outcome (having received an omission at trial n-1 increases DA signal at trial n), regardless of targets,

side or directions. In *Proba*, this effect of previous outcome disappeared, and the target probability (T)

significantly influenced DA variations **(Fig 4D)**.

Overall, the GLM analysis revealed that the primary drivers of DA fluctuations changed depending on the

task setting, with direction, trial outcome, and target probability each playing distinct roles. Direct

examinations of DA transients, categorized by direction, previous outcome or target, supported the

strength of these effects. In *Det*, DA release varied with the direction **(Fig 4E, Fig S6A)** but not with the

target (**Fig S6B**). In *Cplx*, omission on previous trial led to greater reward-induced and shallower omission-

induced transients (**Fig 4F, Fig S6C**), while neither the target nor the direction showed significant effects

(**Fig S6D-E**). At the end of the *Proba* setting, the DA signals were negatively influenced by target

probability, with higher probabilities resulting in smaller positive transients for rewards and deeper

negative transients for omissions **(Fig 4G, Fig S6F)**. Finally, no effect of direction was observed on DA

transients **(Fig S6G)**, and regarding outcome at previous trial, we observed a small effect only for

rewarded trials **(Fig S6H).** Altogether, these results reveal specific patterns in the modulation of DA

transients across task settings. Notably, DA fluctuations were not tied to the same task features across

rules: outcome history dominated in Cplx, direction in Det, and target identity in Proba. This dissociation

indicates that the features driving DA transients are not fixed, but flexibly selected depending on task

structure—supporting the view that phasic DA signals adapt to the relevant contingencies of each context.

NAc dopamine cannot be explained by single model-free reinforcement learning but encodes

state-specific RPEs

GLM analyses demonstrated that DA transients are modulated by distinct task features depending on the

current rule—such as direction in Det, outcome history in Cplx, and target identity in Proba. However,

they do not clarify *how* such features emerge nor whether the signal reflects a genuine reward prediction

error (RPE). To directly test the RPE hypothesis, we used reinforcement learning (RL) models to generate

trial-by-trial RPEs from the actual sequences of choices made by the animals (**Fig S7)**. A critical aspect

of RPE computation is that it depends on the internal representation used to track expected value and on

a well-defined set of competing actions with distinct consequences: from a given state, each choice must

correspond to a different state transition (i.e., reaching a given location, such as pA, is uniquely

determined by one action from that state, rather than being attainable via multiple equivalent actions). For

instance, RPEs can be derived from predictions based on action direction (e.g., U-turn vs. forward), spatial

target (e.g., pA vs. pB), or simply trial outcome regardless of action or location. These different

assumptions correspond to different candidate representations of the task structure. By comparing

theoretical RPEs from each model to recorded DA transients, we can infer which representation best

matches the neural data in each context.

Based on our experimental results, we tested four models reflecting distinct representational schemes

(**Fig. 5A**). Model 1 (M1) used a trial-based representation in which all choices updated a single global

value, ignoring action or target identity. Model 2 (M2) assigned separate values to U-turn and forward

actions, capturing a motor-based distinction. Model 3 (M3) tracked expected value for each target location

independently. Finally, Model 6 (M6) implemented a non-abstracted, fully specified model-free scheme in

which values were associated with each unique state-action pair (e.g., target × direction), reflecting

learning without any structured generalization. All models were implemented using the Rescorla-Wagner

rule to generate trial-by-trial RPEs, which were then used to assess their ability to reproduce key features

of the DA signal in each task context.

In the Deterministic (Det) context, mice developed a directional bias in their choices, favoring forward movements over U-turns, which was mirrored by asymmetries in DA transients (**Fig. 4E**). Consistent with this, models M2 and M6 produced direction-dependent RPEs matching the fiber photometry data (**Fig. 5B–C**), whereas M1 and M3 did not (**Fig. 5C, Fig. S8A**), with M1 even predicting the opposite asymmetry. This supports the idea that, in Det, DA fluctuations reflect value representations incorporating action direction. In the complexity (Cplx) rule, where rewards depended on variability in recent choice sequences, DA transients were modulated by recent outcome history with no dependence on action or spatial features (**Fig. 4F**). Only the trial-based model M1 captured this pattern (**Fig. 5D–E**), whereas models with directional or spatial structure introduced effects not supported by the data (**Fig. 5E, Fig. S8B**), suggesting that animals relied on a simplified, history-tracking representation under Cplx. In the probabilistic (Proba) context, mice progressively developed spatial preferences aligned with fixed reward probabilities, and DA transients showed corresponding target-specific modulation (**Fig. 4G**). Models M3 and M6 reproduced these graded RPE differences across locations (**Fig. 5F–G),** although both tended to introduce additional modulations; among these, only the outcome-history effect (and not direction) was supported experimentally (**Fig. S6H** vs **Fig. S8C**).

Together, these results show that the DA signal does not reflect a unitary, fixed model-free mechanism (M6), but rather encodes context-specific RPEs based on dynamically selected internal representations. This flexible alignment between task structure and neural computation supports a key role for dopamine in representing the features that matter most for decision-making in each context.

A deep RL model captures behavior and Nac dopamine signals

To understand the computational principles that could jointly generate the behavioral trajectories and DA signals observed across rules, we next turned to a deep reinforcement learning (deep RL) approach. Rather than prescribing a specific representation a priori (trial-based, direction-based or spatial), we asked whether a simple neural network trained by RPEs could *learn* appropriate internal representations and reproduce both behavior and DA-like signals. We implemented a minimal feedforward network with one hidden layer trained by temporal-difference learning (Methods, **Fig. 6A**). On each trial, the network received the animal's current location (A, B, or C) and produced five action values (Q-values): two motor actions (Left, Right) and three target-specific actions (go to A, B, or C). Because motor and spatial descriptions can be partially redundant (e.g., "Left" and "go to A" may lead to the same choice), outputs are not mutually exclusive. The model sampled actions from a softmax over Q-values, received reward or omission according to the current rule, and computed a scalar RPE from obtained versus predicted outcome for the chosen action (Methods).

When exposed sequentially to the Deterministic, Complexity and Probabilistic rules, the deep RL agent

reproduced (**Fig. 6B–F**) the main behavioral signatures observed in mice (**Fig. 2C–G**). Success rate

decreased and U-turn rate increased at the Det to Cplx transition and at the Cplx to Proba transition (**Fig.**

6B–C). Sequence complexity increased specifically under Cplx (**Fig. 6D**), and the distribution of target

visits and choice orientation reflected circular foraging in Det, random-like exploration in Cplx, and

exploitation of high-probability targets in Proba (**Fig. 6E–F**). Thus, a single agent, with fixed architecture

and learning rules, recapitulated the diversity of strategies expressed by animals across contexts.

To compare the model's internal "DA" signal with experimental data, we treated the trial-by-trial RPE as

a proxy for NAc DA transients and applied the same GLM analysis to model-generated RPEs as to the

recorded DA signals (**Fig. 6G**). The dominant predictors of model RPEs shifted across rules in close

agreement with the data: direction in Det, current and previous outcomes in Cplx, and target identity

(reward probability) in Proba (**Fig. 6G**), with only a minor contribution of recent history in Proba. Thus,

without explicitly encoding rule identity, the network learned input–action mappings that induced rule-

specific RPE modulations aligned with the representational structure inferred from NAc DA.

Inspection of the network's output usage (**Fig. 6H**) clarified how these representations emerged. In Det,

the agent relied predominantly on a single motor output (Left or Right), implementing a circular policy

(clockwise or counter-clockwise) with few U-turns. In Cplx, Left and Right values converged toward similar

levels and were used more evenly, generating high sequence variability and approximating a value-

independent, randomness-seeking strategy. In Proba, the agent combined spatial and motor outputs to

preferentially visit high-probability targets, yielding stable spatial preferences and frequent U-turns (**Fig.**

6H). Consistent with these learned value landscapes, Det produced a directional asymmetry in RPEs

(smaller RPEs along the dominant direction than for U-turns), Cplx produced stronger positive RPEs after

prior failures, and Proba produced target-dependent RPEs tracking exploitation of p100 and p50.

Together, these results show that a simple deep RL agent trained on the three rules can (i) reproduce the

rule-specific behavioral policies observed in mice and (ii) generate RPE signals whose GLM fingerprints

match rule-dependent NAc DA modulations, supporting the idea that flexible mappings from task features

to RPEs can arise naturally from representation learning. Building on this, we next asked how these DA-

coded representations relate to the *time-resolved* adaptation of choice policies across sessions in both

animals and model.

DA representations track behavioral adaptation across rules

We next asked how the evolution of decision policies across sessions relates to changes in DA dynamics,

and whether this coupling is consistent with the deep RL framework. We assessed the evolution of the

betas from the GLM analysis of DA variations across sessions, along with the evolution of the betas from

the same analysis performed on the RPE generated by the deep RL model (see **Fig. S9A-C** for the
evolution of behavior across session). By construction, these beta coefficients capture how strongly the
internal value representation differentiates between options or outcomes, and can thus be directly related
to evolution of choice bias and success rate.

In the Deterministic rule, the biased circularity profile could emerge from a value discrimination between
two directional actions (right vs left), as suggest the evolution of βRL across sessions and its tendency to
correlate with the circularity profile of mice (**Fig. 7A–B**). This behavior-RPE structure is strongly predicted
by the deep RL model (**Fig. 7C–D**).

Upon transition to the Complexity rule, both mice and the deep RL agent initially experienced high
omission rates because the previously optimal circular policy produced low sequence variability (**Fig.
S9B**). Mice improved performance by increasing U-turns and redistributing them across trials to generate
more variable sequences. Although U-turns could locally increase reward probability (**Fig. S10A**), animals
did not adopt a simple "U-turn after omission" heuristic; instead, performance improved through a more
global reorganization of sequences (**Fig. S10B–D**). The deep RL agent progressively equilibrate the value
of the competing actions R and L, inducing a high entropy policy. As for the mice, this results in a
redistribution of U-turns across sequences and a progressive increase of success rate. Notably, the
emergence of a high-entropy policy did not require changes in the softmax exploration temperature β,
which was held fixed. DA variations remained dominated by recent outcome history (larger responses
after a prior reward than after a prior omission), with a tendency of this effect to decrease across sessions,
and no correlation with improvements in sequence complexity or success rate (**Fig. 7E–F, Fig. S10E–F**).
Regarding the deep RL agent: the history dependent RPE is already present since the start of complexity
and decrease across sessions (**Fig. 7G–H**). The model provides a network-level mechanism for this effect
with the presence of the hidden-layer which makes learning not confined to the selected output: updates
propagate through common units and can partially influence other actions. Deeper simulation analysis
demonstrate that this property could not be explained with a 1-layer model (**Fig S11**). Regarding the
correlation between history effect and complexity of sequence of the deep RL agent (**Fig 7H**), it results
from progressive evolution of both variable across sessions and not from a causal relationship. Thus, in
this context, DA transients reflect a history-dependent RPE based on an abstract contingency (sequence
variability), while policy adaptation proceeds through reconfiguration of representations and values rather
than through DA-driven tuning of the softmax exploration temperature β.

The situation changed in the Probabilistic rule. Mice again exhibited an initial drop-in reward rate, now
because targets differed in reward probability and the previously acquired variable policy was not yet
aligned with these probabilities (**Fig. S9C**). Across sessions, animals increased success rate by biasing
choices toward higher-probability targets, at the cost of more U-turns and more stereotyped trajectories.

In parallel, dependance of DA signal to target identity grew over time, and sessions with stronger
sensitivity of DA to target identity exhibited stronger preference for high-probability targets (**Fig. 7I–J**).
The deep RL agent mirrored these dynamics: under Proba, learned values diverged across targets,
producing increased RPE sensitivity to target identity and a progressive shift toward exploitation (**Fig. 7K–**
L). Across both Cplx and Proba, β remained constant, indicating that apparent changes in
"exploration/exploitation tradeoff" can arise from changes in learned value landscapes and internal
representations rather than from explicit modulation of a global exploration parameter (β).
341

Discussion
By recording dopamine (DA) release in the nucleus accumbens (NAc) while mice adapted to multiple
reward rules in a single spatial task, we asked how a canonical reinforcement-learning variable—reward
prediction error (RPE)—is implemented when the relevant state space itself must change. Across three
reward contexts, we found that DA transients did not simply encode a fixed scalar "value error" tied to
physical actions or locations. Instead, DA responses aligned with different internal descriptions of behavior
in each rule: direction-based in the Deterministic context, history-based in the Complexity context, and
probability-based in the Probabilistic context. By combining GLM-based model comparison, classical RL
models with hand-specified state features, and a deep RL agent that learns its own internal
representations, we show that NAc DA behaves as an RPE computed over flexible, learned action
representations, rather than over a rigid, experimenter-defined state space.
First, our results confirm and extend a consistent pattern observed across the dopamine literature,
wherein phasic DA carries information regarding both the obtained value and the RPE upon delivery or
omission of an expected reward [8,13–22]. It remains unclear whether this response stems from direct
stimulation of MFB DA fibers, resulting in DA release in the NAc, or whether it reflects a subjective value
mediated by circuits beyond the DA system alone [37,38]. While ICSS evoked positive transients across
contexts, their amplitude was strongly modulated by expectation. Unexpected rewards and omissions
triggered positive and negative transients respectively, consistent with classical RPE encoding [8,9,22,32].
Thus, our data reinforce the view that mesolimbic DA provides a relatively low-dimensional teaching signal
that can be read as a real-time RPE, even in freely moving animals performing spatially extended tasks
[8,22,27,39,40]. At the same time, the rule-dependent structure of DA modulation shows that this RPE is not
defined over a fixed "trial" or "arm" variable, but over an internal representation that can be reconfigured
as the task demands change.
Second, mice demonstrated substantial flexibility not only in their policy but also in the internal task-
state/action representation used for value learning. In the Deterministic rule, optimal performance was
achieved by adopting a stereotyped circular policy with few U-turns, and NAc DA was best explained by

an RPE defined over movement direction (U-turn vs forward), consistent with extensive evidence that

phasic dopamine in the nucleus accumbens reports reward prediction errors for well-learned action-

outcome contingencies[41] . In the Complexity rule, by contrast, the same circular policy became

detrimental because it produced low sequence variability. Mice recovered reward rate by increasing U-

turns and distributing them across trials, thereby raising global sequence complexity[10] . This aligns with

operant-learning literature showing that behavioral variability can itself be shaped by reinforcement

contingencies and brought under contextual control[42,43] . Strikingly, in this rule DA no longer differentiated

directions or targets, but instead was best accounted for by an RPE defined over recent outcome history,

consistent with an abstract contingency[33,44] that rewarded variability. Finally, in the Probabilistic rule,

animals exploited fixed reward probabilities associated with locations: they biased choices towards high-

probability targets, accepting more U-turns and more stereotypy. In this context, NAc DA reflected an

RPE over target identity and reward probability, with dependence of DA RPEs to locations growing in

parallel with the behavioral preference for high-probability sites, and consistence with classic work

showing that dopamine signals incorporate reward probability/uncertainty and subjective value[8,9,25,26].

Together, these observations indicate that mice not only adjust policy, but also switch which features of

actions and outcomes are treated as the relevant "state" variables for prediction and error computation, a

core idea in task-state/representation learning frameworks [1,6,45] , and that NAc dopamine tracks these

representation shifts, consistent with the view that RPE-like teaching signals can accompany (and

potentially drive) adaptive reconfiguration of learned representations[46] .

Beyond establishing a rule-dependent mapping between task features and DA-like RPEs, the deep RL

agent offers a minimal mechanistic account of *how* such mappings can emerge when actions admit

partially redundant descriptions. In our architecture, motor (Left/Right) and spatial ("go to A/B/C") outputs

can lead to the same choice, creating a credit-assignment problem in which the agent must attribute

outcomes to one of several partially overlapping action descriptions[47,48] . This simple "credit assignment

under redundancy" naturally produces the stereotyped circular policy in the Deterministic rule: value

concentrates on one directional output, making alternative choices effectively low-value deviations, and

generating the directional RPE asymmetry that matches the DA U-turn effect. Crucially, the same

architecture can also reproduce the Complexity signature—where DA is best captured by a history-

dependent, trial-level representation—because learning is not confined to the chosen output. Weight

updates propagate through shared hidden units, so that updating the value of a selected action also

partially updates the values of other, unchosen actions that rely on overlapping hidden-layer features. As

a result, the hidden layer rapidly comes to encode a coarse estimate of recent reward rate (or global

success), which is then broadcasted to multiple outputs. This provides a natural explanation for why the

"previous omission lead to larger subsequent reward transient" effect is present from the beginning of the

Complexity rule, both in the model and in DA recordings, without requiring a slow, rule-specific

accumulation process. More broadly, these results support a view in which dopaminergic teaching signals

are computed over *learned* internal representations rather than fixed experimenter-defined state spaces.

In the deep RL agent, plasticity in hidden layers both constructs such representations and shapes the

ensuing RPE signal, suggesting a plausible biological mechanism: the same dopaminergic error signal

could, via synaptic plasticity at multiple stages, progressively tune upstream networks to represent

precisely those features that best predict reward in a given context[47] . An important implication is that

individual "profiles" within a rule may emerge downstream of this shared rule-level representation, through

biased readout and attribution over the learned action manifold—an idea that can be directly tested by

quantifying whether hidden-layer activity is more strongly structured by rule identity than by within-rule

phenotypes.

The joint analysis of the evolution of dependence of DA RPEs of mice and RPE of the model to predictors

across sessions further constrains how we should think about DA's role in exploration and policy

adaptation. In the Complexity rule, mice increased sequence variability and improved performance without

developing any systematic DA dependence to specific actions, but displayed DA dependence to recent

reward vs omission. The deep RL agent exhibited the same qualitative pattern: it recovered reward rate

by making repetitive sequences predict low return and by increasing the entropy of its policy, yet did so

without any change in the softmax temperature β, which was held constant across rules. This implies that

the apparent increase in "exploration" in Cplx can emerge from changes in representations and value

estimates, rather than from a dedicated DA-driven modulation of a global exploration parameter.

Conversely, in the Probabilistic rule, both mice and model showed a tight coupling between the growth of

DA-RPE dependence to targets and the consolidation of an exploitative policy favoring high-probability

locations. Here, value-based asymmetries in DA (or RPE) and policy refinement evolved in parallel, again

under a fixed β in the model, because the learned value landscape became more uneven. These

comparisons argue that at least part of the DA–behavior relationship in our data can be explained by

standard RPE-based value learning over flexible state representations, without invoking an explicit DA

control signal for exploration temperature. This does not preclude additional, slower or circuit-specific

mechanisms for tuning exploration–exploitation balance[34,49,50] , but it suggests that they are not required

to account for the pattern we observe.

Several limitations of our approach point to directions for future work. First, fiber photometry in NAc

measures a population-averaged DA signal and cannot resolve heterogeneity across projection-defined

subpopulations or across core vs shell. Different subsets of DA inputs may carry distinct RPEs or

emphasize different state features[23,51,52] , which our bulk signal effectively averages. Second, our task

manipulates reward structure in a relatively simple, discrete set of rules; in more naturalistic

environments[8,53] , changes in contingencies may be more gradual or partially observable, and representation learning may involve hierarchical or belief-state-like structures that go beyond the models tested here. Third, our deep RL agent is intentionally minimal and does not include mechanisms such as meta-learning of learning rates, explicit uncertainty monitoring, or interactions with other neuromodulatory systems. Extending the framework to tasks with richer temporal structure or partial observability, and to models in which DA interacts with noradrenergic or cholinergic signals, will be essential to understand how different neuromodulators jointly shape internal models and exploration strategies.

In conclusion, our findings reveal that dopaminergic signals in the NAc carry a robust RPE-like teaching signal, but that this error is anchored to an internal, learned description of action and context that changes across reward rules. Behavioral adaptation in our task involves both policy changes and representation changes, and NAc DA tracks these representation changes in a way that can be captured by a single deep RL architecture. These results support a view of DA as a neural marker of representation learning in complex environments: not merely reporting errors in a fixed state space, but reporting errors in whatever task representation the brain has currently constructed to solve the problem at hand.

References

1. Niv, Y. Learning task-state representations. Nat Neurosci 22, 1544–1553 (2019).

2. Sutton, R. S. & Barto, A. G. Reinforcement Learning. (MIT Press, 1998).

3. Nakahara, H. & Hikosaka, O. Learning to represent reward structure: A key to adapting to complex environments. Neuroscience Research 1–7 (2012) doi:10.1016/j.neures.2012.09.007.

4. Gershman, S. J., Norman, K. A. & Niv, Y. Discovering latent causes in reinforcement learning. Curr. Opin. Behav. Sci. 5, 43–50 (2015).

5. Soltani, A. & Koechlin, E. Computational models of adaptive behavior and prefrontal cortex. Neuro-psychopharmacology 47, 58–71 (2021).

6. Gershman, S. J. & Niv, Y. Learning latent structure: carving nature at its joints. Curr. Opin. Neurobiol. 20, 251–256 (2010).

7. Farashahi, S., Rowe, K., Aslami, Z., Lee, D. & Soltani, A. Feature-based learning improves adaptability without compromising precision. Nat. Commun. 8, 1768 (2017).

8. Krausz, T. A. et al. Dual credit assignment processes underlie dopamine signals in a complex spatial environment. Neuron (2023) doi:10.1016/j.neuron.2023.07.017.

9. Bousseyrol, E. et al. Dopaminergic and prefrontal dynamics co-determine mouse decisions in a spatial gambling task. Cell Rep. 42, 112523 (2023).

10. Belkaid, M. et al. Mice adaptively generate choice variability in a deterministic task. Communications Biology 3, 1–9 (2020).

11. Beron, C. C., Neufeld, S. Q., Linderman, S. W. & Sabatini, B. L. Mice exhibit stochastic and efficient action switching during probabilistic decision making. Proc National Acad Sci 119, e2113961119 (2022).

12. Tervo, D. G. R. et al. Behavioral variability through stochastic choice and its gating by anterior cingu-
late cortex. Cell 159, 21–32 (2014).

13. Montague, P. R., Dayan, P. & Sejnowski, T. J. A framework for mesencephalic dopamine systems
based on predictive Hebbian learning. The Journal of neuroscience : the official journal of the Society for
Neuroscience 16, 1936–1947 (1996).

14. Schultz, W., Dayan, P. & Montague, P. R. A Neural Substrate of Prediction and Reward. Science
275, 1593–1599 (1997).

15. Eshel, N., Tian, J., Bukwich, M. & Uchida, N. Dopamine neurons share common response function
for reward prediction error. Nature Neuroscience 19, 479–486 (2016).

16. Bayer, H. M. & Glimcher, P. W. Midbrain dopamine neurons encode a quantitative reward prediction
error signal. Neuron 47, 129–141 (2005).

17. Tobler, P. N., Fiorillo, C. D. & Schultz, W. Adaptive coding of reward value by dopamine neurons.
Science (New York, N.Y.) 307, 1642–1645 (2005).

18. Schultz, W. Getting formal with dopamine and reward. Neuron 36, 241–263 (2002).

19. Steinberg, E. E. et al. A causal link between prediction errors, dopamine neurons and learning. Na-
ture Neuroscience 1–10 (2013) doi:10.1038/nn.3413.

20. Roesch, M. R., Calu, D. J. & Schoenbaum, G. Dopamine neurons encode the better option in rats
deciding between differently delayed or sized rewards. Nature Neuroscience 10, 1615–1624 (2007).

21. Kutlu, M. G. et al. Dopamine signaling in the nucleus accumbens core mediates latent inhibition.
Nat. Neurosci. 25, 1071–1081 (2021).

22. Mohebi, A. et al. Dissociable dopamine dynamics for learning and motivation. Nature 570, 65–70
(2019).

23. Jong, J. W. de, Liang, Y., Verharen, J. P. H., Fraser, K. M. & Lammel, S. State and rate-of-change
encoding in parallel mesoaccumbal dopamine pathways. Nat. Neurosci. 27, 309–318 (2024).

24. Gershman, S. J. et al. Explaining dopamine through prediction errors and beyond. Nat. Neurosci. 1–
11 (2024) doi:10.1038/s41593-024-01705-4.

25. Lak, A., Stauffer, W. R. & Schultz, W. Dopamine prediction error responses integrate subjective
value from different reward dimensions. Proceedings of the National Academy of Sciences of the United
States of America 111, 2343–2348 (2014).

26. Fiorillo, C. D., Tobler, P. N. & Schultz, W. Discrete coding of reward probability and uncertainty by
dopamine neurons. Science (New York, N.Y.) 299, 1898–1902 (2003).

27. Hamid, A. A. et al. Mesolimbic dopamine signals the value of work. Nature Neuroscience (2015)
doi:10.1038/nn.4173.

28. Bromberg-Martin, E. S., Matsumoto, M. & Hikosaka, O. Dopamine in motivational control: rewarding,
aversive, and alerting. Neuron 68, 815–834 (2010).

29. Bromberg-Martin, E. S. & Hikosaka, O. Midbrain dopamine neurons signal preference for advance
information about upcoming rewards. Neuron 63, 119–126 (2009).

30. Coddington, L. T. & Dudman, J. T. The timing of action determines reward prediction signals in iden-
tified midbrain dopamine neurons. Nat Neurosci 21, 1563–1573 (2018).

31. Berke, J. D. What does dopamine mean? Nat Neurosci 21, 787–793 (2018).

32. Blanco-Pozo, M., Akam, T. & Walton, M. E. Dopamine-independent effect of rewards on choices
through hidden-state inference. Nat. Neurosci. 1–12 (2024) doi:10.1038/s41593-023-01542-x.

33. Starkweather, C. K., Babayan, B. M., Uchida, N. & Gershman, S. J. Dopamine reward prediction errors reflect hidden-state inference across time. Nat. Neurosci. 20, 581–589 (2017).

34. Dongelmans, M. et al. Chronic nicotine increases midbrain dopamine neuron activity and biases individual strategies towards reduced exploration in mice. Nat Commun 12, 6945 (2021).

35. Naudé, J. et al. Nicotinic receptors in the ventral tegmental area promote uncertainty-seeking. Nature Neuroscience 19, 471–478 (2016).

36. Sun, F. et al. Next-generation GRAB sensors for monitoring dopaminergic activity in vivo. Nat. methods 17, 1156–1166 (2020).

37. Trujillo-Pisanty, I., Conover, K., Solis, P., Palacios, D. & Shizgal, P. Dopamine neurons do not constitute an obligatory stage in the final common path for the evaluation and pursuit of brain stimulation reward. PLoS ONE 15, e0226722 (2020).

38. Millard, S. J. et al. Cognitive representations of intracranial self-stimulation of midbrain dopamine neurons depend on stimulation frequency. Nat. Neurosci. 27, 1253–1259 (2024).

39. Coddington, L. T., Lindo, S. E. & Dudman, J. T. Mesolimbic dopamine adapts the rate of learning from action. Nature 1–9 (2023) doi:10.1038/s41586-022-05614-z.

40. Kutlu, M. G. et al. Dopamine release in the nucleus accumbens core signals perceived saliency. Curr. Biol. 31, 4748-4761.e8 (2021).

41. Hart, A. S., Rutledge, R. B., Glimcher, P. W. & Phillips, P. E. M. Phasic dopamine release in the rat nucleus accumbens symmetrically encodes a reward prediction error term. Journal of Neuroscience 34, 698–704 (2014).

42. Grunow, A. & Neuringer, A. Learning to vary and varying to learn. Psychon B Rev 9, 250–258 (2002).

43. Neuringer, A. Operant variability: evidence, functions, and theory. Psychonomic bulletin & review 9, 672–705 (2003).

44. Babayan, B. M., Uchida, N. & Gershman, Samuel. J. Belief state representation in the dopamine system. Nat. Commun. 9, 1891 (2018).

45. Langdon, A. J., Song, M. & Niv, Y. Uncovering the 'state': Tracing the hidden state representations that structure learning and decision-making. Behav. Process. 167, 103891 (2019).

46. Alexander, W. H. & Gershman, S. J. Representation learning with reward prediction errors. arXiv (2021) doi:10.48550/arxiv.2108.12402.

47. Lillicrap, T. P., Santoro, A., Marris, L., Akerman, C. J. & Hinton, G. Backpropagation and the brain. Nat. Rev. Neurosci. 21, 335–346 (2020).

48. Richards, B. A. et al. A deep learning framework for neuroscience. Nat Neurosci 22, 1761–1770 (2019).

49. Cinotti, F. et al. Dopamine blockade impairs the exploration-exploitation trade-off in rats. Scientific Reports 9, 6770 (2019).

50. Beeler, J. A., Daw, N., Frazier, C. R. M. & Zhuang, X. Tonic dopamine modulates exploitation of reward learning. Frontiers in Behavioral Neuroscience 4, 170 (2010).

51. Lerner, T. N., Holloway, A. L. & Seiler, J. L. Dopamine, Updated: Reward Prediction Error and Beyond. Curr. Opin. Neurobiol. 67, 123–130 (2021).

52. Parker, N. F. et al. Reward and choice encoding in terminals of midbrain dopamine neurons depends on striatal target. Nat. Neurosci. 19, 845–854 (2016).

53. Solié, C. et al. Dopaminergic mechanisms of dynamical social specialization in mouse microsocie-
ties. bioRxiv 2025.02.10.637303 (2025) doi:10.1101/2025.02.10.637303.

54. Khabou, H. et al. Noninvasive gene delivery to foveal cones for vision restoration. JCI insight 3,
D358 (2018).

55. Sun, F. et al. A Genetically Encoded Fluorescent Sensor Enables Rapid and Specific Detection of
Dopamine in Flies, Fish, and Mice. Cell 174, 481-496.e19 (2018).

56. Choi, V. W., Asokan, A., Haberman, R. A. & Samulski, R. J. Production of recombinant adeno-asso-
ciated viral vectors. Current protocols in human genetics Chapter 12, Unit 12.9-12.9.21 (2007).

57. Aurnhammer, C. et al. Universal real-time PCR for the detection and quantification of adeno-associ-
ated virus serotype 2-derived inverted terminal repeat sequences. Human gene therapy methods 23,
18–28 (2012).

58. Lempel, A. & Ziv, J. On the Complexity of Finite Sequences. IEEE Trans. Information Theory 22,
75–81 (1976).

Acknowledgements:

This work was supported by the Centre National de la Recherche Scientifique CNRS UMR 8246 and 8249, INSERM U1130. We are grateful to the animal facilities (IBPS Sorbonne University) and Otilia de Oliveira and Emilie Tubeuf at ESPCI animal facilities. We also thank Jérémie Naudé and Clément Solié for their comments on the manuscript. We thank Deniz Dalkara and the viral core facility at the Vision Institute (Paris) for production of the AAVs. This work has received support under the Major Research Program of PSL Research University "PSL-Neuro" launched by PSL Research University and implemented by ANR (ANR-10-IDEX-0001). Our team is affiliated to DIM C-BRAINS, funded by the Conseil régional d'Ile-de-France.

Fundings:

The Foundation for Medical Research (FRM, Equipe FRM DEQ2013326488 to P.F, PhD fellowhsip ECO201806006688 to J.J., Fourth-year PhD fellowship FDT201904008060 to MC), the French National Cancer Institute Grant TABAC-19-020 and SPA-21-002 (to P.F.). French state funds managed by the ANR (ANR-19-CE16-0028 Bavar to PF, ANR-23-CE37-0017 VarSeek to PF). Memolife Labex, fourth-year PhD fellowship (to JJ and EV).

Authors contributions:

Conceptualization: MC, PF

Injection and implantation surgeries: MC

Behavioral experiments: MC, AG, LK

Fiber photometry recordings: MC, AG

Intracardiac perfusions and immunohistochemistry: MC, AG, EV, TLB

Data analysis: MC, AL, PF

Modelling: MC, AL, PF

Deep RL: AL, PF

Setups development: MC, JJ, AM, EB, SD, PF

Funding acquisition: PF

Writing - original draft: MC, AL, PF

Writing - review and editing: MC, TLB, AM, PF

Competing interests:

Authors declare that they have no competing interests

607   **Figure and Figure legends**

A

ICSS (reward)

ABACBA...

5min session

B

Action selection could rely on:

A
B
C

or

Fwd
Uturn

or

Left
Right

Figure 1

610 **Fig 1. Decision making context: (A)** Three explicit locations in an open field are associated with a
611 possibility of intracranial self-stimulation (ICSS). Two stimulations could not be delivered consecutively in
612 the same location, therefore animals learned to alternate between target. Mice perform successive binary
613 choices to collect ICSS rewards. **(B)** Choice could rely on various overlapping sets of actions.
614
615

Figure 2

Fig. 2. Mice display distinct reward seeking strategies adapted to each rule. A. (Left) Trajectories
throughout conditioning and (Right) Speed profiles around ICSS in the deterministic context (First and
Last sessions). **B.** Three reward delivery rules were successively proposed: Deterministic (*Det*) where all
trials were rewarded (P=100%), Complexity (*Cplx*), where trials are rewarded based on sequence
variability, and Probabilistic (*Proba*), with each target associated to a given probability (P=25%, 50%, and
100%). **C-E** Comparison of success rate, sequence complexity and Uturn rate reveals distinct reward
seeking strategies across contexts. **F.** Locally, a mouse on one location (ex: p_A) has the choice between
the two other points (ex: p_B vs p_C), and therefore performs a gamble computed as $g_A = P(p_B|p_A)$. g>50%
corresponds to clockwise rotation for *Det* and *Cplx*, and to preference for highest probability of reward for
Proba. Proportion of target visits and choice preference at each gamble show a bias for circular foraging
in Det, exploitation in *Proba*, and randomness in *Cplx*. Data are shown as individual points, and mean
±sem. N=49 mice (23 males and 26 females).
628
629

Figure 3

Fig. 3: NAc DA release dynamics reveal expectations built upon rule-specific features. A. Schematic of the experimental design to record DA release during the task with chronic fiber photometry. **B.** Representative signal from one 5-min session with rewards (green) and omissions (red). **C.** For the same example session, signal is time-locked on location entry (t=0) and averaged. Rewards induce peaks and omissions induce dips of DA release. **D.** Density distribution of averaged DA variations (Peak) for rewards and omissions for the last two sessions of Det, Cplx or Proba, and for random stimulations in the rest cage (performed on last day of Det). **E.** After conditioning, mice were randomly and unexpectedly stimulated during the task outside of the rewarded zones (off-target), triggering DA peaks of greater amplitude.

Figure 4

Fig. 4: Defining sources of DA variations. A Each trial is defined by predictors (outcome received, previous outcome received, trajectory chosen to reach target, and target chosen) to fit DA amplitude using GLMs. **B-D.** GLM results at the end of Det, Cplx and Proba. Features explaining DA variations vary across contexts. **E-G.** Direct analysis of DA transients locked on those significant features (Uturn vs Fwd in Det ; reward vs omission at previous trial in Cplx ; p25 vs p50 vs p100 in Proba). Data are shown as individual points, and/or mean ±sem. n is the number of trials, N the number of mice in each condition.

Figure 5

Fig. 5: DA signal embeds an RPE component, modelled from distinct value representations
specific to each rule. A. Mice choice sequences were taken to train Reinforcement Learning (RL)
algorithms, testing three possible action representations to update values and compute corresponding
RPEs. Model 1 (M1) treats all trials equally with fluctuating { V_{Any} }. M2 updates a set of two distinct values
{ V_{Fwd} ; V_{Uturn} }. A spatial model (M3) computes three independent values for each target { V_{pA} ; V_{pB} ; V_{pC}
}. M6 computes 6 independent value considering forward and Uturn for each position A, B or C. We then
trained another GLM assuming DA = $V_{obtained}$ + RPE, with trial RPEs generated from M1, M2, M3 and M6.
B-G. Models reproducing RPEs that explained DA variations vary across contexts. **B.** In M2-Det,
convergence toward 1 is slower for Uturns, leading to higher RPE_{Uturn} and reproducing DA data. **C.** M2
and M6 reproduce RPE data but not M1**. D.** In M1-Cplx, V_{Any} is always updated and fluctuates around
mean success rate. Plotting corresponding RPEs regarding current and previous outcomes mimic DA
data in M1 but not M6. **F-G.** In M3-Proba, value of each target converges and then fluctuates around its
probability, and corresponding RPEs reproduce DA data in M3 and M6. Data are shown as individual
points, and/or mean ±sem. n is the number of trials, N the number of mice in each condition.
663
664

Figure 6

Fig. 6: A deep RL network captures behavior and DA signals A. Schematic of the deep RL network, learning rule and sequence generation. The network outputs the values of a set of five actions: R: right; L: left; A, B and C: going to point A, B and C respectively. **B-D.** Comparison across rules of **B.** success rate, **C.** sequence complexity and **D.** Uturn rate **E.** Proportion of target visits **F.** Choice preference at each gamble. The latter shows a bias for circular foraging in Det, randomness in *Cplx* and exploitation in *Proba*. For Det and Cplx, the figure displays the preference for going right at each location, and for proba it displays the preference for the highest-value option at each location. **G.** Regression coefficients of a GLM at the end of Det, Cplx and Proba. Abreviations stands for: R: reward/omission; UT: forward/uturn; RL: right/left; T:target; P: previous trial's reward/omission. **H**: % of chosen action among the five output of the network. Data are shown as individual points for each simulation, and the bars represent the mean. N=50 simulations.

Figure 7

Figure 7: Deep neural network shows similar performance and learning trajectories than mice

behavior. A, E, I. Evolution of dependence of DA RPEs to principal predictor variable within each rule: **A.**

'right/left' (RL) in Det, **E.** previous outcome (P) in Cplx, **I.** 'target' (T) in proba. The evolution is shown

across sessions spent in each rule with division of sessions into three categories 'start', 'mid' and 'last'

which correspond to different stages in the training schedule. **C, G and K** show the same analysis

performed on the deep RL simulations data. In figures **B,D,F,H,J,L** each data point represent a mouse

(**B,F,J**) or a deep RL simulation (**D,H,L**) at one of the three stages of training schedule. **B, D.** In Det, linear

regression between circularity index and dependence of RPEs to 'right/left' (RL) for mice (**B**) and deep

RL simulation (**D**). **F, G.** In Cplx, linear regression between sequence complexity and dependence of

RPEs to 'previous outcome' (P), for mice (**F**) and deep RL simulation (**G**). **J, L.** In Proba, linear regression

between exploitation index and dependence of RPEs to 'target' (T) for mice (**J**) and deep RL simulation

(**L**).

Materiel and Methods

EXPERIMENTAL MODEL AND SUBJECT DETAILS

Experiments were performed on adult C57Bl/6Rj wild-type mice (Janvier Labs, France). Both male and

female mice, weighing 20-30 g and 8 weeks old at the time of surgery, were used for behavioral

experiments. Only male mice were used in the GRAB$_{DA}$ fiber photometry cohorts. For cre-dependent

GCaMP experiments, DATiCre male mice were used. All mice were kept in an animal facility where

temperature (20 ± 2°C) and humidity were automatically monitored and a circadian 12/12h light–dark

cycle was maintained. All experiments were performed in accordance with the recommendations for

animal experiments issued by the European Commission directives 219/1990, 220/1990, and 2010/63,

and approved by Sorbonne University and ESPCI.

METHOD DETAILS

AAV production: AAVs for GRAB$_{DA2m}$ (pXR1-AAV-hSyn-GRAB-DA4.4) were produced as previously

described [54] (using the cotransfection method from plasmids generously provided by Dr. Yulong Li [36,55]

and purified by iodixanol gradient ultracentrifugation[56]). AAV vector stocks were tittered by quantitative

PCR (qPCR) [57] using SYBR Green (Thermo Fischer Scientific). AAV vectors for GCaMP6f (AAV1-EF1a-

DIO-GCaMP6f-P2A-nls-dTomato) and GCaMP7c (pGP-AAV1-syn-FLEX-jGCaMP7c variant 1513-

WPRE) were directly ordered from Addgene.

Intracranial self-stimulation (ICSS) electrode implantation: Male and female WT mice were

anaesthetized with a gas mixture of oxygen (1 L/min) and 1-3% of isoflurane (Piramal Healthcare, UK)

and then placed into a stereotaxic frame (Kopf Instruments, CA, USA). After the administration of a local

anesthetic (Lurocain, 0.1 mL at 0.67 mg/kg), a median incision revealed the skull, which was drilled at the

level of the median forebrain bundle (MFB). For ICSS, a bipolar stimulating electrode (PlasticOne 2

channels, stainless steel, 10 mm) was then implanted unilaterally (left or right, randomized) in the brain

using the following stereotaxic coordinates (from bregma according to Paxinos atlas): AP −1.4 mm, ML

±1.2 mm, DV −4.8 mm from the brain). Dental cement (SuperBond, Sun Medical) was used to fix the

implant to the skull. An analgesic solution of buprenorphine at 0.015 mg/L (0.1 mL/10 g) was delivered

prior to awakening from the surgery and, if necessary, the following recovering days. After stitching, mice

were placed back in their home-cage and had a minimum of 5 days to recover from surgery. The efficacy

of electrical stimulation was verified through the rate of conditioning during the deterministic setting (see

Intracranial Self Stimulation (ICSS) bandit task). Out of the 54 mice implanted (27 for each sex), 49 were

included in the results (23 males and 26 females).

Virus injections and fiber photometry recordings: 3 cohorts of WT male mice (total of 24) were anaesthetized (Oxygen 1 L/min, Isoflurane 1–3%) and implanted with an ICSS electrode as described above. They were then injected unilaterally (randomized left/right side and ipsi/contralateral side regarding the ICSS electrode) in the NAc lateral shell (1 μL, coordinates from bregma: AP +1.45mm; ML ±1.55mm; DV −4.05mm from the skull) with an adeno-associated virus [36,55] to express GRAB$_{DA2m}$. An optical fiber (200 μm core, NA = 0.39, Thor Labs) coupled to a metallic ferule (1.25 mm) was implanted 100 μm above the injection site in target region and cemented to the skull with blackened cement. 5 DATiCre male mice followed the same procedures for GCaMP experiments in the VTA (1 μL, coordinates from bregma: AP -3.10mm; ML ±0.50mm; DV −4.20mm from the brain), 3 of them with GCaMP7c and 2 with GCaMP6f. Viral expression typically took 10-15 days to achieve a satisfying signal and lasted for up to 3 months. However, some mice exhibited a shorter duration of expression and were therefore excluded for the analysis of later sessions. Although the mice performed the task on a daily basis, fluorescent recordings were made only every 2 or 3 days to prevent sensor bleaching. Low power (100-200 mA) LEDs (465 nm and 405 nm, Doric Lenses) coupled to a patch cord (500 μm core, NA = 0.5, Prizmatix) were used for optical stimulation of the sensors in lock-in mode (572.205 Hz for the 465 nm LED, 208.616 Hz for the 405 nm LED) and collection of 520 nm fluorescence. 405 nm was used as the isobestic wavelength. The optical stimulation patch cord was plugged onto the ferrule during all experimental sessions, even those without recordings, to habituate animals and control for latent experimental effects. After the daily session, a short recording of the autofluorescence signal $F(auto)$, coming from the patchcord only, was performed with same LED intensities, no animal plugged and room in the dark. Raw 520 nm fluorescence was demodulated by the software (Doric Lenses) to extract 465 nm and 405 nm signals. The 405 nm signal was visually checked to account for instability artefacts coming from head movements or patch cord unplugging during the session, and if needed correct the associated 465 nm signal accordingly, otherwise it was not used for signal treatment. 465 nm signal F_i follows several treatment steps according to this formula:

$$\frac{dF_i}{F_0} = \frac{F_i - F(auto) - F_i(fit)}{F_i(fit)} - 1$$

First F_i is subtracted with the constant value of autofluorescence *F(auto)* measured with patch cord only, improving drastically the signal-to-noise ratio. Then, largest transients induced by ICSS were excluded to perform a smoothing on the subsequent truncated signal. We then computed a mono-exponential fit $F_i(fit)$ on this smoothed signal, which was also subtracted to F_i at each time point i to account for exponential decay. The result is then divided by the same $F_i(fit)$ at each time point i to normalize the

signal around 1, and subtracted by the constant 1 to normalize to 0 and obtain positive or negative

transients as dF_i/F_0 over an entire session (5 or 10min). In order to aggregate signals coming from different

sessions for each mouse, and then pool mice for the analysis, we also applied a z-scoring on dF_i/F_0 over

each entire session.

Intracranial self-stimulation (ICSS) bandit task. The ICSS bandit task [9,10,34,35], took place in a circular

open-field with a diameter of 68 cm. Three explicit square-shaped marks (2 × 2 cm) were taped in the

open field, forming an equilateral triangle (side = 35 cm). Entry in the circular zones (diameter = 6 cm)

around each mark was associated with the delivery of a rewarding ICSS stimulation. A LabVIEW (National

Instruments) application precisely tracked and recorded the animal's position with a camera (20 frames/s).

When a mouse was detected in one of the circular rewarding zones, a TTL signal was sent to the electrical

stimulator, which generated a 200 ms train of 5 ms biphasic square waves pulsed at 100 Hz (20 pulses

per train). Two consecutive rewards could not be delivered on the same target, which motivated mice to

alternate between targets and therefore generate sequences of binary choices. ICSS intensity was

adjusted, within a range of 15-200 µA, during early conditioning sessions, so that mice would achieve

between 50 and 120 visits per session (5 min duration) for two successive sessions. ICSS intensity was

then kept constant for all the experiments, even when reward delivery rules changed. Mice with insufficient

scores were excluded. Different reward delivery rules were used, and all animals went through all three

protocols successively. The first is a deterministic (Det) setting, with 10 to 17 daily sessions of 5 min. All

zones were associated with an ICSS delivery (P = 100%). The second, described previously in [10], is a

complex (Cplx) setting where a grammatical complexity algorithm [58] analyses online the choice sequence

that the mouse is producing, calculates the complexity of two potential sequences of length 10 (9 past

targets + next target among the 2 available) and gives a reward only if the complexity of the sequence

increases. Repeating patterns of low complexity will therefore lead to series of omissions, while increasing

variability will increase success rate. Mice did daily sessions during 15-20 days. The third setting is

probabilistic (Proba): each target is associated with a probability to obtain an ICSS stimulation among

three (P = 25%, P = 50%, P = 100%), as described previously [9,34,35]. The probabilities at each location

were pseudo-randomly assigned per mouse, and 15-20 sessions were performed. 2 cohorts of both male

and female mice followed deterministic, complexity and probability settings successively, with no

fluorescent sensor expression. Three cohorts of male mice expressing $GRAB_{DA}$ and implanted with an

optical fiber implantation followed different settings: *i)* the first cohort performed only Det and Cplx, and

recordings started only at the end of Det, *ii)* the second and third cohorts performed Det, Cplx and Proba,

with recordings starting at the beginning of Det, and performed also some control experiments (especially,

unexpected rest cage and off-target ICSS). Consequently, there is variation in animal numbers among

conditions in the figures. Finally, one cohort of DATiCre male mice was tested in Det and Cplx only. We
defined three analysis windows within each condition (see Fig 7) - Start, Late, and End - corresponding
to the following experimental session ranges: Deterministic (Det) sessions 6–7, 11–12, and 14–17;
Complexity (Cplx) sessions 1–4, 5–8, and 10–13; and Probabilistic (Proba) sessions 1–2, 3–6, and 11–
16.
795

QUANTIFICATION AND STATISTICAL ANALYSIS

Behavioral measures: For all those groups, the following measures were analyzed with custom codes
in Python (using mostly Numpy and Pandas libraries, on PyCharm CE) and compared throughout the
different rules: *i)* number of visits, *ii)* success rate, *iii)* time-to-goal, *iv)* choice repartition (proportion of
visits at each location), *v)* percentage of U-turn (target n = target n+2) and *vi)* sequence complexity
(applying the same complexity algorithm calculation but offline and for all choices during a session).
Furthermore, the ICSS bandit task can be seen as a Markovian decision process: every transition can be
considered as a binary choice between two options, since a zone cannot be reinforced twice in a row.
The sequence of choices per session results from the succession of three specific binary choices, or
gambles. For deterministic and complexity, G_c = P(A|C) would be the total number of visits in target A
divided by the total number of visits in targets A and B, when the animal is in target C. Similarly, G_A =
P(B|A) and G_B = P(C|B). A gamble above 50% indicates that the animal has a preference for moving
clockwise (or below 50% for moving counter-clockwise). In probabilistic, direction of conditional
probabilities does not follow spatial repartition of locations, but rather preference for the high value option:
G_{25} = 100% vs 50%, G_{100} = 50% vs 25% and G_{50} = 100% vs 25%. Applying this principle at each choice,
those 3 gambles can be aggregated into single values to give circularity index (going in circle, no matter
clockwise or counter-clockwise), exploitation index (always preferring the highest value option) or
repetition index (always making the same choice at given gamble, no matter the direction or exploitation).
Fiber photometry analysis: All treatments and analyses were performed in Python using custom codes
(mostly Numpy and Pandas libraries). After cleaning and processing each session signal to obtain dF/F
values and z-scored dF/F values, events of interest were extracted to align the signal in [-3s:3s] time
window in dataframes, t_0 being the exact time of location entry (triggering reward delivery or omission),
with 1kHz sampling. Session-wise averages of given conditions for each mouse were then extracted, and
averaged again over multiple mice for statistical analyses. In some conditions, especially when events of
interest were rare (some scenarios of rewards or omissions chains in complexity, or some scenarios of
locations transition in probabilistic), two or more sessions from one animal were pooled as if they were
one (for instance, the last two sessions in a given context) to have enough trials for each animal in this

condition. For the same reason, the third cohort of GRAB$_{DA}$ mice followed 10 min long sessions (instead
of 5 min) in Cplx and Proba settings, with no particular effect on the overall quality of the signal, nor the
duration of GRAB$_{DA}$ expression (up to 3 months). For GRAB$_{DA}$, rewards-elicited positive transients
typically peaked around 250 ms after location entry (duration of ICSS being 200 ms) and decayed during
a bit less than 1s: we therefore extracted maximum and mean of the signal in a 1 s window post location
entry. Omissions-elicited negative transients were longer, reaching their minimum around 800 ms after
location entry and taking roughly 700-800 ms to go back to baseline: we therefore extracted minimum and
mean of the signal in 1.5 s window post location entry. For GCaMP, kinetics depended on the sensor
used: peaks reached maximum value around 250-300 ms post location entry for GCaMP6f and 350-400
ms for GCaMP7c, while dips reached minimum value around the same time (900-1050 ms post location
entry) for both sensors. However, return to baseline after reward-induced peaks was much shorter for
GCaMP6f (500-600 ms post location entry) than for GCaMP7c (2-3 s). For some correlation analyses
(using SciKit Learn Python library), especially the ones regarding z-scored peaks or dips amplitude
regarding outcome chain history, all trials of all mice were pooled together in a given condition.

Generalised Linear Model (GLM) approach: GLM was performed in Python using custom codes
(StatsModels or SciKit Learn library). To disentangle multiple factors that could explain DA signal, due to
high degree of behavioral and task-related variables correlated to each other from one trial to the next,
we designed a generalized linear model where a variable Y is explained by a linear combination of
multiples variables X_i, each of them weighted by a parameter w_i, plus a residual (or intercept) w_0.

$$Y = w_0 + w_1 . X_1 + w_2 . X_2 + \ldots$$

The model aims at fitting variations of Y by determining the weights w_i and their significance. Dependent
variable Y was post location entry 1s average for reward-induced peaks or 1.5s average for omission-
induced dips. Multiple X_i variables have been used, namely: *i)* reward or omission at previous and current
location, *ii)* Forward or U-turn at previous trial, *iii)* current target visited (spatially A, B or C, or in Proba
p_{100}, p_{50} or p_{25}), and *iv)* time since last stimulation (in Restcage stimulation condition). A single GLM was
applied for each mouse in a given condition, then w_i parameters resulting from all those GLMs were
averaged among mice, and the average was statistically compared to 0. Significance, either with positive
or negative weight, indicates that this variable explains part of DA variations.

Reinforcement Learning (RL) models: We used Reinforcement Learning (RL) to compute Reward
Prediction Errors (RPEs) from actual mice choice sequences and see how they match DA data. Before
each trial, the agent contains a set of expected values for each possible action. As one of these actions
is selected, it leads to either a reward ($V_{obtained} = 1$) or an omission ($V_{obtained} = 0$), then RPE is calculated

as $V_{obtained}$ - $V_{expected}$, and a new expected value of this action is fed back into the agent's set for next trials.

From both behavioural and photometry results, we hypothesised and tested three possible value

representations in the bandit task. First, we proposed a simple, one-order representation "going to any

target" or "performing any trial" to get a reward. In this case, all trials are similar, regardless of target or

trajectory choices, and we simply compute and update $V_{expected} = \{ V_{Any} \}$ at each trial. Second, a

representation of internal directionality with a set of two actions and $V_{expected} = \{ V_{Fwd} ; V_{Uturn} \}$. In this case,

RPEs are specific and computed separately for each of the two actions. Third, a spatial representation

"going to target X" with a set of three actions and $V_{expected} = \{ V_{pA} ; V_{pB} ; V_{pC} \}$. Again, RPEs are computed

for each target independently. Modelling the RPE values resulting from each of those three

representations allowed us to compare them and determine which simulation better replicates DA data in

each context. Initial $V_{expected}$ were set consistently with behavior in the task. For Det End, they were all set

to 0.99. For both Cplx End and Proba End, they were set as mean success rate computed from the two

previous sessions. For example, for a given mouse, initial V_{Uturn} to initiate the RL model with choice

sequence from sessions 9-10 is the proportion of rewarded Uturn trials from sessions 7-8. Exception is

for V_{p100} in Proba End where it was also set to 0.99. We arbitrarily tested several learning rates α = {0.001;

0.01; 0.05; 0.2; 0.4}. Results were consistent with experimental data for α = {0.01; 0.05; 0.2; 0.4}. Smaller

α (0.001) led to convergence that was too slow considering mice number of trials provided to models,

while larger α made convergence in Det too quick. In Fig 3 and Fig S6, α is set to 0.05. We next assumed

that in our recordings, DA = $V_{obtained}$ + RPE, and tested which representation accounted most in the error

component using GLMs on top of our RL-computed RPEs (taking as input variables $V_{obtained} = \{1; 0\}$ for

rewards or omissions, and theoretical RPEs computed from Model 1, 2 and 3). Similarly, models were

applied for each mouse in a given context, then w_i parameters were averaged among mice for each

context, and the average was statistically compared to 0. Significant weight indicates that this variable

explains part of DA variations. Finally, we extended this compilation of RL-computed RPE values and

GLM to fit RPE weights to DA data across sessions and contexts (Fig 4 and Fig S7). In this case, we

started RL models with mice choice sequences in Det Start with all $V_{expected}$ equal to zero (naive agents),

computed corresponding RPEs and updated corresponding $V_{expected}$. Consistent with mice progressively

learning and updating values across sessions and contexts, the final $V_{expected}$ of a given time-point became

the initial $V_{expected}$ of the next time point. For instance, from Det Start to Det Late (all $V_{expected}$ becoming

closer to 1, but not at the same speed). Or from Cplx End to Proba Start ($V_{expected}$ of each target therefore

starting to diverge). To allow for longitudinal comparisons, we next scaled (z-score) our data (both

experimental DA and RL models-computed RPEs) on each time point, applied GLMs on each time point,

and then compared the weights *i)* across sessions in a given context and at each transition between

contexts, and *ii)* each of them regarding its difference with 0.

DEEP REINFORCEMENT LEARNING MODEL:

Three-point task simulation: We trained a two-layer deep neural network to predict the values of different actions inside a simulation of the three-point task. The simulation was designed trial-wise. In each trial, the model was located at one of the three points and had to choose an action to go to any of the two available points. We provided the model a set of 5 minimal actions, each corresponding respectively to go right, go left, and go to point A, B or C. After the network predicting the value of these 5 actions, a softmax function was used to convert the output value vector y into probabilities of choice using the following formula:

$$p(choice) = \frac{e^{\beta y}}{\sum e^{\beta y}} \quad (1)$$

Here β was a choice temperature constant, always set to 9 in our simulations to closely fit mouse data, although other reasonable β values produced qualitatively similar results. The chosen action was then sampled using the probabilities. Note that at each trial, one of the go to A, B or C actions, was made unavailable due to the model being already present at this location. It was thus excluded from the softmax computation. As we gave the model abilities to use location information in the available actions (with A, B, C) we also provided information about its current location in the input. We also gave the model an input that would always be equal to one regardless of the position, to facilitate the non-use of location information if they were not necessary to predict the values. Thus, the three possible input vectors were the following:

$$A : [1\ 0\ 0\ 1], \quad B : [0\ 1\ 0\ 1], \quad C : [0\ 0\ 1\ 1] \quad (2)$$

where each corresponds to the location of the model on point A, B or C.

Architecture and initialization: The vector of actions values y is given by the equation:

$$y = XW^1W^2 \quad (3)$$

with X being the vector of inputs as defined in (2), W^1 the weights to compute the hidden layer vector from the input vector, and W^2 the weights to compute the output vector y from the hidden layer vector. We opted for a network with 4 hidden units (same as the number of inputs), even though a different number of hidden units produced similar results (tested with 1 and 10 hidden units). For each simulation, the initialization of W^1 and W^2 were sampled from a uniform distribution in the interval [-0.01; 0.01] such that initial predicted values from y output vector were close to zero.

$$W_{init}^1 = \begin{bmatrix} 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} + \quad \mathcal{U}(-0.01, 0.01)$$

922
$$\tag{4}$$

$$W_{init}^2 = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \end{bmatrix} + \quad \mathcal{U}(-0.01, 0.01)$$

924
$$\tag{5}$$

925   **Training and Reinforcement:** We trained each simulation for 400 trials in each rule set of the three-point

926   task in the same order as the mice: first determinist, then complexity, and finally probabilistic. We updated

927   the weights of the network using stochastic gradient descent at the end of each trial. At each rule switch,

928   the weights of the network were preserved. Each update minimized the following loss function:

929
$$L = (y_{ch} - Stim)^2 \tag{6}$$

930   where y_{ch} is the value of the chosen action and Stim. is the result of the choice, taking the value 1 if the

931   model receives a "stimulation" and 0 if not. From this loss, the gradients to update W^1 and W^2 were

932   computed using chain rule as follow:

933
$$\Delta W^1 = \alpha * 2 * X^T (y_{ch} - Stim) W_{:,ch}^{2T} \tag{7}$$

934
$$\Delta W_{:,ch}^2 = \alpha * 2 * (XW^1)^T (y_{ch} - Stim) \tag{8}$$

where α is the learning rate and was set to 0.02. Note that the gradient for W^1 were computed by only

back-propagating information relative to the computation of the chosen action value, which correspond to

the weights contained in only one column of the W^2 matrix. Similarly, the gradient for W^2 was a one column

vector that would update the weights of the only column of the W^2 matrix that is necessary to compute

the value of the chosen action. Because of this design, the actions were in competition for learning, which

could favor the use of different actions depending on the actual rule set.

Figures and Statistics: Raw figures were plotted using Python custom codes (mostly MatPlotLib library).

Graphics, typography and layout were formatted with Adobe Illustrator. All statistical analyses were

computed using Python with Scipy library and custom programs. Results were most frequently plotted as

individual data points and mean ± sem. The total number of observations in each group and the statistics

used are indicated in figure legends and detailed statistics tables: unless specified, data points indicate

the number of mice (N) on which the statistics were performed, and in some cases, they represent number

of trials (n) either for one example session from one animal, or from all sessions of all animals in a given
condition. Classical comparisons between means were performed using parametric tests (Student's t-
test, or ANOVA for comparing more than two groups, when parameters followed a normal distribution
(Shapiro test P > 0.05)), and non-parametric tests when the distribution was skewed (here, Wilcoxon or
Mann-Whitney U for one/two samples and whether comparison is paired or not, or Kruskall-Wallis for
more than two groups). More complex comparisons with several factors were performed using two-way
or mixed ANOVA regardless of normal distribution for simplicity, with no major impact on results
interpretation (see Fig S1, sex X session effects). Multiple comparisons were corrected using a
sequentially rejective multiple test procedure (Holm). Linear regressions were assessed either with
Pearson (parametric) or Spearman (non-parametric) tests. Probability distributions were compared using
the Kolmogorov–Smirnov (KS) test. All statistical tests were two-sided. $p > 0.05$ was considered not to be
statistically significant. In some cases, $p >$ but close to 0.05 were indicated in the figure (see Tables of
detailed statistics for more information).

Fluorescence immunohistochemistry: After completing the successive rules of the task, mice from the
GRAB$_{DA}$ cohorts were euthanatized by IP injection of euthasol (0.1mL per 30g at 150mg/kg), immediately
followed by paraformaldehyde (PFA) intra-cardiac perfusion, and brains were rapidly removed and post-
fixed in 4% PFA for 2 to 4 days. Serial 60μm sections were cut with a vibratome (Leica).
Immunohistochemistry was performed as follows: free-floating VTA and NAc brain sections were
incubated for 1h at 4°C in a blocking solution of phosphate-buffered saline (PBS) containing 3% bovine
serum albumin (BSA, Sigma A4503) and 0.2% Triton X-100, and then incubated overnight at 4 °C with *i)*
a mouse anti-tyrosine hydroxylase primary antibody (TH, Sigma, T1299) at 1:500 dilution and *ii)* a chicken
anti-eYFP primary antibody (Life technologies Molecular Probes, A- 6455) at 1:1000 dilution, both in PBS
containing 1.5% BSA and 0.2% Triton X-100. The following day, sections were rinsed with PBS and then
incubated for 3 h at 22–25 °C with *i)* Cy3-conjugated anti-mouse secondary antibody (Jackson
ImmunoResearch, 715-165-150) at 1:500 dilution and *ii)* a goat anti-chicken AlexaFluor 488 secondary
antibody (711-225-152, Jackson ImmunoResearch) at 1:1000 dilution, both in a solution of 1.5% BSA and
0.2% Triton X-100 in PBS. After three rinses in PBS, slices were wet-mounted using Prolong Gold Antifade
Reagent with DAPI (Invitrogen, P36930). Microscopy was carried out with a fluorescent microscope Leica
DMR, and images captured in gray level using MetaView software (Universal Imaging Corporation) and
colored post-acquisition with ImageJ. Labeling for YFP in the NAc (along with satisfying signal during the
task) allowed to confirm GRAB$_{DA}$ expression, and fiber implantation in the NAc lateral shell was also
visually checked. Similar procedures were used to check for GCaMP7c and GCaMP6f expression in VTA
DA neurons. For GCaMP7c we used the same anti-TH and anti-eYFP antibodies as previously described.

For GCaMP6f we used a sheep anti-TH primary antibody (AB-1542, Milipore) at 1:500 dilution coupled

with a donkey anti-sheep secondary antibody (713-165-147, Jackson ImmunoResearch) at 1:500 dilution

to highlight DA neurons, and simply used the virus-associated tdTomato to validate expression in the VTA

and optic fiber implantation site. For MFB slices, 100 µm sections were performed and slices were directly

visualized with visible light to check for ICSS electrode implantations.

Statistics and Reproducibility: All experiments were replicated with success (several successive

cohorts of mice).

Supplementary figures

Supplementary figure 1

Fig. S1: Evolution of decision behaviour across sessions, with no major sex effects.

A. Decision parameters throughout Det sessions for males and females. Comparison of **(left)** the

number of trials per session, **(middle-left)** the Uturn rate, **(middle-right)** the sequence complexity, and

(right) the circularity index between sessions 1&2, sessions 4&5 and the last 2 sessions in male and

female mice. In addition, we also compared the final states (Last2) between males and females. A fully

circular mouse would have 0% Uturn, low seq. cplx and 0.5 circul. idx. **B. Same as in A. for Cplx**

sessions. A mouse keeping circular strategy would have low success, 0% Uturn, low seq. cplx and 0.5

circul. idx. A random mouse would have 75% success, 50% Uturn, seq cplx = 1 and circul. idx = 0. **C.**

Same as in A. for Proba sessions. An exploitative mouse would have 75% success, 100% Uturn, low

seq. cplx and 0.5 exploit. idx. A random mouse would have 58.3% success, 50% Uturn, seq cplx = 1 and

exploit. idx = 0. (Data are shown as individual points, and mean ±sem. N = 23 male and 26 female mice.)

1005

1006

Supplementary figure 2

Fig. S2: Additional information on the Cplx rule and mice sequence patterns.

A. Detailed schematic representation of the Cplx rule. The first 9 trials of each session provide

deterministic rewards (P=100%) to launch the Cplx algorithm, which then determines at each trial, in a

sliding window, which target will lead to a reward by comparing the Lempel-Ziv grammatical complexity

of the two potential sequences: 9 past choices + first remaining target VS. 9 past choices + second

remaining target. The mouse will be rewarded only if it chooses the target that increases complexity. If

both sequences have the same complexity, both targets will be rewarded **(see Methods)**. Taking all

possible sequences of size 10 starting from one location, 75% of them are rewarded on the 10th trial.

Therefore, a random agent exploring homogeneously this sequences tree will converge to 75% success

rate. **B. Distribution of mice choice sequences of length 10 at the end of Det and Cplx.** Two

distribution peaks (paths in the decision tree) appear in Det, corresponding to circling behavior (clockwise

and counterclockwise), representing together roughly 25% of all produced sequences (among 512

possibilities). In Cplx, these peaks strongly reduce in size, in favor of more distributed visits of all possible

sequences. **(Insert)** Cumulative distribution comparison between Det and Cplx (Last2 sessions for each

rule). (In B, n is the total number of sequences of length 10, computed from sessions-wise mice

successive choices, from N=49 mice both males and females).

1023

1024

Supplementary figure 3

Fig. S3: Motivation throughout the task and decoupling between vigor and choice parameters.

A. Evolution of motivation across contexts and sessions. Comparison of number of trials across

contexts and sessions (mean of 2 sessions each time). **B. Correlation matrices between various vigor**

and choice parameters across mice in different contexts. Parameters are computed for each mouse

as the mean of 2 sessions (either First2 or Last2, for a given context). Each box represents the linear

correlation between two parameters (Pearson for parametric, Spearman for non-parametric, each dot

being a mouse). The filling color of each box represents the R value. The frame color of each box

represents the p-value (after Bonferroni correction). The warmer the color, the more those two parameters

are significantly correlated. **(Left)** Last2 sessions of Det (11 parameters, x66 Bonferonni correction).

(Middle) First2 and Last2 sessions of Cplx (12 parameters, x78 Bonferonni correction). **(Right)** First2 and

Last2 sessions of Proba (13 parameters, x91 Bonferonni correction). (In A, data are shown as individual

points, and mean ±sem. In B, only R and corrected p-values are shown with color code. Individual data

are available upon request. N is always the number of mice.)

1038

1039

Supplementary figure 4

Fig. S4: DA fiber photometry signals with Grab$_{DA}$ and GCaMP6f A. NAc and MFB slices

immunohistochemistry. Post-hoc verification of optic fiber implant and Grab$_{DA}$ virus expression in the

NAc lateral shell (left), and stimulation electrode implant in the MFB (right). **B. Individual mice NAc DA**

release for rewards and omissions in Cplx. Each line and colour is an individual mouse, averaged for

all trials during last Cplx session, in [-3s:3s] time window locked on location entry. Every single mouse

included in the results displayed reward-induced peaks and omission-induced dips of DA release

significantly different from zero (dashed black lines). **C-D. DA cell activity using GCaMP fiber**

photometry. DATiCre mice were injected with an AAV to express either GCaMP6f or GCaMP7c in VTA

DA neurons, implanted with an optic fiber in the VTA, and stimulation electrode in the MFB, to assess DA

neuron activity in the task. **C. GCaMP6f.** Using similar experimental procedures and signal analyses in

the Cplx context, calcium dynamics of VTA DA neurons show similar reward and omission-induced

transients than NAc lateral shell DA release, in this case with smaller transients amplitudes (worse signal-

to-noise-ratio) whether positive or negative, and faster kinetics for positive transients. **D. GCaMP7c.** Same

as B for GCaMP7c, with greater transient amplitudes (better signal-to-noise-ratio) and slower kinetic,

whether positive or negative. (In B, C, D, curves are shown as mean ±sem for a single session, n is the

number of reward or omission trials in this session.)

1056

1057

Supplementary figure 5

Fig. S5: DA fiber photometry signals in various configurations. A. DA response to expected (Task)

vs unexpected (Restcage) ICSS (same current intensity) in Det Last session. **B.** Same as A but during

first session (S1) of conditioning in Det. **C.** DA response to expected (On-target) vs unexpected (Off-

target) ICSS (same current intensity) in Det Last session. **D.** Same as C but during second session (S2)

of conditioning in Det. **E.** Comparison of DA response for short (<3s), mid ([3s:5s]) and long (>5s) intervals

of stimulation in restcage. Curves are shown as mean ±sem for session-wise average of several mice, N

is the number of mice in each condition. Bar plots are shown as mean ±sem, in addition to individual data

points. **F.** GLM of the amplitude of DA response as a function of interval of stimulation in the restcage, the

same day as Last Det. Weight value of each variable compared to zero.

1067

1068

Supplementary figure 6

Fig. S6: Additional analyses of NAc DA release regarding task behavioral features. A. Individual

data corresponding to transient peak of Fig 4E. Comparison between Fwd and Uturn. **B.** Target effect on

DA transients in Det End. Comparison between pA, pB and pC. **C.** Previous outcome effect on DA

transients in Cplx End. Individual data corresponding to Fig 4F. **(Top)** Reward-induced transients

comparison between previous reward and previous omission. **(Bottom)** Omission-induced transients

comparison between previous reward and previous omission. **D.** Target effect on DA transients in Cplx

End. (Top) Reward-induced transients comparison between pA, pB and pC. **(Bottom)** Omission-induced

transients comparison between pA, pB and pC. **E.** Trajectory effect on DA transients in Cplx End. **(Top)**

Reward-induced transients comparison between Uturn and Fwd. **(Bottom)** Omission-induced transients

comparison between Uturn and Fwd. **F.** Target effect on DA transients in Proba End. Individual data

corresponding to Fig 4G **(Top)** Reward-induced transients comparison between p100, p50 and p25.

(Bottom) Omission-induced transients comparison between p50 and p25. **G.** Trajectory effect on DA

transients in Proba End. **(Top)** Reward-induced transients comparison between Uturn and Fwd. **(Bottom)**

Omission-induced transients comparison between Uturn and Fwd. **H.** Previous outcome effect on DA

transients in Proba End. **(Top)** Reward-induced transients comparison between previous reward and

previous omission. **(Bottom)** Omission-induced transients comparison between previous reward and

previous omission.

(Bar plots are shown as mean ±sem, in addition to individual data points. Curves are shown as mean

±sem. N is always the number of mice in each context.)

1088

1089

A

Supplementary Figure 7

Fig. S7: Detailed schematic of RL modelling for each of the four models. From actual mice choice
sequences, we applied RL models and computed corresponding RPEs. The first model consists in single
value representation "going to any target" or "performing any trial" to get a reward, where we simply
compute $V_{expected}$ = { V_{Any} } and RPE_{Any} at each trial. The second model consists in two value
representations depending on chosen trajectory $V_{expected}$ = { V_{Fwd} ; V_{Uturn} }. In this case, RPE_{Uturn} and
RPE_{Fwd} are specific and computed separately for each of those two actions. The third model consists in
three value representations depending on chosen target $V_{expected}$ = { V_{pA} ; V_{pB} ; V_{pC} }. Again, RPE_{pA}, RPE_{pB}
and RPE_{pC} are computed for each target independently. The fourth model consist in six value considering
forward and Uturn for each position A, B or C $V_{expected}$ = { V_{AF} ; V_{AU} ; V_{BF} ; V_{BU} ; V_{CF} ; V_{CU} }. Again, RPE_{AF},
RPE_{AU}, RPE_{BF}, RPE_{BU} RPE_{CF}, and RPE_{CU} are computed for each target independently.
1100
1101

Supplementary figure 8

Avg RPE modelled from mice choice seq.

Fig. S8: Additional information on the four RL models, comparison of computed RPEs in various

behavioral scenarios, and results in Proba Change context.

A-C. For each model (M$_1$ to M$_6$), computed RPEs were averaged over mice sessions in the same

scenarios used to characterize DA responses (regarding target, trajectory, and previous outcome).

The model that qualitatively reproduces best DA responses in all scenarios in given context is supposed

to be the best value representation that mice are using in this context. **A. End Det context.** Average M1,

M2, M3 and M6-computed RPE comparison between targets, and trajectories. **B. End Cplx context.**

From top to bottom: Average M1, M2, M3 and M6-computed RPE comparison between targets,

trajectories and previous outcome. **C. End Proba context. From top to bottom:** Average M1, M2, M3

and M6-computed RPE comparison between targets, trajectories and previous outcome. Bar plots are

shown as mean ± sem, in addition to individual data points. N is always the number of mice in each

context. Some of this plots are also shown in Figure 5

1114

1115

Supplementary figure 9

Fig. S9: Evolution of choice parameters across rules and sessions in GRAB DA mice.

A. Evolution of choice parameters across Det sessions. Left: Example trajectories of first and last

Det session. Comparison of **(middle)** Uturn rate and **(right)** sequence complexity between sessions 1&2,

sessions 4&5 and last 2 sessions in Grab-DA mice. **B. Evolution of choice parameters across Cplx**

sessions. Left: Example trajectories of first (cyan) and last (blue) Cplx sessions. Comparison of **(middle-**

left) Success rate, **(middle)** Uturn rate, **(middle-right)** sequence complexity and **(right)** circularity index

between sessions 1&2, sessions 4&5 and last 2 sessions in Grab-DA mice. **C. Evolution of choice**

parameters across Proba sessions. Left: Example trajectories of first (light green) and last (dark green)

Proba sessions. Comparison of **(middle-left)** Success rate, **(middle)** Uturn rate, **(middle-right)** sequence

complexity and **(right)** exploitation index between sessions 1&2, sessions 4&5 and last 2 sessions in

Grab-DA mice. (data are shown as mean ±sem, in addition to individual data points. In D, each data point

is one animal at one time point. signal curves are shown as mean ±sem. In A, data are shown as mean

±sem for clarity. Individual data points are available upon requests. Due to multiple corrections generating

dilutions in p-values, **#** symbol has been used in the figure to highlight $p < 0.12$ after correction. N is always

the number of mice in each context.)

1131

1132

Supplementary figure 10

Fig. S10: Additional analyses of DA transients and choice behavior in Cplx.

A. Success rate depending on current Uturn/Fwd choice in Cplx. Left: First 2 sessions. **Right:** Last 2 sessions. **B. Uturn rate depending on previous outcome in Cplx. Left:** First 2 sessions. **Right:** Last 2 sessions. **C. Analysis of chains of successive rewards and omissions in Cplx. Top:** In early Cplx, mice tend to keep repeating circular patterns and therefore get long series of omissions. In late Cplx, omissions are regularly distributed, generating smaller chains, as expected from a random agent. **Bottom-left:** Cumulative distribution of reward and omission chain lengths during first 2 and last 2 Cplx sessions. **Bottom-right:** Average chain lengths per mouse. **D. Same for chains of successive forwards and Uturns. Left:** Cumulative distribution of forward and Uturn chains length during first 2 and last 2 Cplx sessions. **Right:** Average chains length per mouse. For regressions in A, B, each dot is a trial of one mouse. In C, D, E, F, Bar plots are shown as mean±sem, in addition to individual data points. In E, F, cumulative distribution are computed for all trials of all mice together. n is always the number of trials, and N the number of mice, in each context.) **E. Linear regressions of DA transients depending on the number of successive previous rewards or omissions in chains in Cplx Start. Left:** Reward-induced DA peak amplitudes regarding length of successive previous rewards chains (green) or omissions chains (red). **Right:** Same for omission-induced DA dip amplitudes regarding length of successive previous rewards chains (green) or omissions chains (red). **F. Same for Cplx End. Left:** Reward-induced DA peak amplitudes regarding length of successive previous rewards chains (green) or omissions chains (red). **Right:** Same for omission-induced DA dips amplitude regarding length of successive previous rewards chains (green) or omissions chains (red).

Supplementary figure 11

Fig. S11: Property and performance comparison between 1-layer and 2-layers models

A. Sensitivity of model's RPE to previous outcome in Cplx (βP of the full linear model, mean±SEM) according to imposed learning rate (α parameter). The vertical red bar shows the learning rate used in the rest of the paper (α = 0.02). **B.** Derivate of Value at t+1 of the action chosen at t according to RPE at t, calculated for different learning rate (mean±SEM). This figure shows that the difference in between the 2 models in A is not explained by a difference in the amplitude of the update for a given RPE between the 2 models. **C.** Evolution of the derivate of Value at t+1 of the actions unchosen at t according to RPE at t, for the learning rate used in the paper (α = 0.02), for the 2 layers model. The derivate evolves to become strictly positive through training schedule, while this derivate is 0 by definition for the 1 layer model, thus providing explanation for the difference seen in A. **D.** Mean complexity of behavior of the 2 models, calculated on a sequence of 50 trials, accross the 3 rules. This measure provides an estimation of how stereotyped (repetition of the same choices) the behavior of each model is. The dotted line shows the same estimation on the actual mice data. The 1-layer model tends to produce very stereotyped behavior (in Det and Proba) while the 2-layers model is closer to the actual data.