A Bayesian Model-Selection Approach for Determining the Number of Spectral Peaks in Neural Power Spectra

Luc E. Wilson[1*], Jason da Silva Castanheira[1,2*,] Benjamin Lévesque Kinder[1], Sylvain Baillet[1,3†]

1- Montreal Neurological Institute, McGill University, Montreal QC, Canada

2- Department of Experimental Psychology and Institute for Cognitive Neuroscience, University College London, 17-19 Alexandra House, London WC1N 3AZ, UK

3- Centre de Recherche du Centre Hospitalier de l'Université de Montréal (CRCHUM), Department of Neuroscience, University of Montreal

[*] These authors contributed equally: Luc E. Wilson, Jason da Silva Castanheira

[†] Corresponding author: sylvain.baillet@mcgill.ca.

Abstract: Neurophysiological brain activity comprises rhythmic (periodic) and arrhythmic (aperiodic) signal elements, which are increasingly studied in relation to behavioral traits and clinical symptoms. Current methods for spectral parameterization of neural recordings rely on user-dependent parameter selection, which includes selecting the correct maximum number of spectral peaks to fit to the spectrum. This challenges the replicability and robustness of findings. Here, we introduce a data-driven model-selection procedure for determining the appropriate number of oscillatory peaks to fit to neural power spectra, based on the Bayesian Information Criterion (BIC). We present extensive tests of the approach with ground-truth and empirical magnetoencephalography recordings. Data-driven model selection enhances both the specificity and sensitivity of spectral decompositions. Overall, the proposed spectral decomposition with data-driven model selection reduces reliance on user-defined 'maximum number of peaks' settings, enabling more robust, reproducible, and interpretable spectral parameterizations.

Lay summary: Brain activity is composed of rhythmic patterns that repeat over time and arrhythmic elements that are less structured. Recent advances in brain signal analysis have improved our ability to distinguish between these two types of components, enhancing our understanding of brain signals. However, current methods require users to adjust several parameters manually to obtain their results. The outcomes of the analyses, therefore, depend on each user's decisions and expertise. To improve the replicability of research findings, the authors propose a revised method to streamline the analysis of brain signal contents. They developed a new algorithm that defines the parameters of the analytical pipeline informed by the data. The effectiveness of this method is demonstrated with both synthesized and real-world data. The approach is made available to all researchers as a free, open-source app, observing best practices for neuroscience research.

Keywords: Neurophysiology, Spectral decomposition, Time-frequency analysis, Magnetoencephalography, Model selection, Rhythmic and arrhythmic brain signals, Parameter optimization, Reproducibility in research.

1 Introduction

Neural oscillations are rhythmic (periodic) signal components ubiquitously observed in electrophysiology across spatial and temporal scales (Buzsaki & Watson, 2012). In the power spectrum, periodic components can be modelled as Gaussian-shaped peaks emerging from an arhythmic (aperiodic) background (Wen & Liu, 2016; Donoghue et al., 2020; Wilson et al., 2022). Aperiodic activity is spectrally characterized by a reciprocal distribution of signal power that decays with frequency according to a power law ($1/f^{\alpha}$). In practice, the scalar exponent parameter α and broadband offset of the aperiodic model are inferred from estimates of the signal's power spectrum density (PSD) of the electrophysiological signal. Computational neuroscience models and growing empirical evidence suggest that α reflects the physiological balance between excitatory (E) and inhibitory (I) neural activity (Brake et al., 2024; Chini et al., 2022; Gao et al., 2017; Wiest et al., 2023), and the offset is related to aggregate neuronal population spiking (Miller et al., 2014; Voytek & Knight, 2015). These model parameters of the aperiodic spectral component decrease with age, accounting for the observation of a *flatter* power spectrum in aging (Cellier et al., 2021; Donoghue et al., 2020; Voytek et al., 2015). They also fluctuate during cognitive tasks (Donoghue et al., 2020; Gyurkovics et al., 2022; Preston et al., 2022; Waschke et al., 2021) and reflect behavioral traits (Ostlund et al., 2021; Wilson et al., 2022).

Recent algorithms and software such as *specparam* (Donoghue et al., 2020) and Spectral Parameterization Resolved in Time (*SPRiNT;* Wilson et al., 2022) have streamlined the adoption of spectral parameterization in electrophysiological research. These tools require users to define a number of method parameters (hyperparameters), such as model complexity via the pre-specification of the maximum number of spectral peaks N_G to be adjusted from the empirical PSD (Gerster et al., 2022; Ostlund et al., 2022; Wilson et al., 2022). When hyperparameters are not set appropriately, the *specparam* algorithm either fits spurious, outlier spectral peaks or misses genuine spectral peaks (Donoghue et al., 2020). Similarly, time-resolved spectral parametrization tools rely on hyperparameters to minimize the detection of outlier spectral peaks (Brady & Bardouille, 2022; Kosciessa et al., 2020; Seymour et al., 2022; Stokes et al., 2023; Whitten et al., 2011; Wilson et al., 2022).

Setting model hyperparameters is a prevalent challenge across many fields of science and engineering. Good-practice approaches recommend prioritizing parsimonious models with a balance between simplicity (fewer hyperparameters) and the ability to fit the observed data (more flexibility; Vandekerckhove et al., 2015). Limiting the number of spurious peaks fit to the spectrum is crucial, as every additional peak fit to the spectrum increases the number of model parameters by three (i.e., peak center frequency, amplitude, and width), which greatly increases the complexity of the model.

To address this concern, we propose a principled model selection strategy for the parameterization of neural power spectra. The method proceeds with adjusting progressively the number of Gaussian peaks fit to the empirical data spectrum (i.e., the model complexity) and determines the parameters of the simplest model that adequately accounts for the data using the Bayesian

information criterion (BIC). This approach allows us to determine the simplest model that
adequately explains the data, without requiring users to set a maximum number of peaks a priori.
This also enables the quantitation of evidence for periodic activity in spectral data via Bayes factor
analysis. We demonstrate below the method's performance using extensive ground-truth simulated
data and a large set of empirical resting-state magnetoencephalography (MEG) from N=606
participants.
89

90 # 2 Methods
91
2.1 Model Selection using Bayesian Information Criterion.

In the context of parsimonious modeling of power spectra and spectrograms, our goal is to optimize
the trade-off between model fidelity and complexity. This principle emphasizes deriving the most
accurate and representative model directly from empirical data while minimizing the inclusion of
unnecessary assumptions or parameters (Myung, 2000). Among the methods for comparing
models, Bayes factors are noteworthy as they balance model fit evaluation with the principle of
simplicity (Jefferys & Berger, 1992). These factors can be effectively estimated using the Bayesian
Information Criterion (BIC), which offers a pragmatic trade-off between goodness-of-fit and
complexity in terms of the number of model parameters (Schwarz, 1978; Vandekerckhove et al.,
2015).
102
The primary motivation is to select the model with the most parsimonious fit: as such, we opted
against Akaike Information Criterion (AIC), which tends to favour more complex models. We
similarly did not explore other goodness-of-fit metrics, as BIC affords us the ability to easily
compute Bayes Factors evidence for periodic activity in the power spectrum. Note, the outputs of
the algorithm include the log-likelihoods of each model tested, which allows users to convert BIC
metrics to AIC if desired.
109
110 The primary innovation of ms-specparam is a new objective function that is being minimized. In
111 the *specparam* approach, model fitting involves minimizing the least-squares error between model
112 predictions and the empirical power spectrum. The *ms-specparam* method refines this objective
113 by estimating the negative log-likelihood of a model:
114

$$-\ln p\,(\,y \mid x, w, \beta\,) = \frac{\beta}{2} \sum_{i=1}^{N} \{f(x_i, w) - y_i\}^2 - \frac{N}{2}\ln(\beta) + \frac{N}{2}\ln(2\pi)$$

116
117 where (x) and (y) are the frequency bins and empirical spectral power values, respectively;
118 $(f(x_i, w))$ is the spectral power predicted by the model at frequency (x_i); (y_i) is the empirical
119 spectral power value at frequency (x_i); (w) represents the model parameters, (N) the number of
120 frequency bins. (β) is the precision, or inverse variance, of residuals.
121

$$\beta = 1/\sigma^2 \ ,$$

124 Under the assumption of zero-mean (unbiased) Gaussian noise in the empirical power spectrum,
125 minimizing negative log-likelihood provides an equivalent solution to minimizing squared error
126 (Mitchell, 1997). Finally, we express the *ms-specparam* optimization's output in terms of the
127 Bayesian information criterion (BIC):

$$128 \qquad \text{BIC} = 2 \cdot \text{NLL} + \log(N) \cdot k,$$

where NLL is the negative log-likelihood, (N) is the number of frequency bins, and
(k) represents the total number of parameters, which includes the aperiodic parameters (exponent
and offset) and three additional parameters for each peak (center frequency, amplitude,
bandwidth). Note that ($k = 3P + 2$), where (P) represents the number of peaks.

The *ms-specparam* approach, much like the *specparam* algorithm, iteratively fits models of
increasing complexity by adding peaks and minimizing the squared error. Note that for each
additional modelled Gaussian peak, the number of parameters increases by three (i.e., the peak
center frequency, width, and amplitude). As in the default parameterization procedure, peaks are
fit in decreasing order of amplitude, where an additional peak is fit if it satisfies criteria for
amplitude (i.e., 'minimum peak height' and 'relative peak threshold') as well as distance from
other peaks or the spectrum edges. However, *ms-specparam* performs an additional, combined
bounded optimization of both aperiodic and periodic parameters, and converts the squared error
into a negative log-likelihood, which is then used to calculate the BIC. To identify the model
with the lowest BIC, ms-specparam saves optimized models of the spectrum following the
addition of each spectral peak, as well as their respective BIC. Finally, *ms-specparam* compares
and provides the parameters of the model with the lowest BIC, thus achieving a balance between
fit quality and model simplicity. As such, our approach optimizes the set of peaks detected
through the original *specparam* algorithm in order of decreasing peak amplitude, based on BIC.
In fact, the result is nearly equivalent algorithmically to individually setting the 'maximum
number of peaks' hyperparameter in *specparam* for each spectrum to the quantity determined by
ms-specparam to provide the lowest BIC, with the benefit of being data-driven and automatic.

We share *ms-specparam* as a MATLAB plug-in library that interoperates with *Brainstorm* (Tadel
et al., 2011), as well as an equivalent Python library. Both implementations are open-source and
accessible to all users.

2.2 Algorithm Settings and Hyperparameters.
The spectral parameterization of neural power spectra (synthetic and empirical) was conducted in
the frequency range of 1-40 Hz using three distinct approaches, each characterized by different
hyperparameter settings:

Default Hyperparameters: This approach adhered to the default settings established in the
Python implementation of *specparam* (Donoghue et al., 2020), with an increased range for peak
width limits. The hyperparameters included a minimum peak height of 0.1 arbitrary units (a.u.), a
maximum of 6 peaks, peak width limits set within the range of [1, 24] Hz, and a gaussian overlap
threshold of 0.75 s.d.

ms-specparam: This approach used the same hyperparameter settings as *default-specparam*,
including a minimum peak height of 0.1 a.u., a maximum of 6 peaks, peak width limits between
[1, 24] Hz, and a gaussian overlap threshold of 0.75 s.d. The most parsimonious spectral model is
selected according to the procedure described in *Model Selection using Bayesian Information*
Criterion.

2.3 Synthetic Data.

We created 5,000 synthetic neural power spectra using a range of aperiodic parameters: exponents
from 0.5 to 2 Hz^{-1}) and offsets from -8.1 to -1.5 arbitrary units (a.u.). Each power spectrum was
augmented with zero to four peaks, with 1,000 instances for each peak quantity. The parameters
for these peaks fell within specified ranges: center frequencies between 3 and 35 Hz, amplitudes
from 0.1 to 1.5 a.u., and bandwidths (2 s.d.) from 2 to 6 Hz. We ensured a minimum separation of
one bandwidth between adjacent peak frequencies. The frequency domain for simulation spanned
from 0.5 to 100 Hz with increments of 0.5 Hz.

To mimic realistic noise conditions, we introduced Gaussian white noise at varying intensities:
low (0.05 a.u.), medium (0.10 a.u.), and high (0.15 a.u.). We then applied *default-specparam*
(minimum peak height of 0.1 a.u., up to six peaks, peak width range of 1 to 24 Hz, and gaussian
overlap threshold of 0.75 s.d.) alongside *ms-specparam* with identical parameters.

For accuracy assessment, a 'hit' was designated when an identified peak's center frequency was
within one bandwidth (2 s.d.) of a true peak. In cases where multiple identified peaks met this
criterion, the peak with the highest amplitude was selected as the 'hit.' Peaks detected by the
algorithm that did not correspond to a true peak were classified as false positives.
183
184 We defined peak sensitivity as the ratio of 'hits' to the total number of simulated peaks, and the
185 positive predictive value as the ratio of 'hits' to all detected peaks (including false positives). For
186 peaks identified as 'hits,' we calculated the parameter estimation error as the absolute deviation
187 from the true values.
188
2.4 Bayes factor evidence for periodic brain activity.

Bayes factor (BF) provides a statistical measure for comparing two models, offering evidence
about the presence of periodic activity within neural power spectra. The computation of the Bayes
factor follows the formula proposed by Wagenmakers (2007):

$$\text{BF}_{01} = e^{(\text{BIC}_0 - \text{BIC}_1)/2}$$

where (BIC_0) is the Bayesian Information Criterion (BIC) value for the aperiodic-only model and
(BIC_1) is the BIC value of the lowest-BIC model.

In this context, (BIC_0) represents the BIC for the aperiodic-only model, which posits that the data
can be explained without invoking rhythmic components in the power spectrum. (BIC_1), on the
other hand, corresponds to the model that includes both aperiodic and periodic elements and has
the lowest BIC among all models considered.

The Bayes factor (BF_{01}) compares these models, translating the difference in their BIC values into
the odds ratio against periodic activity in the power spectrum. A smaller (BF_{01}) implies stronger
evidence against the aperiodic-only model, thereby indicating the presence of significant periodic
activity within the brain's neural power spectra. Conversely, larger (BF_{01})values suggest that the
periodic components do not significantly improve the model beyond the aperiodic activity alone.

This approach allows for the quantitative assessment of oscillations in neural recordings, providing
a more rigorous foundation for claims of rhythmic brain activity observed in electrophysiological
data.

2.5 Empirical data.

The empirical dataset for our study was obtained from the Cambridge Centre for Aging
Neuroscience repository (Cam-CAN; Shafto et al., 2014; Taylor et al., 2017). This comprehensive
dataset includes 606 healthy individuals aged 18 to 90 years (mean age = 54.69; SD = 18.28), with
a balanced gender representation (299 females). Each participant underwent a thorough
assessment, beginning with a detailed home interview followed by a resting-state
magnetoencephalography (MEG) session. The MEG recordings, lasting approximately 8 minutes
each, were conducted using a 306-channel VectorView MEG system (MEGIN). These recordings
were complemented with structural T1-weighted magnetic resonance imaging (MRI) to provide
anatomical context for MEG source mapping. All data collection occurred at a single, consistent
location to maintain uniformity in data acquisition.

This rich dataset forms the basis for our analyses, allowing for a comprehensive investigation into
the spectral properties of neural signals across a wide age spectrum.

2.5.1 MEG Preprocessing and Source Mapping.

We preprocessed magnetoencephalography (MEG) data with Brainstorm (Tadel et al., 2011;
March 2021 distribution), integrated with MATLAB (2020b; Natick, MA), adhering to established
best-practice guidelines (Gross et al., 2015). The preprocessing methodology followed protocols
detailed previously (da Silva Castanheira et al., 2024a; da Silva Castanheira et al., 2024b).

Line noise artifacts at 50 Hz and its first 10 harmonics were filtered using a notch filter bank.
Additionally, an 88-Hz artifact present in the Cam-CAN dataset (Wiesman et al., 2022) was
removed. To address slow-wave and DC-offset artifacts, a high-pass finite impulse response (FIR)
filter with a cutoff frequency of 0.3 Hz was applied. Signal-Space Projections (SSPs) were
implemented to attenuate cardiac artifacts and mitigate low-frequency (1–7 Hz) and high-
frequency (40–400 Hz) noise components, typically originating from saccades and muscle
activities.

Brain source models were anchored to the individual T1-weighted MRI data of each participant.
Automatic segmentation and labeling of MRI volumes were achieved using FreeSurfer (Fischl,
2012). Co-registration with MEG data was facilitated using approximately 100 head points
digitized for each participant. MEG biophysical head models were computed using *Brainstorm*'s
overlapping-spheres model (default parameters).

Cortical source models were estimated using linearly constrained minimum-variance (LCMV) beamforming, following *Brainstorm*'s default parameters (2018 version for source estimation processes). MEG source orientations were constrained normal to the cortical surface, distributed across 15,000 locations. Neural power spectra were then calculated for each of the 148 cortical regions defined by the Destrieux atlas (Destrieux et al., 2010). These calculations were based on the first principal component of all signals within each region of interest (ROI). Neural spectral power was estimated using Welch's method, utilizing 2-second windows with a 50% overlap. We parameterized the resulting neural power spectra with *default-specparam* (minimum peak height of 0.1 a.u., up to six peaks, peak width range of 1 to 24 Hz, and gaussian overlap threshold of 0.75 s.d.) alongside *ms-specparam* with identical parameters. We chose these hyperparameters based on visual inspection of the data.

2.5.2 Statistical Analyses.

To evaluate the accuracy of spectral parameters generated by *ms-specparam*, we employed two-sample non-parametric permutation t-tests from the *RVAideMemoire* package in R. This statistical approach allowed us to test differences in spectral parameter estimates, specifically focusing on five key variables: aperiodic exponent, aperiodic offset, peak center-frequency, peak amplitude, and peak bandwidth.

To capture differences in residual variance and the number of peaks fitted between algorithms in our empirical data, we similarly relied on paired non-parametric permutation t-tests.

We implemented hierarchical linear regression models using the *lmer* function in R to test how algorithm choice impacts age's effect on both aperiodic exponent and offset. The models were formulated as:

$$y \sim \text{intercept} + (\text{Participant intercept}) + \beta_1 \times \text{chronological age} + \beta_2 \times \text{algorithm} + \beta_3 \times \text{chronological age} \times \text{algorithm}$$

where (y) represents the dependent variables, including the aperiodic exponent and offset.

Separate linear regression analyses were conducted to compare *ms-specparam* against *default-specparam* for each dependent variable of interest. Chronological age and the chosen algorithm (e.g., *ms-specparam* vs. *default-specparam*) were introduced as fixed predictors, and individual participants were treated as a random factor to account for inter-individual variability. Note that we report standardized beta coefficients which can be interpreted as effect sizes, and otherwise report effect sizes using Cohen's D.

3 Results

Figure 1a highlights how user-dependent hyperparameters affect the outcome of spectral parameterization. In the example shown, the hyperparameter specifying the maximum number of peaks expected from spectral parameterization was set manually to a value of 6. However, the spectrum of the present empirical data contains only two peaks (left panel; Figure 1a). Under high

275   signal-to-noise conditions, spectral parameterization may yield only two peaks as expected.
276   However, when data is realistically noisy, the spectral parameterization algorithm may
277   overestimate the number of peaks in the spectrum to account for noise-related fluctuations (right
278   panel; Figure 1a). Ideally, spectral and spectrogram parameterization should automatically and
279   adaptively adjust model hyperparameters to account for the noise level in the data.
280
To address these issues, we propose an approach that proceeds iteratively with the
parameterization of empirical power spectra and spectrograms with increasing model complexity
(i.e., the maximum number of spectral peaks). We derive the Bayesian Information Criterion (BIC)
for each hyperparameter setting. The most parsimonious hyperparameter setting to model the
empirical power spectrum is the one corresponding to the lowest BIC value (Figure 1b). If the
most parsimonious model contains spectral peaks, we can further quantify the evidence for
periodic activity using the Bayes factor relative to the aperiodic-only model (Figure 1c). Our
method, coined *ms-specparam*, is freely available through *Brainstorm* (Tadel et al., 2011) and on
GitHub (github.com/lucwilson/model_selection).
290
We   tested   and   validated   *ms-specparam*   using   5,000   ground-truth,   synthetic   but
neurophysiologically plausible power spectra. We compared its performance against the original
specparam algorithm, configured to its default hyperparameters (referred to as *default-specparam*;
see Methods). We also applied *ms-specparam* to task-free MEG recordings from 606 participants
to replicate, with less dependence on user-selected hyperparameters, the previously reported
findings of an age-related decline in the aperiodic exponent of the neurophysiological power
spectrum (Voytek et al., 2015).

298
Figure 1: Spectral Parameterization with Model Selection
(a) Illustration of a spectral parameterization of a simulated power spectral density estimate (black line) obtained with *specparam* in the context of lower (left panel) and higher (right panel) noise levels. Both spectra are generated using the same spectral parameters (i.e., two spectral peaks). In more noisy conditions, *specparam* (pink line) fits a greater number of spectral peaks (green shaded areas) than what is present (simulated) in the data, resulting in overfitting (right panel). Key: '*cf*' refers to a peak's center frequency, '*amp*' refers to a peak's amplitude, and '*bw*' refers to a peak's bandwidth.
(b) *ms-specparam* is a method for spectral parameterization combined with a model selection procedure. It first adjusts a model for the aperiodic component of the spectrum (subpanel i) before adding spectral peaks (green shaded areas) in an iterative fashion (subpanel ii). These successive models are then assessed via the Bayesian Information Criterion (BIC; subpanel iii).
(c) The resulting BIC model is then subjected to Bayes factor inference against the aperiodic spectral model (panel i) to adjudicate whether spectral peaks are likely to be present in the data

313 power spectrum. A Bayes factor greater than 1 indicates evidence in favour of periodic components
314 in the power spectrum over the aperiodic-only model (panel iv).
315
316 **3.1 Synthetic, Ground-Truth Data.**
317
318 Each of the 5,000 synthetic power spectra comprised an aperiodic component, with offset values
319 ranging from -8.1 to -1.5 arbitrary units (a.u.) and exponents set between 0.5 and 2 Hz^{-1}. We
320 randomly added between 0 and 4 spectral peaks to the aperiodic background of each power
321 spectrum (1,000 simulated spectra for each number of peaks; see Methods). Zero-mean Gaussian
322 noise was added to the resulting power spectra with varying standard deviation values (s.d.).
323
In moderate noise conditions (s.d. = 0.10), *ms-specparam* demonstrated a slightly lower sensitivity
(89%) in detecting spectral peaks compared to *default-specparam* (91%). However, it had a
substantially higher positive predictive value for peak detection (*ms-specparam*: 96%; *default-*
specparam: 63%). On average, *default-specparam* overestimated the number of peaks in the
spectrum by 59%, whereas *ms-specparam* underestimated the number of peaks by 13% (Figure
2a). We observed similar results for sensitivity and PPV in both algorithms at lower and higher
noise levels (Figures S1, S2).
331
We found that, on average, all parameter estimates derived from *ms-specparam* are more
accurate than those derived from *default-specparam*: mean error in aperiodic exponent (t = -
11.94, p = 0.0019, Cohen's D = -0.24; one-tailed permutation t-tests), aperiodic offset (t = -8.18,
p = 0.0019, Cohen's D = -0.16), peak center frequency (t = -14.33, p = 0.0019, Cohen's D = -
0.21), peak amplitude (t = -10.05, p = 0.0019, Cohen's D = -0.15), and peak bandwidth (t = -
12.56, p = 0.0019, Cohen's D = -0.18; Figure 2b).
338
339

a | ms-specparam fits fewer spurious peaks

b | ms-specparam fits spectral parameters better

Figure 2: Performances on Synthetic Stationary Data

(a) Sensitivity and positive predictive value (PPV) for detection of spectral peaks (top row). *ms-specparam* (green) has similar sensitivity (89%) than *default-specparam* (blue; 91%), but superior PPV (96% vs. 63%). The heat maps below report the ground-truth vs. estimated number of spectral peaks (with percent incidence listed in each element) and highlight *ms-specparam*'s improved peak detection accuracy.

(b) Boxplots and empirical density distributions reporting the errors on the estimates of the spectral parameters derived using *ms-specparam* and *default-specparam*. For every spectral parameter, *ms-*

349 *specparam* estimated values with significantly lower mean absolute error (one-tailed permutation
350 t-test, all p<0.05).
351
We then sought to characterize which spectral peak features may impact the detection of spectral
peaks. First, we explored whether the distance between two spectral peaks negatively impacts their
detection. To do so, we computed the maximum distance between two spectral peaks within a
simulation, and assigned it to a quantile. We observed that for synthetic data containing 2 simulated
spectral peaks, ms-*specparam* demonstrated similar sensitivity (92%) in detecting spectral peaks
compared to *default-specparam* (96%) for moderate noise conditions (SNR = 0.04; Figure 3a).
Distance between spectral peaks (i.e., quantiles) did not significantly impact sensitivity across all
simulations. Similarly, we observed minimal effects of distance between spectral peaks on PPV
(Figure 3b).
361
Second, we explore the impact of spectral peak amplitude on spectral peak detection. We similarly
computed sensitivity for each quantile of peak amplitude from lowest amplitude peaks (Q1) to the
highest amplitude peaks (Q4). We observed that both algorithms showed reduced sensitivity to
spectral peaks for low amplitude oscillations, with both algorithms demonstrating lowest
sensitivity for spectral peak detection for synthetic data with four spectral peaks (Figure 3c). We
note that the effect of amplitude on peak detection became increasingly pronounced with additional
synthetic spectral peaks (darker lines, Figure 3c).
369
370
371
372

Figure 3: Larger Spectral Peak Amplitude Increases Peak Detection

(a) Sensitivity for detection of spectral peaks for increasing distances between synthetic spectral peaks (quartiles; x-axis). *ms-specparam* (green) has a similar sensitivity to *default-specparam* (blue) regardless of the distance between two spectral peaks (x-axis). Saturation of the colours indicates the number of synthetic spectral peaks.

(b) Positive predictive value (PPV) for detection of spectral peaks for increasing distances between synthetic spectral peaks (quartiles; x-axis). *ms-specparam* (green) outperforms *default-specparam* (blue) for all quartiles of distances between peaks.

(c) Sensitivity for detecting spectral peaks for the quartiles of peak amplitude (x-axis). Both *default-specparam* and *ms-specparam* show reduced sensitivity for detecting spectral peaks when they are of low amplitude. This effects if more pronounced for simulations with multiple spectral peaks (dark coloured points).

3.2 Empirical MEG Data.

We applied *ms-specparam* to resting-state MEG data from the Cam-CAN repository (N=606; Shafto et al., 2014; Taylor et al., 2017). We first preprocessed and source-mapped the MEG time series using *Brainstorm* (Tadel et al., 2011) following good-practice guidelines (Gross et al., 2013). We then derived the PSDs of each cortical parcel of the Destrieux atlas (Destrieux, 2010; see Methods). We then compared models generated with *ms-specparam* to those from *specparam*,

395 using hyperparameter settings: *default-specparam* (minimum peak height: 0.1 a.u.; maximum
396 number of peaks: 6; peak width limits: [1 24]; gaussian overlap threshold: 0.75 s.d.).
397
We found that *ms-specparam* generated models with less residual variance (i.e., mean squared
error, MSE; average MSE = 1.33×10^{-3}, SD = 4.42×10^{-4}) than *specparam* settings (default: average
MSE = 2.82×10^{-3}, SD = 1.01×10^{-3}; t = -48.11, p < 0.001, Cohen's D = -1.90; Figure 4a). This
observation was consistent across all cortical parcels, with posterior parietal areas showing the
greatest enhancements in model goodness-of-fit (Figure 4a). Reduced residual variance was
consistent over the entire frequency range (1–40 Hz), with marked improvements with respect to
both *specparam* settings over the edges of the spectrum (<5 Hz and >35 Hz; Figure 4a). This held
for spectral models fit to different frequency ranges (i.e., 1-45 Hz and 4-45 Hz; Figure S3).
406
We also observed that *ms-specparam* detected, on average, -0.37 fewer spectral peaks than *default-*
specparam, and therefore, as expected, provided more parsimonious spectral parameterizations (t=
-59.99, p < 0.001, Cohen's D = -0.81; Figure 4b). This was particularly evident in frontal brain
regions, where *ms-specparam* fit 0.3 fewer peaks. We interpret these effects as default *specparam*
fitting more lower amplitude spectral peaks that are common in frontal brain areas, particularly in
the theta range (4-8 Hz) (Donoghue et al., 2020). In line with this interpretation, the spectral peaks
fit by *ms-specparam* were of higher amplitude than *default-specparam* (default average: 0.36; ms-
average 0.44; t= -120.56, p < 0.001, Cohen's D = 0.32), suggesting greater selectivity.
415
416 With *ms-specparam*, we performed Bayes factor analyses (Vandekerckhove et al., 2015) as an
417 objective measure of evidence for the presence of rhythmic activity in the neurophysiological
418 power spectrum. We found that the bilateral cuneus exhibited the highest Bayesian evidence for
419 rhythmic activity in the resting-state, while we found the lowest evidence of rhythmic activity in
420 the medial frontal cortices (Figure 4c).
421
For illustration purposes, Figure 4d shows representative spectral parameterizations obtained from
neurophysiological time series recorded the right post-central gyrus. In this instance, *ms-*
specparam identified one spectral peak while *default-specparam* adjusted five spectral peaks
(*default-specparam* MSE: 1.76×10^{-3}; *ms-specparam:* 1.41×10^{-3}). This example illustrates how *ms-*
specparam reattributes variance previously modelled by several low amplitude oscillatory peaks
back to the arrhythmic exponent to achieve a more parsimonious model.
428
429 With regard to periodic spectral parameters, we observed that *ms-specparam* fitted spectral peaks
430 of larger bandwidths (*ms-specparam* average = 4.13, *default-specparam* average = 2.74; t =
431 192.28, p = 0.0019, Cohen's D = 0.54) but of similar centre frequencies (*ms-specparam* average
432 = 16.17, *default-specparam* average = 15.86; t = - 15.93, p = 0.0019, Cohen's D = -0.04) in
433 comparison to *default-specparam*.
434

a | empirical data: ms-specparam vs specparam model error

b | ms-specparam is more parsimonious

c | Bayesian evidence of periodic brain activity

d | example parameterized spectra

Figure 4: Performances on Empirical MEG Data.

(a) Residual variance analysis across the 606 participants and all brain regions shows *ms-specparam* (green) with consistently lower residual variance, indicating a superior fit relative to default *specparam* (blue; left panel). The brain maps display residual variance values for each cortical parcel. A frequency breakdown (right panel) reveals *ms-specparam* outperforms default *specparam* variations across the spectrum, particularly at the edges of the frequency spectrum.

(b) *ms-specparam* estimates less spectral peaks than *default-specparam*, demonstrating more parsimonious modelling, as reported in the box/density plots (left panel). The brain maps indicate that less spectral peaks (i.e., darker colours) were detected in posterior cortical parcels with *ms-specparam* (right panel).

(c) Bayesian evidence for periodic, rhythmic brain activity mapped across the cortical surface emphasizes occipital and left temporal regions.

(d) Parameterized spectra from the right post-central gyrus of a sample subject highlight the differences between algorithms: *ms-specparam* fits one peak (right panel), reflecting the dominant

450　oscillations, whereas *default-specparam* fits five (left panel), some of which may be redundant or
451　overfitted, as seen in the overlaid spectral models.
452
453　**3.3 Age-Related Flattening of the Aperiodic Spectrum Depends on Hyperparameter**
454　**Choice.**
455
We aimed to replicate with *ms-specparam* previous observations using *specparam* of age-related
decreases in aperiodic exponent (Donoghue et al., 2020; Voytek et al., 2015). We examined
whether the choice of algorithm (i.e., *default-specparam* vs *ms-specparam*) influenced the
detection of these aging effects. To do this, we fitted hierarchical linear regression models where
age, the choice of spectral parameterization algorithm, and their interaction were included as
predictors of both aperiodic exponent and aperiodic offset, respectively. A significant interaction
would suggest that the relationship between chronological age and aperiodic exponent is weakened
by the choice of parameterization algorithm.
464
We found that age-related decreases in aperiodic exponent are moderated by the algorithm used,
whether *ms-specparam* or *specparam* (i.e., a significant interaction between age and spectral
parameterization algorithm). This indicates that the observed age-related changes in aperiodic
exponent may be influenced by the choice of parameterization method rather than solely reflecting
genuine neurophysiological effects (default hyperparameters: $\beta = 0.11$, SE $= 0.04$, CI $[0.04, 0.18]$;
Figure 5a and Table S1).
471
472　We obtained similar results for the age-related decline in aperiodic offset. Our analysis confirmed
473　a significant interaction effect between age and spectral parameterization algorithm, when
474　comparing *ms-specparam* to *default-specparam* ($\beta = 0.07$, SE $= 0.03$, CI $[0.02, 0.13]$; Figure 5b
475　and Table S2).
476
477　Taken together, these observations suggest that the magnitude of age-related declines in the
478　aperiodic exponent and offset are influenced by the choice of spectral parameterization algorithm.
479　Note that the effect size of age was smaller in the spectral models derived from *ms-specparam*
480　(exponent: $\beta = -0.37$ vs $\beta = -0.48$; offset: $\beta = -0.40$ vs $\beta = -0.47$) than *default-specparam*.
481
482　As in our simulation results, we also found that *ms-specparam* identified fewer spectral peaks than
483　*default-specparam,* particularly in the 8-30 Hz range. This reinforces the earlier finding that *ms-*
484　*specparam* curtails the number of detected peaks and underscores the influence of model selection
485　on the characterization of peak parameters across all age groups (Figure 5c).

486
Figure 5: Age-related Neural Spectral Changes and Algorithmic Parsimony

(a) Topographical differences in aperiodic neural components, showing the variations in exponent
(top) and offset (bottom) estimates when using *ms-specparam* versus *default-specparam*. Areas
where *ms-specparam* yields higher parameter estimates are highlighted in blue.
(b) Moderating effect of spectral parameterization method (*ms-specparam* vs. *Default-specparam*)
on the relationship between age and aperiodic spectral components. The left graph shows the
exponent, and the right graph displays the offset, with statistical interactions highlighted.
(c) Frequency-specific empirical distribution of the number of peaks fitted across different age
groups. The histograms show that *ms-specparam* (green) generally fits fewer peaks, especially in
the mid-frequency range (8-30Hz), illustrating a more parsimonious approach to model fitting and
potentially more accurate reflection of age-related spectral changes.
498
499

4 Discussion

Spectral parameterization enables the spectral decomposition of neurophysiological signals into aperiodic and periodic components. Its adoption has grown rapidly over recent years, thanks to open software tools, with the aim of disambiguating the respective functions of rhythmic oscillatory and arrhythmic background neural activity. However, present tools require the manual adjustment of algorithm parameters (hyperparameters), which hinders the reproducibility, interpretability, and proper fitting of spectral parameterization models to the empirical data. In the present report, we addressed this issue with the addition of a principled model selection strategy to *specparam* (*ms-specparam*) to simplify setting key hyperparameters, notably the maximum number of peaks. We validated our approach with synthetic and empirical data. We show that the resulting spectral parameterizations are more parsimonious and fit better the data, while being considerably less dependent on user decisions and expertise.

4.1 Spectral Parameterization with Enhanced Model Parsimony and Goodness-of-Fit.

Our examination of ground-truth data shows that *ms-specparam* is more effective that *specparam* in accurately identifying spectral peaks. It avoids the frequent issue in practice of overfitting the spectral data*,* which typically overestimates the number of periodic components in power spectra (Figure 2a). In empirical data also, *ms-specparam* consistently generates more parsimonious models (Figure 4). We observed enhanced goodness-of-fit (reduced residual variance) in both synthetic and real-world data (Figures 2b and 4a), particularly at the edges of the frequency spectrum. The implications of these findings are twofold: firstly, *ms-specparam*'s parsimonious approach prevents both overfitting and *underfitting* (see Practical Guidelines below). Secondly, the improved accuracy of aperiodic component estimates is critical for characterizing complex neural dynamics (Donoghue et al., 2020; Gerster et al., 2022).

While we did not observe that the distance between synthetic spectral peaks influenced the ability of *ms-specparam* to detect peaks, lower amplitude peaks were on average missed more frequently than their higher amplitude counterparts for both algorithms (Figure 3c). This was particularly evident for synthetic data containing four simulated peaks. We interpret these findings as follows: as the number of peaks increases, the marginal benefit of an additional peak to the overall model fit is reduced. This is especially true because peaks are fit in decreasing order of amplitude. While both algorithms show this sensitivity bias, *ms-specparam* exhibited the lowest sensitivity for low-amplitude peaks.

In cases where data may contain multiple low-amplitude peaks, such as in infant EEG studies, users may prefer the higher positive predictive value of *ms-specparam* over the higher sensitivity of *default-specparam*, particularly when false positive peaks are of greater concern (e.g., when testing for the presence or absence of oscillatory activity)."

An interesting and not inherently obvious effect of model selection to optimize the number of peaks fit to the power spectrum is the reduced residual variance and error in parameter estimates, observed in both the synthetic and empirical data. Our interpretation of this effect is twofold. First, *ms-specparam* simultaneously optimizes all spectral parameters—including both aperiodic

and periodic—which may permit shifting some model variance between the two components that make up the power spectrum. *Second, ms-specparam* fits higher amplitude peaks with larger bandwidths in comparison to *default-specparam*. As observed in the example spectrum plotted in Figure 3B, this yields more parsimonious model fits. We speculate that by removing these narrow-band low amplitude peaks fit by *default-specparam*, *ms-specparam* reassigns this part of this variance to improve the final fit of the aperiodic component of the neural power spectrum. This results, therefore in better overall fits and a reduction in model fit error, principally along the edges of the power spectrum (see Figure 3A).

Note that although *ms-specparam* fits models with less residual variance that are more parsimonious than *default-specparam*, the model selection algorithm takes approximately 8 times longer to run on the empirical data. *Default-specparam*, on average, fit the 148 spectra of a participant in 3.01 seconds (s.d. = 0.48), whereas *ms-specparam* took 24.51 seconds (s.d. = 5.95). These benchmarks were obtained on a standard desktop machine. While *ms-specparam* is therefore slower, the cost remains practical for most research applications, and can be reduced through parallelization or the use of high-performance computing infrastructure.

4.2 Hyperparameter Settings.

Our empirical investigations emphasize the critical role of hyperparameter settings in spectral modelling. Notably, the choice of spectral parameterization algorithm influenced aperiodic parameter estimates across methods (Figures 5a-c). While deviations were modest, suggesting that default spectral parameterizations may have captured the aperiodic component accurately, our comparative analysis with synthetic data indicates that *ms-specparam* yields improved estimates of the aperiodic exponent and offset (Figure 2b).

We replicated with the new model selection approach previous observations of changing aperiodic parameters with age (Cellier et al., 2021; Donoghue et al., 2020; Hill et al., 2022). We found that the aperiodic component of the neurophysiological power spectrum flattens with age, which has been discussed as related to increased neural noise and asynchronous neuronal firing, yielding less structured brain dynamics (Usher et al., 1995; Pozzorini et al., 2013; Voytek et al., 2015; Voytek & Knight, 2015). Several empirical observations support this hypothesis (Bédard et al., 2006; Sosnoff & Newell, 2011).

We found, however, that previously reported effects of shifts in the spectral aperiodic exponent and offset with age are reduced, depending on the spectral parameterization method used and its hyperparameters. This observation encourages the present and further efforts towards more automated and principled parameter selection procedures, promoting robustness and replicability of research results.

4.3 Practical Guidelines.

We provide practical recommendations to adjust the hyperparameters of *ms-specparam*. As with other spectral parameterization methods, we encourage future users to examine their data's power spectra before and after applying *ms-specparam* and verify the model's goodness-of-fit. We refer the reader to the previously published guidelines by Donoghue et al. (2020), Gerster et al. (2022),

and Ostlund et al. (2022), which set good foundational principles for neurophysiological spectral
parameterization. Here, we highlight more specific considerations for the best possible use of *ms-*
specparam:

1. Model selection in *ms-specparam* determines the optimal number of spectral peaks that fit
the empirical power spectrum. The settings of other hyperparameters, including peak width
limits and aperiodic mode, remain to be defined by the user, but should always reflect the
qualities of the data upon visual inspection. The value set for the maximum number of
spectral peaks parameter needs to be larger than the number of peaks that are clearly visible
in the data's power spectrum. In our investigations, we set this value to 6.
2. We encourage users to derive measures of model goodness-of-fit, such as Mean-Squared
Error, R^2, and BIC, as in our *Brainstorm* plug-in of the proposed model selection methods.
Some of these metrics, like R^2, may be influenced by the aperiodic component of the
spectrum, as demonstrated in previous studies (Donoghue et al., 2020). In the context of
model selection, users should choose the spectral model with the lowest BIC (as in the
present study).

To conclude, the present report introduced a model selection approach to the parameterization of
neurophysiological power spectra ~~and spectrograms~~. The approach minimizes the requirement for
user expertise in the adjustment of hyperparameters, which influences the outcome of analyses. It
is grounded in the optimization of parameters that favour model parsimony while maximizing
goodness-of-fit. We foresee that this principled approach will contribute to the robust application
of spectral parameterization in neuroscience research, further elucidating the roles of rhythmic and
arrhythmic brain activity in cognition, health, and disease. We anticipate that *ms-specparam* will
enhance the reproducibility and robustness of reported findings.
614
Data and Software Availability

The *ms-specparam* algorithm~~s~~, as well as simulated power spectra and code used to generate
results, are available on GitHub (github.com/lucwilson/model_selection). Resting-state MEG
recordings were obtained from the CamCAN repository (Shafto et al., 2014; Taylor et al., 2017).

Author Contributions

Conceptualization: LEW, JDSC
Data Curation: LEW, JDSC
Methodology: LEW, JDSC, BLK
Software: LEW, JDSC
Visualization: LEW, JDSC, BLK
Funding acquisition: SB
Writing – original draft: LEW, JDSC, SB
Writing – review & editing: LEW, JDSC, BLK, SB

Declaration of Competing Interests

All authors declare no competing conflicts of interest. The listed funding sources in the **Acknowledgements** did not play any role in the writing of the manuscript or the decision to submit this manuscript for publication.

Acknowledgements

SB is supported by the NIH (R01EB026299-05), the Tier-1 CIHR Canada Research Chair of Neural Dynamics of Brain Systems (CRC-2017-00311), a Discovery Grant from the Natural Sciences and Engineering Research Council of Canada (436355-13), and the Canadian Institutes of Health Research (202503-PJT-542788). This work was also supported by a doctoral fellowship from NSERC (JDSC), as well as by a master's fellowship from NSERC (LEW).

Supplementary Materials

Algorithm Validation with Alternative Noise Conditions.

In addition to injecting moderate noise to the synthetic data, we also evaluated *ms-specparam* performance at low (s.d. = 0.02) and high (s.d. = 0.10) noise conditions. In spectra with low noise, *ms-specparam* detected spectral peaks with comparable sensitivity (92%) to *default-specparam* (92%). The positive predictive value of peaks detected using *ms-specparam* (97%) was notably higher than that of peaks detected using *default-specparam* (68%). In spectra with high noise, *ms-specparam* detected spectral peaks with lower sensitivity (84%) to *default-specparam* (90%). However, the positive predictive value of peaks detected using *ms-specparam* (96%) remained higher than that of peaks detected using *default-specparam* (61%). Taken together, these results support the generalizability of the observed algorithmic performance improvements across noise levels.

654
Figure S1: Performance of *ms-specparam* and *default-specparam* on synthetic stationary data
at higher noise levels (SNR = 0.10).
(a) Sensitivity and positive predictive value (PPV) for spectral peak detection across simulations
with high noise. While *ms-specparam* (green) shows slightly lower sensitivity than *default-*
specparam (blue), it consistently achieves higher PPV, indicating greater reliability in detected
peaks. The accompanying heatmaps show the correspondence between the ground-truth and
estimated number of peaks (values indicate percentage incidence), illustrating *ms-specparam*'s
improved accuracy in peak count estimation.

(b) Boxplots and empirical density plots of absolute estimation errors for spectral parameters
(aperiodic exponent and offset, peak center frequency, amplitude, and bandwidth). *ms-specparam*
yields lower estimation errors across all parameters compared to *default-specparam*.

666
Figure S2: Performance of *ms-specparam* and *default-specparam* on synthetic stationary data
at lower noise levels (SNR = 0.02).
(a) Sensitivity and positive predictive value (PPV) for spectral peak detection across simulations
with low noise. *ms-specparam* (green) and *default-specparam* (blue) show comparable sensitivity,
but *ms-specparam* consistently achieves higher PPV, indicating fewer false positives. The
accompanying heatmaps display the correspondence between ground-truth and estimated number

of peaks (values indicate percentage incidence), highlighting *ms-specparam*'s improved precision
in estimating peak count.
(b) Boxplots and empirical density plots of absolute estimation errors for spectral parameters
(aperiodic exponent and offset, peak center frequency, amplitude, and bandwidth). *ms-specparam*
outperforms *default-specparam* by producing lower estimation errors across all parameter types.
678
679 **Empirical MEG Data (Continued).**
680

a | modelled neural power spectra between 1 and 45 hz

b | modelled nueral power spectra between 4 and 45 Hz

681
Figure S3: *ms-specparam* is Robust Against Choice of Frequency Ranges to be Fit
We tested the robustness of *ms-specparam* against the choice of the frequency range of the
spectrum to fit. Neural power spectra were parameterized between 1 and 45Hz (a) or 4 and 45 Hz
(b) using both algorithms. *ms-specparam* (green) consistently achieved lower residual variance,
indicating a superior fit, relative to *default-specparam* (blue; boxplot) regardless of the frequency
range parameterized. The brain maps display residual variance values for each cortical parcel. A
frequency breakdown (right panel) reveals *ms-specparam* outperforms default *specparam*
variations across the spectrum, particularly at the edges of the frequency spectrum.

	exponent		
Predictors	*Estimates*	*CI*	*p*
(Intercept)	-0.06	-0.13 – 0.01	0.096
algorithm [default vs ms-specparam]	0.12	0.05 – 0.19	**0.001**
age (continuous)	-0.48	-0.55 – -0.41	**<0.001**
algorithm [default vs ms-specparam] × age (continuous)	0.11	0.04 – 0.18	**0.002**
Random Effects			
σ^2	0.39		
$\tau_{00 \text{ subID}}$	0.42		
ICC	0.52		
N $_{\text{subID}}$	606		
Observations	1212		
Marginal R^2 / Conditional R^2	0.187 / 0.607		

699 Table S1. Hyperparameter choice impacts the age's effect on the aperiodic exponent: default
700 hyperparameter setting vs *ms-specparam*.

	offset		
Predictors	*Estimates*	*CI*	*p*
(Intercept)	0.45	0.38 – 0.51	**<0.001**
algorithm [default vs ms-specparam]	-0.89	-0.95 – -0.84	**<0.001**
age (continuous)	-0.47	-0.53 – -0.41	**<0.001**
algorithm [default vs ms-specparam] × age (continuous)	0.09	0.03 – 0.14	**0.002**
Random Effects			
σ^2	0.22		
$\tau_{00 \ subID}$	0.39		
ICC	0.64		
N $_{subID}$	606		
Observations	1212		
Marginal R^2 / Conditional R^2	0.383 / 0.776		

722   Table S2. Hyperparameter choice impacts the age's effect on the aperiodic offset: default
723   hyperparameter setting vs *ms-specparam*.

References

Bédard, C., Kröger, H., & Destexhe, A. (2006). Does the 1/f frequency scaling of brain signals reflect self-organized critical states? *Physical Review Letters, 97*(11), 118102. doi:10.1103/PhysRevLett.97.118102

Brady, B., & Bardouille, T. (2022). Periodic/aperiodic parameterization of transient oscillations (PAPTO)-Implications for healthy ageing. *NeuroImage, 251*, 118974. doi:10.1016/j.neuroimage.2022.118974

Brake, N., Duc, F., Rokos, A., Arseneau, F., Shahiri, S., Khadra, A., & Plourde, G. (2024). A neurophysiological basis for aperiodic EEG and the background spectral trend. *Nature Communications, 15*(1), 1514. doi:10.1038/s41467-024-45922-8

Buzsáki, G., & Watson, B. O. (2012). Brain rhythms and neural syntax: Implications for efficient coding of cognitive content and neuropsychiatric disease. *Dialogues in Clinical Neuroscience, 14*(4), 345-367. doi:10.31887/DCNS.2012.14.4/gbuzsaki

Cellier, D., Riddle, J., Petersen, I., & Hwang, K. (2021). The development of theta and alpha neural oscillations from ages 3 to 24 years. *Developmental Cognitive Neuroscience, 50*, 100969. doi:10.1016/j.dcn.2021.100969

Chini, M., Pfeffer, T., & Hanganu-Opatz, I. (2022). An increase of inhibition drives the developmental decorrelation of neural activity. *eLife, 11*, e78811. doi:10.7554/eLife.78811

da Silva Castanheira, J., Wiesman, A. I., Hansen, J. Y., Misic, B., Baillet, S., Breitner, J., . . . Vitali, P. (2024). The neurophysiological brain-fingerprint of Parkinson's disease. *eBioMedicine*, *105*. doi:10.1016/j.ebiom.2024.105201

da Silva Castanheira, J., Wiesman, A. I., Taylor, M. J., & Baillet, S. (2024). The Lifespan Evolution of Individualized Neurophysiological Traits. *bioRxiv*, 2024.2011.2027.624077. doi:10.1101/2024.11.27.624077

Destrieux, C., Fischl, B., Dale, A., & Halgren, E. (2010). Automatic parcellation of human cortical gyri and sulci using standard anatomical nomenclature. *NeuroImage, 53*(1), 1-15. doi:10.1016/j.neuroimage.2010.06.010

Donoghue, T., Haller, M., Peterson, E. J., Varma, P., Sebastian, P., Gao, R., . . . Voytek, B. (2020). Parameterizing neural power spectra into periodic and aperiodic components. *Nature Neuroscience, 23*(12), 1655-1665. doi:10.1038/s41593-020-00744-x

Fischl, B. (2012). FreeSurfer. *NeuroImage, 62*(2), 774-781. doi:10.1016/j.neuroimage.2012.01.021

Gao, R., Peterson, E. J., & Voytek, B. (2017). Inferring synaptic excitation/inhibition balance from field potentials. *NeuroImage, 158*, 70-78. doi:10.1016/j.neuroimage.2017.06.078

Gerster, M., Waterstraat, G., Litvak, V., Lehnertz, K., Schnitzler, A., Florin, E., . . . Nikulin, V. (2022). Separating neural oscillations from aperiodic 1/f activity: Challenges and recommendations. *Neuroinformatics*. doi:10.1007/s12021-022-09581-8

Gross, J., Baillet, S., Barnes, G. R., Henson, R. N., Hillebrand, A., Jensen, O., . . . Schoffelen, J.-M. (2013). Good practice for conducting and reporting MEG research. *NeuroImage, 65*, 349-363. doi:10.1016/j.neuroimage.2012.10.001

Gyurkovics, M., Clements, G. M., Low, K. A., Fabiani, M., & Gratton, G. (2022). Stimulus-induced changes in 1/f-like background activity in EEG. *The Journal of Neuroscience, 42*(37), 7144. doi:10.1523/JNEUROSCI.0414-22.2022

Hill, A. T., Clark, G. M., Bigelow, F. J., Lum, J. A. G., & Enticott, P. G. (2022). Periodic and aperiodic neural activity displays age-dependent changes across early-to-middle childhood. *Developmental Cognitive Neuroscience, 54*, 101076. doi:https://doi.org/10.1016/j.dcn.2022.101076

Jefferys, W. H., & Berger, J. O. (1992). Ockham's Razor and Bayesian Analysis. *American Scientist,*
80(1), 64-72. Retrieved from http://www.jstor.org/stable/29774559.
Kosciessa, J. Q., Grandy, T. H., Garrett, D. D., & Werkle-Bergner, M. (2020). Single-trial
characterization of neural rhythms: Potential and challenges. *NeuroImage, 206*, 116331.
doi:10.1016/j.neuroimage.2019.116331
Miller, K. J., Honey, C. J., Hermes, D., Rao, R. P. N., denNijs, M., & Ojemann, J. G. (2014). Broadband
changes in the cortical surface potential track activation of functionally diverse neuronal
populations. *NeuroImage, 85*, 711-720. doi:10.1016/j.neuroimage.2013.08.070
Mitchell, T. M. (1997). *Machine Learning.* New York: McGraw-Hill.
Myung, I. J. (2000). The importance of complexity in model selection. *Journal of Mathematical*
Psychology, 44(1), 190-204. doi:10.1006/jmps.1999.1283
Ostlund, B., Donoghue, T., Anaya, B., Gunther, K. E., Karalunas, S. L., Voytek, B., & Pérez-Edgar, K.
E. (2022). Spectral parameterization for studying neurodevelopment: How and why.
Developmental Cognitive Neuroscience, 54, 101073. doi:10.1016/j.dcn.2022.101073
Ostlund, B. D., Alperin, B. R., Drew, T., & Karalunas, S. L. (2021). Behavioral and cognitive correlates
of the aperiodic (1/f-like) exponent of the EEG power spectrum in adolescents with and without
ADHD. *Developmental Cognitive Neuroscience, 48*, 100931. doi:10.1016/j.dcn.2021.100931
Pozzorini, C., Naud, R., Mensi, S., & Gerstner, W. (2013). Temporal whitening by power-law
adaptation in neocortical neurons. *Nature Neuroscience, 16*(7), 942-948. doi:10.1038/nn.3431
Preston, M., Schaworonkow, N., & Voytek, B. (2022). Oscillations and aperiodic activity: Evidence for
dynamic changes in both during memory encoding. *bioRxiv*, 2022.2010.2004.509632.
doi:10.1101/2022.10.04.509632
Schwarz, G. (1978). Estimating the dimension of a model. *The Annals of Statistics, 6*(2), 461-464.
doi:10.1214/aos/1176344136
Seymour, R. A., Alexander, N., & Maguire, E. A. (2022). Robust estimation of 1/f activity improves
oscillatory burst detection. *European Journal of Neuroscience, 56*(10), 5836-5852.
doi:10.1111/ejn.15829
Shafto, M. A., Tyler, L. K., Dixon, M., Taylor, J. R., Rowe, J. B., Cusack, R., . . . Cam-CAN (2014).
The Cambridge Centre for Ageing and Neuroscience (Cam-CAN) study protocol: A cross-
sectional, lifespan, multidisciplinary examination of healthy cognitive ageing. *BMC Neurology,*
14(1), 204. doi:10.1186/s12883-014-0204-1
Sosnoff, J. J., & Newell, K. M. (2011). Aging and motor variability: A test of the neural noise
hypothesis. *Experimental Aging Research, 37*(4), 377-397. doi:10.1080/0361073X.2011.590754
Stokes, P. A., Rath, P., Possidente, T., He, M., Purcell, S., Manoach, D. S., . . . Prerau, M. J. (2023).
Transient oscillation dynamics during sleep provide a robust basis for electroencephalographic
phenotyping and biomarker identification. *Sleep, 46*(1), zsac223. doi:10.1093/sleep/zsac223
Tadel, F., Baillet, S., Mosher, J. C., Pantazis, D., & Leahy, R. M. (2011). Brainstorm: A user-friendly
application for MEG/EEG analysis. *Computational Intelligence and Neuroscience, 2011*,
879716. doi:10.1155/2011/879716
Taylor, J. R., Williams, N., Cusack, R., Auer, T., Shafto, M. A., Dixon, M., . . . Henson, R. N. (2017).
The Cambridge Centre for Ageing and Neuroscience (Cam-CAN) data repository: Structural and
functional MRI, MEG, and cognitive data from a cross-sectional adult lifespan sample.
NeuroImage, 144, 262-269. doi:10.1016/j.neuroimage.2015.09.018
Usher, M., Stemmler, M., & Olami, Z. (1995). Dynamic pattern formation leads to 1/f noise in neural
populations. *Physical Review Letters, 74*(2), 326-329. doi:10.1103/PhysRevLett.74.326

Vandekerckhove, J., Matzke, D., & Wagenmakers, E.-J. (2015). Model comparison and the principle of
parsimony. In *The Oxford Handbook of Computational and Mathematical Psychology.*
doi:10.1093/oxfordhb/9780199957996.013.14
Voytek, B., & Knight, R. T. (2015). Dynamic network communication as a unifying neural basis for
cognition, development, aging, and disease. *Biological Psychiatry, 77*(12), 1089-1097.
doi:10.1016/j.biopsych.2015.04.016
Voytek, B., Kramer, M. A., Case, J., Lepage, K. Q., Tempesta, Z. R., Knight, R. T., & Gazzaley, A.
(2015). Age-related changes in 1/f neural electrophysiological noise. *The Journal of
Neuroscience, 35*(38), 13257. doi:10.1523/JNEUROSCI.2332-14.2015
Wagenmakers, E.-J. (2007). A practical solution to the pervasive problems of p values. *Psychonomic
Bulletin & Review, 14*(5), 779-804. doi:10.3758/BF03194105
Waschke, L., Donoghue, T., Fiedler, L., Smith, S., Garrett, D. D., Voytek, B., & Obleser, J. (2021).
Modality-specific tracking of attention and sensory statistics in the human electrophysiological
spectral exponent. *eLife, 10*, e70068. doi:10.7554/eLife.70068
Wen, H., & Liu, Z. (2016). Separating fractal and oscillatory components in the power spectrum of
neurophysiological signal. *Brain Topography, 29*(1), 13-26.
Whitten, T. A., Hughes, A. M., Dickson, C. T., & Caplan, J. B. (2011). A better oscillation detection
method robustly extracts EEG rhythms across brain state changes: The human alpha rhythm as a
test case. *NeuroImage, 54*(2), 860-874. doi:10.1016/j.neuroimage.2010.08.064
Wiesman, A. I., da Silva Castanheira, J., & Baillet, S. (2022). Stability of spectral estimates in resting-
state magnetoencephalography: Recommendations for minimal data duration with
neuroanatomical specificity. *NeuroImage, 247*, 118823. doi:10.1016/j.neuroimage.2021.118823
Wiest, C., Torrecillos, F., Pogosyan, A., Bange, M., Muthuraman, M., Groppa, S., . . . Tan, H. (2023).
The aperiodic exponent of subthalamic field potentials reflects excitation/inhibition balance in
Parkinsonism. *eLife, 12*, e82467. doi:10.7554/eLife.82467
Wilson, L. E., da Silva Castanheira, J., & Baillet, S. (2022). Time-resolved parameterization of aperiodic
and periodic brain activity. *eLife, 11*, e77348. doi:10.7554/eLife.77348