Generating Synthetic Task-based Brain Fingerprints for Population Neuroscience Using Deep Learning

Emin Serin[1,2,3], Kerstin Ritter[4], Gunter Schumann[5,6], Tobias Banaschewski[7],

Andre Marquand[8]*, Henrik Walter[3]*, for the environMENTAL consortium

[1]Charité – Universitätsmedizin Berlin, Einstein Center for Neurosciences Berlin, 10117, Berlin, Germany.

[2]Bernstein Center for Computational Neuroscience, 10115, Berlin, Germany

[3]Division of Mind and Brain Research, Department for Psychiatry, Charité– Universitätsmedizin Berlin, 10117, Germany

[4]University of Tübingen, Hertie Institute for AI in Brain Health, Tübingen, Germany

[5]Centre of Population Neuroscience and Stratified Medicine (PONS), Department of Psychiatry and Clinical Neuroscience CCM, Charité-Universitätsmedizin Berlin, 10117, Germany.

[6]Centre for Population Neuroscience and Stratified Medicine (PONS), Institute for Science and Technology of Brain-inspired Intelligence (ISTBI), Fudan University, Shanghai, China.

[7]Department of Child and Adolescent Psychiatry and Psychotherapy, Central Institute of Mental Health, Medical Faculty Mannheim, University of Heidelberg, Mannheim, Germany; German Center for Mental Health, Mannheim, Heidelberg, and Ulm, Germany.

[8]Donders Institute for Brain, Cognition and Behavior, Radboud University, Nijmegen, the Netherlands

* shared last authorship

Abstract:

Task-based functional magnetic resonance imaging (tb-fMRI) reveals individual differences in the neural basis of cognitive functions by linking specific tasks to neural responses. However, scaling tb-fMRI to population-level studies is challenging due to its cognitive demands, variations in task design across studies, and the limited scope of tasks in large datasets. To address this, we propose DeepTaskGen, a deep-learning approach that generates non-acquired task-based contrast maps from resting-state fMRI (rs-fMRI) data. Our approach enables generating synthetic task images for non-acquired tasks within the study protocol. We validate this approach using the Human Connectome Project lifespan data, then generate 47 contrast maps from 7 different cognitive tasks for over 20,000 individuals from UK Biobank. DeepTaskGen outperforms several benchmarks in generating synthetic task-contrast maps, exhibiting superior reconstruction performance while retaining inter-individual variation essential for biomarker development. Notably, we further showed that synthetic task contrast maps achieved similar or greater performance compared to actual task contrast maps and resting-state connectomes for predicting a wide range of demographic, cognitive, and clinical variables. This approach will facilitate the study of individual differences and the generation of task-related biomarkers by enabling the generation of arbitrary functional cognitive tasks from readily available rs-fMRI data.

Introduction:

Characterizing inter-individual variability in brain activity patterns has become crucial to understanding individual differences in cognition, behavior, and the risk for or resilience to mental disorders. Over the years, many techniques have been developed to discover the neural basis of individual differences. Among these, task-based functional magnetic resonance imaging (tb-fMRI) has emerged as a powerful technique as it can non-invasively measure changes in brain activity associated with a specific cognitive task. For example, the emotional face-matching task has been shown to activate several brain regions, particularly the amygdala[1], which has associations with mental disorders such as depression and anxiety[2]. Researchers can potentially identify individuals at risk of mental disorders by examining individual differences in task-related brain activation. Moreover, an increasing number of studies highlight that task-related brain activity improves prediction performance for individual differences in cognitive and behavioral traits, including fluid intelligence, cognitive flexibility, working memory capacity, and general cognitive ability, compared to task-free (resting-state) brain activity[3–7]. The flexibility of tb-fMRI in eliciting task-specific activations, coupled with its improved predictive power and promising findings regarding reliability[8,9], has established its role as a robust tool for understanding individual differences in brain activity[10].

Despite its advantages, task-based brain imaging has several limitations.

Firstly, it is less scalable than other brain imaging techniques like anatomical

imaging or resting-state fMRI (rs-fMRI) due to its cognitive demands, the need

for subject training and compliance, and because different studies often use

different task variants, which complicates aggregation across studies.

Therefore, large consortium studies such as the Human Connectome Project[11],

IMAGEN[12], and ABCD[13] mostly have data from only a few (usually simple)

tasks, with some notable exceptions, such as the Human Connectome Project

(HCP), which provides a comprehensive task battery[11]. This is even more

pronounced in populations that have difficulty in performing experimental

tasks, such as children or individuals with neurological or psychiatric

conditions. The second limitation arises from variations in experimental task

designs. Reliable and advanced biomarker discovery requires large-scale,

multi-site datasets to represent individual variations on a population scale.

However, this introduces the challenge of standardization, as researchers

must control for differences in scanning sites, parameters, and variations in

task designs. In many instances it is simply not possible to aggregate task

data from different cohorts because the differences between paradigms used

in each cohort are too large. This challenge is especially pressing in big-data

studies that require large samples to provide sufficient power to detect subtle

effects or to characterize inter-individual variability.

In this paper, we address these limitations by generating *synthetic* task-

based brain images from task-free resting-state data. This approach builds

upon the discovery that resting-state and task-based brain activity share the

same intrinsic network architecture.[14–16] Preliminary work has aimed to predict

inter-individual variations in task-induced brain activity from resting-state

data[15,17] Although interesting, these approaches have important limitations in

that they either fail to fully capture the complexity necessary for retaining

individual-specific information, lack effective methods for transferring learned

parameters to new datasets or do not cover the entire brain. Most importantly,

all such approaches have only been applied to cases where the true task data

were acquired. It is much more challenging to generate contrast images in

cases where the tasks were not acquired at all. We also argue that this feature

is essential for synthetic task images to be useful for biomarker construction.

To demonstrate usefulness, it is of utmost importance to show the predictive

utility of synthetic task images for clinically relevant outcomes, which is the

aim of this study.

Building upon prior work[17], we present a volumetric neural network

architecture, DeepTaskGen, that (i) addresses all the limitations mentioned

above, (ii) provides the ability to generate synthetic task-based images in

cohorts where these tasks were not acquired, and (iii) provides superior

reconstruction performance in several datasets compared to different baseline

methods, while simultaneously retaining individual differences that are

essential for biomarker development. To do so, we first train DeepTaskGen on

the Human Connectome Project Young-Adult (HCP-YA)[11] and demonstrate

competitive performance in retaining individual differences while predicting

task-based contrast maps (i.e., task-based brain activity). Next, we apply our

trained network to the Human Connectome Project Development (HCP-D)

dataset[18] to show its generalizability by predicting task-based contrast maps

absent from this dataset. Next, we apply our trained network to generate

synthetic task images for a comprehensive battery of cognitive functions for

one of the largest population-based datasets currently available (UK

Biobank).[19] Finally, we demonstrate the utility of these synthetic data as

biomarkers by predicting subjects' age, sex, fluid intelligence, grip strength,

and overall health, as well as several clinical measures, including hypertension

and depression diagnosis, alcohol use frequency, anxiety, and depressive

symptom scores. Remarkedly, we show that in many cases, synthetic images

achieve similar or greater performance than actual images.

Fig. 1: Input, DeepTaskGen architecture, and model evaluation on training and independent samples.

a. We utilized voxel-to-ROI rs-fMRI connectomes as input. A connectome was constructed for each subject by calculating the full correlation between the averaged time series from 50 ICA-based ROIs and the time series of individual voxels. **b.** Task-contrast maps for various tasks were predicted from rs-fMRI connectomes using our proposed DeepTaskGen architecture. DeepTaskGen is a volumetric U-Net model with attention mechanism that processes the input resting-state connectome through a series of convolutional blocks, each comprising a 3D convolution layer, batch normalization, and a non-linear activation function. By utilizing max

pooling, the model compresses images while preserving task-relevant patterns, and then, it
up-samples the images to align with the output task contrast maps. The numbers below each
block represent the output shape of each block and the number of feature maps (above). The
details of the architecture are presented in Supplementary Table 1. **c.** We trained and
evaluated DeepTaskGen on the HCP Young Adult dataset. The figure above shows the
reconstruction performance computed by taking Pearson's correlation between predicted and
actual contrast maps for representative contrasts from seven distinct tasks. The figure below
displays the diagonality index (the difference between the on-diagonal and the mean off-
diagonal elements in a correlation matrix, normalized by the mean on-diagonal values),
evaluating models' discriminability performance. We compared DeepTaskGen with methods
like group-averaged contrast maps, retest scans, and a linear model (each depicted in distinct
colors). **d.** We further fine-tuned the trained DeepTaskGen model on the HCP Development
dataset using either task contrasts (e.g., GAMBLING REWARD). We predicted the other
contrast (e.g., EMOTION FACES-SHAPES). The fine-tuned model was compared to the non-
fine-tuned DeepTaskGen and linear models (shown in distinct colors). Reconstruction
performance and discriminability were again used to assess the models' performance for each
task contrast.

Results:

DeepTaskGen demonstrates overall better reconstruction performance and discriminability on the training dataset.

First, we trained DeepTaskGen on the HCP-YA dataset using a train set ($n = 827$) and a validation set ($n = 92$). We used performance metrics assessing two distinct characteristics of synthetic contrast maps. The reconstruction performance, measured by similarity metrics such as Pearson's correlation or Dice Coefficient, quantize overlapping or association between predicted and actual maps. These metrics are widely adopted to evaluate generative methods in the literature[15,17,20–22]. Discriminability (or subject identification) metrics evaluate the subject-specific variation among predicted images, which is essential for biomarker discovery. To evaluate it, we used the diagonality index, a metric adopted in previous studies[17,20,22]. In this study, we assessed DeepTaskGen's reconstruction performance using Pearson's correlation, and diagonality index scores on a separate test set ($n = 39$). Additionally, while not specific to this context, fingerprinting scores are widely accepted for assessing subject identifiability from brain images[23]. Therefore, we present fingerprinting scores along with the Dice AUC score in the Supplementary Material (Supplementary Figure 2, and Table 4,6). Next, we used permutation testing to compare these performance measures with group-average task contrasts, a linear model[15], and retest scans (which can be seen as a theoretical upper bound on prediction ability). Figure 1c displays the results

for seven representative main task contrasts of seven different paradigms,

while Supplementary Figure 1 and Supplementary Tables 3,4 provide the

performance for all 47 task contrasts and their test statistics, respectively.

Additionally, we present the actual and predicted group-average maps for the

seven representative main task contrasts in Figure 2a.

DeepTaskGen produced consistently higher reconstruction performance

than the linear baseline (Fig 1b, Supplementary Figure 1 and 2). It achieved

the highest reconstruction performance on the RELATION REL $(r = .711, \sigma =$

$.067)$, WM PLACE $(r = .707, \sigma = .051)$, RELATIONAL MATCH $(r = .697, \sigma =$

$.071)$, and SOCIAL TOM $(r = .697, \sigma = .059)$ contrasts, while it yielded the

lowest performance on the GAMBLING PUNISH-REWARD $(r = .106, \sigma = .080)$,

and RELATIONAL MATCH-REL $(r = .238, \sigma = .146)$ contrasts. We also observed

a notable difference between the contrast maps with the highest (RELATION

REL) and lowest (GAMBLING PUNISH-REWARD) performance $(r = .605)$. We

achieved the highest reconstruction accuracy in the SOCIAL task, while the

MOTOR task yielded the lowest performance. Notably, this trend was also

observed in the retest scans, indicating significant variations in reliability

across different task-based contrast maps. Additionally, DeepTaskGen ($\mu =$

$.516, \sigma = .167)$, where μ and σ are the mean and standard deviation scores

across 47 contrast maps), achieved significantly greater reconstruction

performance than the linear model ($\mu = .367, \sigma = .127)$ in all 47 task

contrasts, indicating an advantage of our network in predicting task contrast

maps compared to the linear model after FDR correction (Supplementary

Figures 1, 2). DeepTaskGen also performed well relative to retest scans. It

significantly outperformed retest scans ($\mu = .470, \sigma = .206$) in 29 task

contrasts while achieving worse performance in 4 task contrasts. However, we

found no significant difference between DeepTaskGen and retest scans in 14

task contrasts in terms of reconstruction performance. The improved

performance of DeepTaskGen over retest scans can be attributed to scan-

specific noise present in retest scans or shared session-specific information

across both task-based and task-free brain activity retained by DeepTaskGen.

The group-average contrast maps ($\mu = .524, \sigma = .165$) achieved the highest

scores in reconstruction performance, significantly surpassing DeepTaskGen

in 31 tasks while 16 tasks showed no significant difference. However, these

group average maps do not provide any inter-individual variance whatsoever.

This emphasizes that reconstruction performance, although necessary, is not

sufficient for downstream analyses such as prediction and biomarker

development, which require individual-specific information.

DeepTaskGen achieved the highest discriminability, measured with

normalized diagonality index, in the LANGUAGE MATH-STORY task ($\mu =$

$.025, \sigma = .008$), whereas the GAMBLING PUNISH-REWARD task yielded the

lowest ($\mu = .0008, \sigma = .002$). Consistently, the LANGUAGE task showed the

highest discriminability ($\mu = .016, \sigma = .010$), while the MOTOR task had the

lowest ($\mu = .006, \sigma = .006$), which was the task having lowest discriminability

in retest scans. The same pattern of results was observed using the

fingerprinting score (Supplementary Figure 2). Additionally, DeepTaskGen

($\mu = .011, \sigma = .009$) consistently yielded higher discriminability than the linear

model ($\mu = .004, \sigma = .006$) in 40 of 47 task contrasts while providing similar

discriminability in the remaining 7 task contrasts. This indicates our model's

significant advantage in retaining individual differences compared to the linear

model. However, retest scans ($\mu = .097, \sigma = .071$) showed the highest

discriminability, suggesting they provide the most distinct task contrasts.

However, this high discriminability may be influenced by individual-specific

noise.

In summary, compared to various baseline methods, DeepTaskGen

achieves a good balance between reconstruction performance and maintaining

individual-specific variation. The test results for all 47 task contrasts are given

in Supplementary Table 3-6. Although it was not the goal of this work to

systematically compare surface-based approaches with volumetric

approaches, we present error metrics from comparable surface-based deep

learning approaches in Supplementary Figure 5 and 6. These show an

advantage for volumetric approaches in terms of reconstruction, whereas

surface-based approaches show better discriminability independent of model

type.

DeepTaskGen allows for generating contrast maps on an unseen dataset

Next, we evaluated DeepTaskGen's performance in generating task contrasts on a dataset not included in its original training. To do this, we used the HCP-D dataset, which is ideal because it shares multiple tasks with the HCP-YA dataset used for training the model. This, in turn, allows us to assess the quality of the map generation against ground truth. To adapt the pre-trained model to the new dataset, we fine-tuned it using a single task contrast common to both datasets (see Methods). We then used the fine-tuned model to predict the task contrast that we did not use during fine-tuning. For example, the model for the GAMBLING REWARD contrast was fine-tuned using EMOTION FACES-SHAPES, and vice versa for EMOTION FACES-SHAPES. Furthermore, we assessed to what extent the trained model performed on an unseen dataset without fine-tuning, which we referred to as "No Finetune."

Fig 1d depicts the reconstruction and discriminability performance of the models for the task contrasts mentioned above. Overall, fine-tuning improved discriminability according to the diagonality index, and had mixed results for reconstruction. In more detail, DeepTaskGen-based models showed significantly better reconstruction performance (i.e., correlation) than the linear model in the "GAMBLING REWARD" contrast ($t = 10.225$, $p_{1000} = .004$, $\delta = .340$) (Supplementary Table 7), while providing similar performance for EMOTION FACES-SHAPES. While the fine-tuned model with EMOTION FACES-

SHAPES outperformed the non-fine-tuned model in the GAMBLING REWARD

contrast $(t = 3.675, p_{1000} = .005, \delta = .142)$, the fine-tuned model with

GAMBLING REWARD performed significantly worse in the EMOTION FACES-

SHAPES contrast $(t = -11.059, p_{1000} = .004, \delta = -.624)$ compared to the non-

fine-tuned model. A similar pattern of results was observed for Dice AUC

(Supplementary Figure 2).

Regarding discriminability, the fine-tuned model significantly outperformed

both the non-fine-tuned $(t = 4.392, p_{1000} = .003, \delta = .333)$ and linear models

$(t = 3.998, p_{1000} = .003, \delta = .347)$ in the EMOTION FACES-SHAPES task

according to the diagonality score. For the the GAMBLING REWARD contrast,

the fine-tuned model significantly surpassed the non-fine-tuned model $(t =$

$5.743, p_{1000} = .003, \delta = .357)$, yet performed comparably relative to the linear

model $(t = 1.362, p_{1000} = .200)$ (Supplementary Table 8). The reduced

discriminability advantage of the fine-tuned model over the linear model in

the GAMBLING REWARD task is likely due to dataset-specific differences in the

GAMBLING task (see Discussion). The test results for the additional

performance metrics are given in Supplementary Figure 3 and Supplementary

Table 9, 10. Interestingly, fine tuned models show a lower discriminability

under the fingerprinting score. This is not unexpected given they are sensitive

to different aspects of the data. In most cases we prefer the diagonality index,

since it is sensitive to magnitude differences, whilst the fingerprinting score is

a 'winner takes all' approach.

In summary, DeepTaskGen-based models enable the prediction of trained

task contrast maps on datasets lacking such maps. However, the benefit and

optimal approach for fine-tuning varies depending on the specific task contrast

and therefore should be done with care.

Fig. 2: Visualization of group-level contrast maps and similarity (or dissimilarity) among subjects.

a. Group-level contrast maps for seven representative tasks were generated for predicted maps on three datasets (HCP Young Adult, HCP Development, and UK Biobank) and compared to actual task contrast maps from HCP-YA. Activations and deactivations are displayed using

scaled z-scores, with colors indicating the magnitude of the effect (shown in the color gradient

bar). **b.** To visualize within- and between-task variance among subjects, we employed

Uniform Manifold Approximation and Projection (UMAP), a non-linear dimensionality reduction

technique. UMAP projects high-dimensional task contrast maps into two dimensions for clear

visualization, allowing us to assess if the projected datasets contain individual- and task-

specific information necessary for downstream analyses. Each dot represents a subject's task

contrast map for the seven tasks, colored accordingly. Similar subjects are positioned closer

together, indicating similarity, while distant dots represent dissimilarity. Accordingly, wider

spread within tasks and greater distance between tasks represent higher within- and

between-task variability. Note that we fitted a separate UMAP model to each dataset, as

indicated in each column and row.

Predicted task contrast maps achieve stronger or comparable

performance in predicting demographic, cognitive, and clinical

variables

Next, we sought to demonstrate the utility of synthetic task images for

downstream prediction tasks within the UK Biobank dataset. To achieve this,

we fine-tuned our model on the UK Biobank dataset using EMOTION FACES-

SHAPES task contrast ($\mu_{reconstruction}$ = 0.428, $\sigma_{reconstruction}$ = 0.140,

discriminability = 0.189) and predicted seven representative contrasts from

each task available in HCP-YA (Figs. 3-4).

To ensure that the predicted task contrast maps retain overall network

structure and capture individual- and task-related variance for downstream

analyses, we visualized them in two ways, along with the actual task contrast

maps from the HCP-YA dataset as a reference. First, we generated group-

average maps and observed excellent correspondence with the canonical

networks for each task[24] and the actual task contrasts (Fig. 2a). We also noted

variability across datasets (e.g., reduced WM-related activation in UKB, which

comprises mid and late adults, compared to other datasets). Then, we fit

Uniform Manifold Approximation and Projection (UMAP)[25] to each dataset to

visualize high-dimensional differences between individuals and experimental

tasks in a more intuitive two-dimensional space (Fig. 2b). We found that the

predicted task contrast maps generated by DeepTaskGen contain lower

within-task variance yet improved between-task variance compared to actual

task contrast maps. This improvement can be attributed to the extensive

denoising performed by our neural network during reconstruction, enhancing

the signal-to-noise ratio (see Discussion).

Fig. 3: Prediction of subjects' age, sex, fluid intelligence, and dominant

hand grip strength using task contrast maps and resting-state connectome

on UK Biobank.

We predicted subjects' demographic and cognitive measures in the UK Biobank dataset using

three modalities: resting-state connectome, actual contrast map from the EMOTION task, and

seven synthetic task contrast maps. All predictions were made using L2 regularized regression

(i.e., ridge regression) within a 5-fold cross-validation framework with permutation testing

($P = 1000$). Blue represents resting-state connectome and actual task contrast maps, while

red represents predicted task contrast maps. Note that only the EMOTION task has both actual

and predicted contrast maps on UKB, indicated in blue and red, while the remaining six tasks

are indicated in red as UKB does not provide them. Significant predictions based on

permutation testing are highlighted. Error bars indicate the standard deviation of prediction

performance across five CV folds. Balanced accuracy was used for sex classification, while

Pearson's correlation assessed the other variables. Sample sizes for all analyses are indicated

in each figure. An asterisk (*) indicates a significant difference in prediction performance

between annotated maps and resting-state connectome data, while two asterisks (**)

represent a significant difference between the annotated maps and actual task-contrast maps.

Detailed test statistics are provided in Supplementary Tables 12, 14-17.

We then compared the prediction performance of each of the seven

predicted task contrast maps to that of actual task contrast maps and resting-

state connectome data using permutation testing ($P = 1000$). Specifically, we

aimed to predict individuals' demographic, cognitive, and clinical measures,

including age, sex, fluid intelligence, dominant hand grip strength, overall

health, alcohol use frequency, weekly beer intake, hypertension diagnosis,

depression diagnosis, depressive symptoms (Patient Health Questionnaire

[PHQ]-9[26] and Recent Depressive Symptoms [RDS]-4[27]), anxiety symptoms

(Generalized Anxiety Disorder Assessment [GAD]-7[28]) and neuroticism from

predicted and actual task contrast maps, as well as resting-state connectome

data. These were chosen because other studies have reported high prediction

accuracy using these tasks[29,30] and they are measures representing

individuals' mental health. The exact IDs for the variables are given in

Supplementary 11.

The results, presented in Figures 3-4 and Supplementary Tables 12-20,

show that the predicted task contrasts achieved greater or comparable

prediction performance relative to actual EMOTION FACES-SHAPES task

contrasts and resting-state connectome data for all variables. Specifically, we

observed a large improvement in sex and age prediction using synthetic task

contrasts, indicating that DeepTaskGen retains task activity patterns related

to unique biological traits and amplifies their detection due to enhanced signal-

to-noise ratios. Notably, for several clinically relevant measures, including

RDS-4 (Supplementary Figure 4), PHQ-9, hypertension diagnosis, alcohol use

frequency, synthetic task contrasts achieved significant prediction, while

actual brain measures could not survive permutation testing. This enhanced

performance indicates that synthetic task contrast maps can retain amplified

complex activation patterns related to subjects' clinical characteristics.

Additionally, despite low prediction performance, only the actual EMOTION

FACES-SHAPES withstand permutation testing for overall health prediction.

None of the brain measures could survive permutation testing for the

prediction of neuroticism and depression diagnosis (Supplementary Figure 4).

We predicted subjects' clinical measures in the UK Biobank dataset using three modalities:

synthetic task contrast maps, actual task contrast maps, and resting-state connectome data.

resting-state connectome, actual contrast map from the EMOTION task, and seven synthetic

task contrast maps. All predictions were made using L2 regularized regression (i.e., ridge

regression) within a 5-fold cross-validation framework. Permutation testing ($P = 1000$) was

used to assess the significance of out-of-sample performance against a null distribution.

Actual and synthetic brain measures are depicted in blue and red colors, respectively. Note

that only the EMOTION task has both actual and predicted contrast maps on UKB, indicated

in blue and red, while the remaining six tasks are indicated in red as UKB does not provide

them. Significant predictions based on permutation testing are highlighted. Error bars indicate

the standard deviation of prediction performance across five CV folds. Balanced accuracy was

used to measure depression classification performance, while Pearson's correlation was

employed to assess other variables. Sample sizes for all analyses are indicated in each figure.

Test statistics were only performed between predictions surviving permutation testing. The

detailed test statistics are given in Supplementary Tables 12,18-20. The results for the

additional clinical measures are depicted in Supplementary Figure 4.

Discussion:

In this work, we present DeepTaskGen, a robust neural network architecture designed to predict task-based contrast maps using volumetric resting-state connectivity. This architecture enables the prediction of task contrasts on unseen datasets, even when task contrasts are unavailable or have not been acquired. We employed this method to generate task data for a comprehensive battery of cognitive tasks for the UK Biobank dataset and show that these synthetic task images retain individual-specific information essential for biomarker discovery.

We showed that our approach accurately predicts task-based contrast maps from resting-state connectivity in both the training dataset (HCP-YA) and unseen datasets (HCP-D and UKB). DeepTaskGen showed excellent reconstruction performance in that it outperformed retest scans in terms of more than half of the task contrasts and performed consistently better than a linear baseline model, which aligns with previous work[17]. Importantly, DeepTaskGen's generated task contrasts preserve individual differences relative to linear models and group-average maps. This indicates that these synthetic contrast images may be better suited as biomarkers for individual-specific differences. Although group average maps show better reconstruction performance, they do not retain such individual-specific differences.

Notably, we observed variable performance when fine-tuning our model on HCP-D, which can be attributed to slight differences in the GAMBLING task

between HCP-YA and HCP-D. Surprisingly, we found that non-fine-tuned

models often perform as well or better than models fine-tuned for specific

contrasts. More specifically, the GUESSING task is an adaptation of the

GAMBLING task[31], with modifications to make it more child-friendly and

incorporate a magnitude manipulation[18]. This slight difference in the target

task could result in performance loss for the fine-tuned model compared to

the non-fine-tuned model in EMOTION. This may be because the slight

difference in the adapted task could introduce shifts in feature

representations, which the backbone may capture during fine-tuning,

potentially leading to suboptimal transfer and reduced performance.

Conversely, we observed a significant performance advantage of fine-tuning

in GAMBLING, because EMOTION, which is the same in both datasets, was

used for fine-tuning. Moreover, the slight task paradigm variation explains the

lack of discriminability performance gain of the fine-tuned model over the

baseline linear model in GAMBLING and the increased reconstruction

performance discrepancy between datasets compared to EMOTION.

Collectively, these findings underscore the critical role of domain similarity in

fine-tuning outcomes and indicate that fine-tuning should be performed and

evaluated carefully.

One of the key contributions of this work is a set of synthetic images in UKB

for tasks that were not acquired. We made use of these to perform extensive

validation analyses to showcase the advantage of using predicted task

contrast maps for predicting individual differences in an extensive set of

demographic, cognitive, and clinical variables. Our results indicate that these

predicted maps offer equivalent or better performance in all the scenarios we

evaluated relative to actual EMOTION FACES-SHAPE task contrast images and

resting-state connectome data. This is likely because our approach increases

the signal-to-noise ratio in the synthetic data by (i) reducing inherent noise in

functional MRI data and (ii) allowing an increase in the temporal degrees of

freedom from resting-state scans that are frequently longer than task-based

scans. Inherent noise removal (i.e., denoising) occurs on several levels within

the U-Net architecture, most notably on the downsampling (i.e., encoding)

branch. Similar to other dimensionality reduction methods, the network

compresses the information in the input image that is most relevant to the

target image, suppressing unrelated information attributed to noise. During

training, the weights of these blocks are constantly updated to force the

network to extract the most relevant information to the target contrast maps,

minimizing overall loss. Due to these inherent mechanisms, U-Net has been

widely used to remove noise from biomedical images[32,33]. Moreover, we

observed variability in the predictive performance of various synthetic task

contrasts, which indicates DeepTaskGen's capability to retain task-specific

variability, also evidenced in the UMAP visualizations (Fig. 2b). This reinforces

DeepTaskGen as a robust tool to facilitate predictive neuroscience.

Our method builds directly upon the foundational work of Tavor et al.[15] and

Ngo et al.[17], who demonstrated the potential to predict task-based brain

activity from resting-state brain connectivity. However, these previous

methods have additional limitations. Tavor et al. employed a linear model,

which fails to capture the complexity of the shared network architecture

between task-based and task-free brain activity and does not effectively

transfer learned parameters to unseen datasets. Ngo et al.[17] introduced a

neural network-based architecture, but it is limited to the cortical surface,

thereby excluding subcortical areas and cerebellum that are crucial for

cognitive functions[34-36] and mental disorders[37-39]. In contrast, our proposed

network, DeepTaskGen, overcomes these drawbacks, generating task

contrast maps of the entire brain in new cohorts where such maps were not

acquired. Additionally, Ngo et al.[17] proposed a reconstructive-contrastive loss

to enhance inter-subject variance in predicted contrast maps while minimizing

within-subject differences. While the authors observed increased inter-subject

variance, they noted its ineffectiveness for fine-tuning, therefore suggested

using the mean squared error loss (MSE), which may still bias predictions

toward the group average on target datasets. We also observed a similar

pattern, where reconstructive performance decreased with increasing inter-

subject contrast. To address this, we introduced Contrast-Regularized

Reconstructive Loss (CR-R), which can be applied to both training and target

samples without compromising reconstruction performance. It should be

noted that even with these modifications, all methods are regularized toward

predicting the group average, consistent with earlier findings[15,17,40]. Whilst this

approach yields good reconstruction performance, it is clear that sufficient

inter-individual variation remains for meaningful behavioral prediction, as

shown in Figure 3 and in the diagonality index. Moreover, the improved

generalizability to new cohorts and predict tasks that were not acquired is an

important contribution of this work.

DeepTaskGen holds a wide range of implications in neuroscience studies.

One significant application is the prediction of contrast maps for age groups

for whom task data are difficult to acquire, such as children or individuals with

neurological and psychiatric disorders. We showed that synthetic contrast

maps facilitate predictions and biomarker studies within populations where

acquiring task-based fMRI data may be challenging, which creates a significant

potential to expand the scope of precision psychiatry. However, the

correspondence between resting-state and task-evoked brain activation may

vary across different groups, including those with disorders. Therefore, a

model trained solely on healthy controls might require careful fine-tuning to

ensure accurate predictions in disorder groups, which should be a focus of

future studies. Another important application of DeepTaskGen lies in methods

that utilize population data, such as normative modeling[41]. A recent study

modeling the heterogeneity in the Emotional Face Matching Task using

population-wide life-long normative modeling indicates a notable gap in mid-

adulthood age groups[42]. In this case, we believe DeepTaskGen can play an

important role in this context by augmenting contrast maps for the

underrepresented age group in their database. Additionally, while the UKB

dataset contributes a large portion of their data due to its sample size, it only

includes the Emotion Face Matching Task, limiting the replication of such

models for other fMRI tasks. DeepTaskGen can also address this challenge by

generating corresponding synthetic task contrasts by requiring only resting-

state fMRI data, which can then facilitate the development of more

comprehensive normative models. Furthermore, our method can benefit

large-scale imaging genetics studies, such as genome-wide association

studies (GWAS), where potential associations between genotypes and brain-

based phenotypes are studied. For instance, our approach allows pooling data

to test for associations between putative genetic variants and specific task-

evoked activity patterns. A recent study[43] revealed significant genotype-

phenotype associations using multimodal neuroimaging data from UKB, but it

still faces the limitations mentioned above. Thus, DeepTaskGen can also

enhance GWAS by enabling more specific and task-related associations using

synthetic task contrasts. It is important to note the difference in variance

distribution between predicted and actual task-based contrast maps. Actual

images contain task-related variation (i.e., signal) and epistemic variation (or

noise)[41]. During the prediction process, such noise can be effectively removed,

amplifying the variance across experimental tasks by retaining only task-

related variance. This can be seen in the UMAP visualizations in Fig. 2b, where

predicted maps showed lower within-task contrast variance but higher

between-task contrast variance than actual maps. Such removal of epistemic

noise results in an increased signal-to-noise ratio, leading to improved

prediction performance in our validation analyses. While this may not be

critical for traditional statistical methods like group comparisons, it becomes

more important when these images are used in complex models where noise

is explicitly modeled. Therefore, we strongly recommend careful model

designs that consider this difference when incorporating both data types within

a single model. Additionally, one could utilize latent information in the resting-

state connectome extracted by autoencoders to maximize phenotype

prediction performance as this latent information hypothetically contains

necessary details to generate task-based contrast maps. However, like prior

methods, we provide synthetic contrast maps that can surpass the prediction

performance of actual maps, as indicated in this study, while also providing

synthetic maps spatially equivalent to actual maps. This ensures that synthetic

images remain informative and straightforward to interpret, which is critical

for several downstream analyses.

Several methodological considerations should be noted when interpreting

our results. First, the spatial Independent Component Analysis (ICA) and task

contrast maps provided in the HCP-YA dataset are surface-based (i.e., fs_LR

surface). We projected these surface-based images to the volumetric MNI

space using a well-established method, Registration Fusion[44], which, despite

its promise, might not be as optimal as direct registration to the coordinate

system during preprocessing. Therefore, the projected contrast maps may

have potential differences from those originally preprocessed in volumetric

space, which might impact prediction performance. Second, despite being

more reliable than traditional ICA approaches, group-level ICA maps may still

not be optimally reliable due to their data-driven nature. This may be

particularly important when group-level ICA maps are estimated separately

on different datasets. However, in this study, as mentioned above, the same

ICA map provided by HCP was used as the primary map to parcellate rs-fMRI

images across datasets. Additionally, parcellation was done in a common MNI

space to ensure reliability across datasets. Third, the different dimensionalities

of ICA maps used to parcellate rs-fMRI might result in varying prediction

performance. Although ICA maps with higher dimensionality could provide

voxel-to-region of interest (ROI) connectomes with greater granularity, they

would significantly increase the size of the connectome, rendering it

computationally infeasible due to excessive GPU memory usage. Conversely,

ICA maps with lower dimensionality could serve as a natural feature reduction

method; however, the resulting voxel-to-ROI connectome might be too

simplistic to retain the spatial information important for predicting task

contrast maps. Although this is beyond the scope of the current study, we

strongly believe that the effect of input dimensionality on model performance

should be investigated in future studies. Forth, while HCP-YA is the largest

open dataset with multimodal fMRI, the sample size may still be suboptimal

to fully capture the true individualized patterns between rest- and task-based

fMRI[45]. UKB offers a significantly larger sample size, including subjects

recorded multiple times, which can serve as a reference for test-retest

reliability. Although this is beyond the scope of the present study, which aims

to present a model that can generate multi-domain synthetic task-based

contrasts, evaluating generative models on such a large sample will be

necessary in future studies. Moreover, as described in the Methods section,

the presented fine-tuning routine is most effective when the latent brain

network architecture underlying task activations and resting-state

connectome remains relatively stable between the source and target datasets.

When applied across substantially different age groups, model transferability

might be reduced due to the evolution of cognition and brain architecture over

developmental stages, leading to varying brain activation patterns under

cognitive tasks[46]. In such cases, fine-tuning the entire network without

freezing the final layer could provide a better adaptation strategy, allowing

the model to learn age-specific modifications between the task-related final

layer and the brain network-related backbone layers, while leveraging shared

functional patterns. However, as this is not a direct task activation transfer,

researchers should interpret the results more cautiously than those obtained

with the presented fine-tuning routine. Another option would be to incorporate

multi-task learning by adding auxiliary tasks, such as age prediction, during

training and fine-tuning. This approach might force the model to retain age-

related information, as has been evidenced by a previous study[47].

Furthermore, while methods using volumetric images provide varying

reconstruction performance (depending on task contrast), they exhibit lower

discriminability compared to surface-based methods (Supplementary Figure

5,6). Notably, this reduction is not specific to DeepTaskGen but is a

characteristic of volumetric-based methods, as DeepTaskGen demonstrated a

greater performance gain over the baseline linear model compared to surface-

based generative methods (Supplementary Figure 7,8). This difference

between surface and volume can be attributed to factors such as variations in

preprocessing and brain representation (e.g., surface vs. volume, total

number of vertices vs. voxels). Researchers should select surface- or

volumetric-based generative methods based on their research scope (e.g.,

subcortical involvement) and data availability. Additionally, future research

should explore methods to reduce the disparity between surface and

volumetric data.

In summary, we have demonstrated DeepTaskGen, a general-purpose tool

for generating arbitrary synthetic task images from resting-state data. We

consider that this will facilitate the study of individual differences and the

generation of task-related biomarkers.

Methods:

Datasets:

Supplementary Table 2 provides the sample details and functional scan acquisition parameters for the datasets used in this study. Further preprocessing details are provided in the supplementary material.

Human Connectome Project Young-Adult (HCP-YA): The Human Connectome Project Young-Adult (HCP-YA) 1200 Release was used as a main dataset to train and evaluate models[11]. 958 participants comprising all the task and resting-state sessions were included. Of those 958 subjects, 39 have re-test 3T fMRI data from the second visit, which we used as an evaluation set. Rs-fMRI data were acquired in four 15-minute runs, with 1200 timepoints per run, totaling 4800 timepoints per subject. However, since fewer timepoints (e.g., 300-500) are common in neuroimaging datasets and stable functional connectivity can be computed with shorter resting-state acquisitions[22,23], we divided resting-state data into eight contiguous parts (600 timepoints) as previously shown[17]. Similar to previous studies[15,17], we used ROIs from the 50-component parcellation derived from spatial ICA released within HCP-YA to compute individual functional connectivity. As tb-fMRI data, we used 47 unique contrasts from 7 main task domains[24]: WORKING MEMORY, EMOTION, SOCIAL, RELATIONAL, LANGUAGE, MOTOR, and GAMBLING. We used minimally preprocessed and FIX-cleaned fMRI data provided by HCP[48]. While HCP also provides volumetric rs-fMRI data, the spatial ICA maps, and z-

transformed task-activation maps are only surface-based. Therefore, we

projected surface-based data to volumetric space using the registration fusion

(RF-ANTs) method[44]. Registration Fusion is a popular method that allows

nonlinear mapping between MNI152 and fsaverage coordinate systems using

coordinate mapping computed on 745 subjects from the Brain Genomics

Superstruct Project (GSP)[49]. The details of the mapping process are given

elsewhere[44]. Briefly, we separated CIFTI files into a cortical surface in fs_LR

space (wb_command –cifti-separate) and a subcortex in MNI space, mapped

the cortical surface into fsaverage space (wb_command –metric-resample)

using HCP Workbench Command[50]. We then projected it into volumetric space

using registration fusion and combined it with the subcortex to create a whole-

brain volumetric image. Projected contrast maps were then visually checked

for alignment to MNI space and corresponding task activation patterns. Note

that the projected images only contain gray matter. We also binarize a

reference   projected   image   (melodic_IC.dscalar.nii,   containing   ICA

components) to use as a gray matter mask. Subsequently, the scan images

were downsampled to 2x2x2 mm voxel resolution and cropped to the cortex

(resulting image dimension is 76x93x78) to reduce the computational costs.

Human Connectome Project Development (HCP-D): The evaluation of

DeepTaskGen's generalizability across different populations with various age

groups and transferability of learned parameters to unseen datasets was

conducted on the HCP-Development (HCP-D) dataset from the HCP-Lifespan

project[18]. 637 subjects that had completed four resting-state runs (488

timepoints per run) and Emotion[1] and Guessing[31] tasks were included in the

study. The choice of Emotion and Guessing tasks was due to the Emotion task

performed in both the main HCP-YA and HCP-D projects, while the Guessing

task served as an adaptation of the Gambling task in HCP-YA, with some

modifications.

UK Biobank (UKB): To assess the practical applicability of generated

contrast maps and further generalizability of the trained model on a large-

scale sample, we used the UK Biobank dataset[19]. A total of 20,792 subjects

with resting-state (490 timepoints) and Emotion task[1] MRI images were

included in this study.

Voxel-to-ROI functional connectivity:

DeepTaskGen employs resting-state voxel-to-ROI connectivity to predict

task contrasts. Voxel-to-ROI connectivity is computed as Pearson's correlation

between each voxel's time series and the average signal of the target ROI[51].

The target ROIs are derived from components obtained through group-level

independent component analysis (ICA) applied to resting-state fMRI time

series[52]. Voxel-to-ROI connectivity provides an increased spatial resolution

compared to the conventional ROI-to-ROI approach, which requires deeper

models at the generation step. Although voxel-to-voxel connectivity could

produce a higher spatial resolution than voxel-to-ROI connectivity, it is

computationally infeasible due to excessive GPU memory use. Additionally, as

mentioned earlier, the voxel-to-ROI approach allows for modeling the

connectivity of the entire brain, providing a more inclusive solution than the

vertex-to-ROI approach.

DeepTaskGen:

The architecture of DeepTaskGen is depicted in Fig 1. DeepTaskGen is a

volumetric adaptation of BrainSurfCNN[17], a surface-based convolutional

neural network based on U-Net architecture[53] widely used in biomedical image

segmentation with additional attention mechanism[54]. Like autoencoders, U-

Net consists of encoding (i.e., downsampling), decoding (i.e., upsampling)

blocks, a bottleneck layer and skip connections. Specifically, DeepTaskGen's

network architecture is as follows: each block in the encoding and decoding

arms consists of a 3D convolutional layer, batch normalization, and non-linear

ReLU activation function. Additionally, max pooling (MaxPool3d) is applied

before each encoding block to reduce the dimensions of the input image by

half by retaining task-related information. In contrast, compressed images are

upsampled before each decoding block to match the output dimensionality

with actual maps. In addition to BrainSurfCNN[17], we incorporated an attention

gate into each skip connection. This enhancement helps the network focus on

relevant features from the encoding blocks while suppressing irrelevant

activations, thereby improving overall model sensitivity[54]. The details of the

architecture are provided in Supplementary Table 1.

Contrast-Regularized Reconstructive Loss:

Unlike the previous study[17], we did not utilize the reconstructive-contrastive

(RC) loss in model training and fine-tuning. Although RC loss enhances the

variance among subjects' generated contrast maps, it can reduce

reconstruction performance by over-emphasizing the contrastive component,

particularly in transfer samples with smaller datasets, as reported by the

authors[17], who proposed the loss. Instead, we minimize the Contrast-

Regularized Reconstructive Loss (CR-R) loss, in which we regularize the

contrastive part of the reconstruction loss (RC) and further combine it with

the reconstructive loss (i.e., mean squared error, MSE) to prevent the model

from losing focus on increasing reconstruction performance. Given a mini-

batch of N subjects, $B = \{x_i \dots x_N\}$, in which x_i is the actual contrast maps of

subject i, the CR-R loss L_{CR-R} is defined as:

$$(1) L_R = \frac{1}{N}\sum_{i=1}^{N} d(x_i, \hat{x}_i) \qquad (2) L_C = \frac{1}{(N^2-N)/2}\sum_{\hat{x}_j \in B, j \neq i}^{N} d(x_j, \hat{x}_i)$$

$$L_{CR-R} = L_R + \alpha \min(L_R - L_C + \lambda, 0)$$

where $d(.)$ is L2 norm, L_R is the reconstructive loss calculated as mean-

squared error (MSE) between actual and generated contrast maps, and L_C is

the contrastive loss calculated as MSE between subjects generated contrast

maps and actual contrast maps of the remaining subjects. L_{CR-R} encourages

L_C to be larger than L_R by a margin λ and further combines it with L_R to prevent

the model from reducing reconstruction performance while increasing inter-

subject contrast. The hyperparameter α controls the weight of contrastive part

of the in this combined objective. Thanks to its integrated nature, CR-R does

not require separate training sessions with MSE and RC loss, further

simplifying the training process.

Model Training:

DeepTaskGen was trained on HCP-YA ($n_{train} = 827, n_{validation} = 92, n_{test} = 39$)

for 100 epochs using a batch size of 10, CR-R as the loss function ($\lambda = 1$ and

$\alpha = 0.25$), and the Adam optimizer.

As the task contrasts maps projected from fs_LR space (see Supplementary

Material for detailed descriptions) and includes only gray matter, we used only

these voxels to minimize the loss function. The model training was conducted

on a single Nvidia A100-40GB GPU and took approximately 6 hours.

Model transfer to HCP-D and UKB:

Our main objective for the HCP-D dataset was to validate the performance

of DeepTaskGen to predict unavailable arbitrary task contrast maps on an

unseen dataset. For instance, we fine-tuned the model using the EMOTION

FACES-SHAPES contrast to predict the GAMBLING REWARD contrast. This

approach relies on the assumption that the weights in the trained model's

output layer are specific to a given task contrast (e.g., GAMBLING REWARD),

while the backbone layers (i.e., all the layers before the output layer) contain

information shared across multiple task contrasts yet differ across datasets

due to dataset-related features. We also assume that the task-specific output

layer is similar across datasets, as it primarily processes task-specific high-

level features using dataset-specific low- and mid-level features, such as

variations in MRI acquisitions or preprocessing, from the backbone layers,

whereas the backbone layers differ due to dataset-specific differences. By

adapting only the backbone of the model, we can effectively predict the

trained contrasts from HCP-YA. To achieve this, we froze the parameters of

our trained model's output layer and fine-tuned the backbone of our model on

the HCP-D dataset using either GAMBLING-REWARD or EMOTION FACES-

SHAPES contrast. Specifically, we fine-tuned the pre-trained model using only

a single task contrast (e.g., GAMBLING-REWARD) for 50 epochs. We used 515

and 58 subjects for training and validation during fine-tuning, respectively.

Subsequently, we replaced the output layer of the fine-tuned model with one

that matched the target task contrast (e.g., EMOTION FACES-SHAPES) and

predicted the target task contrast maps for 64 test subjects (i.e., holdout set).

The model transfer performance of DeepTaskGen was also compared with that

of a non-fine-tuned model and linear regression.

The initially trained model was further fine-tuned on UKB ($n_{train} =$

$16840, n_{validation} = 1872, n_{test} = 2080$) to test the practical applicability of

predicted task contrast maps. We fine-tuned the backbone of the trained

model using the EMOTION FACES-SHAPES task contrast available in UKB for

50 epochs. Then, we replaced the coefficients in the output layer of the fine-

tuned model with corresponding model coefficients of the 47 task contrasts

available in the training dataset to predict these task contrast maps for 2080

test subjects. Notably, despite being significantly larger than HCP-YA in terms

of sample size, the UK Biobank (UKB) was not utilized for pre-training the

main model, as it only provides one fMRI task, EMOTION, which is insufficient

for training a multi-modal model.

Baselines:

Group-average contrasts: The group-average contrasts were utilized as

a reference to represent the features in the task contrast that are shared

among individuals. A simple predictive model can effectively capture these

common features. By comparing the performance of the predicted task

contrasts with the group-average contrasts, we can assess the degree to

which the predicted task contrasts capture individual-specific information

beyond what is captured by the common features represented in the group-

average contrasts. It could also show the degree to which variation would be

in each task contrast, e.g., a high correlation between true and group-average

task contrasts indicates a reduced level of inter-individual variation.

Retest scans: The additional tb-fMRI data acquired in a second run ($n =$

39) was used to evaluate the reliability of the task contrasts.

Linear Model: We implemented this baseline model based on the approach

presented by Tavor and colleagues[15], as it is the pioneering study in predicting

task-based contrast maps from resting-state connectivity. While the original

method was developed and tested using surface brain images (i.e., CIFTI

files), we adapted it into volumetric space for an unbiased comparison. Within

each of 50 ROIs (defined using 'melodic_IC_ftb.dlabel.nii', provided by HCP,

projected to MNI using registration fusion), we vectorized the input resting-

state connectomes and target contrast maps. A linear regression model was

fit to map between input and target vectors, restricted to these regions

containing only gray matter (157,461 voxels) to prevent nuisance effects of

white matter and CSF signals. Fitting separate linear models to each ROIs

resulted in a large weight matrix with dimensions R x S, where R represents

the number of ROIs and S represents the number of subjects in the training

set and validation set combined ($n = 919$). We averaged this weight matrix

across subjects to create a vector containing average weights for ROIs. We

then predicted the corresponding task contrast maps for subjects in the test

set using this weight vector. This procedure was repeated for each of the 47

task contrasts, resulting in 2.159.650 linear models fit during training.

Visualization of group-level contrast maps and inter-subject and inter-task similarity:

To evaluate the structure of the predicted task contrast maps, we visualized both common structural elements across subjects (Figure 2a) and similarities or differences between subjects for various task contrasts (Figure 2b). Figure 2a displays the common brain structure by presenting the voxel-based sample average of the task contrast maps across all subjects.

We employed a non-linear dimensionality reduction method, Uniform Manifold Approximation and Projection (UMAP)[25], to visualize the similarity or variance between subjects and across various tasks. UMAP preserves global and local topological structure while embedding high-dimensional data into a lower-dimensional space. Specifically, UMAP was utilized to project the high-dimensional task-based contrast maps into a two-dimensional space (i.e., two components), where each dot represents a subject's task contrast map. This allows for a straightforward interpretation of similarity or dissimilarity between subjects and fMRI tasks by considering the distance between dots on the two-dimensional plot. We implemented UMAP in Python using the umap-learn package with default hyperparameters $(n_{neighbors} = 15, metric = euclidean)$. To retain and visualize the global and topological details and achieve optimal embedding within each dataset, we fit a UMAP model to each dataset separately.

Prediction of cognitive and demographic data for validation:

To validate the clinical relevance of our model, we predicted multiple non-imaging variables using the synthetic images derived from the UK Biobank dataset. Specifically, we aimed to predict three main domains: physical (age, sex, grip strength of the dominant hand, overall health), cognitive (fluid intelligence), and mental health (alcohol use frequency, weekly beer intake, hypertension diagnosis, depression diagnosis and symptoms (PHQ-9[26] and RDS-4[27]), anxiety symptoms (GAD-7[28]), and neuroticism). These phenotypes cover key aspects of individuals' demographics and well-being and have been shown to associate brain biomarkers[55]. Additionally, they have been extensively analyzed in the UK Biobank dataset, further supporting their relevance[27,29,30,56]. We used a similar L2 regularized linear model (i.e., ridge regression) and training and evaluation procedure for all these prediction analyses (see below). The exact sample size for each prediction is provided in Figures 3-4.

All regression models were built using predicted contrast maps for seven main task contrasts (EMOTION FACES-SHAPES, GAMBLING REWARD, WM 2BK-0BK, LANGUAGE MATH-STORY, RELATION REL, SOCIAL TOM-RANDOM, MOTOR AVG) as well as subjects' actual EMOTION FACES-SHAPES contrast maps and resting-state connectome as comparison. The resting-state connectome for each subject was computed as Pearson's correlation between each time series extracted using the 50-component ICA parcellation described

earlier (*50x50* correlation matrix for each individual). Feature matrices in

prediction analyses were constructed by taking all gray matter voxel values

within the brain (155,680 features) or extracting the upper triangle of the

correlation matrix (1,225 features) for each subject. We predicted variables

using L2 regularized linear regression. To mitigate the possible effect of the

difference in the number of features derived from task-based contrast maps

and resting-state connectome, the alpha value, which controls regularization

strength, was set to a value computed by dividing the number of features by

the training sample size. This resulted in significantly more regularization for

task-based features than connectome-based features. The 5-fold cross-

validation was used to evaluate models' out-of-sample performance (i.e.,

generalizability), while permutation testing ($P = 1000$) was used to estimate

the significance of models' performance by testing against a null distribution.

Additionally, using permutation testing, we compared the predictive

performance of synthetic contrast maps with actual contrast maps and

resting-state connectome. Specifically, we predicted variables using true

labels and compared 5-fold CV performance using a paired t-test. To create a

null sampling distribution for the *t*-values, we shuffled labels and repeated the

comparisons 1000 times. Then, we computed the p-value as the proportion of

permutations resulting in t-values as extreme as or more extreme than the

observed t-values. Note that predictions were performed on the 2080 subjects

we spared as a test set during the fine-tuning process explained earlier.

Measures of model performance:

Reconstruction performance: Reconstruction performance is one of the primary measures for evaluating a model's performance. It is determined by calculating Pearson's correlation between the predicted and actual task contrast maps for unseen subjects (i.e., those not used in training) in the test set.

Diagonality Index: While reconstruction performance is essential for evaluating a model's capability to generate task contrast maps, it is insufficient for assessing its ability to preserve inter-individual differences in these synthetic maps, which is crucial for downstream biomarker development and individual-specific predictions. To address this, we computed the diagonality index[17,20,22], that measures the difference between the correlations of subjects' actual and predicted contrast maps (on-diagonal) and the mean correlation between subjects' predicted maps and the actual maps of other subjects (off-diagonal). However, the raw diagonality index is not directly comparable across methods, as it only reflects the ratio of cases where the correlation between synthetic and actual maps is highest, without accounting for overall map similarity. To ensure comparability, we normalized the diagonality index by dividing it by the on-diagonal correlation scores (i.e., reconstruction performance).

Prediction performance: The predictive power of both actual and predicted task contrast maps was evaluated using Pearson's correlation

coefficient for the dominant hand's grip strength, brain age, fluid intelligence,

and overall health. For sex classification, balanced accuracy, defined as the

arithmetic mean of the true positive rate and true negative rate, was used as

the evaluation metric.

Statistics and Reproducibility

The Human Connectome Project Young Adult (HCP-YA) and Developmental

(HCP-D) datasets comprise 958 and 637 subjects, respectively, while the UK

Biobank dataset includes 20,792 subjects. Statistical analyses and

reproducibility details for model training and evaluation are provided in the

respective sections of the Results and Methods. Performance comparisons of

methods on HCP-YA and HCP-D were conducted using permutation-tested t-

tests (1000 permutations) on the corresponding test samples (HCP-YA: N =

39; HCP-D: N = 64). Significance was set at $p < 0.05$, with False Discovery

Rate (FDR) correction applied across all comparison pairs and task contrasts.

Effect sizes for significant tests were quantified using Cliff's Delta (δ).

Behavioral, cognitive, demographic, and clinical predictions were performed

on the UK Biobank test set, with sample sizes indicated above each figure

(Figs. 3, 4, Supplementary Figure 4). Prediction performance and significance

were evaluated using 5-fold cross-validation and permutation testing (1000

permutations), and average performance is reported in the manuscript.

Comparisons of prediction performance between synthetic and actual task-

based images were conducted using permutation-tested *t*-tests (1000

permutations), with FDR correction applied across all comparison pairs and

task contrasts. Effect sizes for significant tests were again measured using

Cliff's Delta (δ). To promote transparency and reproducibility, the complete

implementation, including model architecture, training, evaluation, and

downstream validation steps, as well as pre-trained models are provided in an

open-source repository.

Technology use disclosure:

Large language models were used for proofreading (e.g., grammar, typos,

integrity, and clarity checks) and as assistance during Python programming.

All authors have read, corrected, and verified all information presented in this

manuscript and Supplementary Information.

Data availability:

The minimally preprocessed HCP-YA S1200 data can be accessed and

downloaded from the following link:

https://www.humanconnectome.org/study/hcp-young-

adult/document/1200-subjects-data-release. The ICA-based group-averaged

parcellations used to construct resting-state connectomes are available at:

https://www.humanconnectome.org/study/hcp-young-

adult/document/extensively-processed-fmri-data-documentation. Similarly,

preprocessed data for the HCP-D study can be downloaded from

https://www.humanconnectome.org/study/hcp-lifespan-development/data-

releases. The UK Biobank (UKB) dataset is publicly available at

https://www.ukbiobank.ac.uk/.

Code availability:

DeepTaskGen model code can be found on GitHub:

https://github.com/eminSerin/DeepTaskGen. Python scripts to reproduce all

the results presented in this paper are given at

https://github.com/eminSerin/deeptaskgen-paper. Additionally, trained

models to generate task contrast maps on various open datasets are publicly

available at https://github.com/eminSerin/deeptaskgen-models.

Acknowledgement:

Funded by the European Union (Grant agreement No 101057429).

Complementary funding was received by UK Research and Innovation (UKRI)

under the UK government's Horizon Europe funding guarantee (10131373 and

10038599) and the National Key R&D Program of Ministry of Science and

Technology of China (MOST 2023YFE0199700). Views and opinions expressed

are however those of the author(s) only and do not necessarily reflect those

of the European Union, the European Health and Digital Executive Agency

(HADEA), UKRI or MOST. Neither the European Union nor HADEA nor UKRI

nor MOST can be held responsible for them. This work has also been supported

by a Grant from the German Research Foundation to the ENIGMA task-based

fMRI Working Group (DFG ER 724/4–1, WA 1539/11–1). Data used in this

study were provided in part by the Human Connectome Project, WU-Minn

Consortium (principal investigators: D. Van Essen and K. Ugurbil; grant

number 1U54MH091657), funded by the 16 National Institutes of Health (NIH)

institutes and centers supporting the NIH Blueprint for Neuroscience

Research, and by the McDonnell Center for Systems Neuroscience at

Washington University. Additionally, this research utilized data obtained from

UK Biobank, a large-scale biomedical database.

References:

1. Hariri, A. R., Bookheimer, S. Y. & Mazziotta, J. C. Modulating emotional responses: effects of a neocortical network on the limbic system. *Neuroreport* **11**, 43–48 (2000).

2. Swartz, J. R., Knodt, A. R., Radtke, S. R. & Hariri, A. R. A neural biomarker of psychological vulnerability to future life stress. *Neuron* **85**, 505–511 (2015).

3. Gao, S. Combining multiple connectomes improves predictive modeling of phenotypic measures. 9 (2019).

4. Greene, A. S., Gao, S., Scheinost, D. & Constable, R. T. Task-induced brain state manipulation improves prediction of individual traits. *Nat. Commun.* **9**, 2807 (2018).

5. Gal, S., Coldham, Y., Tik, N., Bernstein-Eliav, M. & Tavor, I. Act natural: Functional connectivity from naturalistic stimuli fMRI outperforms resting-state in predicting brain activity. *NeuroImage* **258**, 119359 (2022).

6. Sripada, C., Angstadt, M., Rutherford, S., Taxali, A. & Shedden, K. Toward a 'treadmill test' for cognition: Improved prediction of general cognitive ability from the task activated brain. *Hum. Brain Mapp.* **41**, 3186–3197 (2020).

7. Jiang, R. *et al.* Task-induced brain connectivity promotes the detection of individual differences in brain-behavior relationships. *NeuroImage* **207**, 116370 (2020).

8. Shah, L. M., Cramer, J. A., Ferguson, M. A., Birn, R. M. & Anderson, J. S. Reliability and reproducibility of individual differences in functional connectivity acquired during task and resting state. *Brain Behav.* **6**, e00456 (2016).

9. Tetereva, A., Li, J., Deng, J. D., Stringaris, A. & Pat, N. Capturing brain-

cognition relationship: Integrating task-based fMRI across tasks markedly boosts

prediction and test-retest reliability. *NeuroImage* **263**, 119588 (2022).

10. Woo, C.-W., Chang, L. J., Lindquist, M. A. & Wager, T. D. Building better

biomarkers: brain models in translational neuroimaging. *Nat. Neurosci.* **20**,

365–377 (2017).

11. Van Essen, D. C. *et al.* The WU-Minn Human Connectome Project: An overview.

NeuroImage **80**, 62–79 (2013).

12. Schumann, G. *et al.* The IMAGEN study: reinforcement-related behaviour in

normal brain function and psychopathology. *Mol. Psychiatry* **15**, 1128–1139

(2010).

13. Casey, B. J. *et al.* The Adolescent Brain Cognitive Development (ABCD) study:

Imaging acquisition across 21 sites. *Dev. Cogn. Neurosci.* **32**, 43–54 (2018).

14. Cole, M. W., Ito, T., Bassett, D. S. & Schultz, D. H. Activity flow over resting-

state networks shapes cognitive task activations. *Nat. Neurosci.* **19**, 1718–1726

(2016).

15. Tavor, I. *et al.* Task-free MRI predicts individual differences in brain activity

during task performance. *Science* **352**, 216–220 (2016).

16. Smith, S. M. *et al.* Correspondence of the brain's functional architecture during

activation and rest. *Proc. Natl. Acad. Sci. U. S. A.* **106**, 13040–13045 (2009).

17. Ngo, G. H., Khosla, M., Jamison, K., Kuceyeski, A. & Sabuncu, M. R. Predicting

individual task contrasts from resting-state functional connectivity using a

surface-based convolutional network. *NeuroImage* **248**, 118849 (2022).

18. Somerville, L. H. *et al.* The Lifespan Human Connectome Project in

Development: A large-scale study of brain connectivity development in 5–21

year olds. *NeuroImage* **183**, 456–468 (2018).

19. Miller, K. L. *et al.* Multimodal population brain imaging in the UK Biobank

prospective epidemiological study. *Nat. Neurosci.* **19**, 1523–1536 (2016).

20. Zheng, Y.-Q. *et al.* Accurate predictions of individual differences in task-evoked

brain activity from resting-state fMRI using a sparse ensemble learner.

NeuroImage **259**, 119418 (2022).

21. Cohen, A. D., Chen, Z., Parker Jones, O., Niu, C. & Wang, Y. Regression-based

machine-learning approaches to predict task activation using resting-state fMRI.

Hum. Brain Mapp. **41**, 815–826 (2020).

22. Tik, N. *et al.* Generalizing prediction of task-evoked brain activity across

datasets and populations. *NeuroImage* **276**, 120213 (2023).

23. Finn, E. S. *et al.* Functional connectome fingerprinting: Identifying individuals

using patterns of brain connectivity. *Nat. Neurosci.* **18**, 1664–1671 (2015).

24. Barch, D. M. *et al.* Function in the human connectome: Task-fMRI and individual

differences in behavior. *NeuroImage* **80**, 169–189 (2013).

25. McInnes, L., Healy, J. & Melville, J. UMAP: Uniform Manifold Approximation and

Projection for Dimension Reduction. (2018) doi:10.48550/ARXIV.1802.03426.

26. Kroenke, K., Spitzer, R. L. & Williams, J. B. W. The PHQ-9: Validity of a brief

depression severity measure. *J. Gen. Intern. Med.* **16**, 606–613 (2001).

27. Dutt, R. K. *et al.* Mental health in the UK Biobank: A roadmap to self-report

measures and neuroimaging correlates. *Hum. Brain Mapp.* **43**, 816–832 (2022).

28. Spitzer, R. L., Kroenke, K., Williams, J. B. W. & Löwe, B. A Brief Measure for

Assessing Generalized Anxiety Disorder: The GAD-7. *Arch. Intern. Med.* **166**,

1092 (2006).

29. Gong, W., Bai, S., Zheng, Y.-Q., Smith, S. M. & Beckmann, C. F. Supervised

Phenotype Discovery From Multimodal Brain Imaging. *IEEE Trans. Med. Imaging*

42, 834–849 (2023).

30. He, T. *et al.* Meta-matching as a simple framework to translate phenotypic

predictive models from big to small data. *Nat. Neurosci.* **25**, 795–804 (2022).

31. Delgado, M. R., Nystrom, L. E., Fissell, C., Noll, D. C. & Fiez, J. A. Tracking the

hemodynamic responses to reward and punishment in the striatum. *J.*

Neurophysiol. **84**, 3072–3077 (2000).

32. Zhang, J., Niu, Y., Shangguan, Z., Gong, W. & Cheng, Y. A novel denoising

method for CT images based on U-net and multi-attention. *Comput. Biol. Med.*

152, 106387 (2023).

33. Meng, Z., Fan, Z., Zhao, Z. & Su, F. ENS-Unet: End-to-End Noise Suppression

U-Net for Brain Tumor Segmentation. in *2018 40th Annual International*

Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)

5886–5889 (IEEE, Honolulu, HI, 2018). doi:10.1109/EMBC.2018.8513676.

34. Koziol, L. F. & Budding, D. E. *Subcortical Structures and Cognition*. (Springer

New York, New York, NY, 2009). doi:10.1007/978-0-387-84868-6.

35. Janacsek, K. *et al.* Subcortical Cognition: The Fruit Below the Rind. *Annu. Rev.*

Neurosci. **45**, 361–386 (2022).

36. Stoodley, C. J. The Cerebellum and Cognition: Evidence from Functional

Imaging Studies. *The Cerebellum* **11**, 352–365 (2012).

37. Okada, N. *et al.* Subcortical volumetric alterations in four major psychiatric

disorders: a mega-analysis study of 5604 subjects and a volumetric data-driven

approach for classification. *Mol. Psychiatry* (2023) doi:10.1038/s41380-023-

02141-9.

38. Ho, T. C. *et al.* Subcortical shape alterations in major depressive disorder:

Findings from the ENIGMA major depressive disorder working group. *Hum. Brain*

Mapp. **43**, 341–351 (2022).

39. Hoppenbrouwers, S. S., Schutter, D. J. L. G., Fitzgerald, P. B., Chen, R. &

Daskalakis, Z. J. The role of the cerebellum in the pathophysiology and

treatment of neuropsychiatric disorders: A review. *Brain Res. Rev.* **59**, 185–200

(2008).

40. Kwon, J. *et al.* Predicting task-related brain activity from resting-state brain

dynamics with fMRI Transformer. *Imaging Neurosci.* **3**, imag_a_00440 (2025).

41. Marquand, A. F. *et al.* Conceptualizing mental disorders as deviations from

normative functioning. *Mol. Psychiatry* **24**, 1415–1424 (2019).

42. Savage, H. S. *et al. Unpacking the Functional Heterogeneity of the Emotional*

Face Matching Task: A Normative Modelling Approach.

http://biorxiv.org/lookup/doi/10.1101/2023.03.27.534351 (2023)

doi:10.1101/2023.03.27.534351.

43. Elliott, L. T. *et al.* Genome-wide association studies of brain imaging phenotypes

in UK Biobank. *Nature* **562**, 210–216 (2018).

44. Wu, J. *et al.* Accurate nonlinear mapping between MNI volumetric and

FreeSurfer surface coordinate systems. *Hum. Brain Mapp.* **39**, 3793–3808

(2018).

45. Schulz, M.-A., Bzdok, D., Haufe, S., Haynes, J.-D. & Ritter, K. Performance

reserves in brain-imaging-based phenotype prediction. *Cell Rep.* **43**, 113597

(2024).

46. Rubia, K. Functional brain imaging across development. *Eur. Child Adolesc.*

Psychiatry **22**, 719–731 (2013).

47. Zabihi, M. *et al.* Nonlinear latent representations of high-dimensional task-fMRI

data: Unveiling cognitive and behavioral insights in heterogeneous spatial maps.

PLOS ONE **19**, e0308329 (2024).

48. Glasser, M. F. *et al.* The minimal preprocessing pipelines for the Human

Connectome Project. *NeuroImage* **80**, 105–124 (2013).

49. Holmes, A. J. *et al.* Brain Genomics Superstruct Project initial data release with

structural, functional, and behavioral measures. *Sci. Data* **2**, 150031 (2015).

50. Marcus, D. S. *et al.* Human Connectome Project informatics: Quality control,

database services, and data visualization. *NeuroImage* **80**, 202–219 (2013).

51. Khosla, M., Jamison, K., Kuceyeski, A. & Sabuncu, M. R. Ensemble learning with

3D convolutional neural networks for functional connectome-based prediction.

NeuroImage **199**, 651–662 (2019).

52. Smith, S. M. *et al.* Resting-state fMRI in the Human Connectome Project.

NeuroImage **80**, 144–168 (2013).

53. Ronneberger, O., Fischer, P. & Brox, T. U-Net: Convolutional Networks for

Biomedical Image Segmentation. in *Medical Image Computing and Computer-*

Assisted Intervention – MICCAI 2015 (eds. Navab, N., Hornegger, J., Wells, W.

M. & Frangi, A. F.) vol. 9351 234–241 (Springer International Publishing, Cham,

2015).

54. Oktay, O. *et al.* Attention U-Net: Learning Where to Look for the Pancreas.

Preprint at https://doi.org/10.48550/ARXIV.1804.03999 (2018).

55. Smith, S. M. *et al.* A positive-negative mode of population covariation links brain

connectivity, demographics and behavior. *Nat. Neurosci.* **18**, 1565–1567

(2015).

56. He, T. Deep neural networks and kernel regression achieve comparable

accuracies for functional connectivity prediction of behavior and demographics.

15 (2020).