Brief encounters with real objects modulate medial parietal but not occipitotemporal cortex

Susan G. Wardle[1], Beth Rispoli[1,2], Vinai Roopchansingh[3], & Chris I. Baker[1]

[1]Section on Learning and Plasticity, Laboratory of Brain and Cognition, National Institute of Mental Health, NIH, Bethesda, MD

[2] Department of Neuroscience, Georgetown University Medical Center, Washington, DC

[3]Functional MRI Facility, National Institute of Mental Health, NIH, Bethesda, MD

Abstract

Humans are skilled at recognizing everyday objects from pictures, even if we have never encountered the depicted object in real life. But if we have encountered an object, how does that real-world experience affect the representation of its photographic image in the human brain? We developed a paradigm that involved brief real-world exploration of everyday objects prior to the measurement of brain activity with fMRI while viewing pictures of the objects. We discovered that while object-responsive regions in lateral occipital and ventral temporal cortex were visually driven and contained highly invariant representations of specific objects, those representations were not modulated by real-world exploration. However, real-world experience with an object produced foci of increased activation in medial parietal and posterior cingulate cortex, identifying an important associative region for the experience gained from manual object exploration. The richness of object representations beyond their photographic image has important implications for understanding object recognition in both the human brain and in computational models.

Humans excel at visual object recognition — we can recognize everyday objects in photographs or from simplified line drawings rapidly and with ease[1,2]. Deep neural networks trained on object recognition are also able to label objects with remarkable accuracy, now rivaling human performance[3,4]. However, when humans look at a photograph, we are capable of much more than simply labelling the objects in the image, e.g. as a "dog". We can infer other things about the depicted object based on experience ("Labradors are friendly") or visual features of the image ("the dog is wet"). If we have personal experience with the photographed object (such as a photo of our own dog), we also have access to another form of object knowledge based on real-world experience (e.g. memory of a particular walk, knowledge about the dog's preference for peanut butter). Much of the everyday human experience involves physically interacting with familiar three-dimensional objects, yet most empirical studies of human object recognition have relied on two-dimensional images of unfamiliar objects[5]. Here we investigate to what extent real-world experience with an object influences the neural representation of its two-dimensional image in the human brain.

The neural mechanisms underlying object recognition are not yet fully understood, but it is generally thought to be supported by a series of complex computations along the ventral visual pathway, throughout occipitotemporal cortex[6–10]. Regions in lateral occipital (LO) and ventral temporal cortex (VTC) have been identified that respond preferentially to images of intact objects compared to scrambled versions of the same images[11–13]. These regions are sensitive to object shape in photographs[13], but also respond to more schematic depictions of objects such as line drawings[14] and shape from texture and motion cues[15].

A critical outstanding question is how prior real-world experience with an object modulates the neural representation of its image. Given that a major goal in cognitive neuroscience is to understand real-world object recognition outside of the laboratory and beyond the computer screen[5], revealing how real-world experience with an object shapes the representation of its image in the brain is important for contextualizing the large body of existing research on the neural representation of object images[6,11,16–18]. One hypothesis is that real-world experience with an object modulates the representation of its image directly in object-responsive regions of occipitotemporal cortex. Alternatively, real-world experience may modulate the representation of an object image via other cortical regions outside of the visual ventral pathway, with the visual representation of the image remaining unchanged.

There are several ways in which exploring a real object may alter the neural representation of its photographic image. First, the visual experience of handling the objects may lead to repetition suppression[19,20], a reduction in response when viewing images of the objects. Such reduced responsiveness has been reported when images of an object are repeated[12,21,22], although repetition suppression can be image-specific in visual cortex[23] and may not generalize from 3D to 2D experience[24]. Second, because handling an object allows us to experience it from many different viewpoints this experience may modulate the invariance of its neural representation. The ease with which we recognize objects masks the difficulty of the underlying computational problem. For a given object, the projected retinal image is vastly different across encounters because of variability in visual characteristics such as lighting, position, proximity and viewing angle. Recognizing an object across these substantial visual transformations thus involves a complex computation to tease apart the stable visual features of the object from the changeable visual properties of the viewing context. A large amount of research using 2D images of objects has been directed at understanding how this classic "invariance problem" of object recognition is solved[6,16,17,25]. A study in monkey IT cortex reported a subset of neurons that responded to multiple views of novel objects that had previously been handled by the animal[26]. Although these responses were only able to be compared to unfamiliar objects for a total of four neurons, the data were consistent with more invariant representations for familiar than unfamiliar objects.

Although object representations in human occipitotemporal cortex have been reported to have some degree of invariance, studies have typically focused on the level of categories rather than exemplars[27–29], and on parametrically varying single aspects of an object image at a time (e.g. by changing the size of the image[22,30,31], or its position on the screen[28,30,31]). This contrasts with our experience in the real world, where each encounter we have with a specific object involves multiple simultaneous visual transformations caused by changes in factors such as lighting, viewing angle and distance, and object shape (for non-rigid objects).

To determine how real-world experience with an object may influence the neural representation of its image, we developed an experimental paradigm that combined real-world object exploration with functional magnetic resonance imaging (fMRI) and machine learning analysis methods (**Fig. 1a**). Participants freely explored everyday objects such as mugs and toys prior to having their brain activity

recorded with fMRI while looking at photographs of those same objects, as well as a matched set of unexplored objects of the same type. To preview the results, we found that object identity could be successfully decoded from object-preferring regions of cortex on the lateral occipital and ventral temporal surfaces even across different photographs of the same object— providing strong evidence for invariant object representations. Surprisingly, the invariance of the object representations was not modulated by real-world experience, but real-world exploration of an object was associated with a strong response in cortical areas outside the ventral visual pathway, including posterior cingulate and medial parietal cortex. Our results are important in constraining models of object recognition, and emphasize that in object-responsive cortex, object representations are highly visually-driven. In contrast, viewing a picture of a previously experienced object additionally engages medial brain regions associated with learning and memory— even across modalities and outside the context of an explicit memory or learning task. Together, the results show that the visual representation of an object and its associations engage different regions in the human brain, highlighting the importance of considering the role of cortical areas outside of visual cortex in visual object perception.

Figure 1. Experimental design and methods. (a) In phase 1 of the experiment, participants ($N = 40$) explored the 12 real-world objects from one of the object sets (Set A or Set B) one at a time for 30 seconds each. In phase 2, participants' brain activity was recorded using event-related task fMRI while they looked at pictures of the 24 objects from both sets, half of which they had previously explored. Each object was depicted twice in different contexts for a total of 48 images as shown in (c). In phase 3, participants completed a behavioral memory test in which they viewed each of the 48 images used in the fMRI experiment and indicated whether they had explored the depicted object or not. **(b)** The 48 images used in the fMRI experiment. Each set had two unique exemplars from six object categories, for a total of 12 objects. Each object was photographed in two different contexts (indoor and outdoor) for a total of 24 photographs per object set. All participants saw all 48 images in the fMRI experiment, regardless of which object set they had explored. They did not see any of the photographs prior to the fMRI experiment. **(c)** Mean accuracy on the post-scan object memory test for all participants as a function of whether they explored Set A (Group A, n = 20) or Set B (Group B, n = 20) objects prior to the scanning session. Box plots show the median (center line), upper and lower quartiles (box edges) and the nonoutlier maximum and minimums values (whiskers) for each participant group. The shaded notches for Group A and Group B overlap, indicating no significant difference between the medians at the $p < .05$ level. Memory performance was near ceiling for both groups, indicating that they remembered which objects they had explored and recognized them from the photographs.

Results

To investigate the effect of real-world experience with an object on the neural representation of its photographic image, we created two stimulus sets of everyday objects (bags, clocks, mugs, shoes, socks, toys). Each set of 12 objects had two unique exemplars from each of the six categories, which were photographed in two different contexts (indoor and outdoor) for a total of 24 images per set (**Fig. 1b**). Participants ($N = 40$) freely explored the 12 objects from one set (either Set A or Set B) one at a time for 30 seconds each prior to scanning (**Fig. 1a**). Following exploration, we recorded participants' brain activity using fMRI while they viewed all 48 photographs of the 24 objects, half of which they had explored manually. Participants had not seen any of the images prior to the scan, yet a post-scan memory test revealed that they were able to recognize which objects they had explored from the photographs (**Fig. 1c**). There was no significant difference in the mean accuracy on the memory test for participants who explored Set A objects ($M = 89.90\%$, $SD = 11.77\%$) compared to those who explored Set B objects ($M = 94.58\%$, $SD = 5.91$) as shown by a two-tailed independent samples t-test ($t_{(38)} = -1.592$, $p = 0.120$, 95% CI diff: [-10.649, 1.274], $d = -0.503$).

Highly invariant object representations in object-responsive cortex.

First, we established that explored and unexplored objects produced an equivalently strong magnitude of response in object-responsive regions within lateral occipital (LO) and ventral temporal cortex (VTC) (**Fig. 2**). LO and VTC were functionally defined in each participant's native brain space using data from independent localizer runs which included pictures of scrambled versus intact objects that were not used in the main experiment (**Fig. 3a**). A within subjects 2x2 repeated measures ANOVA confirmed that there were no significant main effects of region of interest ($F_{(1,39)} = 0.107$, $p = .745$, $\eta_p^2 = .003$) or object exploration ($F_{(1,39)} = 0.802$, $p = .376$, $\eta_p^2 = .020$), and no significant interaction ($F_{(1,39)} = 0.690$, $p = .411$ $\eta_p^2 = .017$).

Second, we found that object-responsive LO and VTC both contained highly invariant object representations of individual objects, even for those that were unexplored. To conduct a strict test for invariant object representations in object-responsive LO and VTC, we attempted to decode the identity of objects at the exemplar level across viewing context from patterns of brain activity measured with fMRI (**Fig. 3**). We used a cross-decoding approach and trained a linear classifier to discriminate between patterns of brain activity in these regions associated with looking at a pair of objects in one context (e.g. indoors), and tested classifier performance on new data from trials of the

same object exemplars pictured in a different context (e.g. outdoors). Results of the decoding analysis are shown in **Fig. 4** separately for each group of participants (Group A and Group B, defined by which set of objects the participants explored). One-tailed one-sample t-tests with the Bonferroni correction applied for multiple comparisons ($k = 4$) were used to assess whether decoding performance was greater than chance (50% accuracy) for each group. For both groups of participants, cross decoding of object identity across context was significantly above chance in object-responsive region LO for explored (Group A: $t_{(19)} = 6.536$, $p < 0.0001$, 95% CI: [54.7516, Inf], $d = 1.462$; Group B: $t_{(19)} = 8.892$, $p < 0.0001$, 95% CI: [55.6532, Inf] , $d = 1.988$) and unexplored objects (Group A: $t_{(19)} = 5.528$, $p < 0.0001$, 95% CI: [54.8610, Inf], $d = 1.236$; Group B: $t_{(19)} = 5.462$, $p < 0.0001$, 95% CI: [54.0800, Inf], $d = 1.221$). Cross decoding of object identity across context was also statistically significant for both participant groups in region VTC for explored (Group A: $t_{(19)} = 6.186$, $p < 0.0001$, 95% CI: [54.1317, Inf], $d = 1.403$; Group B: $t_{(19)} = 6.009$, $p < 0.0001$, 95% CI: [54.4920, Inf], $d = 1.344$) and unexplored objects (Group A: $t_{(19)} = 9.252$, $p < 0.0001$, 95% CI: [55.1826, Inf], $d = 2.069$; Group B: $t_{(19)} = 6.419$, $p < 0.0001$, 95% CI: [54.6858, Inf], $d = 1.435$). These results indicate impressive generalization in LO and VTC— the identity of an object could be cross decoded across different photographs of the object, consistent with a high tolerance to visual feature differences in the underlying brain representations.

Next, we tested whether there was a difference in cross decoding accuracy for objects that were explored versus those that were unexplored. For participants who explored Set A objects, there was no significant difference in the accuracy of cross decoding object identity across contexts between explored and unexplored objects in LO ($t_{(19)} = -0.635$, $p = 0.533$, 95% CI: [-2.633, 1.407], $d = -0.142$, two-tailed) or in VTC ($t_{(19)} = -0.670$ $p = 0.511$, 95% CI: [-2.635, 1.357] , $d = -0.150$, two-tailed). This result was replicated in both LO ($t_{(19)} = 1.335$, $p = 0.198$, 95% CI: [-0.595, 2.691], $d = 0.298$, two-tailed) and VTC ($t_{(19)} = -0.117$, $p = 0.908$, 95% CI: [-2.018, 1.805] , $d = -0.026$, two-tailed) for participants who explored Set B objects. Bayesian analysis revealed moderate support for the null hypotheses that there was no difference in decoding performance for explored versus unexplored objects in LO or VTC for participants in both Group A (LO: $BF = 4.833$; VTC: $BF = 4.730$) and Group B (LO: $BF = 2.575$ VTC: $BF = 5.824$). Thus the invariant object representations in object-responsive cortex do not appear to be modulated by real-world exploration of the depicted objects.

Figure 2. Univariate response to explored versus unexplored objects in visual object-selective areas.
Mean t-value averaged across all voxels, object images, and participants ($N = 40$) is shown separately for object-responsive regions on the lateral occipital (LO) and ventral temporal (VTC) cortical surface. Insets show location of the regions of interest, which were defined in each participant's native brain space from independent localizer data.

Figure 3. Method for cross decoding object identity across context from object-selective cortex. (a) Two regions of interest based on independent localizer data were defined in each participant's native brain space on the inflated cortical surface from the contrast *objects > scrambled objects*. LO was defined as the cluster of voxels responding more to intact objects on the lateral occipital surface, and VTC was defined as the cluster of voxels responding more to intact objects in ventral temporal cortex. **(b)** Cross-decoding of object identity across context (indoor vs. outdoor scene) was performed by training a linear classifier to discriminate between a pair of objects photographed in one context (e.g. indoor) from the patterns of activation across voxels in a ROI and then testing the classifier on discrimination between the same pair of objects in the opposite context (e.g. outdoor). This procedure was repeated for each object pair.

Figure 4. Cross decoding of object identity across context from object-responsive cortex. Results for cross-decoding object identity across context for object-responsive regions LO and VTC as a function of whether the object was explored in real life or not. Mean decoding accuracy is averaged across decoding iterations and participants. Error bars indicate +/- 1 SEM. Asterisks denote decoding performance above chance at the *p* < .05 level, Bonferroni corrected for multiple comparisons.

Object exploration modulates activity in medial parietal cortex.

In object-responsive visual cortex we found invariant object representations that were not modulated by real-world object exploration. To examine whether any cortical areas were modulated by prior real-world exploration of the depicted objects, we conducted a whole brain univariate analysis using a general linear model (GLM). An advantage of the counterbalanced experimental design is that the contrast *Explored objects > Unexplored objects* is defined as *Set A > Set B* for Group A participants (*n* = 20), and as *Set B > Set A* for Group B participants (*n* = 20). Thus when conducting a whole brain group level analysis on the entire sample (*N* = 40), any differences found cannot be due to specific images, and must be due to the differences in object exploration. From the group level analysis, we plotted the t-values for all voxels surviving cluster correction (see Methods) on the inflated cortical surface (**Fig. 5a**). This whole brain analysis revealed significant effects of object exploration in the posterior cingulate and medial parietal lobe in the left hemisphere (*t* = 3.55, *p* < .001). Similar effects were revealed to a lesser extent in the right hemisphere, with a significant cluster in the medial parietal lobe (*t* = 3.55, *p* < .001). The unthresholded maps on the cortical surface show similar patterns of medial activation in both hemispheres (**Fig. 5a**). We observe no significant clusters of differential activation for explored objects elsewhere, including somatosensory and motor regions. These data

show that activity in medial parietal cortex in response to viewing a photo of an object is modulated by prior real-world experience with that depicted object.

We examined the response magnitude for explored and unexplored objects in these medial regions by defining two independent regions of interest in medial parietal (MP) and posterior cingulate (PC) cortex from the peaks of activation in one group of participants (e.g. Group A) and calculating the response magnitude from the data for the other group of participants (e.g. Group B— see Methods). We observed an increase in response for explored objects relative to unexplored objects bilaterally across both medial parietal and posterior cingulate cortex, with a stronger overall response in MP (**Fig. 5b**). This was confirmed with a within subjects 2x2x2 repeated measures ANOVA that revealed significant main effects of region of interest ($F_{(1,39)}$ = 5.254, p = .027 η_p^2 = .119) and object exploration ($F_{(1,39)}$ = 33.455, p < .001, η_p^2 = .462). Although there was no main effect of hemisphere ($F_{(1,39)}$ = 0.641, p = .428, η_p^2 = .016), the interactions between hemisphere and region of interest ($F_{(1,39)}$ = 4.512, p = .040, η_p^2 = .104) and hemisphere and object exploration ($F_{(1,39)}$ = 4.549, p = .039, η_p^2 = .104) were both statistically significant, reflecting small differences in the patterns of response between hemispheres. No other interactions were significant.

Figure 5. Whole brain response to viewing photographs of explored versus unexplored objects. (a) t-values from the GLM contrast (*explored - unexplored objects*) are plotted on the inflated cortical surface, the analysis was conducted on combined data for all $N = 40$ participants regardless of which object set they explored. For participants in Group A ($n = 20$) who explored Set A objects, this corresponds to the difference in activation for looking at pictures of *Set A - Set B* objects. For participants in Group B ($n = 20$) who explored Set B objects, this corresponds to the difference in activation for looking at pictures of *Set B - Set A* objects. As image set is counterbalanced across participants, any observed differences at the group level arise from the effects of object exploration. Only the medial view is shown for the left and right hemispheres as no other voxels survived cluster correction ($p < .001$). Insets show unthresholded group maps for each hemisphere on the medial surface.

(b) Mean response to explored and unexplored objects as a function of hemisphere for medial parietal (MP) and posterior cingulate (PC) regions of interest. Insets show approximate location of MP and PC on the medial view of the inflated cortical surface. ROIs were functionally defined from the data for independent groups of subjects— see Methods for details.

Repetition suppression in object-responsive cortex is not modulated by real-world exploration.

We observed no modulation of activity in LO and VTC by real-world object exploration (**Fig. 2**), which suggests that exploring an object does not suppress the overall response to images of that same object. However, as repetition suppression is known to occur in object-responsive cortex for repeated presentations of the same stimulus[12,21,22], it is possible that averaging the fMRI response over all presentations of the object images masked an earlier differential response for explored versus unexplored objects, particularly as participants had not seen any of the object images prior to the scan.

To determine whether such learning effects may account for the lack of modulation by real-world exploration, we plotted the mean response in LO and VTC to each object image over time, as a function of whether the object was explored or not (**Fig. 6a**). We observed classic repetition suppression for object images in both LO and VTC, but there was no modulation by real-world experience. We conducted a within-subjects 2 x 2 x 8 repeated measures ANOVA with the factors *ROI* (LO or VTC), *exploration* (explored vs. unexplored objects) and *run* (experimental runs 1-8) on the mean responses to each image across all voxels for the 38 participants who completed 8 experimental runs. The data from the remaining two participants who completed only 6 experimental runs ($n = 1$ from Group A, $n = 1$ from Group B) were excluded from this statistical analysis but are included in **Fig. 6a**. Mauchly's test indicated that the sphericity assumption was violated for the main effect of run ($X^2 (27) = 60.083, p < .001$) so the Greenhouse–Geisser correction was applied to the degrees of freedom for these statistics and any interactions. There was no main effect of ROI ($F_{(1, 37)} = 0.209, p = .650, \eta_p^2 = .006$) or object exploration ($F_{(1, 37)} = 0.535, p = .469, \eta_p^2 = .014$). In the visual ROIs, the response magnitude was similar for pictures of objects that had been explored compared to those that were not explored prior to the scan. Importantly, there was a main effect of run ($F_{(4.846, 179.310)} = 2.916, p = .016, \eta_p^2 = .073$), and a significant linear trend for run ($F_{(1,37)} = 8.402, p = .006, \eta_p^2 = .185$), indicating significant repetition suppression for both explored and unexplored objects in the object-responsive ROIs (**Fig. 6a**). The linear trend for the ROI x run interaction term was also significant ($F_{(4.846, 179.310)} = 2.916, p = .016, \eta_p^2 = .073$), indicative of the steeper slope for VTC. No other interactions were

statistically significant. Thus in areas LO and VTC, the magnitude of response to a given image decreases as a function of repeated presentation across runs, regardless of whether that object was explored in real life or not.

Medial parietal areas show enhanced responses to photos of explored objects.

The medial parietal areas did show a differential response to explored objects, however we also checked for learning effects in these regions by plotting the mean response over time (**Fig. 6b**). Two new regions of interest — medial parietal (MP) and posterior cingulate (PC), were functionally defined bilaterally for each group of participants using independent fMRI data from the whole brain contrast for the other group (see Methods). As for the visual ROIs, we conducted a 2 x 2 x 8 repeated measures ANOVA with the factors *ROI* (MP or PC), *exploration* (explored vs. unexplored objects) and *run* (experimental runs 1-8). Mauchly's test indicated that the sphericity assumption was violated for the main effect of run (X^2 (27) = 48.418, p < .001) so the Greenhouse–Geisser correction was applied to these statistics and any interactions. There was a significant main effect of object exploration ($F_{(1, 37)}$ = 31.311, p < .001, η_p^2 = .458), indicating an overall higher response magnitude for pictures of objects that had been explored compared to those that were unexplored. There was also a main effect of ROI ($F_{(1, 37)}$ = 5.873, p =0.020, η_p^2 = .137), reflecting the stronger responses overall in MP (**Fig. 6b**). There was no main effect of run ($F_{(5.081, 187.995)}$ = 0.967, p = 0.440, η_p^2 = .025), and none of the interactions between the main effects were statistically significant. There was some evidence of repetition suppression for explored objects but not for unexplored objects (**Fig. 6b)**, supported by the absence of an overall linear trend for run ($F_{(1, 37)}$ = 1.100, p < .301, η_p^2 = .029), but a significant linear trend for the interaction between object exploration and run ($F_{(1, 37)}$ = 7.766, p = .008, η_p^2 = .173). Unlike the object-responsive regions LO and VO, the medial parietal regions exhibit relatively sustained response enhancement for explored objects relative to those that were unexplored. Finally, since there were two presentations of each object per run (i.e. the outdoor and indoor photograph of each object), we confirmed the pattern of results was similar as a function of object presentation number for both visual and medial ROIs (Supplementary Fig. 1).

Figure 6. Differences in the response to the repeated presentation of object images over time in object-responsive and medial brain areas as a function of object exploration. The mean t-value averaged across all participants (N = 40) and the 48 images is shown as a function of run number (one presentation of each image per run) and plotted separately for images of explored (n = 24) and unexplored (n = 24) objects. **(a)** The object-responsive regions in the lateral occipital cortex (LO) and ventral temporal cortex (VTC) show repetition suppression for both explored and unexplored objects. **(b)** The medial parietal (MP) and posterior cingulate (PC) regions of interest show an enhanced response to explored objects compared to unexplored objects, which is evident from the first presentation of the images in the first run. Error bars show ± 1 between-subjects SEM.

Discussion

Using fMRI, we found that prior real-world exploration of an object modulates activity in medial parietal regions in response to later viewing an image of the same object. Importantly, our counterbalanced experimental design ensured that these effects cannot be explained by differences among the images and objects and are attributable to an effect of real-world experience. Notably, real-world experience with an object did not modulate activity in object-responsive regions of lateral occipital and ventral temporal cortex. Our analyses confirmed that even on the first presentation of an individual photograph during the fMRI experiment, there was no difference in the magnitude of response to explored versus unexplored objects in LO or VTC. Instead, these regions were visually driven, containing highly invariant representations of individual objects as demonstrated by successful cross decoding across different photographs of the same object taken in different contexts (indoor vs. outdoor).

We discovered that viewing photographs of explored objects automatically engaged bilateral medial parietal and posterior cingulate cortex, even in the absence of an explicit memory task, and even though participants had never seen the photographs of the objects before. Similar cortical regions have been implicated in the "parietal memory network"[32], which involves medial and lateral regions of parietal cortex associated with both memory encoding and retrieval. However, this is the first time to our knowledge that memory retrieval activity in the parietal memory network has been shown to generalize across modalities— in our paradigm, memory encoding was for real-world objects during the exploration phrase, while memory retrieval occurred for photographs of the same objects viewed during the fMRI experiment. Participants had never seen any of the photographs prior to the fMRI scan, and the effect of exploration was evident on the first presentation. Additionally, the memory retrieval in our paradigm was spontaneous and implicit (i.e. recognizing a previously explored object from its photograph), rather than in the context of an explicit learning or memory task. Consistent with our finding of an enhanced response for explored objects in MP and PC, repetition enhancement (rather than suppression) is found in the parietal memory network [32–34]. Our results suggest that medial brain regions are engaged by the associations created by prior real-world experience with an object, which are spontaneously activated by recognizing an explored object in a photograph. It is also notable that these effects were produced by only thirty seconds of free exploration with an object, evidence

that these associations form rapidly and persist for at least a couple of hours following an object encounter.

Our data show that medial parietal cortex responds more strongly to pictures of objects that we have real-world experience with than to pictures of unfamiliar objects, but it does not isolate which aspects of the real-world experience are the cause of this differential response. Manual exploration of a real-world object involves both tactile and visual sensory input. In addition, the manual exploration of an object generates an episodic memory of the experience, and participants' thoughts during the exploration (for example, of what an object reminds them of, or their opinion of it) are another potential source of a differential response to explored versus unexplored objects. However, as we find no differential response in object-responsive visual areas, our data suggest that it is unlikely to be purely visually driven. Prior fMRI work has shown suppression of the response to familiar object images across object-responsive areas of ventral occipitotemporal cortex when participants were familiarized with a subset of images prior to the scan[35]. We observed classic repetition suppression in object-responsive regions to repeated presentation of the object photographs across runs, but no modulation by real-world experience. Thus repetition suppression in visual areas appears to be modality specific and depends on prior exposure to the same (or similar) image, rather than the same real-world object.

Perirhinal cortex has previously been associated with recognition memory and familiarity for object concepts and pictures[36–40]. In our paradigm, we did not observe a differential response in perirhinal cortex to pictures of explored versus unexplored objects, but there are several relevant differences between our paradigm and those that find perirhinal activation associated with familiarity. Many studies use concrete nouns (e.g. "apple") as object concept stimuli[36,40], in contrast to our stimuli which were photographs of specific object exemplars (e.g. a particular sock). They also frequently involve an explicit study phase followed by ratings of familiarity for the same stimuli[36,38–40], whereas our participants completed a manual object exploration task and had never previously seen the photographs of the objects before the scanning session. Additionally, our paradigm did not involve an explicit memory or familiarity task. It remains an interesting question whether the familiarity signature in perirhinal cortex is modality-specific, but our data suggest that familiarity with a real-life object is not the same as familiarity for a specific image of that object.

An outstanding question is how the extent and nature of prior real-world experience with an object relates to the neural representation of its image. In our paradigm, the behavioral exploration of the objects depicted in the fMRI study was brief and controlled at thirty seconds per object. It is valuable to relate these results to prior studies that have used personally familiar visual stimuli, such as pictures of the participants' own bag or office. The personal familiarity of places and objects has been linked to greater activation in medial regions including posterior cingulate cortex during a task in which participants judged whether an image was familiar or not[41]. Another fMRI study using images of personally familiar stimuli (e.g., images of a participant's own vehicle or the face of their parent) found that their representation in inferior temporal cortex predicted the unique portion of an individual's behavioral judgements of how similar the stimuli were[42]. Additionally, the results of an fMRI study involving novel objects created using the children's construction toy K'NEX suggest that the way objects are used may alter their visual representation in the brain[43]. After using the novel objects to perform tasks (e.g. lifting blocks, crushing cups) in a training phase, activity increased in anterior parts of the left middle temporal gyrus, intraparietal sulcus, and premotor cortex during an in-scanner perceptual matching task in which participants judged whether two photographs depicted the same object or not. Participants were also faster at the behavioral task for the novel objects they trained with. Alongside our finding of strong activation in medial parietal cortex and the posterior cingulate for explored everyday objects, these studies highlight the importance of considering the effect of prior experience with objects on the neural representation of their image.

A complete understanding of human object recognition will require going beyond neural responses to images and detailing the neural representation of actual objects. Prior work has shown that real objects are processed differently than images of objects[5]. For example, repetition suppression in object-preferring regions of lateral occipital cortex and the posterior fusiform is weaker for real objects than for object images as measured with fMRI[24]. The neural representations supporting grasping movements for real objects also differ from those for photographs[44]. Behaviorally, real objects are more memorable than their photographs[45,46] and capture attention more than images[47], with infants as young as 7 months showing a preference for looking at real objects over pictures[48]. Our results complement these studies by showing that even very brief prior real-world experience with an object can modulate the neural representation of its image. Together these results demonstrate the value in incorporating more naturalistic behavioral paradigms and stimuli that go beyond the computer screen to understand human object recognition.

Our finding that object identity can be successfully cross decoded across very different photographs of the same object from patterns of activation across voxels in LO and VTC is important for establishing the invariance of these object-responsive cortical regions. Invariance is generally assumed to increase along the visual processing hierarchy[49]. Previous studies have shown some degree of invariance in object representations in human occipitotemporal cortex across singular visual transformations such as object size[22,30], viewpoint[27], and position in the visual field [28,30]. Most earlier studies of invariance have focused on the category level rather than on the level of particular object exemplars[27–30]. We built on this work by conducting a strict test of object invariance for individual everyday objects. We were able to extract the representation of object identity from across different visual representations of each object by photographing actual objects in two different contexts (indoor and outdoor) and taking advantage of cross-decoding analysis methods to decode object identity across context. This test of invariance is much closer to how we experience objects in everyday life, with multiple visual features changing between the indoor and outdoor photographs of each object (e.g. luminance, contrast, viewpoint, distance, object shape [if non rigid], hue, illumination source, background, etc.). We found that both LO and VTC contained highly invariant representations of everyday household objects. Interestingly, we found no modulation of invariance by real-world object exploration in these visual areas. This may be because we used everyday objects such as mugs and shoes, and although participants had not encountered these specific exemplars before, they have a lifetime of experience with similar objects, which may be sufficient for supporting invariant visual representations of new exemplars.

In sum, our data show that the visual representation of an object is coded separately in the brain from the associations related to real-world exploration of that object. This is consistent with a framework that emphasizes that object concepts are not stored in a single brain region, but in networks of interconnected regions that extend beyond initial processing in sensory circuits[50]. Our discovery that ventral visual cortex contains highly invariant representations of individual objects that are not dependent on real-world experience underscores the efficiency of the human visual system in extracting object identity from the changeable visual features that accompany different viewing contexts. Real-world experience with an object has the potential to create a wide range of associations with an object from multimodal sensory details (how does it feel?) to context (where and when did you see the object?), associative memory (what does it remind you of?) and episodic memory (what

did you do with the object?). Our data points to medial parietal cortex as an important associative region for the information gained from object exploration, complementing the visual object representations in LO and VTC. Overall, our study highlights the importance of considering the role of real-world experience in human object recognition. Although deep neural networks are now proficient in labeling objects from images[3,4], human object perception extends beyond object labeling and encompasses a lifetime of experience manipulating and using objects to support our everyday behavior. A complete account of human object recognition will necessitate incorporating these human aspects of object perception into existing computational models.

Methods

Participants. The experiment was approved by the NIH Institutional Review Board (protocol 93-M-0170, clinical trials # NCT00001360). All participants gave written informed consent and received financial compensation for their time. Forty participants took part in the fMRI experiment (12 male, 28 female, age M = 24.68 years, SD = 4.80 years, range: 18 - 43 years). All participants were screened before taking part to ensure they were right-handed and neurologically healthy with normal or corrected-to-normal vision.

Real-world objects. 24 real-world objects were used as the experimental stimuli in the pre-scanning exploration task. They were divided into two sets of 12 objects, Set A and Set B. Participants explored only one of the object sets prior to scanning. Each set consisted of two exemplars from each of the following object categories: bags, shoes, mugs, clocks, socks, and stuffed toys. The object categories were chosen to be common household items that were small enough to be manipulable, and the specific object exemplars were selected to be distinctive enough to be recognizable in a photograph. The objects were sourced from the first author's personal belongings, thrift stores, and the online marketplace Etsy.

Visual stimuli. The visual stimuli were 48 high-resolution color photographs of the real-world objects. Each of the 24 objects was photographed twice in different contexts using an iPhone XS, once indoors (on a wooden floor) and once outdoors (on grass). The two photographs of each object

were designed to be as visually different as possible, to separate out object identity from the visual features of the specific images as much as possible. The orientation of the object and its shape (if non-rigid, like a sock) were deliberately changed between the two photos. The original photographs were cropped square to equal size [600 x 600 pixels] with the object positioned in the center of the image. No other image manipulations were made. All participants saw all 48 object photographs in the fMRI experiment and post-scan memory test, regardless of whether they explored object Set A or Set B.

Object exploration task. Prior to the MRI scan, participants completed a short object exploration task with one set of real-world objects (either Set A or Set B, counterbalanced across participants) and two experimenters. The first experimenter sat across a table from the participant and handed the participant each of the 12 objects one at a time from a black bag. Participants were given 30 seconds to explore the object however they chose. A second experimenter timed the exploration phase using a stopwatch, and the first experimenter returned the object to the bag at the end of the allocated time before producing the next one. The order of object presentation was randomized across participants, based on the order that the first experimenter pulled them out of the bag. The first experimenter recorded the object order on a sheet of paper by writing the corresponding presentation number [1-12] next to a picture of each object.

fMRI data acquisition. The fMRI experiment consisted of a structural anatomical scan, two functional localizer runs, and up to eight experimental runs. MRI data were acquired with a 3.0T GE Discovery MR750 MRI scanner and 32-channel head coil at the Functional Magnetic Resonance Imaging Core Facility (FMRIF) at the NIH in Bethesda, MD. Functional scans were collected with a multiband three-echo EPI sequence with whole-brain coverage (TR = 2000ms, TEs = 12.9, 32.2, and 51.6 ms, flip angle = 75°, 90 x 90 acquisition matrix, voxel size = 2.5 x 2.5 x 2.5 mm, 50 slices). A high-resolution T1-weighted structural MRI scan (3D-MPRAGE sequence, $1 \times 1 \times 1$ mm voxel size, in-plane matrix size: 256×256, 208 slices, TR = 6.952 ms, TE = 2.92 ms, FA = 8°) was also collected for each participant in the same session.

Visual stimuli were displayed using a flat-panel MRI-compatible 32" Cambridge Research Systems BOLDscreen with resolution 1920×1080 and viewing distance 2.5 m. Experimental and localizer stimuli subtended $5° \times 5°$ of visual angle. Behavioral responses were collected using an MRI-compatible button box.

Object-localizer runs. Two independent functional localizer runs were used to define the object-responsive regions of interest in lateral occipital and ventral temporal cortex in each participant's native brain space. The functional localizer stimuli were color photographs of objects and scrambled objects [600 x 600 pixels] from the BOSS database[5152]. The scrambled object images were created using a custom-script written in MATLAB which defined an 8 x 8 grid over the original object image and shuffled the resulting 64 'tiles' into a new location in the image. Each localizer run started and ended with a 16s fixation period, during which a black fixation cross was centered on a gray screen. The localizer runs used a block design, alternating between 16s blocks of objects and scrambled objects. There were 9 blocks of each stimulus type, for 18 blocks total. Within each 16s block, 20 stimuli were shown one at a time on a gray background in random order for 300 ms with a 500 ms inter-stimulus interval. Since the object photographs had a white background, a white square of the same size was shown on the gray background during the inter-stimulus interval to avoid unnecessary visual transients.

To maintain participants' attention throughout the localizer runs, we used a standard 1-back task. Participants were instructed to press a key when they saw the same image presented twice in a row. In each block, 18 unique stimuli were shown, and 2 stimuli were randomly selected to be repeated for the 1-back task. There were two 1-back trials per block, and they were spaced so that one repeated image occurred at a random interval in the first half of the block, and the second repeated image occurred at a random interval in the second half of the block. Mean task accuracy across all participants and localizer runs was 86.56% ($SD = 11.51\%$).

There was a total of 162 unique stimuli in each stimulus class (objects and scrambled objects), which were only shown once per run, except for the images repeated for the task trials. The images were randomly allocated to blocks each time the code was run. Each localizer run was 5.3 min long, and participants completed 2 runs during the MRI session — one before the experimental runs, and one after the experimental runs.

Experimental runs. In the experimental runs, we used an event-related design to measure the BOLD activation patterns evoked by each real-world object photograph. In each run, the 48 real-world object images (from both Set A and Set B) were shown once in a random order, with the restriction that no more than two objects from the same set were shown in a row. Each experimental run started and ended with a 16s fixation period — a black fixation cross was centered on a gray screen. Trials were 6 s in duration. On each trial, one object was shown for 300 ms on a gray background, and was then

replaced by a black fixation cross during the 5.7 s inter-stimulus interval before the start of the next trial.

As for the localizer runs, we used a 1-back task to maintain participants' attention throughout the experimental runs. There were four task trials per run, and four images were randomly selected to be repeated during the run (two from Set A objects, and two from Set B objects). Participants were instructed to press a key when they saw the same image presented twice in a row, and these repeated trials were removed from the analysis. Mean task accuracy across all participants and experimental runs was 88.75% (SD = 15.58%). Each experimental run was 5.7 min long, and participants completed 6-8 runs during the MRI session.

Post-scan memory task. Following the MRI session, participants completed a short memory task outside the scanner on a MacPro laptop. This was to check that participants could remember and recognize the 12 objects they explored prior to the scanning session from the photographs used in the fMRI experiment. Each of the 48 photographs was shown one at a time on a gray background in the center of the screen for 300 ms. The order of images was random with the restrictions that (i) no more than two objects from the same set were shown in a row, and (ii) the two images of the same object (i.e. indoor and outdoor contexts) were not be shown in a row. Participants used the arrow keys to indicate whether they explored each object in real life (left arrow key) or not (right arrow key). The code waited for their response before proceeding to the next image after an 800 ms inter-stimulus interval. A black fixation cross was always displayed except for when an object image was on the screen.

fMRI preprocessing. fMRI data were preprocessed using the AFNI[53] software package. EPIs were slice-time corrected, motion-corrected, and co-registered to the participant's individual anatomical volume using the customizable script *afni_proc.py*. Spatial smoothing of 4 mm full-width at half-maximum was applied to both localizer and functional runs. The multiecho EPI data was combined into a single time-series using AFNI's "optimally combined" algorithm. All analyses were conducted in the native brain space of each participant.

Functional ROI definition. Two functionally defined regions of interest (ROIs) were defined for each participant in their native brain space from the independent data in the functional localizer runs. Cortical reconstruction was performed using Freesurfer 6.0 from the structural scan for each

participant. Inflated surfaces were visualized in SUMA[54] for functional ROI definition, with the results of the GLM contrast (*objects > scrambled*) overlaid as t-maps. Object responsive regions were defined as the contiguous cluster of voxels that responded more to objects than scrambled objects in lateral occipital cortex (LO) and ventral temporal cortex (VTC) in each participant's native brain space. Functional ROIs were defined on the inflated cortical surface for each participant and then transformed back into their native volume space for further analysis.

An additional two ROIs were defined from the response to explored versus unexplored objects in the experimental runs by splitting the participants (N = 40) into two groups (n = 20) based on which set of objects they explored (Group A and Group B) and defining the ROI for each group from the independent data from the other group. For each group, the unthresholded results of the GLM contrast (*explored > unexplored objects*) were overlaid as t-maps on an inflated surface in SUMA and the medial parietal (MP) and posterior cingulate (PC) ROIs were defined in each hemisphere as the region of contiguous voxels that responded more to explored objects in these anatomical locations. These ROIs were then transformed into the native volume space of each participant in the other group (i.e. Group A's data was used to define Group B's ROIs, and vice versa). The number of voxels in each hemisphere in each of the four ROIs is reported in Supplementary Table 1.

fMRI multivariate pattern analysis. Decoding analysis was performed using The Decoding Toolbox (TDT)[55] and MATLAB. Decoding was performed with a linear SVM in each ROI on the beta weights estimated in a GLM using AFNI for each of the 48 stimuli, producing a separate beta weight for each run.

fMRI group-level statistics. Statistical testing for the whole-brain univariate analysis examining the difference between explored and unexplored objects was performed using AFNI's *3dttest++* and *SurfClust* functions on the standard mesh cortical surface. A group level t-test was performed for the contrast *Explored Objects > Unexplored Objects*. Note that for Group A participants (n = 20), this corresponds to *Set A > Set B*, and for Group B participants (n = 20), this corresponds to *Set B > Set A*. Cluster correction was applied to correct for multiple comparisons (at the $p < .001$ level) and the resulting thresholded t-statistics surviving correction for the whole sample (N = 40) were mapped on the inflated cortical surface (**Fig. 4**). The cluster threshold marking statistical significance at the $p < .001$ level was 79 voxels for the left hemisphere and 121 voxels for the right hemisphere.

Data availability. The experimental stimuli and data underlying the figures will be made publicly available on the Open Science Framework (https://osf.io) following publication.

References

1. Biederman, I. & Ju, G. Surface versus edge-based determinants of visual recognition. *Cognit. Psychol.* **20**, 38–64 (1988).

2. Thorpe, S., Fize, D. & Marlot, C. Speed of processing in the human visual system. *Nature* **381**, 520–522 (1996).

3. He, K., Zhang, X., Ren, S. & Sun, J. Deep Residual Learning for Image Recognition. in 770–778 (2016).

4. Krizhevsky, A., Sutskever, I. & Hinton, G. E. ImageNet Classification with Deep Convolutional Neural Networks. in *Advances in Neural Information Processing Systems* vol. 25 (Curran Associates, Inc., 2012).

5. Snow, J. C. & Culham, J. C. The Treachery of Images: How Realism Influences Brain and Behavior. *Trends Cogn. Sci.* **25**, 506–519 (2021).

6. DiCarlo, J. J., Zoccolan, D. & Rust, N. C. How does the brain solve visual object recognition? *Neuron* **73**, 415–434 (2012).

7. Goodale, M. A. & Milner, A. D. Separate visual pathways for perception and action. *Trends Neurosci.* **15**, 20–25 (1992).

8. Kravitz, D. J., Saleem, K. S., Baker, C. I., Ungerleider, L. G. & Mishkin, M. The ventral visual pathway: an expanded neural framework for the processing of object quality. *Trends Cogn. Sci.* **17**, 26–49 (2013).

9. Ungerleider, L. G. & Haxby, J. V. 'What' and 'where' in the human brain. *Curr. Opin. Neurobiol.* **4**, 157–165 (1994).

10. Ungerleider, L. & Mishkin, M. Two cortical visual systems. in *Analysis of visual behavior* 549–586 (The MIT Press, Cambridge, MA, 1982).

11. Grill-Spector, K., Kourtzi, Z. & Kanwisher, N. The lateral occipital complex and its role in object recognition. *Vision Res.* **41**, 1409–1422 (2001).

12. Kourtzi, Z. & Kanwisher, N. Representation of Perceived Object Shape by the Human Lateral Occipital Complex. *Science* **293**, 1506–1509 (2001).

13. Malach, R. *et al.* Object-related activity revealed by functional magnetic resonance imaging in human occipital cortex. *Proc. Natl. Acad. Sci.* **92**, 8135–8139 (1995).

14. Kanwisher, N., Chun, M. M., McDermott, J. & Ledden, P. J. Functional imaging of human visual recognition. *Cogn. Brain Res.* **5**, 55–67 (1996).

15. Grill-Spector, K., Kushnir, T., Edelman, S., Itzchak, Y. & Malach, R. Cue-Invariant Activation in Object-Related Areas of the Human Occipital Lobe. *Neuron* **21**, 191–202 (1998).

16. Gauthier, I. & Tarr, M. J. Visual Object Recognition: Do We (Finally) Know More Now Than We Did? *Annu. Rev. Vis. Sci.* **2**, 377–396 (2016).

17. Peissig, J. J. & Tarr, M. J. Visual Object Recognition: Do We Know More Now Than We Did 20 Years Ago? *Annu. Rev. Psychol.* **58**, 75–96 (2007).

18. Wardle, S. G. & Baker, C. I. Recent advances in understanding object recognition in the human brain: deep neural networks, temporal dynamics, and context. *F1000Research* **9**, (2020).

19. Henson, R., Shallice, T. & Dolan, R. Neuroimaging Evidence for Dissociable Forms of Repetition Priming. *Science* **287**, 1269–1272 (2000).

20. van Turennout, M., Ellmore, T. & Martin, A. Long-lasting cortical plasticity in the object naming system. *Nat. Neurosci.* **3**, 1329–1334 (2000).

21. Buckner, R. L. *et al.* Functional-Anatomic Correlates of Object Priming in Humans Revealed by Rapid Presentation Event-Related fMRI. *Neuron* **20**, 285–296 (1998).

22. Grill-Spector, K. *et al.* Differential Processing of Objects under Various Viewing Conditions in the Human Lateral Occipital Complex. *Neuron* **24**, 187–203 (1999).

23. Gotts, S. J., Milleville, S. C., Bellgowan, P. S. F. & Martin, A. Broad and Narrow Conceptual Tuning in the Human Frontal Lobes. *Cereb. Cortex* **21**, 477–491 (2011).

24. Snow, J. C. *et al.* Bringing the real world into the fMRI scanner: Repetition effects for pictures versus real objects. *Sci. Rep.* **1**, 130 (2011).

25. Biederman, I. Visual Object Recognition. in *An Invitation to Cognitive Science: Visual Cognition* (1995).

26. Booth, M. C. & Rolls, E. T. View-invariant representations of familiar objects by neurons in the inferior temporal visual cortex. *Cereb. Cortex* **8**, 510–523 (1998).

27. Andresen, D. R., Vinberg, J. & Grill-Spector, K. The representation of object viewpoint in human visual cortex. *NeuroImage* **45**, 522–536 (2009).

28. Carlson, T., Hogendoorn, H., Fonteijn, H. & Verstraten, F. A. J. Spatial coding and invariance in object-selective cortex. *Cortex* **47**, 14–22 (2011).

29. Schwarzlose, R. F., Swisher, J. D., Dang, S. & Kanwisher, N. The distribution of category and location information across object-selective regions in human visual cortex. *Proc. Natl. Acad. Sci.* **105**, 4447–4452 (2008).

30. Vaziri-Pashkam, M. & Xu, Y. An Information-Driven 2-Pathway Characterization of Occipitotemporal and Posterior Parietal Visual Object Representations. *Cereb. Cortex* **29**, 2034–2050 (2019).

31. Xu, Y. & Vaziri-Pashkam, M. Examining the Coding Strength of Object Identity and Nonidentity Features in Human Occipito-Temporal Cortex and Convolutional Neural Networks. *J. Neurosci.* **41**, 4234–4252 (2021).

32. Gilmore, A. W., Nelson, S. M. & McDermott, K. B. A parietal memory network revealed by multiple MRI methods. *Trends Cogn. Sci.* **19**, 534–543 (2015).

33. Gilmore, A. W., Kalinowski, S. E., Milleville, S. C., Gotts, S. J. & Martin, A. Identifying task-general effects of stimulus familiarity in the parietal memory network. *Neuropsychologia* **124**, 31–43 (2019).

34. Nelson, S. M., Arnold, K. M., Gilmore, A. W. & McDermott, K. B. Neural Signatures of Test-Potentiated Learning in Parietal Cortex. *J. Neurosci.* **33**, 11754–11762 (2013).

35. Chao, L. L., Weisberg, J. & Martin, A. Experience-dependent Modulation of Category-related Cortical Activity. *Cereb. Cortex* **12**, 545–551 (2002).

36. Duke, D., Martin, C. B., Bowles, B., McRae, K. & Köhler, S. Perirhinal cortex tracks degree of recent as well as cumulative lifetime experience with object concepts. *Cortex* **89**, 61–70 (2017).

37. Köhler, S. & Martin, C. B. Familiarity impairments after anterior temporal-lobe resection with hippocampal sparing: Lessons learned from case NB. *Neuropsychologia* **138**, 107339 (2020).

38. Martin, C. B., McLean, D. A., O'Neil, E. B. & Köhler, S. Distinct Familiarity-Based Response Patterns for Faces and Buildings in Perirhinal and Parahippocampal Cortex. *J. Neurosci.* **33**, 10915–10923 (2013).

39. Montaldi, D., Spencer, T. J., Roberts, N. & Mayes, A. R. The neural system that mediates familiarity memory. *Hippocampus* **16**, 504–520 (2006).

40. Yang, H., McRae, K. & Köhler, S. Perirhinal cortex automatically tracks multiple types of familiarity regardless of task-relevance. *Neuropsychologia* **187**, 108600 (2023).

41. Sugiura, M., Shah, N. J., Zilles, K. & Fink, G. R. Cortical Representations of Personally Familiar Objects and Places: Functional Organization of the Human Posterior Cingulate Cortex. *J. Cogn. Neurosci.* **17**, 183–198 (2005).

42. Charest, I., Kievit, R. A., Schmitz, T. W., Deca, D. & Kriegeskorte, N. Unique semantic space in the brain of each beholder predicts perceived similarity. *Proc. Natl. Acad. Sci.* **111**, 14565–14570 (2014).

43. Weisberg, J., van Turennout, M. & Martin, A. A Neural System for Learning about Object Function. *Cereb. Cortex* **17**, 513–521 (2007).

44. Freud, E. *et al.* Getting a grip on reality: Grasping movements directed to real objects and images rely on dissociable neural representations. *Cortex* **98**, 34–48 (2018).

45. Snow, J. C., Skiba, R. M., Coleman, T. L. & Berryhill, M. E. Real-world objects are more memorable than photographs of objects. *Front. Hum. Neurosci.* **8**, (2014).

46. Snow, J. C., Gomez, M. A. & Compton, M. T. Human memory for real-world solid objects is not predicted by responses to image displays. *J. Exp. Psychol. Gen.* (2023) doi:10.1037/xge0001387.

47. Gomez, M. A., Skiba, R. M. & Snow, J. C. Graspable Objects Grab Attention More Than Images Do. *Psychol. Sci.* **29**, 206–218 (2018).

48. Gerhard, T. M., Culham, J. C. & Schwarzer, G. Distinct Visual Processing of Real Objects and Pictures of Those Objects in 7- to 9-month-old Infants. *Front. Psychol.* **7**, (2016).

49. Rust, N. C. & DiCarlo, J. J. Selectivity and Tolerance ("Invariance") Both Increase as Visual Information Propagates from Cortical Area V4 to IT. *J. Neurosci.* **30**, 12978–12995 (2010).

50. Martin, A. GRAPES—Grounding representations in action, perception, and emotion systems: How object properties and categories are represented in the human brain. *Psychon. Bull. Rev.* **23**, 979–990 (2016).

51. Brodeur, M. B., Guérard, K. & Bouras, M. Bank of Standardized Stimuli (BOSS) phase II: 930 new normative photos. *PloS One* **9**, e106953 (2014).

52. Brodeur, M. B., Dionne-Dostie, E., Montreuil, T. & Lepage, M. The Bank of Standardized Stimuli (BOSS), a New Set of 480 Normative Photos of Objects to Be Used as Visual Stimuli in Cognitive Research. *PLOS ONE* **5**, e10773 (2010).

53. Cox, R. W. AFNI: Software for Analysis and Visualization of Functional Magnetic Resonance Neuroimages. *Comput. Biomed. Res.* **29**, 162–173 (1996).

54. Saad, Z. S., Reynolds, R. C., Argall, B., Japee, S. & Cox, R. W. SUMA: an interface for surface-based intra-and inter-subject analysis with AFNI. in *2004 2nd IEEE International Symposium on Biomedical Imaging: Nano to Macro (IEEE Cat No. 04EX821)* 1510–1513 (IEEE, 2004).

55. Hebart, M. N., Görgen, K. & Haynes, J.-D. The Decoding Toolbox (TDT): a versatile software package for multivariate analyses of functional imaging data. *Front. Neuroinformatics* **8**, 88 (2015).