2   RH: phylogenetic model exploration with `phyddle`

3 `phyddle`: software for phylogenetic model exploration
4 with deep learning

5   MICHAEL J. LANDIS[1,*], AMMON THOMPSON[2]

6   [1]*Department of Biology, Washington University, St. Louis, MO, 63110, USA*

7   [2]*Participant in an education program sponsored by U.S. Department of Defense (DOD)*

8   *****Corresponding author:** E-mail: michael.landis@wustl.edu.

Abstract.— Many realistic phylogenetic models lack tractable likelihood functions, prohibiting their use with standard inference methods. We present `phyddle`, a pipeline-based toolkit for performing phylogenetic modeling tasks using likelihood-free deep learning approaches. `phyddle` coordinates modeling tasks through five analysis steps (*Simulate*, *Format*, *Train*, *Estimate*, and *Plot*) that transform raw phylogenetic datasets as input into numerical and visualized model-based output. Benchmarks show that `phyddle` accurately performs a range of inference tasks, such as estimating macroevolutionary parameters, selecting among continuous trait evolution models, and passing coverage tests for epidemiological models, even for models that lack tractable likelihoods. `phyddle` has a flexible command-line interface, making it easy to integrate deep learning approaches for phylogenetics into research workflows. Learn more about `phyddle` at `https://phyddle.org`.

(Keywords: phylogenetic models, estimation, deep learning, neural network, supervised learning)

Introduction

Good phylogenetic model design balances biological, statistical, and computational considerations (Felsenstein 1985b; Hansen and Martins 1996; Kelchner and Thomas 2007; Rodrigue and Philippe 2010; Servedio et al. 2014; Rolland et al. 2023). Not only should a phylogenetic model realistically describe how evolutionary lineages change across generations, it should allow accurate estimates to be obtained in a short amount of time.

Unfortunately, in practice, models with desirable biological or statistical properties often yield intractable likelihood functions. Researchers are forced to compromise: either use tractable but suboptimal phylogenetic models, or invest substantial resources and effort to design and validate boutique inference methods for more-realistic models. Most would rather not compromise at all, but must, in part due to our field's reliance on likelihood-based inference for model-fitting. Likelihood-free approaches might be useful for model exploration, where deep learning approaches have demonstrated the ability to solve a variety of difficult, foundational problems in phylogenetics (Suvorov et al. 2020; Borowiec et al. 2022; Voznica et al. 2022; Smith and Hahn 2023; Lambert et al. 2023; Kong et al. 2023; Thompson et al. 2024; Nesterenko et al. 2024; Silvestro et al. 2024; Mo et al. 2024).

This application note introduces `phyddle`, a phylogenetic modeling framework for training neural networks with simulated data through supervised learning (LeCun et al. 2015; Goodfellow et al. 2016; Paszke et al. 2019). A primary goal of `phyddle` is to equip biologists with a deep learning pipeline workflow so they may explore and apply realistic, but otherwise intractable, phylogenetic models in the study empirical of problems. `phyddle` generalizes existing deep learning techniques for modeling lineage diversification and trait evolution to a broader class of user-defined phylogenetic models and scenarios (Bokma 2006; Voznica et al. 2022; Lambert et al. 2023; Thompson et al. 2024).

Overview

`phyddle` uses deep learning and simulation-trained neural networks to perform

phylogenetic modeling tasks. This overview assumes some basic familiarity with deep

learning concepts (see Borowiec et al. 2022 or Goodfellow et al. 2016 for background

reading). `phyddle` pipelines are composed of five modular steps (Figure 1): *Simulate*,

Format, *Train*, *Estimate*, and *Plot*. Settings for each step are controlled through

command-line options and a customizable configuration file. Being a pipeline, `phyddle`

output is stored in a predictable manner, allowing the output from one step to become the

input for downstream steps. `phyddle` functions as both an interactive command-line tool

and as a scriptable interface, allowing researchers to design and debug workflows

line-by-line before writing scripts to automate repetitive and large-scale jobs.

The *Simulate* step generates large numbers of example datasets under a model with

a user-specified simulation script. We have attempted to make the *Simulate* as flexible but

simple as possible so researchers may focus on model design. Users provide `phyddle` with

model simulators written in whatever programming language suits their needs. Users are

encouraged to either modify the simulator scripts bundled with `phyddle`, written using R

(R Core Team 2013), Python (Van Rossum and Drake 2009), RevBayes (Höhna et al.

2016), MASTER (Vaughan and Drummond 2013), and PhyloJunction (Mendes and Landis

2023), or to write their own script from scratch using a language of their choice.

Each simulation script itself defines the phylogenetic model, simulates data under

that model, and saves that data using standard file formats (e.g. Newick, Nexus, and/or

data tables) required by `phyddle`. When run, a simulation generates both a training

example (e.g. a phylogenetic tree and a character matrix) and the training labels (e.g. the

data-generating parameters). All gathered simulations comprise the raw and unformatted

training dataset. Simulation tasks may be run in batches and across processors, in parallel.

Next, the *Format* step encodes raw datasets into a set of tensors, analogous to

N-dimensional arrays of variables, which are later processed by the *Train* step. *Format*

processes all valid examples from *Simulate*, plus any empirical datasets flagged for analysis

Figure 1: Overview of `phyddle` workflow. Researchers provide the software with a configuration file and a simulation script that determine the analysis settings. Upon running `phyddle`, the *Simulate* step produces a raw (unformatted) pool of training datasets that represent data-generating parameters (labels) and realizations of the data-generating model (examples). Next, the *Format* step restructures the raw training data into tensors, while also reclassifying simulating conditions (e.g. parameters) as either data (treated as observed) or labels (to be predicted). The *Train* step loads the tensor data, constructs and fits neural network architecture, saves a copy of the trained network, and reports training results. The *Estimate* step generates model predictions for test and empirical datasets that were not used during training. Lastly, the *Plot* step produces figures and reports that summarize the pipeline results.

by `phyddle`. *Format* converts each raw dataset into three types of tensors: a phylogenetic data tensor, an auxiliary data tensor, and a label tensor. Tensors can be saved either in human-readable .csv format or in a compact .hdf5 format that is often 20x smaller than its .csv counterpart.

Phylogenetic data tensors encode phylogenetic and tip-state data into 2D tensor structure suitable for supervised learning with convolutional neural network (CNN) layers. `phyddle` supports the compact bijective ladderized vector (CBLV; Voznica et al. 2022) for serially sampled trees and the compact diversity vector (CDV; Lambert et al. 2023) for extant-only trees, with the option to include additional rows of phylogenetic branch length information. `phyddle` also allows users to associate multiple categorical or numerical traits with each taxon (+S; Thompson et al. 2024). True to the name, these encodings have a small memory/storage footprint that is linearly proportional to taxon count (compact) and uniquely identify the encoded tree (bijective) (Voznica et al. 2022).

Auxiliary data tensors and label tensors are simpler, and used as input for dense feed-forward neural network (FFNN) layers. Each row in the auxiliary data tensor represents a single, raw dataset, with each column corresponding to a different summary statistic (e.g. tree height, tree balance, etc.) or "known" model parameter (e.g. population size, sampling effort) for the data-generating process. Each row in the label tensor also references a single, raw dataset with columns corresponding to different model parameters. Labels can have numerical (rates, ancestral trait) or categorical values (model-type, ancestral state).

The *Train* step constructs, trains, calibrates, and saves a neural network and its training history. Neural networks are built and trained using PyTorch (Paszke et al. 2019) with the option to use CPU and Nvidia GPU (CUDA) parallelization. `phyddle` combines CNN and FFNN layers for modeling tasks (see Goodfellow et al. 2016 for review). Phylogenetic data tensors are processed as input using a set of convolutional and pooling (CNN) layers, whereas the auxiliary data tensors are processed with fully-connected, dense

(FFNN) layers (Voznica et al. 2022; Lambert et al. 2023; Thompson et al. 2024). The output of these CNN and FFNN layers are then concatenated and passed into a final series of dense FFNN layers for each training target that terminate with an output layer for prediction. `phyddle` allows users to adjust the depths and widths of layers, convolutional settings (stride, dilation, etc.), activation functions, loss functions, and optimizer through the configuration file. *Train* uses the held-out calibration data to generate conformalized prediction intervals (CPIs) for the trained network (Romano et al. 2019) whereby e.g. an 80% CPI is the interval that has a 80% chance of containing the true parameter value, based on the known accuracy of training dataset predictions.

Supervised learning with training examples from *Simulate* is used to train, validate, and calibrate prediction intervals from the neural network. When complete, the trained network is saved to file in .hdf5 so it may be used for future estimation tasks. The training history of network loss, accuracy, etc. for both the training and validation datasets is recorded in a .csv file. Tables of predicted versus true values for the training and test datasets are also saved in .csv files. Lastly, `phyddle` stores the means and standard deviations needed to normalize new biological datasets for use with the trained network for predictions.

The *Estimate* step uses the trained network to make predictions from new datasets. When called, *Estimate* runs against a subset of the simulated examples that were not used during training (the test dataset) to assess performance of the trained network. *Estimate* also runs against any empirical datasets identified by the analysis. It must be stressed that *Estimate* is the simplest and fastest step, generally producing new estimates from the trained network within milliseconds. After the initial cost of generating a training dataset and training the network, new estimates from a trained network are effectively free.

Lastly, the *Plot* step visualizes all output from a `phyddle` analysis, beginning with empirical results and ending with network performance and architecture. Empirical estimates for numerical and categorical variables are first shown independently, and also

plotted in reference against all the marginal densities and dimension-reduced joint densities of the simulated auxiliary data and labels. Network accuracy for training and test datasets are then displayed as scatter plots for numerical labels and confusion matrices for categorical labels. To help assess poor network performance, loss scores across training epochs for training and validation datasets and network architecture are shown last. In addition, *Plot* records data about a `phyddle` run into an easily parsed .csv file.

The modular design of the `phyddle` pipeline makes it relatively easy to design, train, save, and share new models with other biologists. Only a configuration file and the contents of the *Train* directory are needed for other researchers to perform *Estimate* tasks with the trained network on their empirical datasets. Entire project workspaces can be archived to ensure research is reproducible.

To showcase the flexibility and jump-start the adoption of `phyddle`, it is bundled with example configuration files, simulation scripts, and pipeline results for a variety of phylogenetic models (`https://github.com/mlandis/phyddle/workspace`). Current examples include state-dependent speciation-extinction models (SSE), susceptible-infectious-recovered models (SIR), and trait evolution models that variously use R, Python, RevBayes (Höhna et al. 2016), PhyloJunction (Mendes and Landis 2023), and MASTER (Vaughan and Drummond 2013) to simulate training datasets. These generic examples are meant to be adapted by biologists developing customized `phyddle` pipelines to model their systems.

Example analyses

We applied `phyddle` to three phylogenetic modeling scenarios to illustrate how the deep learning software behaves relative to existing likelihood-based methods. Unless otherwise stated, `phyddle` analyses used default settings for the network configuration and training. The full simulated dataset was split into training (70%), validation (5%), test (5%) and calibration (20%) data subsets. Networks were trained for up to 200 epochs, but

155 stopped early if validation loss scores worsened across three consecutive epochs. Results

156 from the *Plot* step were reviewed to confirm each network was properly trained. Method

157 comparisons used examples from the test data subset.

Macroevolution under BiSSE

159   We simulated phylogenetic datasets under a simple binary state-dependent

160 speciation-extinction (BiSSE; Maddison et al. 2007). The BiSSE model is a tree-generating

161 process that assumes that speciation rates and extinction rates depend on the state of an

162 evolving binary character. Our simulation used the following settings:

$$\lambda_1, \lambda_2 \sim \text{Unif}(0, 1) \qquad \text{(birth rates)}$$

$$\mu \sim \text{Unif}(0, 1) \qquad \text{(death rates)}$$

$$q \sim \text{Unif}(0, 1) \qquad \text{(state transition rates)}$$

$$T_{max} \sim \text{Unif}(1, 100) \qquad \text{(max. time)}$$

$$M_{max} \sim \text{Unif}(10, 5000) \qquad \text{(max. num. taxa)}$$

where λ_1 and λ_2 are state-dependent birth rates for lineages in states 1 and 2 respectively,

μ is the state-independent death rate, and q is the symmetric transition rate between states

1 and 2. Each simulation was terminated after T_{max} units of evolutionary time or when the

phylogeny contained M_{max} extant taxa, whichever condition arose first. Only extant taxa

are retained.

We used the R packages `ape` (Paradis and Schliep 2019) and `castor` (Louca and

Doebeli 2018) to simulate and fit phylogenies and character matrices with a BiSSE model.

We simulated datasets with the `castor::simulate_dsse()` function. Datasets with 500 or

fewer taxa included all taxa and had sampling fractions of 1, whereas larger trees were

downsampled to 500 taxa and recorded as having sampling fractions of less than 1. All

data-generating parameters and the sampling fraction were log-transformed before being saved to file for the example dataset. Evolutionary rates were treated as estimation targets, while the sampling fraction was treated as a known parameter. Simulated trees were saved in Newick format, and data matrices were stored as comma-separated value tables. This simulation procedure is stored in the file `sim_bisse.R`, as referenced in the `phyddle` configuration file below.

Maximum likelihood estimates (MLEs) for each dataset were obtained using the `castor::fit_musse()` function under the `nlminb` optimization method. To improve optimization success, each MLE represents 10 trials with 30 initial guesses ("scouts") per trial and one "noisy" guess that is centered on the true data-generating parameters. Optimization was further restricted to search for parameter values within the simulated bounds (minimum 0, maximum 1), as it improved MLE parameter accuracy. We also expect MLE might mildly underperform in this analysis, because the inference model conditions on survival of the tree, rather than the T_{max} and M_{max} stopping criteria used for the simulating model.

Neural network estimates were generated with `phyddle`, using the config file shown as Listing 1. As the comments explain, this config expects extant-only trees with one character and two states per taxon. Four numerical parameters (log-transformed λ_1, λ_2, μ, and q) are estimated, while one numerical parameter (log-transformed sampling proportion, ρ) is treated as known, as stated earlier. Default `phyddle` settings are used for any unspecified settings in the config file (see documentation).

```
# Example phyddle config file for BiSSE
args = {

    #----------------------------------#
    # Project organization             #
    #----------------------------------#
    # Step(s) to run
    'step'              : 'SFTEP',
    # Prefix for output for all setps
    'prefix'            : 'out',
    # Base directory for output
    'dir'               : './',

    #----------------------------------#
    # Simulate Step settings           #
```

```
209        #----------------------------------#
210        # Simulation command string (user provides script)
211        'sim_command'        : 'Rscript sim_bisse.R',
212
213        #----------------------------------#
214        # Format Step settings              #
215        #----------------------------------#
216        # Number of evolutionary characters
217        'num_char'           : 1,
218        # Number of states per character
219        'num_states'         : 2,
220        # No extinct taxa for phylo. tensor (CDV format)
221        'tree_encode'        : 'extant',
222        # How to represent phylo, times? heights and branch lengths?
223        'brlen_encode'       : 'height_brlen',
224        # How to encode discrete states? one_hot or integer
225        'char_encode'        : 'integer',
226        # Model parameters to predict (labels)
227        'param_est'          : {
228            'log_birth_1'     : 'num',
229            'log_birth_2'     : 'num',
230            'log_death'       : 'num',
231            'log_state_rate'  : 'num'
232        },
233        # Model parameters that are known (aux. data)
234        'param_data'         : {
235            'log_sample_frac' : 'num'
236        },
237        # Character matrix output format
238        'char_format'        : 'csv',
239
240        #----------------------------------#
241        # Train/Estimate/Plot Step settings  #
242        #----------------------------------#
243        # Use defaults
244        # (see documentation)
245
246   }
```

Listing 1: Minimal `phyddle` config file for BiSSE analysis. We specify only a few key settings and let `phyddle` apply default values to the remaining settings (see documentation).

²⁴⁷ We simulated 50,000 example datasets for the `phyddle` analysis. The configuration

²⁴⁸ file, simulation script, and pipeline results are stored in the project archive,

²⁴⁹ `bisse_project.tar.gz`. Pipeline results can be reproduced from scratch with the

²⁵⁰ commands in Listing 2:

```
251  $ # load project
252  $ phyddle --load_proj bisse_project.tar.gz
253  $ # delete previous work
254  $ phyddle --clean_proj
255  $ # run all steps
256  $ phyddle -s SFTEP --end_idx 50000
```

Listing 2: Shell commands for BiSSE analysis using `phyddle`.

²⁵⁷ Parameter estimates for `phyddle` (Fig. 2A-D) and maximum likelihood (Fig. 2E-H)

 are each highly correlated with the true data-generating parameters. In addition, `phyddle`

 and maximum likelihood methods tend to agree with each other as much as the truth (Fig.

 2I-L), implying both methods extract similar information from the same data pattern.

Figure 2: Comparison of maximum likelihood and `phyddle` parameter estimates. Each column corresponds to a BiSSE model rate that was estimate: λ_1, λ_2, μ, and q. The first row compares `phyddle` estimates to true parameter values (blue, A-D), the second row compares MLEs to true values (red, E-H), and the third row compares `phyddle` and MLE estimates to each other (gold, I-L). The black line is set to intercept-0 and slope-1, representing perfectly matching values. The colored lines are standard linear regressions, and align with the black line when estimates agree with the truth (blue and red) or with each other (gold).

 Model selection of evolutionary mode

We simulated datasets under four models that represent alternate modes of

continuous trait evolution: Brownian motion for incremental change (BM; Felsenstein

1985a), Ornstein-Uhlenbeck for stationarity (OU; Hansen and Martins 1996), Early Burst

for explosive change (EB; Harmon et al. 2010), and a Normal Inverse Gaussian Lévy process for pulsed change (LP; Landis and Schraiber 2017). Trees were simulated with a standard constant-rate birth-death model, under the following conditions

$$\lambda \sim \text{Unif}(1,5) \qquad \text{(birth rate)}$$
$$\mu \sim \text{Unif}(0,\lambda) \qquad \text{(death rate)}$$
$$T_{max} \sim \text{Unif}(1,5) \qquad \text{(max. sim. time)}$$
$$M_{min} = 100 \qquad \text{(min. num. sampled taxa)}$$
$$M_{max} \sim \text{Unif}(100,300) \qquad \text{(max. num. taxa)}$$

Next, for each tree, we first sampled a model type and its corresponding model parameters and then simulating the dataset:

$$C \sim \{\text{BM}, \text{OU}, \text{EB}, \text{LP}\} \qquad \text{(model type)}$$
$$X_0 \sim \text{Norm}(0,2) \qquad \text{(starting trait value)}$$
$$\sigma^2 \sim \text{Gamma}(1,2) \qquad \text{(process variance)}$$
$$s \sim \text{Gamma}(5,100) \qquad \text{(tip noise)}$$
$$t_{1/2} \sim \text{Gamma}(4,2) \qquad \text{(half-life; OU only)}$$
$$\beta \sim \text{Gamma}(2,2) \qquad \text{(decay; EB only)}$$
$$\kappa \sim \text{Gamma}(3,2) \qquad \text{(process kurtosis; LP only)}$$

where the mean of $\text{Gamma}(\alpha, \beta)$ equals α/β. Process variance and kurtosis are the expected moments for trait change after one unit of time. For the OU process, process variance refers to the Brownian variance (i.e., not the stationary variance) and the optimal value is assumed to equal the ancestral value, X_0. Phylogenetic half-life relates to the OU

mean-reversion strength as $\alpha = \ln(2)/t_{1/2}$ (Hansen 1997). Process variance and kurtosis are

reparameterized into standard model parameters for LP (Landis and Schraiber 2017).

Note, these ranges of parameters were chosen so that datasets generated by more-complex

models (OU, EB, LP) might be misinterpreted as originating from the simpler model

(BM), thereby complicating model selection.

Trait datasets were simulated and fitted using the R package `pulsR`. Maximum

likelihood estimates were obtained after 5 independent Nelder-Mead optimization

attempts. We then computed Akiake Information Criteria (AIC) scores for each model as

$AIC(c) = -2(L_c - K_c)$, where L_c is the maximum log-likelihood and K_c is the number of

free parameters for model c. We treated the model with the lowest $AIC(c)$ value as the

model selected by maximum likelihood (Akaike 1973).

To train `phyddle`, we simulated 200,000 datasets with a maximum tree width of

300. Training targets included σ^2, κ, and C. Other data-generating parameters (e.g. λ, μ,

X_0, etc.) were treated as nuisance parameters and not estimated. We used CDV+S

encoding with one row of numerical values for each species trait. We used a soft-max layer

with a cross-entropy loss function to transform network output that model type $C = c$ with

probability w_c. Interpreting w_c as proportional to the maximum (unlogged-) likelihood

score for model c, we computed a penalized model selection score

$SEL(c) = -2(ln(w_c) - K_c)$. We then treated the model with the smallest value of $SEL(c)$

as the model selected by `phyddle`.

In general, we find both `phyddle` and AIC with `pulsR` are comparable at model

selection (Fig. 3). Both methods consistently select either the true model (diagonal) or the

simpler nested model (BM, top row) in the majority of cases (Fig. 3A-B). Regardless of

whether they selected the true model, both methods tended to select the same model (Fig.

3C, diagonal). We note that `pulsR` requires the numerical integration of a recursively

constructed characteristic function for model fitting, which grows prohibitively expensive

for larger trees (see Landis and Schraiber 2017). The results for the full `phyddle` pipeline

Figure 3: Comparison of model selection for AIC and `phyddle` estimates. Possible models are Brownian motion (BM), Ornstein-Uhlenbeck (OU), Early Burst (EB), and a Lévy process (LP; normal inverse-Gaussian). `phyddle` (A, blue) and AIC (B, red) reliably identify to true data-generating model, or the two methods agree (C, gold), when the frequencies along the diagonal are high. Off-diagonal entries represent model misidentification (A,B) or classification disagreement (C) for that column.

took approximately 15 minutes, whereas the `pulsR` pipeline took 5 hours.

Phylodynamics under SIR with Migration

We compared `phyddle` to the performance of likelihood-based inference methods under two Susceptible-Infected-Recovered (SIR) model scenarios. First, we simulated data for a phylogeographic model of pathogen infection that we refer to as a SIR + Migration or SIRM model (Riley 2007). We consider the case from (Thompson et al. 2024) where all pathogen sampling occurs during the exponential growth phase early in an outbreak, accomplished by rejecting simulations where more than 5% of susceptible individuals were infected. Only during the exponential growth phase, our SIRM model behaves as a serially sampled multitype birth-death model (Stadler and Bonhoeffer 2013; Kühnert et al. 2016), and is analyzed with a known and tractable likelihood function (Maddison et al. 2007; May and Meyer 2024). We used the test data and Bayesian estimates from (Thompson et al. 2024) to compare against our `phyddle` estimates.

We simulated outbreaks among five locations under the following conditions

$$N = 10^6 \qquad \text{(num. of hosts in each location)}$$

$$R_0 \sim \text{Unif}(2, 8) \qquad \text{(basic reproduction number)}$$

$$\gamma \sim \text{Unif}(0.01, 0.05) \qquad \text{(recovery rate)}$$

$$\delta \sim \text{Unif}(0.0001, 0.005) \qquad \text{(sampling rate)}$$

$$m \sim \text{Unif}(0.0001, 0.005) \qquad \text{(migration rate)}$$

$$T = 100 \qquad \text{(sim. time)}$$

$$M_{max} \sim \text{Unif}(20, 499) \qquad \text{(max. num. of sampled taxa)}$$

$$\rho = 0.01 \qquad \text{(probability of extant sampled)}$$

The per-host infection rate during the exponential-growth phase of an outbreak is $\beta = R_0(\gamma + \delta)$. All simulations ran for T units of time, with each contagious individual at the end of the simulation (extant) having ρ probability of being sampled. The trees were downsampled to a maximum of M_{max} taxa.

In the second scenario, pathogens are sampled at a random time during the outbreak, both during and after the exponential growth phase; for this scenario we lack a simple likelihood-based inference strategy. We simulated training and test data under the same settings as above except

$$N = 10^4$$

$$T = 50$$

The smaller population size ensures many of the simulations extend beyond the exponential phase.

Note, the modeled scenarios are analogous, except that the data sampling procedure is expanded under the second scenario. We separately simulate data and train neural

³¹⁴ networks with `phyddle` for each scenario. We are not aware of an exact likelihood-based

³¹⁵ solution for the general SIRM model, i.e. where individuals can be sampled at any time

³¹⁶ during the outbreak and exact numbers of susceptible and infected individuals in location i

³¹⁷ at time t inform the local, instantaneous infection rate (but see Kühnert et al. 2016 and

³¹⁸ Müller et al. 2019). We emphasize that our comparison seeks to measure the accuracy of

³¹⁹ `phyddle` for a model with no simple likelihood-based counterpart. So, even if the

³²⁰ unrestricted SIRM model had easily computable likelihoods, it would be trivial to engineer

³²¹ a more-realistic but less-tractable model (e.g. Moshiri et al. 2019; Shchur et al. 2022;

³²² Gavotte and Frutos 2022; Xu et al. 2024). As such, both our Bayesian analyses use the

³²³ simpler, tractable, and time-constant SIRM model that assumes we only sample during the

³²⁴ exponential growth phase.

³²⁵ We used RevBayes (Höhna et al. 2016) with the TensorPhylo plugin (May and

³²⁶ Meyer 2024) to estimate the joint posterior density of SIRM model parameters. We

³²⁷ assumed the population size (N), recovery rate (γ) and extant sampling probability (ρ)

³²⁸ were known empirically, while the reproduction number (R_0), sampling rate (δ), and

³²⁹ migration rate (m) were estimated. Prior distributions match the simulating distributions

³³⁰ for all parameters. Markov chain Monte Carlo was run for 7,500 generations. A burnin

³³¹ period of 10% of generations was run before MCMC sampling and all model parameters

³³² had effective sample sizes of > 100.

³³³ We used `phyddle` to simulate 53,416 valid training examples for the exponential

³³⁴ phase dataset and 96,555 for the all-phases dataset, as described above. Calibration

³³⁵ datasets for performing conformal prediction by adjusting inner quantile estimates

³³⁶ consisted of 6,677 for the exponential phase dataset and 37,136 for the all-phases dataset.

³³⁷ Parameters N and γ were treated as known, whereas R_0, δ, and m were inferred as free

³³⁸ parameters. We used a CBLV+S tensor with one-hot encoding to represent phylogenetic

³³⁹ and tip states across 5 locations.

³⁴⁰ Under the first scenario without model misspecification for the Bayesian approach,

Figure 4: Comparison of Bayesian and `phyddle` estimates for the basic reproduction number, R_0, when all pathogens are sampled during the exponential growth phase of an outbreak (A-D) or sampled at any time during an outbreak (E - H). True parameter values are plotted against `phyddle` (blue; A and E) and Bayesian (red; B and F) point estimates. Estimated support interval bounds (gold; C, D, G, and H) for `phyddle` and Bayesian methods are also plotted against each other. Any point that falls on a slope-1 intercept-0 line has perfectly matching x and y values. Data displayed is a random subsample of 50 values (roughly 50%). Intervals shown are 95% CPI (conformalized prediction interval) or HPD (highest posterior density). Bayesian estimates and test data for comparison of exponential phase data (A-D) are from (Thompson et al. 2024).

we see that both Bayesian and `phyddle` point estimates for the basic reproduction number

are highly correlated with the true data-generating parameter values (Fig. 4A-B). In

addition, lower and upper bounds for 95% highest posterior density credible intervals and

conformalized prediction intervals are tightly correlated (Fig. 4C-D).

Under the full outbreak scenario, `phyddle` accurately estimates the true

data-generating parameters (Fig. 4E), but the Bayesian posterior point estimates and

support interval bounds no longer agree with `phyddle` (Fig. 4F-H). That is, as the outbreak

progresses, the number of new hosts that are still susceptible to infection decreases so the

infection rate slows, hence the consistent underestimation for the reproductive number when the model assumes unbounded, exponential growth in the number of infections.

Similar results for the sampling rate, δ, and migration rate, m, are provided in the Supplement. This behavior is expected because, although the neural networks trained by `phyddle` conform to all model assumptions encoded into the simulator, the simulator violates the simplifying model assumptions required to obtain a tractable likelihood for our Bayesian analysis.

Although this experiment only demonstrates how inference methods behave when models are correctly versus incorrectly specified for two epidemiological scenarios, the broader need to mitigate model misspecification and potential solution offered by likelihood-free methods, such as `phyddle`, are more general.

Conclusion

We expect that `phyddle` has many possible uses for researchers, both green and seasoned, applied and theoretical. We name a few ideal use cases. First, `phyddle` allows biologists to design and fit phylogenetic models with no known, tractable inference methods, which increases community-level access to newer models worthy of attention. Second, `phyddle` enables users to rapidly test whether a dataset contains any signal under standard models that have likelihood-based inference methods. A one-day analysis could inform a biologist whether they should spend a year collecting data and/or developing new methods. Third, `phyddle` scales well for repetitive tasks, making it ideal for analyses involving many clades, many genes, and/or assessing model sensitivity to phylogenetic uncertainty. Fourth, `phyddle` can be used to provide baseline estimates when developing new likelihood-based approach with no existing points of comparison to benchmark performance. Lastly, because deep learning in phylogenetics is currently underexplored, `phyddle` allows methods developers to systematically document how various modeling, network architecture, and training conditions influence the effectiveness of deep learning

approaches. We believe these attributes will make `phyddle` a useful addition to the nascent field of phylogenetic deep learning.

Software

`phyddle` is an open source project that is written in Python. It depends on a large number of scientific computing libraries, including: `pytorch` (Paszke et al. 2019), `dendropy` (Sukumaran and Holder 2010), `numpy` (Harris et al. 2020), `scipy` (Virtanen et al. 2020), `scikit-learn` (Pedregosa et al. 2011), `pandas` (pandas development team 2020), `h5py` (Collette 2013), and `matplotlib` (Hunter 2007). Code for `phyddle` is hosted at `https://github.com/mlandis/phyddle`. Documentation and tutorials for `phyddle` are hosted at `https://phyddle.org`. Saved workspace projects for the three examples in this manuscript are hosted at `https://github.com/mlandis/phyddle_ms`.

Funding

MJL was supported by NSF DEB-2040347, NIH FIC R01-TW012704, and the Washington University Incubator for Transdisciplinary Futures. This research was supported in part by an appointment to the Department of Defense (DOD) Research Participation Program administered by the Oak Ridge Institute for Science and Education (ORISE) through an interagency agreement between the U.S. Department of Energy (DOE) and the DOD. ORISE is managed by ORAU under DOE contract number DE-SC0014664. All opinions expressed in this paper are the authors' and do not necessarily reflect the policies and views of NSF, NIH, DOD, DOE, or ORAU/ORISE.

Acknowledgements

We are grateful to Albert Soewongsono, Raymond Castillo, Sean McHugh, Sarah Swiston, Fábio Mendes, Sigournie Brock, Tracy Heath, and Erik Scully for feedback and help testing software.

*

References

H Akaike. Information theory and an extension of the maximum likelihood principle. In *2nd International Symposium on Information Theory*, pages 267–281, 1973.

F. Bokma. Artificial neural networks can learn to estimate extinction rates from molecular phylogenies. *Journal of Theoretical Biology*, 243(3):449–454, 2006.

M. L. Borowiec, R. B. Dikow, P. B. Frandsen, A. McKeeken, G. Valentini, and A. E. White. Deep learning as a tool for ecology and evolution. *Methods in Ecology and Evolution*, 13(8):1640–1660, 2022.

A. Collette. *Python and HDF5: unlocking scientific data*. O'Reilly Media, Inc., 2013.

J. Felsenstein. Confidence limits on phylogenies: An approach using the bootstrap. *Evolution*, 39:783–791, 1985a.

J. Felsenstein. Phylogenies and the comparative method. *The American Naturalist*, 125: 1–15, 1985b.

L. Gavotte and R. Frutos. The stochastic world of emerging viruses. *PNAS Nexus*, 1(4): pgac185, 2022.

I. Goodfellow, Y. Bengio, and A. Courville. *Deep Learning*. MIT Press, 2016.

T. F. Hansen. Stabilizing selection and the comparative analysis of adaptation. *Evolution*, pages 1341–1351, 1997.

T. F. Hansen and E. P. Martins. Translating between microevolutionary process and macroevolutionary patterns: the correlation structure of interspecific data. *Evolution*, pages 1404–1417, 1996.

L. J. Harmon, J. B. Losos, T. Jonathan Davies, R. G. Gillespie, J. L. Gittleman, W. Bryan Jennings, K. H. Kozak, M. A. McPeek, F. Moreno-Roark, T. J. Near, et al. Early bursts of body size and shape evolution are rare in comparative data. *Evolution*, 64(8): 2385–2396, 2010.

C. R. Harris, K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, D. Cournapeau, E. Wieser, J. Taylor, S. Berg, N. J. Smith, R. Kern, M. Picus, S. Hoyer, M. H. van Kerkwijk, M. Brett, A. Haldane, J. F. del Río, M. Wiebe, P. Peterson, P. Gérard-Marchant, K. Sheppard, T. Reddy, W. Weckesser, H. Abbasi, C. Gohlke, and T. E. Oliphant. Array programming with numpy. *Nature*, 585(7825):357–362, 2020.

S. Höhna, M. J. Landis, T. A. Heath, B. Boussau, N. Lartillot, B. R. Moore, J. P. Huelsenbeck, and F. Ronquist. RevBayes: Bayesian phylogenetic inference using graphical models and interactive model-specification language. *Systematic Biology*, 65: 726–736, 2016.

J. D. Hunter. Matplotlib: A 2d graphics environment. *Computing in Science & Engineering*, 9(3):90–95, 2007.

S. A. Kelchner and M. A. Thomas. Model use in phylogenetics: nine key questions. *Trends in Ecology & Evolution*, 22(2):87–94, 2007.

Y. Kong, G. P. Tiley, and C. Solís-Lemus. Unsupervised learning of phylogenetic trees via split-weight embedding. *arXiv preprint arXiv:2312.16074*, 2023.

D. Kühnert, T. Stadler, T. G. Vaughan, and A. J. Drummond. Phylodynamics with migration: a computational framework to quantify population structure from genomic data. *Molecular biology and evolution*, 33(8):2102–2116, 2016.

S. Lambert, J. Voznica, and H. Morlon. Deep learning from phylogenies for diversification analyses. *Systematic Biology*, 72(6):1262–1279, 2023.

M. J. Landis and J. G. Schraiber. Pulsed evolution shaped modern vertebrate body sizes. *Proceedings of the National Academy of Sciences*, 2017. doi: 10.1101/151175. Accepted.

Y. LeCun, Y. Bengio, and G. Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

S. Louca and M. Doebeli. Efficient comparative phylogenetics on large trees. *Bioinformatics*, 34(6):1053–1055, 2018.

W. P. Maddison, P. E. Midford, and S. P. Otto. Estimating a binary character's effect on speciation and extinction. *Systematic Biology*, 56:701–710, 2007.

M. R. May and X. Meyer. TensorPhylo (unreleased), 2024. Accessed: 2024-07-05.

F. K. Mendes and M. J. Landis. Phylojunction: a computational framework for simulating, developing, and teaching evolutionary models. *bioRxiv*, 2023.

Yu K Mo, Matthew W Hahn, and Megan L Smith. Applications of machine learning in phylogenetics. *Molecular Phylogenetics and Evolution*, 196:108066, 2024.

N. Moshiri, M. Ragonnet-Cronin, J. O. Wertheim, and S. Mirarab. Favites: simultaneous simulation of transmission networks, phylogenetic trees and sequences. *Bioinformatics*, 35(11):1852–1861, 2019.

N. F. Müller, G. Dudas, and T. Stadler. Inferring time-dependent migration and coalescence patterns from genetic sequence and predictor data in structured populations. *Virus Evolution*, 5(2):vez030, 2019.

Luca Nesterenko, Luc Blassel, Philippe Veber, Bastien Boussau, and Laurent Jacob. Phyloformer: Fast, accurate and versatile phylogenetic reconstruction with deep neural networks. *bioRxiv*, pages 2024–06, 2024.

The pandas development team. pandas-dev/pandas: Pandas, February 2020. URL https://doi.org/10.5281/zenodo.3509134.

E. Paradis and K. Schliep. ape 5.0: an environment for modern phylogenetics and evolutionary analyses in R. *Bioinformatics*, 35(3):526–528, 2019.

A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Köpf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32, 2019.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

R Core Team. R: A language and environment for statistical computing, 2013.

S. Riley. Large-scale spatial-transmission models of infectious disease. *Science*, 316(5829): 1298–1301, 2007.

N. Rodrigue and H. Philippe. Mechanistic revisions of phenomenological modeling strategies in molecular evolution. *Trends in Genetics*, 26(6):248–252, 2010.

J. Rolland, L. F. Henao-Diaz, M. Doebeli, R. Germain, L. J. Harmon, L. L. Knowles, L. H. Liow, J. E. Mank, A. Machac, S. P. Otto, M. Pennell, N. Salamin, D. Silvestro, M. Sugawara, J. Uyeda, C. E. Wagner, and D. Schluter. Conceptual and empirical bridges between micro-and macroevolution. *Nature Ecology & Evolution*, 7(8):1181–1193, 2023.

Y. Romano, E. Patterson, and E. Candes. Conformalized quantile regression. *Advances in Neural Information Processing Systems*, 32, 2019.

M. R. Servedio, Y. Brandvain, S. Dhole, C. L. Fitzpatrick, E. E. Goldberg, C. A. Stern, J. Van Cleve, and J. D. Yeh. Not just a theory—the utility of mathematical models in evolutionary biology. *PLoS Biology*, 12(12):e1002017, 2014.

V. Shchur, V. Spirin, D. Sirotkin, E. Burovski, N. De Maio, and R. Corbett-Detig. Vgsim: scalable viral genealogy simulator for global pandemic. *PLOS Computational Biology*, 18 (8):e1010409, 2022.

D. Silvestro, T. Latrille, and N. Salamin. Toward a semi-supervised learning approach to phylogenetic estimation. *Systematic Biology*, page syae029, 2024.

M. L. Smith and M. W. Hahn. Phylogenetic inference using generative adversarial networks. *Bioinformatics*, 39(9):btad543, 2023.

T. Stadler and S. Bonhoeffer. Uncovering epidemiological dynamics in heterogeneous host populations using phylogenetic methods. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 368(1614):20120198, 2013.

J. Sukumaran and M. T. Holder. Dendropy: a python library for phylogenetic computing. *Bioinformatics*, 26(12):1569–1571, 2010.

A. Suvorov, J. Hochuli, and D. R. Schrider. Accurate inference of tree topologies from multiple sequence alignments using deep learning. *Systematic Biology*, 69(2):221–233, 2020.

A. Thompson, B. J. Liebeskind, E. J. Scully, and M. J. Landis. Deep learning and likelihood approaches for viral phylogeography converge on the same answers whether the inference model is right or wrong. *Systematic Biology*, 73(1):183–206, 2024.

Guido Van Rossum and Fred L. Drake. *Python 3 Reference Manual*. CreateSpace, Scotts Valley, CA, 2009. ISBN 1441412697.

T. G. Vaughan and A. J. Drummond. A stochastic simulator of birth–death master equations with application to phylodynamics. *Molecular Biology and Evolution*, 30(6): 1480–1493, 2013.

P. Virtanen, R. Gommers, T. E. Oliphant, M. Haberland, T. Reddy, D. Cournapeau, E. Burovski, P. Peterson, W. Weckesser, J. Bright, S. J. van der Walt, M. Brett, J. Wilson, K. J. Millman, N. Mayorov, A. R. J. Nelson, E. Jones, R. Kern, E. Larson, C. J. Carey, I. Polat, Y. Feng, E. W. Moore, J. VanderPlas, D. Laxalde, J. Perktold, R. Cimrman, I. Henriksen, E. A. Quintero, C. R. Harris, A. M. Archibald, A. H. Ribeiro, F. Pedregosa, P. van Mulbregt, and SciPy 1.0 Contributors. SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python. *Nature Methods*, 17:261–272, 2020.

J. Voznica, A. Zhukova, V. Boskova, E. Saulnier, F. Lemoine, M. Moslonka-Lefebvre, and O. Gascuel. Deep learning from phylogenies to uncover the epidemiological dynamics of outbreaks. *Nature Communications*, 13(1):3896, 2022.

P. Xu, S. Liang, A. Hahn, V. Zhao, W. T. Lo, B. C. Haller, B. Sobkowiak, M. H. Chitwood, C. Colijn, T. Cohen, K. Y. Rhee, P. W. Messer, M. T. Wells, A. G. Clark, and J. Kim. e3sim: epidemiological-ecological-evolutionary simulation framework for genomic epidemiology. *bioRxiv*, pages 2024–06, 2024.