1 **Neural basis of concurrent deliberation toward a choice and degree of confidence**

2 Miguel Vivar-Lazo[1] & Christopher R. Fetsch[1,2]

3 [1]Zanvyl Krieger Mind/Brain Institute, [2]Solomon H. Snyder Department of Neuroscience,

4 Johns Hopkins University, Baltimore, MD, USA; correspondence: cfetsch@jhu.edu

5

6 **SUMMARY**

7 Decision confidence plays a key role in flexible behavior, but exactly how and when it arises

8 in the brain remains unclear. Theoretical accounts suggest that confidence can be inferred from

9 the same evidence accumulation process that governs choice and response time (RT), implying

10 that a provisional confidence assessment could be updated in parallel with decision formation. We

11 tested this using a novel RT task in nonhuman primates that measures choice and confidence with

12 a single eye movement on every trial. Monkey behavior was well fit by a 2D bounded accumulator

13 model instantiating parallel processing of evidence, rejecting a serial model in which choice is

14 resolved first followed by post-decision accumulation for confidence. Neural activity in area LIP

15 reflected concurrent accumulation, exhibiting within-trial dynamics consistent with parallel updating

16 at near zero time lag, and significant covariation in choice and confidence signals across the

17 population. The results demonstrate that monkeys concurrently process a single stream of

18 evidence to arrive at a choice and level of confidence, and illuminate a candidate neural

19 mechanism for this ability.

20

21 **INTRODUCTION**

22 Decisions are accompanied by a sense of confidence, defined as the degree of belief that

23 the decision is correct. Confidence facilitates learning in the absence of explicit feedback (Daniel &

24 Pollmann, 2012; Guggenmos et al., 2016) and guides decisions that are part of a sequence or

25 hierarchy (Sarafyazd & Jazayeri, 2019; Purcell & Kiani, 2016; van den Berg et al., 2016b). When

26 feedback does occur, confidence informs whether the outcome is surprising (i.e., a high confidence

27 error), driving an increase in learning rate (Rescorla & Wagner, 1972; Sutton & Barto, 1992).

Indeed, it can be shown that the optimal weights for converting sensory neuron activity to decision

evidence can only be obtained with a learning rule that is proportional to confidence (Drugowitsch

et al., 2019). Even when subjects are well-trained and task contingencies are stable, choice biases

continuously evolve in response to previous outcomes in a difficulty-dependent manner,

suggesting a role for confidence (Lak et al., 2020). These facts imply that confidence is of broad

importance for understanding sensorimotor behavior and learning, yet we still lack a mechanistic

understanding of its neuronal underpinnings. Here we focus on the timing of confidence

computations in relation to the primary decision (Xue et al., 2023; Herregods et al., 2023; Moran et

al., 2015; Pleskac & Busemeyer, 2010), with the goal of uncovering the latent dynamics of choice

and confidence signals in the brain (Murphy et al., 2015; Gherman & Philiastides, 2015; Pereira et

al., 2020; Balsdon et al., 2021; Wang et al., 2023; Dou et al., 2024; Fan et al., 2024). Beyond

informing theories of decision making and learning, this question has implications for the

computational and neural basis of metacognition.

Most existing models fall into one of two main alternatives for the dynamics of choice and

confidence formation. The *serial* hypothesis states that the two computations make use of

temporally nonoverlapping streams of evidence (Herregods et al., 2023; Moran et al., 2015;

Pleskac & Busemeyer, 2010). In contrast, the *parallel* hypothesis proposes simultaneous initiation

and temporally overlapping (concurrent) computation of choice and confidence (Dotan et al., 2018;

van den Berg et al., 2016a; Xue et al., 2023) — though this need not exclude additional post-

decision processing (Desender et al., 2021; Maniscalco et al., 2021; see Discussion). Both

hypotheses have received support from behavioral, modeling, and human EEG data, but to date

there have been no single-neuron or population recording studies that directly address this

question. This is important because discerning between the two strategies could benefit from the

spatial and temporal resolution afforded by single-unit electrophysiology, and because ultimately,

we seek biological mechanism. Also, most tasks include a time delay between decision and

confidence reporting (including the waiting-time assay; Lak et al., 2014; Stolyarova et al., 2019),

potentially biasing participants toward a post-decisional strategy.

We circumvented these issues by training monkeys to report choice and confidence

simultaneously in a response-time (RT) paradigm ('peri-decision wagering', peri-dw), building on

previous work in human participants (Kiani et al., 2014a; van den Berg et al., 2016a). The goal was

not to challenge post-decisional accounts of confidence, as this phase clearly plays a role in many

tasks and natural situations. Rather, our task was designed to unveil whether a serial process is

essential for a monkey's deliberation about both aspects of the decision, or if this process is

fundamentally parallel. The approach facilitated evaluation of competing hypotheses on equal

footing within the framework of bounded evidence accumulation, and to shed light on the

underlying neural mechanism. Notably, the task measures choice, RT, and confidence on every

trial, unlike 'opt-out' or uncertain-response paradigms (Kiani et al., 2009; Smith et al., 2012;

Komura et al., 2013; Fetsch et al., 2014a; Li et al., 2023), allowing us to relate neural activity to all

three measures on a trial-by-trial basis.

While monkeys performed the task, we recorded the activity of ensembles of neurons in the

ventral portion of the lateral intraparietal area, LIPv (Shadlen & Kiani, 2013). Previous work has

shown that LIPv (hereafter LIP) contains a representation of a decision variable (DV) that predicts

choice and RT (Roitman & Shadlen, 2002), as well as confidence in an opt-out task (Kiani &

Shadlen, 2009). Recent work using high-density probes found that the DV representation is

observable on single trials (Steinemann et al., 2024) and thus is not an artifact of averaging

(Latimer et al., 2015). Lastly, although one study failed to observe behavioral effects of LIP

inactivation (Katz et al., 2016), at least four others support a causal role for this area in visuo-motor

decisions (Hanks et al., 2006; Zhou & Freedman, 2019; Chen et al., 2020; Jeurissen et al., 2022).

This makes LIP a sensible target for pursuing a population-level understanding of the dynamics of

choice and confidence formation.

Using a combination of computational modeling and model-free analyses, we first show that

a parallel model can explain all three features of the decision in this task, as suggested by previous

work (Fetsch et al. 2014a; Kiani et al., 2014a). Then, using single-neuron analyses and population

decoding, we show that the DV representation in LIP supports concurrent deliberation toward a

choice and associated wager. This work expands the toolkit for studying confidence in animal

models and supports a role for LIP in decisions guided by an online estimate of confidence.

RESULTS

We recorded 407 neurons in area LIP of two rhesus monkeys (*Macaca mulatta*; 207 in monkey H,

200 in monkey G) while they performed the peri-dw task (Figure 1A). The saccade targets

correspond to a motion direction decision (left or right) and a wager (high or low) on the

correctness of that decision. Although behaviorally the task amounts to a choice among four

options, we refer to the left-right decision as 'choice' and the high-low decision as 'wager' or 'bet',

for simplicity and because the results support this interpretation. Monkeys were rewarded or

penalized based on the conjunction of accuracy and wager (Figure 1B): a larger drop of juice for

high vs. low bets when correct, and a time penalty for high bets when incorrect (no penalty for a

low-bet error). As in previous studies (e.g., Roitman & Shadlen, 2002), monkeys showed greater

accuracy (Figure 1B, left) and faster RTs (Figure 1B, middle) when the motion was strong

compared to weak (coh near 0%). Motion strength also influenced wagering behavior in the

expected manner, namely the probability of betting high increased with greater motion strength in

either direction (Figure 1B, right). Importantly, the behavior shows that the low-bet option did not

correspond to opting out of the motion decision: accuracy remained high on low-bet trials, and

choice and RT still varied systematically with motion strength in a manner consistent with a

deliberative process (see Model Fitting section below).

Figure 1. Task, behavioral performance, and model schematics. (A) After the monkey acquired fixation, four targets were presented, followed by a random-dot motion stimulus. At any time after stimulus onset the monkey could make a saccade to one of the targets to signal its choice and wager. The table at the right illustrates the possible outcomes for each trial: if correct, a high bet yielded a larger juice reward compared to a low bet, but if incorrect, a high bet incurred a 2-3 s time penalty assessed on the following trial's pre-stimulus fixation period. Low-bet errors were not penalized. (B) Performance on the peri-dw task pooled across two monkeys (N = 216 sessions, 202,689 trials, including sessions without neural recording). Each behavioral variable is plotted as a function of signed motion strength (%coh, negative=leftward, positive=rightward). Choice (proportion rightward) and RT functions are shown conditioned on wager (low=red, high=blue). Error bars (SE) are smaller than the data points. Smooth curves show logistic regression (choice) and Gaussian (RT) descriptive fits. (C) The serial model begins with a single accumulator with symmetric bounds (standard 1D drift-diffusion model). Arriving at one of the bounds terminates the primary decision (h_1 vs. h_2 = left vs. right in our task) and initiates a secondary process that accumulates evidence toward a 'high' or 'low' bound governing the wager. Crossing either of these bounds terminates the entire decision process and initiates the corresponding response. (D, left) The parallel model comprises two concurrent accumulators that are partially anti-correlated, allowing for variability across trials in the amount of evidence favoring the unchosen option. The first bound to be crossed (the 'winner') dictates the choice and decision time, whereas the losing accumulator dictates confidence by way of a mapping (right) between accumulated evidence and the log odds that the choice made was the correct one (color scale). Importantly, the mapping takes into consideration not only the amount of evidence but also the elapsed time.

Crucially for a behavioral assay of confidence, the monkeys' sensitivity was greater when betting high versus low (Figure 1B left, red vs. blue; $p<10^{-258}$, logistic regression). This was true even when controlling for variability in motion energy within each coherence level, by leveraging multiple repeats of the same random seed (Figure S1A; monkey H: $p<10^{-4}$, monkey G: $p<10^{-6}$; see Methods). Additionally, we fit a session-by-session logistic model separately for high and low bet trials, providing two distributions of weights relating motion strength to choice, and found that they were significantly different (Figure S2A; monkey H: $p<10^{-19}$, monkey G: $p<10^{-37}$). Both monkeys also showed faster RTs when betting high versus low, for all but the largest motion strengths (Figure 1B middle, red vs. blue; asterisks indicate $p<0.0045$ by t-test, Bonferroni corrected). Similarly to choices, we fit a Gaussian function to the average RT as a function of motion strength for each session, separately for high and low bet trials. The amplitude parameters of the fitted Gaussians were greater for low vs. high bets (Figure S2B; monkey H: $p<10^{-7}$, monkey G: $p<10^{-25}$, paired t-test), indicating greater modulation of RT by motion strength when the monkey indicated low confidence. Lastly, we examined wagering behavior as a function of RT (Figure 1B right), separately for each individual motion strength (Figure S3A,B). For most motion strengths, the monkeys bet high less often for longer RTs (Figure S3B; $p<.0085$ for both monkeys for every coherence except 51.2%, Cochran-Armitage trend test with Bonferroni correction). This pattern is remarkably similar to that observed in humans on a similar task (Kiani et al., 2014a), where the results argued that confidence depends on both evidence strength and elapsed time. As in that previous study, the pattern remained significant when controlling for variability in motion energy across trials of a given coherence (Figure S3D; monkey H: $p=0.0003$, monkey G: $p=0.0056$, interaction term between motion energy and RT quintile using ANCOVA).

An inverse relationship between response time and confidence is a classic psychophysical result (Henmon, 1911; Kellogg, 1931; Audley, 1960), replicated in more recent human work (e.g. Kiani et al., 2014a; Desender et al., 2021; Dou et al., 2024). Observing it in monkeys, for the first time to our knowledge, supports the notion that the peri-dw assay is a valid measure of confidence, and it is consistent with a family of accumulator models as addressed below. Note that we

sometimes refer to the wager (or proportion of trials with a high bet) as 'confidence' for simplicity,

acknowledging that confidence is a latent cognitive variable and any behavioral measure is bound

to be imperfect.

Model-free analyses of behavior suggest temporally overlapping choice and

confidence computations

Although the choice and wager were indicated with a single eye movement, this does not

necessitate simultaneity in the processing of evidence. Different temporal windows of the stimulus

could covertly be used to support the two elements of the decision, which would then only be

reported when both were resolved. To test whether monkeys use a consistent serial strategy

(resolving choice first and then confidence, or vice versa) we calculated the influence of stimulus

fluctuations on choice and confidence as a function of time (psychophysical kernels; Kiani et al.,

2008; Nienborg & Cumming, 2009; Zylberberg et al., 2012). Briefly, we quantified the motion

energy for each trial and video frame by convolving the random-dot pattern with two pairs of

spatiotemporal filters aligned to leftward and rightward motion (Adelson & Bergen, 1985). We then

partitioned trials by outcome (choice and wager) and plotted the average relative motion energy

(residuals) for each outcome as a function of time.

Psychophysical kernels for choice are plotted in Figure 2A. Rightward choices were

preceded by more rightward motion energy throughout most of the trial (red line), and the same

was true for leftward choices and leftward motion (blue). The kernels for right and left choice began

to separate about 100 ms after motion onset and remained so until ~100 ms before saccade

initiation. This clear separation, aligned on both motion onset and saccade, suggests that the

monkeys used essentially the entire stimulus epoch to decide motion direction. For confidence, we

calculated the kernels by taking the difference between the motion energy time series for high and

low bets associated with a specific choice (van den Berg, 2016a). For high minus low wager on

rightward choice trials, motion energy

Figure 2. Psychophysical kernels and changes-of-mind for choice and wager. (A) Motion energy profiles conditioned on right and left choices (red and blue, respectively), aligned to motion onset and saccade onset. Shaded regions indicate SEM. Left column is for monkey H and the right for monkey G. Black line at top indicates when right and left traces were significantly different from each other (p<0.05, t-test with Šidák Correction for 140 frames). (B) Confidence kernels computed as the difference in motion energy between right-high and right-low choices (green), and the difference between left-high and left-low choices (purple), aligned to the same events as (A). Colored lines at top of graph indicate when the corresponding traces were significantly different from zero (p<0.05, t-test with Šidák correction).

values were above zero, indicating an excess of rightward motion on high-bet choices compared to

low-bet choices (Figure 2B, green). Similarly, for left choice trials the difference in motion energy

was below zero, indicating more leftward motion on high vs. low bets (Figure 2B, purple). This

analysis shows that both early and late motion evidence is leveraged to inform confidence, for both

monkeys. Comparison of the traces in Figure 2A vs. 2B might suggest that the utilization of the

stimulus for confidence does not identically overlap with choice, especially for monkey H. However,

the substantial overlap does appear to rule out a consistent temporal segregation, such as an

obligatory post-decision mechanism for confidence. Of course, psychophysical kernels rely on trial

averages and cannot resolve dynamics of individual decisions; we partly address this shortcoming

below using neural recordings.

When decisions are reported with an arm movement (Resulaj et al., 2009; van den Berg et

al., 2016a), human subjects occasionally alter their reach trajectory in a manner that suggests a

'change of mind' (CoM) based on continued processing of evidence after movement initiation.

Saccadic choices are generally considered incompatible with CoMs because of their speed and

ballistic nature (Resulaj et al., 2009; but see McPeek et al., 2000; Caspi et al., 2004), but we were

nevertheless able to identify a small subset of trials with multiple saccades in quick succession that

revealed putative CoMs (see Methods). These trials showed characteristic features of CoMs

(Figure 2C-E), including greater frequency on difficult vs. easy trials (Figure 2E; monkey H: p =

0.0076; monkey G: $p<10^{-6}$, Cochran-Armitage test). Changes from incorrect to correct were more

likely when motion strength was high (Figure 2C red line; monkey H: p < 0.0001; monkey G: p <

10^{-5}), whereas correct-to-error CoMs, occurring sparingly, were more likely when motion strength

was low (Figure 2C, dark red line; monkey H: p < 0.0012 monkey G: $p < 10^{-5}$). We also observed

changes from low to high confidence, which for one monkey were more frequent with greater

motion strength (Figure 2D blue line; monkey H: $p < 10^{-60}$ monkey G: p = 0.944), as shown

previously in humans (van den Berg et al., 2016a). The presence of CoMs and changes of

confidence (sometimes both on the same trial) suggests that both dimensions of the decision were

subject to revision at the time of the initial saccade. This argues against a strictly serial process,

although it also highlights a potential window of post-decisional processing, even for saccadic

decisions (McPeek et al., 2000; Caspi et al., 2004).

Model fitting favors parallel deliberation for choice and confidence

Previous studies have typically focused on either a serial (Pleskac & Busemeyer, 2010;

Moran et al., 2015) or a parallel (Vickers, 1979; Shadlen & Kiani, 2013) framework for confidence.

Thus, explicit comparisons of these models have generally been qualitative because of variations

in task design across studies (but see Shekhar & Rahnev, 2024 for a comprehensive evaluation).

Here we provide a quantitative comparison of the two classes of model applied to the same data

from the peri-dw task. Our exemplar of the serial strategy is a one-dimensional drift-diffusion model

(DDM) with post-decision accumulation for confidence (Moran et al., 2015; Herregods et al., 2023;

Figure 1C). The choice is determined by which of two primary decision boundaries is crossed, and

the wager by a second set of bounds symmetric around the primary (winning) bound. The

observed RT is the sum of the time taken to reach both bounds, plus non-decision time. Our

implementation of a parallel strategy is a two-dimensional DDM, where a common accumulation

epoch governs both choice and confidence (Kiani et al., 2014a; van den Berg et al., 2016; Figure

2B). Here there are two accumulators integrating evidence in support of the two alternatives,

equivalent to an anticorrelated race. Two accumulators are necessary because the winning

accumulator determines the choice and RT while the losing accumulator is leveraged to compute

confidence. In contrast, the serial model uses two separate epochs of accumulation to inform

choice and confidence, and therefore requires only a single accumulator. Note that the key

distinction is serial vs. parallel, not 1D vs. 2D; we simply chose these as exemplars based on the

leading candidates in the literature.

Figure 3. Comparison of serial and parallel model fits. The left two columns show results from monkey H and the right two columns monkey G. Within these two columns the left column shows fits to the serial model and the right column the parallel model. (A) Proportion of rightward choices as a function of motion strength (% coh), conditioned on high and low bet trials (red and blue, respectively). The solid dots are empirical data points and solid lines are model fits. (B) Similar to (A) but for mean reaction time. (C) Proportion of high bets as a function of motion strength (% coh), conditioned on correct and error trials (magenta and green, respectively). The fitting procedure used for these panels differs from the previous ones. They are fitted using only correct trials, and the green traces illustrate the resulting prediction for error trials.

The curves in Figure 3 and Figure S4 are fits to the serial (A and C) and parallel models (B

and D) for the two monkeys. Both models capture the general trends in choice, RT, and wager

across motion strengths, at least when pooled across correct/incorrect and high/low wager trials

(Figure S4), and both qualitatively predict greater sensitivity and faster RTs for high vs. low wager.

However, in monkey G the serial model was unable to capture the large difference in reaction time

between high and low bet trials (Figure 3C, middle). The more subtle RT difference in monkey H

was well handled by the serial model (Figure 3A, middle), but this came at the cost of a slightly

poorer fit to the wager-conditioned choice data (Figure 3A vs. B, top). Thus, the behavioral

differences between the two animals served to highlight complementary strengths of the parallel

model: its ability to explain a broader range of confidence-RT relationships while also tolerating a

more subtle increase in sensitivity on high vs. low-bet trials. Quantitative Model comparison

supported these observations: Bayesian information criterion (BIC) was lower for the parallel vs.

the serial model (monkey H: 8.24×10^5 (parallel) < 8.79×10^5 (serial), monkey G: 1.21×10^6 (parallel) <

1.30×10^6 (serial)).

More strikingly, the serial model failed qualitatively to reproduce the confidence pattern on

error trials (Figure 3, bottom row). In general, confidence increases as a function of stimulus

strength for correct choices—which makes intuitive sense—but empirically it often *decreases* with

stimulus strength on incorrect trials. This characteristic 'X-shape' pattern has been proposed as a

statistical signature of confidence in behavior (Sanders et al., 2016) and brain activity (Kepecs et

al., 2008; Rolls et al., 2010; Komura et al., 2013; Bang et al., 2020). In contrast, we (Figure 3,

bottom row) and others (Kiani et al., 2014a; van den Berg et al., 2016a) observed that confidence

increases with motion strength even for errors. As noted previously (Kiani et al., 2014a; Fetsch et

al., 2014b; Desender et al., 2021; Khalvati et al., 2021), these conflicting findings can be explained

by the relative timing of choice vs. confidence. Resolving choice first followed by confidence later

allows for revision of the confidence judgment upon further deliberation. Incorrect choices when the

stimulus was strong are more likely to undergo such revision, as further processing reveals that the

initial choice was incorrect. However, when choice and confidence are reported simultaneously

there is little or no time for revision, and thus confidence on error trials either increases or remains

flat as a function of stimulus strength (Kiani et al., 2014a; van den Berg, 2016a, Desender et al.,

2021). For this reason, the serial model tested here simply cannot reproduce the error-trial

confidence pattern we observed empirically (note that the green curves in Figure 3, bottom, are a

prediction, not a fit). In summary, although basic behavioral patterns are reasonably well predicted

by the serial model, model comparison favors a process where evidence is accumulated in parallel

for constructing a decision and associated level of confidence.

LIP neurons show signatures of concurrent accumulation

Putative DV representations have been observed in several subcortical and cortical areas,

including LIP (Shadlen & Kiani, 2013), as well as in aggregate signals observable with noninvasive

methods in humans (O'Connell & Kelly, 2021). Although the widespread 'ramping' pattern of

activity does not uniquely identify a process of evidence accumulation, a large body of work

supports the assertion that LIP activity reflects such a process during the random-dot motion task.

We reasoned that, if choice and confidence were resolved concurrently during motion viewing

(parallel model), the ramping activity should begin to predict both dimensions of the eventual

saccade at the same time, classically around 200 ms after motion onset (Roitman & Shadlen,

2002). Alternatively, if choice were to be deliberated first followed by confidence later (serial

model), this temporal separation should be evident in the divergence point of neural activity traces

conditioned on the four outcomes.

These traces are shown in Figure 4A for four example neurons. The highest firing rate

corresponds to choices made into the response field (RF) of the neuron, which was almost always

in the left (contralateral) hemifield but was equally likely to overlap the high or low wager target.

The relative ordering of the remaining three traces differs across neurons, possibly due to

idiosyncratic RF properties or nonspatial choice or confidence signals. The key observation is that

the activity preceding saccades to the preferred wager target (low or high) diverges from the

activity for the other wager target (high or low) at about the same time as it diverges from the

traces for ipsilateral choice (right-low and right-high). This pattern is present in each example

neuron as well as in the population averages (Figure 4B,C). There is no evidence that ramping

activity consistently predicts the left-right choice prior to the high-low one (or vice versa), as

expected under a serial model. Instead, to the extent the activity reflects accumulation of evidence

favoring the target in the RF (see below and Discussion), the results support a model in which such

accumulation underlies concurrent deliberation toward a choice and confidence judgment.

To dig deeper into the nature of the observed ramping signals, we tested for statistical

signatures of a noisy accumulation process (Churchland et al., 2011; de Lafuente et al., 2015;

Figure 4. Temporal properties of neural activity in LIP during the peri-dw task. (A) Firing rate of example units split by choice/wager outcome, aligned to motion onset and saccade onset. (B) Population average firing rate (normalized) for neurons with an RF overlapping the left-low target. Colored bars at top indicate when the corresponding trace is significantly below the trace for choices into the RF. (C) Same as B but for left-high neurons. Only low-coherence trials (0, +/- 3.2%, +/- 6.4%) are included in A-C. (D) Theoretical autocorrelation matrix of a standard ideal accumulation process (left) and a delayed accumulator (right; see Methods). (E) Projection of theoretical autocorrelations for top row (gray dotted) and first juxtadiagonal (gray solid) along with the corresponding data after fitting the phi parameter (Methods). Red and blue represent the two populations shown in B,C, pooled data from both monkeys.

Shushruth et al., 2018; Steinemann et al., 2024): increasing variance of the latent rate as a

function of time (variance of conditional expectation, VarCE) and a characteristic autocorrelation

pattern in this latent signal (correlation of conditional expectation, CorCE). These signatures follow

from considering neuronal spiking as a doubly stochastic process described by a Poisson

distribution with an underlying rate that varies within and across trials. For stochastic bounded

accumulation, VarCE should increase linearly with time during deliberation, then decrease near the

saccade as the bound is reached. Second, correlations between firing rates at adjacent time points

(t and t+1) should increase for pairs of bins further out in time from stimulus onset (t+n and t+n+1,

as n increases). Third, the correlation between two time points should decrease as the distance

between them increases (t and t+1 versus t and t+5; Figure 4D, left & Figure 4E, left).

The results supported all three predictions. After 200 ms following motion onset, VarCE

shows a roughly linear increase for at least the next 400 ms (Figure S5, left; left-high neurons,

monkey H: $p < 10^{-7}$, monkey G: $p < 10^{-13}$; left-low neurons, monkey H: $p < 10^{-19}$, monkey G: $p =$

0.0014; linear regression), then decreases near saccade initiation (Figure S5, right; left-high

neurons, monkey H: $p = 0.015$, monkey G: $p = 0.0016$; left-low neurons, monkey H: $p < 10^{-4}$,

monkey G: $p < 10^{-7}$). For CorCE, the results from both monkeys were reasonably well matched to

the predictions (Figure 4E, left; monkey G: $R^2 = 0.74$ and 0.79 for left-high and left-low neurons,

respectively; monkey H: $R^2 = 0.69$ and 0.79, respectively).

These dynamics in variance and autocorrelation are consistent with an underlying neuronal

process that reflects accumulation, and are not easily explained by alternative accounts of LIP

ramping activity such as a gradual shift of attention or simple movement preparation. Critically, the

patterns were present over the same time window in both the high- and low-preferring populations.

This argues against a form of the serial model in which choice is initially resolved by considering

only one pair of targets, followed by a shift to the other pair after some time has elapsed. We

explicitly tested this by computing the expected autocorrelation under a simulated process where

integration is delayed by a random amount of time. Fitting such a model to the data generated a

qualitative and significant mismatch with the CorCE prediction (Figure 4D, right & Figure 4E, right;

monkey H: $p < 0.008$ for both populations, monkey G: $p < 0.012$ for both populations). Taken

together, the results favor a parallel model in which deliberation occurs simultaneously between

both the high and low pairs of targets. What remains to be tested is whether and when these

accumulation signals are predictive of the monkey's choice and wager on individual trials.

Single-trial decoding supports a link between choice and confidence signals

Thus far most of our analyses have relied on trial averages, potentially obscuring the dynamics of individual decisions. We therefore turned to a population decoding approach (Kiani et al., 2014b; Kaufman et al., 2015; Peixoto et al., 2021; Steinemann et al., 2024), leveraging the simultaneous recording of neural ensembles to more directly address the question of parallel vs. serial deliberation. We trained two logistic classifiers, one for the binary choice and another for the binary wager, using the spike counts from the neurons recorded during each session (mean = 14 units/session). The analysis determines the linear weight for each neuron that maximizes the probability of predicting the observed choice or wager (Methods). We can then extract a 'model decision variable' which is simply the log odds of a particular choice or wager, according to the decoder, based on the population spike counts up to time t on a given trial (Kiani et al., 2014b; Peixoto et al., 2021). This quantity is also known as prediction strength or certainty. To facilitate comparison of the two decoders, we collapsed across choices such that positive values of the model DV correspond to correct prediction of the choice, rather than exhibiting symmetry around zero as in previous work.

For both monkeys, the model DV ramped up starting about 200 ms after motion onset (Figure 5A), as shown previously. The DV dynamics differed for the two animals, but both exhibited a ramping slope that depended on motion strength (monkey H: $p < 0.001$, monkey G: $p < 10^{-4}$, linear regression). Cross-validated prediction accuracy also ramped up starting at this time, and critically, did so simultaneously for both the choice and confidence decoders (Figure 5B). Horizontal bars at the top of the plot indicate significant differences from chance level, which occurred for both decoders starting around 200 ms and persisted until saccade onset. At their peaks, both performed well above chance on the test set (Figure 5B), but a notable difference is the timing of the peaks, which for choice is just before saccade onset and for wager is slightly after the saccade (Figure 5B, right). The black bar in Figure 5B indicates a period near the saccade with

327　a significant difference in prediction accuracy between the decoders, highlighting an epoch where

328　choice accuracy peaks but wager accuracy continues to increase.

Figure 5. Population decoders support concurrent readout of choice and wager from a unimodal population.
(A) Log odds ('model decision variable') quantifying prediction strength ('certainty') for the choice decoder as a function of time, aligned on motion onset and conditioned on motion strength. Left graph is monkey H and the right graph is monkey G. (B) Prediction accuracy (proportion correct binary classification in the test set), for both the choice (gray) and wager (brown) decoders, as a function of time and aligned to motion onset and saccade onset. Shaded regions around the traces indicate SEM. Gray and brown bars at top indicate when accuracy for the corresponding decoder was significantly greater than chance. Black bar indicates when prediction accuracy was significantly different for choice vs. wager. (C) Log odds for both choice and wager decoders as a function of time and aligned to motion onset and saccade onset. Line color, error shading, and significance bars are similar to 5B. (D) Correlation between the magnitude of choice and wager weights (red line) compared to the value expected by chance (shuffled data). (E) Histogram of the difference between choice and wager decoder weights.

We next confirmed that this temporal offset is not simply a product of the binary

classification method but also reflects graded prediction strength (log odds or model DV). The log

odds for both choice and wager were significantly different from chance after 200 ms and persisted

until saccade onset (Figure 5C). As with prediction accuracy, the initial peak for choice is near

saccade onset while the peak for the wager occurs about 100 ms after the saccade. We speculate

that this late peak may be related to continued evaluation of evidence for a possible CoM (see

below), although we cannot exclude the possibility of a signal related to expectation of outcome

(reward or penalty).

The results in Figure 5B and 5C offer clear support for parallel deliberation of choice and

wager, refuting a temporal bottleneck associated with a serial strategy. However, a different form of

bottleneck might exist within the population of neurons that manifests as distinct subsets of

neurons supporting choice and wager. The fitted decoder weights used to predict choice and

wager serve as tools for addressing this question. To summarize the relationship between the

choice and wager weights we converted them to an absolute magnitude and performed a

Pearson's correlation (Figure 5D) and a difference test (Figure 5E). For both analyses the weight

time series were marginalized over the accumulation period (Methods). The correlation across the

population was modest (monkey H: $r = 0.18$ & monkey G: $r = 0.21$) but highly significant by

permutation test ($p \ll 0.05$ for both monkeys). Additionally, the distribution of weight differences

was unimodal (Figure 5E, Hartigan's dip test, $p > 0.9$ for both monkeys individually), suggesting a

continuum of contributions to choice and confidence across the population and not two distinct

subpopulations contributing to one or the other.

As mentioned, one way to describe the model DV is as a graded level of certainty (Kiani et

al., 2014b) or even "confidence" (Peixoto et al., 2019) in the prediction of behavior by neural

activity. Although these are just labels (see also Pouget et al., 2016), we wondered whether the

level of certainty of the choice decoder might predict the binary classification by the wager decoder

on a trial-by-trial basis. To test this, we partitioned trials according to whether they were classified

as high or low bets by the wager decoder, by calculating the mean P(High) for the wager decoder

in the period immediately surrounding the saccade. Values above (below) 0.5 indicated a decoded-

high (decoded-low) wager. We then averaged the model DV from the choice decoder, using only

0% coherence trials, and found that it was higher for decoded-high vs. decoded-low trials (Figure

6A). This indicates that the strength with which LIP predicts the upcoming choice covaries with the

degree to which the same population predicts a high bet, consistent with a tight link between

choice and confidence signals. This is surprising given that the spatial/motor dimensions for choice

and wager are orthogonal.

Figure 6. Predictive relationship between choice and wager decoders. (A) Log odds of choice decoder as a function of time, aligned to saccade onset. Red and purple lines are trials separated by whether the wager decoder predicted a high or low bet. Shaded regions are SEM. Black bar at top indicates a significant difference between the traces. (B) Corrected R^2 values from a linear regression relating trial-by-trial transformed choice decoding strength and wager decoder probability (P(High)), as a function of time lag. The blue, red, and purple traces comprise different time windows either aligned to motion onset (MO) or saccade onset (SO). Standard error bars are included as shaded regions near the lines (barely visible). Negative values on the x-axis indicate wager decoder values were regressed with choice decoder values that were x seconds in the past, and vice versa for positive values.

With the established link between decoded choice certainty and wager prediction, we can

now reexamine the temporal differences shown in Figure 5B & 5C, specifically by asking when

choice decoding strength best predicts the wager decoder's probability of a high bet on a given

trial. We fit a linear regression relating choice decoder strength (Methods) at time t to decoded

wager probability at time $t + \Delta t$, where Δt ranges from +/- 200 ms. We found that, during the

deliberation phase (200-600 ms after motion onset and 400-0 ms before saccade onset) the best

prediction between choice strength and wager probability was at zero time lag (Figure 6B, R^2 = .13

& .21 blue and red lines, respectively). Interestingly, the period centered around the saccade gave

rise to two peaks, one at zero lag ($R^2 = 0.12$) and one at a lag of -0.2 s (wager lagging behind

choice; $R^2 = 0.125$). This suggests that the updating of the confidence signal around the decision

time instead reflects a procrastinated element (perhaps evidence, or a bias signal) that was

integrated into the decision variable earlier in time.

DISCUSSION

The neural mechanisms underlying metacognition have become tantalizingly more

accessible over the past two decades through the development of behavioral assays of confidence

in nonhuman animals (Hampton, 2001; Kiani et al., 2009; Middlebrooks & Sommer, 2011; Smith et

al., 2012; Kepecs & Mainen, 2012). A longstanding goal is to connect the rich psychological

literature on process models for confidence with their implementation at the level of neural

populations and circuits. One approach considers how decision accuracy, speed, and confidence

can be jointly explained within the framework of bounded evidence accumulation (Kiani & Shadlen,

2009; Pleskac & Busemeyer, 2010; Fetsch et al., 2014b), an idea presaged by Vickers' balance-of-

evidence hypothesis (Vickers, 1979). Such a framework is motivated by the critical role of response

time in psychophysical theory and experiment (Luce, 1986) and its strong empirical link to

confidence going back at least a century.

Yet embracing a dynamic model still leaves open questions about the temporal evolution of

choice and confidence in the brain. Several authors have emphasized post-decisional processing

(Baranski & Petrusic, 1998), formalized by serial models in which evidence is integrated for

confidence only after termination of the primary decision (Pleskac & Busemeyer, 2010; Moran et

al., 2015; Herregods et al., 2023). This idea follows naturally from the definition of confidence as

the expected probability correct conditioned on a choice (Pouget et al., 2016), and it is sensible to

exploit additional information acquired (or generated internally) after commitment to the choice if

the behavioral context allows it. However, in many other settings it would seem advantageous to

compute a provisional degree of confidence while the decision is still being formed. Decisions are

commonly expressed as motor actions, executed with a degree of vigor (or caution) that depends

on confidence or expected reward (Shadmehr et al., 2019). Also, deliberation itself is a significant

cost (Drugowitsch et al., 2012), so it could be less efficient to extend the deliberation period for

confidence. Lastly, an online prediction of accuracy facilitates rapid decision sequences (van den

Berg et al., 2016b; Lisi et al., 2020; Zylberberg, 2021) and strategic modulations of the decision

process (Balsdon et al., 2020). Recent human studies (Dotan et al., 2018; Balsdon et al., 2020; Li

et al., 2023) offer intriguing evidence for parallel computation of confidence (or at least *certainty*;

Pouget et al., 2016) during decision formation, further supported by electroencephalography

(Gherman & Philiastides, 2015; Balsdon et al., 2021; Dou et al., 2024) and transcranial magnetic

stimulation (Xue et al., 2023). How this might be implemented at the level of neuronal populations

remains unclear and requires a suitable paradigm for nonhuman animals. Here we establish such

a paradigm and provide evidence that monkeys (and LIP neurons) can accumulate samples of

evidence concurrently to guide a single motor action corresponding to a choice and degree of

confidence therein.

Behavioral evidence for concurrent deliberation

First we validated the peri-decision wager as a measure of confidence *per se*, which should covary

with accuracy even when conditioned on the stimulus. If a behavioral report only predicts accuracy

across levels of stimulus strength or difficulty, it could reflect an associative process of

categorization (Smith et al., 2012), or more subtly, an estimate of difficulty itself (Löffler et al.,

2023). We sought to allay these concerns by including a set of identical-seed trials, in which the

random dot movie was identical up to the initiation of the saccade. Controlling for stimulus motion,

the accuracy for high bets was still significantly higher than for low bets, for both monkeys (Figure

S1A). This suggests that the wager reflects, in part, variability in the internal representation of

evidence and/or the reliability of the decision process, including aspects that could fall under the

rubric of attention.

Psychophysical kernels indicated substantial overlap in the stimulus period contributing to

choice and wager, as shown previously in humans (Zylberberg et al., 2012; van den Berg et al.,

2016a), ruling out a strategy where confidence is systematically assessed after (or before) choice

formation. Additionally, a small subset of trials showed evidence for changes of mind (CoMs):

perhaps surprisingly for a saccade task, the monkeys occasionally reversed their initial wager,

choice, or both, implying that both were amenable to revision at the time of initial commitment.

These two lines of evidence suggest that deliberation for choice and confidence occurs in

overlapping time windows, even extending after the stimulus has been extinguished.

Corroboration of a parallel strategy was provided by the superior fits and predictions from

our parallel model compared to the serial model (Figure 3). We then used the model fits to make

predictions for the probability of betting high when a trial outcome is correct vs. incorrect. This

aspect of the behavior strongly argued against the serial strategy, which invariably predicts an 'X-

shape' pattern (decreasing confidence with greater evidence strength on error trials) that was

absent in our data. We did not explicitly test a hybrid model where parallel accumulation is followed

by a period of extra accumulation for confidence (Desender et al., 2021; Maniscalco et al., 2021),

but this too predicts an X-shape, depending on the duration of the second epoch (Desender et al.,

2021). Other behavioral evidence (Kiani et al., 2014a) and model simulations (Khalvati et al., 2021)

similarly appeal to the temporal domain to explain the X-shape, contrary to the conventional

explanation based on signal-detection theory (SDT; Treisman & Faulkner, 1984; Kepecs et al.,

2008) or more general Bayesian formulations (Sanders et al., 2016; Adler & Ma, 2018). The

distinction matters because neural correlates of the X-shape are considered diagnostic of

confidence signals in the brain (Kepecs et al., 2008; Rolls et al., 2010; Komura et al., 2013; Bang

et al., 2020), which could be misleading if the relative timing of choice and confidence

computations are unknown. In general, however, the temporal explanation does not invalidate SDT

as a useful framework, nor its extension to an estimate of decision reliability ('meta-uncertainty';

Boundy-Singer et al., 2022). In fact an exciting future direction would be to link the neural

signatures of meta-uncertainty computations in visual cortex (Boundy-Singer et al., 2024b) to the

temporal dynamics of confidence formation in decision-related areas.

Neural correlates of concurrent deliberation

Individual LIP neurons showed heterogeneous dynamics (Figure 4A), but when combined into

populations with RFs overlapping either the left high or left low target, the averages revealed

accumulation-like responses with interpretable timing relationships for the four outcomes. In

essence, the ramping activity began to predict the wager at about the same time that it began to

predict the left-right decision. Using a theoretical and simulated autocorrelation structure for a

standard and delayed drift diffusion process, we found that both populations show the statistical

signatures of accumulation (VarCE and CorCE) from 200 ms after motion onset, inconsistent with

one form of serial strategy in which the decision process first considers only the low or high pair of

targets then covertly switches to the other pair. Note that previous studies examined these

signatures on simple 2-choice paradigms, so it was unclear whether LIP neurons in our 4-target

task would conform to the same theoretical autocorrelation structure. It will be useful to generate

specific predictions for the variance and autocorrelation of neural signals in more complex

paradigms, including multi-alternative (Churchland et al., 2008) and multi-attribute perceptual and

economic decisions (Kang et al., 2021; Sampson et al., 2023).

To uncover latent decision and confidence signals on individual trials, we constructed

logistic classifiers for choice and wager based on the neural population activity. As shown

previously, the choice decoder displayed a graded prediction (the 'model DV') that was linearly

dependent on coherence, reminiscent of classic LIP ramping activity (Roitman & Shadlen, 2002;

Steinemann et al., 2024). Notably, the population signal was predictive of choice and wager during

identical epochs (Figure 5B & C), consistent with a parallel process. An interesting anomaly was

the temporal offset between choice and confidence decoders at the end of the trial (Figure 5B,C).

This offset was not driven by a lag between the trial-by-trial predictions during decision formation,

but such a lag did emerge around saccade onset (Figure 6B). This could be a correlate of top-

down signals related to attention, expectation, or affect—but another possibility is that it reflects

reevaluation of the evidence for guiding subsequent decisions (van den Berg et al., 2016b; Lak et

al., 2020 Zylberberg, 2021). One could test this by manipulating neural activity during the peri-

decision epoch in a task where optimal behavior depends on confidence in earlier choices. Lastly,

we found that the strength of the decoder's choice prediction ('certainty') was highly correlated with

the probability of a high bet established by the wager decoder (Figure 6A). To our knowledge this

is the first study to directly link a neural representation of choice certainty with a neural prediction

of confidence as measured behaviorally.

Caveats and conclusions

The main limitation of this study is that confidence is mapped onto a stable motor action, namely

the saccade to a high or low target whose positions did not change within a session. We found this

to be necessary for achieving consistent behavioral performance, but it does present a challenge

for disentangling cognitive signals from those involved in motor planning. Could our results be

explained as merely the concurrent evolution of multiple motor plans? We do not think so. First, the

signatures of noisy evidence accumulation (Figure 4E, Figure 5A) suggest that ramping activity in

LIP reflects more than simple motor planning. Second, although there is evidence for parallel

computation of competing plans (Cisek & Kalaska, 2002), even a motor-centric interpretation of our

findings would be something different: simultaneous encoding of two dimensions of a motor plan

(horizontal and vertical), corresponding to distinct transformations of the input (a categorical

judgment vs. the quality of the evidence and/or decision process). It was not a foregone conclusion

that the choice and wager dimensions could be computed in parallel; in fact, a 2-D decision with

similar task structure (simultaneous report of color and motion) exposed a bottleneck preventing

parallel incorporation of multiple evidence streams into a single DV (Kang et al., 2021; Jeurissen,

Zylberberg, & Shadlen, unpublished observations).

Importantly, the current findings are not incompatible with post-decision processing for

confidence. Indeed, even though the peri-decision time window is highly compressed in our task,

there are hints of continued processing related to confidence and potential CoMs (Figure 2C;

Figure 5B). Investigating this window further could be useful for testing mechanisms of confidence

readout, which for a 2D accumulator requires querying the state of the losing race as well as

estimating elapsed time (Kiani et al., 2014a). The contributions to this readout mechanism from

sensory populations versus top-down signals remain to be teased apart. Simultaneous recordings

across multiple brain areas will be essential for resolving this question, bringing us closer to

understanding how neural dynamics convert sensation into belief.

Acknowledgements

We thank members of the lab for their insight and discussions. Additionally, we are grateful to
Ofelia Garalde for helping with animal assistance, and Justin Killebrew, Bill Nash, and Bill Quinlan
for technical assistance. This work was supported by the National Institute of Neurological
Disorders and Stroke (RF1NS132910), the E. Matilda Ziegler Foundation for the Blind, and a
Whitehall Foundation research grant. CF is supported by the France-Merrick Foundation.

REFERENCES

Adelson, E. H., & Bergen, J. R. (1985). Spatiotemporal energy models for the perception of motion. *Journal of the Optical Society of America A*, *2*(2), 284. https://doi.org/10.1364/JOSAA.2.000284

Adler, W. T., & Ma, W. J. (2018). Comparing Bayesian and non-Bayesian accounts of human confidence reports. *PLoS Computational Biology*, *14*(11), 1–34. https://doi.org/10.1371/journal.pcbi.1006572

Audley, R. J. (1960). A stochastic model for individual choice behavior. Psychological Review 67, 1.

Balsdon, T., Mamassian, P., & Wyart, V. (2021). Separable neural signatures of confidence during perceptual decisions. *BioRxiv*, 2021.04.08.439033. https://www.biorxiv.org/content/10.1101/2021.04.08.439033v2%0Ahttps://www.biorxiv.org/content/10.1101/2021.04.08.439033v2.abstract

Bang, D., Kishida, K. T., Lohrenz, T., White, J. P., Laxton, A. W., Tatter, S. B., Fleming, S. M., & Montague, P. R. (2020). Sub-second Dopamine and Serotonin Signaling in Human Striatum during Perceptual Decision-Making. *Neuron*, 1–12. https://doi.org/10.1016/j.neuron.2020.09.015

Baranski, J. V., & Petrusic, W. M. (1998). Probing the Locus of Confidence Judgments: Experiments on the Time to Determine Confidence. *Journal of Experimental Psychology: Human Perception and Performance*, *24*(3), 929–945. https://doi.org/10.1037/0096-1523.24.3.929

Bollimunta, A., Totten, D., & Ditterich, J. (2012). Neural dynamics of choice: Single-trial analysis of decision-related activity in parietal cortex. *Journal of Neuroscience*, *32*(37), 12684–12701. https://doi.org/10.1523/JNEUROSCI.5752-11.2012

Boundy-Singer, Z. M., Ziemba, C. M., & Goris, R. L. T. (2022). Confidence reflects a noisy decision reliability estimate. *Nature Human Behaviour*, *7*(1), 142–154. https://doi.org/10.1038/s41562-022-01464-x

Boundy-Singer, Z. M., Ziemba, C. M., & Goris, R. L. T. (2024a). How does V1 population activity inform pereceptual certainty? *Journal of Vision.* 24(6)12: 1-17.

Boundy-Singer, Z. M., Ziemba, C. M., & Goris, R. L. T. (2024b). Sensory population activity reveals confidence computations in the primate visual system. *bioRxiv.*

Caspi, A., Beutter, B. R., & Eckstein, M. P. (2004). The time course of visual information accrual guiding eye movement decisions during visual search. *Proceedings of the National Academy of Sciences*, *4*(8), 743. http://jov.arvojournals.org/Article.aspx?doi=10.1167/4.8.743%5Cnpapers3://publication/doi/10.1167/4.8.743

Chen, X., Zirnsak, M., Vega, G. M., Govil, E., Lomber, S. G., & Moore, T. (2020). Parietal Cortex Regulates Visual Salience and Salience-Driven Behavior. *Neuron*, *106*(1), 177-187.e4. https://doi.org/10.1016/j.neuron.2020.01.016

Churchland, A. K., Kiani, R., R., C., Wang, X.-J., Pouget, A., & Shadlen, M. N. (2011). Variance as a signature of neural computations during decision-making. *Neuron*, *69*(2), 818–831. https://doi.org/10.1038/mp.2011.182.doi

Cisek, P., & Kalaska, J. F. (2002). Simultaneous encoding of multiple potential reach directions in dorsal premotor cortex. *Journal of Neurophysiology*, *87*(2), 1149–1154. https://doi.org/10.1152/jn.00443.2001

Daniel, R., & Pollmann, S. (2012). Striatal activations signal prediction errors on confidence in the absence of external feedback. *NeuroImage*, *59*(4), 3457–3467. https://doi.org/10.1016/j.neuroimage.2011.11.058

David Smith, J., Couchman, J. J., & Beran, M. J. (2012). The highs and lows of theoretical interpretation in animal-metacognition research. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *367*(1594), 1297–1309. https://doi.org/10.1098/rstb.2011.0366

de Lafuente, V., Jazayeri, M., & Shadlen, M. N. (2015). Representation of accumulating evidence for a decision in two parietal areas. *Journal of Neuroscience*, *35*(10), 4306–4318. https://doi.org/10.1523/JNEUROSCI.2451-14.2015

Desender, K., Donner, T. H., & Verguts, T. (2021). Dynamic expressions of confidence within an evidence accumulation framework. *Cognition*, *207*(May 2020), 104522. https://doi.org/10.1016/j.cognition.2020.104522

Desender, K., Ridderinkhof, K. R., & Murphy, P. R. (2021). Understanding neural signals of post-decisional performance monitoring: An integrative review. *ELife*, *10*, 1–21. https://doi.org/10.7554/eLife.67556

Dotan, D., Meyniel, F., & Dehaene, S. (2018). On-line confidence monitoring during decision making. *Cognition*, *171*(February 2017), 112–121. https://doi.org/10.1016/j.cognition.2017.11.001

Dou, W., Martinez Arango, L. J., Castaneda, O. G., Arellano, L., Mcintyre, E., Yballa, C., & Samaha, J. (2024). Neural Signatures of Evidence Accumulation Encode Subjective Perceptual Confidence Independent of Performance. *Psychological Science*. https://doi.org/10.1177/09567976241246561

Double, K. S., & Birney, D. P. (2024). Confidence judgments interfere with perceptual decision making. *Scientific Reports*, *14*(1), 1–10. https://doi.org/10.1038/s41598-024-64575-7

Drugowitsch, J., Mendonça, A. G., Mainen, Z. F., & Pouget, A. (2019). Learning optimal decisions with confidence. *Proceedings of the National Academy of Sciences of the United States of America*, *116*(49), 24872–24880. https://doi.org/10.1073/pnas.1906787116

Drugowitsch, J., Moreno-Bote, R., Churchland, A. K., Shadlen, M. N., & Pouget, A. (2012). The Cost of Accumulating Evidence in Perceptual Decision Making. *Journal of Neuroscience*, *32*(11), 3612–3628. https://doi.org/10.1523/JNEUROSCI.4010-11.2012

Fan, Y., Doi, T., Gold, J. I., & Ding, L. (2024). Neural Representations of Post-Decision Accuracy and Reward Expectation in the Caudate Nucleus and Frontal Eye Field. *Journal of Neuroscience*, *44*(2). https://doi.org/10.1523/JNEUROSCI.0902-23.2023

Fetsch, C. R., Kiani, R., Newsome, W. T., & Shadlen, M. N. (2014). Effects of Cortical Microstimulation on Confidence in a Perceptual Decision. *Neuron*, *83*(4), 797–804. https://doi.org/10.1016/j.neuron.2014.07.011

Fetsch, C. R., Kiani, R., & Shadlen, M. N. (2014). Predicting the accuracy of a decision: A neural mechanism of confidence. *Cold Spring Harbor Symposia on Quantitative Biology*, *79*, 185–197. https://doi.org/10.1101/sqb.2014.79.024893

Gherman, S., & Philiastides, M. G. (2018). Human VMPFC encodes early signatures of confidence in
perceptual decisions. *ELife*, *7*, 1–28. https://doi.org/10.7554/eLife.38293

Gnadt, J. W., & Andersen, R. A. (1988). Memory related motor planning activity in posterior
parietal cortex of macaque. *Experimental Brain Research*, *70*(1), 216–220.

Guggenmos, M., Wilbertz, G., Hebart, M. N., & Sterzer, P. (2016). Mesolimbic confidence signals
guide perceptual learning in the absence of external feedback. *ELife*, *5*(MARCH2016), 1–19.
https://doi.org/10.7554/eLife.13388

Hanks, T. D., Ditterich, J., & Shadlen, M. N. (2006). Microstimulation of macaque area LIP affects
decision-making in a motion discrimination task. *Nature Neuroscience*, *9*(5), 682–689.
https://doi.org/10.1038/nn1683

Hanks, T. D., Mazurek, M. E., Kiani, R., Hopp, E., & Shadlen, M. N. (2011). Elapsed Decision Time
Affects the Weighting of Prior Probability in a Perceptual Decision Task. *Journal of Neuroscience*,
31(17), 6339–6352. https://doi.org/10.1523/JNEUROSCI.5613-10.2011

Herregods, S., Denmat, P. Le, & Desender, K. (2023). Modelling Speed-Accuracy Tradeoffs in the
Stopping Rule for Confidence Judgments. *BioRxiv*, 1–58.

Hilgenstock, R., Weiss, T., & Witte, O. W. (2014). You'd Better Think Twice: Post-Decision
Perceptual Confidence. *NeuroImage*, *99*, 323–331.
https://doi.org/10.1016/j.neuroimage.2014.05.049

Insabato, A., Pannunzi, M., Rolls, E. T., & Deco, G. (2010). Confidence-related decision making.
Journal of Neurophysiology, *104*(1), 539–547. https://doi.org/10.1152/jn.01068.2009

Jeurissen, D., Shushruth, S., El-Shamayleh, Y., Horwitz, G. D., & Shadlen, M. N. (2022). Deficits in
decision-making induced by parietal cortex inactivation are compensated at two timescales.
Neuron, *110*(12), 1924-1931.e5. https://doi.org/10.1016/j.neuron.2022.03.022

Kang, Y. H. R., Löffler, A., Jeurissen, D., Zylberberg, A., Wolpert, D. M., & Shadlen, M. N. (2021).
Multiple decisions about one object involve parallel sensory acquisition but time-multiplexed
evidence incorporation. *ELife*, *10:e63721*. https://doi.org/10.7554/eLife.63721

Katz, L. N., Yates, J. L., Pillow, J. W., & Huk, A. C. (2016). Dissociated functional significance of
decision-related activity in the primate dorsal stream. *Nature*, *535*(7611), 285–288.
https://doi.org/10.1038/nature18617

Kaufman, M. T., Churchland, M. M., Ryu, S. I., & Shenoy, K. V. (2015). Vacillation, indecision and
hesitation in moment-by-moment decoding of monkey motor cortex. *ELife*, *4:e04677*.
https://doi.org/10.7554/eLife.04677

Kellogg, W. N. (1931). The Time of Judgment in Psychometric Measures. *The American Journal of*
Psychology, *43*(1), 65–86.

Kepecs, A., & Mainen, Z. F. (2012). A computational framework for the study of confidence in
humans and animals. *Philosophical Transactions of the Royal Society B: Biological Sciences*,
367(1594), 1322–1337. https://doi.org/10.1098/rstb.2012.0037

Kepecs, A., Uchida, N., Zariwala, H. A., & Mainen, Z. F. (2008). Neural correlates, computation and
behavioural impact of decision confidence. *Nature*, *455*(7210), 227–231.
https://doi.org/10.1038/nature07200

Khalvati, K., Kiani, R., & Rao, R. P. N. (2021). Bayesian inference with incomplete knowledge explains perceptual confidence and its deviations from accuracy. *Nature Communications*, *12*(1), 1–16. https://doi.org/10.1038/s41467-021-25419-4

Kiani, R., Corthell, L., & Shadlen, M. N. (2014a). Choice certainty is informed by both evidence and decision time. *Neuron*, *84*(6), 1329–1342. https://doi.org/10.1016/j.neuron.2014.12.015

Kiani, R., Cueva, C. J., Reppas, J. B., & Newsome, W. T. (2014b). Dynamics of neural population responses in prefrontal cortex indicate changes of mind on single trials. *Current Biology*, *24*(13), 1542–1547. https://doi.org/10.1016/j.cub.2014.05.049

Kiani, R., Hanks, T. D., & Shadlen, M. N. (2008). Bounded Integration in Parietal Cortex Underlies Decisions Even When Viewing Duration Is Dictated by the Environment. *Journal of Neuroscience*, *28*(12), 3017–3029. https://doi.org/10.1523/JNEUROSCI.4761-07.2008

Kiani, R., & Shadlen, M. N. (2009). Representation of confidence associated with a decision by neurons in the parietal cortex. *Science*, *324*(5928), 759–764. https://doi.org/10.1126/science.1169405

Komura, Y., Nikkuni, A., Hirashima, N., Uetake, T., & Miyamoto, A. (2013). Responses of pulvinar neurons reflect a subject's confidence in visual categorization. *Nature Neuroscience*, *16*(6), 749–755. https://doi.org/10.1038/nn.3393

Lak, A., Costa, G. M., Romberg, E., Koulakov, A. A., Mainen, Z. F., & Kepecs, A. (2014). Orbitofrontal cortex is required for optimal waiting based on decision confidence. *Neuron*, *84*(1), 190–201. https://doi.org/10.1016/j.neuron.2014.08.039

Lak, A., Hueske, E., Hirokawa, J., Masset, P., Ott, T., Urai, A. E., Donner, T. H., Carandini, M., Tonegawa, S., Uchida, N., & Kepecs, A. (2020). Reinforcement biases subsequent perceptual decisions when confidence is low: A widespread behavioral phenomenon. *ELife*, *9*:e49834. https://doi.org/10.7554/eLife.49834

Latimer, K. W., Yates, J. L., Huk, M. L. R. M. A. C., & Pillow, J. W. (2015). Single-trial spike trains in parietal cortex reveal discrete steps during decision-making. *Science*, 34(6244), 184–188. https://doi.org/10.1093/annonc/mdx490/4098869/Hybrid-capture-based-genomic-profiling-of

Lewis, J. W., & Essen, D. C. V. A. N. (2000). Corticocortical Connections of Visual , Sensorimotor , and Multimodal Processing Areas in the Parietal Lobe of the Macaque Monkey. *The Journal of Comparative Neurology*, 428(1), 112–137.

Li, X., Su, R., Chen, Y., & Yang, T. (2023). Optimal policy for uncertainty estimation concurrent with decision making. *Cell Reports*, *42*(3), 112232. https://doi.org/10.1016/j.celrep.2023.112232

Lisi, M., Mongillo, G., Milne, G., Dekker, T., & Gorea, A. (2021). Discrete confidence levels revealed by sequential decisions. *Nature Human Behaviour*, *5*(2), 273–280. https://doi.org/10.1038/s41562-020-00953-1

Ma, W. J., & Jazayeri, M. (2014). Neural Coding of Uncertainty and Probability. *Annual Review of Neuroscience*, *37*(1), 205–220. https://doi.org/10.1146/annurev-neuro-071013-014017

McPeek, R. M., Skavenski, A. A., & Nakayama, K. (2000). Concurrent processing of saccades in visual search. *Vision Research*, *40*(18), 2499–2516. https://doi.org/10.1016/S0042-6989(00)00102-4

Meirhaeghe, N., Riehle, A., & Brochier, T. (2023). Parallel movement planning is achieved via an
optimal preparatory state in motor cortex. *Cell Reports*, *42*(2), 112136.
https://doi.org/10.1016/j.celrep.2023.112136

Meyniel, F., Sigman, M., & Mainen, Z. F. (2015). Confidence as Bayesian Probability: From Neural
Origins to Behavior. *Neuron*, *88*(1), 78–92. https://doi.org/10.1016/j.neuron.2015.09.039

Middlebrooks, P. G., & Sommer, M. A. (2011). Metacognition in monkeys during an oculomotor
task. *Journal of Experimental Psychology: Learning Memory and Cognition*, *37*(2), 325–337.
https://doi.org/10.1037/a0021611

Moran, R., Teodorescu, A. R., & Usher, M. (2015). Post choice information integration as a causal
determinant of confidence: Novel data and a computational account. *Cognitive Psychology*, *78*,
99–147. https://doi.org/10.1016/j.cogpsych.2015.01.002

Murphy, P. R., Robertson, I. H., Harty, S., & O'Connell, R. G. (2015). Neural evidence accumulation
persists after choice to inform metacognitive judgments. *ELife*, *4*:e11946.
https://doi.org/10.7554/eLife.11946

Nguyenkim, J. D., & DeAngelis, G. C. (2003). Disparity-based coding of three-dimensional surface
orientation by macaque middle temporal neurons. *Journal of Neuroscience*, *23*(18), 7117–7128.
https://doi.org/10.1523/jneurosci.23-18-07117.2003

Nienborg, H., & Cumming, B. G. (2009). Decision-related activity in sensory neurons reflects more
than a neurons causal effect. *Nature*, *459*(7243), 89–92. https://doi.org/10.1038/nature07821

O'Connell, R. G. & Kelly, S. P. Neurophysiology of Human Perceptual Decision-Making. Annu Rev
Neurosci 44, 495–516 (2021).

Orozco, S. P., Albert, S. T., & Shadmehr, R. (2021). Adaptive control of movement deceleration
during saccades. *PLoS Computational Biology*, *17*(7), 1–30.
https://doi.org/10.1371/journal.pcbi.1009176

Pachitariu, M., Steinmetz, N. A., Kadir, S. N., Carandini, M. & Harris, K. D. (2016). Fast and accurate
spike sorting of high-channel count probes with KiloSort. Adv. Neural Infor. Process. Syst. 29,
4455–4464.

Peixoto, D., Verhein, J. R., Kiani, R., Kao, J. C., Nuyujukian, P., Chandrasekaran, C., Brown, J., Fong,
S., Ryu, S. I., Shenoy, K. V., & Newsome, W. T. (2019). Decoding and perturbing decision states in
real time. *Nature*. 591, 604-609. https://doi.org/10.1101/681783

Pereira, M., Faivre, N., Iturrate, I., Wirthlin, M., Serafini, L., Martin, S., Desvachez, A., Blanke, O., de
Ville, D. Van, & del Millán, J. R. (2020). Disentangling the origins of confidence in speeded
perceptual judgments through multimodal imaging. *Proceedings of the National Academy of*
Sciences of the United States of America, *117*(15), 8382–8390.
https://doi.org/10.1073/pnas.1918335117

Pleskac, T. J., & Busemeyer, J. R. (2010). Two-stage dynamic signal detection: A theory of choice,
decision time, and confidence. *Psychological Review*, *117*(3), 864–901.
https://doi.org/10.1037/a0019737

Pouget, A., Drugowitsch, J., & Kepecs, A. (2016). Confidence and certainty: Distinct probabilistic
quantities for different goals. *Nature Neuroscience*, *19*(3), 366–374.
https://doi.org/10.1038/nn.4240

Purcell, B. A., & Kiani, R. (2016). Hierarchical decision processes that operate over distinct
timescales underlie choice and changes in strategy. *Proceedings of the National Academy of*
Sciences, *113*(31), E4531–E4540. https://doi.org/10.1073/pnas.1524685113

Rescorla RA, and Wagner AR (1972) A theory of Pavlovian conditioning: variations in the
effectiveness of reinforcement and nonreinforcement. In: Classical conditioning II: current
research and theory (Black AH, Pro-kasy WF, eds.). New York: Appleton-Century-Crofts.

Resulaj, A., Kiani, R., Wolpert, D. M., & Shadlen, M. N. (2009). Changes of mind in decision-making.
Nature, *461*(7261), 263–266. https://doi.org/10.1038/nature08275

Roitman, J. D., & Shadlen, M. N. (2002). Response of neurons in the lateral intraparietal area
during a combined visual discrimination reaction time task. *Journal of Neuroscience*, *22*(21), 9475–
9489. https://doi.org/10.1523/jneurosci.22-21-09475.2002

Saleem KS, and Logothetis NK. (2006). *A Combined MRI and Histology Atlas of the Rhesus Monkey*
Brain. Amsterdam: Academic Press.

Sanders, J. I., Hangya, B., & Kepecs, A. (2016). Signatures of a Statistical Computation in the Human
Sense of Confidence. *Neuron*, *90*(3), 499–506. https://doi.org/10.1016/j.neuron.2016.03.025

Sarafyazd, M., & Jazayeri, M. (2019). Hierarchical reasoning by neural circuits in the frontal cortex.
Science, *364*(6441). https://doi.org/10.1126/science.aav8911

Shadlen, M. N., & Kiani, R. (2013). Decision making as a window on cognition. *Neuron*, *80*(3), 791–
806. https://doi.org/10.1016/j.neuron.2013.10.047

Shadmehr, R., Reppert, T. R., Summerside, E. M., Yoon, T., & Ahmed, A. A. (2019). Movement Vigor
as a Reflection of Subjective Economic Utility. *Trends in Neurosciences*, *42*(5), 323–336.
https://doi.org/10.1016/j.tins.2019.02.003

Shan, H., Moreno-Bote, R., & Drugowitsch, J. (2019). Family of closed-form solutions for two-
dimensional correlated diffusion processes. *Physical Review E*, *100*(3), 321-332.
https://doi.org/10.1103/PhysRevE.100.032132

Shekhar, M. & Rahnev, D. How Do Humans Give Confidence? A Comprehensive Comparison of
Process Models of Perceptual Metacognition. J. Exp. Psychol.: Gen. 153, 656–688 (2023).

Shushruth, X. S., Mazurek, M., & Shadlen, M. N. (2018). Comparison of Decision-Related Signals in
Sensory and Motor Preparatory Responses of Neurons in Area LIP. *Journal of Neuroscience*, *38*(28),
6350–6365. https://doi.org/10.1523/JNEUROSCI.0668-18.2018

Siegle, J. H. et al. (2017). Open Ephys: an open-source, plugin-based platform for multichannel
electrophysiology. *J. Neural Eng.* **14**, 045003.

Steinemann, N. A., Stine, G. M., Trautmann, E. M., Zylberberg, A., Wolpert, D. M., & Shadlen, M. N.
(2023). Direct observation of the neural computations underlying a single decision. *eLife.*
12:RP90859.

Stolyarova, A., Rakhshan, M., Hart, E. E., O'Dell, T. J., Peters, M. A. K., Lau, H., Soltani, A., &
Izquierdo, A. (2019). Contributions of anterior cingulate cortex and basolateral amygdala to

decision confidence and learning under uncertainty. *Nature Communications*, *10*(1).
https://doi.org/10.1038/s41467-019-12725-1

Stringer, C., Pachitariu, M., Steinmetz, N. *et al.* High-dimensional geometry of population
responses in visual cortex. *Nature* **571**, 361–365 (2019). https://doi.org/10.1038/s41586-019-
1346-5

Sutton RS, Barto AG (1998) Reinforcement learning: an introduction. Cambridge, MA: MIT

van den Berg, R., Anandalingam, K., Zylberberg, A., Kiani, R., Shadlen, M. N., & Wolpert, D. M.
(2016a). A common mechanism underlies changes of mind about decisions and confidence. *ELife*,
5:e12192. https://doi.org/10.7554/eLife.12192

van den Berg, R., Zylberberg, A., Kiani, R., Shadlen, M. N., & Wolpert, D. M. (2016b). Confidence Is
the Bridge between Multi-stage Decisions. *Current Biology*, *26*(23), 3157–3168.
https://doi.org/10.1016/j.cub.2016.10.021

Wang, S., Falcone, R., Richmond, B., & Averbeck, B. B. (2023). Attractor dynamics reflect decision
confidence in macaque prefrontal cortex. *Nature Neuroscience*, *26*(11), 1970–1980.
https://doi.org/10.1038/s41593-023-01445-x

Xue, K., Zheng, Y., Rafiei, F., & Rahnev, D. (2023). The timing of confidence computations in human
prefrontal cortex. *Cortex*, *168*, 167–175. https://doi.org/10.1016/j.cortex.2023.08.009

Zhou, Y., & Freedman, D. J. (2019). Posterior parietal cortex plays a causal role in perceptual and
categorical decisions. *Science*. 365(6449), 180-185. https://doi.org/10.1007/978-1-4614-7320-
6_310-1

Zylberberg, A. (2021). Decision prioritization and causal reasoning in decision hierarchies. *PLoS*
Computational Biology. 17(12):e1009688. https://doi.org/10.1371/journal.pcbi.1009688

Zylberberg, A., Barttfeld, P., Sigman, M., & Pereira, A. (2012). The construction of confidence in a
perceptual decision. *Front. Integr. Neurosci. 6*(79), 1–10. https://doi.org/10.3389/fnint.2012.00079

METHODS

EXPERIMENTAL MODEL AND SUBJECT DETAILS

Two male rhesus monkeys (*Macaca mulatta,* 6-8 years old, 8-10 kilograms) were kept and handled

according to National Institutes of Health guidelines and the Institutional Animal Care and Use

Committee at Johns Hopkins University. Standard sterile surgical procedures were performed to

place a PEEK recording chamber (Rogue Research) and titanium head post under isoflurane

anesthesia in a dedicated operating suite. The recording chamber was positioned over a

craniotomy above the right posterior parietal cortex of both animals for access to the intraparietal

sulcus and posterior third of the superior temporal sulcus. The chamber and head post were held

in place using dental acrylic anchored with ceramic bone screws.

METHOD DETAILS

Experimental apparatus

Monkeys were seated in a custom-built primate chair in a sound-insulated booth facing a visual

display (ViewPixx, VPixx Technologies; resolution 1080x960, refresh rate 120 Hz; viewing distance

52 cm) and infrared video eye tracker (Eyelink 1000 Plus, SR Research). Experiments were

controlled by a Linux PC running a modified version of the PLDAPS system (Version 4.1, Eastman

& Huk, 2012) in MATLAB (The MathWorks). Visual stimuli were generated using Psychophysics

Toolbox 3.0 (Brainard, 1997). For correct responses, the monkey was given a fluid reward that was

dispensed using a solenoid-gated system.

Neurophysiology

Recording probes (32- or 128-channel Deep Array, Diagnostic Biochips) were positioned with the

aid of a PEEK grid secured inside the recording chamber. A sharpened guide tube was inserted

through a grid hole so that the tip of the tube just punctured the dura, then a probe was advanced

through the guide tube into the brain using a motorized microdrive (40mm MEM Drive, Thomas

Recording). Bandpass-filtered voltage signals were collected using the Open Ephys acquisition

board and software (Siegle et al., 2017). Post-hoc analysis for identifying single neurons and multi-

unit clusters was done using Kilosort 2.0 (Pachitariu et al., 2016; Stringer et al., 2019). Further

curation was done using the phy2 software (https://phy.readthedocs.io/en/latest/). Data analysis

was performed with custom MATLAB code.

Targeting of LIPv was achieved by selection of grid locations based on a post-surgical

structural MRI scan in which the chamber and grid holes were well visualized. We compared the

MR images to published reports and atlases (Lewis and Van Essen, 2000; Saleem & Logothetis,

2006) to estimate the depth of LIPv (typically 8-12 mm from the dura in our vertical penetration

angle) and corroborated the targeting using white-gray matter transitions and physiological

response properties during the mapping tasks described below. After reaching the target, we let

the probe settle for 30-60 minutes before the start of the experiment. A total of 407 neurons (single

= 148 & multi = 56 in monkey H, single = 107 & multi = 93 G) were collected over 29 sessions (12

for monkey H, 17 for monkey G).

844
Memory saccade task

Sessions began with a standard memory-guided saccade task to identify neurons with

spatially selective activity during the delay period (Gnadt & Andersen, 1998) and to coarsely map

their response fields (RFs). Monkeys were instructed to gaze at a central fixation point (1.5° radius

acceptance window), after which a red target (0.42° diameter circle) was flashed for 100 ms,

located in one of several locations evenly spaced in polar coordinates. The coordinates consisted

of 3 different radii (eccentricities) and 10 or 12 angular positions, giving a total of 30 or 36 unique

target locations. Each target location was presented 10 times in pseudorandom order, requiring a

total of 300 or 360 trials. While fixating, the monkey had to remember the location of the target, and

after a delay of 0.8 s the fixation point was extinguished, instructing the monkey to make a saccade

to the remembered location. RFs were estimated online during/after the memory saccade block by

acquiring multi-unit spikes (threshold crossings) on each recording channel and plotting the mean

firing rate during the memory delay as a function of target location in a 2D heat map. These RF

maps guided the placement of the four targets for the main decision task, such that one or two of

the targets overlapped the RF of multiple neurons in the recorded ensemble.

Main task

The monkeys were trained to perform a reaction-time direction discrimination task with

simultaneous report of choice and confidence ('peri-decision wagering'; Figure 1A). To initiate a

trial the animals acquired fixation on a target on the center of the screen (0.21° diameter). After a

delay of 0.5 s four targets appeared, positioned diagonally from the center of the screen, each

representing a choice (left or right) and a wager, or bet (high or low). The targets representing high

bets were always placed in the upper-left and upper-right quadrants while the low-bet targets were

placed in the lower quadrants (left high: x = -7.3±2.1°, y = 7.3±1.5°; left low: x = -6.9±2.3°, y = -

3.4±1.4°; right high: x = 7.3±2.1°, y = 7.3±1.5°; right low: x = 6.9±2.3°, y = -3.4±1.4°). Each left-right

pair was presented symmetrically around the vertical meridian, but high-bet targets were typically

2-5° further from the fixation point than low-bet targets, in order to counteract the monkeys'

tendency to bet high more often than low.

After another brief delay (0.3-0.6 s, truncated exponential), a dynamic random-dot motion

(RDM) stimulus was presented in a circular aperture. Motion strength, or coherence, was sampled

uniformly on each trial from the set {0%, ±3.2%, ±6.4%, ±12.8%, ±25.6%, ±51.2%}, where positive

is rightward and negative is leftward. The stimulus was constructed as three independent sets of

dots (Roitman & Shadlen, 2002), each appearing for a given video frame then reappearing three

frames (25 ms) later. Upon reappearing, a given dot was either repositioned horizontally to

generate apparent motion in the assigned direction (speed = 2-16°/s, held constant within a

session) with probability given by the coherence on that trial, or otherwise was replotted randomly

within the aperture.

When ready with a decision, the animal could report its choice and wager by making a

single saccade to one of the four targets. When the eyes moved 1.5° away from the target the

RDM and fixation point were extinguished while the four targets remained visible. When the eye

position reached one of the four targets, it was required to hold fixation within 1.5° of the target for

0.1 s to confirm the outcome. Lastly, the animal was either rewarded or given a time penalty

depending on the conjunction of accuracy (choice corresponding to the sign of coherence) and

wager (Figure 1A, right). The penalty for a high-bet error was applied to the subsequent trial where

the animal was required to fixate the central target for a longer period of time (2-3 s) prior to RDM

onset. Reward sizes (~.21 ml for high and ~.19 ml for low bets) and penalty times were chosen to

encourage a wide range of wager probability across different levels of motion strength.

892
893　**QUANTIFICATION AND STATISTICAL ANALYSIS**

894　**Cell selection**

895　To quantify spatial selectivity, we modified a previously described discrimination index (Nguyenkim

896　& DeAngelis, 2003).

897
$$DDI = \frac{R_{max} - R_{min}}{R_{max} - R_{min} + 2\sqrt{\frac{SSE}{N-M}}}$$

R_{max} and R_{min} are the mean firing rates during the delay period at the target spatial location with the

highest and lowest response, respectively. SSE is the sum-squared error around the mean

responses, N is the total number of trials, and M is the total number of unique spatial target

locations. For all analyses except the population logistic decoder, only units (single- and multi-)

with a discrimination index higher than an arbitrary cutoff of 0.45 were kept for further analysis.

Full quantification of RFs was done by fitting a 2D Gaussian to the firing rates during the

delay period of the memory saccade task for each target location:

905
$$FR = A * \frac{1}{2\pi|\Sigma|^{\frac{1}{2}}} \exp\left(-\frac{1}{2}(x - \mu)\Sigma^{-1}(x - \mu)^T\right)$$

where FR is firing rate during the delay period and X is a 2-length vector that contains the X and Y

positions of the target locations (in degrees). The fitted variables include **A** for amplitude, **μ** for the

2D mean location of the RDM (X and Y in degrees), and **Σ** which is the covariance matrix of the

Gaussian (2x2). To reduce the variables for fitting we set the covariance to 0 and only fit for the

two variances. We then normalized the 2D Gaussian to convert it to a probability density and

calculated the final preferred target based on the probabilities corresponding to the 4 targets in the

peri-dw task.

For the population logistic decoder, we included not only units with delay period activity in

the memory saccade task but accepted any that were well defined single neurons or multi-unit

clusters based on careful spike sorting and manual curation. Previous studies have suggested that

decision-related activity can be present even in neurons without memory delay-period activity

(Meister et al., 2013), and we aimed to maximize the sample size to facilitate single-trial decoding.

This broader criterion increased the average number of units per session from 7.5 to 17.3 for

monkey H and from 6.2 to 11.2 for monkey G.

920
921   **Behavioral data analysis**

922   We applied a logistic regression model to fit the proportion of rightward choices, as follows:

923
$$P_{right} = \frac{1}{1+\exp(\beta_0 + \beta_1 Coh + \beta_2 Wager + \beta_3 (Coh)(Wager))}$$

where P_{right} is the probability of a rightward choice, *Coh* is signed motion coherence, *Wager* is the

monkey's bet (high/low), β_0 is the overall bias, β_1 estimates the effect of signed motion coherence

on choices, β_2 is the weight for the bet, and β_3 is the interaction term (used to calculate whether

choice significantly depends on wager). The fitting was done by finding the minimum negative log-

likelihood value under a binomial distribution, using *fminsearch* in MATLAB with the Nelder-Mead

method. For choices conditioned on high and low bets, we fit two separate logistic regressions

after removing the terms to the right of $\beta_1 Coh$ (Figure S1).

The fits to the average reaction times (RTs) as a function of motion strength were done

using a Gaussian distribution, defined as follows:

933
$$RT = A * \frac{1}{\sigma\sqrt{2\pi}} \exp\left(-\frac{1}{2}\left(\frac{coh - 0}{\sigma}\right)^2\right) + b$$

where A is an amplitude term, coh is the signed motion coherence, σ is the standard deviation

controlling the width of the Gaussian, and b is a bias term capturing the fastest mean RT. We fit

this pseudo-gaussian by minimizing root-mean-square error (RMSE) instead of maximizing the

likelihood, because of the amplitude value.

To examine the relationship between accuracy and RT, as well as wager and RT, we

calculated proportion correct and proportion of high bets grouped by RT, using non-overlapping

100 ms time bins starting 100 ms after motion onset. To test for significance as to whether the

trend was decreasing (during the time depicted in Figure 1D) we used a Cochran-Armitage test for

trend:

943
$$T = \sum_{i=1}^{k} t_i (N_{1i} R_2 - N_{2i} R_1)$$
$$Var(T) = \frac{R_1 R_2}{N} \left(\sum_{i=1}^{k} t_i^2 C_i (N - C_i) - 2 \sum_{i=1}^{k-1} \sum_{j=i+1}^{k} t_i t_j C_i C_j \right)$$

where t_i are the weights depicting the trend (in our case linear, so t = [0, 1, 2, 3, 4, …]), N = total

number of trials, N_{ab} is total number of trials for group a (accuracy: correct and error; wager: high

or low) and b is total number of trials for timepoint b. R_a represents total number of trials for group

a irrespective of time, and C_b is total number of trials at timepoint b irrespective of group. The

division of T by $Var(T)$ gives a test statistic that can then be used to compute a p-value.

Motion energy analysis

To estimate the temporal weighting of sensory evidence for choice and confidence, we utilized

motion stimulus fluctuations to perform a psychophysical reverse correlation analysis on both

choice and wager. We convolved each trial's sequence of dots — a 3-dimensional array with the

first two dimensions denoting the X-Y coordinates of the dots' center, and the third dimension

spanning the number of frames — with two pairs of quadrature spatiotemporal filters (Adelson &

Bergen, 1985). The filters were oriented to account for motion in the direction along the choice

axis: 0° motion (rightward) and 180° motion (leftward motion). The convolved quadrature pairs

were squared and summed to give the local motion energy for both the leftward and rightward

directions. These local motion energies were then collapsed across space (first 2 dimensions) to

derive the motion energy provided by the stimulus through time, ME(t). To quantify the net motion

energy, we took the difference between both directions of motion energy (right minus left; Adelson

& Bergen, 1985; Kiani et al., 2008). To strictly look at the fluctuations around the mean and

mitigate potential effects of coherence, we subtracted from each trial the mean motion energy,

conditioned on signed coherence, through time. As most meaningful fluctuations occur at smaller

coherences, we also decided to restrict the analysis to 0%, 3.2% and 6.4% coherence trials.

For the choice kernels (Figure 2A) we simply averaged the motion energy profiles for all

trials with a right choice (red line) or left choice (blue line). The shaded red and blue area

represents the standard error of the mean. To evaluate statistical significance of the choice

kernels, we used a t-test comparing the motion energy profiles for right and left choices at each

time point, applying a Šidák correction matching the number of time samples. For the confidence

kernels (Figure 2B), we instead subtracted the motion energy profiles for high vs. low wager trials

conditioned on a given choice (correct trials only) and computed the standard error of the

difference (shaded area around traces in bottom of Figure 2). To assess significance, we

compared the confidence kernel distribution relative to a value of zero using a t-test with Šidák

correction for the number of time samples.

Parallel model

To formalize the hypothesis of parallel deliberation for choice and confidence, we utilized a two-

dimensional (2D) bounded accumulator model (Kiani et al. 2014), also known as an anticorrelated

race. We adapted a recently developed family of closed-form solutions for a 2D correlated diffusion

process (Shan et al., 2019) to facilitate fitting of the parameters. By conceptualizing the diffusion

process as a Gaussian distribution originating from the third quadrant on a plane with two

absorbing bounds, one can employ the method of images (MoI) to calculate the propagation of the

probability density of the diffusing particle, i.e. the solution to the Fokker-Planck equation. The

constraint making this numerical solution possible limits the discrete number of anti-correlation

values that can be modeled, governed by the number of images:

987
$$rho = \cos\left(-\frac{\pi}{I}\right)$$

988 where rho is the correlation value and I is the number of images. We selected $I = 4$ or $rho = $

989 .7071 for consistency with previous studies (Kiani et al., 2014; Van Den Berg et al., 2016a).

990   Specifically, the MoI yields $P(v_{right}, v_{left}|C, t)$, describing the probability of the

991 accumulator being in a particular position at time t for coherence C. The probability of making a

992 right choice is given by:

$$P(Right|C) =$$
993
$$\frac{\iint P(v_{right} = B, v_{left}|C, t)dv_{left}*P(t)dt}{\int\left(\int P(v_{right} = B, v_{left}|C, t)dv_{left} + \int P(v_{right}, v_{left} = B|C, t)dv_{right}\right)P(t)dt}$$

994 where B is the bound for terminating the accumulation process. To acquire the decision time

995 distribution, we calculated the difference in the survival probability as follows:

996
$$P(DT) = \Delta\left(\iint_{-inf}^{Bound} P(v_{right}, v_{left}|C, t)dv_{right}dv_{left}\right)$$

997 thereby providing the change in probability at each survival timestep, quantifying the probability of

998 crossing a bound. To then calculate the probability of reaction time (decision time plus

999 sensory/motor delays, referred to as non-decision time or *nonDT*), we convolved this probability

1000 density as follows:

1001
$$P(RT) = \int P_{DT}(t - z)P_{nonDT}(z)dz$$

1002 where $P_{nonDT}(z)$ is modeled as a Gaussian distribution with mean (μ_{nonDT}) and standard

1003 deviation (σ_{nonDT}).

1004   To calculate the probability of betting high, we first computed the log-odds of a correct

1005 choice as a function of the state of the losing accumulator (Kiani et al., 2014), as follows:

1006
$$Logodds = Log\left(\frac{\int P(v_{incorrect}, t|v_{correct} = B, C, t)P(C)dC}{\int P(v_{correct}, t|v_{incorrect} = B, C, t)P(C)dC}\right)$$

1007 where $v_{incorrect}$ is the incorrect accumulator (not matching the sign of coherence) and $v_{correct}$ is

1008 the correct accumulator (matching the sign of coherence). This transformation provides a graded

1009 scale for betting that can be transformed into {high, low} responses by applying a cutoff value (θ)

1010 that imposes binary outcomes. To obtain the probability of a high bet we computed:

$$P(high\ wager) =$$

1011
$$\frac{\iint P(v_{right}|v_{left} = B, t, C, Logodds < \theta)P(t) + \iint P(v_{left}|v_{right} = B, t, C, Logodds < \theta)P(t)}{\iint P(v_{right}|v_{left} = B, t, C)P(t) + \iint P(v_{left}|v_{right} = B, t, C)\ P(t)}$$

1012 where $Logodds < \theta$ indicates integration over the area in which $Logodds$ is less than the cutoff

1013 value.

1014   Lastly, we found the best-fitting parameters to the model by using the joint probability of

1015 choice, RT, and wager as follows:

1016
$$P(Right, RT, High) = \prod_{tr=1}^{Trials} P(Right|RT, High) * P(RT|High) * P(High)$$

1017 We calculated the negative log likelihood of this by:

1018
$$-\log(P(Right, RT, High)) =$$
$$-\sum_{tr=1}^{Trials} \log(P(Right|RT, High)) + \log(P(RT|High)) + \log(P(High))$$

The full model had 6 or 7 free parameters, differing slightly between the two animals (see table

below). These included drift rate (K), bound (B), mean non-decision time (μ_{nonDT}), urgency max

(u_M), urgency half-life ($u_{\frac{1}{2}}$), and log-odds cutoff (θ). The urgency signal followed a hyperbolic

function for monkey G, requiring both parameters, and a linear function for monkey H, requiring

one parameter. Also, monkey H required separate non-decision time means for left and right

choices, and a 'wagering offset' (b_w) capturing a tendency to occasionally bet low even for the

highest coherence. Non-decision time standard deviation (σ_{nonDT}) was not a free parameter and

was instead established using psychophysical kernels (van den Berg et al., 2016a, Methods

section). Fitting was done using MATLAB's built-in function *fminsearch* applied in a grid search

method with 30 different starting points.

Monkey	Parameters	Number of Parameters

H	$K, B, \mu_{nonDT,Coh+},$ $\mu_{nonDT,Coh-}, u_M, \theta, b_w$	7
G	$K, B, \mu_{nonDT}, u_M, u_{\frac{1}{2}}, \theta$	6

1029

1030

Serial model

The serial model was constructed as a sequence of two 1D bounded accumulator (drift-diffusion)

models, one for choice followed by a second for confidence (Figure 1C; Moran et al., 2015;

Herregods et al., 2023). There are 6 main parameters: drift rate (K), choice bound (B_c), high

wager bound (B_h), low wager bound (B_l), mean non-decision time (μ_{nonDT}), and urgency signal

for only the confidence accumulator $(u_{M,Conf})$. Parameter estimation predominantly followed the

same logic as the parallel model, using the joint distribution of choice, RT, and wager to fit the

data, with a few minor differences. Computing the probability of rightward choice was similar to the

parallel model and used the following formula:

1040
$$P(Right|C) = \frac{\int P(v_1 = B_c \,|C, t)P(t)dt}{\int (P(v_1 = B_c \,|C, t) + P(v_1 = -B_c \,|C, t))P(t)dt}$$

1041 where v is the accumulator variable for the first 1D accumulator, and the other parameters are

1042 similar to the parallel model. The decision time distribution was calculated as:

1043
$$P(DT) = \int P_{choice}(t - z)P_{wager}(z)dz$$

1044 where P_{choice} is the probability of hitting a bound at time t for the first accumulator and P_{wager} is

1045 the probability of hitting a bound at time t for the second accumulator. For RT we followed the

1046 same procedure as the previous model. Lastly, to calculate the probability of betting high, we used

1047 the following equation:

1048
$$P(High \, wager|C) = \frac{P(v_2 = B_h|C, Choice = R)}{\int P(v_2|C, Choice = R) \, dv_2}P(Choice = R)$$

1049
$$+\frac{P(v_2 = B_h | C, Choice = L)}{\int P(v_2 | C, Choice = L)\, dv_2} P(Choice = L)$$

1050

Monkey	Parameters	Number of parameters
H	$K, B_C, B_h, B_l\ \mu_{nonDT,Coh+},$ $\mu_{nonDT,Coh-}, u_{M,Conf}, b_w$	8
G	$K, B_C, B_h, B_l, \mu_{nonDT},$ $u_{M,Conf}$	6

1051

Changes of mind (CoMs) and changes of confidence

Raw eye position data (sampled at 1000Hz) were converted to velocity and smoothed by applying

a 3rd-order low-pass Butterworth filter with a cutoff frequency of 75Hz (Orozco et al., 2021). Eye

position is a 2D vector containing X and Y position in degrees, while eye velocity was defined as

1D vector that combines the velocities for both directions (X and Y). To preprocess the data, we

first calculated a stricter time for saccade onset by applying a threshold of 20°/s onto the smoothed

velocity data. Subsequently, we centered the eye positions by subtracting the average of the first 5

ms before saccade onset. The initial choice and wager were defined by the location of the saccade

in 1 of 4 quadrants of the screen 5 ms after saccade detection. The final choice and wager

corresponded to the target at which the eye position settled within a 0.1 s grace period following

the initial saccade. This provided an initial and final choice and wager for every trial, allowing for

simple analyses like those for Figure 2C,D,E. CoM frequencies (Figure 2C,D) were conditioned on

the initial outcome; therefore, the frequencies reflect not the proportion of all trials but rather only

trials that initially reached a given outcome (error, correct, low, and high). Lastly, for the rightmost

panels of Figure 2E the probabilities are reflective of all trials, hence the values are much smaller

than on the other plots.

1068

Analysis of neural data based on preferred and chosen target

Two populations of neurons were established based on RF overlap of either the left-high or left-low

target. We computed four normalized firing rate responses for both populations of neurons, where

each response corresponds to one of the four chosen targets (Figure 4B & 4C). To combine across

neurons, we first detrended the responses of each neuron over the coherences of interest [-6.4%, -

3.2%, 0%, 3.2%, 6.4%]. Then the firing rates for each neuron (after smoothing each trial with a 0.1

s exponential filter) were averaged over all trials that met 3 conditions: 1) matched the chosen

target of interest, 2) contained a coherence of interest, and 3) had a RT longer than 0.3 s. Example

neurons in Figure 4A were not detrended or normalized but otherwise the procedure was the

same. The colored bars at the top of Figure 4B & 4C indicate statistical significance based on a

one-tailed t-test evaluating whether the response of the chosen target (aligned with the neurons'

RF) was higher than either of the other three chosen target responses. Given that the testing is

done over multiple timepoints, the one-tailed t-test alpha value was corrected using Šidák's

correction.

1083

Autocorrelation signatures of standard vs delayed accumulator dynamics

An accumulation of noisy evidence produces characteristic variance and autocorrelation

features that can be estimated from single neurons using procedures laid out by previous work

(Churchland et al., 2011; de Lafuente et al., 2015; Shushruth et al., 2018; Steinemann et al., 2022).

Applying the law of total variance to a doubly stochastic process, the variance in spike rate for a

given time bin is a summation of the variance of the underlying latent rate, termed variance of the

conditional expectation (VarCE), and the residual variance expected if the latent rate was constant,

known as point process variance (PPV). To calculate VarCE, one must subtract out the PPV from

the total measured variance. To do this we made two simple assumptions (Churchland et al.,

2011): 1) the observed spiking of a neuron follows a stochastic point process mediated by some

rate parameter, and 2) that at each time bin the PPV is proportional to the mean count:

$$Var(E[Y_i|X_i]) = Var(Y_i) - E[Var(Y_i|X_i)]$$
$$VarCE(Y_i) = Var(Y_i) - \varphi E[N_i]$$

1095

1096   where Y_i represents the random variable capturing the neuron's spike count at timepoint i, X_i is the

1097   random variable for the latent rate at timepoint i, and φ is a constant that is fitted to maximize how

1098   well the observed firing rates match an accumulation of independent identically distributed (iid)

1099   random numbers. $E[N_i]$ is the mean spike count at timepoint i. In addition, it follows that the law of

1100   total covariance is described using a similar equation:

1101
$$Cov(Y_i, Y_j) = Cov(E[Y_i|X_i], E[Y_j|X_j]) + E[Cov(Y_i, Y_j|X_i, X_j)]$$

The first term on the right-hand side is known as the covariance of conditional expectations

(CovCE), which is needed to compute the correlation of conditional expectations (CorCE). The

second term is the expectation of conditional covariance, and its diagonal is the PPV. To calculate

the CorCE, we made another assumption that when $i \neq j$, the expectation of conditional

covariance is zero because the variance from the point process should be independent across

timepoints (Churchland et al., 2011; although this may be untrue for adjacent time bins due to their

shared interspike interval). This simplification makes it possible to state that the CovCE, for $i \neq j$,

is equal to the measured covariance, and the diagonal of the CovCE is then the VarCE. It follows

that to calculate the CorCE, one must simply divide the CovCE by the VarCE:

1111
$$CorCE(Y_i, Y_j) = \frac{CovCE(Y_i, Y_j)}{\sqrt{VarCE(Y_i) * VarCE(Y_j)}}$$

where i and j are time points. The best fitting φ is then calculated by comparing the formulated

CorCE values onto theoretical or simulated correlation values that underlie the hypothesized

generative process (e.g., accumulation).

We tested two theoretical autocorrelation patterns, one pertaining to a standard drift

diffusion process and the other to a delayed drift diffusion process (Figure 4D). The standard

accumulation of iid random numbers was calculated using the following equation:

1118
$$\rho_{i,j} = \sqrt{\min(i,j) \Big/ \max(i,j)}$$

We used 6 different timepoints giving 15 unique combinations ($i = 1:6$ & $j = 1:6$, $i \neq j$). For the

delayed accumulation of iid random numbers, we used a simulation that accumulated noisy

normalized samples of numbers with mean [0.717, 0, -0.717]. We narrowed the simulation to the

first 6 timesteps to compare it to the results from the standard accumulation process. Additionally,

the delay component was constructed by uniformly sampling a value between 1-6, indicating when

the accumulation would begin. Using 10,000 trials we calculated the autocorrelation of the first 6

timesteps for this simulation providing 15 unique combinations ($i = 1:6$ & $j = 1:6$, $i \neq j$).

Additionally, we fit the φ, for both models, according to the following steps: 1) calculate the $E[N_i]$,

$Var(Y_i)$, and $Cov(Y_i, Y_j)$ from observed spikes, 2) compute $VarCE(Y_i)$ using an initial value of $\varphi =$

1, 3) calculate $CorCE(Y_i, Y_j)$ under the assumptions of mentioned above, 4) calculate the mean

squared error (MSE) between the empirical $CorCE(Y_i, Y_j)$ and the theoretical/simulated

autocorrelation values, $\rho_{i,j}$, and 5) iteratively update φ until the MSE between the $CorCE(Y_i, Y_j)$ and

$\rho_{i,j}$ reached the global minimum.

We used 6x60-ms time bins spanning from 170 ms after motion onset to 530 ms after

motion onset. We applied the analysis on trials with coherences of interest [-6.4%, -3.2%, 0%,

3.2%, 6.4%] and reaction times at least 630 ms to minimize bound effects. To combine across

neurons, we calculated the mean response for each time bin of each neuron across all trials and

subtracted that from the mean response for each time bin conditioned on the signed coherence.

This then gives a matrix of residuals that is of size $[neuron * trials \ \ x \ \ time \ bins]$, which is then

used to calculate a covariance matrix. Next, the VarCE is calculated by substituting the raw

variance for the diagonal in the covariance matrix, since the diagonal is the normalized population

variance, and φ is initiated at a value of 1. To calculate the empirical correlation values, each entry

in the covariance matrix is divided by $\sqrt{VarCE(Y_i) * VarCE(Y_j)}$. Lastly, using a fitting procedure

we compare the Fisher z-transformation of the empirical correlation with a Fisher z-transformation

of the ideal correlation and minimize the mean squared error (MSE) of the correlation matrix.

Testing for significant difference between standard and delayed accumulation was done

using a leave-one-out (LOO) cross-validation method. The metric used to test the validation was

the mean absolute percentage error (MAPE). MAPE allowed for comparison between the two

models because both models contained different dependent variables ($\rho_{i,j}$). This method provided

15 different MAPE values, for each model, which were then compared using a one-tailed t-test.

The model with the lowest percentage error distribution better captured the underlying

autocorrelation structure of the data (Figure 4E).

For Figure S5 we recalculated the VarCE but used 6x100-ms time bins spanning -50 ms

before motion onset to 550 ms after motion onset. Here we instead applied the analysis on all trials

irrespective of coherence. The CorCE statistical outcomes and preference for standard over

delayed accumulation process did not differ when using all the coherences. We quantified the

shaded errors bars by using a bootstrap method with 100 resamples.

1156

Population logistic decoder

Data were preprocessed by calculating spike counts in 100 ms time windows, stepping every 20

ms, through the first 600 ms after motion onset, and again separately for spikes aligned 400 ms

before and 200 ms after saccade onset. We looked only at trials with RTs 400 ms and longer. We

used two L1-regularized logistic decoders, one for choice and one for wager:

$$P_t(Right\ choice\ or\ High\ wager) = -\log(1 + \exp(-(w_0 + w * X)) - \xi\|w\|^2$$

where w represents a vector of weights at time t (vector length matches number of neurons), w_0 is

a bias term, and X is the spike count vector for each neuron in the session. The best

hyperparameter ξ was found using a 50-value grid search between [0 1000], using 5-fold cross

validation. The dataset was divided into a training set (90%) and test set (10%), the latter of which

was used to calculate the prediction accuracy (Figure 5B). If P_t was greater than 0.5 this would

indicate that the decoder predicted either a right choice (for the choice decoder) or high bet (for the

wager decoder). Values below 0.5 would indicate either a left choice or low bet. The performance

(accuracy) was defined based on the monkey's choice and wager at the end of the trial. To

compute a 'model decision variable' from neural activity we first take the trials in which the monkey

made a choice that aligns with the signed coherence (except for 0% coherence). Afterwards, we

simply take the log odds of a particular choice (e.g., $\log\left(\frac{P(right)}{1-P(right)}\right)$ for rightward choices) given the

ensemble spike counts up to time t on a given trial (Kiani et al., 2014; Peixoto et al., 2021).

Importantly, for Figure 5A and 5C we used the log odds irrespective of choice, therefore the results

combine $\log\left(\frac{P(right)}{1-P(right)}\right)$ for right choices and $\log\left(\frac{1-P(right)}{P(right)}\right)$ for left choices. Because these log

odds for right choice and left choice are predominantly symmetric, this increases statistical power.

For Figure 5C the log odds for wager are also combined in the following manner: $\log\left(\frac{P(high)}{1-P(high)}\right)$ for

high wagers and $\log\left(\frac{1-P(high)}{P(high)}\right)$ for low wagers.

To test whether the model decision variable (DV, log odds) for the choice decoder

contained a linear increase that was significantly dependent on motion strength, we utilized a linear

regression:

$$DV = \beta_0 + T * \beta_1 + Coh * \beta_2 + T * Coh * \beta_3$$

where β_0 is a bias term, T is time (20 ms time bins for 200-600 ms after motion onset), Coh is

motion coherence level, and $\beta_{1,2,3}$ are the weights accompanying the predictor variables. If the β_3

weight was significantly different from zero ($P < 0.05$), then the modulation of log odds by motion

strength was deemed significant. Importantly, to compute this linear regression we only used the

mean DV shown in Figure 5A, excluding data cut off at the mean RT for each individual

coherence.

As previously mentioned, both logistic decoders provide weights for each neuron through

time. Therefore, to test whether our sample of neurons contained a single population that

contributes approximately equally to choice and wager, we calculated the correlation between the

weight magnitudes (irrespective of sign) as well as the distribution of the difference in weight

magnitude. The weights were preprocessed by taking their absolute value because of our interest

in magnitude and not direction. To calculate the correlation, we compute the Pearson's correlation

between absolute weights for all our neurons at each time point. We collapsed over time by

averaging over the first 600 ms after motion onset and last 400 ms before saccade onset (Figure

5D, red line). We computed significance by randomly permutating the choice and wager weights

1000 times (Figure 5D, blue distribution). Additionally, the choice and wager decoder absolute

weights were also subtracted from one another to create a distribution which informs whether there

is a single population equally contributing to both choice and wager. Significance was evaluated

using the Hartigan's dip test, which tests whether a distribution is unimodal or bimodal.

To determine the trial-by-trial relationship between the choice and wager decoder we first

tested whether the wager decoder was predictive of the DV (log odds). Trials where categorized as

decoded-low or decoded-high confidence by calculating the mean $P(High)$ for the wager decoder

from saccade initiation till 200 ms after. Values above (below) .5 indicated a decoded-high

(decoded-low) wager. We strictly looked at trials with 0% coherence to try and remove any effects

of coherence on the results. Results for Figure 6A were calculated by then averaging the DV on

these decoded-high and decoded-low trials. Significance bars were calculated using a one-tailed t-

test with Šidák's correction. Importantly, differences in peak DV around saccade onset (Figure 6A)

highlight changes in the ratio $\frac{P(right)}{1-P(right)}$.

The temporal offset between the peak log odds for choice and wager (Figure 5B) might

suggest that although deliberation for choice and confidence begins simultaneously, the updating

accrues some lag as the trial progresses. To test this, we related the log odds information of the

choice decoder to the $P(High)$ from the wager decoder. As shown in Figure 6A, there is a link

between the model DV and $P(High)$ that can be exploited to understand whether the temporal

updating is in sync or if there is some lag. In this case, the alternative hypothesis, given that the

peak of $P(High)$ is later than $P(Right)$, is that updating of the DV for choice precedes the updating

for wager. Figure 6B was calculated by using the 3 separate 400-ms time windows described in the

legend. The independent variable, which is $P(right)$ from the choice decoder, was corrected so

that values near 0.5 (chance level) were close to zero and values moving away from 0.5 in either

direction (better predicting left or right choice) became closer to one. This was done using the

following equation:

$$corrected\ P(right) = abs(P(right) - .5) * 2$$

In essence, this remapping of $P(Right)$ is changing the property of choice decoding strength so

that it is monotonic or linear. This transformation makes it possible for a linear relationship to exist

between corrected $P(Right)$ and $P(high)$. To capture this relationship and its dependency on time

lag, we applied a linear regression, using the corrected $P(Right)$ at time t, to the dependent

variable $P(High)$ at time $t + \Delta t$, where Δt range from +/- 200 ms. To quantify how informative

corrected $P(Right)$ is of $P(High)$ we used an R^2 measurement at each time lag. Figure 6B displays

a corrected R^2 which is simply the R^2 value after subtracting out the average R^2 values when the

time series of the decoders for each trial are randomly permuted.

1233

1234

1235

1236

1237

1238

1239

1240

1241

1242

1243

1244

1245

1246

SUPPLEMENTARY FIGURES

Figure S1. Three behavioral variables as a function of motion strength (% coh), including only the identical random seed trials ('double-pass' procedure (Bondy et al., 2018) adapted for 4 options), to control for motion energy within each coherence. (A) Proportion of rightward choices as a function of motion strength. Both monkey H (top) and monkey G (bottom) showed significant differences in sensitivity between high- and low-bet trials. Smooth curves are from logistic regression. (B) Mean RT as a function of motion strength. Monkey H (top) displayed no differences in RT between high and low wager when controlling for motion energy, whereas monkey G (bottom) still showed large differences for all but the highest two coherences. Smooth curves show Gaussian fits. (C) Proportion of high bets as a function of motion strength. Both monkeys bet high more frequently as motion strength increased, irrespective of accuracy. Error bars in all plots are +/- SE.

Figure S2. Session-by-session sensitivity and amplitude parameters from fitting logistic and Gaussian functions to choice and RT, respectively. The vast majority of individual sessions showed greater sensitivity (accuracy) and faster RT amplitude when the monkey bet high vs. low.

Figure S3. (A) Accuracy as a function of RT quantile, split by motion strength (% coh). Accuracy tended to decrease as a function of RT ($p < .0085$ for every coherence except 0% in both monkeys and 51.2% in monkey G). (B) Proportion of trials with a high bet as function of RT. Colors same as A. (C) Accuracy as a function of motion energy. Colors represents five different RT quantiles. Significant increases in accuracy were observed across all RT quantiles for both monkeys (p<0.01). (D) Proportion of trials with a high bet as a function of motion energy. Colors same as C.

Figure S4. Serial and parallel model fits on unconditioned data. (A,C) Serial model fitted to choice, RT, and wager as a function of motion strength (% coh). (B,D) Parallel model fitted to choice, RT, and wager as a function of motion strength (% coh). First two columns correspond to monkey H and the last two to monkey G.

Figure S5. Variance of the conditional expectation (VarCE) estimated for the left-high and left-low populations of neurons. In both monkeys (H=top, G=bottom) VarCE begins to increase at approximately 0.2 s from motion onset, then decreases near saccade onset. Colors represent the two populations, and the shaded regions are standard errors calculated using a bootstrap.