Neural basis of concurrent deliberation toward a choice and degree of confidence

Miguel Vivar-Lazo[1] & Christopher R. Fetsch[1,2]

[1]Zanvyl Krieger Mind/Brain Institute, [2]Solomon H. Snyder Department of Neuroscience,

Johns Hopkins University, Baltimore, MD, USA; correspondence: cfetsch@jhu.edu

ABSTRACT

Decision confidence plays a key role in flexible behavior and (meta)cognition, but its underlying neural mechanisms remain elusive. To uncover the latent dynamics of confidence formation at the level of population activity, we designed a decision task for nonhuman primates that measures choice, reaction time, and confidence with a single eye movement on every trial. Monkey behavior was well fit by a bounded accumulator model instantiating parallel processing of evidence, rejecting a serial model in which the choice is resolved first followed by post-decision accumulation for confidence. Neurons in area LIP reflected concurrent accumulation, exhibiting covariation of choice and confidence signals across the population, and within-trial dynamics consistent with parallel updating at near-zero time lag. The results demonstrate that monkeys can process a single stream of evidence in service of two computational goals simultaneously—a categorical decision and associated level of confidence—and illuminate a candidate neural substrate for this ability.

INTRODUCTION

Evolution has endowed humans and some animals with the ability to assess the quality of their own decisions. This typically manifests as a degree of confidence, defined as an internal estimate of the probability of being correct. Confidence facilitates learning in the absence of explicit feedback (Daniel & Pollmann, 2012; Guggenmos et al., 2016) and guides decisions that are part of a sequence or hierarchy (Sarafyazd & Jazayeri, 2019; Purcell & Kiani, 2016; van den Berg et al., 2016b). When feedback does occur, confidence informs whether the outcome is surprising (i.e., a high confidence error), driving an increase in learning rate (Rescorla & Wagner, 1972; Sutton & Barto, 1992). Indeed, it can be shown that the optimal weights for converting sensory neuron activity to decision evidence can

only be obtained with a learning rule that is proportional to confidence (Drugowitsch et al., 2019).

Despite its broad importance, the mechanisms that give rise to confidence formation remain poorly

understood. Here we use a novel choice-RT-wager paradigm to dissect the temporal evolution of

choice and confidence signals in decision-related neuronal populations. Beyond informing models of

learning and decision making, this approach should help advance our understanding of the

computations underlying metacognition itself.

Most existing models fall into one of two main alternatives for the dynamics of choice and

confidence formation. The *serial* hypothesis states that the two computations make use of temporally

nonoverlapping streams of evidence (Herregods et al., 2023; Moran et al., 2015; Pleskac & Busemeyer,

2010). In contrast, the *parallel* hypothesis proposes simultaneous initiation and temporally overlapping

(concurrent) computation of choice and confidence (Dotan et al., 2018; van den Berg et al., 2016a; Xue

et al., 2023) — though this need not exclude additional post-decision processing (Desender et al.,

2021; Maniscalco et al., 2021; see Discussion). Both hypotheses have received support from

behavioral, modeling, and human EEG data (Murphy et al., 2015; Gherman & Philiastides, 2015;

Pereira et al., 2020; Balsdon et al., 2021; Dou et al., 2024), but to date there have been no single-

neuron or population recording studies that directly address this question. This is important because

discerning between the two strategies could benefit from the spatial and temporal resolution afforded by

spiking data, and because ultimately we seek biological mechanism. Also, most tasks in the literature

(including waiting-time assays; Lak et al., 2014; Stolyarova et al., 2019) impose a time delay between

decision and confidence reporting, potentially biasing participants toward a post-decisional strategy.

We circumvented these issues by training monkeys to report choice and confidence

simultaneously in a response-time (RT) paradigm ('peri-decision wagering', peri-dw), building on

previous work in human participants (Kiani et al., 2014a; van den Berg et al., 2016a). Our aim was not

to challenge post-decisional accounts of confidence in a broad sense. Rather, the task was designed to

unveil whether a serial process is essential for a monkey's deliberation about both aspects of the

decision, or if this process is fundamentally parallel. Our goal was twofold: to evaluate competing

hypotheses on equal footing within the framework of bounded evidence accumulation, and to shed light

on the underlying neural mechanism. Notably, the peri-dw task measures choice, RT, and confidence on every trial, unlike 'opt-out' or uncertain-response paradigms (Kiani et al., 2009; Smith et al., 2012; Komura et al., 2013; Fetsch et al., 2014a; Li et al., 2023), allowing us to relate neural activity to all three measures on a trial-by-trial basis.

While monkeys performed the task, we recorded population activity in the ventral portion of the lateral intraparietal area, LIPv (Shadlen & Kiani, 2013). Previous work has shown that LIPv (hereafter LIP) contains a representation of a decision variable (DV) that predicts choice and RT (Roitman & Shadlen, 2002), as well as confidence in an opt-out task (Kiani & Shadlen, 2009). Recent work using high-density probes found that the DV representation is observable on single trials (Steinemann et al., 2024) and thus is not an artifact of averaging (Latimer et al., 2015). Lastly, although one study failed to observe behavioral effects of LIP inactivation (Katz et al., 2016), at least four others support a causal role for this area in visuo-motor decisions (Hanks et al., 2006; Zhou & Freedman, 2019; Chen et al., 2020; Jeurissen et al., 2022). This makes LIP a sensible target for investigating the neural dynamics of choice and confidence formation.

Using a combination of computational modeling and model-free analyses, we first show that a parallel evidence accumulation mechanism can explain all three features of the decision in this task, as anticipated by previous work (Fetsch et al. 2014a; Kiani et al., 2014a). Then, using single-neuron analyses and population decoding, we show that the DV representation in LIP reflect concurrent deliberation toward a choice and associated wager. This work expands the behavioral toolkit for studying confidence in animal models, and supports a role for posterior parietal cortex in decisions guided by an online estimate of confidence.

RESULTS

We recorded 407 neurons in area LIP of two rhesus monkeys (*Macaca mulatta*; 207 in monkey H, 200 in monkey G) while they performed the peri-dw task (Figure 1A). Each saccade target corresponds to a motion direction decision (left or right) and a wager (high or low) on the correctness of that decision. Although behaviorally the task amounts to a choice among four options, we refer to the left-right

decision as 'choice' and the high-low decision as 'wager' or 'bet', both for simplicity and because the

results support this interpretation. Monkeys were rewarded or penalized based on the conjunction of

accuracy and wager (Figure 1B): a larger drop of juice for high vs. low bets when correct, and a time

penalty for high bets when incorrect (no penalty for a low-bet error). As in previous studies (e.g.,

Roitman & Shadlen, 2002), monkeys showed greater accuracy (Figure 1B, left) and faster RTs (Figure

1B, middle) when the motion was strong compared to weak (coh near 0%). Motion strength also

influenced wagering behavior in the expected manner; namely, the probability of betting high increased

with greater motion strength in either direction (Figure 1B, right). Importantly, the behavior shows that

the low-bet option did not correspond to opting out of the motion decision: accuracy remained high on

low-bet trials, and choice and RT still varied systematically with motion strength in a manner consistent

with a deliberative process (see Model Fitting section below).

Crucially for a behavioral assay of confidence, the monkeys' sensitivity was greater when

betting high versus low (Figure 1B left, red vs. blue; $p<10^{-258}$, logistic regression). This was true even

when controlling for variability in motion energy within each coherence level, by leveraging multiple

repeats of the same random seed (Figure S1A; monkey H: $p<10^{-4}$, monkey G: $p<10^{-6}$; see Methods).

Additionally, we fit a session-by-session logistic model separately for high and low bet trials, providing

two distributions of weights relating motion strength to choice, and found that they were significantly

different (Figure S2A; monkey H: $p<10^{-19}$, monkey G: $p<10^{-37}$). Both monkeys also showed faster RTs

when betting high versus low, for all but the largest motion strengths (Figure 1B middle, red vs. blue;

asterisks indicate $p<0.0045$ by t-test, Bonferroni corrected). Similarly to choices, we fit a Gaussian

function to the average RT as a function of motion strength for each session, separately for high and

low bet trials. The amplitude parameters of the fitted Gaussians were greater for low vs. high bets

(Figure S2B; monkey H: $p<10^{-7}$, monkey G: $p<10^{-25}$, paired t-test), indicating greater modulation of RT

by motion strength when the monkey indicated low confidence. Lastly, we examined wagering behavior

as a function of RT (Figure 1B right), separately for each individual motion strength (Figure S3A,B). For

most motion strengths, the monkeys bet high less often for longer RTs (Figure S3B; $p<.0085$ for both

Figure 1. Task sequence, behavioral performance and model schematics. (A) After the monkey acquires fixation, four targets are presented, followed by a random-dot motion stimulus. At any time after motion onset the monkey can make a saccade to one of the targets to indicate its choice and wager. The table at the right illustrates the possible outcomes for each trial: if correct, a high bet yields a larger juice reward compared to a low bet, but if incorrect, a high bet incurs a 2-3 s time penalty (added to the next trial's pre-stimulus fixation period). Low-bet errors were not penalized. (B) Behavioral results pooled across two monkeys (N = 372 sessions, 401,530 trials, including sessions without neural recording). Each ordinate variable is plotted as a function of signed motion strength (%coh, negative=leftward, positive=rightward). Choice and RT functions are shown conditioned on the wager (low=red, high=blue). Error bars (SE) are smaller than the data points. Smooth curves show logistic regression (choice) and Gaussian (RT, wager) fits. (C) The serial model begins with a single accumulator with symmetric bounds (standard 1D drift-diffusion model). Arriving at one of the bounds terminates the primary decision (h_1 vs. h_2 = left vs. right in our task) and initiates a secondary process that accumulates evidence toward a 'high' or 'low' bound governing the wager. (D, left) The parallel model comprises two concurrent accumulators that are partially anti-correlated (Kiani et al., 2014a). The first bound to be crossed (the 'winner') dictates the choice and decision time, whereas the losing accumulator dictates confidence by way of a mapping (right) between accumulated evidence and the log odds that the choice made was the correct one (color scale).

monkeys for every coherence except 51.2%, Cochran-Armitage trend test with Bonferroni correction).

This pattern is remarkably similar to that observed in humans on a similar task (Kiani et al., 2014a),

where the results argued that confidence depends on both evidence strength and elapsed time. As in

that previous study, the pattern remained significant when controlling for variability in motion energy

across trials of a given coherence (Figure S3D; monkey H: $p=0.0003$, monkey G: $p=0.0056$, interaction

term between motion energy and RT quintile using ANCOVA).

An inverse relationship between response time and confidence is a classic psychophysical

result (Henmon, 1911; Kellogg, 1931; Audley, 1960), replicated in more recent human work (e.g. Kiani

et al., 2014a; Desender et al., 2021; Dou et al., 2024). Observing it in monkeys, for the first time to our

knowledge, supports the notion that the peri-dw assay is a valid measure of confidence, and it is

consistent with a family of accumulator models as addressed below. Note that we sometimes refer to

the wager (or proportion of trials with a high bet) as 'confidence' for convenience, acknowledging that

confidence is a latent cognitive variable, and any behavioral measure is bound to be imperfect.

Model-free analyses reveal temporal overlap in choice and confidence computations

Although the choice and wager were indicated with a single eye movement, this does not necessitate

simultaneity in the processing of evidence. Different temporal windows of the stimulus could covertly be

used to support the two elements of the decision, which would then only be reported when both were

resolved. To test whether monkeys use a consistent serial strategy (resolving choice first and then

confidence, or vice versa) we calculated the influence of stimulus fluctuations on choice and confidence

as a function of time (psychophysical kernels; Kiani et al., 2008; Nienborg & Cumming, 2009;

Zylberberg et al., 2012). Briefly, we quantified the motion energy for each trial and video frame by

convolving the random-dot pattern with two pairs of spatiotemporal filters aligned to leftward and

rightward motion (Adelson & Bergen, 1985). We then partitioned trials by outcome and plotted the

average relative motion energy (residuals) for each outcome as a function of time.

Psychophysical kernels for choice are plotted in Figure 2A. Rightward choices were preceded by

more rightward motion energy throughout most of the trial (red line), and the same was true for leftward

choices and leftward motion (blue). The kernels for right and left choice began to separate about 100

ms after motion onset and remained so until ~100 ms before saccade initiation. This clear separation,

aligned on both motion onset and saccade, suggests that the monkeys used essentially the entire

stimulus epoch, on average, to decide motion direction. For confidence, we calculated the kernels by

taking the difference between the motion energy time series for high and low bets associated with a

specific choice (van den Berg, 2016a). For high minus low wager on rightward choice trials, motion

energy values were above zero, indicating an excess of rightward motion on high-bet choices

compared to low-bet choices (Figure 2B, green). Similarly, for left choice trials the difference in motion

energy was below zero, indicating more leftward motion on high vs. low bets (Figure 2B, purple). This

analysis shows that both early and late motion evidence is leveraged to inform confidence, in both

monkeys. Comparison of the traces in Figure 2A vs. 2B might suggest that the utilization of the stimulus

for confidence does not identically overlap with choice, especially for monkey H. However, the

substantial overlap does appear to rule out a consistent temporal segregation, such as an obligatory

post-decision mechanism for confidence. Of course, psychophysical kernels rely on trial averages and

cannot resolve dynamics of individual decisions; we address this shortcoming below using neural

decoding.

When decisions are reported with an arm movement, human subjects occasionally alter their

reach trajectory in a manner that suggests a 'change of mind' (CoM) based on continued processing of

evidence after movement initiation (Resulaj et al., 2009; van den Berg et al., 2016a). Saccadic choices

are generally considered incompatible with CoMs because of their speed and ballistic nature (Resulaj

et al., 2009; but see McPeek et al., 2000; Caspi et al., 2004); nevertheless, we were able to identify a

small subset of trials with multiple saccades in quick succession that revealed putative CoMs (Figure

2E inset, see Methods). These trials showed characteristic features of CoMs (Figure 2C-E), including

greater frequency on difficult vs. easy trials (Figure 2E; monkey H: $p = 0.0076$; monkey G: $p<10^{-6}$,

Cochran-Armitage test). Changes from incorrect to correct were more likely when motion strength was

high (Figure 2C red line; monkey H: $p < 0.0001$; monkey G: $p < 10^{-5}$), whereas correct-to-error CoMs,

occurring sparingly, were more likely when motion strength was low (Figure 2C, dark red line; monkey

Figure 2. Psychophysical kernels and changes-of-mind for choice and wager. (A) Motion energy profiles conditioned on right and left choices (red and blue, respectively), aligned to motion onset and saccade onset. Shaded regions indicate SEM. Left column is for monkey H and the right for monkey G. Black line at top indicates when right and left traces were significantly different from each other (p<0.05, t-test with Šidák Correction for 140 frames). (B) Confidence kernels computed as the difference in motion energy between right-high and right-low choices (green), and the difference between left-high and left-low choices (purple), aligned to the same events as (A). Colored lines at top of graph indicate when the corresponding traces were significantly different from zero (p<0.05, t-test with Šidák correction). (C) Proportion of change-of-mind (CoM) trials that start with an initial error (light red) or correct (dark red) and end as correct or error, respectively, as a function of motion strength. (D) Proportion of trials that start with an initial low wager (light blue) or high wager (dark blue) and end as high or low wager, respectively, as a function of motion strength. (E) Proportion of trials that are CoMs (of choice, wager, or both) as a function of motion strength. In C-E, top row shows data from monkey H and bottom row is monkey G. Insets show example eye trajectories from choice (top) and wager (bottom) CoM trials.

H: p < 0.0012 monkey G: p < 10^{-5}). We also observed changes from low to high confidence, which for

one monkey were more frequent with greater motion strength (Figure 2D blue line; monkey H: p < 10^{-60}

monkey G: p = 0.944), as shown previously in humans (van den Berg et al., 2016a). The existence of

CoMs and changes of confidence (sometimes both on the same trial) in the peri-dw task suggests that

both dimensions of the decision were subject to revision at the time of the initial saccade. This argues

against a strictly serial process, although it also highlights a brief window of potential post-decision

processing, even for saccadic choices (McPeek et al., 2000; Caspi et al., 2004).

Model fitting favors parallel deliberation for choice and confidence

Previous studies have typically focused on either a serial (Pleskac & Busemeyer, 2010; Moran

et al., 2015) or a parallel (Vickers, 1979; Shadlen & Kiani, 2013) framework for confidence. Thus,

explicit comparisons of these models have generally been qualitative because of variations in task

design across studies (but see Shekhar & Rahnev, 2024). Here we provide a quantitative comparison

of the two classes of model applied to the same data from the peri-dw task. Our exemplar of the serial

strategy is a one-dimensional drift-diffusion model (DDM) with post-decision accumulation for

confidence (Moran et al., 2015; Herregods et al., 2023; Figure 1C). The choice is determined by which

of two primary decision boundaries is crossed, and the wager by a second set of bounds around the

primary (winning) bound. The observed RT is the sum of the time taken to reach both bounds, plus

non-decision time. Our implementation of a parallel strategy is a two-dimensional DDM, where a

common accumulation epoch governs both choice and confidence (Kiani et al., 2014a; van den Berg et

al., 2016; Figure 2B). Here there are two accumulators integrating evidence in support of the two

alternatives, equivalent to an anticorrelated race. Two accumulators are necessary because the

winning accumulator determines the choice and RT while the losing accumulator is leveraged to

compute confidence. In contrast, the serial model uses two separate epochs of accumulation to inform

choice and confidence, and therefore requires only a single accumulator. Note that the key distinction is

serial vs. parallel, not 1D vs. 2D; we chose these specific variants based on the leading candidates in

the literature.

The smooth curves in Figure 3 and Figure S4 are fits to the serial (A and C) and parallel models

(B and D) for the two monkeys. Both models capture the general trends in choice, RT, and wager

across motion strengths, at least when pooled across correct/incorrect and high/low wager trials (Figure

S4), and both qualitatively predict greater sensitivity and faster RTs for high vs. low wagers. However,

in monkey G the serial model was unable to capture the large difference in reaction time between high

Figure 3. Comparison of serial and parallel model fits. Columns (A) and (B) show the results from monkey H, while (C) and (D) are for monkey G. Within each monkey, the left column (A&C) shows fits to the serial model and the right column (B&D) the parallel model. Top row shows proportion of rightward choices as a function of motion strength (%coh), conditioned on high and low bet trials (red and blue, respectively). The solid dots are empirical data points and solid lines are model fits. Middle row shows mean reaction time in the same format. Bottom row shows proportion of high bets as a function of motion strength (% coh), conditioned on correct vs. error trials (magenta and green, respectively).

and low bet trials (Figure 3C, middle). The smaller RT difference in monkey H was well handled by the

serial model (Figure 3A, middle), but this came at the cost of a slightly poorer fit to the wager-

conditioned choice data (Figure 3A vs. B, top). Thus, the behavioral differences between the two

animals served to highlight complementary strengths of the parallel model: its ability to explain a broad

range of confidence-RT relationships while also tolerating a more subtle difference in sensitivity on high

vs. low-bet trials. Quantitative model comparison supported these observations: Bayesian information

criterion (BIC) was lower for the parallel vs. the serial model (monkey H: 8.24×10^5 (parallel) $< 8.79 \times 10^5$

(serial), monkey G: 1.21×10^6 (parallel) $< 1.30 \times 10^6$ (serial)).

More strikingly, the serial model failed to reproduce the confidence pattern on error trials (Figure 3, bottom row; BIC for monkey H: 1.79×10^4 (parallel) < 1.85×10^4 (serial), monkey G: 3.26×10^4 (parallel) < 3.71×10^4 (serial)). In general, confidence increases as a function of stimulus strength for correct choices—which makes intuitive sense—but empirically it often *decreases* with stimulus strength on incorrect trials. This characteristic pattern has been proposed as a statistical signature of confidence in behavior (Sanders et al., 2016) and brain activity (Kepecs et al., 2008; Rolls et al., 2010; Komura et al., 2013; Bang et al., 2020). In contrast, we (Figure 3, bottom row) and others (Kiani et al., 2014a; van den Berg et al., 2016a) observed that confidence increases with motion strength even for errors. As noted previously (Kiani et al., 2014a; Fetsch et al., 2014b; Desender et al., 2021; Khalvati et al., 2021), these conflicting findings can be explained by the relative timing of choice vs. confidence. Resolving choice first followed by confidence later allows for revision of the confidence judgment upon further deliberation. Incorrect choices when the stimulus was strong are more likely to undergo such revision, as further processing reveals that the initial choice was incorrect. However, when choice and confidence are reported simultaneously there is little or no time for revision, and thus confidence on error trials either increases or remains flat as a function of stimulus strength (Kiani et al., 2014a; van den Berg, 2016a, Desender et al., 2021). For this reason, the serial model tested here simply cannot reproduce the qualitative trend in error-trial confidence we observed empirically (note that the green curves in Figure 3, bottom, are a prediction, not a fit). In summary, although basic behavioral patterns are reasonably well predicted by the serial model, model comparison favors a process where evidence is accumulated in parallel for constructing a decision and associated level of confidence.

LIP neurons show signatures of concurrent accumulation

Putative DV representations have been observed in several subcortical and cortical areas, including LIP (Shadlen & Kiani, 2013), as well as in aggregate signals observable with noninvasive methods in humans (O'Connell & Kelly, 2021). Although the widespread 'ramping' pattern of activity does not uniquely identify a process of evidence accumulation, a large body of work supports the assertion that LIP activity reflects such a process during the random-dot motion task. We reasoned that, if choice and

confidence were resolved concurrently during motion viewing (parallel model), the ramping activity

should begin to predict both dimensions of the eventual saccade at the same time, classically around

200 ms after motion onset (Roitman & Shadlen, 2002). Alternatively, if choice were to be deliberated

first followed by confidence later (serial model), this temporal separation should be evident in the

divergence point of neural activity traces conditioned on the four outcomes.

These traces are shown in Figure 4A for four example neurons. The highest firing rate

corresponds to choices made into the receptive field (RF) of the neuron, which was almost always in

the left (contralateral) hemifield but was equally likely to overlap the high or low wager target. The

relative ordering of the remaining three traces differs across neurons, possibly due to idiosyncratic RF

properties or nonspatial decision signals. The key observation is that the activity preceding saccades to

the preferred wager target (low or high) diverges from the activity for the other wager target (high or

low) at about the same time as it diverges from the traces for ipsilateral choice (right-low and right-

high). This pattern is present in each example neuron as well as in the population averages (Figure

4B,C). There is no evidence that ramping activity consistently predicts the left-right choice sooner than

the high-low one (or vice versa), as expected under a serial model. Instead, to the extent the activity

reflects accumulation of evidence favoring the target in the RF (see below and Discussion), the results

support a model in which such accumulation underlies concurrent deliberation toward a choice and

confidence judgment.

To dig deeper into the nature of the observed ramping signals, we tested for statistical

signatures of a noisy accumulation process (Churchland et al., 2011; de Lafuente et al., 2015;

Shushruth et al., 2018; Steinemann et al., 2024): increasing variance of the latent rate as a function of

time (variance of conditional expectation, VarCE) and a characteristic autocorrelation pattern in this

latent signal (correlation of conditional expectation, CorCE). These signatures follow from considering

neuronal spiking as a doubly stochastic process described by a Poisson distribution with an underlying

rate that varies within and across trials. For stochastic bounded accumulation, the first prediction is that

VarCE should increase linearly with time during deliberation, then decrease near the saccade as the

bound is reached. Second, correlations between firing rates at adjacent time points (t and t+1) should

Figure 4. Temporal properties of neural activity in LIP during the peri-dw task. (A) Firing rate of example units split by choice/wager outcome, aligned to motion onset and saccade onset. (B) Population average firing rate (normalized) for neurons with an RF overlapping the left-low target. Colored bars at top indicate when the corresponding trace is significantly below the trace for choices into the RF. (C) Same as B but for left-high neurons. Only low-coherence trials (0, +/- 3.2%, +/- 6.4%) are included in A-C. (D) Theoretical autocorrelation matrix of a standard ideal accumulation process (left) and a delayed accumulator (right; see Methods). (E) Projection of theoretical autocorrelations for top row (gray dotted) and first juxtadiagonal (gray solid) along with the corresponding data after fitting the phi parameter (Methods). Red and blue represent the two populations shown in B,C, pooled data from both monkeys.

increase for pairs of bins further out in time from stimulus onset (t+n and t+n+1, as n increases). Third,

the correlation between two time points should decrease as the distance between them increases (t

and t+1 versus t and t+5; Figure 4D, left & Figure 4E, left).

The results supported all three predictions. After 200 ms following motion onset, VarCE shows a

roughly linear increase for at least the next 400 ms (Figure S5, left; left-high neurons, monkey H: p <

10^{-7}, monkey G: p < 10^{-13}; left-low neurons, monkey H: p < 10^{-19}, monkey G: p = 0.0014; linear

regression), then decreases near saccade initiation (Figure S5, right; left-high neurons, monkey H: p =

0.015, monkey G: p = 0.0016; left-low neurons, monkey H: p < 10^{-4}, monkey G: p < 10^{-7}). For CorCE,

the results from both monkeys were reasonably well matched to the predictions (Figure 4E, left;

monkey G: R^2 = 0.74 and 0.79 for left-high and left-low neurons, respectively; monkey H: R^2 = 0.69 and

0.79, respectively).

These dynamics in variance and autocorrelation are consistent with an underlying neuronal

process that reflects accumulation, and are not easily explained by alternative accounts of LIP ramping

activity such as a gradual shift of attention or simple movement preparation. Critically, the patterns were

present over the same time window in both the high- and low-preferring populations. This argues

against a form of the serial model in which choice is initially resolved by considering only one pair of

targets, followed by a shift to the other pair after some time has elapsed. We explicitly tested this by

computing the expected autocorrelation under a simulated process where integration is delayed by a

random amount of time. Fitting such a model to the data generated a qualitatively and significantly

inferior fit to the CorCE prediction, when contrasted to the standard integration (Figure 4E, left vs. right;

monkey H: p < 0.008, monkey G: p < 0.012 for both left-high and left-low populations). Taken together,

the results favor a parallel model in which deliberation occurs simultaneously between both the high

and low pairs of targets. What remains to be tested is whether and when these accumulation signals

are predictive of the monkey's choice and wager on individual trials.

Single-trial decoding reveals links between choice and confidence signals in LIP

Thus far most of our analyses have relied on trial averages, potentially obscuring the dynamics of

individual decisions. We therefore turned to a population decoding approach (Kiani et al., 2014b;

Kaufman et al., 2015; Peixoto et al., 2021; Steinemann et al., 2024; Charlton & Goris, 2024), leveraging

the simultaneous recording of neural ensembles to more directly address the question of parallel vs.

serial deliberation. We trained two logistic classifiers, one for the binary choice and another for the

binary wager, using the spike counts from the neurons recorded during each session (mean = 14

units/session). The analysis determines the linear weight for each neuron, at each time point, that

maximizes the probability of predicting the observed choice or wager (Methods). We can then extract a

'model decision variable' which is simply the log odds of a particular choice or wager as a function of

time, according to the decoder, based on the population spike counts on a given trial. This quantity is

also known as prediction strength or certainty (Kiani et al., 2014b; Peixoto et al., 2021). To facilitate

comparison of the two decoders, we collapsed across left/right choices (and high/low wagers) such that

positive values of the model DV correspond to correct prediction of either choice (or wager), rather than

exhibiting symmetry around zero as in previous work.

For both monkeys, the model DV ramped up starting about 200 ms after motion onset (Figure

5A), as shown previously. The DV dynamics differed for the two animals, but both exhibited a ramping

slope that depended on motion strength (monkey H: $p < 0.001$, monkey G: $p < 10^{-4}$, linear regression).

Cross-validated prediction accuracy also ramped up starting at this time, simultaneously for both the

choice and confidence decoders (Figure 5B). Horizontal bars at the top of the plot indicate significant

differences from chance level, which occurred for both decoders starting around 200 ms and persisted

until saccade onset. At their peaks, both performed well above chance on the test set (Figure 5B), but a

notable difference is the timing of the peaks, which for choice is just before saccade onset and for

wager is slightly after the saccade (Figure 5B, right). The black bar in Figure 5B indicates a period near

the saccade with a significant difference in prediction accuracy between the decoders, highlighting an

epoch where choice accuracy has peaked but wager accuracy continues to increase. This temporal

offset is not simply a product of the binary classification method but also reflects graded prediction

strength (log odds or model DV): the log odds for both choice and wager were significantly different

from chance after 200 ms and persisted until saccade onset (Figure 5C). As with prediction accuracy,

the initial peak for choice is near saccade onset while the peak for the wager occurs about 100 ms after

the saccade. We speculate that this late peak may be related to continued evaluation of evidence for a

313   possible CoM (see below), although we cannot exclude the possibility of a signal related to expectation

314   of outcome (reward or penalty).

Figure 5. Population decoding of LIP activity supports concurrent readout of choice and wager from a unimodal population. (A) Log odds ('model decision variable') quantifying prediction strength for the choice decoder as a function of time, aligned on motion onset and conditioned on motion strength. Left graph is monkey H and the right graph is monkey G. (B) Prediction accuracy (proportion correct binary classification in the test set), for both the choice (gray) and wager (brown) decoders, as a function of time and aligned to motion onset and saccade onset. Shaded regions around the traces indicate SEM. Data are from both monkeys. Gray and brown bars at top indicate when accuracy for the corresponding decoder was significantly greater than chance. Black bar indicates when prediction accuracy was significantly different for choice vs. wager. (C) Log odds for both choice and wager decoders as a function of time and aligned to motion onset and saccade onset. Line color, error shading, and significance bars are similar to 5B. (D) Correlation between the magnitude of choice and wager decoder weights (red line) compared to the value expected by chance (shuffled data). (E) Histogram of the difference between choice and wager decoder weights. D and E show pooled data from both monkeys.

Regardless, the results in Figure 5B and 5C offer clear support for parallel deliberation for

choice and wager, refuting a temporal bottleneck associated with a serial process. However, a different

form of bottleneck might exist within the population, manifesting as distinct subsets of neurons

supporting choice and wager. The fitted decoder weights used to predict choice and wager serve as

tools for addressing this question. To summarize the relationship between the choice and wager

weights we converted them to an absolute magnitude and performed a Pearson's correlation (Figure

5D) and a difference test (Figure 5E). For both analyses the weight time series were marginalized over

the accumulation period (Methods). The correlation across the population was modest (monkey H: $r =$

0.18 & monkey G: $r = 0.21$) but highly significant by permutation test ($p \ll 0.05$ for both monkeys).

Additionally, the distribution of weight differences was unimodal (Figure 5E, Hartigan's dip test, $p > 0.9$

for both monkeys individually), suggesting a continuum of contributions to choice and confidence

across the population and not two distinct subpopulations contributing to one or the other. At the same

time, this raises the question of whether the population is capable of disentangling the two signals so

that they do not contaminate one another, especially given that the evidence that informs choice and

confidence derives from a single source (the motion stimulus). To address this, we calculated the

angular distance between the n-dimensional (n = number of neurons) decoding weight vectors for

choice vs. confidence, separately for each session. During the deliberation period these vectors were

approximately orthogonal (Figure S6C), facilitating the readout of confidence by a downstream region,

potentially at any time. Interestingly, the time point near the saccade was when the angular distance

was closest to orthogonal, suggesting that the separability of choice and confidence signals is maximal

at the moment of behavioral execution.

As mentioned above, one way to describe the model DV is as a graded level of certainty (Kiani

et al., 2014b) or even "confidence" (Peixoto et al., 2019) in the prediction of behavior by neural activity.

Although these labels do not necessarily imply a neural representation of a given probabilistic quantity

(Pouget et al., 2016), we wondered whether the level of certainty of the choice decoder might predict

the binary classification by the wager decoder on a trial-by-trial basis. To test this, we partitioned trials

according to whether they were classified as high or low bets by the wager decoder, by calculating the

Figure 6. Predictive relationship between choice and wager decoders. (A) Model DV from the choice decoder as a function of time, aligned to saccade onset for left (contralateral) choices and 0% coherence trials only. Traces are separated by whether the wager decoder predicted a high (purple) or low (gold) bet. Shaded regions are SEM. Black bar at top indicates a significant difference between the traces. (B) Same as A but for right choice trials. (C) Log odds of choice decoder as a function of the probability of a high bet predicted by the wager decoder, based on the time window from -0.2 to 0s before saccade for choice and 0 to 0.2 after saccade for wager. Each dot is an individual trial and black line is from a linear regression. Unlike A, purple and gold color represents the behavioral wager outcome and not the decoder prediction. (D) Same as C but for right choice trials only. (E) Corrected R^2 values from a linear regression relating trial-by-trial transformed choice decoding strength and wager decoder probability (P(High)), as a function of time lag between them. The blue, red, and purple traces comprise different time windows either aligned to motion onset (MO) or saccade onset (SO). Standard error indicated by the shaded regions (barely visible). (F) Centroid patterns from K-means clustering using trial-by-trial values of normalized corrected R^2 from E, as a function of time lag. Color gradient matches the period of time in figure E (left: 0.4s before saccade, right: 0.2s before and after saccade).

mean P(High) for the wager decoder in the period immediately surrounding the saccade. Values above

(below) 0.5 indicated a decoded-high (decoded-low) wager. We then averaged the model DV from the

choice decoder, using only 0% coherence trials, and found that it was higher for decoded-high vs.

decoded-low trials (Figure 6A). This indicates that the strength with which LIP predicts the upcoming

choice covaries with the degree to which the same population predicts a high bet, consistent with a tight

link between choice and confidence signals in LIP.

Remarkably, this link was only present for left (contralateral) and not right (ipsilateral) choices

(Figure 6A vs. 6B). To further investigate this stark contrast, we performed a trial-by-trial analysis of the

decoder outcomes centered around the saccade epoch (Figure 6C & 6D). After separating the data by

the monkey's wager on each trial (high=purple, low=gold), we confirmed that the wager decoder

strongly predicted the confidence report irrespective of choice (Figure 6C & 6D top inset; p << .05 for

both). However, the wager prediction was only correlated with choice strength for left choices

(Spearman rank correlation, ρ = 0.274, p << .05 and ρ = -0.037, p=0.11 for left and right choices,

respectively). Because we recorded from the right hemisphere, the population is principally made up of

neurons whose RFs overlapped a left choice target (either high or low). Thus, neurons which largely

represent the unchosen option (associated with the 'losing race' in the accumulator model) do not show

a relationship between choice strength and wager prediction, even though they predict the wager just

as well as the 'winning' neurons (Figure 6D vs. 6C, top histograms; see Discussion).

Having established a link between decoded choice certainty and wager prediction (at least for

contralateral choices), we can now reexamine the temporal differences shown in Figure 5B & 5C,

specifically by asking when choice decoding strength best predicts the wager decoder's probability of a

high bet on a given trial. We fit a linear regression relating choice decoder strength (Methods) at time t

to decoded wager probability at time $t + \Delta t$, where Δt ranges from +/- 200 ms. We found that, during the

deliberation phase (200-600 ms after motion onset and 400-0 ms before saccade onset), the best

prediction between choice strength and wager probability was at a time lag of zero (Figure 6E, R^2 =

0.13 & 0.21 blue and red lines, respectively). Interestingly, the period centered around the saccade (-

0.2<->0.2s, purple line) gave rise to two peaks, one at zero lag (R^2 = 0.12) and one at a lag of -0.2 s

(choice preceding wager; R^2 = 0.13). To parse the dynamics of individual trials that underlie this

bimodal pattern, we applied a K-means clustering algorithm to the trial-by-trial corrected R^2 values and

plotted the corresponding centroids for the periods before and during the saccade (Figure 6F, left and

right, respectively). The top 3 clusters that captured a majority of the data (47%/27%/26% for pre-

saccade and 40%/30%/17% for peri-saccade epoch) were qualitatively similar for both periods (Figure

6F). However, the extra cluster afforded to the peri-saccade period (Figure 6F, right panel, lightest

shade) exposed a pattern that was strikingly similar to the pattern of Figure 6E. It indicates that, on a

small subset of trials (13%), choice and confidence signals showed strongest coupling at both zero-lag

and a lag of ~200 ms (choice update preceding confidence update). We speculate that these trials may

contain a reevaluation of evidence in service of the wager, akin to a replay of the last few samples of

evidence leveraged for the choice as a substitute for external input. Regardless, the main takeaway is

the prominent peak at zero lag, consistent with near-simultaneous updating of a DV for choice and

confidence—a noteworthy finding given the prevalence of serial bottlenecks in various tasks and

systems (Pashler, 1994; Welford, 1952; Sigman & Dehaene, 2005; Kang et al., 2021; Zimnik &

Churchland, 2021; Jun et al., 2022).

DISCUSSION

The neural mechanisms underlying metacognition have become tantalizingly more accessible over the

past two decades through the development of behavioral assays of confidence in nonhuman animals

(Hampton, 2001; Kiani et al., 2009; Middlebrooks & Sommer, 2011; Smith et al., 2012; Kepecs &

Mainen, 2012). A longstanding goal is to connect the rich psychological literature on process models for

confidence with their implementation at the level of neural populations and circuits. One approach

considers how decision accuracy, speed, and confidence can be jointly explained within the framework

of bounded evidence accumulation (Kiani & Shadlen, 2009; Pleskac & Busemeyer, 2010; Fetsch et al.,

2014b), an idea presaged by Vickers' balance-of-evidence hypothesis (Vickers, 1979). Such a

framework is motivated by the critical role of response time in psychophysical theory and experiment

(Luce, 1986) and its strong empirical link to confidence going back at least a century.

Yet embracing a dynamic model still leaves open questions about the temporal evolution of

choice and confidence. Several authors have emphasized post-decisional processing (Baranski &

Petrusic, 1998), formalized by serial models in which evidence is integrated for confidence only after

termination of the primary decision (Pleskac & Busemeyer, 2010; Moran et al., 2015; Herregods et al.,

2023). This idea follows naturally from the definition of confidence as the expected probability correct,

conditioned on a choice (Pouget et al., 2016), and it makes sense to exploit additional information

acquired (or generated internally) after initial commitment if the behavioral context permits. However, in

many settings it would be advantageous to compute a provisional degree of confidence while the

decision is still being formed. Decisions are commonly expressed as a motor action, executed with a

degree of vigor (or caution) that depends on confidence or expected reward (Shadmehr et al., 2019).

Also, deliberation itself is a significant cost (Drugowitsch et al., 2012), so an extended deliberation

period for confidence may be less efficient. Lastly, an online prediction of accuracy facilitates rapid

decision sequences (van den Berg et al., 2016b; Lisi et al., 2020; Zylberberg, 2021) and strategic

modulations of the ongoing decision process (Balsdon et al., 2020). Recent human studies (Dotan et

al., 2018; Balsdon et al., 2020; Li et al., 2023) offer intriguing evidence for parallel computation of

confidence (or at least *certainty*; Pouget et al., 2016) during decision formation, further supported by

electroencephalography (Gherman & Philiastides, 2015; Balsdon et al., 2021; Dou et al., 2024) and

transcranial magnetic stimulation (Xue et al., 2023). How this might be implemented at the level of

neuronal populations remains unclear and requires a suitable paradigm for nonhuman animals

(notwithstanding rare recordings in human patients, e.g. Fu et al., 2022). Here we establish such a

paradigm and provide evidence that monkeys (and LIP neurons) can accumulate samples of evidence

concurrently to guide a single motor action corresponding to a choice and degree of confidence therein.

Behavioral evidence for concurrent deliberation

First, we validated the peri-decision wager as a measure of confidence *per se*, which should covary

with accuracy even when conditioned on the stimulus. If a behavioral report only predicts accuracy

across levels of stimulus strength or difficulty, it could reflect an associative process of categorization

(Smith et al., 2012), or more subtly, an estimate of difficulty itself (Löffler et al., 2023). We sought to

allay these concerns by including a set of identical-seed trials, in which the random dot movie was

identical up to the initiation of the saccade. Controlling for stimulus motion, the accuracy for high bets

was still significantly higher than for low bets, for both monkeys (Figure S1A). This suggests that the

wager reflects, in part, variability in the internal representation of evidence and/or the reliability of the

decision process, including aspects that could fall under the rubric of attention.

Psychophysical kernels indicated substantial overlap in the stimulus period contributing to

choice and wager, as shown previously in humans (Zylberberg et al., 2012; van den Berg et al., 2016a),

ruling out a strategy where confidence is systematically assessed after (or before) choice formation.

Additionally, a small subset of trials showed evidence for changes of mind (CoMs): perhaps surprisingly

for a saccade task, the monkeys occasionally reversed their initial wager, choice, or both, implying that

both were amenable to revision at the time of initial commitment. These two lines of evidence suggest

that deliberation for choice and confidence occurs in overlapping time windows, even extending after

the stimulus has been extinguished.

Corroboration of a parallel strategy was provided by the superior fits and predictions from our

parallel model compared to the serial model (Figure 3). We then used the model fits to make

predictions for the probability of betting high when a trial outcome is correct vs. incorrect. This aspect of

the behavior strongly argued against the serial strategy, which invariably predicts an 'X-shape' pattern

(decreasing confidence with greater evidence strength on error trials) that was absent in our data. We

did not explicitly test a hybrid model where parallel accumulation is followed by a period of extra

accumulation for confidence (Desender et al., 2021; Maniscalco et al., 2021), but this too predicts an X-

shape, depending on the duration of the second epoch (Desender et al., 2021). Other behavioral

evidence (Kiani et al., 2014a) and model simulations (Khalvati et al., 2021) similarly appeal to the

temporal domain to explain the X-shape, contrary to the conventional explanation based on signal-

detection theory (SDT; Treisman & Faulkner, 1984; Kepecs et al., 2008) or more general Bayesian

formulations (Sanders et al., 2016; Adler & Ma, 2018). This distinction matters because neural

correlates of the X-shape are considered diagnostic of confidence signals in the brain (Kepecs et al.,

2008; Rolls et al., 2010; Komura et al., 2013; Bang et al., 2020), which could be misleading if the

relative timing of latent choice and confidence computations is unknown. In general, however, the

temporal explanation does not invalidate SDT as a useful framework, nor its extension to decision

reliability ('meta-uncertainty'; Boundy-Singer et al., 2022). In fact, an exciting future direction would be

to link the neural signatures of meta-uncertainty computations in visual cortex (Boundy-Singer et al.,

2024) to the temporal dynamics of confidence formation in decision-related areas.

Neural correlates of concurrent deliberation

Individual LIP neurons showed heterogeneous dynamics (Figure 4A), but when pooled based on

receptive field overlap with the high or low target, the averages revealed accumulation-like responses

with interpretable timing relationships for the four outcomes. In essence, the ramping activity began to

predict the wager at about the same time that it began to predict the left-right decision. Using a

theoretical and simulated autocorrelation structure for a standard and delayed drift diffusion process,

we found that both populations showed the statistical signatures of accumulation (VarCE and CorCE)

from 200 ms after motion onset, inconsistent with one form of serial strategy in which the decision

process first considers only the low or high pair of targets then covertly switches to the other pair.

To uncover latent decision and confidence signals on individual trials, we constructed logistic

classifiers for choice and wager based on the neural population activity. As shown previously, the

choice decoder displayed a graded prediction (the 'model DV') that was linearly dependent on

coherence, consistent with a neural DV representation (Roitman & Shadlen, 2002; Steinemann et al.,

2024). Notably, the population signal was predictive of choice and wager during identical epochs

(Figure 5B & C), consistent with a parallel process. An interesting anomaly was the temporal offset

between choice and confidence decoders at the end of the trial (Figure 5B,C). This offset was not

driven by a lag between the trial-by-trial predictions during decision formation, but such a lag did

emerge around saccade onset (Figure 6E). This could be a correlate of top-down signals related to

attention, expectation, or affect—but another possibility, consistent with the current findings (Figure 6F),

is that it reflects reevaluation of the evidence for guiding subsequent decisions (van den Berg et al.,

2016b; Lak et al., 2020 Zylberberg, 2021). One could test this more directly by manipulating neural

activity during the peri-decision epoch in a task where optimal behavior depends on confidence in

earlier choices. Lastly, we found that the strength of the decoder's choice prediction ('certainty') was

correlated with the probability of a high bet established by the wager decoder (Figure 6A, 6C). To our

knowledge this is the first evidence directly linking a neural representation of choice certainty with a

neural prediction of confidence as measured behaviorally (see also Boundy-Singer et al., 2024).

Notably, this relationship held only for left choices and not right ones (Figure 6B, 6D), i.e. for

saccades to the contralateral hemifield where most RFs were located. On the surface, this appears to

contradict a key prediction of the 2D accumulator model (Kiani et al., 2014a) that we used to fit the

behavior. In that model it is the losing accumulator which implements the graded relationship between

evidence strength and confidence, since the winning accumulator is always at the bound at the time of

the decision. However, it is important to realize that the mapping between model accumulators and

neuronal populations may not be so straightforward, especially because in our case there are actually

four relevant subpopulations (one for each target). Interestingly, our left-biased population can

nevertheless predict the wager equally well for right choices (Figure 6D), suggesting it may receive

information about confidence indirectly, perhaps from the population representing the chosen option.

What seems clear is that future studies should consider other models in which the winning accumulator

dictates not only choice and RT but also confidence.

Caveats and conclusions

One limitation of this study is that confidence is mapped onto a stable motor action, namely the

saccade to a high or low target whose positions did not change within a session. We found this to be

necessary for achieving consistent behavioral performance, but it does present a challenge for

disentangling cognitive signals from those involved in motor planning. Could the results be explained by

simple motor preparation to one of four independent spatial targets? We do not think so. First, the

observed signatures of noisy evidence accumulation (Figure 4E, Figure 5A) suggest that ramping

activity in LIP reflects more than simple motor planning. Second, if LIP only reflected movement

preparation independent of an evidence-based decision process, there would be no reason to expect a predictive relationship between the choice and wager decoders (Figure 6A), especially on such a fast time scale (Figure 6E). Third, we trained a separate decoder to predict the vertical component of the saccade using a set of control trials where only one wager target was present (either the high or the low; Figure S6A). The decoding axis on these control trials was nearly orthogonal to the axis for decoding the wager on standard 4-target trials (Figure S6C). This implies that confidence and vertical eye movement preparation reside in nearly orthogonal subspaces, hence the confidence signals we observed cannot be reduced to simple motor preparatory activity. One could articulate a motor-centric interpretation of our findings, but it would have to be something like: simultaneous updating of two dimensions of a motor plan (horizontal and vertical), corresponding to distinct transformations of the input (categorical judgment vs. a prediction of accuracy). It was not a foregone conclusion that these two dimensions could be computed in parallel. In fact, a recent study of two-dimensional decisions using a similar target configuration (simultaneous report of color and motion; Kang et al., 2021) suggests there is a bottleneck preventing simultaneous incorporation of two evidence streams into a single DV. Evidently there is no such bottleneck for a single evidence stream informing choice and confidence, at least as far as we can resolve with neural decoding.

Importantly, the current findings are not incompatible with post-decision processing for confidence. Indeed, even though the peri-decision time window is highly compressed in our task, there are hints of continued processing related to confidence and potential CoMs (Figure 2C; Figure 5B). Investigating this window further could be useful for testing mechanisms of confidence readout, which could require querying the state of the accumulator(s) as well as estimating elapsed time (Kiani et al., 2014a). It remains to be seen whether the population responses, corresponding to choice and confidence, are modulated by bottom-up sensory evidence (Yates et al., 2017), or conversely whether online confidence signals feed back onto sensory representations to facilitate perceptual inference (Haefner et al., 2016). Simultaneous recordings across multiple brain areas will be essential for resolving these questions, bringing us closer to understanding how neural dynamics convert sensation into belief.

Acknowledgements

We thank members of the lab for their insight and discussions. Additionally, we are grateful to Ofelia Garalde for animal assistance, and Justin Killebrew, Bill Nash, and Bill Quinlan for technical assistance. This work was supported by the National Institute of Neurological Disorders and Stroke (RF1NS132910), the E. Matilda Ziegler Foundation for the Blind, and a Whitehall Foundation research grant. CF is supported by the France-Merrick Foundation.

METHODS

EXPERIMENTAL MODEL AND SUBJECT DETAILS

Two male rhesus monkeys (*Macaca mulatta,* 6-8 years old, 8-10 kilograms) were kept and handled according to National Institutes of Health guidelines and the Institutional Animal Care and Use Committee at Johns Hopkins University. Standard sterile surgical procedures were performed to place a PEEK recording chamber (Rogue Research) and titanium head post under isoflurane anesthesia in a dedicated operating suite. The recording chamber was positioned over a craniotomy above the right posterior parietal cortex of both animals for access to the intraparietal sulcus and posterior third of the superior temporal sulcus. The chamber and head post were held in place using dental acrylic anchored with ceramic bone screws.

METHOD DETAILS

Experimental apparatus

Monkeys were seated in a custom-built primate chair in a sound-insulated booth facing a visual display (ViewPixx, VPixx Technologies; resolution 1080x960, refresh rate 120 Hz; viewing distance 52 cm) and infrared video eye tracker (Eyelink 1000 Plus, SR Research). Experiments were controlled by a Linux PC running a modified version of the PLDAPS system (Version 4.1, Eastman & Huk, 2012) in MATLAB (The MathWorks). Visual stimuli were generated using Psychophysics Toolbox 3.0 (Brainard, 1997). For correct responses, the monkey was given a fluid reward that was dispensed using a solenoid-gated system.

Neurophysiology

Recording probes (32- or 128-channel Deep Array, Diagnostic Biochips) were positioned with the aid of

a PEEK grid secured inside the recording chamber. A sharpened guide tube was inserted through a

grid hole so that the tip of the tube just punctured the dura, then a probe was advanced through the

guide tube into the brain using a motorized microdrive (40mm MEM Drive, Thomas Recording).

Bandpass-filtered voltage signals were collected using the Open Ephys acquisition board and software

(Siegle et al., 2017). Post-hoc analysis for identifying single neurons and multi-unit clusters was done

using Kilosort 2.0 (Pachitariu et al., 2016; Stringer et al., 2019). Further curation was done using the

phy2 software (https://phy.readthedocs.io/en/latest/). Data analysis was performed with custom

MATLAB code.

Targeting of LIPv was achieved by selection of grid locations based on a post-surgical structural

MRI scan in which the chamber and grid holes were well visualized. We compared the MR images to

published reports and atlases (Lewis and Van Essen, 2000; Saleem & Logothetis, 2006) to estimate the

depth of LIPv (typically 8-12 mm from the dura in our vertical penetration angle) and corroborated the

targeting using white-gray matter transitions and physiological response properties during the mapping

tasks described below. After reaching the target, we let the probe settle for 30-60 minutes before the

start of the experiment. A total of 407 neurons (single = 148 & multi = 56 in monkey H, single = 107 &

multi = 93 G) were collected over 29 sessions (12 for monkey H, 17 for monkey G).

Memory saccade task

Sessions began with a standard memory-guided saccade task to identify neurons with spatially

selective activity during the delay period (Gnadt & Andersen, 1998) and to coarsely map their receptive

fields (RFs). Monkeys were instructed to gaze at a central fixation point (1.5° radius acceptance

window), after which a red target (0.42° diameter circle) was flashed for 100 ms, located in one of

several locations evenly spaced in polar coordinates. The coordinates consisted of 3 different radii

(eccentricities) and 10 or 12 angular positions, giving a total of 30 or 36 unique target locations. Each

target location was presented 10 times in pseudorandom order, requiring a total of 300 or 360 trials.

While fixating, the monkey had to remember the location of the target, and after a delay of 0.8 s the

fixation point was extinguished, instructing the monkey to make a saccade to the remembered location.

RFs were estimated online during/after the memory saccade block by acquiring multi-unit spikes

(threshold crossings) on each recording channel and plotting the mean firing rate during the memory

delay as a function of target location in a 2D heat map. These RF maps guided the placement of the

four targets for the main decision task, such that one or two of the targets overlapped the RF of multiple

neurons in the recorded ensemble.

Main task

The monkeys were trained to perform a reaction-time direction discrimination task with simultaneous

report of choice and confidence ('peri-decision wagering'; Figure 1A). To initiate a trial the animals

acquired fixation on a target on the center of the screen (0.21° diameter). After a delay of 0.5 s four

targets appeared, positioned diagonally from the center of the screen, each representing a choice (left

or right) and a wager, or bet (high or low). The targets representing high bets were always placed in the

upper-left and upper-right quadrants while the low-bet targets were placed in the lower quadrants (left

high: x = -7.3±2.1°, y = 7.3±1.5°; left low: x = -6.9±2.3°, y = -3.4±1.4°; right high: x = 7.3±2.1°, y =

7.3±1.5°; right low: x = 6.9±2.3°, y = -3.4±1.4°). Each left-right pair was presented symmetrically around

the vertical meridian, but high-bet targets were typically 2-5° further from the fixation point than low-bet

targets, in order to counteract the monkeys' tendency to bet high more often than low.

After another brief delay (0.3-0.6 s, truncated exponential), a dynamic random-dot motion

(RDM) stimulus was presented in a circular aperture. Motion strength, or coherence, was sampled

uniformly on each trial from the set {0%, ±3.2%, ±6.4%, ±12.8%, ±25.6%, ±51.2%}, where positive is

rightward and negative is leftward. The stimulus was constructed as three independent sets of dots

(Roitman & Shadlen, 2002), each appearing for a given video frame then reappearing three frames (25

ms) later. Upon reappearing, a given dot was either repositioned horizontally to generate apparent

motion in the assigned direction (speed = 2-16°/s, held constant within a session) with probability given

by the coherence on that trial, or otherwise was replotted randomly within the aperture.

When ready with a decision, the animal could report its choice and wager by making a single

saccade to one of the four targets. When the eyes moved 1.5° away from the target the RDM and

fixation point were extinguished while the four targets remained visible. When the eye position reached

one of the four targets, it was required to hold fixation within 1.5° of the target for 0.1 s to confirm the

outcome. Lastly, the animal was either rewarded or given a time penalty depending on the conjunction

of accuracy (choice corresponding to the sign of coherence) and wager (Figure 1A, right). The penalty

for a high-bet error was applied to the subsequent trial where the animal was required to fixate the

central target for a longer period of time (2-3 s) prior to RDM onset. Reward sizes (~.21 ml for high and

~.19 ml for low bets) and penalty times were chosen to encourage a wide range of wager probability

across different levels of motion strength.

QUANTIFICATION AND STATISTICAL ANALYSIS

Cell selection

To quantify spatial selectivity, we modified a previously described discrimination index (Nguyenkim &

DeAngelis, 2003).

629
$$DDI = \frac{R_{max} - R_{min}}{R_{max} - R_{min} + 2\sqrt{\frac{SSE}{N-M}}} \quad [1]$$

R_{max} and R_{min} are the mean firing rates during the delay period at the target spatial location with the

highest and lowest response, respectively. SSE is the sum-squared error around the mean responses,

N is the total number of trials, and M is the total number of unique spatial target locations. For all

analyses except the population logistic decoder, only units (single- and multi-) with a discrimination

index higher than an arbitrary cutoff of 0.45 were kept for further analysis.

Full quantification of RFs was done by fitting a 2D Gaussian to the firing rates during the delay

period of the memory saccade task for each target location:

$$FR = A * \frac{1}{2\pi|\Sigma|^{\frac{1}{2}}} \exp\left(-\frac{1}{2}(x-\mu)\Sigma^{-1}(x-\mu)^T\right) \quad [2]$$

where FR is firing rate during the delay period and X is a 2-length vector that contains the X and Y

positions of the target locations (in degrees). The fitted variables include **A** for amplitude, **μ** for the 2D

mean location of the RDM (X and Y in degrees), and **Σ** which is the covariance matrix of the Gaussian

(2x2). To reduce the variables for fitting we set the covariance to 0 and only fit for the two variances.

We then normalized the 2D Gaussian to convert it to a probability density and calculated the final

preferred target based on the probabilities corresponding to the 4 targets in the peri-dw task.

For the population logistic decoder, we included not only units with delay period activity in the

memory saccade task but accepted any that were well defined single neurons or multi-unit clusters

based on careful spike sorting and manual curation. Previous studies have suggested that decision-

related activity can be present even in neurons without memory delay-period activity (Meister et al.,

2013), and we aimed to maximize the sample size to facilitate single-trial decoding. This broader

criterion increased the average number of units per session from 7.5 to 17.3 for monkey H and from 6.2

to 11.2 for monkey G.

Behavioral data analysis

We applied a logistic regression model to fit the proportion of rightward choices, as follows:

$$P_{right} = \frac{1}{1+\exp(\beta_0+\beta_1 Coh+ \beta_2 Wager+\beta_3(Coh)(Wager))} \quad [3]$$

where P_{right} is the probability of a rightward choice, *Coh* is signed motion coherence, *Wager* is the

monkey's bet (high/low), β_0 is the overall bias, β_1 estimates the effect of signed motion coherence on

choices, β_2 is the weight for the bet, and β_3 is the interaction term (used to calculate whether choice

significantly depends on wager). The fitting was done by finding the minimum negative log-likelihood

value under a binomial distribution, using *fminsearch* in MATLAB with the Nelder-Mead method. For

choices conditioned on high and low bets, we fit two separate logistic regressions after removing the

terms to the right of $\beta_1 Coh$ (Figure S1).

662   The fits to the average reaction times (RTs) as a function of motion strength were done using a

663   Gaussian distribution, defined as follows:

664
$$RT = A * \frac{1}{\sigma\sqrt{2\pi}} \exp\left(-\frac{1}{2}\left(\frac{coh - 0}{\sigma}\right)^2\right) + b \ [4]$$

where A is an amplitude term, coh is the signed motion coherence, σ is the standard deviation

controlling the width of the Gaussian, and b is a bias term capturing the fastest mean RT. We fit this

pseudo-gaussian by minimizing root-mean-square error (RMSE) instead of maximizing the likelihood,

because of the amplitude value.

To examine the relationship between accuracy and RT, as well as wager and RT, we calculated

proportion correct and proportion of high bets grouped by RT, using non-overlapping 100 ms time bins

starting 100 ms after motion onset. To test for significance as to whether the trend was decreasing

(during the time depicted in Figure 1D) we used a Cochran-Armitage test for trend:

673
$$T = \sum_{i=1}^{k} t_i(N_{1i}R_2 - N_{2i}R_1)$$
$$Var(T) = \frac{R_1 R_2}{N}(\sum_{i=1}^{k} t_i^2 C_i(N - C_i) - 2\sum_{i=1}^{k-1}\sum_{j=i+1}^{k} t_i t_j C_i C_j \ [5]$$

where t_i are the weights depicting the trend (in our case linear, so t = [0, 1, 2, 3, 4, …]), N = total

number of trials, N_{ab} is total number of trials for group a (accuracy: correct and error; wager: high or

low) and b is total number of trials for timepoint b. R_a represents total number of trials for group

a irrespective of time, and C_b is total number of trials at timepoint b irrespective of group. The division

of T by $Var(T)$ gives a test statistic that can then be used to compute a p-value.

Motion energy analysis

To estimate the temporal weighting of sensory evidence for choice and confidence, we utilized motion

stimulus fluctuations to perform a psychophysical reverse correlation analysis on both choice and

wager. We convolved each trial's sequence of dots — a 3-dimensional array with the first two

dimensions denoting the X-Y coordinates of the dots' center, and the third dimension spanning the

number of frames — with two pairs of quadrature spatiotemporal filters (Adelson & Bergen, 1985). The

filters were oriented to account for motion in the direction along the choice axis: 0° motion (rightward)

and 180° motion (leftward motion). The convolved quadrature pairs were squared and summed to give

the local motion energy for both the leftward and rightward directions. These local motion energies

were then collapsed across space (first 2 dimensions) to derive the motion energy provided by the

stimulus through time, ME(t). To quantify the net motion energy, we took the difference between both

directions of motion energy (right minus left; Adelson & Bergen, 1985; Kiani et al., 2008). To strictly look

at the fluctuations around the mean and mitigate potential effects of coherence, we subtracted from

each trial the mean motion energy, conditioned on signed coherence, through time. As most meaningful

fluctuations occur at smaller coherences, we also decided to restrict the analysis to 0%, 3.2% and 6.4%

coherence trials.

For the choice kernels (Figure 2A) we simply averaged the motion energy profiles for all trials

with a right choice (red line) or left choice (blue line). The shaded red and blue area represents the

standard error of the mean. To evaluate statistical significance of the choice kernels, we used a t-test

comparing the motion energy profiles for right and left choices at each time point, applying a Šidák

correction matching the number of time samples. For the confidence kernels (Figure 2B), we instead

subtracted the motion energy profiles for high vs. low wager trials conditioned on a given choice

(correct trials only) and computed the standard error of the difference (shaded area around traces in

bottom of Figure 2). To assess significance, we compared the confidence kernel distribution relative to

a value of zero using a t-test with Šidák correction for the number of time samples.

Parallel model

To formalize the hypothesis of parallel deliberation for choice and confidence, we utilized a two-

dimensional (2D) bounded accumulator model (Kiani et al. 2014), also known as an anticorrelated race.

We adapted a recently developed family of closed-form solutions for a 2D correlated diffusion process

(Shan et al., 2019) to facilitate fitting of the parameters. By conceptualizing the diffusion process as a

Gaussian distribution originating from the third quadrant on a plane with two absorbing bounds, one can

employ the method of images (MoI) to calculate the propagation of the probability density of the

diffusing particle, i.e. the solution to the Fokker-Planck equation. The constraint making this numerical

solution possible limits the discrete number of anti-correlation values that can be modeled, governed by

the number of images:

$$rho = \cos\left(-\frac{\pi}{I}\right) \quad [6]$$

where rho is the correlation value and I is the number of images. We selected $I = 4$ or $rho = .7071$ for

consistency with previous studies (Kiani et al., 2014; Van Den Berg et al., 2016a).

Specifically, the MoI yields $P\left(v_{right}, v_{left} \mid C, t\right)$, describing the probability of the accumulator

being in a particular position at time t for coherence C. The probability of making a right choice is given

by:

$$P(Right|C) =$$
$$\frac{\int\int P\left(v_{right} = B, v_{left} \mid C, t\right) dv_{left} * P(t) dt}{\int\left(\int P\left(v_{right} = B, v_{left} \mid C, t\right) dv_{left} + \int P\left(v_{right}, v_{left} = B \mid C, t\right) dv_{right}\right) P(t) dt} \quad [7]$$

where B is the bound for terminating the accumulation process. To acquire the decision time

distribution, we calculated the difference in the survival probability as follows:

$$P(DT) = \Delta\left(\int\int_{-inf}^{Bound} P\left(v_{right}, v_{left} \mid C, t\right) dv_{right} dv_{left}\right) \quad [8]$$

thereby providing the change in probability at each survival timestep, quantifying the probability of

crossing a bound. To then calculate the probability of reaction time (decision time plus sensory/motor

delays, referred to as non-decision time or *nonDT*), we convolved this probability density as follows:

$$P(RT) = \int P_{DT}(t - z) P_{nonDT}(z) dz \quad [9]$$

where $P_{nonDT}(z)$ is modeled as a Gaussian distribution with mean (μ_{nonDT}) and standard deviation

(σ_{nonDT}).

To calculate the probability of betting high, we first computed the log-odds of a correct choice as

a function of the state of the losing accumulator (Kiani et al., 2014), as follows:

$$Logodds = Log\left(\frac{\int P(v_{incorrect}, t | v_{correct} = B, C, t) P(C) dC}{\int P(v_{correct}, t | v_{incorrect} = B, C, t) P(C) dC}\right) \quad [10]$$

where $v_{incorrect}$ is the incorrect accumulator (not matching the sign of coherence) and $v_{correct}$ is the

correct accumulator (matching the sign of coherence). This transformation provides a graded scale for

737   betting that can be transformed into {high, low} responses by applying a cutoff value (θ) that imposes

738   binary outcomes. To obtain the probability of a high bet we computed:

$$P(high\ wager) =$$

739
$$\frac{\iint P(v_{right}|v_{left} = B, t, C, Logodds < \theta)P(t) + \iint P(v_{left}|v_{right} = B, t, C, Logodds < \theta)P(t)}{\iint P(v_{right}|v_{left} = B, t, C)P(t) + \iint P(v_{left}|v_{right} = B, t, C)\ P(t)} \quad [11]$$

740   where $Logodds < \theta$ indicates integration over the area in which $Logodds$ is less than the cutoff value.

741   Lastly, we found the best-fitting parameters to the model by using the joint probability of choice,

742   RT, and wager as follows:

743
$$P(Right, RT, High) = \prod_{tr=1}^{Trials} P(Right|RT, High) * P(RT|High) * P(High) \quad [12]$$

744   We calculated the negative log likelihood of this by:

$$-\log(P(Right, RT, High)) =$$

745
$$-\sum_{tr=1}^{Trials} \log(P(Right|RT, High)) + \log(P(RT|High)) + \log(P(High)) \quad [13]$$

The full model had 6 or 7 free parameters, differing slightly between the two animals (see table below).

These included drift rate (K), bound (B), mean non-decision time (μ_{nonDT}), urgency max (u_M),

urgency half-life ($u_{\frac{1}{2}}$), and log-odds cutoff (θ). The urgency signal followed a hyperbolic function for

monkey G, requiring both parameters, and a linear function for monkey H, requiring one parameter.

Also, monkey H required separate non-decision time means for left and right choices, and a 'wagering

offset' (b_w) capturing a tendency to occasionally bet low even for the highest coherence. Non-decision

time standard deviation (σ_{nonDT}) was not a free parameter and was instead established using

psychophysical kernels (van den Berg et al., 2016a, Methods section). Fitting was done using

MATLAB's built-in function *fminsearch* applied in a grid search method with 30 different starting points.

Monkey	Parameters	Number of Parameters
Hanzo	$K, B, \mu_{nonDT,Coh+},$ $\mu_{nonDT,Coh-}, u_M, \theta, b_w$	7
Genji	$K, B, \mu_{nonDT}, u_M, u_{\frac{1}{2}}, \theta$	6

Serial model

The serial model was constructed as a sequence of two 1D bounded accumulator (drift-diffusion) models, one for choice followed by a second for confidence (Figure 1C; Moran et al., 2015; Herregods et al., 2023). There are 6 main parameters: drift rate (K), choice bound (B_c), high wager bound (B_h), low wager bound (B_l), mean non-decision time (μ_{nonDT}), and urgency signal for only the confidence accumulator $(u_{M,Conf})$. Parameter estimation predominantly followed the same logic as the parallel model, using the joint distribution of choice, RT, and wager to fit the data, with a few minor differences. Computing the probability of rightward choice was similar to the parallel model and used the following formula:

$$P(Right|C) = \frac{\int P(v_1 = B_c\ |C,t)P(t)dt}{\int \left(P(v_1 = B_c\ |C,t) + P(v_1 = -B_c\ |C,t)\right)P(t)dt} \quad [14]$$

where v is the accumulator variable for the first 1D accumulator, and the other parameters are similar to the parallel model. The decision time distribution was calculated as:

$$P(DT) = \int P_{choice}(t-z)P_{wager}(z)dz \quad [15]$$

where P_{choice} is the probability of hitting a bound at time t for the first accumulator and P_{wager} is the probability of hitting a bound at time t for the second accumulator. For RT we followed the same procedure as the previous model. Lastly, to calculate the probability of betting high, we used the following equation:

$$P(High\ wager|C) = \frac{P(v_2 = B_h|C, Choice = R)}{\int P(v_2|C, Choice = R)\, dv_2} P(Choice = R)$$

$$+ \frac{P(v_2 = B_h|C, Choice = L)}{\int P(v_2|C, Choice = L)\, dv_2} P(Choice = L) \quad [16]$$

Monkey	Parameters	Number of parameters
Hanzo	$K, B_C, B_h, B_l\ \mu_{nonDT,Coh+},$ $\mu_{nonDT,Coh-}, u_{M,Conf}, b_w$	8
Genji	$K, B_C, B_h, B_l, \mu_{nonDT},$ $u_{M,Conf}$	6

Changes of mind (CoMs) and changes of confidence

Raw eye position data (sampled at 1000Hz) were converted to velocity and smoothed by applying a

3rd-order low-pass Butterworth filter with a cutoff frequency of 75Hz (Orozco et al., 2021). Eye position

is a 2D vector containing X and Y position in degrees, while eye velocity was defined as 1D vector that

combines the velocities for both directions (X and Y). To preprocess the data, we first calculated a

stricter time for saccade onset by applying a threshold of 20°/s onto the smoothed velocity data.

Subsequently, we centered the eye positions by subtracting the average of the first 5 ms before

saccade onset. The initial choice and wager were defined by the location of the saccade in 1 of 4

quadrants of the screen 5 ms after saccade detection. The final choice and wager corresponded to the

target at which the eye position settled within a 0.1 s grace period following the initial saccade. This

provided an initial and final choice and wager for every trial, allowing for simple analyses like those for

Figure 2C,D,E. CoM frequencies (Figure 2C,D) were conditioned on the initial outcome; therefore, the

frequencies reflect not the proportion of all trials but rather only trials that initially reached a given

outcome (error, correct, low, and high). Lastly, for the rightmost panels of Figure 2E the probabilities

are reflective of all trials, hence the values are much smaller than on the other plots.

Analysis of neural data based on preferred and chosen target

Two populations of neurons were established based on RF overlap of either the left-high or left-low

target. We computed four normalized firing rate responses for both populations of neurons, where each

response corresponds to one of the four chosen targets (Figure 4B & 4C). To combine across neurons,

we first detrended the responses of each neuron over the coherences of interest [-6.4%, -3.2%, 0%,

3.2%, 6.4%]. Then the firing rates for each neuron (after smoothing each trial with a 0.1 s exponential

filter) were averaged over all trials that met 3 conditions: 1) matched the chosen target of interest, 2)

contained a coherence of interest, and 3) had a RT longer than 0.3 s. Example neurons in Figure 4A

were not detrended or normalized but otherwise the procedure was the same. The colored bars at the

top of Figure 4B & 4C indicate statistical significance based on a one-tailed t-test evaluating whether

the response of the chosen target (aligned with the neurons' RF) was higher than either of the other

805   three chosen target responses. Given that the testing is done over multiple timepoints, the one-tailed t-

806   test alpha value was corrected using Šidák's correction.

808   **Autocorrelation signatures of standard vs delayed accumulator dynamics**

809   An accumulation of noisy evidence produces characteristic variance and autocorrelation

features that can be estimated from single neurons using procedures laid out by previous work

(Churchland et al., 2011; de Lafuente et al., 2015; Shushruth et al., 2018; Steinemann et al., 2022).

Applying the law of total variance to a doubly stochastic process, the variance in spike rate for a given

time bin is a summation of the variance of the underlying latent rate, termed variance of the conditional

expectation (VarCE), and the residual variance expected if the latent rate was constant, known as point

process variance (PPV). To calculate VarCE, one must subtract out the PPV from the total measured

variance. To do this we made two simple assumptions (Churchland et al., 2011): 1) the observed

spiking of a neuron follows a stochastic point process mediated by some rate parameter, and 2) that at

each time bin the PPV is proportional to the mean count:

$$Var(E[Y_i|X_i]) = Var(Y_i) - E[Var(Y_i|X_i)]$$
$$VarCE(Y_i) = Var(Y_i) - \varphi E[N_i] \quad [17]$$

820   where Y_i represents the random variable capturing the neuron's spike count at timepoint i, X_i is the

821   random variable for the latent rate at timepoint i, and φ is a constant that is fitted to maximize how well

822   the observed firing rates match an accumulation of independent identically distributed (iid) random

823   numbers. $E[N_i]$ is the mean spike count at timepoint i. In addition, it follows that the law of total

824   covariance is described using a similar equation:

$$Cov(Y_i, Y_j) = Cov(E[Y_i|X_i], E[Y_j|X_j]) + E[Cov(Y_i, Y_j|X_i, X_j)] \quad [18]$$

The first term on the right-hand side is known as the covariance of conditional expectations (CovCE),

which is needed to compute the correlation of conditional expectations (CorCE). The second term is the

expectation of conditional covariance, and its diagonal is the PPV. To calculate the CorCE, we made

another assumption that when $i \neq j$, the expectation of conditional covariance is zero because the

variance from the point process should be independent across timepoints (Churchland et al., 2011;

although this may be untrue for adjacent time bins due to their shared interspike interval). This

simplification makes it possible to state that the CovCE, for $i \neq j$, is equal to the measured covariance,

and the diagonal of the CovCE is then the VarCE. It follows that to calculate the CorCE, one must

simply divide the CovCE by the VarCE:

835
$$CorCE(Y_i, Y_j) = \frac{CovCE(Y_i, Y_j)}{\sqrt{VarCE(Y_i) * VarCE(Y_j)}} \quad [19]$$

where i and j are time points. The best fitting φ is then calculated by comparing the formulated CorCE

values onto theoretical or simulated correlation values that underlie the hypothesized generative

process (e.g., accumulation).

We tested two theoretical autocorrelation patterns, one pertaining to a standard drift diffusion

process and the other to a delayed drift diffusion process (Figure 4D). The standard accumulation of iid

random numbers was calculated using the following equation:

842
$$\rho_{i,j} = \sqrt{\min(i,j) \Big/ \max(i,j)} \quad [20]$$

We used 6 different timepoints giving 15 unique combinations ($i = 1:6 \ \& \ j = 1:6, \ i \neq j$). For the

delayed accumulation of iid random numbers, we used a simulation that accumulated noisy normalized

samples of numbers with mean [0.717, 0, -0.717]. We narrowed the simulation to the first 6 timesteps

to compare it to the results from the standard accumulation process. Additionally, the delay component

was constructed by uniformly sampling a value between 1-6, indicating when the accumulation would

begin. Using 10,000 trials we calculated the autocorrelation of the first 6 timesteps for this simulation

providing 15 unique combinations ($i = 1:6 \ \& \ j = 1:6, \ i \neq j$). Additionally, we fit the φ, for both

models, according to the following steps: 1) calculate the $E[N_i]$, $Var(Y_i)$, and $Cov(Y_i, Y_j)$ from observed

spikes, 2) compute $VarCE(Y_i)$ using an initial value of $\varphi = 1$, 3) calculate $CorCE(Y_i, Y_j)$ under the

assumptions of mentioned above, 4) calculate the mean squared error (MSE) between the

empirical $CorCE(Y_i, Y_j)$ and the theoretical/simulated autocorrelation values, $\rho_{i,j}$, and 5) iteratively

update φ until the MSE between the $CorCE(Y_i, Y_j)$ and $\rho_{i,j}$ reached the global minimum.

We used 6x60-ms time bins spanning from 170 ms after motion onset to 530 ms after motion

onset. We applied the analysis on trials with coherences of interest [-6.4%, -3.2%, 0%, 3.2%, 6.4%] and

reaction times at least 630 ms to minimize bound effects. To combine across neurons, we calculated

the mean response for each time bin of each neuron across all trials and subtracted that from the mean

response for each time bin conditioned on the signed coherence. This then gives a matrix of residuals

that is of size $[neuron * trials \ \ x \ \ time \ bins]$, which is then used to calculate a covariance matrix.

Next, the VarCE is calculated by substituting the raw variance for the diagonal in the covariance matrix,

since the diagonal is the normalized population variance, and φ is initiated at a value of 1. To calculate

the empirical correlation values, each entry in the covariance matrix is divided by

$\sqrt{VarCE(Y_i) * VarCE(Y_j)}$. Lastly, using a fitting procedure we compare the Fisher z-transformation of

the empirical correlation with a Fisher z-transformation of the ideal correlation and minimize the mean

squared error (MSE) of the correlation matrix.

Testing for significant difference between standard and delayed accumulation was done using a

leave-one-out (LOO) cross-validation method. The metric used to test the validation was the mean

absolute percentage error (MAPE). MAPE allowed for comparison between the two models because

both models contained different dependent variables ($\rho_{i,j}$). This method provided 15 different MAPE

values, for each model, which were then compared using a one-tailed t-test. The model with the lowest

percentage error distribution better captured the underlying autocorrelation structure of the data (Figure

4E).

For Figure S5 we recalculated the VarCE but used 6x100-ms time bins spanning -50 ms before

motion onset to 550 ms after motion onset. Here we instead applied the analysis on all trials

irrespective of coherence. The CorCE statistical outcomes and preference for standard over delayed

accumulation process did not differ when using all the coherences. We quantified the shaded errors

bars by using a bootstrap method with 100 resamples.

Population logistic decoder

Data were preprocessed by calculating spike counts in 100 ms time windows, stepping every 20 ms,

through the first 600 ms after motion onset, and again separately for spikes aligned 400 ms before and

200 ms after saccade onset. We looked only at trials with RTs 400 ms and longer. We used two L1-

regularized logistic decoders, one for choice and one for wager:

$$P_t(Right\ choice\ or\ High\ wager) = -\log(1 + \exp(-(w_0 + w * X)) - \xi\|w\|^2\ [21]$$

where w represents a vector of weights at time t (vector length matches number of neurons), w_0 is a

bias term, and X is the spike count vector for each neuron in the session. The best hyperparameter ξ

was found using a 50-value grid search between [0 1000], using 5-fold cross validation. The dataset

was divided into a training set (90%) and test set (10%), the latter of which was used to calculate the

prediction accuracy (Figure 5B). If P_t was greater than 0.5 this would indicate that the decoder

predicted either a right choice (for the choice decoder) or high bet (for the wager decoder). Values

below 0.5 would indicate either a left choice or low bet. The performance (accuracy) was defined based

on the monkey's choice and wager at the end of the trial. To compute a 'model decision variable' from

neural activity we first take the trials in which the monkey made a choice that aligns with the signed

coherence (except for 0% coherence). Afterwards, we simply take the log odds of a particular choice

(e.g., $\log\left(\frac{P(right)}{1-P(right)}\right)$ for rightward choices) given the ensemble spike counts up to time t on a given trial

(Kiani et al., 2014; Peixoto et al., 2021). Importantly, for Figure 5A and 5C we used the log odds

irrespective of choice, therefore the results combine $\log\left(\frac{P(right)}{1-P(right)}\right)$ for right choices and $\log\left(\frac{1-P(right)}{P(right)}\right)$

for left choices. Because these log odds for right choice and left choice are predominantly symmetric,

this increases statistical power. For Figure 5C the log odds for wager are also combined in the following

manner: $\log\left(\frac{P(high)}{1-P(high)}\right)$ for high wagers and $\log\left(\frac{1-P(high)}{P(high)}\right)$ for low wagers.

To test whether the model decision variable (DV, log odds) for the choice decoder contained a

linear increase that was significantly dependent on motion strength, we utilized a linear regression:

$$DV = \beta_0 + T * \beta_1 + Coh * \beta_2 + T * Coh * \beta_3\ [22]$$

where β_0 is a bias term, T is time (20 ms time bins for 200-600 ms after motion onset), Coh is motion

coherence level, and $\beta_{1,2,3}$ are the weights accompanying the predictor variables. If the β_3 weight was

significantly different from zero ($P < 0.05$), then the modulation of log odds by motion strength was

deemed significant. Importantly, to compute this linear regression we only used the mean DV shown in

Figure 5A, excluding data cut off at the mean RT for each individual coherence.

As previously mentioned, both logistic decoders provide weights for each neuron through time.

Therefore, to test whether our sample of neurons contained a single population that contributes

approximately equally to choice and wager, we calculated the correlation between the weight

magnitudes (irrespective of sign) as well as the distribution of the difference in weight magnitude. The

weights were preprocessed by taking their absolute value because of our interest in magnitude and not

direction. To calculate the correlation, we compute the Pearson's correlation between absolute weights

for all our neurons at each time point. We collapsed over time by averaging over the first 600 ms after

motion onset and last 400 ms before saccade onset (Figure 5D, red line). We computed significance by

randomly permutating the choice and wager weights 1000 times (Figure 5D, blue distribution).

Additionally, the choice and wager decoder absolute weights were also subtracted from one another to

create a distribution which informs whether there is a single population equally contributing to both

choice and wager. Significance was evaluated using the Hartigan's dip test, which tests whether a

distribution is unimodal or bimodal.

To determine the trial-by-trial relationship between the choice and wager decoder we first tested

whether the wager decoder was predictive of the DV (log odds). Trials where categorized as decoded-

low or decoded-high confidence by calculating the mean $P(High)$ for the wager decoder from saccade

initiation till 200 ms after. Values above (below) .5 indicated a decoded-high (decoded-low) wager. We

strictly looked at trials with 0% coherence to try and remove any effects of coherence on the results.

Results for Figure 6A were calculated by then averaging the DV on these decoded-high and decoded-

low trials. Significance bars were calculated using a one-tailed t-test with Šidák's correction.

Importantly, differences in peak DV around saccade onset (Figure 6A) highlight changes in the ratio

$\frac{P(right)}{1-P(right)}$.

The temporal offset between the peak log odds for choice and wager (Figure 5B) might suggest

that although deliberation for choice and confidence begins simultaneously, the updating accrues some

lag as the trial progresses. To test this, we related the log odds information of the choice decoder to the

$P(High)$ from the wager decoder. As shown in Figure 6A, there is a link between the model DV and

$P(High)$ that can be exploited to understand whether the temporal updating is in sync or if there is

some lag. In this case, the alternative hypothesis, given that the peak of $P(High)$ is later than $P(Right)$,

is that updating of the DV for choice precedes the updating for wager. Figure 6E was generated using

the 3 separate 400-ms time windows described in the legend. The independent variable, which is

$P(right)$ from the choice decoder, was corrected so that values near 0.5 (chance level) were close to

zero and values moving away from 0.5 in either direction (better predicting left or right choice) became

closer to one. This was done using the following equation:

$$corrected\ P(right) = abs(P(right) - .5) * 2\ [23]$$

In essence, this remapping of $P(Right)$ is changing the property of choice decoding strength so that it

is monotonic or linear. This transformation makes it possible for a linear relationship to exist between

corrected $P(Right)$ and $P(high)$. To capture this relationship and its dependency on time lag, we

applied a linear regression, using the corrected $P(Right)$ at time t, to the dependent variable $P(High)$

at time $t + \Delta t$, where Δt range from +/- 200 ms. To quantify how informative corrected $P(Right)$ is of

$P(High)$ we used an R^2 measurement at each time lag. Figure 6E displays a corrected R^2 which is

simply the R^2 value after subtracting out the average R^2 values when the time series of the decoders for

each trial are randomly permuted. To inspect the dynamics of this relationship on individual trials, we

applied K-means clustering to the normalized corrected R^2 values (Figure 6F). The number of clusters

was configured using a silhouette method establishing 3 clusters for the period before the saccade, and

4 clusters for the peri-saccade epoch.

REFERENCES

Adelson, E. H., & Bergen, J. R. (1985). Spatiotemporal energy models for the perception of motion. *Journal of the Optical Society of America A, 2*(2), 284. https://doi.org/10.1364/JOSAA.2.000284

Adler, W. T., & Ma, W. J. (2018). Comparing Bayesian and non-Bayesian accounts of human confidence reports. *PLoS Computational Biology*, *14*(11), 1–34. https://doi.org/10.1371/journal.pcbi.1006572

Audley, R. J. (1960). A stochastic model for individual choice behavior. Psychological Review 67, 1.

Balsdon, T., Mamassian, P., & Wyart, V. (2021). Separable neural signatures of confidence during perceptual decisions. *BioRxiv*, 2021.04.08.439033. https://www.biorxiv.org/content/10.1101/2021.04.08.439033v2%0Ahttps://www.biorxiv.org/content/10.1101/2021.04.08.439033v2.abstract

Bang, D., Kishida, K. T., Lohrenz, T., White, J. P., Laxton, A. W., Tatter, S. B., Fleming, S. M., & Montague, P. R. (2020). Sub-second Dopamine and Serotonin Signaling in Human Striatum during Perceptual Decision-Making. *Neuron*, 1–12. https://doi.org/10.1016/j.neuron.2020.09.015

Baranski, J. V., & Petrusic, W. M. (1998). Probing the Locus of Confidence Judgments: Experiments on the Time to Determine Confidence. *Journal of Experimental Psychology: Human Perception and Performance*, *24*(3), 929–945. https://doi.org/10.1037/0096-1523.24.3.929

Bollimunta, A., Totten, D., & Ditterich, J. (2012). Neural dynamics of choice: Single-trial analysis of decision-related activity in parietal cortex. *Journal of Neuroscience*, *32*(37), 12684–12701. https://doi.org/10.1523/JNEUROSCI.5752-11.2012

Boundy-Singer, Z. M., Ziemba, C. M., & Goris, R. L. T. (2022). Confidence reflects a noisy decision reliability estimate. *Nature Human Behaviour*, *7*(1), 142–154. https://doi.org/10.1038/s41562-022-01464-x

Boundy-Singer, Z. M., Ziemba, C. M., & Goris, R. L. T. (2024a). How does V1 population activity inform pereceptual certainty? *Journal of Vision.* 24(6)12: 1-17.

Boundy-Singer, Z. M., Ziemba, C. M., & Goris, R. L. T. (2024b). Sensory population activity reveals confidence computations in the primate visual system. *bioRxiv.*

Caspi, A., Beutter, B. R., & Eckstein, M. P. (2004). The time course of visual information accrual guiding eye movement decisions during visual search. *Proceedings of the National Academy of Sciences*, *4*(8), 743. http://jov.arvojournals.org/Article.aspx?doi=10.1167/4.8.743%5Cnpapers3://publication/doi/10.1167/4.8.743

Chen, X., Zirnsak, M., Vega, G. M., Govil, E., Lomber, S. G., & Moore, T. (2020). Parietal Cortex Regulates Visual Salience and Salience-Driven Behavior. *Neuron*, *106*(1), 177-187.e4. https://doi.org/10.1016/j.neuron.2020.01.016

Churchland, A. K., Kiani, R., R., C., Wang, X.-J., Pouget, A., & Shadlen, M. N. (2011). Variance as a signature of neural computations during decision-making. *Neuron*, *69*(2), 818–831. https://doi.org/10.1038/mp.2011.182.doi

Cisek, P., & Kalaska, J. F. (2002). Simultaneous encoding of multiple potential reach directions in dorsal premotor cortex. *Journal of Neurophysiology*, *87*(2), 1149–1154. https://doi.org/10.1152/jn.00443.2001

Daniel, R., & Pollmann, S. (2012). Striatal activations signal prediction errors on confidence in the absence of external feedback. *NeuroImage*, *59*(4), 3457–3467. https://doi.org/10.1016/j.neuroimage.2011.11.058

David Smith, J., Couchman, J. J., & Beran, M. J. (2012). The highs and lows of theoretical interpretation in animal-metacognition research. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *367*(1594), 1297–1309. https://doi.org/10.1098/rstb.2011.0366

de Lafuente, V., Jazayeri, M., & Shadlen, M. N. (2015). Representation of accumulating evidence for a decision in two parietal areas. *Journal of Neuroscience*, *35*(10), 4306–4318. https://doi.org/10.1523/JNEUROSCI.2451-14.2015

Desender, K., Donner, T. H., & Verguts, T. (2021). Dynamic expressions of confidence within an evidence accumulation framework. *Cognition*, *207*(May 2020), 104522. https://doi.org/10.1016/j.cognition.2020.104522

Desender, K., Ridderinkhof, K. R., & Murphy, P. R. (2021). Understanding neural signals of post-decisional performance monitoring: An integrative review. *ELife*, *10*, 1–21. https://doi.org/10.7554/eLife.67556

Dotan, D., Meyniel, F., & Dehaene, S. (2018). On-line confidence monitoring during decision making. *Cognition*, *171*(February 2017), 112–121. https://doi.org/10.1016/j.cognition.2017.11.001

Dou, W., Martinez Arango, L. J., Castaneda, O. G., Arellano, L., Mcintyre, E., Yballa, C., & Samaha, J. (2024). Neural Signatures of Evidence Accumulation Encode Subjective Perceptual Confidence Independent of Performance. *Psychological Science*. https://doi.org/10.1177/09567976241246561

Double, K. S., & Birney, D. P. (2024). Confidence judgments interfere with perceptual decision making. *Scientific Reports*, *14*(1), 1–10. https://doi.org/10.1038/s41598-024-64575-7

Drugowitsch, J., Mendonça, A. G., Mainen, Z. F., & Pouget, A. (2019). Learning optimal decisions with confidence. *Proceedings of the National Academy of Sciences of the United States of America*, *116*(49), 24872–24880. https://doi.org/10.1073/pnas.1906787116

Drugowitsch, J., Moreno-Bote, R., Churchland, A. K., Shadlen, M. N., & Pouget, A. (2012). The Cost of Accumulating Evidence in Perceptual Decision Making. *Journal of Neuroscience*, *32*(11), 3612–3628. https://doi.org/10.1523/JNEUROSCI.4010-11.2012

Fan, Y., Doi, T., Gold, J. I., & Ding, L. (2024). Neural Representations of Post-Decision Accuracy and Reward Expectation in the Caudate Nucleus and Frontal Eye Field. *Journal of Neuroscience*, *44*(2). https://doi.org/10.1523/JNEUROSCI.0902-23.2023

Fetsch, C. R., Kiani, R., Newsome, W. T., & Shadlen, M. N. (2014). Effects of Cortical Microstimulation on Confidence in a Perceptual Decision. *Neuron*, *83*(4), 797–804. https://doi.org/10.1016/j.neuron.2014.07.011

Fetsch, C. R., Kiani, R., & Shadlen, M. N. (2014). Predicting the accuracy of a decision: A neural mechanism of confidence. *Cold Spring Harbor Symposia on Quantitative Biology*, *79*, 185–197. https://doi.org/10.1101/sqb.2014.79.024893

Gherman, S., & Philiastides, M. G. (2018). Human VMPFC encodes early signatures of confidence in perceptual decisions. *ELife*, *7*, 1–28. https://doi.org/10.7554/eLife.38293

Gnadt, J. W., & Andersen, R. A. (1988). Memory related motor planning activity in posterior parietal cortex of macaque. *Experimental Brain Research*, *70*(1), 216–220.

Guggenmos, M., Wilbertz, G., Hebart, M. N., & Sterzer, P. (2016). Mesolimbic confidence signals guide perceptual learning in the absence of external feedback. *ELife*, *5*(MARCH2016), 1–19. https://doi.org/10.7554/eLife.13388

Hanks, T. D., Ditterich, J., & Shadlen, M. N. (2006). Microstimulation of macaque area LIP affects decision-making in a motion discrimination task. *Nature Neuroscience*, *9*(5), 682–689. https://doi.org/10.1038/nn1683

Hanks, T. D., Mazurek, M. E., Kiani, R., Hopp, E., & Shadlen, M. N. (2011). Elapsed Decision Time Affects the Weighting of Prior Probability in a Perceptual Decision Task. *Journal of Neuroscience*, *31*(17), 6339–6352. https://doi.org/10.1523/JNEUROSCI.5613-10.2011

Herregods, S., Denmat, P. Le, & Desender, K. (2023). Modelling Speed-Accuracy Tradeoffs in the Stopping Rule for Confidence Judgments. *BioRxiv*, 1–58.

Hilgenstock, R., Weiss, T., & Witte, O. W. (2014). You'd Better Think Twice: Post-Decision Perceptual Confidence. *NeuroImage*, *99*, 323–331. https://doi.org/10.1016/j.neuroimage.2014.05.049

Insabato, A., Pannunzi, M., Rolls, E. T., & Deco, G. (2010). Confidence-related decision making. *Journal of Neurophysiology*, *104*(1), 539–547. https://doi.org/10.1152/jn.01068.2009

Jeurissen, D., Shushruth, S., El-Shamayleh, Y., Horwitz, G. D., & Shadlen, M. N. (2022). Deficits in decision-making induced by parietal cortex inactivation are compensated at two timescales. *Neuron*, *110*(12), 1924-1931.e5. https://doi.org/10.1016/j.neuron.2022.03.022

Jun N. Y., Ruff D. A., Kramer L. E., Bowes B., Tokdar S. T., Cohen M. R., Groh J. M. (2022) Coordinated multiplexing of information about separate objects in visual cortex. *eLife* 11:e76452.

Kang, Y. H. R., Löffler, A., Jeurissen, D., Zylberberg, A., Wolpert, D. M., & Shadlen, M. N. (2021). Multiple decisions about one object involve parallel sensory acquisition but time-multiplexed evidence incorporation. *ELife*, *10:e63721*. https://doi.org/10.7554/eLife.63721

Katz, L. N., Yates, J. L., Pillow, J. W., & Huk, A. C. (2016). Dissociated functional significance of decision-related activity in the primate dorsal stream. *Nature*, *535*(7611), 285–288. https://doi.org/10.1038/nature18617

Kaufman, M. T., Churchland, M. M., Ryu, S. I., & Shenoy, K. V. (2015). Vacillation, indecision and hesitation in moment-by-moment decoding of monkey motor cortex. *ELife*, *4*:e04677. https://doi.org/10.7554/eLife.04677

Kellogg, W. N. (1931). The Time of Judgment in Psychometric Measures. *The American Journal of Psychology*, *43*(1), 65–86.

Kepecs, A., & Mainen, Z. F. (2012). A computational framework for the study of confidence in humans and animals. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *367*(1594), 1322–1337. https://doi.org/10.1098/rstb.2012.0037

Kepecs, A., Uchida, N., Zariwala, H. A., & Mainen, Z. F. (2008). Neural correlates, computation and behavioural impact of decision confidence. *Nature*, *455*(7210), 227–231. https://doi.org/10.1038/nature07200

Khalvati, K., Kiani, R., & Rao, R. P. N. (2021). Bayesian inference with incomplete knowledge explains perceptual confidence and its deviations from accuracy. *Nature Communications*, *12*(1), 1–16. https://doi.org/10.1038/s41467-021-25419-4

Kiani, R., Corthell, L., & Shadlen, M. N. (2014a). Choice certainty is informed by both evidence and decision time. *Neuron*, *84*(6), 1329–1342. https://doi.org/10.1016/j.neuron.2014.12.015

Kiani, R., Cueva, C. J., Reppas, J. B., & Newsome, W. T. (2014b). Dynamics of neural population responses in prefrontal cortex indicate changes of mind on single trials. *Current Biology*, *24*(13), 1542–1547. https://doi.org/10.1016/j.cub.2014.05.049

Kiani, R., Hanks, T. D., & Shadlen, M. N. (2008). Bounded Integration in Parietal Cortex Underlies Decisions Even When Viewing Duration Is Dictated by the Environment. *Journal of Neuroscience*, *28*(12), 3017–3029. https://doi.org/10.1523/JNEUROSCI.4761-07.2008

Kiani, R., & Shadlen, M. N. (2009). Representation of confidence associated with a decision by neurons in the parietal cortex. *Science*, *324*(5928), 759–764. https://doi.org/10.1126/science.1169405

Komura, Y., Nikkuni, A., Hirashima, N., Uetake, T., & Miyamoto, A. (2013). Responses of pulvinar neurons reflect a subject's confidence in visual categorization. *Nature Neuroscience*, *16*(6), 749–755. https://doi.org/10.1038/nn.3393

Lak, A., Costa, G. M., Romberg, E., Koulakov, A. A., Mainen, Z. F., & Kepecs, A. (2014). Orbitofrontal cortex is required for optimal waiting based on decision confidence. *Neuron*, *84*(1), 190–201. https://doi.org/10.1016/j.neuron.2014.08.039

Lak, A., Hueske, E., Hirokawa, J., Masset, P., Ott, T., Urai, A. E., Donner, T. H., Carandini, M., Tonegawa, S., Uchida, N., & Kepecs, A. (2020). Reinforcement biases subsequent perceptual decisions when confidence is low: A widespread behavioral phenomenon. *ELife*, *9*:e49834. https://doi.org/10.7554/eLife.49834

Latimer, K. W., Yates, J. L., Huk, M. L. R. M. A. C., & Pillow, J. W. (2015). Single-trial spike trains in parietal cortex reveal discrete steps during decision-making. *Science*, 34(6244), 184–188. https://doi.org/10.1093/annonc/mdx490/4098869/Hybrid-capture-based-genomic-profiling-of

Lewis, J. W., & Essen, D. C. V. A. N. (2000). Corticocortical Connections of Visual , Sensorimotor , and Multimodal Processing Areas in the Parietal Lobe of the Macaque Monkey. *The Journal of Comparative Neurology*, 428(1), 112–137.

Li, X., Su, R., Chen, Y., & Yang, T. (2023). Optimal policy for uncertainty estimation concurrent with decision making. *Cell Reports*, *42*(3), 112232. https://doi.org/10.1016/j.celrep.2023.112232

Lisi, M., Mongillo, G., Milne, G., Dekker, T., & Gorea, A. (2021). Discrete confidence levels revealed by sequential decisions. *Nature Human Behaviour*, *5*(2), 273–280. https://doi.org/10.1038/s41562-020-00953-1

Ma, W. J., & Jazayeri, M. (2014). Neural Coding of Uncertainty and Probability. *Annual Review of Neuroscience*, *37*(1), 205–220. https://doi.org/10.1146/annurev-neuro-071013-014017

McPeek, R. M., Skavenski, A. A., & Nakayama, K. (2000). Concurrent processing of saccades in visual search. *Vision Research*, *40*(18), 2499–2516. https://doi.org/10.1016/S0042-6989(00)00102-4

Meirhaeghe, N., Riehle, A., & Brochier, T. (2023). Parallel movement planning is achieved via an optimal preparatory state in motor cortex. *Cell Reports*, *42*(2), 112136. https://doi.org/10.1016/j.celrep.2023.112136

Meyniel, F., Sigman, M., & Mainen, Z. F. (2015). Confidence as Bayesian Probability: From Neural Origins to Behavior. *Neuron*, *88*(1), 78–92. https://doi.org/10.1016/j.neuron.2015.09.039

Middlebrooks, P. G., & Sommer, M. A. (2011). Metacognition in monkeys during an oculomotor task. *Journal of Experimental Psychology: Learning Memory and Cognition*, *37*(2), 325–337. https://doi.org/10.1037/a0021611

Moran, R., Teodorescu, A. R., & Usher, M. (2015). Post choice information integration as a causal determinant of confidence: Novel data and a computational account. *Cognitive Psychology*, *78*, 99–147. https://doi.org/10.1016/j.cogpsych.2015.01.002

Murphy, P. R., Robertson, I. H., Harty, S., & O'Connell, R. G. (2015). Neural evidence accumulation persists after choice to inform metacognitive judgments. *ELife*, *4*:e11946. https://doi.org/10.7554/eLife.11946

Nguyenkim, J. D., & DeAngelis, G. C. (2003). Disparity-based coding of three-dimensional surface orientation by macaque middle temporal neurons. *Journal of Neuroscience*, *23*(18), 7117–7128. https://doi.org/10.1523/jneurosci.23-18-07117.2003

Nienborg, H., & Cumming, B. G. (2009). Decision-related activity in sensory neurons reflects more than a neurons causal effect. *Nature*, *459*(7243), 89–92. https://doi.org/10.1038/nature07821

O'Connell, R. G. & Kelly, S. P. Neurophysiology of Human Perceptual Decision-Making. Annu Rev Neurosci 44, 495–516 (2021).

Orozco, S. P., Albert, S. T., & Shadmehr, R. (2021). Adaptive control of movement deceleration during saccades. *PLoS Computational Biology*, *17*(7), 1–30. https://doi.org/10.1371/journal.pcbi.1009176

Pachitariu, M., Steinmetz, N. A., Kadir, S. N., Carandini, M. & Harris, K. D. (2016). Fast and accurate spike sorting of high-channel count probes with KiloSort. Adv. Neural Infor. Process. Syst. 29, 4455–4464.

Pasler, H. (1994). Dual-task interference in simple tasks: Data and theory. *Psychological Bulletin*, 116, 220-244.

Peixoto, D., Verhein, J. R., Kiani, R., Kao, J. C., Nuyujukian, P., Chandrasekaran, C., Brown, J., Fong, S., Ryu, S. I., Shenoy, K. V., & Newsome, W. T. (2019). Decoding and perturbing decision states in real time. *Nature*. 591, 604-609. https://doi.org/10.1101/681783

Pereira, M., Faivre, N., Iturrate, I., Wirthlin, M., Serafini, L., Martin, S., Desvachez, A., Blanke, O., de Ville, D. Van, & del Millán, J. R. (2020). Disentangling the origins of confidence in speeded perceptual judgments through multimodal imaging. *Proceedings of the National Academy of Sciences of the United States of America*, *117*(15), 8382–8390. https://doi.org/10.1073/pnas.1918335117

Pleskac, T. J., & Busemeyer, J. R. (2010). Two-stage dynamic signal detection: A theory of choice, decision time, and confidence. *Psychological Review*, *117*(3), 864–901. https://doi.org/10.1037/a0019737

Pouget, A., Drugowitsch, J., & Kepecs, A. (2016). Confidence and certainty: Distinct probabilistic quantities for different goals. *Nature Neuroscience*, *19*(3), 366–374. https://doi.org/10.1038/nn.4240

Purcell, B. A., & Kiani, R. (2016). Hierarchical decision processes that operate over distinct timescales underlie choice and changes in strategy. *Proceedings of the National Academy of Sciences*, *113*(31), E4531–E4540. https://doi.org/10.1073/pnas.1524685113

Rescorla RA, and Wagner AR (1972) A theory of Pavlovian conditioning: variations in the effectiveness of reinforcement and nonreinforcement. In: Classical conditioning II: current research and theory (Black AH, Pro-kasy WF, eds.). New York: Appleton-Century-Crofts.

Resulaj, A., Kiani, R., Wolpert, D. M., & Shadlen, M. N. (2009). Changes of mind in decision-making. *Nature*, *461*(7261), 263–266. https://doi.org/10.1038/nature08275

Roitman, J. D., & Shadlen, M. N. (2002). Response of neurons in the lateral intraparietal area during a combined visual discrimination reaction time task. *Journal of Neuroscience*, *22*(21), 9475–9489. https://doi.org/10.1523/jneurosci.22-21-09475.2002

Saleem KS, and Logothetis NK. (2006). *A Combined MRI and Histology Atlas of the Rhesus Monkey Brain*. Amsterdam: Academic Press.

Sanders, J. I., Hangya, B., & Kepecs, A. (2016). Signatures of a Statistical Computation in the Human Sense of Confidence. *Neuron*, *90*(3), 499–506. https://doi.org/10.1016/j.neuron.2016.03.025

Sarafyazd, M., & Jazayeri, M. (2019). Hierarchical reasoning by neural circuits in the frontal cortex. *Science*, *364*(6441). https://doi.org/10.1126/science.aav8911

Shadlen, M. N., & Kiani, R. (2013). Decision making as a window on cognition. *Neuron*, *80*(3), 791–806. https://doi.org/10.1016/j.neuron.2013.10.047

Shadmehr, R., Reppert, T. R., Summerside, E. M., Yoon, T., & Ahmed, A. A. (2019). Movement Vigor as a Reflection of Subjective Economic Utility. *Trends in Neurosciences*, *42*(5), 323–336. https://doi.org/10.1016/j.tins.2019.02.003

Shan, H., Moreno-Bote, R., & Drugowitsch, J. (2019). Family of closed-form solutions for two-dimensional correlated diffusion processes. *Physical Review E*, *100*(3), 321-332. https://doi.org/10.1103/PhysRevE.100.032132

Shushruth, X. S., Mazurek, M., & Shadlen, M. N. (2018). Comparison of Decision-Related Signals in Sensory and Motor Preparatory Responses of Neurons in Area LIP. *Journal of Neuroscience*, *38*(28), 6350–6365. https://doi.org/10.1523/JNEUROSCI.0668-18.2018

Siegle, J. H. et al. (2017). Open Ephys: an open-source, plugin-based platform for multichannel electrophysiology. *J. Neural Eng.* **14**, 045003.

Sigman M, Dehaene S. (2005) Parsing a Cognitive Task: A Characterization of the Mind's Bottleneck. *PLOS Biology* 3(2): e37

Steinemann, N. A., Stine, G. M., Trautmann, E. M., Zylberberg, A., Wolpert, D. M., & Shadlen, M. N. (2023). Direct observation of the neural computations underlying a single decision. *eLife.* 12:RP90859.

Stolyarova, A., Rakhshan, M., Hart, E. E., O'Dell, T. J., Peters, M. A. K., Lau, H., Soltani, A., & Izquierdo, A. (2019). Contributions of anterior cingulate cortex and basolateral amygdala to decision confidence and learning under uncertainty. *Nature Communications*, *10*(1). https://doi.org/10.1038/s41467-019-12725-1

Stringer, C., Pachitariu, M., Steinmetz, N. *et al.* High-dimensional geometry of population responses in visual cortex. *Nature* **571**, 361–365 (2019). https://doi.org/10.1038/s41586-019-1346-5

Sutton RS, Barto AG (1998) Reinforcement learning: an introduction. Cambridge, MA: MIT

van den Berg, R., Anandalingam, K., Zylberberg, A., Kiani, R., Shadlen, M. N., & Wolpert, D. M. (2016a). A common mechanism underlies changes of mind about decisions and confidence. *ELife*, *5:e12192*. https://doi.org/10.7554/eLife.12192

van den Berg, R., Zylberberg, A., Kiani, R., Shadlen, M. N., & Wolpert, D. M. (2016b). Confidence Is the Bridge between Multi-stage Decisions. *Current Biology*, *26*(23), 3157–3168. https://doi.org/10.1016/j.cub.2016.10.021

Wang, S., Falcone, R., Richmond, B., & Averbeck, B. B. (2023). Attractor dynamics reflect decision confidence in macaque prefrontal cortex. *Nature Neuroscience*, *26*(11), 1970–1980. https://doi.org/10.1038/s41593-023-01445-x

Welford, A. T. (1952). The 'psychological refractory period' and the timing of high-speed performance – A review and a theory. *British Journal of Psychology*, 43, 2-18.

Xue, K., Zheng, Y., Rafiei, F., & Rahnev, D. (2023). The timing of confidence computations in human prefrontal cortex. *Cortex*, *168*, 167–175. https://doi.org/10.1016/j.cortex.2023.08.009

Zhongzheng F., Beam D., Chung J. M., Mamelak A. N., Adolphs R., Rutishauser U. (2022). The geometry of domain-general performance monitoring in the human medial frontal cortex. *Science*, 376(6593)

Zhou, Y., & Freedman, D. J. (2019). Posterior parietal cortex plays a causal role in perceptual and categorical decisions. Science. 365(6449), 180-185.

Zimnik, A.J., Churchland, M.M. Publisher Correction: Independent generation of sequence elements by motor cortex. *Nat Neurosci.* 25, 530 (2022).

Zylberberg, A. (2021). Decision prioritization and causal reasoning in decision hierarchies. *PLoS Computational Biology*. 17(12):e1009688. https://doi.org/10.1371/journal.pcbi.1009688

Zylberberg, A., Barttfeld, P., Sigman, M., & Pereira, A. (2012). The construction of confidence in a perceptual decision. *Front. Integr. Neurosci.* 6(79), 1–10. https://doi.org/10.3389/fnint.2012.00079

Supplementary Information for Vivar-Lazo & Fetsch, "Neural basis of concurrent deliberation toward a choice and degree of confidence.": Figures S1-S6

Figure S1. Three behavioral variables as a function of motion strength (% coh), including only the identical random seed trials ('double-pass' procedure of Bondy et al., 2018*, adapted for 4 options), to control for motion energy within each coherence. (A) Proportion of rightward choices as a function of motion strength. Both monkey H (top) and monkey G (bottom) showed significant differences in sensitivity between high- and low-bet trials. Smooth curves are from logistic regression. (B) Mean RT as a function of motion strength. Monkey H (top) displayed no differences in RT between high and low wager when controlling for motion energy, whereas monkey G (bottom) still showed large differences for all but the highest two coherences. Smooth curves show Gaussian fits. (C) Proportion of high bets as a function of motion strength. Both monkeys bet high more frequently as motion strength increased, irrespective of accuracy. Error bars in all plots are +/- SE.

*Bondy, A. G., Haefner, R. M. & Cumming, B. G. Feedback determines the structure of correlated variability in primary visual cortex. Nat Neurosci 79, 1 (2018).

Figure S2. Session-by-session sensitivity and amplitude parameters from fitting logistic and Gaussian functions to choice and RT, respectively. The vast majority of individual sessions showed greater sensitivity (accuracy) and faster RT amplitude when the monkey bet high vs. low.

Figure S3. (A) Accuracy as a function of RT quantile, split by motion strength (% coh). Accuracy tended to decrease as a function of RT ($p < .0085$ for every coherence except 0% in both monkeys and 51.2% in monkey G). (B) Proportion of trials with a high bet as function of RT. Colors same as A. (C) Accuracy as a function of motion energy. Colors represents five different RT quantiles. Significant increases in accuracy were observed across all RT quantiles for both monkeys (p<0.01). (D) Proportion of trials with a high bet as a function of motion energy. Colors same as C.

Figure S4. Serial and parallel model fits on unconditioned data. (A,C) Serial model fitted to choice, RT, and wager as a function of motion strength (% coh). (B,D) Parallel model fitted to choice, RT, and wager as a function of motion strength (% coh). First two columns correspond to monkey H and the last two to monkey G.

Figure S5. Variance of the conditional expectation (VarCE) estimated for the left-high and left-low populations of neurons. In both monkeys (H=top, G=bottom) VarCE begins to increase at approximately 0.2 s from motion onset, then decreases near saccade onset. Colors represent the two populations, and the shaded regions are standard errors calculated using a bootstrap.

Figure S6. Decoding of wager is distinct from the vertical component of saccade planning. (A) Schematic for 2-target control trials. Targets could be in either the high or low position, and both types were randomly interleaved with the standard 4-target trials, with an average probability of 0.1. (B) Wager decoder log odds as a function of time on trials with the standard 4-target configuration (solid trace, same as Figure 5C, wager) compared to 2-target control trials (dashed trace). Shaded regions indicate SEM. (C) Angle between the indicated pairs of decoder weight vectors as a function of time. Black solid = choice vs. wager on 4-target trials. Black dashed = choice on 4-target trials vs. wager on 2-target trials. Light grey = wager on 4-target vs. wager on 2-target trials. Shaded regions are the SEM. For all three relationships the weight vectors appear closer to orthogonal than parallel.