Tokenized and Continuous Embedding Compressions of Protein Sequence and Structure

Amy X. Lu[a,b], Wilson Yan[a], Kevin K. Yang[c], Vladimir Gligorijevic[b], Kyunghyun Cho[b,d], Pieter Abbeel[a], Richard Bonneau[b], Nathan Frey[b],

[a]*UC Berkeley, 2121 Berkeley Way, Berkeley, 94704, CA, United States*
[b]*Prescient Design & Genentech, 1 DNA Way, South San Francisco, 94080, CA, United States*
[c]*Microsoft Research, 1 Memorial Dr, Cambridge, 02142, MA, United States*
[d]*New York University, 251 Mercer St, New York, 10012, NY, United States*

Abstract

Existing protein machine learning representations typically model either the sequence or structure distribution, with the other modality implicit. The latent space of sequence-to-structure prediction models such as ESMFold represents the *joint distribution* of sequence and structure; however, we find these embeddings to exhibit massive activations, whereby some channels have values $3000\times$ higher than others, regardless of the input. Further, on continuous compression schemes, ESMFold embeddings can be reduced by a factor of $128\times$ along the channel and $8\times$ along the length, while retaining structure information at $<2\text{Å}$ scale accuracy, and performing competitively on protein function and localization benchmarks. On discrete compression schemes, we construct a tokenized all-atom structure vocabulary that retains high reconstruction accuracy, thus introducing a *tokenized representation of all-atom structure that can be obtained from sequence alone*. We term this series of embeddings as CHEAP (Compressed Hourglass Embedding Adaptations of Proteins) embeddings, obtained via the HPCT (Hourglass Protein Compression Transformer) architecture. CHEAP is a compact representation of both protein structure and sequence, sheds light on information content asymmetries between sequence and structure, democratizes representations captured by large models, and is designed to have flexible downstream applications such as generation, search, and prediction.

1. Introduction

Structure is an important determinant in scaffolding functions and biomolecular interactions. Real-world manufacturing of proteins require precise specification of sequence, and most extant functional biomolecules result from evolution in sequence space. Thus, being able to capture information from both sequence and structure modalities is important for many machine learning tasks, such as generation, similarity search, representation learning, and more. Protein sequence datasets can be 10^2 to 10^4 times larger than structural datasets. As of 2024, structural datasets such as the PDB [2] contains 218,196 samples, while sequence-only datasets such as UniRef50 [38] contains 63,849,054 samples. Being able to accurately capture high-precision structural information from sequence input is therefore desirable for machine learning applications in biology.

In recent years, sequence-to-structure prediction [20, 24] or structure-to-sequence design [6, 18] models have become increasingly capable. Such models have been described as "protein

structure foundation models" [44], mirroring a broader paradigm in AI where large models pretrained on large corpora of data can be adapted for an array of downstream tasks [4]. These model capture intricate information that emerges with scale, but in their native formulation as prediction models, they are unable to perform generation, similarity search, property prediction, etc., thus limiting their use as a foundation model.

Since sequence-to-structure models map from $p(\text{sequence})$ to $p(\text{structure})$, its intermediate latent space can be viewed as a representation of the joint distribution $p(\text{sequence, structure})$ (Figure 1B). Of particular interest, ESMFold [24] demonstrates that sequence-to-structure prediction can be built on top of protein language model (pLM) embeddings (Figure 1A). This provides a compact latent space of joint structure and sequence information (Figure 1C).

Figure 1: Deriving a joint latent space of structure and sequence using single sequence sequence-to-structure predictors. **(A)** Inference time usage of ESMFold, reinterpreted from Lin et al. [24]. A protein language model $\phi_{\mathbf{s}}(\mathbf{s})$, and a linear combination of output representations from each layer together maps a sequence $\mathbf{s}$ of length L to a latent embedding $\mathbf{x} \in R^{L \times 1024}$. The Structure Trunk uses this input to predict an output structure, $\hat{\Omega} \in \mathbb{R}^3$, along with a $L \times L$ pairwise embedding, $\mathbf{z}$, as input. At inference time, $\mathbf{z}$ is simply initialized to zeros, and updated in subsequent recycling iterations whereby outputs of the structure module, $\mathbf{s}'$ and $\mathbf{z}'$, are reused as inputs. **(B)** Harnessing the ESMFold latent space to obtain a joint representation of all-atom structure and sequence from sequence input. To decode the latent as structure (e.g. for latent generation), the original ESMFold structure decoder can be used; to map back to sequence, we separately train a sequence decoder, which achieves 99.7% validation accuracy. **(C)** The latent space $\mathbf{x}$ can be viewed as a joint embedding of sequence $\mathbf{s}$ and structure Ω; since the embedding requires only sequence to derive, but can be directly mapped to structure with the frozen ESMFold Folding Trunk, the embedding encodes both sequence and structural information.

Naïvely intercepting this latent space, however, presents numerous challenges. We find that pLM latent spaces contain abnormally high activations in certain channels that persist regardless of the input sequence (Figure 2), rendering them unwieldy for many downstream tasks. Additionally, the intrinsic dimensionality of language models, including protein language models, is often much smaller than the actual channel dimension [40]. Though subtle, embeddings with unnecessarily large dimensions sharply limits their utility. Aside

from increasing computational resource demand, they limit the range of possible downstream applications. For example, high resolution visual synthesis involving larger pixel arrays is generally a more difficult generation task. For protein similarity quantification and search, the dot-product matrix multiplication performed between sequence embeddings has memory constraints that scale in $\mathcal{O}(n^2)$ with the number of channels [3]. Furthermore, existing protein representations typically share the same length L as the original protein [24, 9]; however, as Transformer [43] architectures are being adopted for a broader range of tasks, it may be computationally desirable to downsample along the length dimension, since attention requires $\mathcal{O}(n^2)$ memory with length L. Finally, the compressibility of data provides insight into its complexity and can inform downstream modeling choices; for example, the compressibility of data has been related to the compute-optimal frontier between favoring dataset size as opposed to scaling laws [29].

In this work, we compress the ESMFold latent space and introduce **CHEAP** (Compressed Hourglass Embedding Adaptations of Proteins) representations in two variants: (1) token representations of the discrete biophysical concepts which induces the continuous 3D protein structure, and (2) continuous compressed embeddings that investigates the intrinsic dimensionality for tasks of interest. Continuous CHEAP embeddings can retain structural information at Angstrom-scale accuracy and achieve near 100% accuracy on retaining sequence information, despite reducing the channel dimension by up to 128×, and reducing the length of the embedding (i.e. downsampling) by 2×. Discretized CHEAP tokens also retain high levels of structural information, but unlike concurrent work such as ESM3 [13], CHEAP embeddings can be *obtained from sequence alone*, thus greatly enlarging the size of usable training data for applications requiring structural information. Our investigation furthermore sheds light on the mechanistic interpretability of increasingly popular protein language models, and on the information content asymmetry between structure and sequence, by demonstrating that structural information is much harder to compress than sequence information in protein embeddings. Code will be made publicly available at `https://github.com/amyxlu/cheap-proteins`.

2. Results

2.1. Defining a Joint Structure-Sequence Latent Space

A protein is comprised of a combination of 20 amino acids. Given a protein of length L with one-hot encoded sequence $\mathbf{s} \in \mathbb{I}^{L \times 20}$ and 3D structure $\Omega \in \mathbb{R}^3$, our goal is to find an embedding that encapsulates the joint distribution $\mathbf{x} \sim p(\mathbf{s}, \Omega)$; that is, the embedding $\mathbf{x}$ should both encode sequence information $\mathbf{x} = \phi_{\mathbf{s}}(\mathbf{s})$ and structure information $\mathbf{x} = \phi_{\Omega}(\Omega)$. We first decompose the mapping as

$$\mathbf{x} = \phi(\mathbf{s}, \Omega) = \phi_{\mathbf{s}}(\mathbf{s}) \circ \phi_{\Omega}(\Omega)$$

Though we can train separate encoders for $\phi_{\mathbf{s}}(\cdot)$ and $\phi_{\Omega}(\cdot)$, it is advantageous to leverage large pretrained models to improve performance and reduce computational overhead. In particular, ESMFold demonstrates that structure prediction is possible from protein language model representations learned by sequence masked language modeling, which reduces computation requirements and improves performance for orphan proteins [24]; we use this model as a representative for sequence-to-structure models. The ESM2-3B language model $\phi_{\text{ESM}}(\mathbf{s})$ embeds sequence $\mathbf{s}$ into a 2560-dimensional sequence representation, which then is mapped

via linear projections to an embedding $\mathbf{x} \in \mathbb{R}^{L \times 1024}$. This is used as input to the Folding Trunk $\phi_\Omega^{-1}(\mathbf{s}, \mathbf{z})$, where $\mathbf{z} \in \mathbb{R}^{L \times L \times D_\mathbf{z}}$ represents pairwise contacts. An overview of the original ESMFold model with notations used in this work is shown in Figure 1A.

A key observation is that at inference time, it is empirically sufficient to initialize input $\mathbf{z}$ as an array of zeros to obtain high quality structure predictions as reported in Lin et al. [24], such that $\Omega = \phi_\Omega^{-1}(\mathbf{x}, \mathbf{z})$ becomes $\hat{\Omega} = \phi_{\Omega,\text{Inference}}^{-1}(\mathbf{x})$. That is to say, $\mathbf{x}$ is a direct inverse-mapping from 3D structure Ω to a high-dimensional latent space. This sequence embedding $\mathbf{x}$ therefore, obtained as the latent space of the ESMFold model, can be seen as our embedding of the joint distribution of $\phi(\Omega, \mathbf{s})$:

$$\mathbf{x} = \phi_\mathbf{s}(\mathbf{s}) \qquad \text{Linear combination of ESM2 representations} \qquad (1)$$
$$\Omega = \phi_\Omega^{-1}(\mathbf{x}, \varnothing) \qquad \text{ESMFold Structure Module} \qquad (2)$$

Note that $\mathbf{x}$ is not precisely the same as ESM2 embeddings, since in ESMFold, ESM2 representations from each layer are linearly combined with trainable weights to create the $\mathbf{x}$ embedding that is input to Folding Trunk ϕ_Ω^{-1}. Appendix A provides a code sketch for obtaining $\mathbf{x} \sim p(\mathbf{s}, \Omega)$, and a graphical description is shown in Figure 1B.

We would also like to map this latent space back to sequence and structure space, for assessing compression performance and for generative modeling. To decode this latent space back to protein sequences, a "back-mapping" sequence encoder $\mathbf{s} = \phi_\mathbf{s}^{-1}(\mathbf{s})$ is trained separately, which effectively is the backward mapping of the ESM2 language model. We achieve a per-token accuracy of 99.7% on a randomly partitioned heldout set (detailed in Section 4.5), likely because the task of mapping a language model embedding to 20 classes is fairly simple. To obtain structure from embedding, we can simply use the frozen ESMFold folding trunk, $\Omega = \phi_\Omega^{-1}(\mathbf{x})$. If generative model parameters θ are learned to approximate $p_\theta(\mathbf{x})$, then at inference time, after sampling $\tilde{\mathbf{x}} \sim p_\theta(\mathbf{x}) = p_\theta(s, \Omega)$, we can generate new $\tilde{\mathbf{s}} = \phi_\mathbf{s}^{-1}(\tilde{\mathbf{x}})$ and $\tilde{\Omega} = \phi_\Omega^{-1}(\tilde{\mathbf{x}})$, using the decoders $\phi_\Omega^{-1}(\mathbf{x})$ and $\phi_\mathbf{s}^{-1}(\tilde{\mathbf{x}})$ defined above.

2.2. ESMFold Latent Space Contains Massive Activations

We find that the latent space of ESMFold is pathologically disorganized, whereby some channels have mean values up to $3000\times$ larger than others. This is consistent with reports of this phenomenon in large Transformer [43] models for text and image modalities, where they are sometimes referred to as massive activations [37] or outlier features [7]. Figure 2A visualizes embedding values at various intermediate layers between the ESM2 output and the folding trunk, following variable notations in Appendix A.

Massive activation accumulation begins in the ESM2 language model. The top values in any given layer can be up to $3000\times$ larger than the median activation value in a given layer (Figure 2B). Figure 2C visualizes the means of each channel. When three outlier channels with massive activations are removed, the resulting distribution is more organized; however, removing these three features alone causes structure prediction performance to deteriorate, as seen qualitatively (Figure 2D) and quantitatively (Figure 2E), bringing the TM-Score of predictions down from an average of 0.97 down to 0.14.

Massive activations limits the flexibility with which large protein models can be used as foundation models. Dettmers et al. [7] examines 8-bit model quantization to reduce memory usage during inference, which is rendered difficult due to the expanded numerical range caused by the 0.01% of abnormally high values. Massive activations have also been

Figure 2: ESM2 contains massive activations in its embeddings. **(A)** For certain activations, massive activations occur at certain channels regardless of the sequence positions, at channel positions [274, 641, 37]. The pattern persists across layers (Appendix A). **(B)** Layerwise analysis demonstrating an increase in the magnitude of activations in the 3 billion parameter ESM2 model. Gray denotes the median activation magnitude; blue, green, and purple denote the top 3 largest activation magnitudes per layer output, and are significantly larger than the median activation. **(C)** Histogram of per-channel means. The total range of embedding values is greatly enlarged by the presence of massive activations. By removing three outlier channels with mean absolute values >20, the resulting latent space is closer to the Gaussian assumption necessary for diffusion. **(D)** Structure prediction results after setting the three outlier channels to zero. Purple denotes original ESMFold prediction, and green denotes ESMFold prediction after setting outlier channels to zero. Removing 3 channels with massive activations causes performance to deteriorate. **(E)** Quantitative assessment of the effect of outlier channel removal on structure prediction, measured by the TMScore (measure of structure prediction accuracy) and pLDDT (measure of model confidence), visualized for a random sample of 64 CATH structures. Model performance deteriorates by both metrics.

observed to dominate attention patterns, and have been suggested to act as an implicit bias term [37]. Given that attention mechanisms have been shown to learn protein contacts [30], these massive activations may play interpretable roles in how structure information emerges from protein language models; we leave the specifics of this investigation as future work. We combat this by applying a per-channel normalization scheme, described in Section 4.1.

2.3. A Neural Compression Architecture for Protein Embeddings

The equivalence between data compression and data distribution representation learning is foundational to machine learning [25]. Biological data is comprised of both signal and noise, not all of which is necessary to understand its structure or function; despite this, data

Figure 3: The Hourglass Protein Compression Transformer (HPCT) model. For a protein with 512 amino acids, the embedding right before the ESMFold structure encoder has dimensions 512×1024. To correct for massive activations, the embedding is normalized using the statistics of each channel (Section 4.1). The encoder condenses the channel dimensions with a linear projection and a linear downsampling operation along the length dimension. In the bottleneck layer, we examine methods for obtaining both discrete and continuous compressed embeddings.

compression remains understudied for proteins. Our work aims to bridge this gap by studying protein embeddings as an instance of neural compression. We design the Hourglass Protein Compression Transformer (HPCT) architecture, an autoencoder with a bottleneck layer, further detailed in Section 4.2 and visualized in Figure 3, for protein embedding compression.

Proteins have different lengths, rendering the ResNet [14] autoencoder architecture used in vision a poor choice. Inspired by Nawrot et al. [28], HPCT includes a linear downsampling operation (Algorithm 8) which "shortens" the embedding $x \in \mathbb{R}^{L \times D}$ to $x \in \mathbb{R}^{\frac{L}{S} \times D}$ using a shortening factor of S. A linear projection further compresses the channel dimension. The model is trained end-to-end with a mean-squared error reconstruction loss, such that it is trained to maximally preserve the original content across the bottleneck layer. At inference time, the output of the bottleneck layer is used as the compressed embedding. In early experiments, we also apply a sequence-space loss (i.e. cross-entropy loss constraint that decoded amino acids corresponds to the original) and structure-space loss (backbone Frame-Aligned Point Error [20]), but did not find these to substantially improve performance.

Continuous vs. Discrete Compressions. Performing data compression also has practical motivations. For example, in high-resolution image synthesis, increased number of pixels exacerbates FLOPS needed and generation difficulty. To combat this, Latent Diffusion Models (LDM) [32] performs diffusion modeling [17, 36] in a continuous compressed latent space learned by a VQ-GAN [10] encoder. Another successful technique is encoding continuous images as discrete tokens, and generate tokens using an autoregressive model or by sampling from mask tokens [5, 15, 31]. We aim to make contact with these paradigms by investigating how to build the necessary autoencoder for protein data.

All experiments uses the embedding $\mathbf{x}$ defined in Section 2.1, though the architecture can be used for any sort of embedding compression. The dimensions of $\mathbf{x}$ defined in Section 2.1 is $L \times 1024$ for a sequence with length L.[1] For a protein sequence of length 512, the size of this embedding maps to high-resolution image synthesis. As a point of comparison, LDMs [32] compresses input images of size $256 \times 256 \times 3$ down to $64 \times 64 \times 4$ before diffusing.

At the bottleneck layer of HPCT, we prefer either quantization step at the bottleneck to obtain **discrete** compressed embeddings, or a tanh step to obtain **continuous** compressed embeddings. The tanh layer constrict embedding values to between $[-1, 1]$ and improve its utility (e.g. for latent diffusion); in early experiments, we found that it does not degrade performance.

Compression Evaluation Metrics. In following sections, we assess continuous and discrete compression performance. To assess in-distribution structure reconstruction, we train and assess on the CATH [35] database, though a sequence-only dataset such as Pfam [27] or UniRef [38] can also be used (select results in Appendix C). Mirroring the usage of perceptual losses for assessing compression in images [10], which favors retention of visual details necessary for downstream tasks as opposed to purely reconstruction, we examine reconstruction performance in the structure and sequence space in addition to the mean-squared-error between input and reconstruction. The template modeling score (TM-Score) is a backbone-only metric of structure reconstruction, while root-mean-squared distance (RMSD) is a more fine-grained measure between atom positions. Root-mean-squared paired distance (RMSPD) is similar to RMSD, but uses pairwise distances rather than atom positions; we use it to assess superimposition-free reconstruction accuracy. Sequence reconstruction accuracy is the fraction of token matches after decoding back to sequence space, divided by the number of tokens in the sequence. As reference points for interpreting structure reconstruction results, we note that 1.34Å is the inter-carbon distances taken from Jumper et al. [20], and range of 0.8Å to 4.1Å is the range experimental resolution for the original structures.

2.4. A Discrete Vocabulary of Protein Structure and Function

"Quantization" or "tokenization" here refers learning an encoder that maps an input to a discrete representation. Given a d-dimensional input $\mathbf{a} \in \mathbb{R}^d$, and a pre-specified codebook size C, the goal is to find a set of integers from $\mathcal{C} \in \{0, 1, ..., C\}$ that represents the input. Intuitively, though pixel inputs of the visual world is continuous, many discrete concepts exist, such as color, shape, and size; similarly, though structure exist in the continuous 3D space, the biophysical concepts that cause the shape might manifest discretely. Furthermore, obtaining a discrete vocabulary of representations allows scaling infrastructure for large language models to be applied.

Tokenized representations of protein structure is an area of limited investigation. Foldseek [42] introduces the 3Di vocabulary for its search algorithm, though this is limited to 20 amino acids, and it is known that codebook size (i.e. number of discrete options) is a crucial factor in representation quality. Some concurrent works have also examined characterizing a tokenization scheme for structure [11, 23, 12]. However, these methods are learned on structural input, unlike the scheme here, which can be used on sequence-only input. ESM3

---

[1]Note that the embedding dimension has already been reduced from the $L \times 2560$ ESM-3B embeddings.

[13] constructs separate discrete vocabularies for structure, function, and sequence, as opposed to directly crafting a single discrete embedding that can be decoded into multiple modalities.

While Vector-Quantized Variational Auto-Encoders (VQ-VAE) [41] is a popular choice, it can be difficult to optimize, and is prone to "codebook collapse", whereby a few codes are over-utilized, and require specific intervention [39, 21, 8, 19]. Thus, we also investigate the recently proposed FSQ [26] approach, which obtains token representations without quantizer parameters. Details of the VQ-VAE and FSQ methods are described in Section 4.4.

The choice of codebook size relates to the bits of information content in the data, and the degree to which information loss is tolerable for the downstream task. It is unclear how to best select this for all-atom protein structure and sequence. We find that while VQ-VAE outperforms FSQ on codebook sizes smaller than $2^8 = 256$, FSQ consistently outperforms VQ-VAE on latent space reconstruction MSE, structure space metrics (both the backbone-only TM-Score and the all-atom RMSD), and sequence space metrics (Figure 4). This is consistent with image experiments in Mentzer et al. [26]. FSQ generally has more evenly distributed codebook usage, especially for larger codebooks. This is reflected in the high VQ-perplexity (perplexity when selecting a code during the VQ-VAE quantization process) as codebook size C increases, a metric which does not apply to FSQ.

Figure 4: Assessing structure, sequence, and latent reconstruction across codebook sizes for the FSQ and VQ-VAE methods. **(A)** Across all metrics, FSQ outperforms VQ-VAE at codebook sizes greater than 2^{10}. Blue arrows denote metrics where lower is better, and red arrows denote metrics where higher is better. VQ-perplexity refers to the codebook selection prediction in VQ-VAE, which does not apply to FSQ. **(B)** Examining codebook utilization for FSQ and VQVAE. We find that codebook utilization is generally more favorable using FSQ (left), though we do not find catastrophic codebook collapse for VQ-VAE above a codebook size of 2^4.

2.5. Continuous Compression Performance on Structure Reconstruction and Function Prediction

Our experiments empirically validate the hypothesis that many channel dimensions in protein representations are extraneous and that the intrinsic dimensionality likely lower. Figure 5A examines the ability for compressed embeddings to retain structural information,

examined both with and without length downsampling. Even with a 32× compression factor down to only 32 channels, the model is still able to achieve <1.34Å RMSD in structure fidelity compared to the original prediction. When shortening by a factor of two, one can attain a <1.34Å RMSD at 64 channels or higher. For sequences, there is nearly no drop in reconstruction performance until compressing to less than 8 channels. Interestingly, the largest drops in performance is found after compressing to 4 channels, by both structure and sequence reconstruction accuracy, which may be related to the average number of atoms in amino acid residues. The pairwise RMSD, which is independent of superimposition, is generally lower than the RMSD, suggesting that some atomic distances may be due to loss of precision on trivial 3D super-imposition, rather than insufficiently learning protein information. A visual depiction of how compression changes the predicted structure is shown in Figure 5C. **??** shows TSNE results for embeddings at different levels of compression.

Figure 5: Assessing compressibility of structural and sequence information in protein embeddings. **(A)** Examining compressibility of backbone structure (TM-Score), sequence identity (sequence recovery accuracy), all-atom structure (RMSD), and superimposition-free all-atom structure (pairwise RMSD). Sequence information and backbone information can be preserved nearly perfectly even after reducing down to only 8 channels; all-atom structure RMSD similarly achieves <1.34Å accuracy at 16 channels or less. **(B)** Length information can be compressed while preserving sequence and backbone information even after reducing channel dimensions to 32. **(C)** Visual overlay of structural information compressibility. Even with only 4 embedding channels, secondary structures can be preserved after reconstruction.

We further examine function and localization prediction using datasets from the PEER benchmark [45] for embeddings at different compression levels, and fund that functional information seems to suffer more with compression than structure and sequence information.

Section 4.5 describes the details of the training procedure. This is consistent with recent works demonstrating that protein language models fail on downstream tasks which do not involve structure [22]. For some tasks, such as β-lactamase activity prediction and subcellular localization, compression seems to be more impactful than tasks such as solubility. We show comparisons against other methods along with additional benchmarks in Appendix D. On structure related tasks, compressed embeddings can compare competitively with other methods, sometimes exceeding their performance.

Figure 6: Using linear probes to evaluate compressibiliy of functional information, with $2\times$ lengthwise shortening applied. Orange star denotes uncompressed performance. Unlike structure and sequence, performance degrades more gradually for some functions (e.g. β-lactamase activity), though the performance drop is less pronounced for other tasks (e.g. solubility).

2.6. Interpolation and Noising in the Latent Space

To examine the smoothness of the latent space, we perform linear interpolations in the embedding space, and examine how this manifests in the structure and sequence space. For two real proteins in the CATH dataset, we obtain the CHEAP embedding representation, and perform a linear interpolation as $\mathbf{x}' = t\mathbf{x}_1 + (1 - t)\mathbf{x}_2$. We then transform this embedding back to the sequence and structure space, and examine both their similarities to the proteins which they were interpolating between, and measures of the "naturalness" of the produced sequence via perplexity and of the structure via pLDDT (Section 4.3).

Figure 7A demonstrates reconstruction results in the latent space. We find that the unprocessed ESMFold latent space is not very "smooth" – that is, despite changes linearly in continuous space, the discrete changes in the sequence space is limited, as visualized by the sequence accuracy to the end sequence. A similar case is observed for structures. After the per-channel normalization (Section 4.1) and compressing down to 8 channels, the sequence space is more "smooth" and changes more gradually with linear interpolation in the embedding space; however, the structure space remains less smoothed out. Despite being a smoother interpolation between the two natural proteins, these proteins are less "natural", though it may better reflect the ragged nature of the hypothesized protein fitness landscape [33]. This may reflect the classic quality-versus-diversity trade-off, but also raises questions

on the geometry of the protein structure fitness landscape, and whether a more rugged or sharp landscape is more suitable for exploration. Figure 7C provides a visual of how the structures change when interpolating in the original latent space versus the compressed latent space. The jumps are more gradual when interpolating in the compressed latent space and then transforming back to the embedding with massive activations; however, they also tend to be more unstructured.

Figure 7: Comparing linear interpolation in various embedding spaces as empirical assessment of geometry. **(Top)** To examine how smoothly sequence changes as a result of interpolating in a given latent space, we decode interpolations back to sequence/structure, and examine sequence recovery accuracy (↓) and backbone TMScore (↑) to the final sample. Despite moving linearly in embedding space, the actual sequence and structure samples that embedding interpolations map to remain tightly coupled to proteins seen in the training set. Interpolations typically occupy regions of low perplexity (↓) and high structure prediction confidence (pLDDT, ↑). Our compression and normalization schemes hele improve the smoothness of interpolations and raggedness of the approximated fitness landscape. **(Bottom)** Visual examination of structure reconstructions of linear embedding interpolations.

3. Discussion

In this work, we characterize how the latent space of large protein sequence-to-structure models can represent the joint distribution of sequence and structure. We further identify pathologies of massive activations in ESMFold; indeed, the original paper uses a linear combination of representations from all layer outputs of the language model rather than the final embedding, and though no explicit justification or ablations were given in Lin et al. [24], our findings of how pathological massive activations accrue across layers may contribute to why representations from intermediate layers might be as or more informative than the final layer embedding. We also find that protein sequence embeddings are highly compressible, and develop the Transformer-based HPCT autoencoder architecture. Sequence information can be captured by embeddings of only a 8 channels. All-atom structural information is less compressible than sequence information, but nonetheless, remarkable reconstruction performance can be obtained by embeddings that undergo $128\times$ channelwise compression and $8\times$ lengthwise compression between amino acids. We also develop a *structure tokenization dictionary* which can be *obtained from sequence alone*, unlike concurrently proposed structural tokenizers [11, 23, 12]. Further, we show that FSQ is more effective than the dominant VQ-VAE approach (which has also been used for proteins by recent works [13]), especially for large codebooks.

Building a representation of the joint distribution of structure and sequence has many desirable traits for generation, search, and representation learning. The CHEAP series of embeddings is a compact joint embedding of the latent space that can be flexibly employed. Furthermore, our empirical results raise interesting theoretical questions on the information content and geometry of protein embeddings. The compressibility of embeddings with respect to sequence identity and structural precision corroborates empirical investigations that the intrinsic dimensionality of existing structure foundation models is likely much lower [40], and there may be over-parameterization in existing models. The lack of a clear pattern for linear probes relating to function further illustrates the poorly understood nature of how protein embeddings capture relevant information.

An alternative means of achieving this is to train and/or finetune ESMFold (or another sequence-to-structure model) end-to-end with the bottleneck layer and with a channel normalization before it. We hypothesize that this should improve the properties desirable for empirical downstream use without compromising structure prediction quality, though due to computational resource limitations, we leave this as future work.

4. Methods

4.1. Per-Channel Normalization

To address the issue of massive activations as shown in Figure 2, we use a per-channel normalization scheme. Conventionally, following Ho et al. [17], image generation works rescale image pixel values from $[0, 256]$ to $[-1, 1]$. Subsequent works find this bounding strategy to be important to performance, such as color saturation [34]. To remedy channel-specific massive activations, the embeddings are processed as:

$$\mathbf{x}' = \frac{\mathbf{x} - \mathbf{x}_{\min}}{\mathbf{x}_{\max} - \mathbf{x}_{\min}} \times \Big((c_{\max} - c_{\min}) + c_{\min}\Big)$$

where $\mathbf{x}_{\min}$ and $\mathbf{x}_{\max}$ are vectors with shape $(1024,)$, and broadcasted along length dimension. They denote statistics calculated independently for each channel. This prevents outlier channel values from dominating the normalization. In experiments, we choose $c_{\min} = -1$ and $c_{\max} = 1$.

Visual inspection shows that after this transformation, the distribution better befits the Gaussian distribution needed for diffusion, as visualized in Figure 2. A random subset of 5,000 samples from CATH [35] is used, but we find that these mean and standard deviation statistics vary little across datasets such as CATH, UniRef [38], and Pfam [27], consistent with the general observation that massive activations are not input-specific [37]. In simple diffusion experiments, this greatly improves stability of training.

4.2. Hourglass Compression Transformer

A sketch of the hourglass compression transformer is as follows, inspired largely from Nawrot et al. [28]. Linear downsampling layers serve to shorten the embedding lengthwise, while the downprojection reduces the channel dimension. The attention resampling is an attention layer that attends to both the pre- and post-shortening embeddings. This is similar to the approach in LDM where compressed latent space is taken to be the continuous representation just prior to the VQ layer (except we replace the VQ with FSQ in this case).

Algorithm 1 Hourglass Compression Transformer

Require:
  embedding $\mathbf{a} \in \mathbb{R}^{L \times D}$, mask $\mathbf{m}^{\text{Length}[L]} := \{1,0\}^L$, shortening factor $S \in \mathbb{Z}$, downprojection factor $K \in \mathbb{Z}$, downprojection $W_d \in \mathbb{R}^{D \times \frac{D}{K}}$, upprojection $W_u \in \mathbb{R}^{\frac{D}{K} \times D}$
  procedure HOURGLASSCOMPRESSION($\mathbf{a}, \mathbf{m}$)
    $\mathbf{a} \leftarrow \text{TRANSFORMER}(\mathbf{a}, \mathbf{m})$
    $\mathbf{a}' \leftarrow \text{LINEARDOWNSAMPLING}(\mathbf{a}, S)$ ▷ *Alg. 2*
    $\mathbf{m}' \leftarrow \sum_S \mathbf{m}^{\text{Length}[L] \rightarrow [\frac{L}{S}]} > 0$ ▷ *Reduce*
    $\mathbf{a}' \leftarrow \text{ATTENTIONRESAMPLING}(\mathbf{a}', \mathbf{a}, \mathbf{m}')$
    $\mathbf{c} \leftarrow W_d \mathbf{a}'$
    if quantize **then**
      $\mathbf{c} \leftarrow \text{BOTTLENECK}(\mathbf{c}, \mathbf{m}')$
    else
      $\mathbf{c} \leftarrow \text{TANH}(\mathbf{c})$
    end if
    $\mathbf{a}' \leftarrow W_u \mathbf{c}$
    $\mathbf{a} \leftarrow \text{LINEARUPSAMPLING}(\mathbf{c}', \mathbf{m}')$
    $\mathbf{m} \leftarrow \mathbf{m}'^{\text{Length}[\frac{L}{S}] \rightarrow [L]} > 0$ ▷ *Repeat*
    $\mathbf{a} \leftarrow \text{ATTENTIONRESAMPLING}(\mathbf{a}, \mathbf{a}', \mathbf{m})$
    $\mathbf{a}_{\text{reconstructed}} \leftarrow \text{TRANSFORMER}(\mathbf{a}, \mathbf{m})$
  return $\mathbf{a}_{\text{reconstruction}} \in \mathbb{R}^{L \times D}$, $\mathbf{c} \in \mathbb{R}^{\frac{L}{S} \times \frac{D}{K}}$
  end procedure

Though different operations may be used for $g(x)$, we find a simple linear downsampling to work well (Algorithm 8), which can be seen as a convolution with a filter size and stride both equal to S. Since the original model is designed for sequence-to-sequence tasks rather than

---

Algorithm 2 Hourglass Encoder Shortening by Linear Downsampling

---

Require:
 $\mathbf{a} \in \mathbb{R}^{L \times D}$,
 integer shortening factor S,
 $W \leftarrow W \in \mathbb{R}^{(SD) \times D}$,
 procedure $\text{LINEARDOWNSAMPLING}(\mathbf{a}, S)$
  $\mathbf{a} \leftarrow \mathbf{a} \in \mathbb{R}^{\frac{L}{S} \times (SD)}$               $\triangleright$ Reshape
  $\mathbf{a} \leftarrow \mathbf{a}W$
  return $\mathbf{a} \in \mathbb{R}^{\frac{L}{S} \times D}$
 end procedure

---

compression, we remove the skip connections that would make the solving the reconstruction task trivial. Additionally, we add a projection layer along the channel dimension after each shortening operation. At training time, $\mathbf{x}_{\text{reconstructed}}$ is used for calculating the mean-squared-error reconstruction loss, and at inference time, the output of the encoder is used as the compressed representation, with additional processing in the bottleneck, depending on if the compression is discrete or continuous. Linear downsampling consists of flattening operation, followed by a learned downsampling weight matrix, and finally reshaped back to L/S, where L is the original length, and S is the shortening factor.

4.3. Naturalness Evaluation

For evaluating sequence naturalness with perplexity, we use the autoregressive RITA XL model [16]. Intuitively, perplexity can be seen as a measure of how "confused" a model is when selecting the next token. If a sequence is in-distribution with the natural proteins that the model was trained on, its perplexity will be lower, since the model can make sense of the patterns. Conversely, if a sequence out-of-distribution (e.g. is not a valid protein) and learned patterns from natural proteins cannot help the model discern what the next token should be, then the perplexity increases.

For evaluating structure naturalness, we use the predicted Local Distance Difference Test (pLDDT) score, which is returned by the ESMFold prediction head along with the all-atom structure. The metric was introduced in AlphaFold2 [20] and is a predicted measurement of the model's certainty in the structure at that particular position. Similar to the reasoning behind perplexity as a metric of naturalness, a high pLDDT suggests that a metric is in-distribution with the natural proteins that was seen during sequence-to-structure training. Note that pLDDT tends to favor structured regions, and is typically low for disordered regions, even in real proteins.

4.4. Quantization Methods

Vector-Quantized Variational Autoencoder. The VQ-VAE [41] learns a discrete, compressed semantic representation of the input, typically of images. In the forward pass, the encoder h_e produces a continuous feature representation of input $\mathbf{x}$. Then, each feature vector is mapped to a discrete code in the codebook space, $\mathcal{C}$, where each discrete code is associated with a continous vector $\mathbf{e}_i$. The assembled array of learned codes and their vector embeddings $\mathbf{z} = \{\mathbf{e}_1, \mathbf{e}_2, ... \mathbf{e}_{|\mathcal{C}|}\}$ and their corresponding feature features are fed into the decoder $h_q(\mathbf{z})$.

Since the quantization operation is not differentiable, the straight-through estimator (STE) [1] is used by copying the gradients from the decoder input to the encoder output.

The codebook is selected via a nearest-neighbor search in Euclidean space; auxiliary losses are introduced to pull the code vectors towards the unquantized encoder outputs. As in autoencoder training, a reconstruction loss between output and input is also used. The complete VQ-VAE loss is:

$$L_{\text{VQ}} = \log p(\mathbf{x}|h_q(\mathbf{z})) + ||\text{sg}[h_e(\mathbf{x})] - \mathbf{z}||_2^2 + \beta||h_e(\mathbf{x}) - \text{sg}[\mathbf{z}]||_2^2$$

Finite Scalar Quantization. Rather than using a nearest-neighbor search to choose a code, FSQ directly quantizes the continuous encoder representations $\mathbf{z} \in \mathbb{R}^d$ into L bins:

$$\mathbf{z} = h_e(\mathbf{x}), \mathbf{z} \in \mathbb{R}^d \qquad \text{Continuous encoder representation} \qquad (3)$$
$$\hat{\mathbf{z}} = \tanh(\mathbf{z}) \qquad \text{Bound to } [-1, 1] \qquad (4)$$
$$\hat{\mathbf{z}} = \text{round}(\lfloor (L/2) \rfloor \cdot \hat{\mathbf{z}}) \qquad \text{Discretize to } L \text{ bins and round to nearest integer} \qquad (5)$$

The predetermined bins L is selected to be small relative to VQ-VAE codebook sizes. The *implicit codebook size* $|\mathcal{C}|$, however, comes from the combinatorial possibilities arising from using one of L integers at each of the D channels. For $\mathbf{z}$ with d channels, there are d associated integer representations, and thus $|\mathcal{C}| = L^d$. A large implicit codebook can thus be achieved, while forcing all codes to be used.

4.5. Training

Compression Model Training. For all continuous compression models, we use a learning rate of 8^{-5} with the AdamW optimizer and 5000 warmup steps. For discrete compression models, we use a learning rate of 1^{-4}, with the AdamW optimizer and 1000 warmup steps. Train and test sets were split randomly. CATH is used for all experiments, with the exception of the experiments in Appendix C.

Sequence Decoder. For the sequence decoder, we use a fully connected network with two layers and a hidden size of 1024. This network is able to converge relatively fast. Though ESM2 was already trained with a masked token objective, and thus has pretrained weights that map the language model output to logit space, we opt for retraining, since our defined embedding is intercepted after the linear projection layers (with 1024 dimensions), where as the original ESM2-3B model has 2580 dimensions.

4.6. Function prediction

For results in Figure 5C and Appendix D, we use the dataset splits and tasks from Xu et al. [45]. For all compressed embeddings, we add a trainable projection layer back to 1024, such that the size of the downstream fully-connected network used for prediction is the same size for all compared networks. A mean pool is applied to the embeddings, with a 2-layer multilayer perceptron used as the downstream probe.

5. Acknowledgments

Authors thank Mingjie Sun for productive discussions on massive activations in large language models, and help with producing Figure 2A. Authors additionally thank Sidney Lisanza, Daniel Severo, Igor Mordatch, Andrew Leaver-Fay, and Lian Huang for discussion and comments. AXL is supported in part by the NSERC PGS-D scholarship and Nissan.

References

[1] Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

[2] Helen M Berman, John Westbrook, Zukang Feng, Gary Gilliland, Talapady N Bhat, Helge Weissig, Ilya N Shindyalov, and Philip E Bourne. The protein data bank. *Nucleic acids research*, 28(1):235–242, 2000.

[3] Ron Boger, Amy Lu, Seyone Chithrananda, Kevin Yang, Petr Skopintsev, Ben Adler, Eric Wallace, Peter Yoon, Pieter Abbeel, and Jennifer Doudna. Toph (true retrieval of proteins homologs): Adapting a contrastive question-answering framework for protein search.

[4] Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

[5] Huiwen Chang, Han Zhang, Lu Jiang, Ce Liu, and William T Freeman. Maskgit: Masked generative image transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11315–11325, 2022.

[6] Justas Dauparas, Ivan Anishchenko, Nathaniel Bennett, Hua Bai, Robert J Ragotte, Lukas F Milles, Basile IM Wicky, Alexis Courbet, Rob J de Haas, Neville Bethel, et al. Robust deep learning–based protein sequence design using ProteinMPNN. *Science*, 378: 49–56, 2022.

[7] Tim Dettmers, Mike Lewis, Younes Belkada, and Luke Zettlemoyer. Gpt3. int8 (): 8-bit matrix multiplication for transformers at scale. *Advances in Neural Information Processing Systems*, 35:30318–30332, 2022.

[8] Prafulla Dhariwal, Heewoo Jun, Christine Payne, Jong Wook Kim, Alec Radford, and Ilya Sutskever. Jukebox: A generative model for music. *arXiv preprint arXiv:2005.00341*, 2020.

[9] Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rehawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, et al. Prottrans: Toward understanding the language of life through self-supervised learning. *IEEE transactions on pattern analysis and machine intelligence*, 44(10):7112–7127, 2021.

[10] Patrick Esser, Robin Rombach, and Bjorn Ommer. Taming transformers for high-resolution image synthesis. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 12873–12883, 2021.

[11] Zhangyang Gao, Cheng Tan, and Stan Z Li. Foldtoken2: Learning compact, invariant and generative protein structure language. *bioRxiv*, pages 2024–06, 2024.

[12] Benoit Gaujac, Jérémie Donà, Liviu Copoiu, Timothy Atkinson, Thomas Pierrot, and Thomas D Barrett. Learning the language of protein structure. *arXiv preprint arXiv:2405.15840*, 2024.

[13] Tomas Hayes, Roshan Rao, Halil Akin, Nicholas J Sofroniew, Deniz Oktay, Zeming Lin, Robert Verkuil, Vincent Q Tran, Jonathan Deaton, Marius Wiggert, et al. Simulating 500 million years of evolution with a language model. *bioRxiv*, pages 2024–07, 2024.

[14] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[15] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 16000–16009, 2022.

[16] Daniel Hesslow, Niccoló Zanichelli, Pascal Notin, Iacopo Poli, and Debora Marks. RITA: a study on scaling up generative protein sequence models. *arXiv preprint arXiv:2205.05789*, 2022.

[17] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

[18] Chloe Hsu, Robert Verkuil, Jason Liu, Zeming Lin, Brian Hie, Tom Sercu, Adam Lerer, and Alexander Rives. Learning inverse folding from millions of predicted structures. *Proceedings of the 39th International Conference on Machine Learning*, 162:8946–8970, 2022.

[19] Minyoung Huh, Brian Cheung, Pulkit Agrawal, and Phillip Isola. Straightening out the straight-through estimator: Overcoming optimization challenges in vector quantized networks. In *International Conference on Machine Learning*, pages 14096–14113. PMLR, 2023.

[20] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with AlphaFold. *Nature*, 596(7873): 583–589, 2021.

[21] Adrian Łańcucki, Jan Chorowski, Guillaume Sanchez, Ricard Marxer, Nanxin Chen, Hans JGA Dolfing, Sameer Khurana, Tanel Alumäe, and Antoine Laurent. Robust training of vector quantized bottleneck models. In *2020 International Joint Conference on Neural Networks (IJCNN)*, pages 1–7. IEEE, 2020.

[22] Francesca-Zhoufan Li, Ava P Amini, Yisong Yue, Kevin K Yang, and Alex X Lu. Feature reuse and scaling: Understanding transfer learning with protein language models. *bioRxiv*, pages 2024–02, 2024.

[23] Mingchen Li, Yang Tan, Xinzhu Ma, Bozitao Zhong, Huiqun Yu, Ziyi Zhou, Wanli Ouyang, Bingxin Zhou, Liang Hong, and Pan Tan. Prosst: Protein language modeling with quantized structure and disentangled attention. *bioRxiv*, pages 2024–04, 2024.

[24] Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Robert Verkuil, Ori Kabeli, Yaniv Shmueli, et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science*, 379(6637):1123–1130, 2023.

[25] David JC MacKay. *Information theory, inference and learning algorithms*. Cambridge university press, 2003.

[26] Fabian Mentzer, David Minnen, Eirikur Agustsson, and Michael Tschannen. Finite scalar quantization: Vq-vae made simple. *arXiv preprint arXiv:2309.15505*, 2023.

[27] Jaina Mistry, Sara Chuguransky, Lowri Williams, Matloob Qureshi, Gustavo A Salazar, Erik LL Sonnhammer, Silvio CE Tosatto, Lisanna Paladin, Shriya Raj, Lorna J Richardson, et al. Pfam: The protein families database in 2021. *Nucleic acids research*, 49(D1): D412–D419, 2021.

[28] Piotr Nawrot, Szymon Tworkowski, Michał Tyrolski, Łukasz Kaiser, Yuhuai Wu, Christian Szegedy, and Henryk Michalewski. Hierarchical transformers are more efficient language models. *arXiv preprint arXiv:2110.13711*, 2021.

[29] Rohan Pandey. gzip predicts data-dependent scaling laws. *arXiv preprint arXiv:2405.16684*, 2024.

[30] Roshan M Rao, Jason Liu, Robert Verkuil, Joshua Meier, John Canny, Pieter Abbeel, Tom Sercu, and Alexander Rives. MSA Transformer. *Proceedings of the 38th International Conference on Machine Learning*, 139:8844–8856, 2021.

[31] Ali Razavi, Aaron Van den Oord, and Oriol Vinyals. Generating diverse high-fidelity images with vq-vae-2. *Advances in neural information processing systems*, 32, 2019.

[32] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10684–10695, 2022.

[33] Philip A Romero and Frances H Arnold. Exploring protein fitness landscapes by directed evolution. *Nature Reviews Molecular Cell Biology*, 10(12):866–876, 2009.

[34] Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in Neural Information Processing Systems*, 35:36479–36494, 2022.

[35] Ian Sillitoe, Nicola Bordin, Natalie Dawson, Vaishali P Waman, Paul Ashford, Harry M Scholes, Camilla SM Pang, Laurel Woodridge, Clemens Rauer, Neeladri Sen, et al. Cath: increased structural coverage of functional space. *Nucleic acids research*, 49(D1): D266–D273, 2021.

[36] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. *arXiv preprint arXiv:2010.02502*, 2020.

[37] Mingjie Sun, Xinlei Chen, J Zico Kolter, and Zhuang Liu. Massive activations in large language models. *arXiv preprint arXiv:2402.17762*, 2024.

[38] Baris E Suzek, Yuqi Wang, Hongzhan Huang, Peter B McGarvey, Cathy H Wu, and UniProt Consortium. UniRef clusters: a comprehensive and scalable alternative for improving sequence similarity searches. *Bioinformatics*, 31(6):926–932, 2015.

[39] Yuhta Takida, Takashi Shibuya, WeiHsiang Liao, Chieh-Hsin Lai, Junki Ohmura, Toshimitsu Uesaka, Naoki Murata, Shusuke Takahashi, Toshiyuki Kumakura, and Yuki Mitsufuji. Sq-vae: Variational bayes on discrete representation with self-annealed stochastic quantization. *arXiv preprint arXiv:2205.07547*, 2022.

[40] Lucrezia Valeriani, Diego Doimo, Francesca Cuturello, Alessandro Laio, Alessio Ansuini, and Alberto Cazzaniga. The geometry of hidden representations of large transformer models. *Advances in Neural Information Processing Systems*, 36, 2024.

[41] Aaron Van Den Oord, Oriol Vinyals, et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.

[42] Michel van Kempen, Stephanie S Kim, Charlotte Tumescheit, Milot Mirdita, Cameron LM Gilchrist, Johannes Söding, and Martin Steinegger. Foldseek: fast and accurate protein structure search. *Biorxiv*, pages 2022–02, 2022.

[43] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *arXiv*, 1706.03762, 2017.

[44] Jue Wang, Joseph L Watson, and Sidney L Lisanza. Protein design using structure-prediction networks: Alphafold and rosettafold as protein structure foundation models. *Cold Spring Harbor Perspectives in Biology*, page a041472, 2024.

[45] Minghao Xu, Zuobai Zhang, Jiarui Lu, Zhaocheng Zhu, Yangtian Zhang, Ma Chang, Runcheng Liu, and Jian Tang. Peer: a comprehensive and multi-task benchmark for protein sequence understanding. *Advances in Neural Information Processing Systems*, 35:35156–35173, 2022.

Appendix A. Extracting Embedding from ESMFold

We provide a code sketch of how to obtain the embedding space used in this work, based on modified and annotated source code from ESMFold [24]. Note that `self.esm_s_combine` and `self.esm_s_mlp` are both trained end-to-end with loss objectives from the original ESMFold paper; these weights add more structural awareness to the embedding space which we examine in this work than the original ESM2 3B embedding.

```
# self.esm_s_combine is a learnable weight
self.esm_s_combine = nn.Parameter(torch.zeros(self.esm.num_layers + 1))

# Forward pass through ESM2 language model.
# `esm_s` is a stack of representations from all layer outputs
```

```python
# esm_s = torch.stack(
#   [v for _, v in sorted(res["representations"].items())], dim=2
# )
# Typically, when working with ESM2 LM embeddings, one would use
# embeddings from `res["representations"][final_layer_number]
esm_s, esm_z = self._compute_language_model_representations(esmaa)

# weigh representations from different layers
esm_s = (self.esm_s_combine.softmax(0).unsqueeze(0) @ esm_s).squeeze(2)

# Simple MLP for manipulating output representation
s_s_0 = self.esm_s_mlp(esm_s)

# Pairwise input is initialized to zero:
s_z_0 = s_s_0.new_zeros(B, L, L, self.cfg.trunk.pairwise_state_dim)

# Pointwise add embedding of amino acid
s_s_0 += self.embedding(aa)

########
# Use this representation for CHEAP experiments:
# return s_s_0
########

# In ESMFold code, this embedding is then used as input
# to the structure trunk. We also use this to
# reconstruct structure from the CHEAP embedding.

structure: dict = self.trunk(
    s_s_0, s_z_0, aa, residx, mask, no_recycles=num_recycles
)
```

Appendix B. FSQ codebook

For consistency when comparing with VQ-VAE and the original FSQ paper [26], we use the same FSQ levels:

Target Size $|C|$	2^8	2^{10}	2^{12}	2^{14}	2^{16}
FSQ levels	[8, 6, 5]	[8, 5, 5, 5]	[7, 5, 5, 5, 5]	[8, 8, 8, 6, 5]	[8, 8, 8, 5, 5, 5]

Appendix C. Compression Results on Sequence-Only Datasets

TMScore is calculated with respect to the ESMFold predicted structure, rather than the ground truth structure.

Method		Dimensions		Structure metrics				Sequence metrics
		Codebook	Dim.	TMScore		RMSD		Sequence recovery
				Mean	Median	Mean	Median	Mean
Pfam	Cont.	-	256 x 32	0.939	0.983	1.740	0.740	0.755
		-	256 x 64	0.959	0.991	1.060	0.601	0.756
		-	512 x 8	0.883	0.961	2.707	1.424	0.753
	FSQ	[8,8,8,6,5]	-	0.711	0.716	5.523	4.742	0.555
		[16,16,16,16]	-	0.706	0.698	5.673	4.673	0.538
	Cont.	-	128 x 8	0.760	0.819	5.273	3.739	0.622
			256 x 4	0.564	0.539	10.203	9.927	0.471
		-	256 x 8	0.728	0.786	6.062	4.320	0.471
		-	256 x 32	0.826	0.947	3.740	1.561	0.812
		-	256 x 64	0.972	0.975	1.855	0.837	0.975
			512 x 4	0.552	0.522	10.264	10.065	0.438
		-	512 x 8	0.850	0.925	3.274	1.963	0.960
CATH	FSQ	[8,8,8,6,5]	-	0.853	0.861	3.670	3.668	0.820
		[16,16,16,16]	-	0.875	0.909	3.208	2.900	0.937
	Cont.	-	256 x 8	0.856	0.918	4.170	2.647	0.991
		-	256 x 32	0.931	0.971	2.075	1.185	1.000
		-	256 x 64	0.928	0.992	1.769	0.489	1.000

Appendix D. Comparison with Other Embedding Methods on PEER Benchmark

Extending Figure 5, we also include comparisons to other reported performances in Xu et al. [45]:

	# Dimensions	Flu ↑	Sta ↑	β-lac ↑	Sol ↑	Sub ↑	Bin ↑
DDE	400	0.64	0.65	**0.62**	0.60	0.49	0.77
Moran	240	0.40	0.32	0.38	0.58	0.31	0.56
LSTM	640	0.49	0.53	0.14	0.70	0.63	0.88
Transformer	512	0.64	0.65	0.26	0.70	0.56	0.76
CNN	21	**0.68**	0.64	0.78	0.64	0.59	0.83
ResNet	512	0.64	0.13	0.15	0.67	0.52	0.79
ProtBert	1024	0.34	0.70	**0.62**	0.59	0.59	0.82
ESM-1b	1280	0.43	**0.75**	0.53	0.67	**0.80**	0.92
CHEAP (ours)	4	0.14	0.40	0.13	0.60	0.33	0.68
	8	0.22	0.44	0.17	0.64	0.45	0.74
	16	0.27	0.55	0.23	0.65	0.54	0.84
	32	0.28	0.56	0.28	0.67	0.57	0.87
	64	0.31	0.56	0.28	0.69	0.62	0.90
	128	0.41	0.58	0.38	0.70	0.68	0.90
	256	0.47	0.60	0.41	0.71	0.72	0.92
	512	0.51	0.63	0.36	**0.72**	0.74	0.93
No compression	1024	0.52	0.64	0.45	**0.72**	0.76	**0.94**

Table D.1: Benchmarks on function and localization.

	# Dimensions	Cont	Fold	SSP	Yst
DDE	400	–	0.10	–	0.56
Moran	240	–	0.07	–	0.53
LSTM	640	0.26	0.08	0.69	0.54
Transformer	512	0.18	0.09	0.60	0.54
CNN	21	0.10	0.11	0.66	0.55
ResNet	512	0.20	0.09	0.70	0.49
ProtBert	1024	0.40	0.11	0.82	0.54
ESM-1b	1280	0.46	0.30	0.83	**0.66**
CHEAP (ours)	8	0.28	0.15	0.82	0.45
	64	**0.42**	0.45	0.85	0.48
	128	0.38	0.47	0.85	0.51
	256	0.23	0.50	0.85	0.51
	512	0.37	**0.53**	**0.86**	0.46

Table D.2: Benchmarks on structural and contact tasks.

Appendix E. Compressed Representation TSNE Plots

TSNE of embeddings after and before compression, colored by the "Architecture" level of the CATH classification hierarchy. Qualitative examination shows that despite 128× compression, fold and topology information is still large preserved.

Appendix F. Token Masking on Structure Reconstruction

Mirroring the analysis in Figure 7, we also examine the effect of "disturbing" the tokens on the output structure (Figure 4C), as a sanity check of how tokens encode structural information. The examined model uses FSQ levels $[16, 16, 16, 16]$, and has an implied codebook size of $C = 16^4 = 65536$. Since there is no [MASK] token in the vocabulary, we set different pre-quantization embeddings to 0. Generally, changing a subset of the tokens changes the structure, though since the codebook representations are not evenly spread through out, setting the first channels to zero has less of a detrimental effect.

Figure F.8: Exploring effects of token manipulation on the structure space for the $[16, 16, 16, 16]$ FSQ model, by setting some values to 0 just prior to quantization. The yellow box (top) denotes the original pre-quantization embedding and discrete codes representations of all-atom structure.