VieMedKG: Knowledge Graph and Benchmark for Traditional Vietnamese Medicine

Tam Trinh [1, 2, *]**, Anh Dao** [3, *]**, Hy Thi Hong Nhung** [4]**, Hy Truong Son** [1, †]**,**

[1] University of Alabama at Birmingham, United States
[2] National Economics University, Vietnam
[3] Michigan State University, United States
[4] Hanoi National University of Education, Vietnam
[*] Equal contribution   [†] **Correspondence:** thy@uab.edu

Abstract

Traditional Vietnamese Medicine (TVM) and Traditional Chinese Medicine (TCM) have shared significant similarities due to their geographical location, cultural exchanges, and hot and humid climatic conditions. However, unlike TCM, which has substantial works published to construct a knowledge graph, there is a notable absence of a comprehensive knowledge graph for TVM. This paper presents the first endeavor to build a knowledge graph for TVM based on extensive existing resources from TCM. We name our knowledge graph as VieMedKG. We propose a translation and filtration process to adapt TCM knowledge graphs to TVM, identifying the overlapping and unique elements of TVM. In addition, the constructed knowledge graph is then exploited further for developing a curated benchmark for the knowledge graph-based question-answering problem with the potential to support doctors and patients in assisting doctors and patients in identifying various diseases. Our work will not only bridge the gap between TCM and TVM but also set the foundation for future research into traditional Vietnamese medicine community. Our source code is publicly available at https://github.com/HySonLab/VieMedKG/.

1 Introduction

Traditional Vietnamese Medicine (TVM) is a complete medical system that has been discovered and developed for many thousands of years. In the past, deeply influenced by the ancient philosophies of Yin and Yang, the Five Elements from Traditional Chinese Medicine, TVM has integrated a wide range of elements, including herbal medicine, massage, disease names, and methods to cure them, while also preserving and integrating the unique Vietnamese traditional elements and indigenous knowledge. Since TVM has evolved throughout the long history of Vietnamese nation and people,

a systematic way such as Knowledge Graph to represent a comprehensive view of TVM is crucial. A knowledge graph can effectively organize and represent the complex relationship between various element of TVM such as diseases, symptoms, herbal medicine, the cause of disease and treatment methods. This structured representation can not only help cultural preservation but also make TVM more accessible to develop future research works and applications in the domain of Vietnamese traditional medicine.

However, despite several advantages, building a knowledge graph from a vast resources of TVM requires overcoming many challenges. The knowledge of TVM is often documented in historical texts, local manuscrips or oral communication which are inherently unstructured and lack of standardardiztion. Knowledge Graphs help to prevent hallucination in Large Language Models (LLMs) because they are more rigorous and structured. Therefore, processing these kind of data into a knowledge graph for TVM can be time consuming and costly. At the same time, many works (Chen et al., 2023; Cheng et al., 2018; Long et al., 2019; Zhou et al., 2010) have been published with significant efforts to collect, validate, contruct and exploit several downstream application of TCM in knowledge graph representation such as graph-based question answering and infomation retrieval. Realizing the similarities between TCM and TVM, we propose a method to leverage the existing TCM knowledge graph as a foundation in order to build a comprehensive knowledge graph for TVM. Our approach involves not only translating TCM data into Vietnamses version but also filtering and adapting that data to preverse and reflect the uniqueness of Vietnamese traditional medicine. By doing so, we can effectively utilize the huge amount of TCM data already available. Furthermore, we also analysis and propose a benchmark for graph-based question answering problem on our TVM knowledge

Figure 1: Illustrative representation of VieMedKG, showing the connections among entities

graph. To sum up, our contributions can be divided into the following categories:

- We introduce a new knowledge graph VieMedKG for Traditional Vietnamese Medicine built upon the current existing Traditional Chinese Medicine by applying translation and filtration process. To the best of our knowledge, this is the first endeavor to construct a systemetic way to represent TVM knowledge (see Figure 1).

- We propose a curated benchmark for graph-based question answering problem about TVM and further analysis some methods on VieMedKG.

2 Related works

2.1 TCM and TVM dataset

The availability of comprehensive datasets is crucial for knowledge discovery in TCM. Several significant TCM data resources have been developed. China TCM Patent Database (CTCMPD), managed by the State Intellectual Property Office of China, includes over 19,000 patents and 40,000 formulae (Liu and Sun, 2004). TCMBank (Lv et al., 2023), extended from TCM Database@Taiwan (Chen, 2011), includes 9,192 herbs, 61,966 ingredients, 15,179 targets, and 32,529 diseases.

In addition, several notable efforts have been made to construct TCM Knowledge Graphs. Yu et al. (2017) constructed the TCM health care knowledge graph through ontology-based database integration. Zheng et al. (2020) constructed

TCMKG by training deep learning model for named entity recognition, aligning data, and creating triples based on the ontology. Zhang and Hao (2024) adopted Large Language Models for name entity recognition to construct a knowledge graph of TCM.

In the context of Vietnamese Medicine, several datasets have been developed to facilitate research and application in this field. VietHERB, a database for Vietnamese Herbal Species, was built in an ontology-based structure to organize the numerous hierarchical multi-class of herbs (Nguyen-Vo et al., 2018). However, Nguyen-Vo et al. (2018) pointed out that the limitations of obtaining data are poor handwriting records and unexpected incorrect information when computerizing from hard-copied documents. ViMQ, a Vietnamese Medical Question Dataset, contains 9,000 questions for the two tasks of intent classification and named entity recognition (Huy et al., 2021). Despite these resources, there is no benchmark for Question Answering (QA) over Knowledge Graphs (KGs) for Vietnamese Medicine, highlighting a gap that needs to be addressed for further advancement in this field.

2.2 Question Answering System using Knowledge Graphs (KGs)

Early efforts in Knowledge Graph Question Answering (KGQA) aimed to convert natural language queries into formal logical queries using deep neural semantic parsing such as (Andreas et al., 2016; Lan et al., 2019; Yin et al., 2016). However, these approaches struggle with complex queries that need multi-hop reasoning and managing constraints on incomplete knowledge graphs. An alternative research approach to Knowledge Graph Question Answering (KGQA) frames the task as a graph traversal problem, directly reasoning on the input graph to uncover structural patterns in transitive relations. Methods like VRN (Zhang et al., 2018), GraftNet (Sun et al., 2018), and PullNet (Sun et al., 2019) employ graph neural networks and local subgraph searches to navigate entities within the knowledge graph.

Recent advancements in integrating large language models (LLMs) with knowledge graphs (KGs) have shown significant progress. Techniques such as REALM (Guu et al., 2020) and RAG (Lewis et al., 2020) have been developed to retrieve documents and enhance language models using these documents. Furthermore, KGs can serve as a

valuable & rigorous knowledge source, where information is succinctly encoded, and several methods have been proposed to integrate these facts from KGs into language models (Galetzka et al., 2021; Rony et al., 2022; Kang et al., 2022). Nevertheless, these approaches generally require extensive training data and frequent model updates for various downstream tasks. Recent research (Izacard et al., 2024) indicates that retrieval-augmented language models can achieve strong performance with few-shot learning. In our work, we will experiment with retrieval-augmented language models using both zero-shot and few-shot learning, without additional training steps.

3 Method

3.1 Knowledge Graph for Traditional Vietnamese Medicine (VieMedKG)

3.1.1 Access to Traditional Medical Knowledge

Both TVM and TCM share a historical foundation due to Vietnam's annexation by China for over a thousand years, facilitating the transfer of medical knowledge and practices. Both traditions heavily rely on herbal remedies, but TVM adapts its pharmacopeia to include local Vietnamese plants suited to the tropical climate, unlike the temperate-climate plants used in Chinese Medicine (Bui, 2019). Additionally, TVM data collection faces challenges like poor handwriting in historical records and errors during computerization (Nguyen-Vo et al., 2018). In contrast, TCM benefits from a well-established and comprehensive database developed over several decades. As a result, leveraging the TCM database can improve the accuracy and depth of medical research. In this study, we obtained structured data from OpenKG, the Chinese open database. Our dataset, presented in Traditional Chinese, contains comprehensive information on 9,464 different diseases, including their symptoms, treatments, medications, patient advice, and linked diseases.

3.1.2 Translation

Vietnamese word formation has been significantly influenced by Chinese, with Chinese-originated words accounting for about 70% of Vietnamese vocabulary, termed Sino-Vietnamese, and about 50% in modern Vietnamese (Đặng, 2003). Sino-Vietnamese can be easily translated word by word, often resulting in meaningless translations, and some terms lack Vietnamese equivalents but have

English ones. Therefore, we have decided to translate from Chinese to English, then from English to Vietnamese.

Baidu Translator is widely recognized as the most popular tool for translating Chinese to English quickly through free internet use (Yao et al., 2012). According to (Razzaka et al., 2019), Baidu translation tends to be more accurate and contextually appropriate for traditional Chinese literature than Google Translator, which is one of the most popular translators. Furthermore, Baidu Translator offers a specialized API for medical translations. For instance, the Chinese term "附錄" is translated by Google Translator as "phụ lục," referring to a section at the end of a book, whereas Baidu Translator renders it as "ruột thừa," aligning with its medical meaning as a small organ attached to the intestines on the right side of the human body.

Consequently, we have chosen to utilize Baidu Translator for translation. To ensure accuracy and the quality of the translations, we then used GPT-4 (Achiam et al., 2023) and human evaluation, which is checked by a linguistic expert with a PhD in Chinese linguistics for fact-checking, translating quality, and refinement.

3.1.3 Construction of VieMedKG

The construction of VietMedKG requires a number of processes such as Entity Disambiguation and Entity Linking. The core of the knowledge graph are the triple's entities, attributes, and relationships. The entities and attributes are combined and fed into the knowledge graph through the popular graph database - Neo4j database (Miller, 2013) to store data about nodes and relationships. Entities have 5 labels including disease, symptom, treatment, medicine, and advice corresponding to which relationships include HAS_SYMPTOM, HAS_TREATMENT, USE_MEDICINE, HAS_ADVICE, and IS_LINKED_WITH. Each entity provides its own additional attributes with detailed information as Figure 4 shows. The constructed medical data knowledge graph includes 41,549 nodes and 42,112 relationships. The detailed description of the knowledge graph is shown in Table 3 and Table 4.

VieMedKG is stored in Neo4j Graph Database, a NoSQL database that falls under the category of graph databases, adhering to the mathematical theory of trees. In Neo4j, nodes are represented as vertices and relationships as edges. A literature review by (López and la Cruz, 2015), indicates that

Neo4j demonstrates superior performance in terms of time response and provides shorter pathfinding compared to relational databases.

3.1.4 Benchmark Dataset for Question Answering

Triple creation In constructing a benchmark dataset for question-answering systems, the process of triple creation is pivotal. A triple is composed of three components: a head, a relation, and a tail. In the context of a dataset centered on diseases, the head represents the name of the disease, the relation denotes the attribute associated with the disease, and the tail indicates the value of that attribute. These triples are then used to generate various types of questions, including 1-hop and 2-hop questions, which assess the ability of question-answering systems to navigate different levels of complexity in the knowledge base.

We used the two sequential approaches which are label concatenation method and the usage of Large Language Model (LLM). The initial method involves concatenating labels from unseen triples to generate questions. For instance, using the triple ("*pertussis*", "*people_easy_get*", "*More common in children*") would create a question such as "*Pertussis have people easy get?*". Despite potentially generating grammatically incorrect or nonsensical questions, this approach effectively imparts textual information to the model concerning keywords linked with the relations.

1-hop question dataset For 1-hop question, we designed 32 types of questions in total (see Table 5). In exploring the relationship between extensive medical information (an attribute in the graph) and disease identification, this study encountered challenges with question length. Utilizing all details from attributes resulted in overly long questions. To address this, the GPT-4 language model (Achiam et al., 2023) was employed. GPT-4 offered two functionalities: 1) random summarization of an attribute, and 2) targeted selection of a key point within that attribute. Both approaches aimed to shorten the question to under 25 words while preserving its core meaning.

2-hop question dataset We designed 10 types of questions (see Table 5). To address the issue of lengthy questions, we employed a similar methodology as used for the 1-hop questions.

Creating multiple answer questions We grouped questions of the same type from the dataset and calculated the Jaccard similarity (Niwattanakul et al., 2013) between attribute values used in question creation. If the similarity exceeded 0.9, we merged the answers accordingly. This process ensured that questions with highly similar attributes yielded merged answers, optimizing question diversity while maintaining relevance.

Generating natural-sounding question using LLM We employed the GPT-4 language model to create natural-sounding questions from those generated by the label concatenation method. Using zero-shot prompting, we instructed the model to emulate doctors or patients seeking disease information. Figure 2 demonstrates the question generation process from triples, involving feeding pairs of triples and target questions derived from the training data.

By applying GPT-4 (Achiam et al., 2023) to our training set, we harnessed its ability to encode relationships between words and phrases, thus producing coherent questions even for triples with previously unseen relations. Subsequently, we manually reviewed and eliminated nonsensical questions, and utilized uniform sampling to establish the benchmark. The dataset consists of 4,232 questions, including 2,164 one-hop questions and 2,068 two-hop questions. Table 6 provides a detailed description of the benchmark.

3.2 Retrieval-Augmented Generation (RAG) with VietMedKG

3.2.1 The Cypher Query

Neo4j's query language is called Cypher (Francis et al., 2018). Cypher is a declarative query language for graphs that uses graph pattern-matching as a main mechanism for graph data selection for both read-only and mutating operations. As an example, the query to retrieve symptoms of pertussis can be stated as follows:

```
START Disease=node:
    Disease(disease_name={disease_name})
MATCH (Disease)-[:HAS_SYMPTOM] ->
    (Symptom:disease_symptom)
WHERE Sisease.disease_name = 'pertussis'
RETURN Symptom.disease_symptom,
    COUNT(*)
ORDER BY COUNT(*) DESC
```

Figure 2: Overview of the procedure for question generation. The input is a triple from the KG, and the output is a natural language question.

This query starts by searching the index called "Disease" for a node whose attribute "disease_name" is set to the contents of the parameter "disease_name". It then uses pattern matching to find all symptoms associated with this disease. The "WHERE" clause ensures that we are specifically querying for the disease "pertussis". As a result, the query returns all symptoms associated with pertussis and how often they were encountered during the traversal, which is also the sort criterion. Attributes could be accessed by "Symptom.disease_symptom".

To enhance the effectiveness of Cypher statements in practice, leveraging the few-shot learning capabilities of large language models (LLMs) involves presenting examples that guide the model in generating Cypher statements. This approach facilitates the adaptation of Cypher syntax to specific query requirements, ensuring compatibility with database structures and query outcomes.

3.2.2 Augmenting LLM answer with RAG and zero-shot prompting

Figure 3 illustrates the architecture of the Retrieval-Augmented Generation (RAG) system. The workflow begins with the user submitting a question. This question is then processed using a Cypher query and LLM to generate relevant queries. The retrieved nodes are used to query the knowledge graph through Cypher queries, extracting additional contextual information. The results are returned in JSON format, after which LLM generates an answer based on the augmented query and the contextual information provided by the knowledge graph.

4 Experiments

4.1 Experiment Design

Researchers have been working on Question-Answering (QA) system for Vietnamese such as (Tran et al., 2023). However, in this paper, we propose the first-ever QA system that incorporates Knowledge Graph (i.e. VieMedKG) for medicine in Vietnamese. We evaluated our QA system using a benchmark dataset designed for QA tasks based on VieMedKG. In our experiments, we employed large language models (LLMs), specifically GPT-4 (Achiam et al., 2023) and Gemini 1.0 Pro (Team et al., 2023), using zero-shot prompting to serve as baseline for the benchmark. Subsequently, we leveraged our RAG system with the GPT-4 and Gemini 1.0 Pro as the generator to measure the performance for both 1-hop and 2-hop benchmark dataset.

To evaluate the retrieval performance and determine the contribution of retrieved triples to answer generation, we employed accuracy as our primary metric. For assessing the overall performance of the QA system, we utilized metrics including BLEU (Papineni et al., 2002), ROUGE (Lin, 2004), and METEOR (Lavie and Agarwal, 2007) scores.

4.2 Experimental Results and Analyses

The performances of retrieval and question-answering are detailed in Tables 1 and 2, respectively. When compared to the zero-shot prompting capabilities of state-of-the-art language models such as GPT-4 and Gemini 1.0 Pro, our system exhibits a significant improvement in question-answering performance. Specifically, our proposed RAG system enhances the BLEU score of GPT-4 by approximately 7.19 times and that of Gemini 1.0 Pro by approximately 6.76 times for 1-hop

Figure 3: Overview of the RAG system. The process begins with a user question processed through Cypher and LLM queries to retrieve relevant knowledge graph nodes. An answer is then generated using the augmented query and contextual information.

questions, and by approximately 11.19 times for GPT-4 and 5.83 times for Gemini 1.0 Pro for 2-hop questions. These considerable improvements come with only a marginal increase in inference latency, adding an average of 8.40 seconds for GPT-4 and 5.52 seconds for Gemini 1.0 Pro.

Model	1-hop	2-hop
GPT4	0.4143	0.4
Gemini 1.0 Pro	0.5075	0.4909

Table 1: Results for 1-hop and 2-hop retrieval performance.

5 Conclusion

In this paper, we have introduced the first knowledge graph for Traditional Vietnamese Medicine (TVM), leveraging resources from Traditional Chinese Medicine (TCM). Through systematic translation and filtration, we adapted TCM knowledge graphs to reflect TVM's unique elements, addressing a gap in the documentation of Vietnamese medical knowledge. Our knowledge graph, VieMedKG, serves as a foundational resource for future research and applications in the TVM domain. By providing a curated benchmark for knowledge graph-based question answering, we have laid the groundwork

for further developments in QA systems for traditional medicine. Our experiments demonstrate the feasibility and potential of using advanced language models and retrieval-augmented generation techniques in this context.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Jacob Andreas, Marcus Rohrbach, Trevor Darrell, and Dan Klein. 2016. Learning to compose neural networks for question answering. *arXiv preprint arXiv:1601.01705*.

Anita Bui. 2019. Traditional vietnamese medicine between chinese heritage and national tradition. *Chinese Medicine and Culture*, 2(1):21–25.

Calvin Yu-Chian Chen. 2011. Tcm database@ taiwan: the world's largest traditional chinese medicine database for drug screening in silico. *PloS one*, 6(1):e15939.

Jiyu Chen, Jinchuan Qian, Xinmin Zhang, Zhihuan Song, Chenying Wen, and Xueer Fan. 2023. Gpbp: Pipeline extraction of entities and relations for construction of urban utility tunnel knowledge graph. In

Model	1-hop			2-hop		
	BLEU	METEOR	ROUGE	BLEU	METEOR	ROUGE
GPT4	0.058	0.157	0.104	0.021	0.092	0.112
Gemini 1.0 Pro	0.051	0.14	0.123	0.035	0.126	0.118
GPT4 + RAG (ours)	**0.417**	**0.552**	**0.508**	**0.235**	**0.325**	**0.298**
Gemini 1.0 Pro + RAG (ours)	0.345	0.492	0.479	0.204	0.265	0.246

Table 2: Results for 1-hop and 2-hop question-answering performance. We highlight the best result for each metric.

2023 CAA Symposium on Fault Detection, Supervision and Safety for Technical Processes (SAFEPROCESS), pages 1–6. IEEE.

Boya Cheng, Yuan Zhang, Dejun Cai, Wan Qiu, and Dongxin Shi. 2018. Construction of traditional chinese medicine knowledge graph using data mining and expert knowledge. In *2018 International Conference on Network Infrastructure and Digital Content (IC-NIDC)*, pages 209–213.

Nadime Francis, Alastair Green, Paolo Guagliardo, Leonid Libkin, Tobias Lindaaker, Victor Marsault, Stefan Plantikow, Mats Rydberg, Petra Selmer, and Andrés Taylor. 2018. Cypher: An evolving query language for property graphs. In *Proceedings of the 2018 International Conference on Management of Data*, SIGMOD '18, page 1433–1445, New York, NY, USA. Association for Computing Machinery.

Fabian Galetzka, Jewgeni Rose, David Schlangen, and Jens Lehmann. 2021. Space efficient context encoding for non-task-oriented dialogue generation with graph attention transformer. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 7028–7041, Online. Association for Computational Linguistics.

Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Ming-Wei Chang. 2020. Realm: retrieval-augmented language model pre-training. In *Proceedings of the 37th International Conference on Machine Learning*, ICML'20. JMLR.org.

Ta Duc Huy, Nguyen Anh Tu, Tran Hoang Vu, Nguyen Phuc Minh, Nguyen Phan, Trung H. Bui, and Steven Q. H. Truong. 2021. *ViMQ: A Vietnamese Medical Question Dataset for Healthcare Dialogue System Development*, page 657–664. Springer International Publishing.

Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. 2024. Atlas: few-shot learning with retrieval augmented language models. *J. Mach. Learn. Res.*, 24(1).

Minki Kang, Jin Myung Kwak, Jinheon Baek, and Sung Ju Hwang. 2022. Knowledge-consistent dialogue generation with knowledge graphs.

Yunshi Lan, Shuohang Wang, and Jing Jiang. 2019. Knowledge base question answering with a matching-aggregation model and question-specific contextual relations. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 27(10):1629–1638.

Alon Lavie and Abhaya Agarwal. 2007. Meteor: an automatic metric for mt evaluation with high levels of correlation with human judgments. In *Proceedings of the Second Workshop on Statistical Machine Translation*, StatMT '07, page 228–231, USA. Association for Computational Linguistics.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS '20, Red Hook, NY, USA. Curran Associates Inc.

Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.

Yanhuai Liu and Yanling Sun. 2004. China traditional chinese medicine (tcm) patent database. *World Patent Information*, 26(1):91–96.

Hai Long, Yan Zhu, Lirong Jia, Bo Gao, Jing Liu, Lihong Liu, and Heinrich Herre. 2019. An ontological framework for the formalization, organization and usage of tcm-knowledge. *BMC Medical Informatics and Decision Making*, 19:79–89.

Félix Melchor Santos López and Eulogio Santos De la Cruz. 2015. Literature review about neo4j graph database as a feasible alternative for replacing rdbms. *Industrial Data*, 18:135–139.

Qiujie Lv, Guanxing Chen, Haohuai He, Ziduo Yang, Lu Zhao, Kang Zhang, and Calvin Yu-Chian Chen. 2023. Tcmbank-the largest tcm database provides deep learning-based chinese-western medicine exclusion prediction. *Signal Transduction and Targeted Therapy*, 8(1):127.

Justin J Miller. 2013. Graph database applications and concepts with neo4j. In *Proceedings of the southern association for information systems conference, Atlanta, GA, USA*, volume 2324, pages 141–147.

Thanh-Hoang Nguyen-Vo, Tri Le, Duy Pham, Tri Nguyen, Phuc Le, An Nguyen, Thanh Nguyen, Thien-Ngan Nguyen, Vu Nguyen, Hai Do, et al. 2018. Vietherb: a database for vietnamese herbal species. *Journal of chemical information and modeling*, 59(1):1–9.

Suphakit Niwattanakul, Jatsada Singthongchai, Ekkachai Naenudorn, and Supachanun Wanapu. 2013. Using of jaccard coefficient for keywords similarity.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*, ACL '02, page 311–318, USA. Association for Computational Linguistics.

Md Abdur Razzaka, Md Serajul Islamb, Sharowar Hossainc, and Jinzhang Jiang. 2019. Exploring and learning english: An analysis of baidu and google translation.

Md. Rony, Ricardo Usbeck, and Jens Lehmann. 2022. Dialokg: Knowledge-structure aware task-oriented dialogue generation. *ArXiv*, abs/2204.09149.

Haitian Sun, Tania Bedrax-Weiss, and William Cohen. 2019. PullNet: Open domain question answering with iterative retrieval on knowledge bases and text. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 2380–2390, Hong Kong, China. Association for Computational Linguistics.

Haitian Sun, Bhuwan Dhingra, Manzil Zaheer, Kathryn Mazaitis, Ruslan Salakhutdinov, and William W Cohen. 2018. Open domain question answering using early fusion of knowledge bases and text. *arXiv preprint arXiv:1809.00782*.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Cong Dao Tran, Nhut Huy Pham, Anh Tuan Nguyen, Truong Son Hy, and Tu Vu. 2023. ViDeBERTa: A powerful pre-trained language model for Vietnamese. In *Findings of the Association for Computational Linguistics: EACL 2023*, pages 1071–1078.

Jia Yao, Muyun Yang, Junmao Meng, Dongqing Xiao, Tiejun Zhao, and Sheng Li. 2012. How good is web based mt: A case study on paper title translation. In *2012 International Conference on Asian Language Processing*, pages 213–216. IEEE.

Wenpeng Yin, Mo Yu, Bing Xiang, Bowen Zhou, and Hinrich Schütze. 2016. Simple question answering by attentive convolutional neural network. *arXiv preprint arXiv:1606.03391*.

Tong Yu, Jinghua Li, Qi Yu, Ye Tian, Xiaofeng Shun, Lili Xu, Ling Zhu, and Hongjie Gao. 2017. Knowledge graph for tcm health preservation: Design, construction, and applications. *Artificial intelligence in medicine*, 77:48–52.

Yichong Zhang and Yongtao Hao. 2024. Traditional chinese medicine knowledge graph construction based on large language models. *Electronics*, 13(7).

Yuyu Zhang, Hanjun Dai, Zornitsa Kozareva, Alexander Smola, and Le Song. 2018. Variational reasoning for question answering with knowledge graph. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32.

Ziqiang Zheng, Yongguo Liu, Yun Zhang, and Chuanbiao Wen. 2020. Tcmkg: A deep learning based traditional chinese medicine knowledge graph platform. In *2020 IEEE International Conference on Knowledge Graph (ICKG)*, pages 560–564.

Xuezhong Zhou, Yonghong Peng, and Baoyan Liu. 2010. Text mining for traditional chinese medical knowledge discovery: a survey. *Journal of biomedical informatics*, 43(4):650–660.

Đức Siêu Đặng. 2003. *Dạy và học từ Hán Việt ở trường phổ thông*. Giáo dục.

A Description of VieMedKG

Figure 4: Graph Schema for VietMedKG.

Figure 5: Subgraph of VieMedKG, visualized using Neo4j.

Entity Type	No. of Entities
disease	9,464
symptom	8,806
treatment	8,806
medicine	8,806
advice	5,577
Total	**41,549**

Table 3: Number of Entities by Type.

Relationship Type	No. of Relationships
HAS_SYMPTOM	8,806
HAS_TREATMENT	8,806
USE_MEDICINE	8,806
HAS_ADVICE	5,577
IS_LINKED_WITH	10,117
Total	**42,112**

Table 4: Number of Relationships by Type.

1-hop question type	2-hop question type
disease_description_to_disease,	disease_symptom_to_cure_probability
disease_category_to_disease,	disease_symptom_to_nutrition_do_eat,
disease_cause_to_disease,	disease_symptom_to_nutrition_not_eat,
disease_symptom_to_disease,	disease_symptom_to_nutrition_recommend_meal,
check_method_to_disease,	disease_symptom_to_check_method,
cure_department_to_disease,	disease_cause_to_cure_method,
cure_method_to_disease,	associated_disease_to_cure_method,
cure_department_to_disease,	associated_disease_to_nutrition_do_eat,
associated_disease_to_disease,	associated_disease_to_nutrition_not_eat,
nutrition_do_eat_to_disease,	disease_category_to_cure_department.
nutrition_recommend_meal_to_disease,	
nutrition_not_eat_to_disease,	
disease_prevention_to_disease,	
associated_disease_to_disease,	
drug_recommend_to_disease,	
disease_to_disease_description,	
disease_to_disease_category,	
disease_to_disease_cause,	
disease_to_disease_symptom,	
disease_to_check_method,	
disease_to_people_easy_get,	
disease_to_cure_method,	
disease_to_cure_method,	
disease_to_cure_probability,	
disease_to_nutrition_do_eat,	
disease_to_nutrition_recommend_meal,	
disease_to_nutrition_not_eat,	
disease_to_disease_prevention,	
disease_to_drug_detail,	
disease_to_drug_common,	
disease_to_drug_recommend,	
disease_to_associated_disease.	

Table 5: Question types of 1-hop and 2-hop questions.

Question	No. of answers per question	No. of questions
	1	900
1-hop	2	500
	3+	761
	1	658
2-hop	2	410
	3+	1,000

Table 6: Description of KGQA benchmark.