Fidelity of focal sound source reproduction by higher (9th) order ambisonics and perceptual effects of reproduction errors

Nima Zargarnezhad[1,2, a], Bruno Mesquita[2], Ewan A Macpherson[3,4], Ingrid Johnsrude[1,2,3,4]

[1] *Department of Psychology, Western University, London, ON, Canada*

[2] *Western Center for Brain and Mind, Western University, London, ON, Canada*

[3] *School of Communication Sciences and Disorders, Western University, London, ON, Canada*

[4] *National Center for Audiology, Western University, London, ON, Canada*

Higher-order ambisonic rendering is an increasingly common acoustic field reproduction technique that enables presentation of virtual sounds at nearly any location in 3D space, relatively unconstrained by the veridical locations of loudspeakers. We evaluated whether 3D sound reproduction through a 9th order ambisonic system was sufficiently accurate to probe the limits of human spatial perception. In Experiment 1, we estimated minimum audible angles for human listeners at a variety of reference points on the horizontal plane. Our estimated values are similar to absolute thresholds obtained using single-channel free-field presentation for locations within ±51° on the horizontal plane, including values approaching 1° on the midline[1], regardless of speaker density. This demonstrates the adequacy of the AudioDome for studies of human auditory spatial perception, at least for displacement in the horizontal plane. In Experiment 2 we estimated monaural and binaural localization cues by presenting linear chirp sweeps (0-22050 Hz) at the horizontal reference points tested in Experiment 1 and recorded ear canal signals through a head and torso simulator. Although localization cues for low-frequency components were well preserved,

[a] Email: nzargarn@uwo.ca

they were distorted for components above 4000 Hz. In Experiment 3 we provide evidence that these high-frequency distortions are processed as cues to elevation.

Keywords: Higher-Order Ambisonics, Soundscape Reproduction, Sound Localization, Minimal Audible Angle, Spatial Hearing

I. INTRODUCTION

Human auditory perceptual experience is essentially spatial in nature, despite the fact that, unlike for vision and touch, the sensory epithelium is not spatiotopically organized. Whereas our skin and retinas are equipped with receptors that, by their location in the sensory array, encode information about the spatial position of events in the world. Our cochlea is organized by frequency, and appears to compute location from a variety of different temporal and spectral sound features often requiring integration across the two ears. Sound location relative to the head is primarily estimated through binaural cues, such as Interaural Time Difference (ITD) and Interaural Level Difference (ILD) which index the delay of sound arrival time and level between ears[2,3]. While spectral detail in reasonably broadband sounds provides cues to elevation, ITDs are more useful for lower frequencies (below 1000 Hz), whereas ILDs are more salient at higher frequencies (above 1500 Hz)[2,4,5]. In addition to these cues, which inform the listener about the lateral location of a sound source relative to the midline, monoaural spectral cues contribute to estimating the elevation and front/back location of the source. These cues are the result of sound filtering by the listener's head, upper body, and by the pinnae of the ears. This filtering, referred to as the Head-Related Transfer Function (HRTF), is an individual response function that characterizes the sound received by each ear. A pair of HRTFs for a given individual can be used to filter a sound such that it is perceived by that person as coming from a particular location in 3D space. Individual HRTFs enable the recreation of a spatial hearing experience in experimentally controlled settings, over headphones[2,6–8]. In practice, because estimating individual HRTFs is a time-consuming, expensive, complex (requiring specialized equipment) and somewhat unpleasant process (usually involving the insertion of a microphone near the eardrum), generic HRTFs are typically used[3,8]. These simulations, while delivering a 'spatialized' percept, generally do not deliver as compelling a spatial percept as free-field listening.

High-density 3-dimensional loudspeaker (LSP) arrays are expensive, but deliver a compelling,

free-field, spatial percept, derived from the participant's HRTFs, and afford opportunities to study

naturalistic behaviors (such as audio-visually guided grasping). In the basic implementation, each

sound source is presented from exactly one LSP. This method, Single-Channel (SC) panning, limits

the presented sound source locations to the locations of actual LSPs - which are typically many

centimeters apart. This is obviously inadequate for the study of the limits of human spatial

perception. Another method, called Vector Based Amplitude Panning (VBAP), overcomes the

limited resolution of SC panning by distributing a virtual sound source's energy among the

surrounding LSPs and enables the simulation of sound sources between LSP locations. VBAP first

determines the minimum number of nearby LSPs for any given location then distributes the sound

gain among those LSPs such that their vector sum results in a sound image with the appropriate gain

at the intended location[9]. This algorithm essentially utilizes one LSP when the intended sound

source coincides with an LSP location (identical to SC presentation in this situation); two LSPs when

it aligns on the line between two LSPs; and three LSPs if the sound location neither coincides with

an LSP nor aligns with the line connecting two LSPs. The energy spread (spatial blurring) of a sound

source using VBAP presentation depends on its distance from nearby LSPs and LSP geometry, and

so sound source images are nonhomogeneous in their apparent diffusion[10].

Ambisonic panning is another reproduction method that utilizes a 3D LSP array to reproduce

3D soundscapes. For ambisonic panning, the soundscape (comprising one sound, or many) is

decomposed into a series of spherical harmonics that describe the sound pressure level, velocity, and

its higher order derivatives in different directions within the 3-dimensional acoustic environment.

Although utilizing higher order derivatives of the sound wave velocity enables the encoding of more

focal sound sources, decoding them in the virtual acoustic environment requires more presentation

channels (LSPs); therefore, the spatial resolution of ambisonic reproduction is limited by the number

of LSPs in the array. Theoretically, ambisonic panning has higher spatial resolution than SC and

VBAP presentation methods with an equalized energy spread using all loudspeakers for all sound

source positions[11]. With lower order ambisonic panning systems (orders 1 to 4), rendered sound

sources are perceived as "blurry" or diffuse, and resolution is poor. As the order of the system

increases, rendered sound sources are, in theory, less blurry, such that a normal listener might

perceive them as more crisply focal and thus be better able to resolve closely adjacent sources[12].

Generally, all sound reproduction methods are an approximation of real-world acoustic

characteristics and reproduction is not perfect. The perceptual effects of reproduction errors and the

extent to which these errors are acceptable depends on the intended use of the system. Presenting

sound sources with SC will minimize errors in localization, but it limits the spatial resolution of

soundscape reproduction. VBAP has greater spatial resolution than SC, but the energy of sound

sources is spread unequally throughout the 3D space, such that the blurriness of sound sources

depends on their location relative to LSPs. Although rendering through ambisonics improves on SC

and VBAP, even higher order systems may not perfectly reproduce sound locations: errors in

timbral and reconstructed ITD and ILD information have been noted in simulations[13].

Additionally, soundscape reconstruction with ambisonics is valid within the area in which the

superposition of spherical harmonics is reliable; a minimum ambisonics order is required for the

system to reproduce planewaves below a particular wavelength reliably, within a sphere of a

particular size located at the center of the array.[7,14] The possibility of reproduction errors affecting

perception may preclude the use of this technology for spatially precise reproduction of acoustic

environments..

The goal of the present study is to validate the utility of a custom-built LSP array for conducting

studies of human perception of auditory space. This array at Western University (called the

"AudioDome", Sonible, GmbH, Austria) consists of 4 dual-channel subwoofers and 91 LSPs

geodesically arranged in a sphere with a radius of approximately 1.65 m, located in a sound

attenuating chamber (FIG 1.A). The AudioDome is capable of single-channel (SC), VBAP, and 9th-

order ambisonic panning, in order to reproduce 3D acoustic environments. We aimed to

characterize the spatial fidelity and perceptual outcomes of the AudioDome's ambisonic panning to

validate its use, and identify any limitations, before future psychoacoustic and soundscape studies are

conducted using the setup, and this work is also valuable for others using similar Higher-Order

Ambisonic (HOA) arrays for human perceptual research.

We first measured horizontal spatial acuity by human listeners, in order to evaluate the

perceptual effects of ambisonic spatial blurring in the horizontal plane. Traditional SC presentation

has determined that minimal audible angles (MAA) are ~1° on the midline, and then acuity

monotonically decreases to ~2° at 45° azimuth, and to more than ~8° at azimuth locations above

75° off the midline.[1,2] In Experiment 1, we measured listeners' horizontal MAAs. We also

investigated whether obtained MAA depended on the distance of the rendered source from the

nearest LSPs: higher MAAs in virtual positions further away from LSPs would indicate that the

focality of rendered sources was not the same everywhere on the surface of the sphere defined by

the LSP array.

Subsequently, using a Head-and-Torso Simulator (HATS), we compared the spectral

composition of rendered sound, and reconstructed ITD and ILD cues delivered to the center of the

array (Experiment 2), for SC, VBAP and ambisonic panning.

Finally, based on the findings in the first two experiments, we measured the effects of spectral

distortions introduced by ambisonics on the perception of elevation by human listeners (Experiment

3).

FIG. 1. (color online) A. The AudioDome (Sonible, GmbH, Austria): the array consists of 91 LSPs

and 4 subwoofers geodesically arranged in a spherical shape with a radius of approximately 1.65 m in

a sound attenuating chamber. This system is equipped with SC, VBAP, and 9[th] order ambisonic

panning technologies. The AudioDome in a sound attenuating chamber. B. A schematic of the

reference points used in Experiments 1-3. Locations of LSPs (filled circles) and locations between

LSPs (open circles) on the horizontal plane with their labels and the participant's head at the center.

II.   EXPERIMENT 1

The first experiment examined whether the spatial blurring of sound sources reproduced with

9[th]-order ambisonics was above or below the threshold of human acuity (MAA) studied with SC

reproduction[1,2,15]. Furthermore, we examined whether spatial acuity was worse (indicative of more

blurred sources) when virtual sources were located at a greater distance from the nearest LSPs.

We estimated Minimum Audible Angles (MAAs)[1,2,15] on the frontal half of the horizontal plane

at several locations that coincided with actual LSPs or at the midpoints of adjacent pairs (FIG 1.B).

The highest spatial acuity (lowest MAAs) was expected at the front of the array (0° azimuth)[1,2] and

should approach 1° if ambisonic panning renders point sources at a spatial resolution at or below

the limits of human acuity. However, the LSP density is also greatest at 0° azimuth. Accordingly, we

tested another condition in which participants were rotated to face another region of the array with

the lowest LSP density, also on the horizontal plane. This allowed us to determine whether distance

from the nearest LSPs changes the focality of sources. If we observe MAAs of ~ 1° in both

conditions, we can conclude that the array is able to render point sources at a spatial resolution at or

below the limits of human acuity, everywhere on the surface of the sphere defined by the geodesic

array.

A. Materials and Methods

Participants were seven (4 female) young (aged 18-25 years), healthy, normally hearing

(thresholds measured audiometrically at both ears at octaves of 125 Hz up to 8 kHz; participants

were excluded if their threshold exceeded 25 dB HL at any tested frequency in either ear), right-

handed, naive listeners with no history of neurological disorders. Participants sat in the middle of the

AudioDome with their head positioned at the center of the dome. The chair was set to face the

origin of the array's coordinate system (0° azimuth and elevation angles) so that the ears aligned with

the ±90° azimuth line, and the ear level was aligned with the 0° elevation level by adjusting the chair

height.

Horizontal MAAs were estimated at 17 locations (reference points) on the horizontal plane; nine

of these coincided with LSPs within the ±90° azimuth range and eight were at midpoints between

adjacent LSPs (FIG 1.B and TABLE I). Participants completed a location discrimination task in

which they reported whether the second noise burst of a pair was in a location clockwise, or

counterclockwise, from the first. In each trial, one sound was at the location of a reference point,

and one at the location of a test point. In each of 17 experimental blocks, one reference point was

tested against 13 test points (six on each side, and one co-located) 20 times each. These data were

then used to calculate a psychometric function relating the probability of a perceived direction

response to the distance of test points from the reference. Test points were presented across larger

ranges for the four most lateral reference points given that acuity is poorer in this region[1]; test points

ranged across ±12° from the reference for L8 and R8, ±9° for L7 and R7, and ±6° for all other

reference points (to maintain the number of test points at 13, the increment size was adjusted

accordingly, all ranges are inclusive). The MAA at each reference point was estimated by fitting a

sigmoid to each individual's psychometric data, and then reading off the 75% threshold value, which

was taken as the just-noticeable difference (JND[16]) . Equation 1 describes the model $\psi_{RP}(\varphi)$ used to

describe the probability ,ψ, that the test sound, rendered at probe angle φ, was perceived to be

counterclockwise relative to the sound rendered at the reference point, RP. Parameters α_{RP} and β_{RP},

representing the center and steepness of the sigmoid function, were estimated using a non-linear

least-squares method[17,18].

146
$$\psi_{RP}(\varphi) = \frac{1}{1 + e^{\frac{-(\varphi - \alpha_{RP})}{\beta_{RP}}}} \qquad (1)$$

The two sounds (reference and test) were broad-band white-noise bursts (range 0-22050 Hz at

44100 Hz sampling rate), 450 ms in duration, separated by a 200 ms silent gap[15]. Participants could

respond (and change their response) up to 1250 ms after the second burst ended. The noise bursts

were generated using the 'wgn' function in MATLAB 2022b software[19] with the signal power set to -

25 dBW with 22.5 ms long cosine²-shaped attack and decay ramps. The audio files were presented at

73.1 dB SPL to the participants in the AudioDomeAudioDome, which had a background noise level

of 25.2 dB SPL at its quietest (SNR = 47.9 dB). Eighty different noise bursts were generated and

pseudo-randomly assigned to different trials in the experiment.

The experiment was held in the AudioDome (Sonible GmbH, Vienna, Austria), the loudpseaker

array that consists of 91 KEF E 301 loudspeakers with 4.25" coax drivers in egg-shaped drivers and

approximately linear frequency responses, and 4 subwoofers with 2 independent drivers for the

lower portion of the spectrum (<150 Hz), geodesically arranged in a spherical shape with a radius of

approximately 1.65 m. This system is equipped with SC, VBAP, and 9th order ambisonic panning

technologies.

The experiment was held in darkness to rule out the influence of vision on sound localization[20];

all the surfaces on the chamber walls were covered with black sound absorbing foam and black

Velcro was used to cover the AudioDome skeleton and LSP joints in order to minimize potential

acoustic and optical reflections. The only light source was the red LED used for eye fixation, placed

at 0° azimuth and elevation. This was illuminated for the duration of each trial to inform the

participant of the trial progression (illuminated at the start of each trial and extinguished at the end).

The participants were instructed not to move, to keep their eyes open, and to fixate on the red light.

An 8-mm magnetic sensor was attached behind the participants' heads to track their motion. (Those

head tracking data were not used). Participants used two buttons on a small wireless keypad to

indicate the direction in which they perceived the sound to 'jump' from the first burst to the second

(clockwise/counter clockwise) on each trial. The order of test and reference points was

counterbalanced, such that for each reference point, the first burst of each trial was located at the

test point on 10 trials, and at the reference point on the other 10.

Reference point C, at 0° azimuth and elevation and coincided with an LSP, is also surrounded by

several other LSPs; four within ±11.64° azimuth and ±20.91° elevation. In contrast, reference points

L5 and R5 are themselves virtual and in rather sparse LSP regions: the nearest LSPs are located at

±18.69° azimuth and±11.64° elevation (FIG 3.A). The higher concentration of LSPs at the front

(reference point C) may result in more focal sound source reproduction at this location, enabling

more accurate discrimination and lower MAAs. If we only test participants facing towards reference

point C, this density difference is confounded with spatial acuity, which is best at the front and

decreases at lateral positions[1]. To test the effect of density without the confound, we tested two

further conditions (blocks), identical to the others, in which we rotated the chair so that participants

faced L5 and R5. This enabled us to compare frontal MAAs for the reference points in the regions

of highest (C) and lowest (L5 and R5) LSP concentrations. In these 'rotated' blocks, the participants

completed the task for a reference point in front of them (L5 or R5). The red LED fixation point

was set at L5 and R5 for these blocks.

The 19 experiment blocks (17 facing reference point C, one facing L5, and one facing R5) were

split into two sessions over two days. Session One consisted of consent, audiometry, a demographic

questionnaire, head measurements (not presented or analyzed here), followed by training, a practice

block, and eight blocks testing four pairs of symmetric reference points. In Session Two,

participants completed another practice block, then the remaining four pairs of reference points, the

two rotated conditions and reference point C. At the end, the participants were asked about their

attentiveness during the task, their understanding of the task, and any strategies they used to

respond, then they were debriefed. The reference point pairs were randomly assigned to the two

sessions at the beginning of the first session. The order of reference point blocks within a session

was randomized. Also, the order in which the three frontal MAA blocks at C, L5, and R5 were

tested was pseudo-randomly assigned to participants (each of the six possible permutations was

assigned to a participant). Within each block, the order of the trials was fully randomized.

At the beginning of each session, participants completed a practice block which consisted of 20

suprathreshold trials with pairs of noise bursts presented at different locations drawn from the

following locations: C, L2, L4, L6, and L8 (the left LSP locations). The leftmost noise burst of the

pair was presented first on half of the practice trials (i.e., clockwise response would be correct). To

ensure participants properly learned the task, they only proceeded to the main experiment block

after achieving 100% accuracy on the practice block for pairs separated by relatively large distances

(i.e., C vs. L6, C vs. L8, and L2 vs. L8). Feedback on accuracy was provided during practice blocks;

in the main experiment participants were informed about missed trials or too slow reaction times at

the end of each block. One participant who marginally passed the audiometry results was not able to

achieve a high accuracy after three tries in the first session's practice block and was not tested

further. We; we collected and analyzed data from the remaining six participants.

B. Results

Sigmoid functions were adequate fits to data reference points C, L1, R1, L2, R2, L3, R3, R4, L5,

and L5 for all 6 participants. At other reference points, one or more participants performed at or

below chance level (1 participant at reference points L4, R6, and R7, 2 at L6 and L7, 3 at R8, and 4

at L8). As it is impossible to estimate the 75% threshold for a flat line, those data were removed

from the analysis. MAA values are illustrated in FIG 2 and summarized in TABLE I. The average

MAAs across participants are in the range of 0.95° to 2.38° at reference points within about 32° off

the midline (C, L1-L4, and R1-R4; see TABLE I). At reference points that are 50° to 90° from the

midline (L5-8; R5-8) these values are more divergent and asymmetrical between left and right. On

the left, average MAAs were 4.46° for both L5 and L6, and for the most extreme lateral locations,

L7 and L8, they were 5.84° and 21.78°, respectively. On the right, average MAAs were 2.81° at R5,

8.48° at R6, 7.94° at R7, and 6.24° at R8. The values at L8 and R8 were based on data from two (L8)

or three (R8) participants, and one of the participants included for L8 was an outlier with a threshold

of 36.24 degrees. Therefore, these lateral data are probably not reliable.

FIG. 2. (color online) The horizontal MAAs for sound sources reproduced with 9th-order

ambisonics. The line shows average values across participants; individual 75% thresholds are shown

with dots. The shaded region illustrates one standard deviation. (One individual's MAA at -90° (L8)

was 36.24°; this value contributed to the average but is not shown in the figure.)

TABLE I. Reference point azimuth coordinate (φ), estimated average MAAs with standard

errors (SE), and the number of participants remained in MAA estimation after excluding flat

psychometric curves (N). Approximation of previously measured MAAs with pure tones in free-

field are read from Fig. 6 of the Mills manuscript[1] and put in the MAA$_{SC}$ column for comparison.

Reference Point		φ_{RP} (°)		MAA $\pm$ SE (°)		MAA$_{SC}$ (°)	N	
C		0		1.03 $\pm$ 0.12		~1	6	
L1	R1	5.82	-5.82	1.11 $\pm$ 0.08	0.95 $\pm$ 0.12	~1	6	6
L2	R2	11.64	-11.64	1.40 $\pm$ 0.18	1.29 $\pm$ 0.17	~1.2	6	6
L3	R3	21.68	-21.68	1.64 $\pm$ 0.12	1.69 $\pm$ 0.36	~1.5	6	6
L4	R4	31.72	-31.72	2.38 $\pm$ 0.23	2.10 $\pm$ 0.32	~1.8	5	6

L5	R5	50.41	-50.41	4.46 ± *0.66*	2.81 ± *0.47*	~2	6	6
L6	R6	69.09	-69.09	4.46 ± *1.16*	8.48 ± *1.55*	~3	4	5
L7	R7	79.55	-79.55	5.84 ± *2.30*	7.94 ± *2.31*	~4	4	5
L8	R8	90.00	-90.00	21.78 ± *14.47*	6.24 ± *3.46*	> 10	2	3

In the rotated conditions, when participants were facing reference points L5 and R5, the average

MAAs were 1.20°±0.08° (N=6) at L5 and 1.17°±0.12° (N=6) at R5. (FIG 3.B). These values do not

differ from the frontal MAA obtained at C (three-condition repeated-measures ANOVA; $F_{(2,10)}$ =

0.8275, p = 0.4650). This indicates that similar MAAs are obtained for frontal positions, regardless

of the density of the LSP array at that location.

FIG. 3. (color online) A. A flattened illustration of the LSP locations (light grey dots) in the array

with reference points C, L5, and R5 (small dark dots). Note that C coincides with an LSP and is

surrounded by other LSPs nearby (as close as ±11.64° horizontally), while L5 and R5 are ±18.69°

azimuth and ±11.64° elevation away from the nearest LSPs. B. The midline MAA estimated at

different locations with different LSP densities. Individual data are illustrated with small dots and the

error bars show standard error of the mean.

In the post-experiment questionnaire, all participants reported perceiving noise bursts presented

at lateral locations L6-L8 and R6-R8 as above or below the horizontal plane, and this was

particularly true on the right side. Some participants used this illusory or artifactual elevation percept

as an indication of location in the horizontal plane. For example, one participant had concluded that

in trials at the R8 reference point, the noise burst that is perceived as higher was located clockwise

relative to the other one.   (This in fact was wrong and resulted in a flipped psychometric function.)

The possible cause of the elevation percept is investigated further in the following experiments.

C. Discussion

In this experiment horizontal MAAs were estimated for 17 reference points on the horizontal plane

for wide-band noise bursts reproduced with 9[th]-order ambisonics. The estimated MAAs were

consistently low around the midline and increased at more lateral locations. These results align well

with previous reports of human spatial acuity tested in free-field settings: MAAs within the range of

±25° azimuth match with the values reported by Mills [1] measured for 500 Hz and 1000 Hz pure

tones[1]. At other locations, the estimated MAAs do not differ substantially from the Mills[1] values

except for L8 (90° on the left). Also, all frontal MAAs reported here (in both the original and

rotated conditions) were smaller than those obtained in free-field testing with high-pass pink noise,

as reported by Strybel and Fujimoto[15], possibly because of the greater sound information and cues

available with broad-band noise. Our results demonstrate that sound sources reproduced with 9[th]-

order ambisonic panning are sufficiently focal such that two adjacent sources can be resolved at or

below the level of normal human spatial acuity at least for broadband sounds on the horizontal

plane, within 50.41° off the midline. The MAAs obtained at lateral azimuthal locations (greater than,

50.41° from the midline) diverge from those recorded using free field methods[1]. The divergence of

these may be due to the small number of samples, since several participants were excluded at these

lateral locations.

Frontal MAAs were tested on the midline, both when the individual was facing reference point

C, where the LSP density was highest, and also when the individual was facing L5 and R5 (see FIG

3), regions with the lowest LSP concentration. Obtained thresholds did not differ, implying that the

simulation precision is homogeneous across regions with different LSP densities. This observation

reassuringly indicates that the energy spread, and the blurring of virtual sound sources, are truly

location independent – at least with the 9th-order ambisonic panning used here. This confirms

theoretical predictions about the advantage of higher-order ambisonics over VBAP[7].

Finally, we investigated the anecdotal reports of elevation perception, which were unexpected.

We first made sure that the simulation codes did not send any commands to reproduce sounds

sources at any elevation level other than 0°. Then, three authors (NZ, BM, and IJ) and another

person (DQ) sat in the AudioDome and listened to a block of the task at L8. We agreed that the

virtual sound sources were sometimes heard from different elevation levels. This illusion

disappeared when we rotated to face L8 in the middle of the block. This observation motivated

Experiment 2, in which we quantified the localization cues for virtual sound sources rendered with

higher-order ambisonics.

III.   EXPERIMENT 2

In Experiment 1, participants' performance dropped substantially at lateral sound sources, more

than expected based on previous free-field measurements[1]. For example, at ±90° (reference points

L8 and R8), data for at least half of the participants were at chance, or below chance, at all test

points Participants in Experiment 1 also reported hearing sounds from lateral locations as above or

below the midline. These observations suggest that the spectral profile of the sounds was distorted

and was providing artifactual cues to elevation. Given that elevation perception relies on high-

frequency monoaural spectral information[2,21], we suspected that the ambisonics algorithm or

implementation (erroneously) resulted in the creation of notch filtering in the higher part of the

spectrum.

To investigate whether elevation perception at lateral locations was perhaps a result of artifactual

localization cues, we first evaluated spectral and ITD and ILD information for ambisonic sound

sources as recorded through a Head and Torso Simulator (HATS) placed in the same position and

facing the same direction as the participants in Experiment 1 (FIG. 4). Then we estimated the

spectrum, ITD, and ILD values for wideband-noise sources presented from horizontal LSP

locations using SC, VBAP, and ambisonic panning. Then, the values were estimated for the low-

frequency and the high-frequency portions of the spectrum and were compared across the two

bands. As SC only applies the LSP frequency response to the audio files it serves as the "ground

truth" for measurements. Hence, to identify errors in the spectral content of reproduced sound

localization cues, ITD, and ILD values derived from recordings of sound presented using VBAP

and ambisonic panning were compared to those using SC presentation.

A. Materials and Methods

The HATS type 4128C produced by Brüel & Kjær (Denmark) was used in this experiment. This

manikin simulates the acoustic properties of an average adult's upper body, head, and ears. The

HATS was placed on a tripod at the position of an ideal listener in the AudioDome and faced

towards the origin of the system with the ears at 0° elevation level aligned with the ±90° azimuth

line (FIG. 4).

FIG. 4. (color online) The HATS manikin in the measurement position in the AudioDome.

A sinusoidal chirp sweep was presented from target locations while the acoustic content was

recorded by two half-inch microphones located in the HATS built-in ears; to estimate binaural and

monaural cues as they are heard by an actual (average) human. The chirp signal was a broad-band

linear frequency sweep starting from 0 Hz to 22050 Hz sampled at 44100 Hz rate with a duration of

22.05 s (1000 Hz/s) and a constant amplitude of 78.1 dB SPL (Equation 2).

$$x_{chirp}(t) = \sin(1000\pi t^2) \qquad (2)$$

The sweep was presented from all the reference points tested in Experiment 1 (TABLE I) with

VBAP and ambisonic panning modalities, and SC when possible (when source location coincided

with an LSP; i.e., reference points C, L2, R2, L4, R4, L6, R6, L8, and R8). For each method, sweeps

were presented 4 times at each location, starting from R8 in counterclockwise order to L8. The

sweeps were interleaved with 2 s periods of silence, to ensure that any reverberations from the

previous sweep presentation had ceased, and that panning commands and triggers were transmitted

properly. Data for all three reproduction methods were recorded in one session in the following

order: SC, VBAP, and ambisonic panning. The HATS position and orientation did not change

during the recording.

1. Spectral content estimation

The power spectrum of the chirp sweep, and of each recording, was estimated using the

pspectrum function in MATLAB[22] with a frequency resolution of 200 Hz and leakage of 0.85. To

estimate the HATS transfer function for each panning method, at each target location, in each ear,

the spectra of corresponding recordings were divided by the chirp sweep spectrum and averaged

across the 4 repetitions. To measure the difference between the original and recorded spectra for

high and low frequencies, the spectrum was divided into two bands: a low-frequency band from 0

Hz to 4000 Hz, and a high-frequency band from 4000 Hz to 22050 Hz. The 4000 Hz boundary was

chosen based on the equation introduced by Ward and Abhayapala[7,14]; this equation derives the

minimum ambisonic order required to accurately reproduce a planewave with a particular

wavelength within a sphere of a particular radius at the center of the array. Using this equation, our

9th-order system is capable of accurately reproducing frequencies up to 4000 Hz within a sphere of

~12 cm radius at the center. (Male heads average 56.7 cm in circumference[23], which, if approximated

to a circle yields a radius of 9 cm. Thus 12 cm is a conservative estimate that also allows for some

error in head position.) Then, the HRTF amplitude spectra of sounds recorded from VBAP and

ambisonic panning were compared against SC HRTFs using the gain-difference score ΔG as

described in Equation 3[24]. In Eq. 3, $|\text{HRTF}_{panning}(f)|$ represents the HRTF magnitude of the

'panning' method at frequency 'f', and 'f_L' and 'f_H' represent the lower and the higher bound of the

estimation frequency band, respectively.

347
$$\Delta G_{panning}(f_L, f_H) = 10 log_{10} \frac{\int_{f_L}^{f_H} |HRFT_{panning}(f)|^2 df}{\int_{f_L}^{f_H} |HRFT_{SC}(f)|^2 df} \tag{3}$$

2. ITD estimation

ITDs are more dominant for frequencies below 1 kHz[2,4,5] and thus any reconstruction error at

higher frequencies are not important. However, in the frequency range of 1000-1500 Hz neither

ITD nor ILD cues dominate localization[2,4,5], therefore to assess the general quality of ITD

reconstruction, the 1000-1500 Hz range with some margin was included in the lower frequency

portion of the spectrum for ITD estimations. For ITD measurement, the spectrum was again

divided to two portions: but this time the lower frequency band extended from 0 Hz to 1800 Hz,

and the higher frequency band from 1800 Hz to 22050 Hz. To estimate the ITD within each range,

the portion of the recording that corresponded to each frequency range (based on the chirp signal

presentation timing) was taken. Then this portion of the signal was temporally upsampled with a

factor of 10 to increase the temporal resolution of the cross-correlation function used in the next

stage. Finally, the ITD was estimated as the lag amount that maximized the cross-correlation

between the left and right channel recordings (delayed in the right channel relative to the left). ITDs

were reported as the average of the 4 values estimated for each location with each reproduction

method.

3. ILD estimation

To estimate ILDs, the Fourier transform of the signal in both ears was estimated with the *fft*

function in MATLAB[22]. As in the spectral content analysis, a boundary of 4000 Hz was used to split

the spectrum into low-frequency and high-frequency bands. The sum of squared values of the

Fourier coefficients of frequencies within each band indicated the spectral power of that band. The

ratio of the spectral power in the left channel over the spectral power in the right channel was used

to estimate ILDs. ILDs were estimated for each measurement separately and the average across the

4 repetitions were used to calculate an ILD value for each reference point and reproduction method.

B. Results

The HRTF for the left and right channels of the HATS for sound sources from horizontal LSP

locations is shown in FIG 5.A for SC and ambisonic panning methods. This panel, in combination

with the gain-difference scores, ΔG, for the two frequency bands illustrated in FIG 5.B, shows that

the ΔG is larger at higher frequencies than at lower frequencies, and, overall, ambisonically rendered

sounds have lower power than SC sounds. (VBAP is theoretically equivalent of SC panning when

the sound sources coincide with an LSP location, therefore VBAP HRTF magnitudes are not

included. In panel B the ΔG between VBAP and SC is shown and approximates 0 everywhere,

confirming the equivalence of VBAP and SC presentation methods for veridical loudspeaker

locations.)

A

B

FIG. 5. (color online) A. The HRTF magnitudes (left, and right) for sounds reproduced at LSP

locations on the horizontal plane in the AudioDome. Only SC and ambisonic panning methods are

shown. The top row shows the spectra of sound sources presented on the midline (reference point

C). On the other rows, the left pair of panels shows the spectra of response to presentations at L2,

L4, L6 and L8, in the left and right ears. The right pair of panels show the spectra of response to

presentations at R2, R4, R6, and R8. B. The gain-difference score (ΔG) which compares the

magnitude spectra of SC and other presentation methods is shown for the low frequency (0-4000

Hz) and high frequency (4000-22050 Hz) regions in the channel ipsilateral to the source location (for

$\varphi = 0°$ the average of both channels is illustrated). $F_c = 4000$ Hz was set as the boundary frequency

that splits the spectrum. ΔG for VBAP - SC   illustrates the noise ceiling of the score - the fact that

its values are around 0 dB confirms the equivalence of VBAP and SC for these reference point

locations.

FIG. 6. (color online) The average ITD (left column) and ILD (right column) values in low (top

row) and high (bottom row) frequency bands across different reproduction methods for sound

sources at reference points across the horizontal plane. The boundary frequencies to split low and

high bands were 1800 Hz for ITD and 4000 Hz for ILD panels. Data for locations between LSPs

are available only for VBAP and ambisonic panning. Error bars are standard error.

For all the reference points tested in Experiment 1, the average ITD and ILD values were

estimated for the three sound reproduction methods (only LSP locations for SC) as illustrated in

FIG 6. When the sound source was located on the horizontal midline ($\varphi = 0°$) ITD values were 0 μs

for all reproduction methods, and all repetitions. This confirms that the HATS was positioned

properly in the center of the array during the experiment. The average low-frequency (0-1800 Hz)

ITDs for SC and VBAP followed a monotonic trend from reference point L8 (–90°) through the

midline (C) to R8 (+90°), and ranged between ±703 μs. ITD values were symmetrical between left

and right. ITDs measured from VBAP presentations were equal to those of SC ITDs at LSP

locations as theoretically expected. For ambisonics, the average low-frequency ITDs ranged from -

658 μs to +681 μs with a monotonic trend from reference point L8 (–90°) through the midline (C)

to R8 (+90°). ITDs were slightly different between the left and right hemifields (maximum

difference ~ 23 μs) at L3/R3, L6/R6, L7/R7, and L8/R8 pairs. The average low-frequency ITDs

for VBAP and ambisonics were equal for L7/L8 and R7/R8 pairs. Average high-frequency (1800-

22050 Hz) ITDs for SC also followed a monotonic trend within the range of ±726 μs, and had equal

magnitudes on the right and left except at the L4/R4 pair where they differed by ~23 μs. Average

high-frequency ITDs for VBAP again matched the values of SC at LSP locations and were

symmetrical on the left and right, except for the L8/R8 pair which differed by 40 μs. At locations

between LSPs,ITDs derived from VBAP data diverged from the monotonic trend and were not

always symmetrically equal in magnitude. ITDs measured in the high-frequency region for ambisonic

presentation ranged from -840 μs to749 μs, with a non-monotonic trend at the front (L2 to R2); the

magnitude of these ITDs were symmetrically equal up ±51°, and the trend diverged from SC ITD

values on the sides (L6-L8 and R6-R8). The standard deviation (across four recordings per

reproduction method, per reference point) of all measured ITD values was 0 μs, except for the high

frequency band VBAP ITD at $\varphi = -90°$ which had a standard deviation of 11.34 μs.

Average low-frequency (0-4000 Hz) ILDs for SC were within the range of ±11.5 dB with a

monotonic trend within ±69.09° azimuth angle and a lower magnitude of ±5.8 dB at ±90°. The

average low-frequency ILD was -0.55 dB when the source was at the center (reference point C).

(Note that ITD was 0 μs at this point indicating that HATS was probably not poorly placed, so the

this small low-frequency ILD may result from different shapes of the left and right ears of the

HATS.) At symmetrical locations, these values were relatively equal in magnitude (less than 1.1 dB

different). For VBAP, the average low-frequency ILDs closely matched (less than 0.8 dB different)

with SC at LSP locations but diverged from the SC trend at locations between LSPs, particularly at

L1 and R1. Average low-frequency ILDs for VBAP were symmetrical on the left and right (less than

1.8 dB different). For ambisonic sources, average low-frequency ILDs were close to SC across the

horizontal plane (less than 2.2 dB different) except at L8, where they differed by 3.7 dB. Average

high-frequency (4000-22050 Hz) ILDs for SC-presented sounds ranged from -12.09 dB to 12.25 dB,

and were bilaterally symmetrical (less than 1.8 dB different), and trended monotonically from

reference point L8 (–90°) through the midline (C) to R8 (+90°). High-frequency ILDs for VBAP

matched SC values (less than 0.3 dB different), and were relatively symmetrical (less than 2.6 dB

difference between left and right homologous locations). VBAP high-frequency ILD measurements

diverged from interpolated SC data between LSPs, particularly at L1, R1, L7, and R7. Finally, high-

frequency ILDs measured from ambisonic presentation were close to those measured for SC

presentation between 69.09° and -50.41° azimuth locations (less than 1.9 dB different) and had

symmetrical magnitudes (less than 2.4 dB difference between left and right), but diverged

significantly and asymmetrically from SC data (and interpolations) at more lateral locations. Finally,

the standard deviation of the four ILD estimates did not exceed 0.07 dB at any location for any

reproduction method.

C. Discussion

Frequency responses to broadband sweeps were measured from the left and right ear canals of a

head and torso simulator (HATS), positioned in the AudioDome the same way as participants in

Experiment 1, for all reference points tested in Experiment 1. SC presentation at the frontal LSP

location ($\varphi = 0°$) produced responses in the left and right channels that are similar to each other and

to frontal HRTF magnitudes previously reported[2]. At all locations, within each channel, the

magnitude spectra of HRTF differ between ambisonic panning and SC presentation. Although the

power of ambisonically rendered sound sources is generally less than that of SC sources, the

difference in magnitude between the two reproduction methods is not homogenous across the

spectrum. In the high frequency range (4000-22050 Hz), the power of ambisonically rendered sound

is 1.5-8 dB below SC values for LSP-coincident reference points (the only exception is $\varphi = -90°$,

where high frequency power matches between reproduction methods). In the low frequency region

(0 – 4000 Hz) the power difference between the two methods was in the ±2.5 dB range, which is

overall lower than the power difference in the high-frequency region. Furthermore, the reproduction

method with higher power in this low-frequency band varies with the sound source location. (FIG

5.B)

Low-frequency (0-1800 Hz) ITDs for sources presented over SC followed a monotonic trend, f

from reference point L8 (–90°) through the midline (C) to R8 (+90°), within a range similar to

previous reports; for example, Feddersen et al. demonstrated ITDs between ±670 µs over this

range[2,25]. VBAP low-frequency ITDs matched these values at locations coincident with LSPs, as

expected, but diverged from interpolated SC values at positions between LSPs. Low-frequency ITDs

measured from ambisonically presented sounds were not only close to those of SC presented

sounds, but they aligned better than did VBAP ITDs with the interpolated SC values at midpoint

locations. For the higher frequency band (1800-22050 Hz), SC ITDs changed monotonically over

the reference points from L8 to R8 as expected. VBAP and ambisonic ITDs diverged from

interpolated SC values at locations between LSPs, and this divergence was more marked, and values

were more asymmetrical between left and right, than for the low-frequency range. Fortunately, these

higher-frequency ITDs are not relevant for perception and so these high-frequency ITD

reproduction errors may not be perceptually salient. Thus our results indicate that neither VBAP

nor ambisonic panning produce appreciable ITD errors (FIG 6, left column) and the ITDs accord

well with those in the literature.

In the low-frequency region (0-4000 Hz), ILDs for SC-presented sounds are somewhat smaller than

expected from published work. Feddersen et al[2,25] demonstrated ILDs between 0-20 dB for

frequency subbands below 4000 Hz, with lower frequencies having smaller ILDs. Our low values

might be due to averaging across the band. VBAP values matched those for SC presented sounds at

LSP locations but diverged from the interpolated values at locations between LSPs. In contrast,

although low-frequency ILDs for ambisonically presented sweeps were somewhat different from SC

values at LSP locations, they were overall closer to the interpolated SC data across all locations. In

the higher frequency range (4000-22050 Hz) ILD values measured from VBAP presentation were

similar to those for SC presented sounds at LSP locations but still diverged from interpolated SC

values between LSPs. High-frequency ILDs for ambisonically presented sweeps matched SC values

at frontal locations (C, L1-4; R1-4), but diverged significantly from the SC trend at the most lateral

locations (L7-8, R7-8). High frequency ILDs measured from ambisonically rendered sweeps differed

at homologous locations on the left and right. Given that ILD information used to localize sounds is

derived from high-frequency components of sounds these differences between ambisonic and SC

ILDs are likely to mislead human perceptual localization, especially when low-frequency ITDs are

not present to down-weight high-frequency ILDs[5,26](FIG 6, the right column). In general, binaural

localization information is largely preserved for frequencies below 4000 Hz in the AudioDome,

consistent with theoretical predictions.[7,14]ILD and HRTF cues at frequencies above 4000 may not be

correctly reproduced.

Finally, the spectral content, ITDs, and ILDs for sound sources presented ambisonically at the

most lateral locations ($\varphi = \pm69.09°$ and $\varphi = \pm90°$) differ on the right and left sides (for example,

look at the spectral power peaks at ~8 kHz in FIG 5.A). These unexpected asymmetrical

reconstruction errors are not observed when SC or VBAP reconstruction methods are used. The

asymmetries are most visible in the magnitude spectra. To ensure that this was not an artefact of the

recording setup or analysis method, the HATS was horizontally rotated 180° to face the back of the

AudioDome and the chirp sweeps were presented at $\varphi = \pm90°$ locations with all three presentation

methods again. The asymmetries in the estimated magnitude spectra were reversed in the rotated

compared to the unrotated condition, indicating that the asymmetry results from the implementation

of ambisonic panning in the AudioDome. (See supplementary figure FIG.S. 1.) This implies that

there may be some asymmetry in the LSP or other hardware setup in the AudioDome, resulting in

somewhat different spectral errors at very lateral locations – beyond $\varphi = 69.09°$ - on the left and

right sides at frequencies over 4000 Hz. Interestingly, other studies that simulated or tested

ambisonic systems have also observed asymmetric reconstruction errors; Neal and Zahorik[13]

simulated SC, VBAP, and ambisonic reconstruction with different orders and estimated

reconstruction error and the potential impact on psychoacoustic localization cues (total level, ILD,

and ITD). Although not thoroughly discussed, they also report cue reconstruction errors that differ

between the left and right side in their simulations, especially for higher-order ambisonics. Other

examples can be found in Figures 9.11 and 9.13 in the sound-field review chapter of "Immersive

Sound" by Nicol[7] that illustrate ITD and ILD estimates across different locations on the horizontal

plane for a sound source at $\varphi = 0°$ rendered using 19th-order ambisonic system. Again, asymmetry of

reconstructed cues is observable, although not discussed and interpreted in the text. Ambisonic

panning might be very sensitive to implementation details such as LSP calibration, adjustment, etc.

Although it seems that reconstruction error asymmetry has not attracted much attention in the field,

it could be an issue when ambisonic technology is used for psychoacoustic experimentation;

erroneous conclusions about left-right asymmetry in human performance might be drawn when in

fact the source of the asymmetry is, at least in part, in the implementation of ambisonics.

IV.   EXPERIMENT 3

During Experiment 1, participants anecdotally reported perceiving ambisonically presented

sound sources, particularly those at lateral locations, as elevated. This was surprising, since all sounds

were presented at locations in the horizontal plane. In Experiment 2, we determined that, at lateral

locations, spectral information above 4kHz was distorted when sounds were rendered using

ambisonic panning. Given that the spectral content in the 4-16 kHz range is important for sound

source elevation perception[21], these spectral differences might serve as unintended elevation cues. In

Experiment 3, we aim to provide empirical evidence for the anecdotal reports in Experiment 1 and

we hypothesize that they could be explained by the findings in Experiment 2. To achieve this goal,

we had an independent group of listeners compare the perceived elevation of one of a pair of noise

bursts, both presented at the same location: one reproduced with ambisonics and one presented

through a single channel. We tested the same reference points as in Experiment 1, and participants

were blind to the fact that sound sources were programmed to be collocated. Our hypothesis about

systematic errors in the reproduction of high-frequency information creating artefactual elevation

cues is investigated by comparing the degree to which lowpass, ambisonic sounds (i.e., without high-

frequency cues) are heard as elevated above their SC controls, compared to wideband, ambisonic

sources with high-frequency information, and thus artefactual elevation cues.

A. Materials and Methods

Twelve (5 female) young (aged 22-30 years), healthy, normally hearing (thresholds measured

audiometrically at both ears at octaves of 125 Hz up to 8 kHz; participants were excluded if their

threshold exceeded 25 dB HL at any tested frequency in either ear), right-handed listeners with no

history of neurological disorders completed the task. (Four listeners were excluded for the following

reasons: two reported concussion history, one did not pass the audiometry test, and one reported

during the debrief that they did not follow the eye fixation instructions.) Listeners had no experience

with AudioDome experiments. The experiment setup and participant positioning were similar to

Experiment 1 (except that no head tracking sensors were applied).

Participants completed an elevation discrimination task for reference points C, L4, R4, L6, R6,

L8, and R8 as listed in TABLE I. On each trial, participants were presented with two noise bursts

and were instructed to report the relative elevation of the second burst compared to the first one.

The trials were presented in two conditions: in the 'lowpass' condition both noise bursts contained

only frequency components below 4000 Hz (the boundary value for accurate acoustic environment

reproduction with ambisonic panning as explained in Experiment 2[7,14]), and in the 'wideband'

condition two wide-band noise bursts, with components between 0 and 22050 Hz, were presented.

In both conditions the noise bursts were presented from the same location: one was presented with

SC, and the other with 9^{th}-order ambisonic panning. (Ambi$_{low}$ vs. SC$_{low}$, Ambi$_{wide}$ vs. SC$_{wide}$ trials).

Twenty trials of each type were included for each reference point, with the SC-presented burst first

on half the trials. Another forty trials per reference point were tested in which both noise bursts

were presented with SC (SC$_{low}$ vs. SC$_{low}$, SC$_{wide}$ vs. SC$_{wide}$ trials) as filler trials (they were not analyzed

later). To ensure participants stayed engaged, an additional 20 trials with large veridical elevation

differences, both bursts presented using SC, were included at each reference point. The azimuth

angle of sources in these trials was optimized to match the azimuth angle of the reference points,

therefore, based on the AudioDome's layout, the veridical elevation angle differences ranged

between 61° and 94°. Thus, 100 trials were tested per reference point; 700 trials total.

The stimuli were generated using MATLAB[22] with the same parameters as Experiment 1. The

lowpass noise bursts were originally generated as wideband (0-22050 Hz) and then, before the

attack-decay envelope was applied, were filtered with an FIR lowpass filter with a passband

frequency of 4000 Hz, a stopband of 4900 Hz, pass gain of 1 dB, stop gain of -80 dB, and a density

factor of 20, designed and generated with MATLAB's Signal Processing Toolbox[22,27]. Overall, 200

different noise bursts were generated and pseudo-randomly assigned to trials (the same noise burst

was assigned to both intervals of a single trial). The 700 trials were divided into five experimental

blocks, each with an equal number of trials of all trial types at all reference points. The order of trial

presentation was fully randomized. For each participant, stimulus assignment, trial order, and

presentation method order within Ambi vs. SC test trials were pseudorandomized such that all noise

bursts were presented an equal number of times at all reference points. .

As in Experiment 1, lights were extinguished, and a red LED was placed at the front, on the

horizontal plane at ear level for gaze fixation. Participants were instructed to report the relative

elevation of the second noise burst compared to the first one (above/below) via keypress on a small

keypad. At the beginning of the experiment, participants practiced the task on 14 trials in which

both bursts were presented single channel and there was a large veridical elevation displacement

between them (2 practice trials per reference point). They proceeded to the main trials once they

passed a 75% accuracy threshold in the practice block (the block was repeated after clarification of

the instructions if they performed with a lower accuracy). Feedback about accuracy was provided to

participants only during the practice block. Feedback about average reaction time (acceptable or too

slow, given the number of missed trials) and the number of response-missed trials was provided at

the end of each main block to keep participants focused on the task. The data were collected within

one session.

In the preprocessing stage, trials with no responses were removed from the data. Then, the

proportion of trials on which the ambisonically presented sound was perceived as elevated was

estimated for each participant, for all trial types, at each reference point.

B. Results

We predicted that ambisonically rendered sounds with frequency components over 4 kHz would

be heard as elevated compared to the same sound presented over a single channel on $Ambi_{wide}$ trials,

whereas ambisonically rendered sounds without such components would not (i.e., $Ambi_{low}$ trials). In

fact, in most cases the ambisonically presented sound was perceived to be below the SC sound. The

average proportion of trials on which the ambisonically presented sound was perceived as elevated,

as a function of reference point for both lowpass and wideband noise bursts, is, is illustrated in FIG

7.A ($Ambi_{low}$ and $Ambi_{wide}$). These values are reliably below the 50% value expected by chance at C

($t_{low}(7) = -16.17, \ p < 10^{-6}$ & $t_{wide}(7) = -2.44, \ p < 0.05$), L4 ($t_{low}(7) = -20.11, \ p < 10^{-6}$ & $t_{wide}(7) = -$

5.23, $p < 0.05$), R4 ($t_{low}(7) = -6.45, \ p < 10^{-3}$ & $t_{wide}(7) = -15.56, \ p < 10^{-6}$), and L8 ($t_{low}(7) = -4.87, \ p$

< 0.01 & $t_{wide}(7) = -3.23, \ p < 0.05$). At R6 ($t(7) = -2.51, \ p < 0.05$) and R8 ($t(7) = -6.07, \ p < 10^{-3}$)

only the $Ambi_{low}$ proportion is below the chance level. All other values do not differ from the 50%

chance level ($p > 0.05$). It is possible that the timbral and power difference between ambisonically

rendered and SC rendered sounds was erroneously interpreted as an elevation difference, with

participants reporting the burst with less power (i.e., the ambisonically rendered burst) as lower in

elevation.

Even though subjects exhibited a response bias towards reporting the SC presented sound as

higher, we could still ask whether there is a difference in the degree to which wideband

ambisonically rendered sounds are heard as elevated, relative to the lowpass ambisonically rendered

sounds (which presumably contain fewer misleading localization cues). We therefore tested the

difference between $Ambi_{wide}$ –and $Ambi_{low}$. This value was computed individually for each person

and is shown in FIG 7.B. This value will be positive if $Ambi_{wide}$ trials yield a greater proportion of

elevation responses than do $Ambi_{low}$ trials, as predicted These values were indeed significantly

positive at C ($t(7) = 2.06$, $p < 0.05$), L4 ($t(7) = 2.12$, $p < 0.05$), R6 ($t(7) = 6.25$, $p < 10^{-3}$), and R8

($t(7) = 4.61$, $p < 10^{-2}$) reference points, ut not at R4, L6, and L8.

FIG. 7. (color online) A. The average proportion of ambisonically rendered sounds perceived as

elevated, compared to the SC reference interval for each of the two experimental conditions,

Ambi$_{wide}$ and Ambi$_{low}$ B. The degree to which ambisonically rendered wideband noise bursts are

reported as elevated (relative to their SC reference) compared to ambisonically rendered lowpass

noise bursts (i.e., every set of two columns in panel A were subjected to the following arithmetic

operation: Ambi$_{wide}$ – Ambi$_{low}$). Error bars in both panels represent the 95% confidence interval of

the grand mean. Dots show individual participant data. Except at R4 which the grand mean is

negative, all values are greater than zero, although only C, L4, R6 and R8 are significantly greater

than zero, demonstrating a reliably greater tendency for wideband ambisonically rendered sounds to

be perceived as elevated, compared to lowpass ambisonically rendered sounds, at these locations.

The lack of significance at the other locations could be due to a lack of power.

C. Discussion

In Experiment 3, we compared the perceived elevation of lowpass and wideband sounds,

ambisonically reproduced at horizontal reference points, relative to the same sounds presented from

a single loudspeaker at the same location. Rather surprisingly, the ambisonically rendered sounds

appeared to be generally perceived as below their SC controls. There is a perceptible timbral

difference between the ambisonic and SC rendered sources, and the ambisonic sources also have

lower power (as documented in Experiment 2). Participants may have interpreted these differences

in the ambisonic sounds to indicate a source below the horizontal plane.

Despite this general response bias, we observed that a greater proportion of ambisonic sounds

were perceived as elevated relative to the SC reference sound on wideband trials, compared to

lowpass trials, at almost all reference points (FIG 7.A). This consistent effect suggests that the high-

frequency components included in the wideband, but not lowpass, sounds were distorted by

ambisonic presentation, contributing to perceived elevation as predicted. However, there was also

more variability in response to wideband than lowpass trials. This is not surprising because each

participant has their own HRTF, so individuals will interpret the spurious spectral cues present in

the high-frequency components differently. Also, as illustrated in FIG 7.B, the effect of high-

frequency components in the perceived elevation of ambisonic sources seems to be somewhat

variable across different locations, being more pronounced at lateral locations on the right side. This

is consistent with our observations in Experiment 2 of larger reproduction errors on the right side,

compared to the left, possibly due to subtle asymmetries in the location or calibration of

loudspeakers. In this study, we assessed the fidelity of a 9^{th}-order ambisonic loudspeaker array for

the reproduction of focal sound sources on the horizontal plane.

V.   CONCLUSIONS AND DISCUSSION

In this study, we assessed the fidelity of a 9^{th}-order ambisonic loudspeaker array for the

reproduction of focal sound sources on the horizontal plane. In Experiment 1, we quantified the

limits of human spatial acuity in the frontal half of the horizontal plane with wideband sound

sources presented with ambisonic panning. Values for the minimal audible angle (MAA), the just

noticeable difference in horizontal displacement ranged from 1.03 - 1.2°, for the horizontal midline

location, similar to previous findings.[1] In fact, MAAs were similar to the existing literature for

locations within the range of ±51° degrees azimuth[1], confirming that ambisonic panning in the

AudioDome results in sources that are so focal that any blurring is below the threshold for human

auditory spatial acuity. The recordings through a head-and-torso simulator in Experiment 2

demonstrated that ITD cues, estimated for ambisonic sources on the horizontal plane at frequencies

up to 1800 Hz, are not distorted.

Our system is theoretically restricted to accurately reproduce plane-waves up to 4 kHz for a

sphere of radius of 12 cm[7,14], and indeed we noticed distortions in the frequency region above 4

kHz, which altered the spectral profile in ways that might alter localization. Spectral magnitudes in

the range of ILDs were also affected, with left-right asymmetries that could create artefactual ILDs.

In Experiment 3, we showed that ambisonic reconstruction errors in the frequency region 4000-

22050 Hz are associated with a greater tendency to perceive the rendered sources as elevated,

compared to similar sounds without components in this frequency region. Overall, we showed that

the AudioDome can reproduce focal sources reliably if high frequencies (above 4000 Hz) are

omitted.

Based on these observations, for accurate localization it seems best to limit the reproduced

spectral content in the AudioDome to components below 4000 Hz for accurate spatial

reproduction. For naturalistic studies of speech listening in the presence of competing talkers and

other sounds, inclusion of information above 4000 Hz is desirable and so SC reproduction may be

preferable.

Additionally, we showed that ambisonic panning reproduces sources more homogenously and

reliably than does VBAP, at locations between loudspeakers. We also observe a general difference of

reproduction error of high frequency components of sound between left and right symmetrical

locations (here, high frequency is above 1800 Hz for ITDs and above 4000 Hz for ILD and spectral

cues); although this asymmetry might be only specific to our system, there is evidence of this

phenomenon in other studies simulated ambisonic rendering[7,13]. While its basis might be related to

the sensitivity of the ambisonic implementation to loudspeaker array calibration or positioning, the

causes are unknown and future work is required to investigate to reveal the causes of this

observation.

This project is the first study that aimed to utilize the AudioDome to test human perception,

andand it is also a pioneer in conducting psychophysical experiments using a higher-order

ambisonics system, demonstrating that sources rendered with a 9[th] order ambisonic system are

sufficiently focal such that any blurring is below the threshold of human auditory spatial resolution.

Although there are issues with ambisonic rendering of components above 4 kHz, this research lays

the groundwork for future experiments on naturalistic human auditory perception.

SUPPLEMENTARY MATERIAL

At the end of Experiment 2, the HATS was rotated horizontally 180° so we could measure the

effect of physical orientation of the HATS on the recording content; it is possible that the

asymmetrical reproduction errors are due to asymmetries in the HATS structure (the model's pinnae

for left and right are not perfectly symmetrical as natural pinnae). If this hypothesis is true, then the

response of the left and right channels should not change as we rotate the manikin and record the

same sounds. However, as observed in FIG S.1, this is true for SC presentation, but for ambisonics,

the response in the left channel transfers to the right ear and vice versa, showing that the recording

is reflecting the true spectral content of the reproduced sounds at the recording location.

FIG.S. 1. (color online) The magnitude spectra of auditory responses to chirp sweeps presented

from L8 and R8 (±90°) in both channels when the HATS is facing the center ($\varphi = 0°$) and when it is

fully rotated to face the back of the AudioDome ($\varphi = 180°$).

ACKNOWLEDGMENTS

The authors would like to thank Dr. Derek Quinlan and Karsten Pravoslav Babin for their

invaluable help and support with experiment hardware setup and programming. We thank the

Canadian Foundation for Innovation (CFI) for funding the AudioDome, and the Natural Sciences

and Engineering Research Council (NSERC) for research funding.

AUTHOR DECLARATIONS

Conflict of Interest

The authors have no conflicts to disclose.

Ethics Approval

The experiments presented in this manuscript were approved by The Western University Non-

Medical Research Ethics Board. Informed consent was obtained from all participants.

DATA AVAILABILITY

The data that support the findings of this study are available from the corresponding author

upon reasonable request.

REFERENCES

[1]A. W. Mills, "On the minimum audible angle," J. Acoust. Soc. Am. **30**, 237–246 (1958).

[2]J. Blauert, *Spatial Hearing: The Psychophysics of Human Sound Localization*, (MIT Press, 1997).

[3]C. J. Plack, *The sense of hearing*, (Third edition. | Abingdon, Oxon; New York, NY: Routledge, 2018.,

Routledge, 2018).

[4]Rayleigh, "XII. On our perception of sound direction," Lond. Edinb. Dublin Philos. Mag. J. Sci. **13**,

214–232 (1907).

[5]E. A. Macpherson, and J. C. Middlebrooks, "Listener weighting of cues for lateral angle: the duplex

theory of sound localization revisited," J. Acoust. Soc. Am. **111**, 2219–2236 (2002).

[6]H. Møller, "Fundamentals of binaural technology," , doi: 10.1016/0003-682X(92)90046-U.

doi:10.1016/0003-682X(92)90046-U

[7]P. Roginska, *Immersive Sound, Chapter 9: Sound Field*, (Routledge, 2017), 1st Edition.

[8]S. Li, and J. Peissig, "Measurement of head-related transfer functions: A review," Appl. Sci. (Basel)

10, 5014 (2020).

[9]V. Pulkki, "Virtual sound source positioning using vector base amplitude panning," JAES **45**, 456–

466 (1997).

[10]V. Pulkki, "Uniform spreading of amplitude panned virtual sources," in *Proceedings of the 1999 IEEE*

Workshop on Applications of Signal Processing to Audio and Acoustics. WASPAA'99 (Cat.

No.99TH8452) (IEEE, 1999) pp. 187–190.

[11]F. Zotter, and M. Frank, *Ambisonics*, (Springer International Publishing, 2019).

[12]S. Bertet, J. Daniel, E. Parizet, and O. Warusfel, "Investigation on Localisation Accuracy for First

and Higher Order Ambisonics Reproduced Sound Sources," Acta Acustica united with

Acustica **99**, 642–657 (2013).

[13]M. T. Neal, and P. Zahorik, "The impact of head-related impulse response delay treatment strategy

on psychoacoustic cue reconstruction errors from virtual loudspeaker arrays," J. Acoust. Soc.

Am. **151**, 3729 (2022).

[14]D. B. Ward, and T. D. Abhayapala, "Reproduction of a plane-wave sound field using an array of

loudspeakers," IEEE Trans. Speech Audio Process. **9**, 697–707 (2001).

[15]T. Z. Strybel, and K. Fujimoto, "Minimum audible angles in the horizontal and vertical planes:

effects of stimulus onset asynchrony and burst duration," J. Acoust. Soc. Am. **108**, 3092–

3095 (2000).

[16]G. A. Gescheider, "Psychophysics: The fundamentals.,"

[17]P. Virtanen, R. Gommers, T. E. Oliphant, M. Haberland, T. Reddy, D. Cournapeau, E. Burovski,

et al., "SciPy 1.0: fundamental algorithms for scientific computing in Python," Nat. Methods

17, 261–272 (2020).

[18]K. W. Vugrin, L. P. Swiler, R. M. Roberts, N. J. Stucky-Mack, and S. P. Sullivan, "Confidence

region estimation techniques for nonlinear regression in groundwater flow: Three case

studies," , doi: 10.1029/2005WR004804. doi:10.1029/2005WR004804

[19]The MathWorks Inc., *MATLAB 2022b*, (2022). Retrieved from https://www.mathworks.com

[20]V. Tabry, R. J. Zatorre, and P. Voss, "The influence of vision on sound localization abilities in

both the horizontal and vertical planes," Front. Psychol. **4**, 932 (2013).

[21]J. Hebrank, and D. Wright, "Spectral cues used in the localization of sound sources on the median

plane," J. Acoust. Soc. Am. **56**, 1829–1834 (1974).

[22]The MathWorks Inc., *MATLAB 2023b*, (2023). Retrieved from https://www.mathworks.com

[23]A. K. D. Nguyen, A. A. Simard-Meilleur, C. Berthiaume, R. Godbout, and L. Mottron, "Head

circumference in Canadian male adults: Development of a normalized chart," Int. J.

Morphol. **30**, 1474–1480 (2012).

[24]F. Brinkmann, A. Lindau, S. Weinzierl, M. Müller-Trapet, R. Opdam, M. Vorländer, and Others,

"A high resolution and full-spherical head-related transfer function database for different

head-above-torso orientations," J. Audio Eng. Soc. **65**, 841–848 (2017).

[25]W. E. Feddersen, T. T. Sandel, D. C. Teas, and L. A. Jeffress, "Localization of high-frequency

tones," J. Acoust. Soc. Am. **29**, 988–991 (1957).

[26]M. L. Folkerts, and G. C. Stecker, "Spectral weighting functions for lateralization and localization

of complex sound," J. Acoust. Soc. Am. **151**, 3409 (2022).

[27]The MathWorks Inc., *MATLAB Signal Processing Toolbox*, (2023). Retrieved from

https://www.mathworks.com