CarpeDeam: A *De Novo* Metagenome Assembler for Heavily Damaged Ancient Datasets

Louis Kraft[1][*], Johannes Söding[5,6,7], Martin Steinegger[8,9,10], Annika Jochheim[2,5,6], Peter Wad Sackett[1], Antonio Fernandez-Guerra[†2,3,4], and Gabriel Renaud[†1,*]

[1]Department of Health Technology, Section for Bioinformatics, Technical University of Denmark, Kongens Lyngby, Denmark

[2]Centre for Ancient Environmental Genomics, Globe Institute, University of Copenhagen, Copenhagen, Denmark

[3]Lundbeck Foundation GeoGenetics Centre, Globe Institute, University of Copenhagen, Copenhagen, Denmark

[4]Ancient Environmental Genomics Initiative for Sustainability, Globe Institute, University of Copenhagen, Copenhagen, Denmark

[5]Quantitative and Computational Biology Group, Max Planck Institute for Multidisciplinary Sciences, Göttingen, Germany

[6]International Max-Planck Research School for Genome Sciences (IMPRS-GS)

[7]Campus Institute Data Science (CIDAS), University of Göttingen, Germany

[8]School of Biological Sciences, Seoul National University, Seoul, South Korea

[9]Artificial Intelligence Institute, Seoul National University, Seoul, South Korea

[10]Institute of Molecular Biology and Genetics, Seoul National University, Seoul, South Korea

[*]Correspondence: lokraf@dtu.dk, gabriel.reno@gmail.com

[†]These authors contributed equally to this work.

March 20, 2025

Abstract

De novo assembly of ancient metagenomic datasets is a challenging task. Ultra-short fragment size and characteristic postmortem damage patterns of sequenced ancient DNA molecules leave current tools ill-equipped for ideal assembly. We present CarpeDeam, a novel damage-aware *de novo* assembler designed specifically for ancient metagenomic samples. Utilizing maximum-likelihood frameworks that integrate sample-specific damage patterns, CarpeDeam demonstrates improved recovery of longer continuous sequences and protein sequences in many simulated and empirical datasets compared to existing assemblers. As a pioneering ancient

metagenome assembler, `CarpeDeam` opens the door for new opportunities in functional and taxonomic analyses of ancient microbial communities.

1 Keywords

Ancient DNA, Metagenomics, *de novo* Assembly, Microbes, Proteins

2 Background

DNA recovered from ancient organisms, termed ancient DNA (aDNA), has transformed evolutionary science. Besides the exploration of ancestral human populations, aDNA enables the reconstruction of past environments covering eukaryotic species diversity and microbial community dynamics [1, 2, 3, 4]. However, the computational analysis of aDNA is challenging [5, 6]. Two primary processes lead to the breakdown and chemical alteration of aDNA. Hydrolytic mechanisms cause the degradation of DNA molecules and deamination converts cytosines into uracil molecules. These are misinterpreted as putative base substitutions during DNA sequencing [7]. This phenomenon, known as "damage", occurs predominantly at the ends of aDNA fragments, and the rate of occurrence of damage at each fragment position can be quantified [8, 9, 10, 11]. As a result, aDNA fragments show elevated frequencies of C→T substitutions at the 5′ end and G→A substitutions at the 3′ end, respectively [12]. Along with the short fragment size, damage profiles are commonly used for aDNA authentication [13, 14, 15, 16]. However, the ambiguity introduced by deaminated bases hampers downstream analysis such as read mapping or genome assembly [17, 18, 19].

Metagenomes represent the collective genetic material from various species within a sample, derived from environments such as the human gut or soil, including bacteria, archaea, viruses, and eukaryotes [20, 21]. The field has expanded with the advent of massive parallel sequencing, leading to a deeper understanding of microbial diversity and functional profiling on Earth [22, 23, 24]. However, analysing metagenomic datasets relies on dedicated tools as the data is inherently complex due to high species diversity and varying abundance profiles, and the choice of tools depends on the specific research goals [25]. There are two main approaches that follow different objectives when analysing metagenomic data: taxonomic classification and functional annotation [26].

Taxonomic classification categorizes genomic sequences to determine microbial composition, thus offering an overview of the taxonomic diversity [27]. Numerous tools have been developed, utilizing both read-based and assembly-based approaches. Read-based methods employ various strategies such as marker gene analysis, database alignment, or k-mer-based techniques [28, 27, 29, 30]. Assembly-based methods, which work with either assembled contigs or long reads, potentially

increase classification accuracy. These approaches rely on tailored data structures or alignment techniques to efficiently process large numbers of sequences [31, 32, 33, 34]. Notably, taxonomic classification has been widely applied to ancient metagenomes [35, 36, 37, 38, 39, 3], with specialized tools developed to address the unique challenges posed by degraded, short aDNA fragments [40, 41].

While functional annotation of sequences can be achieved by mapping reads to protein databases, assembly-based methods often provide more accurate and comprehensive results, particularly in metagenomic studies with many unknown or distantly related species [42]. *De novo* assembly is commonly used to uncover a wide range of elements, from protein-coding genes to entire genomes. This approach is especially advantageous for ancient samples, where modern references may fail to capture distantly related species. Moreover, short fragment lengths and characteristic aDNA damage patterns further complicate alignment-based methods [43].

Several studies have demonstrated the applicability of *de novo* assembly for searching aDNA samples for antibiotic-resistance genes or unknown metabolites, or for reconstructing whole genomes [44, 17, 45, 46, 47, 48, 49]. For instance, a study by Wan *et al.* [50] recently demonstrated the potential of mining proteomes from extinct species, termed the "extinctome", to identify novel antimicrobial genes. Considering that approximately 90% of prokaryotic genomes are protein-coding [51, 52, 53], *de novo* assembly of extinct species is the gateway for revealing unknown proteomes. While Klapper *et al.* [17] highlighted the fact that deeply sequenced datasets can be assembled using conventional assembly algorithms, the assembly process becomes more challenging when dealing with samples that exhibit high damage rates and low coverage.

To demonstrate the effects of varying fragment length and damage patterns, we simulated fragments of a simple metagenomic environment with different fragment sizes and deamination rates. As shown in Fig. **1(A)**, fragment length and damage drastically influence the outcome of ancient metagenome assembly. The damage patterns used for the simulations (Fig. **1(B)**) represent two levels of damage intensities as they can be found in studies profiling ancient microorganisms. Even at moderate damage levels with the first position of the $5'$ end exhibiting a damage rate of $\sim$35%, we observed a significant drop in assembly performance. Several studies have documented rates of nucleotide misincorporation at the $5'$ end, ranging from 15% to 60% [17, 36, 54, 55, 56, 3, 57]. Our findings highlight the need for optimized assembly algorithms to address the unique characteristics of ancient metagenomic datasets.

There are two major classes of *de novo* assembly algorithms: Overlap Layout Consensus (OLC) and de Bruijn graphs. OLC algorithms rely on the computation of full read overlaps, while de Bruijn graph algorithms construct contigs using sub-sequences of length k (k-mers) [60]. Although OLC algorithms are precise, they are computationally impractical for assembling large datasets produced by high-throughput sequencing technologies [61, 62]. Consequently, de Bruijn graph algorithms

Figure 1: **A)** Impact of aDNA damage and fragment length on metagenomic assembly. The plots show the sum of all contigs larger than 500bp after assembling a simulated toy dataset with either `MEGAHIT` [58] or `metaSPAdes` [59]. Each bar plot refers to a different combination of fragment length and damage rate of the simulated data. While empirical data is inherently more complex in terms of variation in fragment lengths and damage patterns, our simplified dataset demonstrates how common assemblers are limited by aDNA damage. **B)** Damage patterns used for the simulation of aDNA fragments. We used two levels of deamination rates for the simulations: moderate damage and mild damage compared to the rates found in ancient microbial studies [17, 36, 54, 55, 56, 3, 57]. The blue traces represent C-to-T substitution rates, while the red traces indicate G-to-A substitution rates.

have become the prevalent algorithmic basis for most assemblers developed in the past decade. De Bruijn graph assemblers connect k-mers that overlap by at least k-1 nucleotides in a graph structure, thereby efficiently assembling short reads into contigs [63, 64, 58]. However, de Bruijn graph assemblers face a precision-sensitivity trade-off when assembling complex metagenomic data. Longer k-mers provide higher specificity for individual species but suffer from reduced sensitivity in populations with high intra-species diversity. Conversely, shorter k-mers offer increased sensitivity but lack the specificity required to effectively distinguish between closely related species [65, 62]. Moreover, as k-mer length increases, sequencing errors are more likely to interfere with matching k-mers correctly, making read correction methods necessary to address this issue. Ancient metagenomic datasets, characterized by damaged and short fragments, amplify this issue by naturally increasing diversity and complexity and thereby stretching the limits of de Bruijn graph assemblers [6]. New assembly strategies are needed to overcome these issues.

The *de novo* metagenomic assembler `PenguiN` [62] uses a greedy-iterative overlap-based assembly method. Inspired by the protein level assembler `PLASS` [65], it clusters reads based on shared k-mers. Extension candidates are then selected from these clusters using a Bayesian model that leverages alignment length and sequence identity between the query and extension candidate in

both protein and nucleotide space. The extension process continues iteratively, first clustering, then extending. Clustering reduces the computational complexity of finding overlaps from quadratic in the number of reads to quasi-linear. This overlap-centric approach avoids the precision-sensitivity trade-off seen for de Bruijn graph assemblers, resulting in improved recovery from highly diverse metagenomic datasets [65, 62].

Here we introduce `CarpeDeam`, a *de novo* assembler specifically designed for ancient metagenomic data, based upon the greedy-iterative workflow of `PenguiN` [62]. It addresses the aforementioned challenge of high damage levels. Each iteration comprises three phases: First, sequences are clustered based on shared k-mers analogues to PenguiN. `CarpeDeam` additionally refines clusters by using a filter that employs a purine-pyrimidine encoding [66]. This encoding, which we refer to as RYmer space, ensures that cluster assignments of sequences are robust to aDNA damage events. In the second phase, sequences with base substitutions that are likely to be due to damage in the aDNA fragments are corrected. The final phase involves the elongation of contigs through an extension rule that takes into account aDNA-specific substitution patterns.

We introduce `CarpeDeam`, a novel assembler specifically designed for ancient metagenomic datasets. Our analysis highlights the challenges assemblers face when dealing with aDNA datasets, as performance varies greatly depending on fragment length distributions and damage patterns. `CarpeDeam` demonstrates superior performance in simulated datasets and in many empirical datasets, recovering unique genomic segments that are missed by other assemblers. `CarpeDeam` offers two modes: a default "safe" mode for reducing errors and an "unsafe" mode for increased sensitivity. These promising results mark an important step forward in damage-specific assembly; however, further advancements will be needed to fully address the complexities of ancient metagenomic datasets.

3   Results

Workflow of `CarpeDeam`

`CarpeDeam` is an assembler based on the metagenome assembler `PenguiN`. It employs a similar greedy, iterative overlap strategy, yet it incorporates several critical adjustments tailored for assembling ancient metagenomic data. Whereas `PenguiN` utilizes six-frame translated reads to find overlaps in amino acid space, we omit this step as ancient DNA fragments are ultrashort, resulting in even shorter amino acid sequences. In the text, we use the term aDNA fragments to describe the trimmed and merged sequencing reads (see discussion in Lien *et al.* [67]).

Overall `CarpeDeam` relies on three iteratively repeated steps: During **PHASE 1** (see Fig. **2**), sequences are clustered based on shared k-mers via the `MMseqs2 linclust` algorithm [68]. In this

process, each sequence within a cluster is required to align to the center sequence with a minimum sequence identity. The center sequence is defined as the longest sequence within the cluster and becomes the focus for subsequent correction or extension processes, depending on the stage. The remaining sequences in the cluster, termed member sequences, overlap with the center sequence and contribute to its damage correction. In the extension phases, they serve as extension candidates. While `PenguiN` applies a relatively high default sequence identity threshold (99%), the presence of deaminations in aDNA requires a reduction in this threshold as the sequence identity is naturally lower even for sequences of the same provenance. `CarpeDeam` filters clusters using a reduced sequence identity threshold of 90% while introducing the concept of RYmer sequence identity, which converts sequences to a reduced nucleotide alphabet of purines (adenine and guanine) and pyrimidines (cytosine and thymine) to account for deaminated bases. First, the clusters are generated with all member sequences sharing at least one k-mer with the center sequence and the sequence similarity of the full overlap is computed following `PenguiN`'s workflow. Additionally, we compute the sequence similarity in RYmer space, where an A or a G is encoded as R (one letter encoding for purine) and a C or T as Y (one letter encoding for pyrimidine), of the full overlap. For a detailed explanation of this concept, please refer to Section S7 of the Supplementary Material. Overall, the RYmer space sequence identity allows for mismatches due to deamination events.

In **PHASE 2** (see Fig. 2), `CarpeDeam` corrects deaminated bases. Any base in the center sequence of a cluster that is covered by at least one other sequence from the cluster can be corrected. Employing the user-provided damage patterns, the method utilizes a maximum-likelihood estimation to infer the most probable base for each position. The likelihood model is explained in more detail in Methods Section 6.

During **PHASE 3** (refer to Fig. 2), sequences are extended. `PenguiN` employs an extension rule based on a Bayesian model, which selects the most suitable extension for each cluster. In contrast, we split the extension process into two distinct phases. The initial phase exclusively targets non-extended sequences (i.e. aDNA fragments). The key aspect is that the damage pattern provided by the user is only valid for these sequences, enabling the application of our likelihood model. Consequently, the initial phase focuses on extending the center sequence using yet non-extended sequences. Within each iteration, the extension continues as long as our likelihood model supports a strong belief in the accuracy of the extension (see Methods Section 6). The subsequent phase involves merging contigs: sequences that have already been extended and corrected. For this, `CarpeDeam` applies `PenguiN`'s Bayesian model with adjustments to improve its applicability to ancient datasets (see Methods Section 6).

We assessed the performance of `CarpeDeam` by generating 18 simulated datasets derived from three distinct ancient environments: gut microbiome [44], dental calculus [35], and bone material [69]. For each environment, six datasets were created with varying levels of coverage and damage. Fur-

Figure 2: `CarpeDeam`'s main workflow: The input are aDNA sequences (FASTQ format) which have been trimmed and, for paired-end data, merged. During an iterative process, the fragments are corrected and extended to long contigs. In **PHASE 1** the fragments are grouped into clusters sharing at least one k-mer as well as an overlap sequence identity of 99% in RYmer space. **PHASE 2** corrects deaminated bases. In particular, the center sequence of each cluster (which is always the longest sequence) is assigned the most likely base per position given the evidence of overlapping sequences in the cluster and the user-provided damage patterns. In **PHASE 3**, the center sequence of each cluster is extended by the candidate sequence from the cluster that is most likely to be the correct extension. In fact, **PHASE 3** is divided into two steps. First, only aDNA fragments (non-extended sequences) are taken into account for extension, as the provided damage patterns are only valid for non-extended sequences. In the second step of **PHASE 3** exclusively contigs (sequences that already have been extended at least once) are used for the extension, applying a modified Bayesian extension model from the native `PenguiN` assembler.

181 thermore, we assembled and evaluated two empirical datasets, performing taxonomic classification

182 and protein similarity search on the contigs as evaluation criteria (see Methods Section 6 for further

details).

According to our findings, `MEGAHIT` [58] and `metaSPAdes` [59] are the metagenomic assemblers of choice and have been applied in published studies for *de novo* assembly of ancient metagenomic datasets [44, 17, 45, 46, 47, 48, 49]. To evaluate `CarpeDeam`'s efficacy, we conducted an extensive benchmark comparison against the state-of-the-art assemblers `MEGAHIT` and `metaSPAdes` as well as the novel assembler `PenguiN` [62].

Overall, during our analysis we found that `CarpeDeam` can produce an elevated number of misassemblies. To offer users more flexibility in managing this trade-off, we introduced two operational modes for `CarpeDeam`: safe and unsafe. The safe mode (set as default) additionally implements a consensus-calling approach during the extension phase to reduce misassemblies. Users can opt for the unsafe mode, which disables only the consensus calling mechanism, potentially increasing sensitivity at the cost of a higher rate of chimeric contigs. This dual-mode approach allows users to balance between assembly sensitivity and accuracy based on their specific research needs and dataset characteristics. A detailed description of the consensus approach can be found in section 6.

Simulated Data

Evaluation Strategy of Assembly Quality with `metaQUAST` and `Prokka`

We simulated 81 datasets of metagenomic paired-end Illumina short reads of three different environments by varying three parameters: average coverage depth (3X, 5X, and 10X), fragment length distributions (`medium`, `short`, and `ultra-short`), and DNA damage patterns (`moderate`, `high`, and `ultra-high`). The simulation procedure is described in Section 6. The taxonomic profiles of our simulated datasets were derived from three publications [69, 35, 44], representing varying levels of complexity in species diversity. For instance, the most complex dataset mirrors a gut microbiome consisting of 116 identified microbial species derived from Wibowo *et al.* [44], with individual species abundances ranging from a maximum of 10.77% to a minimum of 0.011%. At 10X average coverage, this results in the least abundant species having a coverage of only 0.15X. While all species had the same simulated rate of damage and fragmentation patterns, we also created non-uniform simulations where different species have different rates of damage and fragmentation patterns (see Supplementary Material, Section S4).

We assembled the simulated datasets with `CarpeDeam`, `PenguiN` [62], `MEGAHIT` [58] and `metaSPAdes` [59].

All assemblers were run with their default parameters, except for the minimum contig length, which was set to a minimum of 500bp. For `CarpeDeam` we ran both the *safe* and the *unsafe* mode.

We specified the flag `--only-assembler` for `metaSPAdes` because we observed the program getting stuck in the step that aims to correct sequencing errors. Skipping this step was advised in the issues section of the `metaSPAdes` GitHub repository (issue 306).

The reference genomes underlying our simulations were used to evaluate the assemblies of all four assemblers. We used the original references to compute the following alignment-based metrics: NA50, LA50, largest alignment, duplication ratio, misassemblies and mismatches per 100kb as generated by `metaQUAST` [70]. We set the sequence identity threshold at 90% for the `metaQUAST` [70] alignments as suggested in the `metaQUAST` documentation. Additionally, we mapped the aDNA fragments back to the contigs using `Bowtie2` [71] with `--very-sensitive-local` and reported the fraction of mapped fragments against the contigs via `SAMtools` [72].

Comparison of Assemblers Based on Standard Metrics Reported by `metaQUAST`

For our benchmark, we set the minimum contig length to 500 bp. Figure **3** presents four key metrics—largest alignment, number of misassemblies per contig, covered genome fraction, and NA50—for nine selected datasets: `moderate` damage and `short` fragment length at coverage depths of 3X, 5X, and 10X. Results for all 81 datasets are provided in Section S2 of the Supplementary Material.

`CarpeDeam`, in both its safe and unsafe modes, and `MEGAHIT` demonstrated strong performance across the presented assembly metrics. In contrast, `PenguiN` and `metaSPAdes` were less effective at assembling comparable fractions of the metagenomes.

A notable difference was observed in the "largest alignment" metric (Fig. **3**, row 1), where `CarpeDeam`'s unsafe mode consistently produced substantially longer contigs compared to other assemblers. This advantage was particularly evident in the calculus and gut datasets. For most datasets even `CarpeDeam`'s safe mode yielded larger maximum alignments than `MEGAHIT`, while not achieving ultra-long alignments as the unsafe mode did. Only for the 3X gut dataset, `MEGAHIT` had a larger alignment than both `CarpeDeam` modes. `PenguiN` and `metaSPAdes` both had significantly shorter maximum alignments.

As expected, the increased sensitivity of `CarpeDeam`'s unsafe mode came at the cost of a higher misassembly rate, as shown by the "misassemblies per contig" metric (Fig. **3**, row 2). For the 3X gut dataset `CarpeDeam`'s unsafe mode generated more than twice as many misassemblies per contig than `MEGAHIT`, for the 5X gut dataset four times as many per contig than `MEGAHIT` and for the 10X gut datasets six times as many per contig than `MEGAHIT`.

Although `CarpeDeam`'s safe mode exhibited an elevated misassembly rate compared to `MEGAHIT`, `PenguiN`, and `metaSPAdes`, the difference was less pronounced. The most notable difference was ob-

served in the 10X gut datasets, where the safe mode created about 2.5 times as many misassemblies per contig as `MEGAHIT`.

The fraction of recovered genomic content is shown in row 3 of Fig. **3** and `CarpeDeam` (both modes) score the highest in this category. Although the genome fraction recovered by `MEGAHIT` varied across datasets, it generally fell between the values obtained by `CarpeDeam`'s safe and unsafe modes. For the gut dataset the values of the recovered genomic fractions were for `CarpeDeam`'s safe mode, `CarpeDeam`'s unsafe mode and for `MEGAHIT` (in that order): 2.1%, 2.9% and 3.0% for the 3X dataset, 4.7%, 6.2% and 5.8% for the 5X dataset and 10.4%, 12.8% and 9.2% fot the 10X dataset. Both `metaSPAdes` and `PenguiN` recovered a substantially lower genome fraction.

Finally, the NA50 metric is presented in Fig. **3**, row 4. Generally, the N50 metric represents the length of the shortest contig such that half of the total assembled length is contained in contigs of this length or longer. While N50 is a commonly used metric to get a first impression of assembly quality, it does not distinguish between contigs that align with a reference genome and those that do not. The NA50 metric on the other hand considers only those contigs that have aligned to a reference genome. This adjustment helps to mitigate the influence of long chimeric or misassembled contigs that might artificially inflate the N50 value.

The top three performers in terms of NA50 values are `CarpeDeam` (in both safe and unsafe modes) and `MEGAHIT`. It is worth noting that `CarpeDeam`'s unsafe mode sometimes exhibits significantly higher NA50 values for certain datasets.

Table 1 presents additional metrics reported by `metaQUAST` [70] for evaluating the gut datasets with `moderate` damage and `short` fragment length distribution, representing the most complex of the three samples. Additional results for the dental calculus and bone datasets, which are progressively less complex, as well as other parameter combinations of fragment length distributions and damage patterns, are provided in the Supplementary File 1.

The table shown also includes the fraction of aDNA fragments mapped against the assembly. Across all three datasets, `CarpeDeam`'s unsafe mode consistently demonstrated a higher number of aDNA fragments mapping to its contigs than other assemblers. Notably, `MEGAHIT` performed very well for the 3X coverage gut dataset, with the highest values for both the "Genome fraction" and "Largest Alignment" metrics.

The metric "mismatches per 100kb" is also presented in Table 1. `MEGAHIT` consistently exhibited the lowest number of mismatches per 100kb across all coverage levels. Interestingly, `PenguiN` displayed the highest mismatch values, exceeding 1000 mismatches per 100kb for all three coverages (3X, 5X, and 10X). This observation aligns with the fact that `PenguiN` does not perform base correction, as it was designed for modern viral metagenomes. In contrast, the de Bruijn graph

Figure 3: Performance evaluation of assemblers `CarpeDeam` (safe and unsafe modes), `MEGAHIT`, `metaSPAdes`, and `PenguiN` across nine simulated datasets. Results are presented for datasets with category `moderate` damage and `short` fragment length distribution, simulated for three environments (gut, dental calculus, and bone) and three coverage levels (3X, 5X, and 10X). The metrics shown are largest alignment (row 1), misassemblies per contig (row 2), genome fraction (row 3), and NA50 (row 4). Each bar represents the performance of an assembler for a specific metric, coverage, and environment.

assemblers `MEGAHIT` and `metaSPAdes` employ bubble merging algorithms to resolve bases in cases where multiple possibilities exist.

Despite `CarpeDeam` recovering significantly more than `PenguiN`, the higher mismatch rate per 100kb in `CarpeDeam` is indicative of its damage correction process, which is based on `PenguiN`. `CarpeDeam`'s safe mode shows a lower mismatch rate per 100kb than its unsafe mode, yet is higher than `MEGAHIT`. For instance, for the 5x gut dataset in Table 1, the mismatch rates are 449 mm.p 100kb (`CarpeDeam` safe), 613 mm.p 100kb (`CarpeDeam` unsafe), 159 mm.p 100kb (`MEGAHIT`), 1147 mm.p 100kb (`PenguiN`), 379 mm.p.100kb (`metaSPAdes`). As indicated in Table 1, `CarpeDeam` exhibits a higher duplication rate. This impacts the mismatch rate per 100 kbp because the number of mismatches computed by `metaQUAST` is proportional to the duplication ratio. Consequently, mismatch rates can be elevated when there are numerous overlapping alignments, as each assembly alignment is analysed independently. Additionally, the higher misassembly rate contributes to the mismatch rate. For instance, a misassembled contig aligning to the reference can accumulate mismatches at the ends of the aligned region due to chimeric nature of the contig. Since `metaQUAST` tolerates a certain degree of sequence divergence, these mismatches are included in the calculation, further elevating the mismatch rate.

The tables reveal a general trend where `CarpeDeam` demonstrates higher sensitivity, producing a larger number of contigs. This is indicated by its elevated duplication ratio and higher mapped fraction, while achieving a genome fraction similar to `MEGAHIT`. Our observations align with the findings presented in the `PenguiN` [62] manuscript: `PenguiN`'s approach recovers more strain-resolved viral genomes, while generally exhibiting a higher duplication rate. In contrast, `MEGAHIT` appears to prioritize precision, generating fewer contigs with a lower rate of misassemblies, resulting in capturing less of the genomic diversity present in the sample.

We show NA50 and LA50 in Table 1 as they can be viewed as more informative as their "non-aligned" counterparts N50 and L50. A higher NA50 is considered better as it describes the minimum alignment length to be considered, covering half of the alignment length of all contigs. For LA50, however, a lower value is considered better, as it describes the number of aligned blocks that need to be considered to cover half of the alignment length of all contigs. It must be noted that these metrics need to be evaluated in the context of the covered genome fraction. For instance, while `PenguiN` and `metaSPAdes` both have small LA50 values, the tools recovered a much smaller genome fraction than `CarpeDeam` and `MEGAHIT`.

Table 1: Assembly evaluation metrics for the simulated gut metagenomic environment with **moderate** damage and **short** fragment length distribution.

Assembler	Cov.	Genome Fraction (%)	Largest Alignment	Reads Mapped Fraction	NA50	LA50	Misassemblies per contig	# Mismatches per 100kb	Duplication Ratio	Total Length (bp)	Total Len. > 1000bp
CarpeDeam (safe mode)	3X	2.101	6,223	0.227	801	4,004	0.011	395.290	1.095	9,796,467	3,402,822
CarpeDeam (safe mode)	5X	4.658	12,431	0.395	905	7,270	0.013	389.740	1.132	22,446,367	10,049,155
CarpeDeam (safe mode)	10X	10.390	37,369	0.627	1,163	12,068	0.017	399.340	1.202	53,148,016	30,956,547
CarpeDeam (unsafe mode)	3X	2.919	13,325	0.314	1,043	3,799	0.022	512.640	1.116	13,875,108	7,349,327
CarpeDeam (unsafe mode)	5X	6.188	42,402	0.508	1,302	5,061	0.029	504.740	1.180	31,087,499	18,945,119
CarpeDeam (unsafe mode)	10X	12.763	136,564	0.762	2,464	5,468	0.052	518.150	1.395	75,781,097	58,813,418
MEGAHIT	3X	3.025	13,419	0.246	934	4,037	0.009	158.760	1.008	12,938,041	5,982,557
MEGAHIT	5X	5.757	8,461	0.317	903	8,831	0.010	160.800	1.008	24,629,258	10,713,343
MEGAHIT	10X	9.168	12,385	0.313	966	12,524	0.008	153.460	1.009	39,242,566	18,863,238
metaSPAdes	3X	0.110	981	0.007	554	373	0.016	481.170	1.001	469,988	0
metaSPAdes	5X	0.211	1,806	0.015	574	645	0.006	377.930	1.003	902,081	38,373
metaSPAdes	10X	0.592	4,064	0.049	629	1,463	0.002	328.500	1.012	2,550,384	417,629
PenguiN	3X	0.021	838	0.002	549	78	0.018	979.500	1.045	93,626	0
PenguiN	5X	0.049	886	0.005	563	172	0.000	1037.790	1.054	218,456	0
PenguiN	10X	0.151	1,038	0.014	555	577	0.006	1182.980	1.122	721,791	1,043

Impact of Fragment Length Distributions and Damage Levels on Assembly Performance

Our simulation of three different samples, with varying coverages, fragment lengths, and damage profiles, resulted in a total of 81 datasets. The results of these assemblies are presented in the Supplementary Material, Section S2, as extended heatmaps for various metrics reported by metaQUAST [70].

There were several key observations. Fragment length distributions had a notable impact on the assembly performance. The distributions are shown in the Supplementary Material, Fig. S1 (A). Assemblies derived from the `medium` fragment length distribution (median 58 bp) generally outperformed those from the `short` (median 47 bp) and `ultra-short` (median 42 bp) distribution (Supplementary Material, Fig. S2 - S13). Interestingly, datasets with `ultra-short` fragments often recovered a slightly higher genome fraction than those with `short` fragments, despite the latter distribution having a longer median fragment length. This trend is particularly evident for assemblers such as `CarpeDeam`, `PenguiN`, and `metaSPAdes`, while it is less pronounced for `MEGAHIT`. The distributions differ in their maximum fragment lengths, with the `ultra-short` distribution reaching up to 140 bp and the `short` distribution reaching only 120 bp. These rare longer fragments likely have a disproportionate influence on assembly performance.

Damage profiles also played a critical role in assembly outcomes. Counterintuitively, the parameter combination of `ultra-high` damage and `medium` fragment lengths yielded the highest genome fractions in many cases. This contrasts with the `moderate` damage datasets, which consistently performed worse. A closer examination of the damage profiles revealed that the slope of the substitution rates across positions is a significant factor. While `moderate` damage had the lowest substitution rate at position 1 of the simulated fragments, it maintained relatively high rates at position 5, suggesting that a steeper decline in substitution rates positively influences assembly performance.

Evaluation of Non-Misassembled Contigs Across Assemblers

To further evaluate the quality of assemblies beyond the genome fraction metric, we assessed the ability of each assembler to reconstruct long, non-misassembled contigs as classified by metaQUAST. While genome fraction provides valuable information, it does not account for the length of individual contigs mapping back to the reference genome (by default metaQUAST considers all alignments over 65bp). Consequently, a high number of short contigs may inflate the genome fraction without necessarily representing superior assembly quality. To address this limitation, we analysed the number of non-misassembled contigs exceeding 2000 bp for each assembler across the datasets with `short` fragment length and `moderate` damage.

We demonstrate CarpeDeam's capacity to generate longer accurate contigs across datasets, shown in Supplementary Material, Fig. S18. CarpeDeam (unsafe mode) consistently produced more long contigs for all datasets except one (3X coverage bone dataset, where MEGAHIT outperformed both CarpeDeam modes). CarpeDeam's safe mode and MEGAHIT exhibited alternating performance, with CarpeDeam producing more longer non-misassembled contigs in four cases and MEGAHIT in four cases. Notably, PenguiN and metaSPAdes generated significantly fewer long contigs compared to other assemblers. Although CarpeDeam produced a higher number of misassemblies, which would require careful filtering in downstream analyses, the increased quantity of non-misassembled contigs over 2000 bp suggests a notable improvement in assembly contiguity.

Comparison of Non-Coding Genomic Content Across Assemblers

To complement our metaQUAST alignment analysis, we performed an additional examination of the assembly fractions (Fig. 4). We used skani [73], a tool for calculating average nucleotide identity (ANI) and aligned fraction (AF), employing an approximate mapping method without base-level alignment. Contigs shorter than 1000bp were excluded to focus on long genomic segments.

We categorized the mapping results into groups to provide a detailed evaluation of the assembly quality and its ability to handle redundancy and variation. The category *unmapped_nondup_bp* includes non-redundant nucleotides in the assemblies that do not map to the reference with an average nucleotide identity (ANI) of over 99%. These sequences represent unique content that was not successfully aligned to the reference. In contrast, *unmapped_dup_bp* comprises nucleotides in the assemblies that also do not map to the reference but include redundant sequences, reflecting over-represented regions introduced by the assembler.

For mapped base pairs, *mapped_dup_var_bp* consists of duplicates that are highly similar to reference sequences (ANI > 99%) but show minor variations, such as mutations present in some species but absent in others. This category highlights the assembly's ability to capture genetic diversity. Meanwhile, *mapped_dup_red_bp* represents redundant mapped base pairs that are likely a result of assembling more than one contig for the same genomic region, indicating redundancy in the assembly process.

The category *mapped_dup_red_rep_bp* quantifies the subset of redundant mapped base pairs required to create a representative set. By comparing this to *mapped_dup_red_bp*, one can infer metrics similar to the "duplication ratio" reported by metaQUAST, highlighting how redundant base pairs captured by *mapped_dup_red_bp* are distributed. This subset, defined by *mapped_dup_red_rep_bp*, represents the unique base pairs within the redundant regions.

Finally, *mapped_nondup_bp* captures the non-redundant mapped base pairs, excluding the dupli-

cates. This category indicates how much of the reference is covered by base pairs that map with high ANI and are unique, making them especially valuable for downstream analyses.

Overall, we conducted this mapping strategy to provide a more detailed evaluation of the nucleotide fractions in the assembled contigs that can be mapped to the reference. Unlike `metaQUAST`'s Genome Fraction metric, which applies a minimum alignment length and a fixed sequence similarity threshold, `skani` offers a more flexible approach to assessing mappings.

Our six categories capture detailed differences in the assemblies, including their ability to manage redundancy, capture genetic variation (e.g., within highly similar genetic regions), and evaluate completeness in terms of reference coverage. These results help users evaluate CarpeDeams' suitability for their specific research needs. For instance, while higher redundancy may complicate downstream analyses like binning, it poses less of a concern when focusing on specific gene regions, where sensitivity is of greater interest.

Fig. 4, panel A, presents the results for the gut dataset across 10X, 5X, and 3X coverage levels. Our analysis revealed that `CarpeDeam` (unsafe mode) exhibited the highest $mapped\_non\_dup\_bp$ fraction, particularly in the 10X coverage dataset. This advantage decreased at lower coverages (5X and 3X), with the difference between `CarpeDeam` and `MEGAHIT` diminishing. Substantial fractions of $unmapped\_non\_dup\_bp$ sequences were observed across assemblies, most notably in `CarpeDeam` (safe and unsafe) and `MEGAHIT`. `PenguiN` and `metaSPAdes` showed significantly lower fractions across all mapping categories compared to other assemblers.

We further investigated the types of genomic features other than coding regions recovered by different assemblers (Fig. 4, panel B). For this analysis, we used `Prokka`'s annotation output. Our results showed that `CarpeDeam` demonstrated a strong ability to recover rRNA, tRNA and repeat region segments while `MEGAHIT` assembled significantly less base pairs that could be classified by `Prokka`. It should be noted that only the results for `MEGAHIT` and `CarpeDeam` (safe and unsafe) are presented here, as other assemblers recovered substantially less genomic content overall, making their inclusion in the plot impractical for comparative purposes. The results refer to the gut dataset with `moderate` damage and the `short` fragment length distribution.

Fig. 4, panel C, illustrates the recovery of rRNAs and tRNAs with sequence identities above and below 98%. For tRNAs in the 3X gut dataset, `CarpeDeam` (safe mode) and `MEGAHIT` reconstructed comparable numbers of high-identity ($ge98\%$) sequences, while `CarpeDeam` (unsafe) outperformed both, reconstructing more than three times as many. This difference became more pronounced in the 5X and 10X datasets, where both `CarpeDeam` modes assembled significantly more high-identity tRNAs than `MEGAHIT`. For rRNA reconstruction we could observe a distinct pattern: `MEGAHIT` recovered very few, whereas both `CarpeDeam` modes recovered several rRNAs. For instance, for the 10X gut dataset, `CarpeDeam`'s unsafe mode could recover more than 200 rRNAs of which

Figure 4: Analysis of mapped fractions of base pairs, genomic features, and RNA recovery across different assemblers and coverage levels for the gut dataset. (A) Distribution of mapping categories (mapped non-duplicated, mapped duplicated variant, mapped duplicated redundant representative, mapped duplicated redundant, unmapped non-duplicated, and unmapped duplicated base pairs) for assemblies of the gut dataset at 10X, 5X, and 3X coverage levels. (B) Types of genomic features recovered in contigs based on Prokka annotations, for different assemblers (gut dataset). (C) Recovery of rRNAs and tRNAs with sequence identities above and below 98% for `MEGAHIT` and `CarpeDeam` (safe and unsafe modes) across different coverage levels (gut dataset; `moderate` damage, `short` fragment length distribution).

more than 100 had a sequence identity of 98%. Notably, `CarpeDeam` (safe mode) recovered fewer rRNAs overall, but those recovered predominantly exhibited ≥98% sequence identity. Conversely, `CarpeDeam` (unsafe mode) recovered a larger quantity of rRNA, albeit with a considerable fraction (<50%) showing <98% sequence identity. Interestingly, some RNA sequences annotated by `Prokka` in the assemblies failed to match the reference annotation. While `CarpeDeam` (safe) and `MEGAHIT` exhibited similarly low rates of these "no hit" instances, `CarpeDeam` (unsafe) demonstrated the highest occurrence of unmatched annotations.

Evaluation of Recovered Protein Content in Assembled Contigs

Effectively reconstructing protein-coding sequences is essential for creating detailed microbial gene catalogs. These catalogs organize genes found in microbial communities and serve as references for standardized analysis across different samples and studies, making the accurate reconstruction of protein-coding sequences a crucial aspect of our evaluation [74]. Therefore, we assessed the performance of the assemblers in reconstructing proteins by predicting proteins from the reference genomes of our simulated metagenomes with `short` fragment length distribution and `moderate` damage using `Prokka` [75] and searching for highly similar proteins with `MMseqs2 map` [76].

Fig. 5 shows the number of predicted open reading frames (ORFs i.e. DNA translated into amino acid space) that exhibit significant similarity to predicted proteins from the reference genomes.

We reported the number of unique matches in the reference. This approach allowed us to measure the assemblers' ability to reconstruct biologically meaningful protein-coding sequences.

CarpeDeam's unsafe mode consistently outperformed other assemblers in assembling more proteins (Fig. 5, panel (A)). However, for the 3X bone dataset, MEGAHIT assembled more proteins than CarpeDeam's unsafe mode. Apart from the 3X bone dataset, MEGAHIT assembled significantly more proteins than CarpeDeam's safe mode for the bone 5X and gut 3X datasets. In contrast, CarpeDeam's safe mode assembled significantly more proteins for all 10X datasets, as well as the 3X and 5X calculus datasets. For the gut 5X dataset, MEGAHIT and CarpeDeam's safe mode assembled a very similar number of proteins. The other assemblers assembled significantly fewer proteins across all datasets.

Figure 5: Evaluation of predicted protein sequences. Results are presented for CarpeDeam (safe and unsafe modes), MEGAHIT, metaSPAdes, and PenguiN across datasets with moderate damage and short fragment lengths in three simulated environments (Bone, Dental Calculus, and Gut) with varying coverage levels (3X, 5X, and 10X). The figure shows the number of predicted ORFs with significant similarity to reference proteins, filtered for alignments covering ≥90% of the reference protein and ≥90% sequence similarity.

As Table 1 of the metaQUAST results indicates that CarpeDeam tends to assemble a higher rate of duplicated contigs compared to other assemblers. Therefore, we conducted additional analysis to

assess the impact of duplications on downstream processes. Of particular interest was the potential inflation of unique protein sequence counts in our protein analysis due to duplicated sequences. To address this concern, we performed three additional analyses that account for duplication rates.

First, we clustered predicted proteins with the `linclust` [68] algorithm at 100% sequence identity and 80% coverage, then searched the cluster representatives against the predicted proteins from the reference using the `MMseqs2 map` [76] module.

Second, to account for potential duplicates in the reference itself, we clustered the predicted proteins from the reference at 100% sequence identity and 80% coverage. We then searched these clustered reference proteins against the predicted proteins from the contigs using `MMseqs2 map`.

Finally, we employed `miniprot` [77] to search the predicted proteins from the reference directly against the DNA contigs. This method bypasses potential undercalling by our protein predictor and focuses on protein-to-DNA alignments directly, providing a complementary perspective to the second analysis. We applied a filter to only obtain hits with at least 95% sequence identity and 95% coverage of the reference proteins. In all cases we reported the number of unique proteins from the reference.

Overall, these additional analyses still favor `CarpeDeam`, although `MEGAHIT` recovers similar numbers of proteins especially in the 3X datasets. The detailed results of these analyses are visualized in the Supplementary Material, Section S3.

Assembly of Empirical Datasets

Next, we extended our analysis to include 20 empirical metagenomic datasets from five distinct sample sites. These datasets were obtained from a study by Fellows Yates *et al.* [36] and represent ancient metagenomic samples from oral microbiomes of Neanderthals and Homo sapiens. The datasets exhibit varying levels of damage, which we used as input for the damage pattern parameter of `CarpeDeam`. Detailed information about these samples is summarized in Table 2. For the damage pattern input parameter of `CarpeDeam`, we used the average damage rate across all taxonomies reported.

Identification of Homologous Proteins in Empirical Datasets

Given the absence of ancient reference genomes for the empirical datasets, our evaluation focused on the proteome space. In the context of ancient prokaryotic samples, the ideal scenario would be to identify ancient proteins that exhibit strong similarity to existing sequences while remaining previously undiscovered. To maximize the detection of similar proteins from our assembled contigs, we employed a sensitive screening approach. We used the `--easy-search` module of `MMseqs2` [76]

Dataset	Microbiome Origin	Period	# Reads (merged)	Length	N50	GC(%)
TAF008.B0101	Modern Human	LSA	8,929,849	35-141	53	56.17
TAF016.B0101	Modern Human	LSA	1,631,218	35-141	97	63.35
TAF017.A0101	Modern Human	LSA	1,879,275	35-141	82	56.46
TAF017.C0101	Modern Human	LSA	1,981,178	35-141	47	51.25
TAF017.C0101.171215	Modern Human	LSA	1,970,380	35-141	47	51.12
TAF018.A0101	Modern Human	LSA	5,361,000	35-141	84	63.17
TAF018.B0101	Modern Human	LSA	5,327,186	35-141	57	52.6
EMN001.A0101	Modern Human	UP	9,911,123	35-141	69	55.41
ECO002.B0101	Modern Human	Meso	9,173,902	35-141	48	49.44
ECO002.C0101	Modern Human	Meso	8,841,304	35-141	48	49.71
ECO004.B0101	Modern Human	Meso	7,748,024	35-141	52	50.08
ECO004.C0101	Modern Human	Meso	6,965,132	35-141	50	52.55
ECO006.B0101	Modern Human	Meso	7,533,408	35-141	64	61.37
ECO010.B0101	Modern Human	Meso	8,903,259	35-141	48	49.89
OAK001.A0101	Modern Human	LSA	6,252,614	35-141	48	57.32
OAK003.A0101	Modern Human	LSA	13,951,366	35-141	61	53.48
OAK004.A0101	Modern Human	LSA	10,976,392	35-141	53	54.21
OAK005.A0101	Modern Human	LSA	13,749,370	35-141	59	56.99
GDN001.A0101	Neanderthal	MP	13,440,839	35-141	65	58.58
GDN001.B0101	Neanderthal	MP	11,972,554	35-141	52	57.12

Table 2: aDNA fragments statistics and sample metadata for the empirical ancient oral microbiome datasets from Fellows Yates *et al.* [36]. LSA = Later Stone Age, UP = Upper aleolithic, Meso = Mesolithic, MP = Middle Paleolithic. Library Prep indicates whether the sequencing data was paired-end. The table includes the total number of merged reads, minimum and maximum aDNA read lengths, N50, and GC content.

with `--search-type 4`, which extracts all possible open reading frames (ORFs) from the contigs and searches the resulting amino acid sequences against a provided database. For this analysis, we queried the UniRef100 database [78], which encompasses over 400 million reference protein sequences.

The search results were subsequently filtered using stringent criteria: sequence identity ($\geq 35\%$), E-value ($\leq$E-12), and alignment length (≥ 100 residues). Figure 6, panel (A), presents the number of unique hits in the UniRef100 database, considering only the best hit for each query based on the lowest E-value. This approach allows to assess the potential unknown protein content in our aDNA assemblies while maintaining only highly significant matches.

Figure 6, panel (A), shows the number of unique protein hits per sample and assembler in a heatmap. The performance of assemblers varies considerably across samples. Overall, `MEGAHIT` and `CarpeDeam` generally performed best, with `MEGAHIT` clearly outperforming all other assemblers in the ECO and TAF samples. In contrast, `CarpeDeam` achieved the best results in the GDN, EMN and OAK samples.

Interestingly, although `metaSPAdes` did not perform as well as `MEGAHIT` in previous analyses, it assembled more unique protein hits in the EMN dataset. When comparing the safe and unsafe modes of `CarpeDeam`, the safe mode yielded more hits in most datasets, indicating the presence of

494 frameshifts likely caused by misassemblies in the unsafe mode.

Figure 6: **(A)** Heatmap of unique UniRef100 protein hits for ORFs predicted from contigs assembled by `CarpeDeam`, `MEGAHIT`, `PenguiN`, and `metaSPAdes` across empirical samples (Grouped by sample site). Hits were were filtered by E-value $\leq e^{-12}$, $\geq 35\%$ identity, alignment length ≥ 100 residues. **(B)** Venn diagrams of species-level taxonomic assignments from translated contigs queried against the Genome Taxonomy Database for the Datasets GDN001.A0101 and EMN001.A0101.**(C)** Recovered genome fraction for highly damaged taxa, as reported by `metaQUAST`.

Exploring Taxonomy Assignment through Contig Translation into Protein Space

Another use case for assembled contigs is taxonomic classification. This approach offers several advantages over classifying individual short reads, especially in the context of aDNA analysis. Contig-based classification improves accuracy by leveraging longer sequences, which is particularly beneficial for ultra-short, degraded aDNA fragments. It also helps mitigate misclassifications caused by conserved regions or horizontal gene transfer events [32, 79, 34].

Considering these advantages, we assessed the performance of assemblers in recovering proteins informative for taxonomic assignment using two empirical datasets: EMN001.A0101 and GDN001.A0101. Open reading frames (ORFs) were extracted directly from the assembled contigs using the `--easy-taxonomy` module of `MMseqs2` [34], which translates the contigs in all six reading frames and queries them against the Genome Taxonomy Database (GTDB) [80]. For a detailed description of the workflow, see Section 6.

It is important to note that this approach primarily focuses on detecting bacteria closely related to modern species, specifically those represented in the GTDB, which is derived from RefSeq and GenBank genomes. Consequently, this method may not necessarily identify completely unknown species. The discovery of novel species presents significant challenges, as potential misassemblies would require careful downstream analysis to ensure accurate identification and exclusion of misassembled sequences.

Given these considerations, we adopted a conservative approach with stringent criteria for taxonomic assignment. Matches were filtered to meet the following thresholds: a minimum of 95% sequence identity in amino acid space, at least 70% target protein coverage, and an E-value ($\leq$E-6). This conservative strategy aims to minimize false positives while maintaining high confidence in the reported taxonomic assignments.

We quantified the number of distinct species identified by each assembler based on the proteome alignment (Fig. 6, Panel (**B**)). This metric provides a comparative measure of the assemblers' performance in recovering taxonomically informative sequences from our empirical aDNA samples.

Figure 6, Panel (**B**), row 1 presents the taxonomic assignment results for the GDN001 dataset. A substantial number of species were identified by all assemblers, with `MEGAHIT` and `CarpeDeam` (unsafe mode) sharing the largest common set. Notably, both `MEGAHIT` and `CarpeDeam` identified a considerable number of unique taxa, with `MEGAHIT` slightly outperforming `CarpeDeam` (234 vs. 218 unique taxa, respectively; first Venn diagram).

Row 2 of Panel (**A**) displays results for the EMN001.A0101 dataset, revealing a similar pattern to GDN001.A0101. However, consistent with its lower damage rate, the assemblies of the EMN001.A0101 dataset yielded identifications for a larger number of taxa overall. `CarpeDeam`

demonstrated a marginal advantage in unique taxa identification compared to `MEGAHIT` (605 vs. 529, respectively; third Venn diagram).

A key observation from this analysis is that no single assembler consistently outperforms the others. While the different algorithms naturally share a significant portion of their results, each assembler reveals unique findings.

To further evaluate the assemblers' performance on highly damaged taxa, we focused on four species reported by Fellows Yates *et al.* [36] to exhibit damage patterns of up to 40% that were identified in both samples: *Fretibacterium fastidiosum*, *Fusobacterium nucleatum*, *Tannerella forsythia*, and *Treponema denticola*. We used the reference genomes of these taxa as input for `metaQUAST` [70] and reported the recovered genome fraction using a contig length cutoff of 500 bp.

The analysis of the GDN001.A0101 dataset revealed that `CarpeDeam` was the only assembler capable of recovering any fraction of a reference genome. While no assembler successfully recovered sequences from *F. fastidiosum*, *T. denticola* or *T. forsythia*, `CarpeDeam` in unsafe mode recovered approximately 0.07% of the *F. nucleatum* genome, whereas safe mode recovered around 0.025%.

In the EMN001.A0101 dataset, most assemblers recovered only small fractions of the reference genomes. Notably, `MEGAHIT` failed to assemble any contigs longer than 500 bp that mapped to either *F. nucleatum* or *T. forsythia*. Among the assemblers, `CarpeDeam` performed best, recovering the largest fractions for all four target species. Interestingly, the safe and unsafe modes of `CarpeDeam` showed similar performance, yielding comparable fractions of the reference genomes.

Table 3 shows the relative abundances of four species presented in Fig. 6, panel (C), derived using `MetaPhlan2` [81]. The abundances are generally very low (<1%) and differ between the datasets. In GDN001.A0101, *T. forsythia* is absent, while other species have abundances below 0.12%. Notably, only *F. nucleatum* had a small genome fraction assembled by `CarpeDeam`. In contrast, EMN001.A0101 shows higher abundances for *F. nucleatum* and *F. fastidiosum* ($\approx$0.25%), correlating slightly better with the genome fractions recovered.

Overall, no clear proportional relationship is observed between relative abundance and genome recovery, likely due to the low abundances and approximative nature of the tools. Since the contigs were filtered to have a minimum length of 500 bp, this could also contribute to the lack of correlation.

Species Abundance in %	GDN001.A0101	EMN001.A0101
Fretibacterium fastidiosum	0.11313	0.24148
Fusobacterium nucleatum	0.03592	0.26263
Tannerella forsythia	0	0.02834
Treponema denticola	0.10765	0.02202

Table 3: Relative abundances of bacterial species in the two samples as reported by `Metaphlan2`, found in the data repository of the study by Fellows Yates *et al.* [36].

Detection of rRNA Genes and Potential Biosynthetic Gene Clusters

16S rRNA gene detection is widely used for phylogenetic analysis in metagenomic studies due to the conserved regions of the gene [82]. However, in aDNA studies, detection of the full-length (approximately 1500 bp [82]) 16S rRNA gene is challenging because of the short fragment lengths and characteristic damage patterns inherent to aDNA. Previous studies have targeted several of the nine hypervariable V1–V9 regions [83, 84, 85, 86, 87, 88], which are considerably shorter, thereby requiring the reconstruction of only a few hundred base pairs rather than the full ∼1500 bp gene. Nevertheless, Ziesemer *et al.* [89] demonstrated that targeting specific hypervariable segments in aDNA studies remains challenging when using amplicon sequencing; in such cases, *de novo* assembly can significantly improve the recovery of either full genes or hypervariable regions.

We investigated the detection of 16S rRNA genes by assessing the number of unique hits detected across sequence identity thresholds ranging from 90% to 100%. To ensure robust capture of hypervariable regions, we required that the annotated contigs span at least 80% of a 16S rRNA gene. In Fig. 7, Panel (**A**), we present the number of unique hits across different sequence identity thresholds rather than relying on a single cutoff.

Figure 7: (**A**) Detection of 16s rRNA genes. Shown are the numbers of unique hits in the SILVA database from assembled contigs that were annotated with `Prokka` and filtered by sequence identity thresholds (90% to 100%) and a minimum coverage of 80%. (**B**) Identification of BGC protoclusters in the OAK003 sample using `antiSMASH`.

For the GDN001.A0101 dataset, all assemblers performed similarly; however, `CarpeDeam` in both

modes recovered more 16S rRNA hits (<200) compared to other assemblers (<150) at the 90% similarity threshold. The number of hits converged with increasing sequence identity, and no assembler reconstructed 16S rRNA genes with sequence similarity above 95%. At 95%, metaSPAdes recovered the most hits (11), followed by CarpeDeam and MEGAHIT.

In contrast, the EMN001.A0101 dataset showed a significantly different result. Only CarpeDeam assembled 16S rRNA genes, with the unsafe mode recovering over 2500 hits and the safe mode over 1500 hits at the 90% similarity threshold. At 95% similarity, both modes of CarpeDeam converged, still recovering over 600 unique hits.

For a deeper investigation of the 16S rRNA genes in the EMN001.A0101 dataset, we examined contigs that aligned to the SILVA database covering at least 99% of a full-length 16S rRNA gene with a minimum sequence identity of 95% (a threshold commonly used for genus-level identification [90, 91, 92]). CarpeDeam was the only assembler that produced contigs meeting these criteria. We then assigned taxonomic labels to the recovered 16S rRNA genes and compared these with the genera reported by Fellows Yates *et al.*, where they were using a read alignment approach. To rule out contamination, we also compared the detected genera against a catalogue of potential contaminants provided by Fellows Yates *et al.*. Additionally, we mapped the reads back to the genes to validate their ancient authenticity (PyDamage[93] results in the external data repository). Notably, CarpeDeam recovered three genera on species level (*Actinobacteria*, *Brachymonas*, and *Johnsonella*, shown in bold in Table 4) that were absent in the Fellows Yates *et al.* study and not listed as contaminants. In total, we identified five taxa on species level (sequence similarity ≥99% [94]) and five taxa on genus level (sequence similarity ≥95% [90, 91, 92]). Overall, this analysis underscores the enhanced sensitivity of CarpeDeam and demonstrates its suitability as a complementary method for taxonomic identification alongside read mapping approaches. The result is also remarkable given the low sequencing depth, as the EMN001.A0101 dataset comprised fewer than 10 million merged reads.

Additionally, we evaluated the assemblers' ability to reconstruct contigs containing biosynthetic gene clusters (BGCs). Fig. 6 (panel **A**) indicates that the OAK samples are the most protein-rich. Accordingly, we selected the OAK003 sample for further analysis. Using antiSMASH [95], we screened the contigs from each assembler for BGCs and reported the number of protoclusters per BGC type. A protocluster is defined as a genomic region that contains the core biosynthetic genes for a specific secondary metabolite along with its neighbouring genes. Based on curated detection rules, each protocluster corresponds to a single product type [96].

Fig. 7 (panel **B**) shows that antiSMASH identified 11 distinct protocluster types across all assemblers. Both CarpeDeam modes contain the highest number of protoclusters, with 62 identified in safe mode and 52 in unsafe mode. MEGAHIT contains 25 protoclusters, PenguiN contains 10, and

Species Level Identification	Sequence Similarity	16S rRNA Gene Coverage
Brachymonas sp. canine oral taxon 015	**0.988**	**1.0**
Johnsonella ignava ATCC 51276	**0.998**	**1.0**
Propionibacterium sp. oral taxon 192 str. F0372	**0.998**	**1.0**
Desulfobulbus oralis	0.998	0.996
Streptococcus sanguinis SK150	0.994	0.997
Genus Level Identification		
Actinobacteria bacterium canine oral taxon 406	0.983	1.0
Aggregatibacter aphrophilus	0.987	1.0
Chlorobium sp. ShCl03	0.966	0.999
Actinomyces slackii	0.960	0.998
Pseudopropionibacterium massiliense	0.952	0.999

Table 4: Best hit alignments of assembled contigs to the SILVA 16S rRNA gene database for the EMN001.A0101 dataset. Bold entries denote three species that were not detected by Fellows Yates *et al.* using the MALT approach. The values for sequence similarity and gene coverage correspond to the highest scoring alignment for each genus.

metaSPAdes contains 8. The distribution of protocluster types varied among assemblers. For example, MEGAHIT did not detect any *RRE-containing*, *lassopeptide*, or *terpene* protoclusters, which were present in the CarpeDeam assemblies.

Another notable difference was observed in the total number of aligned nucleotides. We searched the protein sequences reported by antiSMASH against the nr database and summed the alignment lengths of the best hits, determined by the lowest E-value. The safe mode of CarpeDeam assembled sequences with more than twice the total aligned length (in base pairs) compared to MEGAHIT. When aligning the BGC protocluster sequences against the nr database, the best hits had a median sequence similarity exceeding 92% for CarpeDeam, MEGAHIT, and metaSPAdes, while PenguiN showed a lower median similarity of over 83%. To ensure ancient authenticity, we mapped the OAK003 reads against the BGC-involved contigs, all of which exhibited characteristic nucleotide substitutions at the fragment ends (see PyDamage[93] results in the external data repository).

4   Discussion

Evaluating Assembly Algorithms: Understanding Strengths, Limitations, and Underlying Assumptions

The reconstruction of full-length genes or entire genomes from ancient metagenomes poses significant challenges for *de novo* assemblers. *De novo* assembly of metagenomic samples is already complex for modern samples and it becomes exceptionally challenging with aDNA due to its degraded nature, characterized by extremely short fragment sizes and deaminated nucleotides.

While modern metagenomic assemblers like MEGAHIT [58] and metaSPAdes [59] are widely used,

their de Bruijn Graph implementations face a precision-sensitivity trade-off when dealing with highly complex datasets [65, 62]. As graph complexity increases, these tools must employ simplification strategies, potentially compromising assembly completeness or accuracy, especially in regions of high genomic diversity or low coverage.

PenguiN[62] addresses this issue through a greedy iterative overlap approach, leveraging whole read information for improved performance in variant-rich datasets. Ancient metagenomic datasets, particularly those from poorly preserved samples, present additional challenges for both de Bruijn graph and overlap-based assembly strategies. Base substitutions in aDNA fragments artificially increase the genomic diversity in metagenomic samples. Deep sequencing can facilitate assembly [17], but it may be impractical due to sample limitations or cost constraints [6].

Our tool, CarpeDeam, builds upon PenguiN's whole-read approach, incorporating a maximum-likelihood framework that utilizes sample-specific damage pattern matrices for contig correction and extension. Given the close relationship between CarpeDeam and PenguiN, with large parts of their algorithms sharing the same codebase, it is essential to clarify their distinctions.

Both assemblers share a foundational concept – leveraging the MMseqs2 linclust algorithm to cluster reads based on shared k-mers, yet they differ significantly in their suitability for assembling aDNA datasets. Overall, clustering by shared k-mers enables both tools to extend sequences in an overlap-based consensus approach. This method avoids an all-vs-all read comparison, which scales quadratically with the number of input reads and is thus computationally infeasible.

In both assemblers, a cluster is defined by sequences that not only share at least one k-mer with the cluster representative (the longest sequence) but also meet a sequence similarity threshold regarding the overlapping portions of two sequences. For PenguiN, this threshold is set to 99% by default, meaning that within the overlap of a member sequence and its cluster representative, at least 99% of the bases must be identical [62]. The assumption that sequences belonging to the same cluster are highly similar makes PenguiN particularly well-suited for assembling viral genomes or microbial 16S rRNAs from modern, non-ancient metagenomic samples, which it was specifically designed for. Furthermore, PenguiN uses a Bayesian framework to infer the most likely extension, given the observations of overlap length and sequence similarity. PenguiN's framework relies on the premise that mismatches in overlapping reads are rare and primarily arise from sequencing errors. Sequencing errors, especially in modern Illumina datasets, tend to be minimal ($<$ 0.1 - 0.6%) [97] and can be further reduced upstream of assembly by quality filtering reads before assembly [98]. Consequently, PenguiN does not include a base correction algorithm; it relies on overlaps between presumed high-quality reads for accurate assembly.

However, this design makes PenguiN unsuitable for aDNA assembly. aDNA fragments inherently contain postmortem base substitutions, which artificially inflate sequence diversity and disrupt

assumptions about sequence identity. Without correcting these substitutions, `PenguiN` faces two critical challenges. First, damaged reads may fail to cluster because the sequence mismatches caused by deaminations reduce overlap identity below the required 99% threshold. Second, even if damaged reads do cluster and overlap, the accumulation of deaminated bases during iterative extensions can propagate errors, further hindering assembly. While it is possible to lower the sequence identity threshold, as we did with `CarpeDeam`, this alone does not address the issue of accumulating damage.

These challenges are addressed by `CarpeDeam`, which incorporates damage-aware correction, extension, and RY-mer sequence identity filtering to adapt `PenguiN`'s sensitivity for aDNA samples.

To maintain objectivity, we ran all assemblers in their default modes, as this reflects the typical approach researchers might take when applying these tools. However, we recognize that the performance of assemblers may vary depending on parameter settings, particularly for challenging datasets such as aDNA. In our case, we noticed that `metaSPAdes` encountered issues during the error correction step, which is designed to address sequencing errors rather than ancient DNA damage. To proceed, we followed the advice provided by the developers in a related GitHub issue (see Section 3, subsection "simulated data", and ran `metaSPAdes` in "only assembler" mode as suggested. Given the unique characteristics of ancient DNA, a comprehensive parameter benchmarking study could provide valuable insights into optimizing assembly strategies. However, such an exploration is beyond the scope of the current manuscript.

Significant Impact of Fragment Length Distribution and Damage Patterns on the Assembly Process

Our extended analysis of simulated aDNA samples, incorporating three fragment length distributions (`medium`, `short`, and `ultra-short`), three levels of DNA damage (`moderate`, `high`, and `ultra-high`), and three depths of coverage (3X, 5X, and 10X), revealed that all these factors significantly influence the *de novo* assembly of aDNA samples.

Modern *de novo* assemblers are generally designed to handle sequencing reads that, when merged upon assembly, are several hundred base pairs in length. In a paired-end sequencing context, read lengths typically range from 2x75 bp to 2x300 bp [99], providing a very different starting condition compared to aDNA samples. aDNA molecules are heavily degraded, resulting in short DNA fragments with read length distributions peaking well below 100 bp [100]. These distributions often follow an inverse exponential relationship between fragment length and abundance [101]. A commonly used metric, the median fragment length, serves as an informative proxy for estimating the most abundant read size, which is expected to significantly influence the assembly process.

Our simulations support this observation to some extent. Larger median fragment lengths and more uniform length distributions, such as those observed in the `medium` fragment length distribution used in this study (Supplementary Material, Fig. S1 (A)), positively impact assembly quality. However, we also observed that rare long fragments (>100 bp) seemingly have a disproportionate influence on assembly outcomes. Despite being a small minority, these long sequences appear to act as exceptionally useful anchors, enabling assemblers to produce more contiguous and less fragmented assemblies. This effect was observed in both de Bruijn graph assemblers, `MEGAHIT` and `metaSPAdes`, and was even more pronounced in the overlap-consensus assemblers, `CarpeDeam` and `PenguiN`.

Damage levels also had a significant influence on assembly quality. The three damage levels used in this study (`moderate`, `high`, and `ultra-high`) differ in two key aspects. First, the maximum damage at the first position of a fragment varies considerably, with substitution rates ranging from 0.33 in `moderate` damage to 0.58 in `ultra-high` damage. Second, the damage levels differ in their slope, representing how quickly substitution rates decline along the fragment. For example, while `ultra-high` damage exhibits a substitution rate of only 0.05 at position 5, `moderate` damage maintains a substitution rate of approximately 0.14 at the same position.

Interestingly, all assemblers struggled more with the `moderate` damage level and its lower decline rate compared to the `ultra-high` damage level, as demonstrated in the Supplementary Material, Section S2. This counterintuitive result can be explained by the mechanics of the assembly algorithms.

For de Bruijn graph-based assemblers, such as `MEGAHIT` and `metaSPAdes`, the extraction of k-mers as building blocks presents a challenge. These assemblers often start with $k = 21$ or higher [58, 59]. With already short fragment lengths, the number of k-mers that can be extracted is limited. For instance, in the case of a 40 bp read where the first and last 5 bases have relatively high substitution rates, only the central portion of the read contributes k-mers that accurately represent the original sequence. k-mers spanning damaged regions are more likely to contain mismatches, making it difficult to find matching k-mers from other reads, and thereby impeding graph extension.

Overlap-based assemblers, such as `CarpeDeam` and `PenguiN`, face a different set of challenges. Reads are clustered together based on shared k-mers, but the full overlap must meet a minimum sequence identity threshold (90% for `CarpeDeam`, 99% for `PenguiN`). For ultra-short reads with high substitution rates in the first few positions, the sequence identity can quickly fall below these thresholds. While lowering the threshold could mitigate this issue, it would significantly increase computational resource usage (due to larger clusters) and the risk of misassemblies.

These findings are critical for future studies utilizing *de novo* assembly for aDNA and highlight the importance of developing methods specifically optimized for highly fragmented and damaged

DNA.

Impact of Coverage Depth on the Assembly Process and the Issue of Misassemblies

The role of coverage depth in the assembly process has been risen in other studies as well. For instance, Klapper *et al.* [17] assembled ancient metagenomic datasets to identify biosynthetic gene clusters (BGCs), leading to the experimental validation of previously unknown molecules. Their findings showed that while modern metagenomic samples produced more contiguous assemblies than ancient samples, deeply sequenced ancient metagenomes achieved similarly high-quality assemblies [17].

Our simulations support this observation. Higher average coverage depths consistently resulted in better assemblies across multiple metrics. However, as detailed in Supplementary Material, Section S2, current assemblers still face challenges when dealing with the short fragment lengths and high levels of damage. For instance, while MEGAHIT often achieved genome fractions comparable to CarpeDeam, it underperformed in terms of largest alignment and NA50. This highlights the limitations of assemblers not specifically designed for aDNA, even under high-coverage conditions.

Another study by Jackson *et al.* [102] demonstrated as well that deeply sequenced samples could be successfully assembled with MEGAHIT. However, deep sequencing is often impractical due to sample limitations or cost constraints [6].

The improved performance of de Bruijn graph-based assemblers with high coverage is straightforward to explain: higher coverage ensures that genome positions are more likely to be covered by k-mers free of deaminated bases, enabling more contiguous paths through the assembly graph. Theoretically, the same principle applies to overlap-based assemblers like CarpeDeam and PenguiN. While higher coverage datasets in our simulations led to improved assembly metrics overall, a significant misassembly rate could be observed. In unsafe mode, CarpeDeam exhibited particularly high misassembly rates, especially in high-coverage datasets.

This issue led to the introduction of the safe mode for CarpeDeam. In early assembly stages, short reads may overlap with 100% sequence identity, particularly in cases involving mobile genetic elements (MGEs) shared between species [103]. Under these conditions, the assembler cannot reliably distinguish sequences from different species. Graph-based assemblers handle this by marking such regions as diverging paths, effectively "cutting" contigs at these points, resulting in shorter but accurate assemblies. The safe mode of CarpeDeam addresses this issue by utilizing a consensus calling mechanism, thereby reducing misassembly rates severalfold, albeit at the cost of shorter contigs. Users can alternatively choose the unsafe mode, which disables the consensus calling mechanism, potentially increasing sensitivity but at the risk of producing more misassembled or

chimeric contigs.

It must be noted that it might seem counterintuitive why `CarpeDeam`'s unsafe mode exhibited exceptionally high misassembly rates in high-coverage datasets, where higher coverage should theoretically improve assembly. We believe that this is triggered by sequences of highly abundant species. In some cases, clusters may contain reads that overlap perfectly with the center sequence at 100% identity. While the correct extension may originate from a less abundant species, the assembler is more likely to select a perfectly overlapping but incorrect sequence from the most abundant species, leading to misassemblies. A detailed investigation of this issue is provided in Supplementary Material, Section S4, where we are showing that identical sequences can occur within a single genome or between genomes of different species, with considerable variation across prokaryotic taxa [104, 103] (Supplementary Material Fig. S16 and Fig. S17).

Our observations highlight the trade-off between sensitivity and accuracy in metagenomic assembly, especially in the context of aDNA and diverse prokaryotic communities. The availability of safe and unsafe modes allows users to adjust the assembly approach based on their specific research goals and the nature of their datasets.

A potential future solution could involve incorporating a graph-like structure within the clusters sharing a k-mer, combining the overlap-based approach with the flexibility of graph assemblers. However, this approach requires further research. Downstream analyses—such as protein prediction or contig alignments against reference databases—can help identify misassembly breakpoints, enabling researchers to extract valuable insights from the contigs for further investigation.

Protein-Centric Approaches in aDNA Research

We assembled 20 empirical datasets from 5 sample sites, two of which were further analysed for taxonomic classification. The results underscore the potential of protein prediction in aDNA research to uncover novel insights. Protein prediction becomes feasible only with sequences that are sufficiently long for ORF prediction, which is challenging when dealing with inherently short aDNA reads. As highlighted by Borry *et al.* [93], predicting ORFs directly from ancient DNA reads is extremely difficult, if not impossible, with current tools. By contrast, *de novo* assembly generates sequences long enough for ORF prediction.

Proteins offer unique advantages in aDNA research as they are more conserved than nucleotide sequences. Modern tools like `MMseqs2` [76], and `DIAMOND` [105] enable rapid and sensitive screening of translated sequences against large protein databases. These advantages highlight the potential of protein-centric approaches for the discovery of functional elements and taxonomic profiling in aDNA datasets.

Gene- and protein-centric approaches have already demonstrated success in related fields. Klapper *et al.* [17] identified and experimentally validated bioactive molecules from biosynthetic gene clusters in ancient metagenome-assembled genomes. Wan *et al.* [50] applied deep learning to analyse proteomes of extinct organisms, identifying potential antimicrobial peptides effective against highly pathogenic bacteria. Such studies could benefit from advanced *de novo* assembly methods with higher sensitivity, such as those provided by `CarpeDeam`.

Our results confirm this potential but also reveal substantial variability in assembler performance across datasets. While `CarpeDeam` and `MEGAHIT` generally performed best, the ECO datasets presented an exception, with `MEGAHIT` outperforming `CarpeDeam`. This may be explained by the high variability in damage patterns within the ECO datasets. The damage patterns per sample are shown in the Supplementary Material, Fig. S19. The ECO datasets deviate most from the average damage profile used as input, whereas the EMN and GDN datasets show relatively small deviations. Incorporating species-specific damage patterns could significantly enhance assembly performance, but implementing this approach would be challenging as it requires substantial modifications to the tool's core code base. While our method yields superior results in many cases, these findings highlight that no single assembler performs best across all datasets, emphasizing the importance of employing diverse assembly strategies. We recommend that assembling large environmental samples should include careful preprocessing to remove non-damaged contaminants and minimize extreme variance in ancient sequence damage profiles.

Although protein-based taxonomy profiling is not yet widely used in aDNA research, it remains a promising alternative to nucleotide-based approaches, which have their own challenges, as mapping methods face significant limitations due to the low mapability of short reads in metagenomic datasets [41, 106]. By leveraging the conserved nature of amino acid sequences, protein-based taxonomy offers the potential for more accurate assignments. Our taxonomic classification results showed that both `CarpeDeam` and `MEGAHIT` identified a substantial number of unique taxa not detected by other assemblers. This result demonstrates that further development of assembly strategies holds significant potential for uncovering additional biological insights from existing datasets.

Further Applications: 16S rRNA-Based Taxonomic Assignment and Exploration of Biosynthetic Gene Clusters

Sequencing of 16S rRNA genes is widely used for phylogenetic analyses to discriminate taxa at various levels [107, 108]. Sequencing the full-length (1500 bp) gene provides the most accurate classifications [94]. Targeting specific hypervariable regions of the 16S rRNA gene has also been explored for phylogenetic analysis [109]. Previous efforts in ancient microbiome reconstructions

[83, 84, 85, 86, 87, 88] have encountered challenges due to ancient DNA fragmentation—often with lengths rarely exceeding 200 bp—which hampers the sequencing of long hypervariable regions such as the V4 region [89, 110]. In contrast, shotgun metagenomics, widely employed for profiling complex microbiomes, can yield increased false positives and negatives because of the high species diversity in environmental samples. Although Eisenhofer *et al.* [110] contend that shotgun metagenomics is best suited to capture the full spectrum of microbial diversity, we propose that *de novo* assembly can be leveraged for refining taxonomic specificity. However, reconstructing 16S rRNA genes is inherently challenging because their highly conserved regions often extend beyond the typical k-mer length used by de Bruijn graph assemblers, resulting in highly branched graphs and fragmented assemblies [62, 111, 112]. Despite these challenges, our approach successfully assembled contigs that align with curated 16S rRNA gene databases with high sequence similarity.

We compared the taxonomic classification from the study by Fellows Yates *et al.*, which used read mapping on shotgun-sequenced samples, with our 16S rRNA *de novo* assembly approach applied to the same sample. Although we did not recover all the taxa reported by Fellows Yates *et al.*, our method successfully identified three full-length 16S rRNA genes at species-level that were absent in their analysis. Thereby, we highlighted the complementary potential of *de novo* assembly to mapping approaches for phylogenetic analysis.

Our analysis of the assemblers' ability to reconstruct genes within BGCs indicated that `CarpeDeam` increases sensitivity by identifying both additional BGC types not detected by other assemblers and a higher overall number of BGC candidates. This enhanced performance was further supported by longer alignment lengths of BGC genes recovered by `CarpeDeam`. However, as shown by Klapper *et al.*, deeply sequenced samples are preferable for BGC analyses, with detection being particularly effective in datasets that yield contigs of at least 10 kb.

Limitations of `CarpeDeam`

`CarpeDeam` uses a greedy iterative approach, which may not be as time-efficient as the de Bruijn graph methods employed by assemblers such as `MEGAHIT` and `metaSPAdes` (see runtime and memory usage in Supplementary Material, Section S7). However, `CarpeDeam` represents a valuable alternative to the long-established dominance of de Bruijn graph algorithms, demonstrating its potential to outperform these methods in specific benchmark metrics. While de Bruijn graphs have been the foundation of *de novo* assembly for decades [113], our results highlight the promise of alternative strategies. The greedy overlap-based approach, initially introduced by the protein-level assembler `PLASS`, adapted by the protein-guided nucleotide assembler `PenguiN`, and further refined in `CarpeDeam`, offers increased sensitivity, uncovering sequences that remain undetectable by other assemblers.

A unique feature of `CarpeDeam` is its use of a damage matrix, introducing a novel concept in aDNA assembly. The assembler currently applies a global damage model, which does not account for differences in damage across sequences within a sample. Future updates could include species-specific damage profiles to better reflect the diverse damage patterns seen in metagenomic datasets. Despite this limitation, `CarpeDeam` has successfully assembled empirical datasets with damage variation within a limited range of $\pm 10\%$, demonstrating its applicability to ancient metagenomic samples.

`CarpeDeam`'s primary limitation is its tendency to assemble a higher fraction of misassemblies. This issue, along with potential solutions, was discussed earlier, including the introduction of safe and unsafe modes to mitigate the problem. While the safe mode reduces misassemblies, it raises the question of which mode is best suited for a given dataset, as results can vary. For instance, our investigation of Non-Misassembled Contigs (see Section 3 and Supplementary Material Fig. S18) revealed that in 8 out of 9 datasets, the unsafe mode produced more non-misassembled contigs than the safe mode. This is due to a key feature of both `PenguiN` and `CarpeDeam`, which allows single reads to be used multiple times during assembly, potentially creating redundant contigs. Redundancy is reduced during the final clustering step, where sequences are grouped at 97% sequence identity, but this process also allows any sequence to become a cluster's center sequence if it is the longest and shares a k-mer with at least one other sequence. Consequently, the unsafe mode generates more non-misassembled contigs, but also more misassemblies, leading to a higher "misassemblies per contig" ratio. In contrast, the safe mode aborts extensions when potential misassembly origins are detected, resulting in shorter contigs and fewer non-misassembled contigs larger than 2000 bp. Ultimately, the choice between modes depends on the downstream analysis. For instance, researchers prioritizing sensitivity in aDNA assembly might prefer the unsafe mode, albeit with the need for more careful downstream filtering (e.g., alignment-based methods), while others may favour the safe mode for its higher robustness across assembled contigs.

The analysis of protein sequences derived from the assembled contigs revealed that `CarpeDeam` could recover more unique proteins compared to other assemblers, as illustrated in Figure 5, panel **(A)**. Additionally, `CarpeDeam` demonstrated a higher aligned fraction of amino acid residues belonging to high-confidence aligned proteins, as shown in **panel (B)**. However, the differences between `MEGAHIT` and `CarpeDeam` in protein recovery were not as pronounced as the mapped fraction of nucleotide base pairs suggested (Figure 4 panel **(A)**). For instance, `CarpeDeam`'s assembly in unsafe mode mapped more than twice as many nucleotides of non-duplicated base pairs against the reference compared to `MEGAHIT`. This discrepancy between nucleotide mapping and protein recovery indicates that a notable proportion of potential protein-coding sequences are not accurately predicted, likely due to frame-shifts, indels, or erroneous base corrections. Such errors in the assembled sequences can disrupt reading frames or introduce premature stop codons, leading

to incomplete or missed protein predictions. This observation highlights that while `CarpeDeam`'s damage correction algorithm demonstrates significant improvements over existing methods, there remains potential for further refinement.

5   Conclusion

`CarpeDeam` represents a significant advance in aDNA assembly as the first sample-specific, damage-aware assembler. Our experiments on both simulated and empirical data demonstrate `CarpeDeam`'s ability to improve the assembly of long, continuous sequences from degraded aDNA. By incorporating a maximum-likelihood framework that utilizes sample-specific damage pattern matrices, `CarpeDeam` outperforms existing assemblers in recovering genes and RNA sequences, from metagenomic samples. The tool's dual operational modes - safe and unsafe - offer users flexibility in balancing sensitivity and accuracy based on their research goals. While challenges remain in reconstructing full-length genomes from highly degraded samples, `CarpeDeam`'s improved recovery of RNA content highlights its potential for taxonomic classification and functional analysis, particularly in ancient microbiomes. As the first damage-aware metagenome assembler, `CarpeDeam` lays the groundwork for future innovations in this field. Looking ahead, combining `CarpeDeam`'s novel approach with established de Bruijn graph methods could potentially lead to even more robust and accurate aDNA assembly techniques, further advancing our ability to reconstruct and analyse ancient microbial communities.

6   Methods

Test Data

To assess the assembly performance of ancient metagenomic samples, we simulated three distinct metagenomic environments. Each environment varied in complexity, including different abundance profiles of species. The taxonomic composition was modeled on previously published studies from Granehall *et al.* [35], Wibowo *et al.* [44], and Der Sarkissian *et al.* [69]. We simulated data with three levels of average coverage (3X, 5X, and 10X), three fragment length distributions (`medium`, `short`, and `ultra-short`) and three levels of damage (`moderate`, `high`, and `ultra-high`). In total, 81 datasets were generated. Table 5 provides an overview of representative datasets with `short` fragment length and `moderate` damage.

The fragment length distributions used in the simulations were labeled `medium`, `short`, and `ultra-short`, with the `medium` distribution derived from the EMN001.A0101 sample (Fellows Yates *et al.* [36]), the `short` distribution from the Vi33.19 sample (Gansauge *et al.* [114]), and the `ultra-short`

Sample	# Taxa	Coverage	# Reads (merged)	Total Length	GC Content (%)
Bone	34	3X	13,481,538	689,950,613	57.62
Bone	34	5X	22,469,438	1,149,702,991	57.62
Bone	34	10X	44,938,811	2,299,239,612	57.62
Dental Calculus	59	3X	8,169,233	417,738,204	43.77
Dental Calculus	59	5X	13,615,501	696,358,011	43.76
Dental Calculus	59	10X	27,231,047	1,392,706,548	43.77
Gut	116	3X	25,583,926	1,308,958,512	42.45
Gut	116	5X	42,640,124	2,181,743,052	42.45
Gut	116	10X	85,279,973	4,363,114,755	42.45

Table 5: Characteristics of simulated ancient metagenomic datasets representing three distinct environments: Bone, Dental Calculus, and Gut. The table summarizes the number of taxa, average coverage depth, number of sequences, total sequence length, and GC content (%) for representative datasets simulated with `short` fragments and `moderate` damage.

distribution from the OAK001.A0101 sample (Fellows Yates *et al.* [36]). The distributions as well as the damage level categories are shown in the Supplementary Material, Fig. S1. We used `gargammel` [115] to simulate paired-end reads for the bacterial communities using the aforementioned damage patterns and fragment length distributions. Adapters were trimmed, and paired-end reads were merged with `leeHom` [116] using the `--ancientdna` option. The simulated reads were aligned to the reference genomes with `Bowtie2` [71], and the resulting BAM files were processed with `DamageProfiler` [9]. The estimated damage patterns were then used as input for `CarpeDeam`, which incorporates these patterns into its maximum likelihood framework. This workflow avoided any bias in favour of `CarpeDeam`, as the simulation closely reflects how damage patterns are realistically derived.

The empirical datasets we benchmarked the assemblers against were obtained from Fellows Yates *et al.* [36]. Fellows Yates *et al.* provided extensive analysis of the species found in these datasets, which made them highly suitable for our analysis, as we could utilize the presented damage patterns for the input of `CarpeDeam`. The damage patterns observed in these datasets varied across species. This variability allowed us to infer `CarpeDeam`'s robustness against varying damage levels, as it uses a single damage profile for all input data. An overview of the C→T substitution frequencies for identified species can be found in the Supplementary Material, Fig. S19.

Benchmark Workflow

Evaluation of Simulated Metagenomic Datasets

The assembly performance was evaluated using metrics reported by `metaQUAST` [70]. For all 81 simulated datasets, we ran `metaQUAST` and mapped the reads against the assemblies, providing the

reference genomes used for the simulations. The minimum sequence identity for alignments was set to 90%, as suggested in the `metaQUAST` documentation. While the full `metaQUAST` results for all datasets can be found in the Supplementary Material, the results in the main manuscript focus on a subset of the simulations: three levels of coverage (3X, 5X, and 10X) for the three different environments (`Gut`, `Dental Calculus`, and `Bone`) simulated with `moderate` damage and `short` fragment length distribution. Informative metrics for this subset are reported in Fig. 3 and Table 1, with additional tables for dental calculus and bone simulations available in the Supplementary Material (Tables S2 and S3). For the alignment evaluation, `metaQUAST` uses the pairwise sequence aligner `minimap2` [58].

To complement the genome fraction metric and provide a more comprehensive assessment of assembly quality, we evaluated the ability of each assembler to reconstruct longer, correct contigs. Specifically, we quantified the number of correct contigs of length 2000 bp or longer for each assembler across a subset of the datasets. This analysis addresses a limitation of the genome fraction metric, which does not account for the length distribution of contigs mapping to the reference genome (Supplementary Material Fig. S18).

We further assessed the assemblers' performance in reconstructing protein content. This analysis involved annotating the produced contigs and searching for similar proteins using `Prokka` [75], which employs `Prodigal` [117] for open reading frame prediction and searches against three core databases.

We utilized the `MMseqs2 map` [76] module in `--cov-mode 1` with the `--min-seq-id` parameter set to 0.9 to find very similar sequence matches with at least 90% sequence identity and covers the target by at least 90%. We then reported the number of unique matches in the reference (Fig. 5, panel **(A)**).

In panel **(B)** of Fig. 5, we analysed the fraction of amino acid residues in the assembled proteins that aligned to the predicted reference proteins. Again, we used `Prokka` [75] to predict proteins from the assembled contigs. We then searched these predicted proteins against the reference proteins using the `MMseqs2 map` module. We set the minimum coverage parameter `-c` to 0 and the `--min-seq-id` parameter to 0.9, to report any alignments with at least 90% sequence identity. From these high-confidence alignments, we counted the number of amino acid residues for each assembled protein. We then calculated the fraction of mapped amino acid residues compared to the total number of residues in the assembled proteins. This fraction of aligned amino acid residues is shown in panel **(B)** of the figure.

Taxonomy Assignment of Contigs and Protein Similarity Search of Empirical Datasets

For two empirical datasets, EMN001.A0101 and GDN001.A0101, we conducted a taxonomic assignment analysis using the assembled contigs. Since we did not have the ground truth for the empirical datasets (only selected identified species from Fellows Yates *et al.* [36]) we employed different evaluation methods. First, we used the `MMseqs2` taxonomy module [34] for taxonomic classification. This module translates contigs in all six reading frames and searches the amino acid sequences against a target database. For our target, we used proteomes that are representatives for species according to the Genome Taxonomy Database (GTDB) [80]. These proteomes are the cluster representatives for each species, and this database was downloaded using the `databases` module of `MMseqs2` [76]. The GTDB is a phylogenetically consistent, genome-based taxonomy that uses a large number of quality-controlled genomes to infer evolutionary relationships among bacteria and archaea.

We analysed the number of unique species assigned to the translated contigs, considering all species where at least one translated contig covered a single-copy protein by at least 90%. We then examined the number of shared taxa and unique taxa per assembler (see Fig. 6), panel (**B**).

Additionally, we analysed the capability of the assemblers to assemble protein fractions that can be used for identifying evolutionary related proteins. We predicted open reading frames (ORFs) from the contigs generated by all assemblers using `Prodigal` [117] with the "meta" setting, considering only full-length ORFs for further analysis. We then used MMseqs2's easysearch module [76] to search the amino acid sequences against the UniProt100 database [118], filtering the results by a minimum sequence identity of 0.35, an E-value smaller than 1e-5, and a minimum alignment length of 100 residues. The number of unique protein hits is reported in Fig. 6, panel **A**.

rRNA Detection and BGC Screening

We analysed the ability of the assemblers to reconstruct 16S rRNA genes, which are key markers for taxonomic classification. Assembled contigs were annotated for RNA sequences using `Prokka` [75], and the annotated RNA sequences were clustered at 99% sequence similarity and a minimum coverage of 99% to reduce redundancy with `MMseqs2 linclust` [68]. The clustered RNA sequences were then searched against the SILVA database [119], which includes 510,495 high-quality, full-length 16S and 18S rRNA sequences. To focus specifically on bacterial origin, we filtered the database to retain only bacterial rRNA genes, resulting in a subset of 432,033 sequences.

To ensure specificity, the results were filtered to retain only sequences that covered at least 80% of a database entry. The number of unique hits in the SILVA database, spanning sequence similarity thresholds from 90% to 100%, is shown in Fig. 7, panel **A**.

For BGC screening, we used `antiSMASH 7.1` [95] to identify biosynthetic gene clusters by searching against the `antiSMASH` database. Subsequently, `MMseqs2` [68] was employed to search the BGC sequences against the nr database, allowing us to evaluate sequence similarity and alignment length.

Deamination Correction in Assembly Process

The assembly workflow incorporates a correction stage for deaminated bases at the start of each iteration. First, sequences are clustered based on shared k-mers, following `PenguiN`. The choice of k-mer size impacts clustering accuracy, with larger k values generally producing clusters that more reliably group sequences of common origin. Given the typically short length of aDNA fragments, a default k-mer size of 20 is set. The clusters are characterized by:

- A center sequence, which is either a contig (an extended sequence not found in the raw input data) or an aDNA fragment. It is the longest sequence in the cluster.

- All remaining members of the cluster are aDNA fragments (non-extended fragments).

- All members of a cluster fulfill threshold criteria such as sequence identity and E-value (as in `PenguiN`) and the newly introduced RYmer sequence identity, which exclusively counts mismatches between purines and pyrimidines, thereby tolerating mismatches due to deamination, i.e. C→T or G→A substitutions.

The goal is to correct the center sequence of each cluster, using alignments from member sequences and user-provided damage patterns that estimate base substitutions in the input data.

Consider a cluster containing a center sequence C and at a given position in this sequence, we seek to find the most likely base b_C given the data. The data consists of a set of aDNA fragments $\mathcal{R}$ aligning at that position. The fragments in $\mathcal{R}$ share at least one k-mer with C. More prosaically, we seek $P[b_C \mid \mathcal{R}]$ which can be obtained by finding b_C which maximizes the expression $P[\mathcal{R} \mid b_C]$ assuming a uniform prior for all 4 DNA nucleotides. The independence assumption allows us to say:

$$P[\mathcal{R} \mid b_C] = \prod_{R \in \mathcal{R}} P[R \mid b_C]$$

For a base b_R in R at that position, each factor is defined as:

$$P[b_R \mid b_C] = \begin{cases} \delta(b_C \to b_R)(1 - \epsilon) & \text{if } b_R = b_C \\ \frac{\epsilon}{3} + \delta(b_C \to b_R)(1 - \epsilon) & \text{if } b_R \neq b_C \end{cases}$$

Here ϵ represents the sequencing error rate and is set at $\frac{1}{1000}$ for all bases as `PenguiN` does not store the quality scores at this stage. The term $\delta(b_C \rightarrow b_R)$ represents the rate of substitution from C to R due to aDNA damage as provided by the user for this particular position in the fragment. To illustrate, if the rate of C to T at the 5' end is 30%, then $\delta('C' \rightarrow' C') = 0.7$ and $\delta('C' \rightarrow' T') = 0.3$. In the case of the bases not matching, we consider the possibility of either sequencing error or damage. If the bases match, then no damage has occurred and the base was called correctly. We neglect the possibility of a deamination followed by a sequencing error which would result in the same base as it is dwarfed by the other term.

Assembly with aDNA fragments

Selecting the extension candidate

Following the initial correction of the center sequence in each cluster, the workflow proceeds with a damage-aware extension process. This involves extending the center sequences of each cluster using sequences that are part of the cluster that share at least one k-mer with the center sequence and meet additional criteria such as minimum sequence identity, E-value, and RYmer sequence identity. In this phase, only member sequences that are fragments rather than assembled contigs are considered, as the provided damage patterns are only applicable to sequences not yet merged as contigs. The selection of the most suitable sequence for extension is based on the overlap length and the number of matches within this overlap. However, as deamination events occur in aDNA, potential mismatches between the center sequence and the extension candidates are introduced. Therefore, the identification of the optimal sequence for extension is challenging.

Assuming that all bases in the center sequence C are correctly identified, we can calculate the likelihood of observing a specific overlap between C and an aDNA fragment R_i, conditional on the damage pattern δ. This approach accounts for potential deamination events, such as observing a base 'G' in the center sequence and 'A' in the overlapping fragment, without classifying them as highly improbable, depending on the damage pattern.

The question is which R_i is the best candidate for extension. More specifically, we seek R_i which maximizes $P[R_i \mid C]$. Let us define b_C as the base in the center sequence and b_{R_i} in the fragment. We have a nuisance parameter b_δ which is the base post damage.

The likelihood for a single nucleotide b_{R_i} of fragment R_i is given by:

$$P(b_{R_i} \mid b_C) = \sum_{b_\delta \in \{A,C,G,T\}} \delta(b_C \rightarrow b_\delta) \left(\begin{cases} (1-\epsilon) & \text{if } b_\delta = b_{R_i} \\ \frac{\epsilon}{3} & \text{if } b_\delta \neq b_{R_i} \end{cases} \right)$$

again, ϵ is $\frac{1}{1000}$. $\delta(b_C \rightarrow b_\delta)$ is the rate of nucleotide substitution due to aDNA damage.

However, not every aDNA fragment overlaps with the same amount of bases with C. Only com-

puting the overlapping portions would put longer overlaps at a disadvantage. Let us say that the

longest overlap among the candidates for extension is l_{max} bp long. If $l_{R_i} < l_{max}$ counting the

$l_{max} - l_{R_i}$ missing bases as mismatches would be unfair to shorter overlaps as even random se-

quences will be 25% similar. We therefore count the probability of the missing bases as $K^{(l_{max} - l_{R_i})}$.

K is a constant between 0 and 1, representing the probability of a random match between two

bases. The value of K is set by default at $\frac{1}{4}$.

Stopping criterion

After identifying the extension candidate with the highest likelihood, this candidate is merged

with the center sequence. This process continues iteratively, incorporating aDNA fragments that

meet the sequence identity criteria, until no further suitable candidates remain. The extension

process is terminated if no candidates satisfy the sequence identity threshold, or if the likelihood

is significantly lower than the likelihood for a random match, given that it satisfies the minimum

sequence identity threshold in the overlap (e.g. 90%). The likelihood of an alignment given the

damage pattern is calculated, as well as the likelihood of observing a random match. The ratio

of these two likelihoods determines the termination of the extension and can be set by the user.

The minimum ratio used as threshold for accepting an extension was established through empirical

testing to optimize the balance between sensitivity and precision. In Fig. S20 in the Supplementary

Material the influence of different damage levels on the odds ratio threshold is visually modeled.

The likelihood of observing the alignment by chance is calculated by multiplying the probability of

a random match. Since every member sequence aligns to the center sequence with a user-defined

sequence identity threshold, we use these values for a random match. For instance, if the threshold

is set at 90% and the longest overlap is 20 bases, then the random model will have a likelihood of

0.9^{20}.

This likelihood ratio approach allows for a relatively low sequence identity threshold (e.g., 90%)

in the first phase which includes clustering sequences based on shared k-mers and calculating the

overlap alignment, facilitating the inclusion of highly deaminated sequences. At the same time, it

ensures an early termination of the extension process to guard against erroneous extensions.

Damage-aware Rule for Merging Contigs

1103 The extension process is divided into two distinct phases: an initial extension phase that exclu-

1104 sively considers non-extended aDNA fragments (damage patterns are only valid for unmodified

sequences), followed by a second extension phase dedicated to merging contigs in the same cluster.

This second phase of extension focuses on merging contigs, allowing for a higher sequence identity threshold (98-99%) due to the correction of contigs in the previous phase. This threshold aligns with the default values in `PenguiN`. However, the potential presence of residual uncorrected bases, i.e. due to very low coverage, requires a modification of the extension strategy. However, we could not use the same strategy as described in Section 6, because firstly, the damage matrix becomes inapplicable to previously extended contigs due to the loss of positional information. Secondly, the significant variation in overlap length when merging contigs demands different penalizing strategies for shorter overlaps. For example, the contig merging step may encounter extension candidates with overlap lengths ranging from a few hundred to several thousand base pairs.

We modified `PenguiN`'s original extension rule (see Supplementary Note 1 in Jochheim *et al.* [62]) to score residual uncorrected bases. The original Bayesian approach in `PenguiN`'s algorithm models the extension process using a beta-binomial distribution, considering alignment length and mismatch count within overlaps. The extension of contigs stops when there are no longer any contigs matching above the identity threshold.

In the original rule, a match is assigned a value of 1 and a mismatch a value of 0. However, we have modified the value returned for mismatches between either C and T or G and A. The idea being that an extension candidate might have a mismatch due to an uncorrected base. Therefore, the sequence similarity of the overlap will be lower than it would be if the mismatch had been correctly corrected.

Given an observed mismatch of either C and T or G and A, we established a scoring function $f(s, \phi(L), \delta)$, that is:

$$f(s, L, \delta) = \delta \left(W \cdot s \cdot + (1 - W) \cdot \frac{\phi(L) - f_{min}}{f_{max} - f_{min}} \right) \tag{1}$$

where:

- L is the length of the alignment

- $s = \frac{m}{L}$ is the sequence similarity, with m being the number of matches in the alignment

- $\phi(L)$ is a scaling factor that accounts for the overlap length, which is based on a power law described by Sheinman *et al.* [104].

- δ is an approximation for the substitution rate. As the positional context is lost, we set it as the average damage rate for a particular base pair found in the original damage matrix.

Here, W is a weighting constant that balances the influence of the sequence similarity and the

length-dependent factor. The value of W is set to 0.5. The function $\phi(L)$ is motivated by the work of Sheinman *et al.* [104], describing the relative frequency of identical sequences found among bacterial genomes depending on their length. We utilize the power law to evaluate an overlap being genuine by scoring the overlap length:

$$\phi(L) = \frac{1.4 \times 10^{-9}}{L^3} \tag{2}$$

For practical implementation, we establish boundary conditions for the scaling factor $\phi(L)$:

$$f_{min} = \phi(10) \quad \text{and} \quad f_{max} = \phi(10000) \tag{3}$$

These constraints indicate that an overlap of 10 base pairs provides minimal confidence that two sequences belong to the same genome, while an overlap of 10000 base pairs or more provides maximum confidence.

Thereby, we aim to account for residual damaged bases in the contig merging step, ensuring that extension candidates with short overlaps but very high sequence identity, and candidates with long overlaps but lower sequence identity due to residual damages, are not disproportionately favoured.

Misassembly Prevention by Consensus Calling: Introducing two modes of CarpeDeam

CarpeDeam's algorithm relies on clustering sequences based on shared k-mers, utilizing the algorithm from the MMseqs2 [76] k-mers matcher module. As described by Jochheim *et al.* [62], this approach enables the use of whole sequence overlaps, providing an advantage over de Bruijn graph assemblers that use fixed-size k-mers, losing the context of the aDNA fragment information.

For modern samples with low sequencing error rates ($\leq 1\%$ [120]), PenguiN can apply a high default sequence similarity threshold of 99% between the center sequence and any member sequence, ensuring highly specific clusters. However, aDNA samples require a more lenient approach due to deaminated bases appearing as mismatches during clustering. To mitigate this issue while still excluding unsuitable candidates for extension, we implemented an additional threshold: the RYmer sequence identity. This method examines overlaps in Purine-Pyrimidine space, allowing mismatches between C and T as well as G and A, but restricting other mismatches. We also considered modifying the clustering algorithm to cluster sequences based on RYmers instead of k-mers. This would enable clustering impervious to damage. However, the extremely short nature of aDNA fragments prevented us from increasing the RYmer size sufficiently to achieve the specificity

required for effective clustering and extension. We demonstrated this by plotting the fraction of unique k-mers and RYmers of different sizes found in 1000 different bacterial genomes. The results can be found in the Supplementary Material, Fig. S21.

In practice, we applied an RYmer sequence identity threshold of 99.9% and a sequence identity threshold of 90%, permitting a certain level of Purine-Purine or Pyrimidine-Pyrimidine mismatches while minimizing other mismatches. Despite these measures, we observed a higher rate of misassemblies, particularly emerging in early extension phases where sequences are still very short ($\leq$200bp), as these sequences lack sufficient specificity for clustering while allowing for deamination-induced mismatches. Investigation of the higher rate of misassemblies observed with `CarpeDeam` can be found in the Supplementary Material, Section S4.

To address these challenges, we developed a consensus-based approach that independently evaluates the left and right extending regions of all candidate sequences. These extending regions are the areas not covered by the center sequence but present in overlapping extension candidates. For each side (left and right), we construct a consensus sequence by considering all extension candidates. The consensus is built base-by-base, requiring at least five extension candidates to cover each position. This method results in two consensus sequences—one for the left extension and one for the right extension. The new center sequence is then formed by concatenating the left consensus, the original center sequence, and the right consensus. A schematic representation of this approach is shown in in the Supplementary Material Fig. S22. This approach is referred to as "safe mode" in the manuscript and is used as the default mode in `CarpeDeam`. It can be changed to "unsafe mode" by setting the parameter flag `--unsafe` to 1.

By aligning each member sequence to the consensus sequence and applying the updated overlap information to both the fragment extension and contig merging steps, we successfully reduced the level of misassemblies. However, this improvement came at the cost of a slight decrease in sensitivity. This trade-off resulted in the development of two distinct modes for `CarpeDeam`, offering users flexibility in balancing assembly accuracy and completeness based on their specific research requirements.

7 Declarations

Data Availability

The simulated reads for the analysed datasets in this publication, along with additional files, are accessible on Zenodo under the DOI: 10.5281/zenodo.13208898.

Code Availability

The software is publicly available at https://github.com/LouisPwr/CarpeDeam. All scripts and benchmark data for assembly and analysis presented in this manuscript are available at https://github.com/LouisPwr/CarpeDeamAnalysis.

Software Versions

PenguiN 4-687d7 (GitHub clone from Jan. 2024), MEGAHIT v1.2.9, metaSPAdes v3.15.5, metaQUAST v5.0.2, Bowtie2 2.3.5.1-6, SAMtools 1.19, seqkit 2.6.1, prodigal V2.6.3, MMseqs2 Release 15-6f452, Prokka 1.14.6, skani 0.2.2, miniprot 0.13-r248

Competing Interests

The authors declare no competing interests.

Acknowledgements

We would like to acknowledge that this research and the PhD scholarships of Louis Kraft were funded by the Novo Nordisk Data Science Investigator grant number NNF20OC0062491. We thank the Technical University of Denmark's Department of Health Technology for additional funding. Additionally, we would like to thank Joshua Rubin and Nicola Vogel for their thoughtful comments on our manuscript. The authors thankfully acknowledge the computer resources and the technical support provided by the BMBF-funded de.NBI Cloud within the German Network for Bioinformatics Infrastructure (de.NBI) (031A537B, 031A533A, 031A538A, 031A533B, 031A535A, 031A537C, 031A534A, 031A532B). AF-G is supported by a grant from the Danish National Research Foundation (DNRF174). L.K. acknowledges the use of OpenAI/ChatGPT and Anthropic/Claude to proofread the manuscript.

Author Contributions

G.R. conceived the project. L.K. and G.R. designed and developed the method. L.K. implemented the method and tested it. L.K. conducted all tests. L.K. and A.F.G simulated datasets. A.F.G. provided expertise, computational resources and benchmark workflows and conducted additional analyses. J.S. supported the method development. M.S. and A.J. contributed software expertise and guidance in addressing data-centric issues. P.W.S provided IT infrastructure expertise. L.K. and G.R. wrote the manuscript. All authors approved the final manuscript.

Funding

Funding for this research was provided by a Novo Nordisk Data Science Investigator grant number NNF20OC0062491 (GR). This funding source provided the salaries for LK. Additional funding for computational resources was provided by the Department for Health Technology at DTU. The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

References

[1] A. Margaryan, D. J. Lawson, M. Sikora, F. Racimo, S. Rasmussen, I. Moltke, L. M. Cassidy, E. Jørsboe, A. Ingason, M. W. Pedersen, T. Korneliussen, H. Wilhelmson, M. M. Buś, P. de Barros Damgaard, R. Martiniano, G. Renaud, C. Bhérer, J. V. Moreno-Mayar, A. K. Fotakis, M. Allen, R. Allmäe, M. Molak, E. Cappellini, G. Scorrano, H. McColl, A. Buzhilova, A. Fox, A. Albrechtsen, B. Schütz, B. Skar, C. Arcini, C. Falys, C. H. Jonson, D. Błaszczyk, D. Pezhemsky, G. Turner-Walker, H. GestsdÓttir, I. Lundstrøm, I. Gustin, I. Mainland, I. Potekhina, I. M. Muntoni, J. Cheng, J. Stenderup, J. Ma, J. Gibson, J. Peets, J. Gustafsson, K. H. Iversen, L. Simpson, L. Strand, L. Loe, M. Sikora, M. Florek, M. Vretemark, M. Redknap, M. Bajka, T. Pushkina, M. Søvsø, N. Grigoreva, T. Christensen, O. Kastholm, O. Uldum, P. Favia, P. Holck, S. Sten, S. V. Arge, S. EllingvÅg, V. Moiseyev, W. Bogdanowicz, Y. Magnusson, L. Orlando, P. Pentz, M. D. Jessen, A. Pedersen, M. Collard, D. G. Bradley, M. L. Jørkov, J. Arneborg, N. Lynnerup, N. Price, M. T. P. Gilbert, M. E. Allentoft, J. Bill, S. M. Sindbæk, L. Hedeager, K. Kristiansen, R. Nielsen, T. Werge, and E. Willerslev, "Population genomics of the Viking world," Nature, no. 7825, pp. 390–396, 2020.

[2] K. H. Kjær, M. Winther Pedersen, B. De Sanctis, B. De Cahsan, T. S. Korneliussen, C. S. Michelsen, K. K. Sand, S. Jelavić, A. H. Ruter, A. M. A. Schmidt, K. K. Kjeldsen, A. S. Tesakov, I. Snowball, J. C. Gosse, I. G. Alsos, Y. Wang, C. Dockter, M. Rasmussen, M. E. Jørgensen, B. Skadhauge, A. Prohaska, J. Å. Kristensen, M. Bjerager, M. E. Allentoft, E. Coissac, A. Rouillard, A. Simakova, A. Fernandez-Guerra, C. Bowler, M. Macias-Fauria, L. Vinner, J. J. Welch, A. J. Hidy, M. Sikora, M. J. Collins, R. Durbin, N. K. Larsen, and E. Willerslev, "A 2-million-year-old ecosystem in Greenland uncovered by environmental DNA," Nature, vol. 612, pp. 283–291, 12 2022.

[3] A. Fernandez-Guerra, G. Borrel, T. O. Delmont, B. Elberling, A. M. Eren, S. Gribaldo, A. Jochheim, R. A. Henriksen, K.-U. Hinrichs, T. S. Korneliussen, M. Krupovic, N. K. Larsen, R. Laso-Pérez, M. W. Pedersen, V. K. Pedersen, K. K. Sand, M. Sikora, M. Steinegger, I. Veseli, L. Wörmer, L. Zhao, M. Žure, K. Kjær, and E. Willerslev, "A 2-million-year-old microbial and viral communities from the Kap København Formation in North Greenland," Cold Spring Harbor Laboratory, 6 2023.

[4] N. A. Vogel, J. D. Rubin, M. Swartz, J. Vlieghe, P. W. Sackett, A. G. Pedersen, M. W. Pedersen, and G. Renaud, "euka: Robust tetrapodic and arthropodic taxa detection from modern and ancient environmental ¡scp¿DNA¡/scp¿ using pangenomic reference graphs," Methods in Ecology and Evolution, vol. 14, p. 2717–2727, 9 2023.

[5] K. Prüfer, U. Stenzel, M. Hofreiter, S. Pääbo, J. Kelso, and R. E. Green, "Computational challenges in the analysis of ancient DNA," Genome Biology, vol. 11, no. 5, p. R47, 2010.

[6] C. Der Sarkissian, I. M. Velsko, A. K. Fotakis, Å. J. Vågene, A. Hübner, and J. A. Fellows Yates, "Ancient Metagenomic Studies: Considerations for the Wider Scientific Community," mSystems, vol. 6, 12 2021.

[7] A. W. Briggs, U. Stenzel, P. L. F. Johnson, R. E. Green, J. Kelso, K. Prüfer, M. Meyer, J. Krause, M. T. Ronan, M. Lachmann, and S. Pääbo, "Patterns of damage in genomic DNA sequences from a Neandertal," Proceedings of the National Academy of Sciences, vol. 104, p. 14616–14621, 9 2007.

[8] C. Michelsen, M. W. Pedersen, A. Fernandez-Guerra, L. Zhao, T. C. Petersen, and T. S. Korneliussen, "metaDMG – A Fast and Accurate Ancient DNA Damage Toolkit for Metagenomic Data," Cold Spring Harbor Laboratory, 12 2022.

[9] J. Neukamm, A. Peltzer, and K. Nieselt, "DamageProfiler: fast damage pattern calculation for ancient DNA," Bioinformatics, vol. 37, p. 3652–3653, 4 2021.

[10] H. Jónsson, A. Ginolhac, M. Schubert, P. L. F. Johnson, and L. Orlando, "mapDamage2.0: fast approximate Bayesian estimates of ancient DNA damage parameters," Bioinformatics, vol. 29, p. 1682–1684, 4 2013.

[11] L. Zhao, R. A. Heriksen, A. D. Ramsøe, R. Nielsen, and T. S. Korneliussen, "Revisiting the Briggs ancient DNA damage model: a fast regression method to estimate postmortem damage," Cold Spring Harbor Laboratory, Nov. 2023.

[12] J. Dabney, M. Meyer, and S. Paabo, "Ancient DNA Damage," Cold Spring Harbor Perspectives in Biology, vol. 5, p. a012567–a012567, 5 2013.

[13] S. Pääbo, H. Poinar, D. Serre, V. Jaenicke-Després, J. Hebler, N. Rohland, M. Kuch, J. Krause, L. Vigilant, and M. Hofreiter, "Genetic Analyses from Ancient DNA," Annual Review of Genetics, vol. 38, p. 645–679, 12 2004.

[14] E. Willerslev and A. Cooper, "Review Paper. Ancient DNA," Proceedings of the Royal Society B: Biological Sciences, vol. 272, p. 3–16, 12 2004.

[15] S. Peyrégne and B. M. Peter, "AuthentiCT: a model of ancient DNA damage to estimate the proportion of present-day DNA contamination," Genome Biology, vol. 21, 9 2020.

[16] G. Renaud, V. Slon, A. T. Duggan, and J. Kelso, "Schmutzi: estimation of contamination and endogenous mitochondrial consensus calling for ancient DNA," Genome Biology, vol. 16, 10 2015.

[17] M. Klapper, A. Hübner, A. Ibrahim, I. Wasmuth, M. Borry, V. G. Haensch, S. Zhang, W. K. Al-Jammal, H. Suma, J. A. Fellows Yates, J. Frangenberg, I. M. Velsko, S. Chowdhury, R. Herbst, E. V. Bratovanov, H.-M. Dahse, T. Horch, C. Hertweck, M. R. González Morales, L. G. Straus, I. Vilotijevic, C. Warinner, and P. Stallforth, "Natural products from reconstructed bacterial genomes of the Middle and Upper Paleolithic," <u>Science</u>, vol. 380, p. 619–624, 5 2023.

[18] A. Oliva, R. Tobler, A. Cooper, B. Llamas, and Y. Souilmi, "Systematic benchmark of ancient DNA read mapping," <u>Briefings in Bioinformatics</u>, vol. 22, 4 2021.

[19] I. M. Velsko, L. A. F. Frantz, A. Herbig, G. Larson, and C. Warinner, "Selection of Appropriate Metagenome Taxonomic Classifiers for Ancient Microbiome Research," <u>mSystems</u>, vol. 3, Aug. 2018.

[20] J. C. Wooley, A. Godzik, and I. Friedberg, "A Primer on Metagenomics," <u>PLoS Computational Biology</u>, vol. 6, p. e1000667, 2 2010.

[21] J. Handelsman, "Metagenomics: Application of Genomics to Uncultured Microorganisms," <u>Microbiology and Molecular Biology Reviews</u>, vol. 68, p. 669–685, Dec. 2004.

[22] S. Nayfach, S. Roux, R. Seshadri, D. Udwary, N. Varghese, F. Schulz, D. Wu, D. Paez-Espino, I.-M. Chen, M. Huntemann, K. Palaniappan, J. Ladau, S. Mukherjee, T. B. K. Reddy, T. Nielsen, E. Kirton, J. P. Faria, J. N. Edirisinghe, C. S. Henry, S. P. Jungbluth, D. Chivian, P. Dehal, E. M. Wood-Charlson, A. P. Arkin, S. G. Tringe, A. Visel, H. Abreu, S. G. Acinas, E. Allen, M. A. Allen, L. V. Alteio, G. Andersen, A. M. Anesio, G. Attwood, V. Avila-Magaña, Y. Badis, J. Bailey, B. Baker, P. Baldrian, H. A. Barton, D. A. C. Beck, E. D. Becraft, H. R. Beller, J. M. Beman, R. Bernier-Latmani, T. D. Berry, A. Bertagnolli, S. Bertilsson, J. M. Bhatnagar, J. T. Bird, J. L. Blanchard, S. E. Blumer-Schuette, B. Bohannan, M. A. Borton, A. Brady, S. H. Brawley, J. Brodie, S. Brown, J. R. Brum, A. Brune, D. A. Bryant, A. Buchan, D. H. Buckley, J. Buongiorno, H. Cadillo-Quiroz, S. M. Caffrey, A. N. Campbell, B. Campbell, S. Carr, J. Carroll, S. C. Cary, A. M. Cates, R. A. Cattolico, R. Cavicchioli, L. Chistoserdova, M. L. Coleman, P. Constant, J. M. Conway, W. P. Mac Cormack, S. Crowe, B. Crump, C. Currie, R. Daly, K. M. DeAngelis, V. Denef, S. E. Denman, A. Desta, H. Dionisi, J. Dodsworth, N. Dombrowski, T. Donohue, M. Dopson, T. Driscoll, P. Dunfield, C. L. Dupont, K. A. Dynarski, V. Edgcomb, E. A. Edwards, M. S. Elshahed, I. Figueroa, B. Flood, N. Fortney, C. S. Fortunato, C. Francis, C. M. M. Gachon, S. L. Garcia, M. C. Gazitua, T. Gentry, L. Gerwick, J. Gharechahi, P. Girguis, J. Gladden, M. Gradoville, S. E. Grasby, K. Gravuer, C. L. Grettenberger, R. J. Gruninger, J. Guo, M. Y. Habteselassie, S. J. Hallam, R. Hatzenpichler, B. Hausmann, T. C. Hazen, B. Hedlund, C. Henny, L. Herfort, M. Hernandez, O. S. Hershey, M. Hess, E. B. Hollister, L. A. Hug,

D. Hunt, J. Jansson, J. Jarett, V. V. Kadnikov, C. Kelly, R. Kelly, W. Kelly, C. A. Kerfeld, J. Kimbrel, J. L. Klassen, K. T. Konstantinidis, L. L. Lee, W.-J. Li, A. J. Loder, A. Loy, M. Lozada, B. MacGregor, C. Magnabosco, A. Maria da Silva, R. M. McKay, K. McMahon, C. S. McSweeney, M. Medina, L. Meredith, J. Mizzi, T. Mock, L. Momper, M. A. Moran, C. Morgan-Lang, D. Moser, G. Muyzer, D. Myrold, M. Nash, C. L. Nesbø, A. P. Neumann, R. B. Neumann, D. Noguera, T. Northen, J. Norton, B. Nowinski, K. Nüsslein, M. A. O'Malley, R. S. Oliveira, V. Maia de Oliveira, T. Onstott, J. Osvatic, Y. Ouyang, M. Pachiadaki, J. Parnell, L. P. Partida-Martinez, K. G. Peay, D. Pelletier, X. Peng, M. Pester, J. Pett-Ridge, S. Peura, P. Pjevac, A. M. Plominsky, A. Poehlein, P. B. Pope, N. Ravin, M. C. Redmond, R. Reiss, V. Rich, C. Rinke, J. L. M. Rodrigues, W. Rodriguez-Reillo, K. Rossmassler, J. Sackett, G. H. Salekdeh, S. Saleska, M. Scarborough, D. Schachtman, C. W. Schadt, M. Schrenk, A. Sczyrba, A. Sengupta, J. C. Setubal, A. Shade, C. Sharp, D. H. Sherman, O. V. Shubenkova, I. N. Sierra-Garcia, R. Simister, H. Simon, S. Sjöling, J. Slonczewski, R. S. Correa de Souza, J. R. Spear, J. C. Stegen, R. Stepanauskas, F. Stewart, G. Suen, M. Sullivan, D. Sumner, B. K. Swan, W. Swingley, J. Tarn, G. T. Taylor, H. Teeling, M. Tekere, A. Teske, T. Thomas, C. Thrash, J. Tiedje, C. S. Ting, B. Tully, G. Tyson, O. Ulloa, D. L. Valentine, M. W. Van Goethem, J. VanderGheynst, T. J. Verbeke, J. Vollmers, A. Vuillemin, N. B. Waldo, D. A. Walsh, B. C. Weimer, T. Whitman, P. van der Wielen, M. Wilkins, T. J. Williams, B. Woodcroft, J. Woolet, K. Wrighton, J. Ye, E. B. Young, N. H. Youssef, F. B. Yu, T. I. Zemskaya, R. Ziels, T. Woyke, N. J. Mouncey, N. N. Ivanova, N. C. Kyrpides, and E. A. Eloe-Fadrosh, "A genomic catalog of Earth's microbiomes," Nature Biotechnology, vol. 39, p. 499–509, Nov. 2020.

[23] L. P. Coelho, R. Alves, A. R. del Rio, P. N. Myers, C. P. Cantalapiedra, J. Giner-Lamia, T. S. Schmidt, D. R. Mende, A. Orakov, I. Letunic, F. Hildebrand, T. Van Rossum, S. K. Forslund, S. Khedkar, O. M. Maistrenko, S. Pan, L. Jia, P. Ferretti, S. Sunagawa, X.-M. Zhao, H. B. Nielsen, J. Huerta-Cepas, and P. Bork, "Towards the biogeography of prokaryotic genes," Nature, vol. 601, pp. 252–256, Dec. 2021.

[24] L. A. Hug, "The ever-changing tree of life," Nature Microbiology, Aug. 2024.

[25] A. M. Eren, E. Kiefl, A. Shaiber, I. Veseli, S. E. Miller, M. S. Schechter, I. Fink, J. N. Pan, M. Yousef, E. C. Fogarty, F. Trigodet, A. R. Watson, O. C. Esen, R. M. Moore, Q. Clayssen, M. D. Lee, V. Kivenson, E. D. Graham, B. D. Merrill, A. Karkman, D. Blankenberg, J. M. Eppley, A. Sjödin, J. J. Scott, X. Vázquez-Campos, L. J. McKay, E. A. McDaniel, S. L. R. Stevens, R. E. Anderson, J. Fuessel, A. Fernandez-Guerra, L. Maignien, T. O. Delmont, and A. D. Willis, "Community-led, integrated, reproducible multi-omics with anvi'o," Nature Microbiology, vol. 6, p. 3–6, Dec. 2020.

[26] C. Quince, A. W. Walker, J. T. Simpson, N. J. Loman, and N. Segata, "Shotgun metagenomics, from sampling to analysis," Nature Biotechnology, vol. 35, p. 833–844, 9 2017.

[27] S. H. Ye, K. J. Siddle, D. J. Park, and P. C. Sabeti, "Benchmarking Metagenomics Tools for Taxonomic Classification," Cell, vol. 178, p. 779–794, 8 2019.

[28] A. Blanco-Míguez, F. Beghini, F. Cumbo, L. J. McIver, K. N. Thompson, M. Zolfo, P. Manghi, L. Dubois, K. D. Huang, A. M. Thomas, W. A. Nickols, G. Piccinno, E. Piperni, M. Punčochář, M. Valles-Colomer, A. Tett, F. Giordano, R. Davies, J. Wolf, S. E. Berry, T. D. Spector, E. A. Franzosa, E. Pasolli, F. Asnicar, C. Huttenhower, and N. Segata, "Extending and improving metagenomic taxonomic profiling with uncharacterized species using MetaPhlAn 4," Nature Biotechnology, vol. 41, p. 1633–1644, 2 2023.

[29] D. E. Wood and S. L. Salzberg, "Kraken: ultrafast metagenomic sequence classification using exact alignments," Genome Biology, vol. 15, 3 2014.

[30] J. Lu, F. P. Breitwieser, P. Thielen, and S. L. Salzberg, "Bracken: estimating species abundance in metagenomics data," PeerJ Computer Science, vol. 3, p. e104, 1 2017.

[31] D. Kim, L. Song, F. P. Breitwieser, and S. L. Salzberg, "Centrifuge: rapid and sensitive classification of metagenomic sequences," Genome Research, vol. 26, p. 1721–1729, Oct. 2016.

[32] D. H. Huson, B. Albrecht, C. Bağcı, I. Bessarab, A. Górska, D. Jolic, and R. B. H. Williams, "MEGAN-LR: new algorithms allow accurate binning and easy interactive exploration of metagenomic long reads and contigs," Biology Direct, vol. 13, Jan. 2018.

[33] P. Menzel, K. L. Ng, and A. Krogh, "Fast and sensitive taxonomic classification for metagenomics with Kaiju," Nature Communications, vol. 7, Apr. 2016.

[34] M. Mirdita, M. Steinegger, F. Breitwieser, J. Söding, and E. Levy Karin, "Fast and sensitive taxonomic assignment to metagenomic contigs," Bioinformatics, vol. 37, p. 3029–3031, 3 2021.

[35] L. Granehäll, K. D. Huang, A. Tett, P. Manghi, A. Paladin, N. O'Sullivan, O. Rota-Stabelli, N. Segata, A. Zink, and F. Maixner, "Metagenomic analysis of ancient dental calculus reveals unexplored diversity of oral archaeal Methanobrevibacter," Microbiome, vol. 9, 9 2021.

[36] J. A. Fellows Yates, I. M. Velsko, F. Aron, C. Posth, C. A. Hofman, R. M. Austin, C. E. Parker, A. E. Mann, K. Nägele, K. W. Arthur, J. W. Arthur, C. C. Bauer, I. Crevecoeur, C. Cupillard, M. C. Curtis, L. Dalén, M. Díaz-Zorita Bonilla, J. C. Díez Fernández-Lomana, D. G. Drucker, E. Escribano Escrivá, M. Francken, V. E. Gibbon, M. R. González Morales, A. Grande Mateu, K. Harvati, A. G. Henry, L. Humphrey, M. Menéndez, D. Mihailović, M. Peresani, S. Rodríguez Moroder, M. Roksandic, H. Rougier, S. Sázelová, J. T. Stock,

L. G. Straus, J. Svoboda, B. Teßmann, M. J. Walker, R. C. Power, C. M. Lewis, K. Sankaranarayanan, K. Guschanski, R. W. Wrangham, F. E. Dewhirst, D. C. Salazar-García, J. Krause, A. Herbig, and C. Warinner, "The evolution and changing ecology of the African hominid oral microbiome," <u>Proceedings of the National Academy of Sciences</u>, vol. 118, 5 2021.

[37] Z. Patterson Ross, J. Klunk, G. Fornaciari, V. Giuffra, S. Duchêne, A. T. Duggan, D. Poinar, M. W. Douglas, J.-S. Eden, E. C. Holmes, and H. N. Poinar, "The paradox of HBV evolution as revealed from a 16th century mummy," <u>PLOS Pathogens</u>, vol. 14, p. e1006750, 1 2018.

[38] C. P. Andam, C. J. Worby, Q. Chang, and M. G. Campana, "Microbial Genomics of Ancient Plagues and Outbreaks," <u>Trends in Microbiology</u>, vol. 24, p. 978–990, 12 2016.

[39] M. L. Carpenter, J. D. Buenrostro, C. Valdiosera, H. Schroeder, M. E. Allentoft, M. Sikora, M. Rasmussen, S. Gravel, S. Guillén, G. Nekhrizov, K. Leshtakov, D. Dimitrova, N. Theodossiev, D. Pettener, D. Luiselli, K. Sandoval, A. Moreno-Estrada, Y. Li, J. Wang, M. T. P. Gilbert, E. Willerslev, W. J. Greenleaf, and C. D. Bustamante, "Pulling out the 1," <u>The American Journal of Human Genetics</u>, vol. 93, p. 852–864, 11 2013.

[40] R. Hübler, F. M. Key, C. Warinner, K. I. Bos, J. Krause, and A. Herbig, "HOPS: automated detection and authentication of pathogen DNA in archaeological remains," <u>Genome Biology</u>, vol. 20, 12 2019.

[41] Z. Pochon, N. Bergfeldt, E. Kırdök, M. Vicente, T. Naidoo, T. van der Valk, N. E. Altınışık, M. Krzewińska, L. Dalén, A. Götherström, C. Mirabello, P. Unneberg, and N. Oskolkov, "aMeta: an accurate and memory-efficient ancient metagenomic profiling workflow," <u>Genome Biology</u>, vol. 24, 10 2023.

[42] S. Liu, C. D. Moon, N. Zheng, S. Huws, S. Zhao, and J. Wang, "Opportunities and challenges of using metagenomic data to bring uncultured microbes into cultivation," <u>Microbiome</u>, vol. 10, May 2022.

[43] M. Hofreiter, J. L. A. Paijmans, H. Goodchild, C. F. Speller, A. Barlow, G. G. Fortes, J. A. Thomas, A. Ludwig, and M. J. Collins, "The future of ancient DNA: Technical advances and conceptual shifts," <u>BioEssays</u>, vol. 37, p. 284–293, Nov. 2014.

[44] M. C. Wibowo, Z. Yang, M. Borry, A. Hübner, K. D. Huang, B. T. Tierney, S. Zimmerman, F. Barajas-Olmos, C. Contreras-Cubas, H. García-Ortiz, A. Martínez-Hernández, J. M. Luber, P. Kirstahler, T. Blohm, F. E. Smiley, R. Arnold, S. A. Ballal, S. J. Pamp, J. Russ, F. Maixner, O. Rota-Stabelli, N. Segata, K. Reinhard, L. Orozco, C. Warinner, M. Snow, S. LeBlanc, and A. D. Kostic, "Reconstruction of ancient microbial genomes from the human gut," <u>Nature</u>, vol. 594, p. 234–239, 5 2021.

[45] M. A. Spyrou, K. I. Bos, A. Herbig, and J. Krause, "Ancient pathogen genomics as an emerging tool for infectious disease research," Nature Reviews Genetics, vol. 20, p. 323–340, 4 2019.

[46] P. Rozwalak, J. Barylski, Y. Wijesekara, B. E. Dutilh, and A. Zielezinski, "Ultraconserved bacteriophage genome sequence identified in 1300-year-old human palaeofaeces," Nature Communications, vol. 15, 1 2024.

[47] J. C. Brealey, H. G. Leitão, T. van der Valk, W. Xu, K. Bougiouri, L. Dalén, and K. Guschanski, "Dental Calculus as a Tool to Study the Evolution of the Mammalian Oral Microbiome," Molecular Biology and Evolution, vol. 37, p. 3003–3022, 5 2020.

[48] H. P. Hodgins, P. Chen, B. Lobb, X. Wei, B. J. M. Tremblay, M. J. Mansfield, V. C. Y. Lee, P.-G. Lee, J. Coffin, A. T. Duggan, A. E. Dolphin, G. Renaud, M. Dong, and A. C. Doxey, "Ancient Clostridium DNA and variants of tetanus neurotoxins associated with human archaeological remains," Nature Communications, vol. 14, 9 2023.

[49] L. G. E. Wilkins, C. L. Ettinger, G. Jospin, and J. A. Eisen, "Metagenome-assembled genomes provide new insight into the microbial diversity of two thermal pools in Kamchatka, Russia," Scientific Reports, vol. 9, Feb. 2019.

[50] F. Wan, M. D. T. Torres, J. Peng, and C. de la Fuente-Nunez, "Deep-learning-enabled antibiotic discovery through molecular de-extinction," Nature Biomedical Engineering, 6 2024.

[51] S. L. Salzberg, "Next-generation genome annotation: we still struggle to get it right," Genome Biology, vol. 20, 5 2019.

[52] V. L. Chan, "Bacterial Genomes and Infectious Diseases," Pediatric Research, vol. 54, p. 1–7, 7 2003.

[53] T. T. Binnewies, Y. Motro, P. F. Hallin, O. Lund, D. Dunn, T. La, D. J. Hampson, M. Bellgard, T. M. Wassenaar, and D. W. Ussery, "Ten years of bacterial genome sequencing: comparative-genomics-based discoveries," Functional & Integrative Genomics, vol. 6, p. 165–185, 5 2006.

[54] S. Rasmussen, M. E. Allentoft, K. Nielsen, L. Orlando, M. Sikora, K.-G. Sjögren, A. G. Pedersen, M. Schubert, A. Van Dam, C. M. O. Kapel, H. B. Nielsen, S. Brunak, P. Avetisyan, A. Epimakhov, M. V. Khalyapin, A. Gnuni, A. Kriiska, I. Lasak, M. Metspalu, V. Moiseyev, A. Gromov, D. Pokutta, L. Saag, L. Varul, L. Yepiskoposyan, T. Sicheritz-Pontén, R. A. Foley, M. M. Lahr, R. Nielsen, K. Kristiansen, and E. Willerslev, "Early Divergent Strains of Yersinia pestis in Eurasia 5,000 Years Ago," Cell, vol. 163, p. 571–582, 10 2015.

[55] V. J. Schuenemann, K. Bos, S. DeWitte, S. Schmedes, J. Jamieson, A. Mittnik, S. Forrest, B. K. Coombes, J. W. Wood, D. J. D. Earn, W. White, J. Krause, and H. N. Poinar, "Targeted enrichment of ancient pathogens yielding the pPCP1 plasmid ofYersinia pestisfrom victims of the Black Death," Proceedings of the National Academy of Sciences, vol. 108, 8 2011.

[56] S. Rampelli, S. Turroni, C. Mallol, C. Hernandez, B. Galván, A. Sistiaga, E. Biagi, A. Astolfi, P. Brigidi, S. Benazzi, C. M. Lewis, C. Warinner, C. A. Hofman, S. L. Schnorr, and M. Candela, "Components of a Neanderthal gut microbiome recovered from fecal sediments from El Salt," Communications Biology, vol. 4, 2 2021.

[57] M. Sikora, E. Canteri, A. Fernandez-Guerra, N. Oskolkov, R. Ågren, L. Hansson, E. K. Irving-Pease, B. Mühlemann, S. H. Nielsen, G. Scorrano, M. E. Allentoft, F. V. Seersholm, H. Schroeder, C. Gaunitz, J. Stenderup, L. Vinner, T. C. Jones, B. Nystedt, J. Parkhill, L. Fugger, F. Racimo, K. Kristiansen, A. K. N. Iversen, and E. Willerslev, "The landscape of ancient human pathogens in Eurasia from the Stone Age to historical times," Cold Spring Harbor Laboratory, 10 2023.

[58] D. Li, C.-M. Liu, R. Luo, K. Sadakane, and T.-W. Lam, "MEGAHIT: an ultra-fast single-node solution for large and complex metagenomics assembly via succinct de Bruijn graph," Bioinformatics, vol. 31, p. 1674–1676, 1 2015.

[59] S. Nurk, D. Meleshko, A. Korobeynikov, and P. A. Pevzner, "metaSPAdes: a new versatile metagenomic assembler," Genome Research, vol. 27, p. 824–834, 3 2017.

[60] Z. Li, Y. Chen, D. Mu, J. Yuan, Y. Shi, H. Zhang, J. Gan, N. Li, X. Hu, B. Liu, B. Yang, and W. Fan, "Comparison of the two major classes of assembly algorithms: overlap-layout-consensus and de-bruijn-graph," Briefings in Functional Genomics, vol. 11, p. 25–37, 12 2011.

[61] B. Haider, T.-H. Ahn, B. Bushnell, J. Chai, A. Copeland, and C. Pan, "Omega: an Overlap-graphde novoAssembler for Metagenomics," Bioinformatics, vol. 30, p. 2717–2722, June 2014.

[62] A. Jochheim, F. A. Jochheim, A. Kolodyazhnaya, É. Morice, M. Steinegger, and J. Söding, "Strain-resolved de-novo metagenomic assembly of viral genomes and microbial 16S rRNAs," Microbiome, vol. 12, Oct. 2024.

[63] V. Raghavan, L. Kraft, F. Mesny, and L. Rigerte, "A simple guide to de novo transcriptome assembly and annotation," Briefings in Bioinformatics, vol. 23, 1 2022.

[64] A. Bankevich, S. Nurk, D. Antipov, A. A. Gurevich, M. Dvorkin, A. S. Kulikov, V. M. Lesin, S. I. Nikolenko, S. Pham, A. D. Prjibelski, A. V. Pyshkin, A. V. Sirotkin, N. Vyahhi,

G. Tesler, M. A. Alekseyev, and P. A. Pevzner, "SPAdes: A New Genome Assembly Algorithm and Its Applications to Single-Cell Sequencing," Journal of Computational Biology, vol. 19, p. 455–477, 5 2012.

[65] M. Steinegger, M. Mirdita, and J. Söding, "Protein-level assembly increases protein sequence recovery from metagenomic samples manyfold," Nature Methods, vol. 16, p. 603–606, 6 2019.

[66] S. Whelan, J. E. Allen, B. P. Blackburne, and D. Talavera, "ModelOMatic: Fast and Automated Model Selection between RY, Nucleotide, Amino Acid, and Codon Substitution Models," Systematic Biology, vol. 64, p. 42–55, 9 2014.

[67] A. Lien, L. P. Legori, L. Kraft, P. W. Sackett, and G. Renaud, "Benchmarking software tools for trimming adapters and merging next-generation sequencing data for ancient DNA," Frontiers in Bioinformatics, vol. 3, Dec. 2023.

[68] M. Steinegger and J. Söding, "Clustering huge protein sequence sets in linear time," Nature Communications, vol. 9, 6 2018.

[69] C. Der Sarkissian, L. Ermini, H. Jónsson, A. N. Alekseev, E. Crubezy, B. Shapiro, and L. Orlando, "Shotgun microbial profiling of fossil remains," Molecular Ecology, vol. 23, p. 1780–1798, 3 2014.

[70] A. Mikheenko, V. Saveliev, and A. Gurevich, "MetaQUAST: evaluation of metagenome assemblies," Bioinformatics, vol. 32, p. 1088–1090, 11 2015.

[71] B. Langmead and S. L. Salzberg, "Fast gapped-read alignment with Bowtie 2," Nature Methods, vol. 9, p. 357–359, 3 2012.

[72] H. Li, B. Handsaker, A. Wysoker, T. Fennell, J. Ruan, N. Homer, G. Marth, G. Abecasis, and R. Durbin, "The Sequence Alignment/Map format and SAMtools," Bioinformatics, vol. 25, p. 2078–2079, 6 2009.

[73] J. Shaw and Y. W. Yu, "Fast and robust metagenomic sequence comparison through sparse chaining with skani," Nature Methods, vol. 20, p. 1661–1665, Sept. 2023.

[74] S. Commichaux, N. Shah, J. Ghurye, A. Stoppel, J. A. Goodheart, G. G. Luque, M. P. Cummings, and M. Pop, "A critical assessment of gene catalogs for metagenomic analysis," Bioinformatics, vol. 37, p. 2848–2857, Apr. 2021.

[75] T. Seemann, "Prokka: rapid prokaryotic genome annotation," Bioinformatics, vol. 30, p. 2068–2069, 3 2014.

[76] M. Steinegger and J. Söding, "MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets," Nature Biotechnology, vol. 35, p. 1026–1028, 10 2017.

[77] H. Li, "Protein-to-genome alignment with miniprot," <u>Bioinformatics</u>, vol. 39, Jan. 2023.

[78] B. E. Suzek, Y. Wang, H. Huang, P. B. McGarvey, and C. H. Wu, "UniRef clusters: a comprehensive and scalable alternative for improving sequence similarity searches," <u>Bioinformatics</u>, vol. 31, p. 926–932, 11 2014.

[79] F. A. B. von Meijenfeldt, K. Arkhipova, D. D. Cambuy, F. H. Coutinho, and B. E. Dutilh, "Robust taxonomic classification of uncharted microbial sequences and bins with CAT and BAT," <u>Genome Biology</u>, vol. 20, Oct. 2019.

[80] D. H. Parks, M. Chuvochina, D. W. Waite, C. Rinke, A. Skarshewski, P.-A. Chaumeil, and P. Hugenholtz, "A standardized bacterial taxonomy based on genome phylogeny substantially revises the tree of life," <u>Nature Biotechnology</u>, vol. 36, p. 996–1004, 8 2018.

[81] D. T. Truong, E. A. Franzosa, T. L. Tickle, M. Scholz, G. Weingart, E. Pasolli, A. Tett, C. Huttenhower, and N. Segata, "MetaPhlAn2 for enhanced metagenomic taxonomic profiling," <u>Nature Methods</u>, vol. 12, p. 902–903, Sept. 2015.

[82] J. S. Johnson, D. J. Spakowicz, B.-Y. Hong, L. M. Petersen, P. Demkowicz, L. Chen, S. R. Leopold, B. M. Hanson, H. O. Agresta, M. Gerstein, E. Sodergren, and G. M. Weinstock, "Evaluation of 16S rRNA gene sequencing for species and strain-level microbiome analysis," <u>Nature Communications</u>, vol. 10, Nov. 2019.

[83] C. J. Adler, K. Dobney, L. S. Weyrich, J. Kaidonis, A. W. Walker, W. Haak, C. J. A. Bradshaw, G. Townsend, A. Sołtysiak, K. W. Alt, J. Parkhill, and A. Cooper, "Sequencing ancient calcified dental plaque shows changes in oral microbiota with dietary shifts of the Neolithic and Industrial revolutions," <u>Nature Genetics</u>, vol. 45, p. 450–455, Feb. 2013.

[84] S. Luciani, G. Fornaciari, O. Rickards, C. M. Labarga, and F. Rollo, "Molecular characterization of a pre-Columbian mummy and in situ coprolite," <u>American Journal of Physical Anthropology</u>, vol. 129, p. 620–629, Dec. 2005.

[85] F. Rollo, S. Luciani, I. Marota, C. Olivieri, and L. Ermini, "Persistence and decay of the intestinal microbiota's DNA in glacier mummies from the Alps," <u>Journal of Archaeological Science</u>, vol. 34, p. 1294–1305, Aug. 2007.

[86] M. Ubaldi, S. Luciani, I. Marota, G. Fornaciari, R. J. Cano, and F. Rollo, "Sequence analysis of bacterial DNA in the colon of an Andean mummy," <u>American Journal of Physical Anthropology</u>, vol. 107, p. 285–295, Nov. 1998.

[87] C. Warinner, J. F. M. Rodrigues, R. Vyas, C. Trachsel, N. Shved, J. Grossmann, A. Radini, Y. Hancock, R. Y. Tito, S. Fiddyment, C. Speller, J. Hendy, S. Charlton, H. U. Luder,

D. C. Salazar-García, E. Eppler, R. Seiler, L. H. Hansen, J. A. S. Castruita, S. Barkow-Oesterreicher, K. Y. Teoh, C. D. Kelstrup, J. V. Olsen, P. Nanni, T. Kawai, E. Willerslev, C. von Mering, C. M. Lewis, M. J. Collins, M. T. P. Gilbert, F. Rühli, and E. Cappellini, "Pathogens and host immunity in the ancient human oral cavity," Nature Genetics, vol. 46, p. 336–344, Feb. 2014.

[88] R. Y. Tito, D. Knights, J. Metcalf, A. J. Obregon-Tito, L. Cleeland, F. Najar, B. Roe, K. Reinhard, K. Sobolik, S. Belknap, M. Foster, P. Spicer, R. Knight, and C. M. Lewis, "Insights from Characterizing Extinct Human Gut Microbiomes," PLoS ONE, vol. 7, p. e51146, Dec. 2012.

[89] K. A. Ziesemer, A. E. Mann, K. Sankaranarayanan, H. Schroeder, A. T. Ozga, B. W. Brandt, E. Zaura, A. Waters-Rist, M. Hoogland, D. C. Salazar-García, M. Aldenderfer, C. Speller, J. Hendy, D. A. Weston, S. J. MacDonald, G. H. Thomas, M. J. Collins, C. M. Lewis, C. Hofman, and C. Warinner, "Intrinsic challenges in ancient microbiome reconstruction using 16S rRNA gene amplification," Scientific Reports, vol. 5, Nov. 2015.

[90] P. Yarza, P. Yilmaz, E. Pruesse, F. O. Glöckner, W. Ludwig, K.-H. Schleifer, W. B. Whitman, J. Euzéby, R. Amann, and R. Rosselló-Móra, "Uniting the classification of cultured and uncultured bacteria and archaea using 16S rRNA gene sequences," Nature Reviews Microbiology, vol. 12, p. 635–645, Aug. 2014.

[91] B. J. Tindall, R. Rosselló-Móra, H.-J. Busse, W. Ludwig, and P. Kämpfer, "Notes on the characterization of prokaryote strains for taxonomic purposes," International Journal of Systematic and Evolutionary Microbiology, vol. 60, p. 249–266, Jan. 2010.

[92] R. A. Barco, G. M. Garrity, J. J. Scott, J. P. Amend, K. H. Nealson, and D. Emerson, "A genus definition for bacteria and archaea based on a standard genome relatedness index," mBio, vol. 11, Feb. 2020.

[93] M. Borry, A. Hübner, A. B. Rohrlach, and C. Warinner, "PyDamage: automated ancient damage identification and estimation for contigs in ancient DNA de novo assembly," PeerJ, vol. 9, p. e11845, July 2021.

[94] R. C. Edgar, "Updating the 97% identity threshold for 16S ribosomal RNA OTUs," Bioinformatics, vol. 34, p. 2371–2375, Feb. 2018.

[95] K. Blin, S. Shaw, H. E. Augustijn, Z. L. Reitz, F. Biermann, M. Alanjary, A. Fetter, B. R. Terlouw, W. W. Metcalf, E. J. N. Helfrich, G. P. van Wezel, M. H. Medema, and T. Weber, "antiSMASH 7.0: new and improved predictions for detection, regulation, chemical structures and visualisation," Nucleic Acids Research, vol. 51, p. W46–W50, May 2023.

[96] K. Blin, S. Shaw, K. Steinke, R. Villebro, N. Ziemert, S. Y. Lee, M. H. Medema, and T. Weber, "antiSMASH 5.0: updates to the secondary metabolite genome mining pipeline," Nucleic Acids Research, vol. 47, p. W81–W87, Apr. 2019.

[97] N. Stoler and A. Nekrutenko, "Sequencing error profiles of Illumina sequencing instruments," NAR Genomics and Bioinformatics, vol. 3, Jan. 2021.

[98] Q. Zhou, X. Su, and K. Ning, "Assessment of quality control approaches for metagenomic data analysis," Scientific Reports, vol. 4, Nov. 2014.

[99] B. E. Slatko, A. F. Gardner, and F. M. Ausubel, "Overview of Next-Generation Sequencing Technologies," Current Protocols in Molecular Biology, vol. 122, Apr. 2018.

[100] S. Sawyer, J. Krause, K. Guschanski, V. Savolainen, and S. Pääbo, "Temporal Patterns of Nucleotide Misincorporations and DNA Fragmentation in Ancient DNA," PLoS ONE, vol. 7, p. e34131, Mar. 2012.

[101] I. Glocke and M. Meyer, "Extending the spectrum of DNA sequences retrieved from ancient bones and teeth," Genome Research, vol. 27, p. 1230–1237, Apr. 2017.

[102] I. Jackson, P. Woodman, M. Dowd, L. Fibiger, and L. M. Cassidy, "Ancient Genomes From Bronze Age Remains Reveal Deep Diversity and Recent Adaptive Episodes for Human Oral Pathobionts," Molecular Biology and Evolution, vol. 41, Mar. 2024.

[103] M. G. Durrant, M. M. Li, B. A. Siranosian, S. B. Montgomery, and A. S. Bhatt, "A Bioinformatic Analysis of Integrative Mobile Genetic Elements Highlights Their Role in Bacterial Adaptation," Cell Host & Microbe, vol. 27, pp. 140–153.e9, 1 2020.

[104] M. Sheinman, K. Arkhipova, P. F. Arndt, B. E. Dutilh, R. Hermsen, and F. Massip, "Identical sequences found in distant genomes reveal frequent horizontal transfer across the bacterial domain," eLife, vol. 10, 6 2021.

[105] B. Buchfink, K. Reuter, and H.-G. Drost, "Sensitive protein alignments at tree-of-life scale using DIAMOND," Nature Methods, vol. 18, p. 366–368, Apr. 2021.

[106] S. Dolenz, T. van der Valk, C. Jin, J. Oppenheimer, M. B. Sharif, L. Orlando, B. Shapiro, L. Dalén, and P. D. Heintzman, "Unravelling reference bias in ancient DNA datasets," Bioinformatics, vol. 40, July 2024.

[107] C. R. Woese and G. E. Fox, "Phylogenetic structure of the prokaryotic domain: The primary kingdoms," Proceedings of the National Academy of Sciences, vol. 74, p. 5088–5090, Nov. 1977.

[108] S. Sanschagrin and E. Yergeau, "Next-generation Sequencing of 16S Ribosomal RNA Gene Amplicons," Journal of Visualized Experiments, Aug. 2014.

[109] S. Kameoka, D. Motooka, S. Watanabe, R. Kubo, N. Jung, Y. Midorikawa, N. O. Shinozaki, Y. Sawai, A. K. Takeda, and S. Nakamura, "Benchmark of 16S rRNA gene amplicon sequencing using Japanese gut microbiome data from the V1–V2 and V3–V4 primer sets," BMC Genomics, vol. 22, July 2021.

[110] R. Eisenhofer, S. Wright, and L. Weyrich, "Benchmarking a targeted 16S ribosomal RNA gene enrichment approach to reconstruct ancient microbial communities," PeerJ, vol. 12, p. e16770, Mar. 2024.

[111] C. Yuan, J. Lei, J. Cole, and Y. Sun, "Reconstructing 16S rRNA genes in metagenomic data," Bioinformatics, vol. 31, p. i35–i43, June 2015.

[112] C. S. Miller, B. J. Baker, B. C. Thomas, S. W. Singer, and J. F. Banfield, "EMIRGE: reconstruction of full-length ribosomal genes from microbial community short read sequencing data," Genome Biology, vol. 12, May 2011.

[113] R. Rizzi, S. Beretta, M. Patterson, Y. Pirola, M. Previtali, G. Della Vedova, and P. Bonizzoni, "Overlap graphs and de Bruijn graphs: data structures for de novogenome assembly in the big data era," Quantitative Biology, vol. 7, p. 278–292, Dec. 2019.

[114] M.-T. Gansauge and M. Meyer, "Selective enrichment of damaged DNA molecules for ancient genome sequencing," Genome Research, vol. 24, p. 1543–1549, 7 2014.

[115] G. Renaud, K. Hanghøj, E. Willerslev, and L. Orlando, "gargammel: a sequence simulator for ancient DNA," Bioinformatics, vol. 33, p. 577–579, 11 2016.

[116] G. Renaud, U. Stenzel, and J. Kelso, "leeHom: adaptor trimming and merging for Illumina sequencing reads," Nucleic Acids Research, vol. 42, p. e141–e141, 8 2014.

[117] D. Hyatt, G.-L. Chen, P. F. LoCascio, M. L. Land, F. W. Larimer, and L. J. Hauser, "Prodigal: prokaryotic gene recognition and translation initiation site identification," BMC Bioinformatics, vol. 11, 3 2010.

[118] A. Bateman, M.-J. Martin, S. Orchard, M. Magrane, R. Agivetova, S. Ahmad, E. Alpi, E. H. Bowler-Barnett, R. Britto, B. Bursteinas, H. Bye-A-Jee, R. Coetzee, A. Cukura, A. Da Silva, P. Denny, T. Dogan, T. Ebenezer, J. Fan, L. G. Castro, P. Garmiri, G. Georghiou, L. Gonzales, E. Hatton-Ellis, A. Hussein, A. Ignatchenko, G. Insana, R. Ishtiaq, P. Jokinen, V. Joshi, D. Jyothi, A. Lock, R. Lopez, A. Luciani, J. Luo, Y. Lussi, A. MacDougall, F. Madeira, M. Mahmoudy, M. Menchi, A. Mishra, K. Moulang, A. Nightingale, C. S. Oliveira, S. Pundir, G. Qi, S. Raj, D. Rice, M. R. Lopez, R. Saidi, J. Sampson, T. Sawford, E. Speretta, E. Turner, N. Tyagi, P. Vasudev, V. Volynkin, K. Warner, X. Watkins, R. Zaru, H. Zellner, A. Bridge, S. Poux, N. Redaschi, L. Aimo, G. Argoud-Puy, A. Auchincloss, K. Axelsen, P. Bansal, D. Baratin, M.-C. Blatter, J. Bolleman, E. Boutet, L. Breuza,

C. Casals-Casas, E. de Castro, K. C. Echioukh, E. Coudert, B. Cuche, M. Doche, D. Dornevil, A. Estreicher, M. L. Famiglietti, M. Feuermann, E. Gasteiger, S. Gehant, V. Gerritsen, A. Gos, N. Gruaz-Gumowski, U. Hinz, C. Hulo, N. Hyka-Nouspikel, F. Jungo, G. Keller, A. Kerhornou, V. Lara, P. Le Mercier, D. Lieberherr, T. Lombardot, X. Martin, P. Masson, A. Morgat, T. B. Neto, S. Paesano, I. Pedruzzi, S. Pilbout, L. Pourcel, M. Pozzato, M. Pruess, C. Rivoire, C. Sigrist, K. Sonesson, A. Stutz, S. Sundaram, M. Tognolli, L. Verbregue, C. H. Wu, C. N. Arighi, L. Arminski, C. Chen, Y. Chen, J. S. Garavelli, H. Huang, K. Laiho, P. McGarvey, D. A. Natale, K. Ross, C. R. Vinayaka, Q. Wang, Y. Wang, L.-S. Yeh, J. Zhang, P. Ruch, and D. Teodoro, "UniProt: the universal protein knowledgebase in 2021," Nucleic Acids Research, vol. 49, p. D480–D489, 11 2020.

[119] C. Quast, E. Pruesse, P. Yilmaz, J. Gerken, T. Schweer, P. Yarza, J. Peplies, and F. O. Glöckner, "The SILVA ribosomal RNA gene database project: improved data processing and web-based tools," Nucleic Acids Research, vol. 41, p. D590–D596, Nov. 2012.

[120] N. Stoler and A. Nekrutenko, "Sequencing error profiles of Illumina sequencing instruments," NAR Genomics and Bioinformatics, vol. 3, 1 2021.