MyVivarium: A cloud-based lab animal colony management application with near-

realtime ambient sensing

Robinson Vidva[a], Mir Abbas Raza[b], Jaswant Prabhakaran[c], Ayesha Sheikh[b], Alaina Sharp[b],

Hayden Ott[b], Amelia Moore[b], Christopher Fleisher[b], Pothitos M. Pitychoutis[b], Tam V. Nguyen[c],

and Aaron Sathyanesan[b,d] *

[a] Digirobi Solutions, Bengaluru, Karnataka, India

[b] Department of Biology, College of Arts & Sciences, University of Dayton, Dayton, OH, USA

[c] Department of Computer Science, College of Arts & Sciences, University of Dayton, Dayton,

OH, USA

[d] Department of Electrical and Computer Engineering, School of Engineering, University of

Dayton, Dayton, OH, USA

*Corresponding author:

Aaron Sathyanesan, PhD

Contact email: asathyanesan1@udayton.edu

Address: 300 College Park, Dayton, OH, USA

ABSTRACT

Research-animal colony management is a critical determinant of scientific productivity in labs

conducting preclinical research. However, labs generally use *ad hoc* paper-based or

spreadsheet-based methods to manage animal colonies. Current software-based solutions are

limited based on cost, ease of implementation and deployment, and lack of remote access. In

addition, most current solutions lack integration of realtime monitoring of ambient variables that

affect colony wellbeing and breeding efficiency. Keeping these functionalities in mind, we built

MyVivarium – a cloud-based animal colony database management web application that can be

easily deployed and sustained for a cost comparable to starting and maintaining a lab website.

For mouse colony management, MyVivarium allows for the tracking of individual mice or litters

within holding-cage and breeding-cage records by multiple users at designated levels of access.

Physical identities of cages are mapped onto the database using printable cage-card templates

with cage-specific QR codes, enabling quick record updating using mobile devices. Tasks can

be easily assigned with reminders for experiments or cage maintenance. Finally, MyVivarium

integrates near-realtime internet-of-things (IoT)-based ambient sensing using low-cost open-

source hardware to track humidity, temperature, vivarium-worker activity, and room illuminance.

Taken together, MyVivarium is a novel open-source cloud-based application template that can

serve as a low-cost, simple, and efficient solution for digital management of research animal

colonies**.**

KEYWORDS: vivarium, colony management, mouse colony, mouse facility, open-source

technology, IoT sensors, biological database.

INTRODUCTION

Animal colony management is a routine task performed by many laboratories that use model systems to answer biological research questions. Many labs that use rats or mice as a model system often are responsible for animal husbandry and well-being of the animal subjects under their purview. This can result in the day-to-day management of hundreds of animal cages per lab. While technological solutions have been widely adopted in other areas of routine lab tasks ranging from scientific data management to chemical inventory, animal colony management has remained fairly insulated from adoption of information management systems. Although large mouse repositories often invest in software solutions to increase efficiency in mouse colony management, barriers remain in the average academic lab choosing a dedicated software-based solution (Maier et al., 2015).

With the steadily increasing *per diem* costs of maintaining rodent research colonies ("Per Diem Animal Housing Rates | Boston University Office of Research," 2016), efficient handling of resources is an increasing concern. This is especially true for new and early career principal investigators (PIs) who typically transition from independent bench research to a management-heavy role. Typical start-up budgets for new PIs prioritize big-ticket equipment purchases, personnel costs (Dolgin, 2018), and may even include statistical software costs, however, research management tools and applications are not usually given much consideration, with a dedicated laboratory information management system (LIMS) often being designated a luxury add-on. Given the significantly high prices of commercially available LIMS, this lack of consideration may seem justified. Further, it is often surmised that animal colony management can be accomplished *ad hoc*. While large-scale survey data of mouse researchers is lacking, anecdotal evidence from the collective research experiences of the authors of this manuscript indicate that most solutions for mouse colony management generally take the form of a spreadsheet using *Microsoft Excel* or *Google Sheets* which are regularly updated in a semi-

collaborative manner. During a typical colony inspection, a researcher would visit the vivarium,

which is often separated in location from the main area of the lab, carrying along a paper copy

of the colony cage list. Following routine updates to the paper list, this information is then soft-

copy transcribed at a later time since directly updating spreadsheet entries in the vivarium while

monitoring mouse cages may not be as portable-device-friendly. Information directly related to a

particular strain, such as genotype visualized on a gel image, is usually maintained separately in

a lab notebook. While many labs have *de facto* adapted this general form of mouse colony data

management, this method is cumbersome and has multiple points of failure due to its reliance

on disparate tools and the lack of an integrated framework.

Rodent strains used in preclinical research as model systems of disease have genetic or

chromosomal modifications that often make them more sensitive to changes in ambient

temperature, relative humidity, and light (Chesler et al., 2002; Jaric et al., 2022; Kudo et al.,

2019; Richter et al., 2011). In addition, human presence or foot traffic may also negatively affect

genetically or chromosomally modified mouse strains. Consequently, alterations in these

vivarium ambient factors can result in reduced colony productivity and breeding efficiency as

well as general colony wellbeing. In-house vivarium staff usually perform routine checks on

these ambient factors – however, since these checks are only performed once or twice a day,

alterations in ambient factors that occur between inspection windows or outside normal working

hours may be missed. Sudden unexplained losses in colony breeding performance can cause

significant delays in experimental timelines and decreased return-on-investment. The effects of

lab animal colony related disruption can potentially be disproportionately worse for early-career

PIs compared to mid-career or senior PIs since earlier success in terms of research output for

new PIs may be predictive of successful grant proposals during this stage. Commercial

solutions to monitor ambient factors in rodent colonies do exist, however, these are significantly

cost-prohibitive. A cost-effective colony-management solution that can also track alterations in

ambient environmental factors would thus be of significant benefit.

The advent of the modern web has brought with it ever-improving tools for rapid and remote

management of scientific data (Hall and Tiropanis, 2012; Wood et al., 2014). Leveraging the

decreasing cost and increasing ease of modern web development, early career researchers

have become conversant with designing websites for sharing their research programs (Mishra,

2020). We reasoned that if the barrier to entry for using a rodent colony management system

were reduced to the level of launching and maintaining a laboratory website, this would increase

the adoption of such a system.

Recently, a few open source database applications for rodent colony management solutions

have been introduced (Pawar and Batra, 2018; Renschen et al., 2020). However, these systems

were primarily implemented to run on local servers and networks, limiting their access especially

in situations of contingency (Chambliss and Tolan, 2020; Gao et al., 2021). While these

solutions can be moved to the internet, it is not trivial to do this securely and seamlessly. For

someone such as a bench-biologist with limited knowledge of web development, this is

especially difficult to carry out. Further, to our knowledge, no open-source solution for lab animal

colony management has integrated ambient sensing. In this manuscript, we describe the design

of *MyVivarium* – an open-source application framework for lab animal colony management with

cloud-based access as the primary starting point. We built MyVivarium using a PHP-based

technology stack running on a managed cloud-hosted virtual private server. Importantly, we

prioritized cost by using an inexpensive server option (~$6 USD per month for 1GB RAM, 25GB

SSD, 1 TB Transfer, 1 Core Processor), however, application performance was not affected

with overall server CPU usage being relatively low. MyVivarium enables all the necessary

standard operating procedures for vivarium maintenance including cage and mouse record

maintenance with the ability to generate QR-code-enhanced cage cards for easy mobile access

and tracking. In order to efficiently track experiments linked to mice in specific cages, tasks and

reminder can be set up with designated researchers assigned to these tasks. Finally, we

describe the assembly and integration of automated low-cost Raspberry-Pi-IoT ambient sensing

monitoring sensors which continuously stream temperature, humidity, illuminance, and vivarium

room activity data to MyVivarium in near-realtime. Fluctuations in ambient environmental factors

based on user-defined thresholds and time-windows trigger automated alerts that are sent via a

chat message to designated personnel. MyVivarium is thus a complete open-source solution for

cost-efficient cloud-based lab animal colony management suitable for academic research labs

as well as vivarium management staff.

RESULTS

We built MyVivarium using modern web technologies for both server-side and client-side

operations (**Figure 1**). The backend uses *PHP* for server-side scripting and *MySQL* for

database management. The front end utilizes *HTML*, *CSS*, and *JavaScript*, including the

Bootstrap framework for responsive design and user interface components. *Composer* is

employed for dependency management, incorporating libraries such as *PHPMailer* for email

functionalities and *Dotenv* for environment variable management.

Key features of MyVivarium include user registration and profile management, lab and cage

management, real-time ambient sensing with internet-of-things (IoT) sensors, notes

management, tasks and reminders, email notifications, and print cage card functionality (**Figure**

2). The application supports secure session handling, cross-site request forgery (CSRF)

protection, and role-based access controls. The user management functionality includes

features for registration, login, profile management, email verification, and password reset via

email. Lab and cage management modules enable users to add, view, edit, and delete breeding

and holding cages. Each module provides detailed information about the cages, including

associated litter and mouse data. Additionally, users can manage strains by adding, editing, and

deleting strain records. We have shared all necessary code and a how-to guide in a public

repository (https://github.com/myvivarium/MyVivarium) for users to get their specific MyVivarium

web applications set up according to their particular needs and requirements. We have also

included a link to a demo website in the repository to showcase the different functionalities

within MyVivarium (https://demo.myvivarium.online/).

Cage, mouse, and litter management forms the core of MyVivarium (**Supplemental Figure 1**).

We designed the database architecture using active feedback from vivarium workers over the

course of development of MyVivarium. The MyVivarium database includes the `cages` table

which forms a core part of the architecture and contains essential information about each cage,

including the cage ID, the name of the principal investigator, the number of mice, and any

specific remarks linked to a cage (**Supplemental Figure 1**). Linked to this core table is the

`users` table, which holds necessary information about users, including their role within the lab,

position or designation, and MyVivarium access approval status. This ensures that each cage

can be associated with specific users, facilitating proper access and management of

responsibilities. The `holding` table stores essential information about individual mice in holding

cages, including their strain, date of birth, sex, and parent cage. This table ensures that all

necessary details about each holding cage are recorded systematically. The `mouse` table stores

detailed information about individual mice within the holding cages. The database architecture

for breeding cages in MyVivarium includes the `breeding` table which contains information

about each breeding pair, including their source cage IDs, type of cross, male and female IDs,

and their dates of birth. Linked to this table is the `litters` table which records details about

offspring, such as the number of pups per litter, number of surviving pups, sex, and any other

relevant remarks. This setup enables monitoring and analysis of breeding outcomes per cage.

The `strains` table contains information about various strains of mice including strain IDs,

names, and other identifiers, enabling tracking of different genetic lines. In order to link

documentation related to the institutional animal care and use committee (IACUC) to specific

strains, we also included an `iacuc` table. This enables better integration of IACUC-related tasks

to help with the preparation of compliance and animal usage reports. Additional tables, including

`files` and `notes`, support the documentation and communication needs within MyVivarium.

The `files` table stores metadata about uploaded documents, while the `notes` table enables

users to record observations and updates related to specific cages or mice. The `tasks` table

manages tasks and assignments, tracks their status, and enables increased efficiency for time-

sensitive vivarium tasks in the range of days-to-months. For more day-to-day tasks such as

cage-changes and regular maintenance, we included a `maintenance` table to enable quick

recording of maintenance logs. Finally, the schema also includes the `cage_iacuc` and

`cage_users` tables to establish relationships between cages, IACUC protocols, and users.

Together, these tables create a robust framework for vivarium workers to manage and track

details of holding cages and the individual mice within them as well as breeding cages and the

breeders and litters within them.

From a user-experience perspective, once approved users are logged in to their lab's

MyVivarium, holding and breeding cages are accessible in the web application via the

"Dashboards" menu (**Supplemental videos 1-4** [desktop]**, 5-8** [smartphone]). Within the holding

cage dashboard, new holding cages can be added using the "+" icon. The cage and mouse

characteristics can be added based on the features mentioned previously under the database

architecture. Individual cages can be viewed ("eye" icon), edited ("pencil/writing" icon)

(**Supplemental video 9**), or deleted ("trash can" icon) (**Supplemental video 10**). Under the

view menu, cage and mouse details can be viewed, along with a helpful "Sticky note" feature to

note any special remarks regarding the cage or mice. Under the edit menu, individual cage or

mouse characteristics or features can be edited and saved. We also included separate notes

specific to individual mice which can be helpful when mice are earmarked for experiments or to

note any odd behaviors or health issues for individual mice that may need follow-up. The

"Maintenance logs" feature captures quick day-to-day entry logs for cage changes and other

routine maintenance tasks (**Supplemental videos 11-12**). This feature can be used for multiple

cages on the same page. An upload feature can be used to upload any files pertinent to the

cage or individual mice such as genotyping gel image data (**Supplemental videos 13-14**). The

breeding cage menu also has similar buttons within it with distinct editability for features that are

different from holding cages such as litter and breeder mouse details (**Supplemental videos**

15-16). For both holding and breeding mouse cages, we have included a feature that

conveniently generates cage cards on ready-to-print templates (**Supplemental Figure 2a,**

Supplemental videos 17-18). Each cage card template has a QR code that links it to its

MyVivarium record (**Supplemental video 19**). Our print feature allows cage cards to be readily

printed using a standard laser or deskjet printer on commercially available cardstock with 3" x 5"

perforations (4 per page) that can then easily fit in standard cage card holders (**Supplemental**

Figure 2b).

Since vivarium work is closely linked to planning and scheduling experiments, we designed a

"Tasks" feature to enable further integration of colony management into research projects.

Individual tasks can be added using the "Manage tasks" menu under settings (**Supplemental**

videos 20-21). We used an intuitive design to assign tasks to specific researchers and link

these tasks to particular cages, with the option of adding due dates. Email reminders related to

tasks can be sent at user-defined frequencies. Once the user is logged in to their lab's

MyVivarium site, tasks appear on the homepage in a form similar to a Kanban board which can

significantly enhance efficiency and productivity in project management (Jacobs et al., 2022).

Recently, the relationship between ambient housing conditions of rodents used in research

studies and potential confounding effects on metabolism and physiology has attracted much

attention (Corrigan et al., 2020; Ganeshan and Chawla, 2017; Unger et al., 2023). It is important

to monitor ambient environmental factors since fluctuations in these factors can inadvertently

alter animal health and behavioral responses, potentially skewing data, which would be of

particular relevance to studies in neuroscience, endocrinology, physiology, and metabolism

research. We designed and assembled a standalone open-source IoT-based multi-sensor

system that is capable of monitoring temperature, humidity, illuminance, and vivarium worker

activity, and feed this data directly into MyVivarium. We used inexpensive but accurate Inter-

Integrated Circuit (I^2C) sensors to enable the monitoring of ambient factors (**Figure 3a-b**) that

can have an effect on colony wellbeing, metabolism, and physiology.

Harnessing the ability of I^2C sensors (targets) with unique addresses to communicate with a

controller board synchronously, we serially connected a SHT30 (temperature and humidity),

VL53L1X (proximity), and a VEML7700 (illuminance) sensor, each equipped with its own inbuilt

pull-up resistor, to a Raspberry Pi 4B. We deployed a total of three sensor module sets (two in

each of the vivarium rooms assigned to AS, and one in the vivarium room assigned to PP). In all

three deployments, we placed the assembled sensor modules in the vivarium rooms in a

configuration similar to that shown in **Figure 3c**. We used custom python scripts to record

ambient factors from data transmitted to the Pi, including temperature (ºC), relative humidity

(%), illuminance (lux), and vivarium worker-to-sensor proximity (cm) which is a proxy for

vivarium worker presence or activity. We then used docker containers in IOTstack (SensorsIOT,

2024) to log sensor data to an InfluxDB database and visualize sensor datastreams using

Grafana. We registered a low-cost domain name and used a Cloudflare tunnel to expose the

local Grafana application to be accessible through this domain. We embedded the Grafana

dashboard into MyVivarium using the inline frame element (iframe).

Using our Pi-IoT system we have been able to record near-realtime ambient factor data

continuously for months (**Figure 4**). In our Grafana dashboard we marked the maximum ("max")

and minimum ("min") temperature (18-26ºC) and relative humidity (30-70%) as recommended

by *The Guide*, an authoritative publication issued by the office of laboratory animal welfare

(OLAW), which is a part of the National Institutes of Health (NIH) (National Research Council,

2011), and the Jackson Laboratory, a non-profit mouse repository ("Mouse Room Conditions |

The Jackson Laboratory," 2023) for easy identification and reporting of alterations in these

conditions. In general, temperature stayed within the recommended window (**Figure 4a:** data

from four months, **Figure 4b**: data denoted in **Figure 4a** with arrows and grey bars from May 2nd

2024), however, on few occasions across four months, relative humidity had short transient

increases above the recommended maximum of 70% (**Figure 4c**). In general, increases in

humidity seemed to follow the trend of relative humidity in Dayton, OH (**Figure 4c**, grey plot),

with prolonged increases in external environmental humidity preceding transient spikes in

vivarium rooms 1 (**Figure 4c**, **blue**) and 2 (**Figure 4c**, **orange**). Our illuminance sensor

placements were able to effectively capture lights ON and OFF in rooms 1 and 2 (**Figure 4e-f**).

Our proximity sensors were also able to detect activity in both rooms as inverted spikes (**Figure**

4g-h).

Using our system, we were able to monitor changes in ambient temperature, humidity, and

illuminance (**Supplemental videos 22-23**). In response to increased humidity that was

observed for a specific day (**Figure 5a**), we reported this to all users of our MyVivarium as a

general message using "Sticky Notes" (**Figure 5b**). While this is an easy way to notify users of

any abnormal events, it requires users to actively monitor the dashboard values. Our

illuminance sensor values on March 12th 2024 indicated that the lights in room 1 did not come

ON as usual (**Figure 4e, asterisk**) due to an erroneous manual override of the automated light

cycle. This error had not been identified and rectified till later that day. In order to reduce the

likelihood of such events that could significantly alter the mood and wellbeing of mice, we set up

an automated alerting system. We used the alerting system within Grafana to define thresholds

for illuminance sensor values. We set two separate alert rules to fire corresponding to abnormal

events within distinct phases of the light cycle i.e. lights ON > 15 minutes during the 6 PM – 6

AM window and lights OFF > 15 minutes during the 6 AM – 6 PM window. After confirming that

the alert was working within Grafana, we created a dedicated Google space to receive alerts via

an integrated webhook. The webhook application program interface (API) is then used by the

Grafana alerting system to send a predefined chat message with a link to the dashboard directly

into the Google space when the alert fires ("Build a Google Chat app as a webhook | Google

for Developers," 2023). We tested our alerting system by blocking light entry to the illuminance

sensor using black unreflective paper and were able to successfully receive alerts to the google

space (**Figure *5*c-d, Supplemental video 24**). We have provided all code

(https://github.com/myvivarium/RPi-IoT) and documentation (https://github.com/myvivarium/RPi-

IoT/wiki) needed to set up our RPi-IoT system. An example snapshot of our Grafana interactive

dashboard can be found here:

https://snapshots.raintank.io/dashboard/snapshot/BS9oMWCz8rpT2H3xoGVoHyDHSobyJrrW

For admin-related tasks, we used a tier-based approach to control management access to

MyVivarium. Typically, when setting up MyVivarium for the first time, a PI or lab

director/manager would designate themselves as an administrator (admin-tier, full access) and

delegate one or a few key personnel as admins (admin-tier, full access) (**Supplemental video**

25). This enables distributive administration to increase efficiency of approving authorized

users, determining access levels, and deleting unused or old user profiles. In addition to the

admin-tier which has full access privileges, we have included a standard-tier user type with

limited access to modifying and editing cage, mouse, and litter records. This enables greater

control over which vivarium users have record-modifying privileges in order to reduce the

likelihood of erroneous record modification. Admins can also perform strain management

wherein new strains can be added to MyVivarium (**Supplemental videos 26-27**). This is

advantageous for multiple reasons including standardization of mouse strain designation in

cage and mouse records to prevent non-standard strain nomenclature by users, and easy

linking of mouse strains to repositories such as The Jackson Laboratory to enable streamlining

of mouse purchases or – in the case of custom generated lines – to enable sharing mouse lines

with collaborators. We have also included and would like to emphasize the use of the *Research*

Resource Identifier (RRID) for mouse strains to enable precise and standardized record-keeping

("MMRRC - Introduction," n.d.). Once strains have been added, users can easily search for

these strains in the search bar when adding and filling out a cage record. Standardizing mouse

strains in this manner helps researchers in both day-to-day research activities and in the sharing

of results with the broader community of practice, especially for cases when a single mouse

model can be represented by multiple strains in mouse repositories. In practice, since mouse

strains and mouse models are often referred to by common names and not their lengthy official

names or strain numbers listed in repositories, we have included common names to link

particular strains to popular usage. As an example, in our mouse colony we house *Ts65Dn* mice

which are an established Down syndrome mouse model (Haydar and Reeves, 2012). Ts65Dn

mice are generally available as two separate strains through Jackson Laboratory – strain

#005252 ("005252 - Ts(17(16))65Dn Strain Details," n.d.; "RRID | Resource Report (RRID:

IMSR_JAX:005252)," n.d.) and strain #001924 ("001924 - Ts65Dn Strain Details," n.d.; "RRID |

Resource Report (RRID: IMSR_JAX:001924)," n.d.). These strains have official names

B6EiC3Sn.BLiA-Ts(17^{16})65Dn/DnJ and B6EiC3Sn a/A-Ts(17^{16})65Dn/J respectively. "Ts65Dn" is

the common name of both these strains. Using the combination of the RRIDs, official, and

common names in MyVivarium helps disambiguate these strains in colony management.

307 Finally, in order to enable integration of IACUC-related tasks and compliance such as assigning

308 mouse strains to approved IACUC protocols and providing IACUC protocol access to users, we

309 included a functionality where PIs or designated supervisors with admin access can perform

310 these tasks in a streamlined way. PIs can easily assign mouse strains and upload IACUC

311 protocols to their MyVivarium web applications (**Supplemental video 28**). We also included a

312 "Export CSV" functionality to export all database tables in CSV format for download

313 (**Supplemental video 29**), which can be helpful to monitor usage of mice and enable greater

314 compliance with the 3Rs (Graham and Prescott, 2015) as well as for data analysis regarding

315 mouse breeding efficiency and correlation to ambient environmental factors.

316 **DISCUSSION**

317 Mouse colony management is an integral part of biomedical and preclinical research (Elliott et

318 al., 2018). While technology-driven solutions have increasingly been adopted in other areas of

319 laboratory data management such as that seen with the increasing popularity of electronic

320 laboratory notebooks (Higgins et al., 2022), animal colony management has lagged behind.

321 While there may be multiple reasons why technological solutions may not be applied to certain

322 laboratory tasks, two major reasons are cost and difficulty of implementation. We designed

323 MyVivarium as a low-cost low-barrier solution to starting and maintaining a cloud-based

324 research animal colony management application which is cross-device compatible. In addition,

325 in our public repository we have provided detailed documentation for getting a MyVivarium web

326 application up-and-running in a plug-and-play manner with minimal coding requirements. Our

327 open-source RPi-IoT system can be used to stream near-realtime ambient environmental data

328 from the vivarium rooms into a MyVivarium web application. In comparison to other tools (**Table**

1), MyVivarium is a significant step forward in enabling efficient animal colony management that

is also open-source.

Our initial production deployment of MyVivarium for the mouse colony designated to AS was in

October 2023, with a preliminary pilot version launched a few months prior in August 2023. We

launched a second MyVivarium web application on the same server for the mouse colony

designated to PP in December 2023. Currently, the two MyVivarium web app databases have a

total of 82 cage records across two different labs with a combined total of 254 mice belonging to

12 transgenic and three background lines. Additionally, we have 15 users in total with 6 users

having admin access. We have had seamless access to MyVivarium without any interruptions

since production deployment.

We employed the widely used and open-source LAMP stack (Linux as web server; Apache as

database server; MySQL as database; PHP as programming language) ("What is a LAMP

Stack?," 2024) to build MyVivarium. Even though the LAMP stack traces its origins to the early

days of the modern web (Kunze, 1998), its flexibility and open-source nature has made it a

foundational set of web development tools still popular today. While it has been found that the

LAMP stack is slower in terms of response time in comparison to an alternative stack such as

MEAN (MongoDB as database program; Express.js as web application framework back end;

Angular as client-side application framework; Node.js as application runtime) in an "address

book" system, it has also been suggested that LAMP is superior to MEAN in handling relational

data which is found in an animal colony management scenario (Karanjit, 2016). While we have

used widely used web components that have been relatively early origins, concerns about

outdated forms of technology and digital objects are not entirely unfounded (Meur and Tarocco,

2019; Rothenberg, 1999) since many open-source software could potentially face issues due to

a lack of active development. This is evident in the case of colony management software since

to our knowledge, of the four significant publicly available open-source colony management

tools including MausDB (Maier et al., 2008), JCMS (Donnelly et al., 2010), RodentSQL (Pawar

and Batra, 2018), and TopoDB (Renschen et al., 2020), two are effectively unusable due to

unavailability of critical installation files (MausDB), and potential incompatibility and

obsolescence issues (JCMS) (Sundberg and Simons, 2020). Additionally, while the available

MausDB public repository has detailed documentation regarding installation, JCMS lacks any

installation documentation with no active forks in development by other users. Given these

realities, the fact remains that while not guaranteeing active development, releasing software as

open-source remains an effective strategy in combating digital obsolescence (Nano, 2023).

With an eye towards making MyVivarium as accessible as possible, especially for labs in under-

resourced contexts and communities, we prioritized cost-savings in both web components as

well as the hardware and software components needed for the RPi-IoT system. Our initial

server costs were significantly reduced due to discounts from our hosting provider ($0 for 6

months). Similar to our setup, if a "founder lab" sets up a server using a cloud hosting provider,

this single server can then used to launch multiple MyVivarium applications for multiple other

labs that want to use MyVivarium. This would be an additional cost-saving measure, reducing

the server cost further depending on the number of labs that join the server. Importantly, we

designed MyVivarium such that each lab would have their own secure instance without their

data being accessed by the lab that initially set up the server. When comparing costs of similar

systems to monitor IoT in vivarium-related contexts (**Table 2**), we found that our RPi-IoT system

was significantly cheaper than the next highest priced system – the MR1 sensor (Pallidus

[@PallidusSensing], 2024). It must be mentioned however, that the comparison between our

system and the MR1 sensor is not strictly one-to-one since the MR1 is placed within a cage and

hence captures ambient data within a cage and captures mouse activity instead of vivarium

worker activity. Although our system can readily be modified to this end (the presence sensor in

our system is similar in function to what is likely a PIR sensor in the MR1), this is not exactly our

aim at this time. In addition, the free version of the cloud interface provided by Pallidus Sensing

LLC only allows users 30 prior days of retrieval ("Pallidus Free Cloud," n.d.). Our dashboard

design using the Grafana OS version allows for unlimited retrieval of data.

While we consider MyVivarium to be a significant advance in comprehensive open-source

colony management, we would like to note some limitations of this tool. First, as is the case with

all web applications that are hosted on the cloud, MyVivarium web applications can be

potentially subject to malicious action by unapproved actors. Cloud security in a MyVivarium

web application that is enhanced by Cloudflare, while significantly reducing the chances of

attack, does not completely eliminate all likelihood of malicious entry. As best practice related to

any web-related application, we provide three suggestions including the prioritization of

database security by admins, obtaining regular backups of the database stored in a secure

location, and strong password management by all users. While we built MyVivarium as being

primarily remote-accessible, users with primary concerns over security can also choose to host

a MyVivarium web application running on a local server. Second, a MyVivarium cloud-hosted

web application is also subject to internet outages which are becoming more common according

to recent analysis by Cloudflare (Belson, 2024). Third, we have not included any version

tracking of cage records triggered by user-defined changes. Since MyVivarium is under active

development, we plan to incorporate this feature in a future release. Finally, the total number of

cage records that we have included in our specific MyVivarium applications is lower compared

to other tested solutions (Renschen et al., 2020) emphasizing the need for further testing and

performance monitoring as cage records increase. However, given the current seamless

performance of MyVivarium in our hands, we do not anticipate significant performance deficits

for other labs with hundreds of cages.

Taken together, MyVivarium is a low-cost, effective, and rapidly deployable cloud-based

solution for research mouse colony management with extensive documentation on installation

and customization. We envision MyVivarium to be of significant benefit especially to new

independent investigators who would like to make their colony management more efficient

without expending much time or effort by themselves or their personnel. Future development

includes the incorporation of MyVivarium into a larger ecosystem of lab management which

would track purchasing and budgets, chemical inventory, as well as integration into an easy-to-

deploy open-source cloud-based electronic laboratory notebook currently in development.

Finally, we also plan to develop and incorporate tools for big data analysis into MyVivarium to

enable researchers to identify critical factors that affect colony breeding efficiency, health, and

well-being.

METHODS

Web-server and database building strategy

We followed a structured approach to build the web server and database for MyVivarium,

ensuring the system is robust and user-friendly. The strategy encompasses installing and

configuring the web server, integrating PHP for dynamic content generation, and setting up a

reliable database system. We used PHP for server-side scripting, leveraging its ease of

integration with web servers and widespread use in web development. The web server utilized

is Apache, known for its robustness and extensive documentation, ensuring reliable

performance. Composer, a dependency manager for PHP, is employed to manage libraries

such as PHPMailer for email functionality and Dotenv for environment variable management.

Configuration settings, including database credentials and SMTP settings, are stored in a `.env`

file, which the Dotenv library loads into the application for secure and flexible configuration.

MySQL is the database management system used, and it was chosen for its reliability and

performance. The database schema manages various aspects of vivarium operations, including

user management, breeding cages, holding cages, tasks, notes, and more. Tables are created

with appropriate relationships and constraints to ensure data integrity.

Web server setup

We selected Apache as our web server because of its widespread usage and strong support in

the industry. Apache offers a stable and secure platform that can effectively meet the needs of

MyVivarium. The setup process entails installing Apache and configuring it to host the

MyVivarium application. It involves setting up virtual hosts to manage multiple web applications

on a single server and configuring the server to utilize PHP for processing dynamic web pages.

PHP integration

PHP is integrated into the Apache web server to enable the server to process PHP scripts. PHP

is a widely used scripting language, especially suited for web development. It allows us to

create dynamic content and seamlessly interact with the MySQL database. Composer, a

dependency manager for PHP, handles external libraries and dependencies, ensuring the

application has all the necessary tools and libraries to function correctly.

Database configuration

We chose MySQL as the database management system because of its reliability and efficiency

in handling large amounts of data. The database schema stores and manages different data

types needed for MyVivarium, including user information, breeding and holding cage data,

tasks, and notes.

Environment configuration

The configuration settings for the database and other essential components are stored in a

`.env` file. This file includes environment-specific settings, such as database credentials and

SMTP settings for email functionality. The application utilizes the Dotenv library to load these

settings, providing a secure and flexible method for managing configuration data.

Security and compliance

We placed security as a high priority in the development of MyVivarium. Our system is

configured to ensure secure data transmission and storage. Passwords are hashed before

being stored in the database, and sensitive information is protected using state-of-the-art

encryption. Our system is designed to comply with industry standards and regulations, ensuring

user data is handled with the utmost care.

Deployment

To deploy the application, we set up the web server and database on a server running Ubuntu,

a widespread and stable Linux distribution known for its security. The process involves installing

Apache, PHP, and MySQL, configuring the server to host the MyVivarium application, and

ensuring all services run smoothly. After setup, we tested the application to ensure it was fully

functional and ready for use. A detailed guide on installing a LAMP (Linux, Apache, MySQL,

PHP) stack on Ubuntu can help new users set up their own version of MyVivarium (Yang et al.,

2024). We used Cloudflare as the DNS provider, adding an additional layer of security to our

MyVivarium application. To implement this, we moved our domain from our previous registrar to

Cloudflare by updating the domain's nameservers to Cloudflare's nameservers. This process

involves logging into the domain registrar's account, locating the DNS settings, and replacing

the existing nameservers with those provided by Cloudflare. After the domain was successfully

transferred, we subscribed to Cloudflare's free plan, which includes essential security features

such as DDoS protection and basic firewall rules. These measures protect the application from

malicious attacks and ensure high availability. We configured Cloudflare to filter incoming traffic,

block potential threats, and optimize content delivery for improved performance and security.

This setup reasonably ensures that a MyVivarium web application remains resilient against

cyber threats while maintaining seamless access for legitimate users. Note that this

configuration needs to be done separately and is not part of the code in the GitHub repository.

Finally, a complete list of all the files in MyVivarium have been included in our GitHub repository

(https://github.com/myvivarium/MyVivarium).

478 Cage-card print functionality and QR-code accessibility

In order to physically link cage-records to MyVivarium, we incorporated a cage-card print

functionality. We printed cage-cards directly from a browser and onto cardstock with 3" x 5"

perforations (4 per page) (Amazon.com, WA; ASIN: B09BZST43T) using a standard LaserJet

printer. We incorporated QR-codes into the cage-card design in order to increase efficiency in

managing records using mobile devices. We have tested QR-code accessibility using android

tablets, as well as android-based and apple-based smartphones. In all our testing and use, QR-

code access has been seamless.

486 RPi-IoT design and assembly

Hardware components

We used a Raspberry-Pi based design for our IoT system. All sensors used were I^2C based

which made the use of multiple sensors with different addresses straightforward. For each of

our sensor modules, we used a Raspberry Pi model 4B with 2 GB RAM (Adafruit Industries

LLC, NY) with a 128 GB RAM running the 64-bit Raspberry Pi Bookworm OS

(https://www.raspberrypi.com/software/). The Pi was cooled inside a case using both active

cooling and passive cooling elements (Amazon.com, WA; B0963HHSWK). We used three I^2C

sensors including the SHT30 Temperature and Humidity Sensor (Adafruit LLC, NY), Adafruit

VEML7700 Lux Sensor - I2C Light Sensor (Adafruit LLC, NY), and the Adafruit VL53L1X Time

of Flight Distance Sensor for 30 to 4000mm (Adafruit LLC, NY). Connectors and wires were

purchased from Adafruit. A detailed list of hardware components with vendor weblinks is

provided in the bill of materials in our GitHub repository (https://github.com/myvivarium/RPi-IoT).

Data visualization and software components

Detailed steps regarding software installation steps can be found on our GitHub repository wiki

(https://github.com/myvivarium/RPi-IoT/wiki). Briefly, we installed TigerVNC server

(https://tigervnc.org/) on the Pi to enable remote sessions for easy management and data

retrieval. We then configured the Pi to be able to detect I2C device interfacing. We also

registered a free DuckDNS account to track changes in the IP address of the Pi in the event it

restarted and a new IP address was assigned to the Pi. Next, we used IOTstack to run all

necessary IoT-related applications on the Pi using a Docker stack (SensorsIOT, 2024).

Specifically, we built our stack to include DuckDNS, Grafana, InfluxDB, and Portainer. We then

created a database: `multisensors` to store sensor data. We then installed all relevant

libraries for the Pi to detect streaming data from the I2C sensors. We wrote a python script

(`influxdb-multisensor.py`) to log sensor data to the `multisensors` database as well as

store a redundant CSV per day of recording (Sathyanesan, 2024). Intervals at which data can

be logged to the InfluxDB database is user-defined, however, relevant for our purposes and also

to balance sensor functionality, we used a time interval of 1 minute. After confirming that the

database is actively being updated with sensor data input using Grafana, we installed a service

file to ensure that the `influxdb-multisensor.py` script runs even if the Pi restarts. We then

purchased a low-cost domain name using a domain name registration service (Cloudflare, San

Francisco, CA; 1 year domain registration price = $6.65 USD), added this domain to Cloudflare

using a free account, and used a Cloudflare tunnel ("Argo Tunnel," 2018;

"cloudflare/cloudflared," 2024) to securely expose the local Grafana application running on the

Pi. Once the Cloudflare tunnel was active, we were able to access our sensor data directly from

the domain. We then obtained the embed URL for individual panels of our dashboard and used

these in MyVivarium under the Admin tasks section to directly view near-realtime sensor data.

Finally, in order to enable alerting via Grafana and Google chat, we used a webhook app within

Google space and added this as a contact point in Grafana's alerting system. We defined alert

rules for abnormal illuminance sensor values for both light and dark cycles of the vivarium

rooms. We set the evaluation period as 15 minutes with a pending period of 15 minutes, which

meant that if the sensor was detecting abnormal light function for at least 30 minutes, then it will

send a notification via the webhook app.

Vivarium facility

The University of Dayton vivarium is a modern animal facility specifically designed for rodent

(mice and rats) micro-isolator caging with each room that holds animal cages containing

Allentown Phantom animal transfer stations. All rooms including those that hold animal cages as

well as procedure rooms are independently controlled for air pressure (positive or negative),

temperature, and timer-controlled lighting. Lighting in rooms include both white and red

dimmable lights. Humidity is controlled centrally by the University of Dayton facilities

management.

ACKNOWLEDGEMENTS

We would like to thank the Director of the University of Dayton Vivarium, Dr. Jeffrey Kavanaugh,

and our vivarium veterinarian, Dr. Paul A. Stull, DVM, for helpful suggestions during the early

phase of this study.

FUNDING

We would like to acknowledge the Graduate Student Summer Fellowship awarded to MAR, A.

Sheikh, HO, and AM, the Dean's Summer Fellowship awarded to JP, A. Sharp and CF, and

startup funding to AS provided by the College of Arts & Sciences, University of Dayton.

DATA AND CODE AVAILABILITY

All code has been uploaded to public GitHub repositories:

https://github.com/myvivarium/MyVivarium and https://github.com/myvivarium/RPi-IoT. All data

will be uploaded to a public repository upon manuscript being sent out for peer-review.

REFERENCES

001924 - Ts65Dn Strain Details. n.d. https://www.jax.org/strain/001924
005252 - Ts(17(16))65Dn Strain Details. n.d. https://www.jax.org/strain/005252
Argo Tunnel: A Private Link to the Public Internet. 2018. . *The Cloudflare Blog.*
https://blog.cloudflare.com/argo-tunnel
Belson D. 2024. Q2 2024 Internet disruption summary. *The Cloudflare Blog.*
https://blog.cloudflare.com/q2-2024-internet-disruption-summary
Build a Google Chat app as a webhook | Google for Developers. 2023.
https://web.archive.org/web/20240630230519/https://developers.google.com/workspace/
chat/quickstart/webhooks
Chambliss AB, Tolan NV. 2020. Contingency Planning in the Clinical Laboratory: Lessons
Learned Amidst COVID-19. *The Journal of Applied Laboratory Medicine* **5**:832–836.
doi:10.1093/jalm/jfaa068
Chesler EJ, Wilson SG, Lariviere WR, Rodriguez-Zas SL, Mogil JS. 2002. Influences of
laboratory environment on behavior. *Nat Neurosci* **5**:1101–1102. doi:10.1038/nn1102-
1101
cloudflare/cloudflared. 2024.
Corrigan JK, Ramachandran D, He Y, Palmer CJ, Jurczak MJ, Chen R, Li B, Friedline RH, Kim
JK, Ramsey JJ, Lantier L, McGuinness OP, Mouse Metabolic Phenotyping Center
Energy Balance Working Group, Banks AS. 2020. A big-data approach to understanding
metabolic rate and response to obesity in laboratory mice. *eLife* **9**:e53560.
doi:10.7554/eLife.53560
Dolgin E. 2018. How to start a lab when funds are tight. *Nature* **559**:291–293.
doi:10.1038/d41586-018-05655-3
Donnelly CJ, McFarland M, Ames A, Sundberg B, Springer D, Blauth P, Bult CJ. 2010. JAX
Colony Management System (JCMS): an extensible colony and phenotype data
management system. *Mamm Genome* **21**:205–215. doi:10.1007/s00335-010-9250-1
Elliott JJ, Miller CT, Hagarman JA, Kelley ST, Tardif SD, Hacker SO, Bettis A. 2018.
Management of Research Animal Breeding Colonies In: Weichbrod RH, Thompson GA
(Heidbrink), Norton JN, editors. Management of Animal Care and Use Programs in
Research, Education, and Testing. Boca Raton (FL): CRC Press/Taylor & Francis.
Ganeshan K, Chawla A. 2017. Warming the mouse to model human diseases. *Nat Rev*
Endocrinol **13**:458–465. doi:10.1038/nrendo.2017.48
Gao J, Yin Y, Myers KR, Lakhani KR, Wang D. 2021. Potentially long-lasting effects of the
pandemic on scientists. *Nat Commun* **12**:6188. doi:10.1038/s41467-021-26428-z
Graham ML, Prescott MJ. 2015. The multifactorial role of the 3Rs in shifting the harm-benefit
analysis in animal models of disease. *European Journal of Pharmacology*, Translational
value of animal models **759**:19–29. doi:10.1016/j.ejphar.2015.03.040
Hall W, Tiropanis T. 2012. Web evolution and Web Science. *Computer Networks*, The WEB we
live in **56**:3859–3865. doi:10.1016/j.comnet.2012.10.004
Haydar TF, Reeves RH. 2012. Trisomy 21 and early brain development. *Trends Neurosci*
35:81–91. doi:10.1016/j.tins.2011.11.001
Higgins SG, Nogiwa-Valdez AA, Stevens MM. 2022. Considerations for implementing electronic
laboratory notebooks in an academic research environment. *Nat Protoc* **17**:179–189.
doi:10.1038/s41596-021-00645-8
Jacobs M, Buck A, Petersen T, Kaim E. 2022. What is Kanban? - Azure DevOps.
https://web.archive.org/web/20240305014636/https://learn.microsoft.com/en-
us/devops/plan/what-is-kanban

Jaric I, Voelkl B, Clerc M, Schmid MW, Novak J, Rosso M, Rufener R, Kortzfleisch VT von,
Richter SH, Buettner M, Bleich A, Amrein I, Wolfer DP, Touma C, Sunagawa S, Würbel
H. 2022. The rearing environment persistently modulates mouse phenotypes from the
molecular to the behavioural level. *PLOS Biology* **20**:e3001837.
doi:10.1371/journal.pbio.3001837
Karanjit A. 2016. MEAN vs. LAMP Stack. *Culminating Projects in Computer Science and
Information Technology*.
Kudo E, Song E, Yockey LJ, Rakib T, Wong PW, Homer RJ, Iwasaki A. 2019. Low ambient
humidity impairs barrier function and innate resistance against influenza infection.
Proceedings of the National Academy of Sciences **116**:10905–10910.
doi:10.1073/pnas.1902840116
Kunze M. 1998. LAMP: Freeware Web Publishing System with Database Support (Translated
from the Original German). *Computertechnik*.
Maier H, Lengger C, Simic B, Fuchs H, Gailus-Durner V, Hrabé de Angelis M. 2008. MausDB:
An open source application for phenotype data and mouse colony management in large-
scale mouse phenotyping projects. *BMC Bioinformatics* **9**:169. doi:10.1186/1471-2105-
9-169
Maier H, Schütt C, Steinkamp R, Hurt A, Schneltzer E, Gormanns P, Lengger C, Griffiths M,
Melvin D, Agrawal N, Alcantara R, Evans A, Gannon D, Holroyd S, Kipp C, Raj NP,
Richardson D, LeBlanc S, Vasseur L, Masuya H, Kobayashi K, Suzuki T, Tanaka N,
Wakana S, Walling A, Clary D, Gallegos J, Fuchs H, de Angelis MH, Gailus-Durner V.
2015. Principles and application of LIMS in mouse clinics. *Mamm Genome* **26**:467–481.
doi:10.1007/s00335-015-9586-7
Meur J-YL, Tarocco N. 2019. The obsolescence of Information and Information Systems CERN
Digital Memory project. *EPJ Web Conf* **214**:09003. doi:10.1051/epjconf/201921409003
Mishra J. 2020. Use your lab website to make a compelling first impression. *Nature*.
doi:10.1038/d41586-020-01298-5
MMRRC - Introduction. n.d. https://www.mmrrc.org/about/generalInfo.php
Mouse Room Conditions | The Jackson Laboratory. 2023.
https://web.archive.org/web/20231206081828/https://www.jax.org/jax-mice-and-
services/customer-support/technical-support/breeding-and-husbandry-support/mouse-
room-conditions
Nano E. 2023. Digital obsolescence In: CEUR-WS, editor. Doctoral Symposium of ICT4S 2023,
The International Conference on Information and Communications Technology for
Sustainability. Rennes, France. pp. 36–47.
National Research Council. 2011. Guide for the Care and Use of Laboratory Animals: Eighth
Edition. Washington, DC: The National Academies Press. doi:10.17226/12910
Pallidus Free Cloud. n.d. . *Pallidus*. https://pallidus.io/products/pallidus-free-cloud
Pallidus [@PallidusSensing]. 2024. Want to monitor the environment of your housing room? We
have an affordable solution for monitoring temperature, humidity, light, noise levels, and
human activity! Get in touch to learn more or see a live demo! https://t.co/XpxL0m2dqh.
Twitter.
Pawar S, Batra H. 2018. RodentSQL: a software suite for colony management of animal
protocols. *Future Science OA* **4**:FSO330. doi:10.4155/fsoa-2018-0054
Per Diem Animal Housing Rates | Boston University Office of Research. 2016.
https://web.archive.org/web/20231206134704/https://www.bu.edu/research/ethics-
compliance/animal-subjects/housing/per-diem-housing-rates/
Renschen A, Matsunaga A, Oksenberg JR, Santaniello A, Didonna A. 2020. TopoDB: a novel
multifunctional management system for laboratory animal colonies. *Database*
2020:baaa098. doi:10.1093/database/baaa098

Richter SH, Garner JP, Zipser B, Lewejohann L, Sachser N, Touma C, Schindler B, Chourbaji
S, Brandwein C, Gass P, Stipdonk N van, Harst J van der, Spruijt B, Võikar V, Wolfer
DP, Würbel H. 2011. Effect of Population Heterogenization on the Reproducibility of
Mouse Behavior: A Multi-Laboratory Study. *PLOS ONE* **6**:e16461.
doi:10.1371/journal.pone.0016461
Rothenberg J. 1999. Avoiding Technological Quicksand: Finding a Viable Technical Foundation
for Digital Preservation • CLIR. *CLIR*. https://www.clir.org/pubs/reports/rothenberg/
RRID | Resource Report (RRID: IMSR_JAX:001924). n.d.
https://rrid.site/data/record/nlx_154697-
1/IMSR_JAX:001924/resolver?q=001924&l=001924&i=rrid::imsr_jax:001924
RRID | Resource Report (RRID: IMSR_JAX:005252). n.d.
https://rrid.site/data/record/nlx_154697-
1/IMSR_JAX:005252/resolver?q=IMSR_JAX%3A005252&l=IMSR_JAX%3A005252&i=rr
id::imsr_jax:005252
Sathyanesan A. 2024. myvivarium/RPi-IoT: Open-source IoT for MyVivarium web apps.
https://github.com/myvivarium/RPi-IoT
SensorsIOT. 2024. SensorsIot/IOTstack.
Sundberg B, Simons A. 2020. jaxcs/JCMS-root: The Jackson Laboratory Colony Management
System. https://github.com/jaxcs/JCMS-root
Unger CA, Hope MC, Aladhami AK, Velázquez KT, Enos RT. 2023. How stable is your
vivarium's temperature? Fluctuations in vivarium temperature significantly impact
metabolism and behavior impeding scientific reproducibility. *Physiology & Behavior*
258:114029. doi:10.1016/j.physbeh.2022.114029
What is a LAMP Stack? - LAMP Stack Explained - AWS. 2024.
https://web.archive.org/web/20240717231209/https://aws.amazon.com/what-is/lamp-
stack/
Wood D, King M, Landis D, Courtney W, Wang R, Kelly R, Turner JA, Calhoun VD. 2014.
Harnessing modern web application technology to create intuitive and efficient data
visualization and sharing tools. *Front Neuroinform* **8**. doi:10.3389/fninf.2014.00071
Yang K, Heidi E, Abid E. 2024. How To Install Linux, Apache, MySQL, PHP (LAMP) Stack on
Ubuntu | DigitalOcean.
https://web.archive.org/web/20240704012542/https://www.digitalocean.com/community/t
utorials/how-to-install-lamp-stack-on-ubuntu
680

Figure 1. MyVivarium System Architecture Overview. MyVivarium system architecture consists of three main components: the
client side, the server side, and external services. Each component interacts with the others to provide a robust and secure web
application for managing vivarium operations. *Client-side:* MyVivarium's front-end is built using standard web technologies, including
HTML, CSS, and JavaScript, ensuring that the user interface is interactive and responsive. Users can interact with the application
through web browsers such as Chrome and Firefox with cross-device compatibility. *External services:* Cloudflare provides DNS
services and security features, including DDoS protection, to enhance the reliability and security of the MyVivarium application.
Server-Side: The backend is built on a LAMP stack, consisting of Linux (operating system), Apache (webserver), MySQL (database),
and PHP (scripting language). The database includes tables such as `users`, `breeding`, `holding`, `mouse`, `files`, `settings`,
`litter`, `tasks`, `notes`, and `strains`, which store various types of data required for the application's functionality. *IoT Data*: The
system integrates IoT sensor data to monitor ambient parameters such as temperature, humidity, illuminance, and presence.
Scheduler: A scheduler (cron job) handles tasks such as sending reminder emails utilizing the `email_queue` for processing. Cron
jobs automate database queries and sending emails through SMTP using PHPMailer.

Figure 2. MyVivarium web application navigation overview. The MyVivarium web application navigation is intuitive, structured
into "Home", "Dashboards", and "Settings". The "Home" section includes "Cages Summary", "Tasks Summary", and "General Notes".
The "User Login" provides links for registration and password recovery. "Dashboards" gives access to holding cage and breeding
cage management, including adding, editing, viewing, and deleting cages, printing cage cards, maintenance logs, and near-realtime
ambient sensing via the IoT sensor datastream. "Settings" includes user profile management, task management, and admin options
such as managing users, lab details, mouse strains, IACUC protocols, and data export in CSV format. The Logout option allows
users to log out securely. This structure ensures easy access to all functionalities, with specific options available based on user roles
and permissions.

Figure 3. Design, assembly, and deployment of MyVivarium Pi-IoT sensor system. **a.**
Components of Pi-IoT sensor system include 1: Jumper wires (to extend reach) 2: SHT30
Temperature and humidity sensor with plastic shell casing 3: VL53L1X distance or time-of-flight
sensor which can measure distance to a person (vivarium-worker) 4: VEML7700 illuminance
sensor which can detect lights ON and OFF 5 and 6: STEMMA-QT connectors (for Raspberry Pi
GPIO pins to sensors and between sensors) 7: Raspberry Pi 4B (2 GB) in a case with a cooling
fan. **b.** Fritzing sketch of serial connections between I^2C sensors and Raspberry Pi GPIO pins
based on a validated sensor module build. Wire color designations are as follows – red: power
(+ve), black: ground (-ve), yellow: SCL (serial clock), blue: SDA (serial data). Note that in a, the
color of SDA (data) is white. **c.** Assembled sensor module deployed in our vivarium room.
Sensors have been affixed to the lower part of the mouse cage transfer station. The Raspberry
Pi has been placed in a corner of a mouse cage rack.

Figure 4. Continuous near-realtime ambient factor recording over a period of months using MyVivarium Pi-IoT sensor system. a. Temperature (ºC) recorded over four months in vivarium rooms 1 (blue) and 2 (orange). Temperature in Dayton, OH is plotted as reference (grey). Dotted lines represent minimum ("min" = 18 ºC) and maximum ("max" = 26 ºC) recommended temperatures. Time-window (grey shaded rectangle) between arrows (12 midnight May 2nd, 2024 – 12 midnight May 3rd, 2024) is shown in greater detail in **b. c.** Relative humidity (%) recorded over four months. Humidity in Dayton, OH is plotted as reference (grey). Dotted lines represent minimum ("min" = 30%) and maximum ("max" = 70%). Time-window (grey shaded rectangle) is shown in greater detail in **d. e.** Illuminance sensor values recorded over months. Asterisk indicates an abnormal event detected by the sensor due to an erroneous manual override of the automated light cycle **f.** Sensor value change over the course of 24 hours shows vivarium lights OFF (light bulb turned off) and lights ON (light bulb turned on) in rooms 1 and 2 set to a 6 AM – 6 PM light cycle. **g.** Proximity sensor values for rooms 1 and 2 recorded for months **h.** Vivarium worker presence or activity is detected as negative deflections. Minimum and maximum temperature and humidity thresholds are based on suggested recommendations by *The Guide* (Office of Laboratory Animal Welfare, National Institutes of Health) and the Jackson Laboratory ("Mouse Room Conditions | The Jackson Laboratory," 2023; National Research Council, 2011).

Figure 5. User notification of sensor readings and automated alerts. a. Increased humidity
in vivarium rooms 1 (blue) and 2 (orange) on February 27th, 2024. **b.** General user notification
using the "Sticky notes" on MyVivarium. **c.** Abnormal illuminance event and automated alert
testing (arrow indicating when black unreflective paper was used to block the illuminance sensor
from light exposure) shows reduced illuminance (orange) at 3:30 PM on March 25th **d.** Alert
message triggered by Grafana and relayed via a Google chat webhook app to a dedicated
Google space.

Table 1. Comparison of MyVivarium to other available open-source and commercial colony management tools

Name	Open-source or commercial/proprietary	Cost	Admin management	File upload	Tasks and Reminders	Smart-device compatible	Tool-linked cage card functionality	IoT ambient sensing and alerts
MyVivarium	Open-source https://github.com/myvivarium/MyVivarium	Low	Yes	Yes	Yes	Yes	Yes; QR-code	Yes
TopoDB	Open-source (Renschen et al., 2020) https://github.com/UCSF-MS-DCC/TopoDB	Low	Yes	Yes	No	Not mentioned, unavailable, or not tested	Not mentioned or unavailable	No
RodentSQL	Open-source (Pawar and Batra, 2018) https://github.com/spawar2/Java_SQL_MiceExperiment_Record_Tracking_Software	Low	Yes	No	Unclear	Not mentioned, unavailable, or not tested	Yes; barcode	No
MausDB	Open-source (Maier et al., 2008) https://github.com/MouseGenomics/mausdb	Low	No	Yes	Yes	No	Yes; barcode	No
mLIMS	Commercial/proprietary https://bioinforx.com/web/product_mlims.php	Very high	Yes	Yes	Yes	Yes	Yes; QR code	No
SoftMouse (2 users)	Commercial/proprietary https://www.softmouse.net/login.jsp	High	Yes	Yes	Yes	Yes	Yes; QR code	No
PyRAT	Commercial/proprietary https://www.scionics.com/pyrat.html	High	Yes	Yes	Yes	Yes	Yes; QR code	No

740 **Table 2. Comparison of MyVivarium RPi-IoT ambient sensing tool compared to other**
741 **tools**

Name	Open-source or commercial/pro prietary	Cost of components (in USD)	
		Software-related	**Hardware-related**
MyVivarium RPi-IoT system	Open-source https://github.com /myvivarium/RPi-IoT	Grafana Open source: $0; Domain name registration: varies, but as low as $6 per year	$110.08
Pallidus MR1 sensor and Pallidus cloud software (Pallidus Sensing LLC)	Commercial/ proprietary https://pallidus.io/ products/mr1-sensor	Pallidus Free: $0 (only access to last 30 days of data); Pallidus professional cloud: $2,990.00	$399.00 per sensor, however can only be added to an existing installation; Pallidus starter kit (8 sensors): $4,499.00 (includes only one year subscription to cloud)
REM Module and Guardian software (excludes software maintenance, training, and installation) (Techniplast, USA)	Commercial/ proprietary https://digitalcage-tecniplast.com/en/products/rem.html	> $800.00 license fee	> $2000.00