1
2
3   **AmygdalaGo-BOLT: an open and reliable AI tool to trace boundaries of human amygdala**
4   - Short Title: AmygdalaGo-BOLT
5

6   **Authors**
7   Quan Zhou,[1,2†] Bo Dong,[3†] Peng Gao,[1,2†] Jintao Wei,[3] Jiale Xiao,[2] Wei Wang,[2] Peipeng Liang,[4]
8   Danhua Lin,[2] for the Chinese Color Nest Consortium,[††] Xi-Nian Zuo,[1,2,5,6*] Hongjian He,[3,7,8*]
9

Affiliations
[1]State Key Laboratory of Cognitive Neuroscience and Learning, Beijing Normal University,
Beijing 100875, China.
[2]Faculty of Psychology, Beijing Normal University, Beijing 100875, China.
[3]College of Biomedical Engineering and Instrument Science, Zhejiang University, Hangzhou
310027, China.
[4]School of Psychology, Capital Normal University, Beijing 100048, China.
[5]Developmental Population Neuroscience Research Center, McGovern Institute for Brain
Research, Beijing Normal University, Beijing 100875, China.
[6]National Basic Science Data Center, Beijing 100190, China.
[7]School of Physics, Zhejiang University, Hangzhou 310058, China.
[8]State Key Laboratory of Brain-Machine Intelligence, Zhejiang University, Hangzhou 310027,
China.
*Corresponding authors. Email: hhezju@zju.edu.cn; xinian.zuo@bnu.edu.cn.
†These authors contributed equally to this work.
††A list of CCNC authors and their affiliations appears at the end of the paper. More information
about CCNC is available at https://ccnp.scidb.cn/en.

Abstract
Each year, thousands of brain MRI scans are collected to study structural development in children
and adolescents. However, the amygdala, a particularly small and complex structure, remains
difficult to segment reliably, especially in developing populations where its volume is even
smaller. To address this challenge, we developed AmygdalaGo-BOLT, a boundary-aware deep
learning model tailored for human amygdala segmentation. It was trained and validated using 854
manually labeled scans from pediatric datasets, with independent samples used to ensure
performance generalizability. The model integrates multiscale image features, spatial priors, and
self-attention mechanisms within a compact encoder-decoder architecture to enhance boundary
detection. Validation across multiple imaging centers and age groups shows that AmygdalaGo-
BOLT closely matches expert manual labels, improves processing efficiency, and outperforms
existing tools in accuracy. This enables robust and scalable analysis of amygdala morphology in
developmental neuroimaging studies where manual tracing is impractical. To support open and
reproducible science, we publicly release both the labeled datasets and the full source code.

Teaser
An AI model enables accurate amygdala segmentation across ages and centers, supporting large-
scale brain imaging studies.
46

INTRODUCTION

Accurately segmenting the human amygdala, a small, structurally complex region, remains a major challenge in large-scale neuroimaging studies of brain development. The amygdala plays a central role in mood regulation, cognitive learning, and memory consolidation, and has been strongly implicated in behavioral pathologies - particularly during critical stages of socio-emotional maturation such as childhood and adolescence (*1–3*). Magnetic resonance imaging (MRI) has enabled detailed investigation of amygdala structure, facilitating the construction of developmental trajectories and the investigation of neurodevelopmental processes underlying various neuropsychiatric conditions (*4,5*). However, reliable volumetric analysis hinges on precise boundary-based segmentation—a task that remains technically challenging.

Conventional approaches have primarily relied on manual delineation of in vivo neuroimaging data, guided by histological atlases. While manual segmentation is considered the gold standard, it is time-consuming and infeasible for large-scale datasets. To address the limitations, researchers have developed automated segmentation tools based on probabilistic estimates (e.g., Markov random fields), Bayesian inference, and multi-atlas label fusion (*6–12*). These methods underpin popular tools like *FreeSurfer* and *volBrain*, which offer reasonable performance in whole-brain segmentation. However, these tools were not developed exclusively for amygdala segmentation. As a result, they struggle with boundary precision in this region, particularly in pediatric samples: *FreeSurfer* overestimates amygdala volume by 13–28%, while *volBrain* underestimates it by 36–38% (*13*). These discrepancies underscore fundamental limitations of existing segmentation frameworks. The amygdala's small size, low contrast with surrounding tissue, and complex anatomical context make it especially challenging to delineate accurately (*6, 11, 14*). Rule-based or atlas-driven models - such as those using probabilistic inference or multi-atlas fusion - struggle to accommodate such local variability, particularly in children and adolescents, where the amygdala is both smaller and still undergoing dynamic maturation. Consequently, systematic biases in volume estimation can compromise the precision and reliability of measuring amygdala, potentially undermining the validity of findings in developmental neuroimaging studies.

To address these challenges, we developed AmygdalaGo-BOLT, a boundary-aware deep learning algorithm trained on a large dataset of manually segmented pediatric amygdalae (*13*). The algorithm is built on a Transformer model (*15*) that emphasizes accuracy in boundary delineation. Rather than relying on predefined anatomical priors, it learns boundary features directly from data, enabling flexible adaptation to anatomical variability across development. In this study, we benchmarked AmygdalaGo-BOLT against widely used segmentation tools across internal and external neuroimaging cohorts, demonstrating its accuracy, stability, and generalizability for amygdala segmentation in developmental neuroimaging.

RESULTS

Performance on CKG-CCNC (Training Site)
Table 1 summarizes the comparative performance of BOLT3D against conventional segmentation algorithms within the CKG-CCNC test cohort. BOLT3D outperformed all other methods across multiple key metrics, demonstrating superior segmentation accuracy and boundary precision. It achieved a Dice coefficient of 0.904, notably higher than U-Net3D (0.851), U-Net3D++ (0.787), and ResU-Net3D (0.841), indicating greater overlap with manual annotations. A similar pattern emerged for the Jaccard Similarity (JS) coefficient, with BOLT3D reaching 0.825. In terms of boundary accuracy, BOLT3D achieved the lowest 95th-percentile Hausdorff Distance (HD95) of 1.097, indicating superior alignment with anatomical ground truth compared to U-Net3D (1.565),

U-Net3D++ (1.963), and ResU-Net3D (1.669). The average symmetric surface distance (ASSD) further demonstrated that BOLT3D's segmentation output aligned more closely with reference annotations compared to other methods. Evaluation of detection performance further highlighted BOLT3D's advantage. It achieved a precision of 0.883 and recall of 0.929, resulting in a high F1-score of 0.905, reflecting its ability to balance false positive suppression with high true positive detection. Finally, BOLT3D attained a relative volume difference (RVD) of just 0.056, over 40% lower than the next-best method, underscoring its accuracy in volumetric estimation.

Fig. 1. Comparative visualization of amygdala segmentation in a representative participant. The segmentation results of different methods illustrate the preservation of structural integrity (middle row) and the precision of boundary delineation (bottom row). Manual segmentation (left column) serves as the reference standard. The proposed BOLT3D method (right column) shows superior performance in both volumetry and boundary definition, outperforming FreeSurfer (second column) and U-Net3D (third column).

Fig. 1 presents segmentation results from multiple algorithms on a representative participant, demonstrating that BOLT3D most closely aligns with manual reference standard in both volumetric estimation and boundary delineation. Notably, the amygdala delineated by FreeSurfer deviates markedly from both the morphological and manual segmentation. The presence of multiple empty regions indicates an inability to accurately capture the structural integrity of the amygdala. A closer inspection of the periphery suggests that FreeSurfer exhibits numerous irregularities when compared with the manual reference standard. Although Unet produces segmentations that are morphologically more consistent with manual references, volumetric evaluation reveals substantial overestimation. In contrast, BOLT3D produces segmentation results that more closely match manual delineations in both overall shape and boundary accuracy. Notably, the superposition and edge correspondence in BOLT3D outputs demonstrate minimal deviation from reference, indicating precise volume estimation and structural fidelity.

Table 1. Performance evaluation on different methods of tracing amygdala in the CKG-CCNC cohort.

Method	Dice	JS	HD95	ASD	ASSD	Precision	Recall	RVD
FreeSurfer	0.776	0.636	2.530	1.093	0.954	0.732	0.832	0.142
U-Net3D	0.851	0.743	1.565	0.746	0.693	0.774	0.951	0.239
U-Net3D++	0.787	0.651	1.963	1.064	0.982	0.658	0.985	0.512
ResU-Net3D	0.841	0.728	1.669	0.806	0.736	0.754	0.957	0.279
BOLT3D	**0.904**	**0.825**	**1.097**	**0.483**	**0.467**	**0.883**	**0.929**	**0.056**

127
128 **Fig. 2. Volume dice analysis of the overall amygdala structure for participants from the CKG-CCNC (A) and BNU-CAC (B) cohorts.** Since
129 the CKG-CCNC data were used during training, the overall performance was slightly higher than for the unseen BNU-CAC dataset for all deep-
130 learning network methods. However, the proposed BOLT3D model achieved a dice score above 0.8 for both cases.
131

CY: Beijing Chaoyang Hospital
HN: Henan Provincial People's Hospital
LG: Longgang District Central Hospital of Shenzhen
TJ: Tianjin Medical University General Hospital
TT: Beijing Tiantan Hospital
MZ: Meizhou People's Hospital
XY: Xiangya Hospital of Central South University
ZJU: Zhejiang University
ZN: Zhongnan Hospital of Wuhan University
ZZ: The First Affiliated Hospital of Zhengzhou University

132
133 **Fig. 3. A comparison of amygdala segmentation outcomes for itinerant volunteers from ZJU-MTC.** (A) The proposed BOLT3D
134 methodology (depicted in red) consistently demonstrated superior performance relative to U-Net3D (depicted in blue) across all centers for each
135 participant, thereby underscoring its robust cross-center generalization efficacy. (B) All centers were equipped with identical model 3T scanners,
136 geographically dispersed across China, with their respective names and abbreviations provided on the right.
137

The generalizability of BOLT3D was first validated on an dataset from BNU-CAC, an
independent imaging center not included in model training, comprising 116 children. As shown in
Table S1, BOLT3D maintained strong performance despite distributional shifts, achieving a Dice
coefficient of 0.845 and a Jaccard similarity (JS) of 0.733. Distance-based evaluations further
confirmed accuracy, with HD95 and ASD values of 1.594 and 0.654, respectively. The average

symmetric surface distance (ASSD) of 0.666 exhibited less variability than that observed with U-
Net, suggesting more stable boundary delineation. In terms of detection performance, BOLT3D
attained a precision of 0.933 and a recall of 0.775, effectively balancing false-positive suppression
and true-positive identification. The relative volume difference (RVD) was 0.168, indicating low
deviation in volumetric estimation. These indicators suggest the performance of BOLT3D was not
compromised significantly, despite the distribution variations encountered at new centers. In
addition, this technique significantly outperformed comparable algorithms, thereby affirming the
multi-center accuracy and consistency offered by integrating the consistency module. Here, we
presented segmentation results from 116 unseen participants in BNU-CAC, compared to the 347
observed scans from CKG-CCNC (see Fig. 2). Since BNU-CAC participants originate from
different data distribution and were not included in model training, the overall performance on
this dataset is lower compared to the CKG-CCNC scans. This performance gap likely arises due
to variations in feature distributions, inter-data noise, or other unaccounted factors that affect
segmentation accuracy. Despite this decline in overall performance with unseen data, BOLT3D
significantly outperforms the baseline model, demonstrating strong generalization capabilities.
To further evaluate cross-site robustness, the model was tested on the ZJU-MTC dataset, which
includes three "traveler" participants scanned at ten different imaging centers (Fig. 3). BOLT3D
consistently outperformed U-Net3D across all sites, with Dice improvements ranging from 0.02
to 0.07. These results highlight BOLT3D's resilience to multi-center heterogeneity and support its
applicability to large-scale, multi-center neuroimaging studies.
163
Ablation Study in ZJU-MTC
We conducted ablation experiments on the ZJU-MTC dataset to evaluate the contribution of key
BOLT3D components to segmentation accuracy and generalization. As shown in Fig. 4A–B, the
model variant incorporating the MGAC backbone (but excluding the SAM module) yielded
substantially higher Dice scores and lower ASSD values compared to U-Net3D and FreeSurfer,
across both volumetric and boundary metrics. These results reflect MGAC's ability, via a
Transformer-based multi-granularity attention framework, to capture both global context and
local anatomical detail, thereby improving segmentation accuracy and structural fidelity.

We then assessed the SAM module's effect on cross-site consistency by comparing segmentation performance across ten imaging centers. Integration of SAM into the full BOLT3D pipeline led to consistent performance under diverse scanning conditions gains over the MGAC-only variant (Fig. 4C), demonstrating its utility in mitigating inter-site variability. Qualitative comparisons further illustrated improved boundary adherence following SAM-based refinement (Fig. 4D).

Foster Fast and Valid Large-scale Amygdala-centered Neuroscience Research

Fig. 5. A correlation analysis of amygdala volume as determined by segmentation algorithms compared with manual reference standards. The dataset included 347 internal validation scans, with the results of manual segmentation depicted on the horizontal axis. Among the evaluated methods, the proposed BOLT3D algorithm achieved the highest correlation with manual references for the left (A) and right (F) regions of the amygdala, signifying higher consistency in volumetric measurements. In contrast, correlation coefficients for alternative segmentation tools, including U-Net3D (B, G), ResU-Net3D (C, H), U-Net3D++ (D, I), and FreeSurfer (E, J), fell within a range of 0.46 to 0.60. The volume distributions derived from each algorithm are represented on the respective vertical axes.

To assess segmentation validity, we evaluated the Pearson correlation between automated and
manual amygdala volume estimates using 347 internal validation scans from the CKG-CCNC
dataset (excluding the training set). As shown in Fig. 5, BOLT3D achieved the highest correlation
with manual segmentation for both the left (R = 0.74) and right (R = 0.70) amygdalae,
outperforming U-Net3D, U-Net3D++, ResU-Net3D, and FreeSurfer (R = 0.46–0.61). This strong
linear association demonstrates BOLT3D's superior accuracy in volumetric quantification. In
addition, the narrow scatter distribution observed with BOLT3D highlights its within-subject
consistency and stability across individuals. To further quantify agreement and systematic
deviation, Bland–Altman analysis was conducted on the same dataset (Fig. 6). BOLT3D showed
the narrowest limits of agreement (–0.66 to +0.35 mm³) and the smallest mean difference from
manual labels (–0.152 mm³), indicating minimal bias and high consistency. In contrast, alternative
methods exhibited substantially greater overestimations, with average differences ranging from –
0.647 to –1.874 mm³. These discrepancies were up to 12.329 times larger than those observed
with BOLT3D, emphasizing its advantage in volumetric measurement precision.
206
To evaluate the capability of each algorithm to capture developmental trajectories, we plotted
amygdala volume growth curves across age using algorithm-derived segmentations (Fig. 7).
These were benchmarked against manually annotated volumes, considered the reference standard
(*13*). Both manual and automated segmentations revealed parallel growth patterns for boys and
girls, with boys consistently exhibiting larger amygdala volumes throughout development.
Manual tracing indicated a linear increase in bilateral amygdala volume from childhood to early
adulthood, a trend closely mirrored by BOLT3D, which employed multi-feature fusion. This was
supported by the estimated degrees of freedom (edf) reported in Table S2. Although the bilateral
amygdala volumes predicted by BOLT3D were slightly larger than those of manual annotations,
the scatter plot exhibits a more confined aggregation among age cohorts. In contrast, FreeSurfer
produced an inverted U-shaped trajectory that deviated markedly from the linear pattern observed
in both manual and BOLT3D results. Thus, the scatter plots reveal an increase in variability
between age cohorts, with bilateral amygdala volumes exceeding those derived from both manual
annotations and BOLT3D. This outcome demonstrates significant advantages for the fitting of
growth curves compared to other algorithms, attesting to the robustness and accuracy of BOLT3D
in considering gender- and age-related changes when estimating amygdala volume. Compared to
conventional and other advanced algorithms, this technique excels at capturing subtle changes in
growth curves, not only in terms of overall adaptation efficiency but also in terms of accurately
predicting curve details and particular features. These findings improved our understanding of
amygdala development over time with respect to gender differences and age-related factors.
227

A   BOLT-3D

B   U-Net3D

C   U-Net3D++

D   FreeSurfer

E   ResU-Net3D

228
229 **Fig. 6. Bland–Altman analysis of volumetric agreement between automated methods and manual reference.** Bland–Altman plots were used
230 to assess the agreement between volume estimates from different automated segmentation algorithms and the manual reference standard across 347
231 left amygdala scans. The central dashed blue lines indicate the mean differences, and the dashed yellow lines represent the limits of agreement
232 (±1.96 standard deviations from the mean). Each blue dot corresponds to an individual subject.

Fig. 7. The developmental trajectory of the amygdala, as delineated by our model and comparative methodologies. The FreeSurfer results (left) exhibit an inverted U-shaped curve, indicative of a non-linear growth pattern. Conversely, the growth curves predicted by our BOLT3D model (right) exhibit a striking agreement with the linear trajectory observed in the manual tracing method (middle). Blue denotes trajectories for males, while red represents trajectories for females. These trajectories are enveloped by shaded 95% confidence intervals. Individual scatter points represent segmentation outcomes from distinct cases, while the lines connecting these points indicate results acquired from multiple scans of the same participant.

AmygdalaGo-BOLT3D Model Availability

The AI training platform supporting this work was provided by High-Flyer AI (Hangzhou High-Flyer AI Fundamental Research Co., Ltd.). We deploy the optimal model parameters to be applied to any user-specified dataset in the interest of open science as well as provide tutorials and source codes at the Science Data Bank (https://ccnp.scidb.cn/en).

DISCUSSION

Deep-learning methods of tracing boundaries of amygdala are highly valuable for reproducibility by providing standardized, automated pipelines that minimize the variability introduced by manual tracing or traditional atlas-based methods. In open neuroscience, where large-scale datasets are shared across institutions, AI-driven segmentation ensures consistent and reproducible annotations, making results more comparable across studies. In the present work, we develop an open-source AI tool, AmygdalaGoBOLT3D, which allows researchers to collaborate,

validate, and refine models using publicly available datasets, fostering transparency and
innovation. Traditional segmentation techniques, whether manual or atlas-based, are time-
consuming and prone to inter-rater variability, especially for small structures like the amygdala. A
deep-learning model such as AmygdalaGO-BOLT3D trained on large datasets can provide 1)
higher segmentation accuracy, especially for challenging cases with low-contrast boundaries; 2)
faster processing, reducing the time required for segmentation from hours to seconds; 3)
improved generalization, allowing them to adapt to different populations, imaging protocols, and
scanner types. Another example of AI-based segmentation using multi-atlas priors and 3D
convolutional networks (*32*) has demonstrated superior performance over traditional methods.
Our AmygdalaGo addressed the intricacies posed by low contrast and structural complexities that
distinguish the amygdala from adjacent tissues. A boundary contrastive learning algorithm was
efficient to align model-predicted boundaries more accurately with a ground truth, culminating in
more precise segmentation across a wide range of subject ages, ranging from childhood and
adolescence to adulthood. It also maintained remarkably consistent performance when deployed
in multi-center adult datasets, underscoring exceptional generalization proficiency and robust
performance across varied data sources and contexts. This transformer could be a valuable new
tool in the field of cognitive neuroscience. For example, previous studies have identified a
relationship between the size of social networks and the volume of the amygdala (*33–35*).
Recent advances in open neuroimaging data have significantly increased our understanding of
the intricate structures and networks within the human brain (*36*). The aggregation of images from
various large-scale data repositories has significantly improved statistical power, allowing for the
discernment of subtle variability within the human amygdala (*37,38*). However, there is a
pressing need for new research methodologies to enhance the computational efficiency and
practical applicability of these automated extraction tools (*13,39*). Global imaging collaborations
have been instrumental in the evolution of population neuroscience (*40,41*), driven by extensive
MRI initiatives (*42*), which have been crucial for driving innovations in analytical techniques and
translational research (*43*). As an open-source deep-learning segmentation tool, AmygdalaGO-
BOLT3D democratizes access to high-quality neuroimaging analysis, making it possible for
researchers without extensive expertise in neuroanatomy to conduct high-precision studies. This
is crucial for 1) low-resource institutions that may lack access to expert manual tracers; 2) large-
scale, multi-site collaborations where standardized, automated segmentation ensures data
harmonization; 3) early-career researchers and students who can leverage open-source AI tools
without requiring specialized training in segmentation techniques. By integrating deep learning
into open neuroscience platforms, the AmygdalaGO-BOLT3D pipeline can be widely distributed,
continually improved, and used globally, accelerating discoveries in neurodevelopment,
psychiatric disorders, and neurodegenerative diseases.
We note that the present study lacks a detailed subdivision of the amygdala, specifically finer-
grained nuclei labeling. Future work will focus on providing granular annotations and establishing
a computational baseline to support a more nuanced analysis of the amygdala. Unlike static atlas-
based segmentation tools, AmygdalaGO-BOLT3D improves over time by leveraging
crowdsourced data and federated learning approaches. This means that as new datasets become
available, its model can be updated, enhancing its robustness and adaptability. Community-driven
platforms such as OpenNeuro (https://openneuro.org/), NeuroVault (https://neurovault.org/), and
ScienceDB (https://ccnp.scidb.cn/en) can serve as repositories for the model training and
validation, ensuring that this AI-driven technique remains cutting-edge and inclusive.
AmygdalaGo-BOLT, a deep-learning method for boundary tracing in human brain images,
offers a scalable, accurate, and open-access solution for amygdala segmentation. It aligns with the
principles of open neuroscience in four keyways: 1) Reproducibility - AI-driven segmentation
ensures consistent and replicable results across studies; 2) Efficiency - Faster and more precise
segmentation compared to manual tracing; 3) Accessibility - Enables global participation in

neuroimaging research; 4) Adaptability - The model improves over time with diverse datasets.
Unlike conventional approaches, BOLT3D incorporates an MGAC module, specifically designed
to integrate global and local semantic features. Additionally, its boundary contrast learning
strategy refines edge delineation, addressing the persistent challenge of distinguishing the
amygdala from adjacent structures. These innovations establish AI-driven segmentation as a
transformative tool for large-scale brain imaging, advancing more inclusive, transparent, and
impactful discoveries in amygdala neuroscience.
316
317 **MATERIALS AND METHODS**
318
This section provides an overview of the datasets, model architecture, training procedures, and
evaluation protocols used in the development and validation of AmygdalaGo-BOLT3D. We first
describe the MRI datasets employed for model training and validation. Next, we detail the
network architecture, including its multi-granularity adaptive collaboration, boundary contrast
learning, and transformer-based refinement modules. Subsequently, we explain the training
configuration and implementation settings. Finally, we present the evaluation metrics utilized to
assess segmentation performance.
326
327 **Datasets**
328
Training Dataset
The AmygdalaGo-BOLT3D model was trained using data from the Chongqing cohort of the
Chinese Color Nest Cohort (CKG-CCNC), part of the CCNP development project (*16–18*). This
cohort included 198 baseline participants aged 6–17 years, from whom a total of 427 T1-weighted
MRI scans were acquired. To ensure balanced age distribution and demographic
representativeness, 140 participants were selected from the full pool. For each, one high-quality
scan was retained after rigorous visual inspection to exclude motion artifacts and anatomical
abnormalities. From these, 80 scans were randomly selected for model training (Table 2). Manual
boundary tracing of the amygdala was performed according to standardized protocols (*13*).
338
Validation Datasets
Model validation was conducted using three datasets. First, the remaining 347 MRI scans from
the full CKG-CCNC sample (excluding the 80 used for training) were used for internal validation.
Second, external validation was performed using brain MRI data from two independent cohorts:
the Beijing Normal University Childhood Adversity Cohort (BNU-CAC), comprising 116
children aged 8–13 years scanned once (*19*), and the Zhejiang University Multi-center Traveler
Cohort (ZJU-MTC), which included three adult participants scanned across ten different MRI
centers using harmonized protocols (*20*). In all validation datasets, the amygdalae were manually
segmented using the same boundary tracing procedures as in the training set to ensure
consistency. During testing, input image dimensions were down-sampled to 48 × 64 × 80 to
minimize computational demands. No post-processing optimization techniques were employed,
thereby ensuring an objective assessment of model performance.
351

Table 2: Sample demographic information and sample characteristics of the three testbed datasets.

	CKG-CCNC (training)	CKG-CCNC (validation)	BNU-CAC (validation)	ZJU-MTC (validation)
N (number of participants)	80	176	116	3
N (females/males)	40/40	93/83	60/56	2/1
Design	cross-sectional	accelerated longitudinal	cross-sectional	longitudinal
Age range (baseline)	6–17 (years)	6–17 (years)	8–13 (years)	23,26/23 (years)
N (number of scans)	80	347	116	30

352
353 **Model Architecture**
354

Overall Framework

We implemented AmygdalaGo-BOLT in three stages: 1) robust global localization, 2) precise delineation, and 3) generalizable segmentation. When examining the structure of the amygdala, the observer must first capture the entire cerebral region and subsequently estimate the approximate position of the amygdala within the image. This estimate relies on prior knowledge of limbic system anatomy and considers adjacent structures such as the hippocampus. After this initial phase, the observer leverages a detailed understanding of internal amygdala morphology, gray matter intensity, and other pertinent information used to execute a full regional delineation. The segmentation process is then enhanced using a transformer-based algorithm employed to discern boundary contrast. It aims to improve both the robustness of global amygdala localization and the precision of boundary delineation, thereby improving inter-individual consistency. This process includes the following key elements:

1. Comprehensive detection of amygdala positioning in T1-weighted (T1w) MR images was achieved by employing a transformer-based network. This model (BOLT3D) constructs a multi-granularity adaptive collaboration (MGAC) architecture, which integrates a global coarse-grained perceptual module. It determines the global semantics of the amygdala structure, thereby enhancing positional sensitivity. Since intricate details are often neglected in global representations, a local fine-grained enhancement module was developed to increase the perception and retention of detailed information. Coarse-grained global and fine-grained local data were further harmonized by introducing a multi-granular adaptive fusion module. This allowed BOLT3D to concurrently consider differences between the entire amygdala and adjacent structures, as well as similarities within the amygdala itself. It facilitates the recognition of global positioning characteristics and local disparities, thereby improving the accuracy and robustness of amygdala structure location estimates. The overarching design objective is then to perform a more precise and exhaustive detection of amygdala tracing contours.

2. A novel strategy is introduced for learning boundary contrast, to address dependency challenges for manual segmentation boundaries and enhance the congruence between predicted and actual delineations. It improves the delineation of limbic structures from adjacent tissues by amplifying characteristic differences between the amygdala and surrounding tissues, while minimizing intra-amygdala variations. Consequently, this step refines the alignment between automated boundary segmentation and manual segmentation outcomes, enabling a more precise demarcation of amygdala dimensions.

3. A modified Segment Anything Model (SAM) is introduced to refine coarse predictions and enhance the generalizability of BOLT3D. Coarse outputs from the MAGC module are sampled as point cues and fed into the 3D Prompt Encoder, which integrates anatomical priors to enhance segmentation accuracy. To adapt SAM for amygdala segmentation, three key modifications are implemented: (1) a lightweight Volumetric Feature Encoder (VFE) to extract MRI-specific volumetric features, (2) a 3D Prompt Encoder (PE) to refine spatial embeddings and anatomical representations, and (3) a Volumetric Mask Decoder (VMD) to enhance segmentation precision by processing the refined feature representations. These adaptations enable SAM to effectively manage the amygdala's small size, improve boundary delineation via contrastive learning, and enhance generalization across diverse subjects. By integrating these domain-specific refinements, the model achieves greater segmentation accuracy and robustness.

Fig. 8. A schematic diagram of the AmygdalaGo-BOLT architecture. (A) The overall model structure consists of two principal components: a MAGC-Net (responsible for initial segmentation) and an SAM. The latter is tasked with the refinement of segmentation results, including three essential components: a lightweight Volume Feature Encoder (VFE), a 3D Prompt Encoder (PE), and a Volumetric Mask Decoder (VMD). The MAGC network produces preliminary segmentation results and strategically samples voxels, which are then fed into the SAM prompt encoder to guide the refinement process. (B) The MAGC block, a key network module designed to address challenges posed by the size of the amygdala, ensures the extraction of accurate semantic features. (C) The included edge contrast learning optimization strategy, incorporated to further augment edge delineation and enhance overall segmentation precision.

Multi-Granularity Adaptive Collaboration

Global and local semantic features were initially derived from the original MR image data using a multi-granularity semantic generation module, as depicted in Fig. 8B. Specifically, for T1w images I, the module exploited local induction capabilities by employing two 3D convolutions to extract primary local features F_l. This approach facilitated the computation of relationships among feature points, thereby enabling the extraction of global semantic information from regions

exhibiting high responses to initial position features. Subsequently, preliminary global features F_g were constructed as follows. A feature map F' of dimensions $d \times H \times W$ was derived from the input image I using a single convolutional layer and subsequently projected onto a weighting map via two convolutional layers. The channel count in the weight map was given by hw ($h \leq H$, $w \leq W$), where h and w represent the dimensions of a predefined global semantic map. The weight map was then flattened for the Softmax computation, and the resulting weights were used to aggregate semantic information within the F' mapping through matrix multiplication, producing the final F_g result. In the following illustrations, dimensions are presented in an abbreviated form for brevity.

The MGAC module includes three components: a global module for coarse-grained perception, a local module for fine-grained enhancement, and an adaptive module for multi-granularity fusion, as depicted in Fig. 8C. These components independently optimize global and local features, which are interactively integrated to enhance model performance. Fig. 8B illustrates the positioning of the adaptive MGAC module within the overall framework, while Fig. 8C details the corresponding internal structure. Each MGAC module receives two inputs: global coarse-grained (F_g) and local fine-grained (F_l) semantic characteristics. Significant discrepancies in semantic distributions between these two sets of characteristics were mitigated by using BatchNorm3D to normalize the inputs. A linear position projection from previous work was then mapped based on the positional relationships of the elements, ensuring the arrangement of tokens within the transformer remained unchanged while preserving their positional correlations (21). However, this approach neglects local structural information, which is vital for image data. Although integrating positional encoding enables the transformer to learn positional relationships, such encoding from randomly initialized parameters requires extensive training data, which poses a challenge for medical image analysis. Traditional positional encoding data were then substituted with convolutional layers, thereby incorporating the inductive bias inherent in convolutions. This substitution facilitated the preservation of local structural information intrinsic in the images while avoiding the limitations of positional encoding.

A three-dimensional (3D) depth-wise convolution strategy was employed to convolve relationships among local neighborhoods within fine-grained semantic features, thereby introducing visual bias. In contrast, 3D pointwise convolutions were used to calculate global coarse-grained semantic features. The results, denoted as F_g and F_l, were subsequently flattened into a one-dimensional (1D) sequence to facilitate Transformer processing. This transformation involved converting F_g into a global query vector F_g^q and a global content vector F_g^v. Similarly, F_l, which encapsulates detailed information, was transformed into a local index vector F_l^k and a local content vector F_l^v through analogous operations. In contrast, the internal architectures of the global coarse-grained perception module and the local fine-grained enhancement module remained consistent, as illustrated in Fig. 8B. These modules are primarily comprised of two components: a multi-head self-attention mechanism and a feedforward neural network. The Z_l term initially replaced the input in the multi-head self-attention mechanism and was then expanded into a 1D sequence. A fully connected layer served as the transformation layer, converting the input to a query vector, an index vector, and a content vector. The multi-head attention matrix could subsequently be determined as:

$$Z_l' = MHSA\big(LN(Z_l)\big) + Z_l \tag{1}$$

where, the feedforward layer further refined the relationships among voxel features, while integration with residual mechanisms augmented the data flow. This approach preserved original features and mitigated vanishing gradients, as described by:

$$Z_{l'}^v = FFN\big(LN(Z_l')\big) + Z_l' \qquad (2)$$

In this context, $MHSA(\cdot)$ denotes a multi-head self-attention mechanism, $LN(\cdot)$ signifies layer normalization, and $FFN(\cdot)$ represents a feedforward neural network. The global coarse-grained perception module and the local fine-grained enhancement module employed Eqs. 1 and 2 to transform the input global content vector F_g^v and the local content vector F_l^v, respectively. The resulting updated global content vector $F_{g'}^v$ and the local content vector $F_{l'}^v$ were obtained upon completion of the processing step. The correlation matrix Att was then derived using F_g^q as a query vector and F_l^k as an index vector, within the context of the adaptive multi-granularity fusion module, as illustrated in Fig. 8. The resulting correlation was calculated as follows:

$$Att_{i,j} = \frac{1}{\sqrt{d_k}}\left(\frac{e^{F_{g_i}^q \cdot F_{l_j}^{k\top}}}{\sum_{j=1}^n e^{F_{g_i}^q}}\right) \qquad (3)$$

where $Att_{i,j}$ represents the attention weight quantifying the alignment between the i-th voxel feature in the global query vector F_g^q and the j-th voxel feature in the local index vector F_l^k. Correlation scores between different local features were then computed using a scaled dot-product operation. To stabilize the attention distribution and prevent over-concentration in specific local regions, a scaling factor of $1/\sqrt{d_k}$ was applied, where d_k denotes the dimension of an individual attention head, corresponding to the number of channels within F_g^q. After computing the similarity matrix $Att_{i,j}$, it is mapped back into the original feature space, encompassing both the global content vector space F_g^v and the local content vector space F_l^v. Specifically, the given similarity matrix Att undergoes direct propagation into a Softmax function, to produce a sparse feature distribution for the local fine-grained branch F_l^v. This distribution is then subjected to matrix multiplication with F_l^v, followed by convolution operations to further refine the feature distribution. This sequence can be represented by:

$$F_l' = DW(softmax(Att)F_l^v) + F_{l'}^v \qquad (4)$$

In the case of a global coarse-grained branch F_g^v, the matrix Att requires transposition to determine the similarity score between individual feature points and the query feature. Subsequently, matrix multiplication with F_g^v is performed and the resultant product is processed using deep separable convolutions to enhance the smoothness of feature distributions. In addition, a residual technique is employed to preserve the integrity of information and mitigate issues with vanishing gradients. Ultimately, this module yields the following output:

$$F_g' = DW\big(softmax(Att^\top)F_g^v\big) + F_{g'}^v \qquad (5)$$

Tracing Boundary Contrast Learning

Most existing 3D segmentation algorithms (*22–24*) neglect the explicit segmentation of structural boundaries. However, some algorithms strive to improve boundary delineation using attention mechanisms (*25,26*). Despite these efforts, there remains a lack of comprehensive and targeted research focused on evaluating the influence of boundary regions on segmentation outcomes. To address this issue, we propose meticulously aligning boundary information from manual annotations with model segmentation outputs, thereby introducing an innovative boundary contrast learning framework.

Previous contrastive learning methodologies have predominantly been applied at the image
level. For example, positional techniques (*27*) extend 3D images to 2D sequences to determine
spatial relationships between positive and negative samples as part of contrastive learning. The
Mask Transfiner model (*28*) adopts contrastive learning within image patches, rather than at the
image level, utilizing pseudo-labels to generate patches with distinct semantic categories and
forming positive and negative sample pairs. However, these strategies are inadequate for high-
resolution segmentation of the amygdala, which exhibits proximity with same-type pixels
throughout a 3D image. It requires the separation of pixel types and the clustering of similar
pixels based on individual labels. Here, boundary pixels were used to construct positive and
negative sample pairs to maximize distinctions between boundary pixels and adjacent non-
relevant pixels, as illustrated in Fig. 8. Specifically, the local neighborhood around the boundary
was designated as a subset, establishing a contrast learning strategy for overlapping 3D patch
areas distributed throughout 3D space. Kernels adjacent to the boundary were then used to select
the dimensions of 3D patch spaces in each subset. Manually segmented amygdala data thus
served as a basis for constructing both positive and negative samples. The InfoNCE information
maximization algorithm (*29*) was then used to calculate the disparity between positive and
negative samples in the latitude space on a hypersphere. The kernel size was set to $5 \times 5 \times 5$
(based on the anatomical dimensions of the amygdala) and each subset formed positive and
negative samples within this specified area. As illustrated in Fig. 8, the model was specifically
designed to focus on and exclusively compute boundary voxels. Initially, all boundary regions B_l
were considered in manual annotations. For each voxel x_i in B_l, the sampling scope for positive
and negative voxels was then confined to the local neighborhood N_i. Under this constraint,
positive samples $x_j \in N_i \wedge l_i = l_j$ were identified for boundary voxels x_i, while any remaining
neighborhood voxels were treated as negative samples $x_j \in N_i \wedge l_i \neq l_j$. In this paper, j denotes
sample voxels within the neighborhood N_i corresponding to the voxel i, with l_i and l_j representing
the voxel categories for x_i and x_j, respectively. Consequently, the boundary voxel contrast learning
algorithm enhanced feature discernment for structurally organized boundary voxels, thereby
establishing a target for contrast optimization within boundary voxels, which is crucial for
enhancing the segmentation of boundary regions. Specifically, for the voxels x_i within boundary
regions B_l, learned representations were incentivized to be more congruent with voxel features
from the same category, while being less congruent with features of disparate categories. This
process can be described as follows:

542
$$L_{CBL} = \frac{-1}{B_l} \sum_{x_i \in B_l} \log \left(\frac{\sum_{x_j \in N_i \wedge l_j = l_i} \exp\left(-\frac{d(f_i, f_j)}{\tau}\right)}{\sum_{x_k \in N_i} \exp\left(-\frac{d(f_i, f_k)}{\tau}\right)} \right) \quad (6)$$

543
where f_i represents the characteristics of x_i, $d(\cdot, \cdot)$ denotes the distance function, and τ is a
temperature coefficient used in contrastive learning. The numerator captures the similarity
between positive instances, while the denominator reflects the similarity between positive and
negative instances. In a contrastive loss framework, the objective is to maximize similarity among
positive pairs while minimizing similarity between positive and negative pairs. Consequently,
increasing intra-class similarity (bringing positive instances closer) while decreasing inter-class
similarity (pushing positive and negative instances further apart) leads to a lower loss. The
temperature coefficient τ is a predefined hyperparameter that controls model's sensitivity to
negative samples. Larger values of τ flatten the distribution of $d(f_i, f_j)$, causing the model to treat
all negative samples more uniformly, which reduces learning efficacy. Conversely, smaller values
of τ emphasize more difficult negative samples, some of which may be mislabeled positive

samples, leading to false negatives. This approach limits model convergence and restricts
generalization capabilities. Therefore, selecting an optimal temperature coefficient is crucial to
balancing learning efficiency and discrimination ability.
558
SAM Consistency Module
The SAM framework was used to develop a consistency strategy to mitigate discrepancies arising
from the scanning of different subjects. This strategy is comprised of three integral components: a
volume feature encoder, a 3D prompt encoder, and a volume mask decoder. The principal
contributions of each can be specifically delineated as follows. First, an SAM is introduced,
which is specifically designed for amygdala segmentation tasks. Unlike existing approaches to
improving SAMs, the novelty of our model lies in its comprehensive consideration of factors such
as the volume, shape, and relative position of the amygdala. This process eschews conventional
slice-by-slice feature extraction in favor of a holistic total volume approach. The model also
establishes interslice associations, which are exceptionally well-suited to structures with intricate
core regions. In contrast to traditional algorithms, this technique provides a more comprehensive
representation of anatomical structures, particularly for smaller entities.
Second, the incorporation of a 3D prompt encoder ensures the preservation of prior spatial
position information and 3D spatial features provided by the user. In contrast to 2D prompt
encoders, this strategy provides more precise relative position cues in multidimensional space.
The effective merging of 3D cue information with embedding features derived from a volume
feature encoder is then facilitated by a novel volume mask decoder. This decoder harnesses
interaction mechanisms between prior cue and MRI embeddings, facilitating seamless integration.
The fusion mechanism then adeptly captures nuanced details within the feature space, offering a
robust tool for the precise depiction of anatomical structures. SAMs constitute an interactive
segmentation methodology predicated on iterative operations. This framework enhances the
representational capacity of the model through the incorporation of positional cues and pre-
segmentation data, thereby facilitating continuous optimization of segmentation accuracy via
multiple interactive iterations. Notably, the accuracy of existing SAMs is suboptimal when
applied directly to medical imaging tasks (especially amygdala segmentation). To address this
issue, the structure of the proposed 2D SAM has been meticulously customized for amygdala
segmentation. This includes the introduction of an advanced SAM, which is comprised of three
integral encoders used for volume features, 3D cues, and volume masks.
The function of the Volume Feature Encoder (VFE) is to transform input T1w structural
images into an MRI embedding vector. Unlike the 2D encoder used in traditional SAMs, this
process allows simultaneous consideration of volume, shape, and relative position, thereby
offering a more comprehensive representation of anatomical structures to enhance the processing
of complex regions surrounding the core area. A 3D prompt encoder was also used to encode
prior information, incorporating interactive cues and existing amygdala segmentation results. The
3D prompt encoder consists of two components: a click-cue branch and a presegmentation cue
branch. The click-cue branch converts user-provided cue points into learnable location embedding
features to more precisely delineate amygdala location. The pre-segmentation prompt encoder
uses the last click made during interactive segmentation as input. Alternatively, it provides pre-
segmentation results to the model, thereby prompting adjustments and optimization of the current
segmentation result. As such, a volume mask detector (VMD) was developed to effectively
integrate information from the prompt encoder with embeddings produced by the feature encoder.
This VMD also facilitated the retrieval and refinement of information pertaining to the amygdala,
ensuring a seamless alignment of cue feature information and initial feature encoder output.
The VMD is a pivotal component to exhaustively explore key characteristics within the
amygdala, thereby enhancing model efficacy in intricate clinical scenarios. It aims to combine
MRI embedding vectors (produced by the volume feature encoder) with userprovided prompt

inputs (used to determine the correlation between them), culminating in precise predictive results. The 3D mask decoder generates MRI and cue embeddings using a multi-layered fusion 3D feature encoder, facilitating multi-level and multiperspective information extraction. This comprehensive fusion mechanism enables a more complete assimilation of MR images and improves the differentiation of anatomical structures, thereby increasing predictive precision. In conclusion, the decoder generates precise predictions of specific structures or lesions within images, offering crucial support for clinicians in making accurate diagnoses and devising treatment strategies.

Training Configuration

Implementation of Loss Function
We implemented an advanced deep-supervised strategy to formulate the loss function. Specifically, this involved the integration of supervisory signals in each intermediate and terminal module, thereby facilitating enhanced gradient propagation and optimization of network training efficiency. Two distinct loss functions were incorporated for each supervisory signal, namely, binary crossentropy (BCE) and Dice loss. The overall loss function was constructed as follows:

$$L = \sum_{k=1}^{4} \left(L_{\mathrm{BCE}}^{k} + L_{\mathrm{Dice}}^{k} \right) \tag{7}$$

An adapted version of BCE loss was employed to address issues with imbalances between positive (amygdala) and negative (other tissue) samples. Hereafter, the superscript k is excluded for simplicity, while L$_{extBCE}$ is defined as follows:

$$L_{\mathrm{BCE}} = -\frac{\sum_{i=1}^{H} \sum_{j=1}^{W} (1 + \alpha_{i,j}) \sum_{l=0}^{1} (g_{i,j} = l) log Pr(p_{i,j} = l | \Psi)}{\sum_{i=1}^{H} \sum_{j=1}^{w} (\alpha_{i,j})} \tag{8}$$

where $l \in (0, 1)$ denotes two label categories. The variables $p_{i,j}$ and $g_{i,j}$ represent predicted and ground truth values, respectively, at the spatial coordinate (i, j) within a CT image characterized by a width of W and a height of H. The symbol Ψ encompasses all model parameters and $Pr(p_{i,j} = l)$ signifies the predicted probability. The term $\alpha_{i,j} \in [0, 1]$ describes the pixel-specific weight and can be expressed as:

$$\alpha_{i,j} = \left| \frac{\sum_{(m,n) \in A_{i,j}} g_{m,n}}{\sum_{(m,n) \in A_{i,j}} 1} - g_{i,j} \right| \tag{9}$$

where Ai,j denotes the region adjacent to pixel (i, j) and $| \cdot |$ signifies the calculation of absolute value. Furthermore, Dice loss was defined as:

$$L_{\mathrm{Dice}} = 1 - \frac{\sum_{i=1}^{H} \sum_{j=1}^{W} (2g_{i,j}p_{i,j})(1 + \alpha_{i,j})}{\sum_{i=1}^{H} \sum_{j=1}^{W} (g_{i,j} + p_{i,j} + g_{i,j}p_{i,j})(1 + \alpha_{i,j})} \tag{10}$$

Implementation Details
The model was implemented using the PyTorch framework and trained on a full capabilities of the Tesla A10 GPU to optimize computational efficiency. The AdamW optimizer (*30*), a common choice within the transformer architecture domain, was used for routine updates of network parameters. The learning rate was empirically set to 1e^{-4}, balancing training stability and

convergence speed, with a weight decay of $1e^{-4}$. Memory consumption was mitigated by designating a batch size of 1, with a training process encompassing 100 iterations. This configuration ensured the model underwent sufficient training cycles to achieve optimal performance and effectively discern feature representations.

Evaluation Metrics

Model performance was assessed using standard medical image segmentation metrics, including region overlap measures (Dice Similarity Coefficient and Jaccard Similarity), boundary distance measures (Hausdorff Distance (HD95), Average Surface Distance (ASD), and Average Symmetric Surface Distance (ASSD)), volumetric comparison (Relative Volume Difference, RVD), and classification metrics (Precision and Recall) (*31*).

The Dice similarity coefficient (Dice) measures the similarity between a predicted binary region (P) and a ground truth (GT). It is formulated as:

$$\text{Dice} = \frac{2|P \cap G|}{|P| + |G|} \tag{11}$$

where P and G denote voxel sets for the segmented area and GT, respectively. The term $|\cdot|$ denotes a cardinality computation operation, which provides the number of elements in a set.

Jaccard Similarity (JS) is defined as the area of intersection between predicted segments and labels, divided by the area of union between the two, expressed as:

$$\text{JS} = \frac{|P \cap G|}{|P \cup G|} \tag{12}$$

Hausdorff Distance (HD) measure the maximum surface distance distribution between the predicted segmentation result and the ground truth. HD95 is an improvement on the Hausdorff distance that reduces the impact of outliers by taking the 95% quantile.

$$\text{HD95}(P, G) = \text{Percentile}_{95}\left(D_{pred \to gt} \cup D_{gt \to pred}\right) \tag{13}$$

Average Surface Distance (ASD) is used to measure the surface distance difference between the predicted segmentation result and the ground truth.

$$\text{ASD}(P, G) = \frac{1}{|P| + |G|}\left(\sum_{x \in P} \min_{y \in G} d(x, y) + \sum_{y \in G} \min_{x \in P} d(y, x)\right) \tag{14}$$

Average Symmetric Surface Distance (ASSD) is a commonly used symmetric surface distance metric in medical image segmentation evaluation. It measures the surface distance difference between the predicted segmentation result and the ground truth, while considering the bidirectional distance from prediction to GT and from GT to prediction.

$$\text{ASSD}(P, G) = \frac{1}{2}\left(\frac{1}{|P|}\sum_{x \in P} \min_{y \in G} d(x, y) + \frac{1}{|G|}\sum_{y \in G} \min_{x \in P} d(y, x)\right) \tag{15}$$

Precision is a commonly used evaluation metric that measures the proportion of positive predictions in the predicted segmentation results that are correct, especially for unbalanced datasets.

$$\text{Precision} = \frac{\sum_i(P_i = 1 \wedge G_i = 1)}{\sum_i(P_i = 1 \wedge G_i = 1) + \sum_i(P_i = 1 \wedge G_i = 0)} \tag{16}$$

Recall is another important evaluation metric that measures how many positive pixels in the true segmentation are correctly predicted as positive. It reflects the coverage of the model for positive samples.

$$\text{Recall} = \frac{\sum_i(P_i = 1 \wedge G_i = 1)}{\sum_i(P_i = 1 \wedge G_i = 1) + \sum_i(P_i = 0 \wedge G_i = 1)} \tag{17}$$

Relative Volume Difference (RVD) is one of the commonly used evaluation indicators in medical image segmentation tasks, which is used to measure the volume difference between the predicted segmentation result and the GT.

$$\text{RVD} = \frac{\sum_i P_i - \sum_i G_i}{\sum_i G_i} \tag{18}$$

Supplementary Materials

This PDF file includes:
Table S1, S2

REFERENCES AND NOTES

1. S. Sammallahti, F. Serdarevic, H. Tiemeier, Excessive crying, behavior problems, and amygdala volume: A study from infancy to adolescence. *J. Am. Acad. Child Adolesc. Psychiatry* **62**, 675–683 (2023).
2. Y. Chai, P. Gehrman, M. Yu, T. Mao, Y. Deng, J. Rao, H. Shi, P. Quan, J. Xu, X. Zhang, H. Lei, Z. Fang, S. Xu, E. Boland, J. R. Goldschmied, H. Barilla, N. Goel, M. Basner, M. E. Thase, Y. I. Sheline, D. F. Dinges, J. A. Detre, X. Zhang, H. Rao, Enhanced amygdala-cingulate connectivity associates with better mood in both healthy and depressive individuals after sleep deprivation. *Proc. Natl. Acad. Sci. U S A* **120**, e2214505120 (2023).
3. D. Paré, D. B. Headley, The amygdala mediates the facilitating influence of emotions on memory through multiple interacting mechanisms. *Neurobiol. Stress* **24**, 100529 (2023).
4. J. Song, Amygdala activity and amygdala-hippocampus connectivity: Metabolic diseases, dementia, and neuropsychiatric issues. *Biomed. Pharmacother.* **162**, 114647 (2023).
5. Z. Ben-Zion, N. Korem, N. B. Fine, S. Katz, M. Siddhanta, M. C. Funaro, O. Duek, T. R. Spiller, S. K. Danböck, I. Levy, I. Harpaz-Rotem, Structural neuroimaging of hippocampus and amygdala subregions in posttraumatic stress disorder: A scoping review. *Biol. Psychiatry Glob. Open Sci.* **4**, 120–134 (2024).
6. B. Fischl, D. H. Salat, E. Busa, M. Albert, M. Dieterich, C. Haselgrove, A. Van Der Kouwe, R. Killiany, D. Kennedy, S. Klaveness, A. Montillo, N. Makris, B. Rosen, A. M. Dale, Whole brain segmentation: Automated labeling of neuroanatomical structures in the human brain. *Neuron* **33**, 341–355 (2002).
7. M. Trombini, D. Solarna, G. Moser, S. Dellepiane, A goal-driven unsupervised image segmentation method combining graph-based processing and Markov random fields. *Pattern Recognit.* **134**, 109082 (2023).
8. B. Patenaude, S. M. Smith, D. N. Kennedy, M. Jenkinson, A Bayesian model of shape and appearance for subcortical brain segmentation. *Neuroimage* **56**, 907–922 (2011).
9. C. Y. Liu, J. S. Chou, Bayesian-optimized deep learning model to segment deterioration patterns underneath bridge decks photographed by unmanned aerial vehicle. *Autom. Constr.* **146**, 104666 (2023).
10. L. Xie, L. E. Wisse, J. Wang, S. Ravikumar, P. Khandelwal, T. Glenn, A. Luther, S. Lim, D. A. Wolk, P. A. Yushkevich, Deep label fusion: A generalizable hybrid multi-atlas and deep convolutional neural network for medical image segmentation. *Med. Image Anal.* **83**, 102683 (2023).
11. J. V. Manjón, P. Coupé, volBrain: An online MRI brain volumetry system. *Front. Neuroinf.* **10**, 30 (2016).

12. H. Liu, D. Nie, J. Yang, J. Wang, Z. Tang, A new multi-atlas based deep learning segmentation framework with differentiable atlas feature warping. *IEEE J. Biomed. Health. Inf.* **28**, 1484–1493 (2023).

13. Q. Zhou, S. Liu, C. Jiang, Y. He, X. N. Zuo, Charting the human amygdala development across childhood and adolescence: Manual and automatic segmentation. *Dev. Cognit. Neurosci.* **52**, 101028 (2021).

14. J. C. Pruessner, L. M. Li, W. Serles, M. Pruessner, D. L. Collins, N. Kabani, S. Lupien, A. C. Evans, Volumetry of hippocampus and amygdala with high-resolution MRI and three-dimensional analysis software: Minimizing the discrepancies between laboratories. *Cereb. Cortex* **10**, 433–442 (2000).

15. Y. Lee, J. Kim, J. Willette, S. J. Hwang, in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (IEEE, 2022), pp. 7287–7296.

16. X. R. Fan, Y. S. Wang, D. Chang, N. Yang, M. J. Rong, Z. Zhang, Y. He, X. Hou, Q. Zhou, Z. Q. Gong, L. Z. Cao, H. M. Dong, J. J. Nie, L. Z. Chen, Q. Zhang, J. X. Zhang, L. Zhang, H. J. Li, M. Bao, A. Chen, J. Chen, X. Chen, J. Ding, X. Dong, Y. Du, C. Feng, T. Feng, X. Fu, L. K. Ge, B. Hong, X. Hu, W. Huang, C. Jiang, L. Li, Q. Li, S. Li, X. Liu, F. Mo, J. Qiu, X. Q. Su, G. X. Wei, Y. Wu, H. Xia, C. G. Yan, Z. X. Yan, X. Yang, W. Zhang, K. Zhao, L. Zhu, A longitudinal resource for population neuroscience of school-age children and adolescents in China. *Sci. Data* **10**, 545 (2023).

17. S. Liu, Y. S. Wang, Q. Zhang, Q. Zhou, L. Z. Cao, C. Jiang, Z. Zhang, N. Yang, Q. Dong, X. N. Zuo, Chinese Color Nest Project: An accelerated longitudinal brain-mind cohort. *Dev. Cognit. Neurosci.* **52**, 101020 (2021).

18. A. C. Feng, J. Qiu, X. Chen, X. Liu, X. N. Zuo, Chinese color nest project (CCNP) I: Growing up in China. *Chin. Sci. Bull.* **62**, 3008–3022 (2017).

19. J. Sun, Y. Jiang, X. Wang, S. Zilioli, P. Chi, L. Chen, J. Xiao, D. Lin, Cortisol reactivity as a mediator of peer victimization on child internalizing and externalizing problems: The role of gender differences. *Res. Child Adolesc. Psychopathol.* **50**, 283–294 (2022).

20. Q. Tong, H. He, T. Gong, C. Li, P. Liang, T. Qian, Y. Sun, Q. Ding, K. Li, J. Zhong, Multicenter dataset of multi-shell diffusion MRI in healthy traveling adults with identical settings. *Sci. Data* **7**, 157 (2020).

21. A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, J. Uszkoreit, N. Houlsby, in *Proceedings of the International Conference on Learning Representations* (OpenReview, 2020), pp. 1–22.

22. Ö. Çiçek, A. Abdulkadir, S. S. Lienkamp, T. Brox, O. Ronneberger, in *Proceedings of the Medical Image Computing and Computer-Assisted Intervention-MICCAI 2016: 19th International Conference* (Springer, 2016), pp. 424–432.

23. W. Chen, B. Liu, S. Peng, J. Sun, X. Qiao, in *Brainlesion: Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries: 4th International Workshop, BrainLes 2018* (Springer, 2019), pp. 358–368.

24. Y. Jiang, Y. Zhang, X. Lin, J. Dong, T. Cheng, J. Liang, SwinBTS: A method for 3D multimodal brain tumor segmentation using swin transformer. *Brain Sci.* **12**, 797 (2022).

25. H. Liu, G. Huo, Q. Li, X. Guan, M. L. Tseng, Multiscale lightweight 3D segmentation algorithm with attention mechanism: Brain tumor image segmentation. *Expert Syst. Appl.* **214**, 119166 (2023).

26. J. Cheng, J. Liu, L. Liu, Y. Pan, J. Wang, in *Proceedings of the 2019 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)* (IEEE, 2019), pp. 1031–1036.

27. L. Tang, Y. Zhan, Z. Chen, B. Yu, D. Tao, in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (IEEE, 2022), pp. 8489–8499.

28. L. Ke, M. Danelljan, X. Li, Y. W. Tai, C. K. Tang, F. Yu, in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (IEEE, 2022), pp. 4412–4421.

29. A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, I. Sutskever, in *Proceedings of the 38th International Conference on Machine Learning* (PMLR, 2021), pp. 8748–8763.

30. Y. Xu, H. Wei, M. Lin, Y. Deng, K. Sheng, M. Zhang, F. Tang, W. Dong, F. Huang, C. Xu, Transformers in computational visual media: A survey. *Comput. Vis. Media* **8**, 33–62 (2022).

31. A. Borji, M. M. Cheng, H. Jiang, J. Li, Salient object detection: A benchmark. *IEEE Trans. Image Process.* **24**, 5706–5722 (2015).

32. J. Wu, X. Tang, Brain segmentation based on multi-atlas and diffeomorphism guided 3D fully convolutional network ensembles. *Pattern Recognit.* **115**, 107904 (2021).

33. R. W. McGugin, A. Roche, J. Ma, I. Gauthier, Challenges in replication: Does amygdala gray matter volume relate to social network size?. *Cogn. Affect. Behav. Neurosci.* **24**, 707–719 (2024).

34. R. Kanai, B. Bahrami, R. Roylance, G. Rees, Online social network size is reflected in human brain structure. *Proc. R. Soc. Lond. B Biol. Sci.* **279**, 1327–1334 (2012).

35. K. C. Bickart, C. I. Wright, R. J. Dautoff, B. C. Dickerson, L. F. Barrett, Amygdala volume and social network size in humans. *Nat. Neurosci.* **14**, 163–164 (2011).

36. B. Lu, X. Chen, F. X. Castellanos, P. M. Thompson, X. N. Zuo, Y. F. Zang, C. G. Yan, The power of many brains: Catalyzing neuropsychiatric discovery through open neuroimaging data and large-scale collaboration. *Sci. Bull.* **69**, 1536–1555 (2024).

37. D. L. Cotter, C. E. Campbell, K. Sukumaran, R. McConnell, K. Berhane, J. Schwartz, D. A. Hackman, H. Ahmadi, J. C. Chen, M. M. Herting, Effects of ambient fine particulates, nitrogen dioxide, and ozone on maturation of functional brain networks across early adolescence. *Environ. Int.* **177**, 108001 (2023).

38. M. L. Hatzenbuehler, D. G. Weissman, S. McKetta, M. R. Lattanner, J. V. Ford, D. M. Barch, K. A. McLaughlin, Smaller hippocampal volume among Black and Latinx youth living in high-stigma contexts. *J. Am. Acad. Child Adolesc. Psychiatry* **61**, 809–819 (2022).

39. K. Ghanem, K. Saltoun, A. Suvrathan, B. Draganski, D. Bzdok, Longitudinal microstructural changes in 18 amygdala nuclei resonate with cortical circuits and phenomics. *Commun. Biol.* **7**, 477 (2024).

40. T. Paus, Population neuroscience: why and how. *Hum. Brain Mapp.* **31**, 891–903 (2010).

41. E. B. Falk, L. W. Hyde, C. Mitchell, J. Faul, R. Gonzalez, M. M. Heitzeg, D. P. Keating, K. M. Langa, M. E. Martz, J. Maslowsky, F. J. Morrison, D. C. Noll, M. E. Patrick, F. T. Pfeffer, P. A. Reuter-Lorenz, M. E. Thomason, P. Davis-Kean, C. S. Monk, J. Schulenberg, What is a representative brain? Neuroscience meets population science. *Proc. Natl. Acad. Sci. U S A* **110**, 17615–17622 (2013).

42. R. A. Bethlehem, J. Seidlitz, S. R. White, J. W. Vogel, K. M. Anderson, C. Adamson, S. Adler, G. S. Alexopoulos, E. Anagnostou, A. Areces-Gonzalez, D. E. Astle, B. Auyeung, M. Ayub, J. Bae, G. Ball, S. Baron-Cohen, R. Beare, S. A. Bedford, V. Benegal, F. Beyer, J. Blangero, M. Blesa Cábez, J. P. Boardman, M. Borzage, J. F. Bosch-Bayard, N. Bourke, V. D. Calhoun, M. M. Chakravarty, C. Chen, C. Chertavian, G. Chetelat, Y. S. Chong, J. H. Cole, A. Corvin, M. Costantino, E. Courchesne, F. Crivello, V. L. Cropley, J. Crosbie, N. Crossley, M. Delarue, R. Delorme, S. Desrivieres, G. A. Devenyi, M. A. Di Biase, R. Dolan, K. A. Donald, G. Donohoe, K. Dunlop, A. D. Edwards, J. T. Elison, C. T. Ellis, J. A. Elman, L. Eyler, D. A. Fair, E. Feczko, P. C. Fletcher, P. Fonagy, C. E. Franz, L. Galan-Garcia, A. Gholipour, J. Giedd, J. H. Gilmore, D. C. Glahn, I. M. Goodyer, P. E. Grant, N. A. Groenewold, F. M. Gunning, R. E. Gur, R. C. Gur, C. F. Hammill, O. Hansson, T. Hedden, A. Heinz, R. N. Henson, K. Heuer, J. Hoare, B. Holla, A. J. Holmes, R. Holt, H. Huang, K. Im, J. Ipser, C. R. Jack Jr, A. P. Jackowski, T. Jia, K. A. Johnson, P. B. Jones, D. T. Jones, R. S. Kahn, H. Karlsson, L. Karlsson, R. Kawashima, E. A. Kelley, S. Kern, K. W. Kim, M. G. Kitzbichler, W. S. Kremen, F. Lalonde, B. Landeau, S. Lee, J. Lerch, J. D. Lewis, J. Li, W. Liao, C. Liston, M. V. Lombardo, J. Lv, C. Lynch, T. T. Mallard, M. Marcelis, R. D. Markello, S. R. Mathias, B. Mazoyer, P. McGuire, M. J. Meaney, A. Mechelli, N. Medic, B. Misic, S. E. Morgan, D. Mothersill, J. Nigg, M. Q. W. Ong, C. Ortinau, R. Ossenkoppele, M. Ouyang, L. Palaniyappan, L. Paly, P. M. Pan, C. Pantelis, M. M. Park, T. Paus, Z. Pausova, D. Paz-Linares, A. Pichet Binette, K. Pierce, X. Qian, J. Qiu, A. Qiu, A. Raznahan, T. Rittman, A. Rodrigue, C. K. Rollins, R. Romero-Garcia, L. Ronan, M. D. Rosenberg, D. H. Rowitch, G. A. Salum, T. D. Satterthwaite, H. L. Schaare, R. J. Schachar, A. P. Schultz, G. Schumann, M. Schöll, D. Sharp, R. T. Shinohara, I. Skoog, C. D. Smyser, R. A. Sperling, D. J. Stein, A. Stolicyn, J. Suckling, G. Sullivan, Y. Taki, B. Thyreau, R. Toro, N. Traut, K. A. Tsvetanov, N. B. Turk-Browne, J. J. Tuulari, C. Tzourio, É. Vachon-Presseau, M. J. Valdes-Sosa, P. A. Valdes-Sosa, S. L. Valk, T. van Amelsvoort, S. N. Vandekar, L. Vasung, L. W. Victoria, S. Villeneuve, A. Villringer, P. E. Vértes, K. Wagstyl, Y. S. Wang, S. K. Warfield, V. Warrier, E. Westman, M. L. Westwater, H. C. Whalley, A. V. Witte, N. Yang, B. Yeo, H. Yun, A. Zalesky, H. J. Zar, A. Zettergren, J. H. Zhou, H. Ziauddeen, Z. Zugman, X. N. Zuo, Brain charts for the human lifespan. *Nature* **604**, 525–533 (2022).

43. Z. X. Zhou, L. Z. Chen, M. P. Milham, X. N. Zuo, Six cornerstones for translational brain charts. *Sci. Bull.* **68**, 795–799 (2023).

Acknowledgments:

Funding:

This work was supported by The STI 2030 - the major projects of the Brain Science and Brain-Inspired Intelligence Technology 2021ZD0200500 (X-N.Z.)

Start-up Funds for Leading Talents at Beijing Normal University (X-N.Z.)

National Natural Science Foundation of China 82102134, 82322035, 62273076 (X-N.Z.)

Key-Area Research and Development Program of Guangdong Province 2019B030335001(X-N.Z.)

Beijing Municipal Science and Technology Commission Z161100002616023, Z181100001518003 (X-N.Z.)

Major Project of National Social Science Foundation of China 20&ZD296 (X-N.Z.)

CAS-NWO Programme 153111KYSB20160020 (X-N.Z.)

National Basic Research (973) Program 2015CB351702 (X-N.Z.)

Chinese Academy of Sciences Key Research Program KSZD-EW-TZ-002 (X-N.Z.)

International Collaboration of National Natural Science Foundation of China 81220108014 (X-N.Z.)

China Postdoctoral Science Foundation 2023M740301 (Q.Z).

Author contributions:

Conceptualization: H-J.H., X-N.Z.

Methodology: B.D., Q.Z., P.G.

Investigation: Q.Z., B.D., P.G.

Resources: X-N.Z., H-J.H.

Data curation: Q.Z., P.G.

Visualization: B.D., P.G.

Supervision: H-J.H., X-N.Z.

Writing—original draft: B.D., Q.Z.

Writing—review and editing: All authors contributed to the critical review and editing of the manuscript.

Competing interests: The authors declare that they have no competing interests.

For the Chinese Color Nest Consortium (CCNC)：

Xi-Nian Zuo[1,2,3,4,7,18], Ning Yang[1,2,3,4], Zhe Zhang[5], Ye He[6], Hao-Ming Dong[1,4,8], Lei Zhang[9], Xing-Ting Zhu[2], Xiao-Hui Hou[7], YinShan Wang[1,3], Quan Zhou[1,2,3], Zhu-Qing Gong[1,2,3], Li-Zhi Cao[2,4], Ping Wang[1], Yi-Wen Zhang[2], Dan-Yang Sui[20], Ting Xu[21], GaoXia Wei[2,4], Zhi Yang[2,4], Lili Jiang[2,4], Hui-Jie Li[2,4], Ting-Yong Feng[11], Antao Chen[11], Jiang Qiu[11], Xu Chen[11], Xun Liu[2,4], Ke Zhao[2,4], Yi Du[2,4], Min Bao[2,4], Yuan Zhou[2,4], Yan Zhuo[14], Zhentao Zuo[14], Li Ke[1], Fei Wang[22], Zhi-Xiong Yan[7], Xue-Quan Su[7], F.Xavier Castellanos[23], Michael Peter Milham[21,24], Yu-Feng Zang[25]

[1]State Key Laboratory of Cognitive Neuroscience and Learning, Beijing Normal University, Beijing, 100875, China.

[2]Department of Psychology, University of Chinese Academy of Sciences, Beijing, 100049, China.

[3]Developmental Population Neuroscience Research Center, International Data Group/McGovern Institute for Brain Research, Beijing Normal University, Beijing, 100875, China.

[4]Key Laboratory of Behavioural Science, Institute of Psychology, Chinese Academy of Sciences, Beijing, 100101, China.

[5]College of Education, Hebei Normal University, Shijiazhuang, 050024, China.

[6]School of Artificial Intelligence, Beijing University of Posts and Telecommunications, Beijing, 100876, China.

[7]Laboratory of Cognitive Neuroscience and Education, School of Education Science, Nanning Normal University, Nanning, 530299, China.

[8]Changping Laboratory, Beijing, 102206, China.

[9]School of Government, Shanghai University of Political Science and Law, Shanghai, 201701, China.

[10]School of Psychology, Research Center for Exercise and Brain Science, Shanghai University of Sport, Shanghai, 200438, China.

[11]Faculty of Psychology, Southwest University, Chongqing, 400715, China.

[12]NYU-ECNU Institute of Brain and Cognitive Science at New York University Shanghai, Shanghai, 200062, China.

[13]Faculty of Arts and Science, New York University Shanghai, Shanghai, 200122, China.

[14]State Key Laboratory of Brain and Cognitive Science, Institute of Psychology, Chinese Academy of Sciences, Beijing, 100101, China.

[15]School of Psychology and Cognitive Science, East China Normal University, Shanghai, 200062, China.

[16]Department of Psychology, Renmin University of China, Beijing, 100872, China.

[17]Beijing Key Laboratory of Learning and Cognition, School of Psychology, Capital Normal University, Beijing, 100048, China.

[18]School of Education, Hunan University of Science and Technology, Hunan Xiangtan, 411201, China.

[19]National Basic Science Data Center, Beijing, 100190, China.

[20]Flight Research Department, Aviation University of Air Force, Jilin Changchun 130012, China.

[21]Center for the Developing Brain, Child Mind Institute, New York, NY, USA.

[22]Affiliated Nanjing Brain Hospital, Nanjing Medical University, Nanjing 210000, China.

[23]Department of Child and Adolescent Psychiatry, New York University Grossman School of Medicine, New York, NY 10016, USA.

[24]Nathan S. Kline institute for Psychiatric Research, Orangeburg, New York, NY 10962, USA.

[25]Institute of Psychological Sciences, Hangzhou Normal University, Hangzhou 311121, China.