# Sequence action representations contextualize during early skill learning.

Debadatta Dash[1], Fumiaki Iwane[1], William Hayward[1], Roberto Salamanca-Giron[1],

Marlene Bonstrup[2], Ethan R. Buch[1]*, and Leonardo G. Cohen[1]*

[1]Human Cortical Physiology and Neurorehabilitation Section, NINDS, NIH, USA

[2]Department of Neurology, University of Leipzig Medical Center, Leipzig, Germany

*To whom correspondence should be addressed

cohenl@ninds.nih.gov, ethan.buch@nih.gov

Declaration of interests. The authors declare no competing interests.

# Abstract

Activities of daily living rely on our ability to acquire new motor skills composed of precise action sequences. Here, we asked if the millisecond-level neural representation of an action performed at different contextual sequence locations within a skill differentiates or remains stable during early motor learning. We first optimized multi-scale machine learning decoders predictive of sequence-embedded finger movements from magnetoencephalographic (MEG) activity. Using this approach, we found that the neural representation of the same action performed in different contextual sequence locations, progressively differentiated—primarily during rest intervals of early learning (offline)—predicting skill gains. In contrast, representational differentiation during practice (online) failed to predict learning. The regions contributing to this representational differentiation evolved with learning, shifting from the contralateral pre- and post-central cortex during early learning (trials 1–11) to increased involvement of the superior and middle frontal cortex once skill performance plateaued (trials 12–36). Thus, the neural substrates supporting finger movements and their representational differentiation during early skill learning differ from those supporting stable performance during the subsequent skill plateau period. Representational contextualization extended to Day 2, exhibiting specificity for the practiced skill sequence. Altogether, our findings indicate that sequence action representations contextually differentiate during early skill learning, an issue relevant to brain-computer interface applications in neurorehabilitation.

## Introduction

Motor learning is required to perform a wide array of activities of daily living, intricate athletic endeavors, and professional skills. Whether it's learning to type more quickly on a keyboard [1], improve one's tennis game [2], or play a piece of music on the piano [3]– all these skills require the ability to execute sequences of actions with precise temporal coordination. Action sequences thus form the building blocks of fine motor skills [4]. Practicing a new motor skill elicits rapid performance improvements (early learning) [1] that precede skill performance plateaus [5]. Skill gains during early learning accumulate over rest periods (micro-offline) interspersed with practice [1, 6-10], and are up to four times larger than offline performance improvements reported following overnight sleep [1]. During this initial interval of prominent learning, retroactive interference immediately following each practice interval reduces learning rates relative to interference after passage of time, consistent with stabilization of the motor memory [11]. Micro-offline gains observed during early learning are reproducible [7, 10-13] and are similar in magnitude even when practice periods are reduced by half to 5 seconds in length, thereby confirming that they are not merely a result of recovery from performance fatigue [11]. Additionally, they are unaffected by the random termination of practice periods, which eliminates the possibility of predictive motor slowing as a contributing factor [11]. Collectively, these behavioral findings point towards the interpretation that micro-offline gains during early learning represent a form of memory consolidation [1].

This interpretation has been further supported by brain imaging and electrophysiological studies linking known memory-related networks and consolidation mechanisms to rapid offline performance improvements. In humans, the rate of hippocampo-neocortical neural replay predicts

micro-offline gains [6]. Consistent with these findings, Chen et al. [12] and Sjøgård et al. [13] furnished direct evidence from intracranial human EEG studies, demonstrating a connection between the density of hippocampal sharp-wave ripples (80-120 Hz)—recognized markers of neural replay [11]—and micro-offline gains during early learning. Further, Griffin et al. reported that neural replay of task-related ensembles in the motor cortex of macaques during brief rest periods— akin to those observed in humans [1, 6-8, 14]—are not merely correlated with, but are causal drivers of micro-offline learning [15]. Specifically, the same reach directions that were replayed the most during rest breaks showed the greatest reduction in path length (i.e. – more efficient movement path between two locations in the reach sequence) during subsequent trials, while stimulation applied during rest intervals preceding performance plateau reduced reactivation rates and virtually abolished micro-offline gains [15]. Thus, converging evidence in humans and non-human primates across indirect non-invasive and direct invasive recording techniques link hippocampal activity, neural replay dynamics and offline skill gains in early motor learning that precede performance plateau.

During skill learning, the neural representation of a sequential skill binds discrete individual actions (e.g. - single piano keypress) into complex, temporally and spatially precise sequence representations (e.g. - a refrain from a piece of music) [16-20]. After a skill is learned over extended periods (i.e., weeks), the neural representation of the sequence changes significantly [20], while the representation of its individual action components (e.g., finger movements) does not [21]. On the other hand, it is not known whether individual sequence action representations differentiate or remain stable during the early stages of skill learning, when the memory is still not fully formed [1]. Furthermore, it is unknown whether the neural representations of identical movements, performed at different positions within a skill sequence (i.e. - the skill *context*),

differentiate with learning—an important consideration for advancing robust brain-computer interface (BCI) applications [22-26].

Examining the millisecond-level differentiation of discrete action representations during learning is challenging, as evolving neural dynamics concurrently encode skill sequences and their individual action components [20, 27] across multiple spatial scales [28]. To address this problem, we first optimized a multi-scale decoder aimed at predicting keypress actions from magnetoencephalographic (MEG) neural activity. Using this optimized approach, we report that an individual sequence action representation differentiates depending on the sequence context in a way that predicts early skill learning. This representational contextualization developed predominantly over rest rather than during practice intervals—in parallel with rapid consolidation of skill.

# Results

Participants engaged in a well characterized sequential skill learning task. [1, 6, 11] that involved repetitive typing of a sequence (4-1-3-2-4) performed with their (non-dominant) left hand over 36 trials with alternating periods of 10s *practice* and 10s *rest* (*inter-practice rest*; *Day 1 Training*; **Figure 1A**), a practice schedule that minimizes reactive inhibition effects [11, 29] (see Methods). Individual keypress times and finger keypress identities were recorded and used to quantify skill as the correct sequence speed (keypresses/s) [1].

Figure 1. Experimental design and behavioral performance. *A. Skill learning task.* Participants engaged in a procedural motor skill learning task, which required them to repeatedly type a keypress sequence, "4 − 1 − 3 − 2 − 4" (1 = little finger, 2 = ring finger, 3 = middle finger, and 4 = index finger) with their non-dominant, left hand. The *Day 1 Training* session included 36 trials, with each trial consisting of alternating 10s practice and rest intervals. The rationale for this task design was to minimize reactive inhibition effects during the period of steep performance improvements (early learning) [11, 29] (see **Methods**). After a 24-hour break, participants were retested on performance of the same sequence (4-1-3-2-4) for 9 trials (*Day 2 Retest)* to inform on the generalizability of the

findings over time and MEG recording sessions, as well as single-trial performance on 9 different sequences (*Day 2*

*Control*; 2-1-3-4-2, 4-2-4-3-1, 3-4-2-3-1, 1-4-3-4-2, 3-2-4-3-1, 1-4-2-3-1, 3-2-4-2-1, 3-2-1-4-2, and 4-2-3-1-4) to

inform on specificity of the findings to the learned skill. MEG was recorded during both Day 1 and Day 2 sessions

with a 275-channel CTF magnetoencephalography (MEG) system (CTF Systems, Inc., Canada). **B. Skill Learning**.

As reported previously[1], participants on average reached 95% of peak performance by trial 11 of the *Day 1 Training*

session (see **Figure 1 - figure supplement 1A** for results over all *Day 1 Training* and *Day 2 Retest* trials). At the

group level, total early learning was exclusively accounted for by micro-offline gains during inter-practice rest

intervals (**Figure 1B, inset**). **C. Keypress transition time (KTT) variability.** Distribution of KTTs normalized to the

median correct sequence time for each participant and centered on the mid-point for each full sequence iteration during

early learning (see **Figure 1—figure supplement 1B** for results over all *Day 1 Training* and *Day 2 Retest* trials). Note

the initial variability of the relative KTT composition of the sequence (i.e. – 4-1, 1-3, 3-2, 2-4, 4-4), before it stabilizes

by trial 6 in the early learning period.

Participants reached 95% of maximal skill (i.e. - Early Learning) within the initial 11 practice trials

(**Figure 1B**), with improvements developing over inter-practice rest periods (micro-offline gains)

accounting for almost all total learning across participants (**Figure 1B, inset**)**[1]**. In addition to the

reduction in sequence duration during early learning, the duration of individual keypress

transitions became more consistent across repeated sequence iterations (**Figure 1C**). On average

across subjects, 2.32% ± 1.48% (mean ± SD) of all keypresses performed were errors, which were

evenly distributed across the four possible keypress responses. While errors increased

progressively over practice trials, they did so in proportion to the increase in correct keypresses,

so that the overall ratio of correct-to-incorrect keypresses remained stable over the training session.

On the following day, participants were retested on performance of the same sequence (4-1-3-2-

4) over 9 trials (*Day 2 Retest*), as well as on the single-trial performance of 9 different untrained

sequences (*Day 2 Controls*: 2-1-3-4-2, 4-2-4-3-1, 3-4-2-3-1, 1-4-3-4-2, 3-2-4-3-1, 1-4-2-3-1, 3-2-

4-2-1, 3-2-1-4-2, and 4-2-3-1-4). As expected, an upward shift in performance of the trained

sequence (0.68 ± SD 0.56 keypresses/s; t = 7.21, *p* < 0.001) was observed during *Day 2 Retest*,

indicative of an overnight skill consolidation effect (**Figure 1 - figure supplement 1A**).

**Keypress actions are represented in multi-scale hybrid-space manifolds.**

We investigated the differentiation of neural representations of the same index finger keypress

performed at different positions of the skill sequence. A set of decoders were constructed to predict

keypress actions from MEG activity as a function of both the learning state and the ordinal position

of the keypress within the sequence. We first characterized the spectral and spatial features of

keypress state representations by comparing performance of decoders constructed around

broadband (1-100Hz) or narrowband [delta- (1-3Hz), theta- (4-7Hz), alpha- (8-14 Hz), beta- (15-

24 Hz), gamma- (25-50Hz) and high gamma-band (51-100Hz)] MEG oscillatory activity. We

found that decoders trained on broadband data consistently outperformed those trained on

narrowband activity. Whole-brain parcel-space (70.11% ± SD 7.11% accuracy; n = 148 brain

regions; t = 1.89, *p* = 0.035, df = 25, Cohen's d = 0.17, **Figure 2A**; also see **Figure 2B** for

topographic map of feature importance scores) and voxel-space (74.51% ± SD 7.34% accuracy; n

= 15684; t = 7.18, *p* < 0.001, df = 25, Cohen's d = 0.76, **Figure 2A**; also see **Figure 2C** for

topographic map of feature importance scores)[30] decoders exhibited greater accuracy than all

regional voxel-space decoders constructed from individual brain areas (**Figure 2D**; maximum

accuracy of 68.77%± SD 7.6%; also see **Figure 2 – figure supplements 1 & 2**). Thus, optimal

decoding required information from multiple brain regions, predominantly contralateral to the

hand engaged in the skill task (**Figure 2B** and **C**).

**Figure 2. Spatial and oscillatory contributions to neural decoding of finger identities** *A) Contribution of whole-brain oscillatory frequencies to decoding.* When trained on broadband activity relative to narrow frequency band features, decoding accuracy (i.e. - test sample performance) was highest for whole-brain voxel-space (74.51% ± SD

7.34%, t = 8.08, $p < 0.001$) and parcel-space (70.11% ± SD 7.11%, t = 13.22, $p < 0.001$) MEG activity. Thus, decoders

trained on whole-brain broadband data consistently outperformed those trained on narrowband activity. Dots depict

decoding accuracy for each participant. *$p < 0.05$, **$p < 0.01$, ***$p < 0.001$, ns.: not significant.

**B) Whole-brain parcel-space decoding.** Color-coded standard (FreeSurfer *fsaverage*) brain surface plot displaying

the relative importance of individual brain regions (parcels) to broadband whole-brain parcel-space decoding

performance (far-left light gray box plot in *A*). **C) Whole-brain voxel space decoding.** Color-coded standard

(FreeSurfer *fsaverage*) brain surface plot displaying the relative importance of individual voxels to broadband whole-

brain voxel-space decoding performance (far-left dark gray box plot in *A*). **D) Regional voxel-space decoding.**

Broadband voxel-space decoding performance for top-ranked brain regions across the group is displayed on a standard

(FreeSurfer *fsaverage*) brain surface and color-coded by accuracy. Note that while whole-brain parcel- and voxel-

space decoders relied more on information from brain regions contralateral to the engaged hand, regional voxel-space

decoders performed similarly for bilateral sensorimotor regions.

Next, given that the brain simultaneously processes information more efficiently across multiple

spatial and temporal scales [28, 31, 32], we asked if the combination of lower resolution whole-

brain and higher resolution regional brain activity patterns further improve keypress prediction

accuracy. We constructed hybrid-space decoders (N = 1295 ± 20 features; **Figure 3A)** combining

whole-brain parcel-space activity (n = 148 features; **Figure 2B**) with regional voxel-space activity

from a data-driven subset of brain areas (n = 1147 ± 20 features; **Figure 2D**). This subset covers

brain regions showing the highest regional voxel-space decoding performances (top regions across

all subjects shown in **Figure 2D; Methods – *Hybrid Spatial Approach***). Accuracy was higher for

hybrid- (78.15% ± SD 7.03%; weighted mean F1 score of 0.78 ± SD 0.07) than for voxel- (74.51%

± SD 7.34%; paired *t*-test: t = 6.30, $p < 0.001$, df = 25, Cohen's d = 0.39) and parcel-space decoders

(70.11% ± SD 7.48%; paired *t*-test = 12.08, $p < 0.001$, df = 25, Cohen's d = 0.98, **Figure 3B,**

**Figure 3 – figure supplement 1,6**). Note that while features from contralateral brain regions were

more important for whole-brain decoding (in both parcel- and voxel-spaces), regional voxel-space

decoders performed best for bilateral sensorimotor areas on average across the group. Thus, a

multi-scale hybrid-space representation best characterizes the keypress action manifolds.

**Figure 3. Hybrid spatial approach for neural decoding during skill learning** *A. Pipeline*. Sensor-space MEG data ($N$ = 272 channels) were source-localized (voxel-space features; $N$ = 15684 voxels), and then parcellated (parcel-space features; $N$ = 148) by averaging the activity of all voxels located within an individual region defined in a standard template space (Desikan-Killiany Atlas). Individual regional voxel-space decoders were then constructed and ranked. The final hybrid-space keypress state (i.e. – 4-class) decoder was constructed using all whole-brain parcel-space features and top-ranked regional voxel-space features (see Methods). **B. Decoding performance across parcel, voxel, and hybrid spaces.** Note that decoding performance was highest for the hybrid space approach compared to performance obtained for whole-brain voxel- and parcel spaces. Addition of linear discriminant analysis (LDA)-based dimensionality reduction further improved decoding performance for both parcel- and hybrid-space approaches. Each dot represents accuracy for a single participant and method. "∗∗∗" indicates $p < 0.001$ and "∗" indicates $p < 0.05$. *C. Confusion matrix of individual finger identity decoding for hybrid-space manifold features.* True predictions are located on the main diagonal. Off-diagonal elements in each row depict false-negative predictions for each finger, while off-diagonal elements in each column indicate false-positive predictions. Please note that the index finger keypress had the highest false-negative misclassification rate (11.55%).

We implemented different dimensionality reduction or manifold extraction strategies including principal component analysis (PCA), multi-dimensional scaling (MDS), minimum redundant maximum relevance (MRMR), and linear discriminant analysis (LDA) [33] to map the input feature (parcel, voxel, or hybrid) space to a low-dimensional latent space [18]. LDA-based manifold extraction led to the greatest classifier performance gains, improving keypress decoding accuracy to 90.47% ± SD 3.44% (**Figure 3B**; weighted mean F1 score = 0.91 ± SD 0.05). In comparison to the hybrid-space decoder, whole-brain parcel-space decoder performance also improved following LDA-based dimensionality reduction (82.95% ± SD 5.48%), while whole-brain voxel-space decoder accuracy dropped substantially (40.38 % ± SD 6.78%; also see **Figure 3 – figure supplement 2**).

Notably, decoding of index finger keypresses (executed at two different ordinal positions in the

sequence) exhibited the highest false negative (0.115 per keypress) and false positive (0.067 per

prediction) misclassification rates compared with all other digits (false negative rate range = [0.067

0.114]; false positive rate range = [0.085 0.131]; **Figure 3C**), raising the hypothesis that the same

action could be differentially represented when executed within different contexts (i.e. – at

different locations within the skill sequence). Testing the keypress state (4-class) hybrid decoder

performance on Day 1 after randomly shuffling keypress labels for held-out test data resulted in a

performance drop approaching expected chance levels (22.12% ± SD 9.1%; **Figure 3 – figure**

**supplement 3C**). An alternate decoder trained on ICA components labeled as movement or

physiological artefacts (e.g. – head movement, ECG, eye movements and blinks; **Figure 3 – figure**

**supplement 3A,D**) and removed from the original input feature set during the pre-processing stage

approached chance-level performance (**Figure 4 – figure supplement 3**), indicating that the 4-

class hybrid decoder results were not driven by task-related artefacts.

Utilizing the highest performing decoders that included LDA-based manifold extraction, we

assessed the robustness of hybrid-space decoding over multiple sessions by applying it to data

collected on the following day during the *Day 2 Retest* (9-trial retest of the trained sequence) and

*Day 2 Control* (single-trial performance of 9 different untrained sequences) blocks. The decoding

accuracy for *Day 2* MEG data remained high (87.11% ± SD 8.54% for the trained sequence during

*Retest*, and 79.44% ± SD 5.54% for the untrained *Control* sequences; **Figure 3 – figure**

**supplement 4**). Thus, index finger classifiers constructed using the hybrid decoding approach

robustly generalized from Day 1 to Day 2 across trained and untrained keypress sequences.

**Inclusion of keypress sequence context location optimized decoding performance.**

Next, we tracked the trial-by-trial evolution of keypress action manifolds as training progressed. Within-subject keypress neural representations progressively differentiated during early learning. A representative example in **Figure 4A** (top row) depicts increased four-digit representation clustering across trials 1, 11, and 36. The cortical representation of these clusters changed over the course of training, beginning with predominant involvement of contralateral pre-central areas in trial 1 before transitioning to greater contralateral post-central, superior frontal, and middle frontal cortex contributions in trials 11 and 36 (**Figure 4A**, bottom row), paralleling improvements in decoding performance (see **Figure 4 – figure supplement 1** for trial-by-trial quantitative feature importance score changes during skill learning).

**Figure 4. Evolution of keypress neural representations with skill learning** *A. Keypress neural representations differentiate during early learning.* t-SNE distribution of neural representation of each keypress (top scatter plots) is shown for trial 1 (start of training; top-left), 11 (end of early learning; top-center), and 36 (end of training; top-right) for a single representative participant. Individual keypress manifold representation clustering in trial 11 (top-center; end of early learning) depicts sub-clustering for the index finger keypress performed at the two different ordinal

positions in the sequence (Index$_{OP1}$ and Index$_{OP5}$), which remains present by trial 36 (top-right). Spatial distribution

of regional contributions to decoding (bottom brain surface maps). The surface color heatmap indicates feature

importance scores across the brain. Note that decoding contributions shifted from contralateral right pre-central cortex

at trial 1 (bottom-left) to contralateral superior and middle frontal cortex at trials 11 (bottom-center) and 36 (bottom-

right). *B. Confusion matrix for 5-class decoding of individual sequence items.* Decoders were trained to classify

contextual representations of the keypresses (i.e., 5-class classification of the sequence elements 4-1-2-3-4). Note that

the decoding accuracy increased to 94.15% ± SD 4.84% and the misclassification of keypress 4 was significantly

reduced (from 141 to 82). *C. Trial-by-trial classification accuracy for 2-class decoder (Index$_{OP1}$ vs. Index$_{OP5}$).* A

decoder (200 ms window duration aligned to the KeyDown event) was trained to differentiate between the two index

finger keypresses embedded at different positions within the practiced skill sequence (Index$_{OP1}$ at ordinal position 1

vs. Index$_{OP5}$ at ordinal position 5). Decoder accuracy progressively improved over early learning, stabilizing around

96% by trial 11 (end of early learning). Similar results were observed for other decoding window sizes (50, 100, 150,

250 and 300 ms; see **Figure 4 – figure supplement 2**). Taken together, these findings indicate that the neural feature

space evolves over early learning to incorporate sequence location information.

The trained skill sequence required pressing the index finger twice (**4**-1-3-2-**4**) at two contextually

different ordinal positions (sequence positions 1 and 5). Inclusion of sequence location information

(i.e. – sequence context) for each keypress action (five sequence elements with the one keypress

represented twice at two different locations) improved decoding accuracy (t = 7.09, $p$ < 0.001, df

= 25, Cohen's d = 0.86, **Figure 4B)** from 90.47% (± SD 3.44%) to 94.15% (± SD 4.84%; weighted

mean F1 score: 0.94), and reduced overall misclassifications by 54.3% (from 219 to 119; **Figure**

**3C and 4B**). The improved decoding accuracy is supported by greater differentiation in neural

representations of the index finger keypresses performed at positions 1 and 5 of the sequence

(**Figure 4A**), and by the trial-by-trial increase in 2-class decoding accuracy over early learning

(**Figure 4C)** across different decoder window durations (**Figure 4 – figure supplement 2**). As

expected, the 5-class hybrid-space decoder performance approached chance levels when tested

with randomly shuffled keypress labels (18.41% ± SD 7.4% for Day 1 data; **Figure 4 – figure**

**supplement 3C**). Task-related eye movements did not explain these results since an alternate 5-

class hybrid decoder constructed from three eye movement features (gaze position at the KeyDown

event, gaze position 200ms later, and peak eye movement velocity within this window; **Figure 4**

**– figure supplement 3A**) performed at chance levels (cross-validated test accuracy = 0.2181;

**Figure 4 – figure supplement 3B, C**).

On Day 2, incorporating contextual information into the hybrid-space decoder enhanced

classification accuracy for the trained sequence only (improving from 87.11% for 4-class to

90.22% for 5-class), while performing at or below-chance levels for the Control sequences ($\leq$

30.22% $\pm$ SD 0.44%). Thus, the accuracy improvements resulting from inclusion of contextual

information in the decoding framework was specific for the trained skill sequence.

**Neural representation of keypress sequence location diverged during early skill learning.**

We used a Euclidian distance measure to evaluate the differentiation of the neural representation

manifold of the same action (i.e. - an index-finger keypress) executed within different local

sequence contexts (i.e. - ordinal position 1 vs. ordinal position 5; **Figure 5**). To make these distance

measures comparable across participants, a new set of classifiers was then trained with group-

optimal parameters (i.e. – broadband hybrid-space MEG data with subsequent manifold extraction

(**Figure 3 – figure supplements 2)** and LDA classifiers (**Figure 3 – figure supplements 7)** trained

on 200ms duration windows aligned to the KeyDown event (see Methods, **Figure 3 – figure**

**supplements 5**).

**Figure 5: Neural representation distance between index finger keypresses performed at two different ordinal**

**positions within a sequence. A.** *Contextualization increases over Early Learning during Day 1 Training*. Online

(green) and offline (purple) neural representation distances (*contextualization*) between two index finger key presses

performed at ordinal positions 1 and 5 of the trained sequence (4-1-3-2-4) are shown for each trial during Day 1

Training. Both online and offline contextualization between the two index finger representations increase sharply over

*Early Learning* before stabilizing across later *Day 1 Training* trials. **B.** *Contextualization develops predominantly*

*during rest periods (offline) on Day 1.* The cumulative neural representation differences during early learning were

significantly greater over rest (*Offline contextualization*; right) than during practice (*Online contextualization*; left)

periods (t = 4.84, *p* < 0.001, df = 25, Cohen's d= 1.2). **C.** *Contextualization acquired on Day 1 was retained on Day*

*2 specifically for the trained sequence.* The neural representation differences assessed across both rest and practice

for the trained sequence (4-1-3-2-4) were retained at *Day 2 Retest*. This is in stark contrast with the reduction in

contextualization for several untrained sequences controlling for: 1) index finger keypresses located at the same

ordinal positions 1 and 5 but within a different intervening sequence pattern (*Pattern Specificity Control*: 4-2-3-1-4,

51.05% lower contextualization); 2) use of a finger different than the index (little or ring finger) in both ordinal

positions 1 and 5 (*Finger Specificity Control*: 2-1-3-4-2, 1-4-2-3-1 and 2-3-1-4-2; 35.80% lower contextualization);

and 3) multiple index finger keypresses occurring at ordinal positions other than 1 and 5 (*Position Specificity Control*: 4-2-4-3-1 and 1-4-3-4-2; 22.06% lower contextualization). Note that offline contextualization cannot be measured for the *Day 2 Control* sequences as each sequence was only performed over a single trial.

The Euclidian distance between neural representations of $Index_{OP1}$ and $Index_{OP5}$ increased progressively during early learning (**Figure 5A**)—predominantly during rest intervals (*offline contextualization*) rather than during practice (*online*) (t = 4.84, p < 0.001, df = 25, Cohen's d = 1.2; **Figure 5B**; **Figure 5 – figure supplement 1A**). An alternative online contextualization approach equaling the time interval between online and offline comparisons (*Trial-based;* 10 seconds between $Index_{OP1}$ and $Index_{OP5}$ observations in both cases) rendered a similar result (**Figure 5 – figure supplement 2B**).

Offline contextualization strongly predicted cumulative micro-offline gains (r = 0.903, $R^2$ = 0.816, p < 0.001; **Figure 5 – figure supplement 1A, inset**) across decoder window durations ranging from 50 to 250ms (**Figure 5 – figure supplement 1B, C**). The offline contextualization between the final sequence of each trial and the second sequence of the subsequent trial (excluding the first sequence) yielded comparable results. This suggests that pre-planning at the start of each practice trial did not directly influence the offline contextualization measure [36, 42] (**Figure 5 – figure supplement 2A**, *$1^{st}$ vs. $2^{nd}$ Sequence approaches*). Conversely, online contextualization (using either measurement approach) did not explain early learning gains during practice (i.e. – **Figure 5 – figure supplement 3**). Within-subject correlations were consistent with these group-level findings. The average correlation between offline contextualization and micro-offline gains within individuals was significantly greater than zero (**Figure 5 – figure supplement 4, left**; t = 3.87, p = 0.00035, df = 25, Cohen's d = 0.76) and stronger than correlations between online contextualization and either micro-online (**Figure 5 – figure supplement 4, middle**; t = 3.28, p =

0.0015, df = 25, Cohen's d = 1.2) or micro-offline gains (**Figure 5 – figure supplement 4, right**; t = 3.7021, p = 5.3013e-04, df = 25, Cohen's d = 0.69). These findings were not explained by behavioral changes of typing rhythm (t = -0.03, *p* = 0.976; **Figure 5 – figure supplement 5**), adjacent keypress transition times ($R^2 = 0.00507$, F[1,3202] = 16.3; **Figure 5 – figure supplement 6**), or overall typing speed (between-subject; $R^2 = 0.028$, *p* = 0.41; **Figure 5 – figure supplement 7**).

Finally, contextualization of Index$_{OP1}$ vs. Index$_{OP5}$ representations observed on *Day 1* generalized to *Day 2 Retest* of the trained skill sequence. Distances between representations for the same keypress performed twice within untrained sequences were lower in magnitude (*Day 2 Control*)— pointing to specificity of the contextualization effect **(Figure 5C).**

# Discussion

The main findings of this study during which subjects engaged in a naturalistic, self-paced task were that individual sequence action representations differentiate during early skill learning in a manner reflecting the local sequence context in which they were performed, and that the degree of representational differentiation—particularly prominent over rest intervals—predicts skill gains.

**Optimizing decoding of sequential finger movements from MEG activity**

The initial phase of the study focused on optimizing the accuracy of decoding individual finger keypresses from MEG brain activity. Recent work showed that the brain simultaneously processes information more efficiently across multiple—rather than a single—spatial scale(s) [28, 31]. To this effect, we developed a novel hybrid-space approach designed to integrate neural representation dynamics over two different spatial scales: (1) *whole-brain parcel-space* (i.e. – spatial activity

patterns across all cortical brain regions) and (2) *regional voxel-space* (i.e. – spatial activity

patterns within select brain regions) activity. We found consistent spatial differences between

whole-brain parcel-space feature importance (predominantly contralateral frontoparietal, **Figure**

**2B**) and regional voxel-space decoder accuracy (bilateral sensorimotor regions, **Figure 2D**). The

*whole-brain parcel-space* decoder likely emphasized more stable activity patterns in contralateral

frontoparietal regions that differed between individual finger movements [21, 34], while the

*regional voxel-space* decoder incorporated information related to adaptive interhemispheric

interactions operating during motor sequence learning [31, 35, 36], particularly pertinent when the

skill is performed with the non-dominant hand [37-39]. The hybrid-space decoder which achieved

an accuracy exceeding 90%—and robustly generalized to Day 2 across trained and untrained

sequences—surpassed the performance of both parcel-space and voxel-space decoders and

compared favorably to other neuroimaging-based finger movement decoding strategies [6, 24, 40-

42].

Evaluation of individual brain oscillatory activity revealed that low-frequency oscillations (LFOs)

were the main contributors to broadband MEG decoding accuracy [18, 43]. Task-related

movements—which also express in lower frequency ranges—did not explain these results given

the near chance-level performance of alternative decoders trained on (a) artefact-related ICA

components removed during MEG pre-processing (**Figure 3 – figure supplement 3A-C)** and on

(b) task-related eye movement features **(Figure 4 – figure supplement 3B, C)**. This explanation

is also inconsistent with the minimal average head motion of 1.159 mm (± 1.077 SD) across the

MEG recording (**Figure 3 – figure supplement 3D**). How could LFOs contribute to keypress

decoding accuracy? LFOs, observed during movement onset in the cerebral cortex of animals [44,

45] and humans [46-48], encode information about movement trajectories and velocity [44, 45].

They also contain information related to movement timing [49-51], preparation [52, 53],

sensorimotor integration [47], kinematics [52, 53] and may contribute to the precise temporal

coordination of movements required for sequencing [54]. Within clinical contexts, LFOs in the

frontoparietal regions, the main contributors to decoding performance in the present study, have

been linked to recovery of motor function after brain lesions like stroke [46, 49, 55].

**Neural representations of individual sequence actions differentiate during early skill learning.**

Next, we exploited this hybrid decoding approach to investigate if individual sequence action

representations differentiate or remain stable during early skill learning, when the memory is not

yet fully formed [1]. The first hint of representational differentiation was the highest false-negative

and lowest false-positive misclassification rates for index finger keypresses performed at different

locations in the sequence compared with all other digits (**Figure 3C**). This was further supported

by the progressive differentiation of neural representations of the index finger keypress (**Figure**

**4A**) and by the robust trial-by-trial increase in 2-class decoding accuracy across time windows

ranging between 50 and 250ms (**Figure 4C; Figure 4 – figure supplement 2**). Further, the 5-class

classifier—which directly incorporated information about the sequence location context of each

keypress into the decoding pipeline—improved decoding accuracy relative to the 4-class classifier

(**Figure 4C**). Importantly, testing on Day 2 revealed specificity of this representational

differentiation for the trained skill but not for the same keypresses performed during various

unpracticed control sequences (**Figure 5C**).

The main region contributing information to representational differentiation during early practice

(trials 1-10) was the primary motor cortex, followed by the somatosensory cortex (trial 11), both

of which are known to be actively engaged in skill acquisition [6, 16, 56-59]. Concurrently,

information from the superior frontal and middle frontal cortex—which encode hierarchical

structures of skill sequences [20]—steadily increased in importance and emerged as the two most

crucial decoding contributors once skill performance plateau had been reached (trials 15 to 36;

**Figure 4 – figure supplement 1**) [27, 60]. Thus, the neural substrates supporting finger

movements and their representational differentiation during early skill learning (the time period

during which 95% skill gains in the training session occur [1, 29], trials 1-11 in this study) differed

from those supporting stable performance during the subsequent skill plateau period [16, 61] (trials

12-36 in this study).

**Differentiation of neural representations developed predominantly during rest periods**

**interspersed with practice.**

We then focused on the timeline of differentiation of index finger keypress neural

representations—which we refer to as contextualization—over early learning. We found that

contextualization increased progressively during early learning—predominantly during short rest

breaks (offline) rather than during practice (online; **Figure 5** and **Figure 5 – figure supplement**

**2B**). Offline contextualization consistently predicted early learning gains—a finding consistently

observed across a range of decoding windows (50–250ms; **Figure 5 – figure supplement 1**). This

result remained unchanged when measuring offline contextualization between the last and second

sequence of consecutive trials, ruling out pre-planning effects [36, 42] (**Figure 5 – figure**

**supplement 2A**). On the other hand, online contextualization did not predict learning (**Figure 5 –**

**figure supplement 3**). Consistent with these results the average within-subject correlation

between offline contextualization and micro-offline gains was significantly stronger than within-

subject correlations between online contextualization and either micro-online or micro-offline

gains (**Figure 5 – figure supplement 4**).

Offline contextualization was not driven by trial-by-trial behavioral differences, including typing

rhythm (**Figure 5 – figure supplement 5**) and adjacent keypress transition times (**Figure 5 –**

**figure supplement 6**) nor by between-subject differences in overall typing speed (**Figure 5 –**

**figure supplement 7**)—ruling out a reliance on differences in the temporal overlap of keypresses.

Importantly, offline contextualization documented on Day 1 stabilized once a performance plateau

was reached (trials 11-36), and was retained on Day 2, documenting overnight consolidation of

the differentiated neural representation. A possible neural mechanism supporting contextualization

could be the emergence and stabilization of conjunctive "what–where" representations of

procedural memories [62] with the corresponding modulation of neuronal population dynamics

[63, 64] during early learning. Exploring the link between contextualization and neural replay

could provide additional insights into this issue [6, 12, 13, 15].

In this study, classifiers were trained on MEG activity recorded during or immediately after each

keypress, emphasizing neural representations related to action execution, memory consolidation

and recall over those related to planning. An important direction for future research is determining

whether separate decoders can be developed to distinguish the representations or networks

separately supporting these processes. Ongoing work in our lab is addressing this question. The

present accuracy results across varied decoding window durations and alignment with each

keypress action support the feasibility of this approach (**Figure 3—figure supplement 5**).

**Limitations**

One limitation of this study is that contextualization was investigated for only one finger

movement (index finger or digit 4) embedded within a relatively short 5-item skill sequence.

Determining if representational contextualization is exhibited across multiple finger movements

embedded within for example longer sequences (e.g. – two index finger and two little finger

keypresses performed within a short piece of piano music) will be an important extension to the

present results. While a supervised manifold learning approach (LDA) was used here because it

optimized hybrid-space decoder performance, unsupervised strategies (e.g. - PCA and MDS,

which also substantially improved decoding accuracy in the present study; **Figure 3 – figure**

**supplement 2**) are likely more suitable for real-time BCI applications. Finally, caution should be

exercised when extrapolating findings during early skill learning, a period of steep performance

improvements, to findings reported after insufficient practice [65], post-plateau performance

periods [66], or non-learning situations (e.g. performance of non-repeating keypress sequences in

[65]) when reactive inhibition or contextual interference effects are prominent. Ultimately, it will

be important to develop new paradigms allowing one to independently estimate the different

coincident or antagonistic features (e.g. - memory consolidation, planning, working memory and

reactive inhibition) contributing to micro-online and micro-offline gains during and after early

skill learning within a unifying framework.

**Summary**

In summary, individual sequence action representations contextualize during early learning of a

new skill and the degree of differentiation parallels skill gains. Importantly, the neural

representation changes across rest periods developed to a larger extent than during practice

intervals of early learning in parallel with rapid consolidation of skill. It is possible that the

systematic inclusion of contextualized information into sequence skill practice environments could

improve learning in areas as diverse as music education, sports training, and rehabilitation of motor

skills after brain lesions.

## **Materials and Methods**

**Study Participants**

The study was approved by the Combined Neuroscience Institutional Review Board of the

National Institutes of Health (NIH). A total of thirty-three young and healthy adults (comprising

16 females) with a mean age of 26.6 years (± 0.87 SEM) participated in the study after providing

written informed consent and undergoing a standard neurological examination. No participants

were actively engaged in playing musical instruments in their daily lives, as per guidelines outlined

in prior research [67, 68]. All study scientific data were de-identified and permanently unlinked

from all personal identifiable information (PII) before the analysis. These data are publicly

available upon request (https://nih.box.com/v/hcpsSkillLearningData). Two participants were

excluded from the analysis due to MEG system malfunction during data acquisition. An additional

5 subjects were excluded because they failed to generate any correct sequences in two or more

consecutive trials. The study was powered to determine the minimum sample size needed to detect

a significant change in skill performance following training using a one-sample t-test (two-sided;

alpha = 0.05; 95% statistical power; Cohen's d effect size = 0.8115 calculated from previously

acquired data in our lab [69]). The calculated minimum sample size was 22. The included study

sample size (n = 27) exceeded this minimum [1].

**Experimental Setup**

Participants practiced a procedural motor skill learning task that involved repetitively typing a 5-

item numerical sequence (4-1-3-2-4) displayed on a computer screen. They were instructed to

perform the task as quickly and accurately as possible using their non-dominant, left hand on a

response pad (Cedrus LS-LINE, Cedrus Corp). Each numbered sequence item corresponded to a

specific finger keypress: 1 for a little finger keypress, 2 for a ring finger keypress, 3 for a middle

finger keypress, and 4 for an index finger keypress. Individual keypress times and identities were

recorded and used to assess skill learning and performance.

Participants practiced the skill for 36 trials. Each trial spanned a total of 20 seconds and included

a 10 second practice round followed by a 10 second inter-practice rest period. The task design used

to evaluate early learning followed specific recommendations by Pam and Rickard, 2015 1)

utilizing 10s practice trials and 2) constraining our analysis of micro-offline gains to early learning

trials (where performance monotonically increases and 95% of overall performance gains occur),

which are prior to the emergence of the "scalloped" performance dynamics strongly linked to

reactive inhibition effects (see [29] and others [70, 71]). This is precisely the portion of the learning

curve Pam and Rickard referred to when they stated "…*rapid learning during that period masks*

*any reactive inhibition effect"* [29].

The five-item sequence was displayed on the computer screen for the duration of each practice

round and participants were directed to fix their gaze on the sequence. Small asterisks were

displayed above a sequence item after each successive keypress, signaling the participants' present

position within the sequence. Inclusion of this feedback minimizes working memory loads during

task performance [72]. Following the completion of a full sequence iteration, the asterisks were

removed. The asterisk display did not provide error feedback as it appeared for both correct and

incorrect keypresses. At the end of each practice round, the displayed number sequence was

replaced by a string of five "X" symbols displayed on the computer screen, which remained for

the duration of the inter-practice rest period. Participants were instructed to focus their gaze on the

screen during this time. The behavior in this explicit sequence learning motor tasks is highly

generative in nature rather than reactive to stimulus cues as in the serial reaction time task (SRTT).

A similar real-world example would be manually inputting a long password into a secure online

application in which one intrinsically generates the sequence from memory and receives similar

feedback about the password sequence position (also provided as asterisks), which is typically

ignored by the user. The response pad was positioned in a manner that minimized wrist, arm or

more proximal body movements during the task. The head was restrained with an inflatable air

bladder, and head position was assessed at the beginning and at the end of each recording. The

mean measured head movement across the study group was 1.159 mm ($\pm$ 1.077 SD; **Figure 3 –**

**figure supplement 3**).

On the next day, participants were tested (*Day 2 Retest*) with the same trained sequence (4-1-3-2-

4) for 9 trials as well as for 9 different unpracticed control sequences (*Day 2 Control*; 2-1-3-4-2;

4-2-4-3-1; 3-4-2-3-1; 1-4-3-4-2; 3-2-4-3-1; 1-4-2-3-1; 3-2-4-2-1; 2-3-1-4-2; 4-2-3-1-4) each for

one trial. The practice schedule structure for Day 2 was same as Day 1, with 10s practice trials

interleaved with 10s of rest.

**Behavioral data analysis**

*Skill*

Skill, in the context of the present task, is quantified as the *correct sequence typing speed*, (i.e., -

the number of correctly typed sequence keypresses per second; kp/s). That is, improvements in the

speed/accuracy trade-off equate to greater skill. Keypress transition times (KTT) were calculated

as the difference in time between the *keyDown* events recorded for consecutive keypresses. Since

the sequence was repeatedly typed within a single trial, individual keypresses were marked as

correct if they were members of a 5 consecutive keypress set that matched any possible circular

shift of the displayed 5-item sequence. The instantaneous correct sequence speed was calculated

as the inverse of the average KTT across a single correct sequence iteration and was updated for

each correct keypress. Trial-by-trial skill changes were assessed by computing the median correct

sequence typing speed for each trial.

***Early Learning***

The *early learning* period was defined as the trial range (1 - T trials) over which 95% of the total

skill performance was first attained at the group level. We quantified this by fitting the group

average trial-by-trial correct sequence speed data with an exponential model of the form:

$$L(t) = C1 + C2\,(1 - e^{-kt})$$

Here, the trial number is denoted by *t*, and *L(t)* signifies the group-averaged performance at trial *t*.

Parameters *C1* and *C2* correspond to the pre-training performance baseline and asymptote,

respectively, while *k* denotes the learning rate. The values for *C1*, *C2*, and *k* were computed using

a constrained nonlinear least-squares method (MATLAB's lsqcurvefit function, trust-region-

reflective algorithm) and were determined to be 0.5, 0.15, and 0.2, respectively. The early learning

trial cut-off, denoted as *T*, was identified as the first trial where 95% of the learning had been

achieved. In this study, *T* was determined to be trial 11.

Performance improvements over rest (*micro-offline gains),* for each rest period of a trial, were

calculated as the net change in performance (instantaneous correct sequence typing speed) from

the end of one practice period to the onset of the next (i.e. – over a single inter-practice rest period).

*Micro-online gains* (performance improvements during practice periods) were computed as the

change in performance between the beginning and end of a single practice trial. Total early learning

was derived as the sum of all *micro-online* and *micro-offline* gains over trials 1-11. Cumulative

micro-offline gains, micro-online gains, and total early learning were statistically compared using

1-way ANOVAs and post-hoc Tukey tests.

## MRI Acquisition

545    We acquired T1-weighted high-resolution anatomical MRI volumes images (1 mm$^3$ isotropic

546    MPRAGE sequence) for each participant on a 3T MRI scanner (GE Excite HDxt or Siemens

547    Skyra) equipped with a 32-channel head coil. These data allowed for spatial co-registration of an

548    individual participant's brain with the MEG sensors, and individual head models required for

549    surface-based cortical dipole estimation from MEG signals (i.e. – MEG source-space modeling).

## MEG Acquisition

We recorded continuous magnetoencephalography (MEG) at a sampling frequency of 600 Hz

using a CTF 275 MEG system (CTF Systems, Inc., Canada) while participants were seated in an

upright position. The MEG system comprises a whole-head array featuring 275 radial 1$^{st}$-order

gradiometer/SQUID channels housed in a magnetically shielded room (Vacuumschmelze,

Germany). Three of the gradiometers (two non-functional and one with high channel noise after

visual inspection) were excluded from the analysis resulting in a total of 272 MEG channels for

analysis. Synthetic 3$^{rd}$ order gradient balancing was applied to eliminate background noise in real-

time data collection. Temporal alignment of behavioral and MEG data was achieved using a TTL

trigger. Head position in the scanner coordinate space was monitored using head localization coils

at the nasion, left, and right pre-auricular locations. These fiducial positions were co-registered in

the participants' T1-MRI coordinate space using a stereotactic neuronavigation system

(BrainSight, Rogue Research Inc.). MEG data was acquired starting 6 min before the task (resting-

state baseline) and continued through the end of the 12 min training session.

**MEG Data Analysis**

*Preprocessing*

MEG data were preprocessed using the FieldTrip [73] and EEGLAB [74] toolboxes on MATLAB 2022a. Continuous raw MEG data (acquired at 600 Hz) were band-pass filtered between 1-100 Hz with a 4th order noncausal Butterworth filter. 60 Hz line noise was removed with a narrow-band discrete Fourier transform (DFT) notch filter. Independent component analysis (ICA) was used to remove typical MEG signal artifacts related to eye blinks or movement or cardiac pulsation. All recordings were visually inspected and marked to denoise segments containing other large amplitude artifacts due to movements. Eye movements were simultaneously recorded during MEG (EyeLink 1000 Plus; Fs = 600 Hz).

*Source Reconstruction and Parcellation*

For each participant, individual volume conduction models were established to depict the propagation of brain-generated currents through tissue to externally measurable magnetic fields. This was accomplished through a single-shell head corrected-sphere approach based on the brain volume segmentation of their high-resolution T1 MRI. Source models and surface labels from the Desikan-Killiany Atlas [30] were created for each participant using inner-skull and pial layer surfaces obtained through FreeSurfer segmentation and connectome-workbench. Aligning sensor positions in the MEG helmet to individual head space involved warping MEG head coil positions (mean of pre and post recording) to the fiducials of the MRI, applying the same transformation matrix to all MEG sensors.

The individual source, volume conduction model, and sensor positions were then utilized to generate the forward solution at each source dipole location, describing the propagation of source activity from each cortical location on the grid to each MEG sensor. The Linearly Constrained

Minimum-Variance (LCMV) beamformer was employed for computing the inverse solution. Each

trial of MEG activity contributed to calculating the inverse solution data covariance matrix. The

individual sample noise covariance matrix was derived from 6 minutes of pre-training rest MEG

data recorded in the same subject during the same session. A total of 15,684 surface-based cortical

dipoles (source-space voxels) were estimated.

Source-space parcellation was carried out by averaging all voxel time-series located within distinct

anatomical regions defined in the Desikan-Killiany Atlas [30]. Since source time-series estimated

with beamforming approaches are inherently sign-ambiguous, a custom Matlab-based

implementation of the *mne.extract_label_time_course* with "*mean_flip*" sign-flipping procedure

in MNE-Python [75] was applied prior to averaging to prevent within-parcel signal cancellation.

All voxel time-series within each parcel were extracted and the time-series sign was flipped at

locations where the orientation difference was greater than 90° from the parcel mode. A mean

time-series was then computed across all voxels within the parcel after sign-flipping.

**Feature Selection for Decoding**

Features were extracted from the MEG activity at several spatial, oscillatory, and temporal scales.

*Oscillatory Analysis*

MEG signals were band limited to broadband (1-100 Hz) and standard neural oscillatory frequency

bands defined as delta (1-3 Hz), theta (4-7 Hz), alpha (8-14 Hz), beta (15-24 Hz), gamma (25-50

Hz), and high-gamma (51-100 Hz) with a 4th order non-causal Butterworth filter. The decoding

analysis was conducted independently for each band of MEG activity.

 *Spatial Analysis.*

Decoding was performed at sensor space as well as at source space. For sensor space decoding the

feature dimension was 272 (corresponding to the 272 gradiometer channels). At the source space,

decoding was executed at both the high-resolution voxel and low-resolution parcel space. The

feature dimension for voxel-space decoding was 15,684, representing the total number of

independently estimated cortical dipoles. For parcel-space decoding, the feature dimension was

148, derived from spatially averaging the voxel activities within each parcel defined by the

Desikan-Killiany Atlas. In both cases, decoding was carried out across all oscillatory frequency

bands (i.e. - broadband, delta, theta, alpha, beta, gamma, and high-gamma) for comprehensive

comparison.

*Temporal Analysis.*

Temporal MEG activity corresponding to each keypress was defined by taking a time window of

[ t + Δt], where t ∈ [0 : 10 ms : 100 ms] and Δt ∈ [25 ms : 25 ms : 350 ms]. In other words, a

sliding window of variable width (from 25 ms to 350 ms with 25 ms increments) with onset ranging

from the *keyDown* event (i.e. – t = 0ms) to +100ms after the *keyDown* event (with increments of

10 ms) was used. This approach generated 140 different temporal windows for each keypress for

each participant. MEG activity was averaged over each of these time widows and independently

analyzed for decoding. The optimal time window was selected for each subject that resulted in

best cross-validation performance (**Figure 3 – figure supplement 5**). This window optimization

analysis was performed for each frequency band and spatial scale.

*Hybrid Spatial Approach.*

First, we evaluated the decoding performance of each brain region in decoding finger identity. We

trained decoders on the regional voxel-space activity patterns within each functional brain area to

predict finger identity. Brain regions were then ranked from 1 to 148 based on their decoding

accuracy at the group level. In a stepwise manner, we incrementally incorporated voxel activities

of brain regions, starting from the top-ranked region. In other words, first, we concatenated the

voxel-level features of the highest-ranked region with whole-brain parcel-level features for

decoding analysis. Subsequently, we added the voxel-level features of the second-ranked brain

region, along with those of the top-ranked region to the parcel-level features for decoding and

continued this process. This iterative addition of brain regions was performed until decoding

accuracy reached saturation. The optimal feature space comprised all 148 parcel-space features in

conjunction with voxel-space features from the top 8 brain regions.

*Dimension Reduction*

We used several supervised and unsupervised dimension reduction techniques including linear

discriminant analysis (LDA), minimum redundant maximum relevance (MRMR), principal

component analysis (PCA), Autoencoder, Diffusion maps, factor analysis, large margin nearest

neighbor (LMNN), multi-dimensional scaling (MDS), neighbor component analysis (NCA),

spatial predictor envelope (SPE)[33] on each of the spatial feature space (sensor, parcel, voxel,

and hybrid). Among these techniques, PCA, MDS, MRMR, and LDA emerged as particularly

effective in significantly improving decoding performance.

PCA, a method for unsupervised dimensionality reduction, transformed the high-dimensional

dataset into a new coordinate system of uncorrelated principal components. These components,

capturing the maximum variance in the data, were iteratively added to reconstruct the feature space

and execution of decoding. MDS finds a configuration of points in a lower-dimensional space such

that the distances between these points reflect the dissimilarities or similarities between the

corresponding objects in the original high-dimensional space. MRMR, an approach combining

relevance and redundancy metrics, ranked features based on their significance to the target variable

and their non-redundancy with other features. The decoding process involved starting with the

highest-ranked feature and iteratively incorporating subsequent features until decoding accuracy

reached saturation. LDA finds the linear combinations of features (dimensions) that best separate

different classes in a dataset. It projects the original features onto a lower-dimensional space

(number of classes -1) while preserving the class-discriminatory information. This transformation

maximizes the ratio of the between-class variance to the within-class variance. In our study, LDA

transformed the features to a 3-dimensional hyperdimensional space that were used for decoding.

Dimension reduction was applied to train data and then with the tuned parameters of the dimension

reduction model test data was transformed for decoder metrics evaluation. Decoding accuracies

were systematically compared between the original and reduced dimension feature spaces,

providing insights into the effectiveness of each dimension reduction technique. By rigorously

assessing the impact of dimension reduction on decoding accuracy, the study aimed to identify

techniques that not only reduced the computational burden associated with high-dimensional data

but also enhanced the discriminative power of the selected features. This comprehensive approach

aimed at optimizing the neural representation of each finger keypress for decoding performance

across various spatial contexts.

**Decoding Analysis**

Decoding analysis was conducted for each participant individually, employing a randomized split

of the data into training (90%) and test (10%) samples for 8 iterations. For each iteration, to

optimize decoder configuration, an 8-fold cross-validation was applied to the training samples,

allowing for the fine-tuning of hyperparameters and selection of the most effective model. Across

participants, on average, the total number of individual keypresses for the whole duration of

training was 219 ± SD: 66 (keypress 1: little), 205 ± SD: 66 (keypress 2: ring), 209 ± 66 (keypress

3: middle), and 426 ± SD: 131 (keypress 4: index). Only keypresses belonging to correctly typed

sequence iterations (94.64% ± 4.04% of all keypresses) were considered. The total number of

keypresses for keypress 4 was approximately twice that of keypresses 1, 2, and 3, as it was the

only action that occurred more than once in the trained sequence (4-1-3-2-4), albeit in two different

sequence contexts or ordinal positions. Considering the higher (2x) number of samples for one-

class, we independently oversampled the keypresses 1, 2 and 3 to avoid overfitting to the over-

represented class. Importantly, oversampling was applied independently for each keypress class,

ensuring that validation folds were never oversampled, and training folds did not share common

oversampled patterns. The decoder configuration demonstrating the best validation performance

was selected for each iteration, and subsequently, test accuracy was evaluated on the

independent/unseen test samples. This process was repeated for the 8 different iterations of train-

test splitting and the average test accuracy was reported. This rigorous methodology aimed at

generalizing decoding performance to ensure robust and reliable results across participants.

Further, decoding evaluation was performed on the Day 2 data, for both the trained (*Day 2 Retest;*

9 trials) and untrained sequences (*Day 2 Control*; 9 different single-trial tests).

***Machine Learning Classifiers***

We employed a diverse set of machine learning decoders, including Naïve Bayes (NB), decision

trees (DT), ensembles (EN), k-nearest neighbor (KNN), linear discriminant analysis (LDA),

support vector machines (SVM), and artificial neural network (ANN), to train features generated

with all possible combinations of spatial, temporal, and oscillatory scales for comprehensive

comparative analysis. The hyperparameters of these decoders underwent fine-tuning using

Bayesian optimization search.

The Naive Bayes classifier was configured with a normal distribution predictor and Gaussian

Kernel, while the KNN classifier had a K value of 4 (for keypress decoding) and utilized the

Euclidean distance metric. For decision trees, the maximum number of splits was set to 4 (for

keypress decoding), with leaves being merged based on the sum of risk values greater or equal to

the risk associated with the parent node. The optimal sequence of pruned trees was estimated, and

the predictor selection method was 'Standard CART,' selecting the split predictor that maximizes

the split-criterion gain over all possible splits of all predictors. The split criterion used was 'gdi'

(Gini's diversity index). Ensembles employed the bagging method with random predictor

selections at each split, forming a random forest. The maximum number of learning cycles was set

to 100 with a weak learner based on discriminant analysis. For SVM, the RBF kernel was selected

through cross-validation (CV), and the 'C' parameter and kernel scale were optimized using

Bayesian optimization search. In the case of LDA, the linear coefficient threshold and the amount

of regularization were computed based on Bayesian optimization search. The ANN decoder

consisted of one hidden layer with 128 nodes, followed by a sigmoid and a softmax layer, each

with 4 nodes (for keypress decoding). Training utilized a scaled conjugate gradient optimizer with

backpropagation, employing a learning rate of 0.01 (coarse to fine tuning) for a maximum of 100

epochs, with early stopping validation patience set to 6 epochs.

Additionally, we assessed long short-term memory recurrent neural networks (LSTM-RNN) and

bidirectional LSTM-RNN to train the time series of each keypress for decoding. The configuration

of these RNNs included two hidden (Bi)LSTM layers of 100 units, followed by three fully

connected layers (50, 10, and 4), and a softmax layer with 4 nodes to decode the four keypress

classes. The networks were trained using an Adam optimizer with an initial learning rate of 0.001,

a learning rate drop factor of 0.1 after 20 epochs, and a maximum epoch of 400. For regularization,

20% dropouts after the (Bi)LSTM layers, 50% dropout after the fully connected layers, and L2

Norm with a gradient threshold value of 0.1 were employed. These hyperparameter values were

chosen based on grid search optimization during cross-validation. The optimal classifier algorithm

was selected for each subject that resulted in best cross-validation performance (**Figure 3 – figure**

**supplement 7**).

*Decoding Performance Metrics*

Decoding performance was assessed using several metrics, including accuracy (%), which

indicates the proportion of correct classifications among all test samples. The confusion matrix

provided a detailed comparison of the number of correctly predicted samples for each class against

the ground truth. The F1 score, defined as the harmonic mean of the precision (percentage of true

predictions that are actually true positive) and recall (percentage of true positives that were

correctly predicted as true) scores, was used as a comprehensive metric for all one-versus-all

keypress state decoders to assess class-wise performance that accounts for both false-positive and

false-negative prediction tendencies [76, 77] . A weighted mean F1 score was then computed

across all classes to assess the overall prediction performance of the multi-class model. Test

accuracies based on the best decoder performance (LDA in our case) were reported and used for

statistical comparisons.

*Decoding During Skill Learning Progression*

We systematically assessed decoding performance of the 2-class decoder (Index$_{OP1}$ vs Index$_{OP5}$)

at each trial during the skill learning process to identify the relationship between the evolution of

differentiated index finger decoding proficiency and the acquired skill. Our approach involved

evaluating decoder performance individually for each *Day 1 Training* trial. To mitigate the

influence of varying sample sizes in later trials, we ensured an equal number of samples (first $k$

keypresses) in each trial.

We used t-distributed stochastic neighborhood estimation (t-SNE) to visualize the evolution of

neural representations corresponding to each keypress at each trial of the learning period. Within

t-SNE distributions, index finger keypresses were separately labeled based upon their sequence

location (i.e., $Index_{OP1}$ and $Index_{OP5}$ for ordinal positions 1 and 5, respectively).

***Decoding Sequence Elements***

Finally, we performed decoding of each contextual action of the sequence (i.e., $Index_{OP1}$, Little,

Middle, Ring, and $Index_{OP5}$). We used the same decoding strategy (90%-10% split for train and

test, 8-fold cross validation of training samples to select best decoder configuration, hybrid spatial

features, and LDA based dimension reduction) to decode these 5-classes. Note, oversampling was

not needed after sub-grouping the index finger keypresses into two separate classes based on their

context. Decoding sequence elements were evaluated for both *Day 1 Training*, *Day 2 Retest* and

*Day 2 Control* data.

***Feature Importance Scores***

The relative contribution of source-space voxels and parcels to decoding performance (i.e. –

feature importance score) was calculated using minimum redundant maximum relevance

(MRMR)[95] and highlighted in topography plots. MRMR, an approach that combines both

relevance and redundancy metrics, ranked individual features based upon their significance to the

target variable (i.e. – keypress state identity) prediction accuracy and their non-redundancy with

other features.

**Neural Representation analysis**

We evaluated the *online* (within-trial) and *offline* (between-trial) changes in the neural representation of the contextual actions ($Index_{OP1}$ and $Index_{OP5}$) for each trial during training. For offline differentiation, we evaluated the Euclidian distance between the hybrid spatial features of the last index finger keypress of a trial ($Index_{OP5}$) to the first index finger keypress ($Index_{OP1}$) of the subsequent trial, mirroring the approach used to calculate micro-offline gains in skill. This offline distance provided insights on the net change in contextual representation of the index finger keypress during each interspersed rest interval. For online differentiation, we calculated the mean Euclidian distance between $Index_{OP1}$ and $Index_{OP5}$ of all the correctly typed sequences within a practice trial. Online differentiation informed on the net change in the contextual representation of the index finger keypress within each practice trial. Cumulative offline and online representation distances across participants were compared using 2-sample *t*-tests. Additionally, we computed trial-by-trial differences in offline and online representations during early learning, exploring their relationships with cumulative micro-offline and micro-online gains in skill, respectively, through regression analysis and Pearson correlation analysis. Linear regression models were trained utilizing the *fitlm* function in MATLAB. The model employed M-estimation, formulating estimating equations and solving them through the Iteratively Reweighted Least Squares (IRLS) method[96]. Key metrics such as the square root of the mean squared error (RMSE), which estimates the standard deviation of the prediction error distribution, the coefficient of explained variance ($R^2$), the F-statistic as a test statistic for the F-test on the regression model, examining whether the model significantly outperforms a degenerate model consisting only of a constant term, and the *p*-value for the F-test on the model were computed and compared across different models. This

multifaceted approach aimed to uncover the nuanced dynamics of neural representation changes

in response to skill acquisition.

As a control analysis, we also computed the difference in neural representation between $Index_{OP1}$

and $Index_{OP5}$ on *Day 2 Retest* data for the same sequence (**4**-1-3-2-**4**) as well as for different *Day*

*2 Control* untrained sequences where the same action was performed at ordinal positions 1 and 5

(**2**-1-3-4-**2**; **1**-4-2-3-**1**; **2**-3-1-4-**2**; **4**-2-3-1-**4**). Finally, we assessed for specificity of

contextualization to the trained sequence, by evaluating differentiation between index finger

keypress representations performed at two different positions within untrained sequences (**4**-2-**4**-

3-1 and 1-**4**-3-**4**-2). The cumulative differences across participants were compared with 2-sample

*t*-tests.

## Data Availability

799  All de-identified and permanently unlinked from all personal identifiable information (PII) data

800  are publicly available. ([Box Repository](#)).

## Acknowledgments.

802  We thank Ms. Tasneem Malik, Ms. Michele Richman, and NIMH MEG Core Facility staff for

803  their support. This work utilized the computational resources of the NIH HPC Biowulf cluster

804  ([http://hpc.nih.gov](http://hpc.nih.gov)). This research was supported by the Intramural Research Program of the

805  NINDS, NIH.

## Supplementary Materials

**Figure 1 – figure supplement 1: Behavioral performance during skill learning. A) Total Skill Learning over Day 1 Training (36 trials) and Day 2 Retest (9 trials)**. As reported previously [1], participants on average reached 95% of peak performance during *Day 1 Training* by trial 11. Note that after trial 11 performance stabilizes around a plateau through trial 36. Following a 24-hour break, participants displayed an upward shift in performance during the *Day 2 Retest* – indicative of an overnight skill consolidation effect. **B) Keypress transition time (KTT) variability.** Distribution of KTTs normalized to the median correct sequence time for each participant and centered on the mid-point for each full sequence iteration during early learning. Note that the initial variability of the five component transitions in the sequence (i.e. – 4-1, 1-3, 3-2, 2-4, 4-4) stabilize by trial 6 in the early learning period and remain stable throughout the rest of *Day 1 Training* (through trial 36) and *Day 2 Retest*.

**Figure 2 – figure supplement 1: Oscillatory contributions at individual brain regions.** Decoding performance of regional voxel-space activity patterns within individual brain areas for each narrowband oscillatory range is displayed in the form of a heatmap for both the left and right hemisphere. Optimal decoding performance from regional voxel-space decoders were obtained from bilateral superior frontal (Left: 68.77% ± SD 7.6%; Right: 67.52% % ± SD 6.78%), middle frontal (Left: 63.41% ± SD 7.58%; Right: 62.78% % ± SD 76.94%), pre-central (Left: 62.37% % ± SD 6.32%; Right: 62.69% ± SD 5.94%), and post-central (Left: 61.71% ± SD 6.62%; Right: 61.09% ± SD 6.2%) brain regions. Superior parietal, central, paracentral, anterior-cingulate, and precuneus regions also showed greater (> 60%) decoding performance. For Delta band, only superior frontal regions showed > 60% decoding performance.

**Distribution of correlation coefficients between parcel-space and respective regional voxel-space signals**

**Figure 2 – figure supplement 2: Distribution of correlation coefficients between parcel-space and respective**

**regional voxel-space signals.** The correlation (y-axis) between regional voxel-space time-series for all voxels within

a parcel, with the average time-series for that parcel is shown for all parcels (x-axis) for a single representative subject.

The regional voxel-space selected for inclusion in the hybrid model decoder for this participant is highlighted in red

(n=8). The cumulative distribution PDF is shown on the right (grey distribution is for the whole brain; red distribution

is for the voxel-space selected for inclusion in the hybrid model decoder for this participant).

**Figure 3 – figure supplement 1: Contribution of whole-brain oscillatory frequencies to decoding.** Accuracy for decoders trained on four different input feature spaces—sensor, whole-brain parcel, whole-brain voxel and hybrid (combination of whole-brain parcel plus regional voxel)—was highest for broadband MEG activity, closely followed by delta band-limited activity. The hybrid approach resulted in the highest broadband decoding accuracy, as well as the highest accuracy for each individual narrowband range. Sensor-, parcel- and voxel-space decoders displayed similar accuracy with respect to one another for broadband MEG activity, and also for all narrowband ranges assessed. Dots depict decoding accuracy for each participant. "***" indicates $p < 0.001$, "**" indicates $p < 0.01$, and "**n.s.**" denotes no statistical significance (i.e. - $p > 0.05$).

**Figure 3 – figure supplement 2: Comparison of different dimensionality reduction techniques.** Dimensionality

reduction was applied to the input features for each approach [parcel (N=148)/voxel(N=15684)/hybrid(N=1295)] [33].

The results with principal component analysis (PCA, in green), multi-dimensional scaling (MDS, in blue), minimum

redundant maximum relevance algorithm (MRMR, in red), linear discriminant analysis (LDA, in black) are shown in

comparison to performance obtained using all input features (in magenta). For parcel space, all these approaches

increased the mean decoding accuracy with PCA and LDA showing statistically significant improvement [1-way

ANOVA: F= 13.05, $p < 0.001$; post hoc Tukey tests: $p$ =0.032 (PCA), $p < 0.001$ (LDA), $p > 0.05$ (MDS, MRMR)].

At the voxel space, there was no statistically significant improvement with either of the approaches ($p > 0.05$). MRMR

showed the highest improvement but not statistically significant with post hoc Tukey tests ($p = 0.14$). With LDA the

performance dropped significantly. For hybrid space, all the dimensionality reduction techniques were significant in

improving decoding performance [1-way ANOVA: F= 21.32, post hoc Tukey tests: $p < 0.05$] and the best

improvement was seen with LDA.

**Figure 3 – figure supplement 3: A)** Example of ICA component time-series for components labeled as artefacts from a single subject during MEG data pre-processing. The features of these components are consistent with known motion and physiological artefacts in MEG data. **B)** 4-class confusion matrix and **C)** decoding performance of keypress action labels from ICA components labeled as artefacts and removed from the MEG data during pre-processing. These components failed to predict keypress labels above chance levels (as shown by decoding performance after random label shuffling). Note that in all cases, decoding performance from movement and physiological artefacts was substantially lower than 4-class MEG hybrid-space decoding for all participants. **D)** Head position was assessed at the beginning and at the end of each recording and used to measure head movement. The mean measured head movement across the study group was 1.159 mm (± 1.077 SD).

**Figure 3 – figure supplement 4: Confusion matrices for decoding performance on Day 2 Retest (A) and Day 2 Control (B) data.** Note that the hybrid decoding strategy generalized to Day 2 data with 87.11% keypress decoding accuracy for the trained sequence (Day 2 Retest) and 79.44% accuracy for decoding keypresses embedded within untrained control sequences (Day 2 Control).

**Figure 3 – figure supplement 5: A)** Average decoding accuracies across participants with varying window parameters (top panel). The x-axis indicates the onset of window for decoding analysis with respect to keypress onset (i.e. – KeyDown event = 0), while the y-axis indicates the window size. The heatmap color denotes the decoding accuracy for all window size/location pairings. The best decoding accuracy across subjects is obtained using a window size of 200 ms with the leading edge aligned to the KeyDown event (i.e. – 0 ms; marked by the dashed lines and open circle). **B)** Decoder window parameters (onset and duration) used for each subject in reported decoder accuracy comparisons (**Figures 2-4**). Please note that the group-optimal set of parameters (window onset = 0 ms; window size = 200 ms; LDA dimensionality reduction) was utilized for all contextualization analyses (**Figure 5**) to allow for comparison across participants.

**Figure 3 – figure supplement 6: Comparison of decoding performances with two different hybrid approaches**.
Hybrid$_{Overlap}$ (regional voxel-space features from top-ranked parcels combined with all whole-brain parcel-space features as shown in **Figures 3B** and **Figure 3 – figure supplements 1,3-5** of the manuscript) and Hybrid$_{Non-overlap}$ (regional voxel-space features of top-ranked parcels and spatially *non-overlapping* whole-brain parcel-space features). Filled circle markers represent decoding accuracy for individual subjects. Dashed lines indicate the trend in performance change across participants between decoding approaches. Note, that Hybrid$_{Overlap}$ (the approach used in our manuscript) significantly outperforms the Hybrid$_{Non-overlap}$ approach (Wilcoxon signed rank test, $z = 3.7410$, $p = 1.8326e-04$), despite the removed features ($n = 8$) only comprising less than 1% of the overall input feature space. These results indicate that the spatially overlapping (lower resolution) whole-brain *parcel-space* features provide unique information compared to the (higher resolution) *regional* voxel-space patterns.

**Figure 3 – figure supplement 7: Comparison of different decoder methods.** Performance for different decoders

used is shown for each participant. The results show that linear discriminant analysis classifier (LDA) was the optimal

choice. Results from LDA decoder analyses were used for all subjects and results reported in the manuscript.

909
910
911

**Figure 4 – figure supplement 1: Quantification of regional trial-by-trial feature importance score during skill**

**learning.** The quantification of regional importance in decoding for each trial is shown for the regions that showed

highest decoding accuracy, i.e., superior frontal, middle frontal, pre-central, and post-central cortex. Note that the

feature importance score was higher for the contralateral pre-central cortex which shifted to the contralateral middle

frontal cortex during later trials, as can be seen with the divergence of line plots about trial 11.

**Figure 4 – figure supplement 2: Trial-by-trial classification accuracy for 2-class decoder (Index$_{OP1}$ vs. Index$_{OP5}$).**

Several decoders (with varying window durations aligned to the KeyDown event) were trained to differentiate between the two index finger keypresses embedded at different positions within the practiced skill sequence (Index$_{OP1}$ at ordinal position 1 vs. Index$_{OP5}$ at ordinal position 5). Decoding accuracy for the 200 ms duration windows (i.e. – the optimal window size for 4-class decoding of individual keypresses) progressively improves over early learning, stabilizing around 96% by trial 11 (end of early learning). Similar results were observed for all other decoding window sizes (50, 100, 150, 250 and 300 ms), with overall accuracy slightly lower compared to 200 ms. These findings indicate that the neural representations of the skill action is updated over early learning to incorporate sequence location information.

**Figure 4 – figure supplement 3: A)** Scatter plot of gaze positions at the KeyDown event and 200ms after the

KeyDown event (i.e. – beginning and ending of window used for decoding keypress labels from MEG input features)

from a representative participant. Transparent grey dots indicate all gaze positions during practice trials. The overall

mean gaze position during practice trials is indicated by the black filled circle marker. Colored right-pointing triangle

markers indicate the gaze position at the KeyDown event for each ordinal position keypress (Index$_{OP1}$ – magenta;

Little$_{OP2}$ – yellow; Middle$_{OP3}$ – blue; Ring$_{OP4}$ – green; Index$_{OP5}$ – brown), while left-pointing triangle markers indicate

the gaze position 200ms after the KeyDown event. The mean gaze position for these two time-points is indicated by

the larger-sized triangle markers. **B)** Confusion matrix showing that three eye movement features fail to predict

asterisk position on the task display above chance levels (Fold 1 test accuracy = 0.21718; Fold 2 test accuracy =

0.22023; Fold 3 test accuracy = 0.21859; Fold 4 test accuracy = 0.22113; Fold 5 test accuracy = 0.21373; Overall

cross-validated accuracy = 0.2181). Since the ordinal position of the asterisk on the display is highly correlated with

the ordinal position of individual keypresses in the sequence, this analysis provides strong evidence that keypress

decoding performance from MEG features is not explained by systematic relationships between finger movement

behavior and eye movements (i.e. – behavioral artefacts). **C)** 5-class decoding of ordinal position keypress labels from

eye movement recording features approached chance levels (as shown by decoding performance after random label

shuffling). Note that all decoding performances from eye movement data was substantially lower than MEG hybrid-

space decoding for all participants.

**Figure 5 − figure supplement 1. A) Relationship between offline neuronal representational change and micro-offline learning.** Offline contextualization—calculated as the Euclidian distance between the neural representations observed for the first Index$_{OP1}$ keypress from practice trial, *n*, and the last Index$_{OP5}$ keypress from practice trial, *n-1*—

increased over early learning. A linear regression analysis (shown in the inset) revealed a strong temporal relationship (correlation coefficient [$r$] = 0.903 and coefficient of variance explained [$R^2$] = 0.816) between contextualization and cumulative micro-offline gains over early learning. **B) Changes in offline contextualization for different decoding window durations as a function of rest breaks.** We constructed decoders from different MEG input feature time windows (window durations of 50, 100, 150, 200, 250 and 300ms; all aligned to the KeyDown event), to assess the robustness of the offline contextualization finding with respect to this parameter selection. Offline contextualization showed similar trends for all options tested. **C) Relationship between offline neuronal representational change and micro-offline learning.** The linear regression analysis from **(A)** was repeated for all contextualization measures from **(B)** obtained after varying the MEG input feature window size (50 – 300 ms). This strong temporal relationship was observed for all window durations ($0.598 \geq R^2 \geq 0.816$), except for 300 ms ($R^2 = 0.284$) where temporal overlap of individual keypress features was most prominent.

**Figure 5 – figure supplement 2: Trial-by-trial trends for offline and online contextualization changes. A)** Offline contextualization between the last sequence of a preceding trial and the <u>second</u> sequence of the subsequent one (skipping the first sequence of that trial) rendered a comparable result, inconsistent with a possible confounding effect of pre-planning [78, 79]. **B)** Two different approaches were used to characterize online contextualization changes. The *sequence-based* approach calculated the mean distance between $Index_{OP1}$ and $Index_{OP5}$ for each correct sequence iteration within a trial (green)**.** A second *trial-based* approach was also implemented, which controlled for the passage of time between observations used in both online and offline distance measures (10 seconds between $Index_{OP1}$ and $Index_{OP5}$ observations in both cases). Note that the *trial-based* approach showed no increase in online contextualization over early learning. Importantly, the overall magnitude of online contextualization by the end of early learning was similar with both measurement approaches and both were reduced relative to offline contextualization.

**Figure 5 – figure supplement 3: Online contextualization versus micro-online learning.** The relationship between online contextualization and online learning is shown for both *sequence-based* (**A**, left) and *trial-based* (**B**, right) distance measurement approaches. There was no significant relationship between online learning and online contextualization regardless of the measurement approach.

**Figure 5 – figure supplement 4: Within-subject correlations between online and offline contextualization changes versus learning.** Pirate plots displaying individual subject correlation coefficients for offline (i.e. – over rest) and online (i.e. – during practice) contextualization changes versus micro-offline and micro-online performance gains. Within-subject correlations were significantly greater for offline contextualization changes versus micro-offline performance gains than for online contextualization changes versus either micro-online or micro-offline performance gains. The average correlation between offline contextualization and micro-offline gains within individuals was significantly greater than zero (**left;** t = 3.87, p = 0.00035, df = 25, Cohen's d = 0.76) and stronger than correlations between online contextualization and either micro-online (**middle**; t = 3.28, p = 0.0015, df = 25, Cohen's d = 1.2) or micro-offline gains (**right**; t = 3.7021, p = 5.3013e-04, df = 25, Cohen's d = 0.69).

**Figure 5 – figure supplement 5: Online versus offline changes in keypress transition patterns. A)** Trial-by-trial

Euclidian distance between the relative share of each keypress transition time to the full sequence duration (i.e. –

differences in typing rhythm). This distance was calculated for the first and last sequence of each trial (online pattern

distance; green) and the last sequence of a trial versus the first sequence of the next (offline pattern distance; purple).

**B)** Cumulative online (green; left) and offline (purple; right) pattern distances recorded over all forty-five trials

covering Days 1 and 2. Note the comparable online and offline typing rhythm changes do not explain differences

between online and offline contextualization fully developed by trial 11 (**Figure 5**).

**Figure 5 – figure supplement 6: Relationship between adjacent index finger transitions and online**
**contextualization.** The above scatter plot shows that the sum of adjacent index finger keypress transition times (i.e.
– the 4-4 transition at the conclusion of one sequence iteration and the 4-1 transition at the beginning of the next
sequence iteration) versus online contextualization distances measured during practice trials. Both the keypress
transition times and online contextualization scores were z-score normalized within individual subjects, and then
concatenated into a single data superset. A simple linear regression between keypress transition time predictor and
the online contextualization response variable showed a very weak linear relationship between the two ($R^2$ =
0.00507, F[1,3202] = 16.3). This result shows that contextualization of index finger representations does not reflect
the amount of overlap between adjacent keypresses.

1005

**Figure 5 – figure supplement 7: Between subject differences in typing speed versus online contextualization. A)**

Between-subject relationship between plateau performance speed and online contextualization. The plateau

performance typing speed showed no significant relationship with the degree of online contextualization ($R^2 = 0.028$,

$p = 0.41$). Each dot represents the maximum speed attained and the corresponding degree of contextualization of each

participant. Thus, the magnitude of online contextualization was not dependent on how fast individuals could perform

the task at the end of early learning. **B)** Trial-by-trial relationship between typing speed and degree of online

contextualization. We also performed a trial-by-trial regression analysis that related the degree of online

contextualization for each trial with the median typing speed for that trial. The violin plot represents the distribution

of $R^2$ values obtained with regression analysis and here each dot represents a trial. Note that, there was no significant

relationship at any trial (mean $R^2 = 0.06$; $p > 0.05$).

**REFERENCES**

1.  Bönstrup, M., et al., *A Rapid Form of Offline Consolidation in Skill Learning.* Curr Biol, 2019. **29**(8): p. 1346-1351 e4.
2.  Schmidt, R.A., et al., *Motor control and learning: A behavioral emphasis*. 2018: Human kinetics.
3.  Doyon, J. and H. Benali, *Reorganization and plasticity in the adult brain during learning of motor skills.* Current opinion in neurobiology, 2005. **15**(2): p. 161-167.
4.  Dehaene, S., et al., *The Neural Representation of Sequences: From Transition Probabilities to Algebraic Patterns and Linguistic Trees.* Neuron, 2015. **88**(1): p. 2-19.
5.  Walker, M.P. and R. Stickgold, *Sleep-dependent learning and memory consolidation.* Neuron, 2004. **44**(1): p. 121-33.
6.  Buch, E.R., et al., *Consolidation of human skill linked to waking hippocampo-neocortical replay.* Cell Rep, 2021. **35**(10): p. 109193.
7.  Jacobacci, F., et al., *Rapid hippocampal plasticity supports motor sequence learning.* Proc Natl Acad Sci U S A, 2020. **117**(38): p. 23898-23903.
8.  Mylonas, D., et al., *Maintenance of Procedural Motor Memory across Brief Rest Periods Requires the Hippocampus.* J Neurosci, 2024. **44**(14).
9.  Hayward, W., et al., *Procedural Motor Memory Deficits in Patients With Long-COVID.* Neurology, 2024. **102**(3): p. e208073.
10. Brooks, E., et al., *Micro-consolidation occurs when learning an implicit motor sequence, but is not influenced by HIIT exercise.* NPJ Sci Learn, 2024. **9**(1): p. 23.
11. Bönstrup, M., et al., *Mechanisms of offline motor learning at a microscale of seconds in large-scale crowdsourced data.* NPJ Sci Learn, 2020. **5**: p. 7.
12. Chen, P.-C., et al., *Hippocampal ripples during offline periods predict human motor sequence learning.* bioRxiv, 2024: p. 2024.10.06.614680.
13. Sjøgård, M., et al., *Hippocampal ripples mediate motor learning during brief rest breaks in humans.* bioRxiv, 2024.
14. Wamsley, E.J., et al., *Memory Consolidation during Ultra-short Offline States.* J Cogn Neurosci, 2023. **35**(10): p. 1617-1634.
15. Griffin, S., et al., *Ensemble reactivations during brief rest drive fast learning of sequences.* Nature, 2025.
16. Karni, A., et al., *Functional MRI evidence for adult motor cortex plasticity during motor skill learning.* Nature, 1995. **377**(6545): p. 155-8.
17. Song, S. and L.G. Cohen, *Practice and sleep form different aspects of skill.* Nat Commun, 2014. **5**: p. 3407.
18. Natraj, N., et al., *Compartmentalized dynamics within a common multi-area mesoscale manifold represent a repertoire of human hand movements.* Neuron, 2022. **110**(1): p. 154-174 e12.
19. Ghilardi, M.F., et al., *Learning of a sequential motor skill comprises explicit and implicit components that consolidate differently.* J Neurophysiol, 2009. **101**(5): p. 2218-29.
20. Yokoi, A. and J. Diedrichsen, *Neural organization of hierarchical motor sequence representations in the human neocortex.* Neuron, 2019. **103**(6): p. 1178-1190.
21. Beukema, P., J. Diedrichsen, and T.D. Verstynen, *Binding During Sequence Learning Does Not Alter Cortical Representations of Individual Actions.* J Neurosci, 2019. **39**(35): p. 6968-6977.
22. Merino, E.C., A. Faes, and M.M. Van Hulle, *The role of distinct ECoG frequency features in decoding finger movement.* J Neural Eng, 2023. **20**(6).
23. Liu, C., et al., *Decoding the EEG patterns induced by sequential finger movement for brain-computer interfaces.* Frontiers in Neuroscience, 2023. **17**.

24.  Lee, H.S., et al., *Individual finger movement decoding using a novel ultra-high-density electroencephalography-based brain-computer interface system.* Front Neurosci, 2022. **16**: p. 1009878.
25.  Zhao, Y., et al., *Decoding finger movement patterns from microscopic neural drive information based on deep learning.* Med Eng Phys, 2022. **104**: p. 103797.
26.  Yao, L., B. Zhu, and M. Shoaran, *Fast and accurate decoding of finger movements from ECoG through Riemannian features and modern machine learning techniques.* Journal of Neural Engineering, 2022. **19**(1): p. 016037-016037.
27.  Hikosaka, O., et al., *Parallel neural networks for learning sequential procedures.* Trends Neurosci, 1999. **22**(10): p. 464-71.
28.  Munn, B.R., et al., *Multiscale organization of neuronal activity unifies scale-dependent theories of brain function.* Cell, 2024.
29.  Pan, S.C. and T.C. Rickard, *Sleep and motor learning: Is there room for consolidation?* Psychol Bull, 2015. **141**(4): p. 812-34.
30.  Destrieux, C., et al., *Automatic parcellation of human cortical gyri and sulci using standard anatomical nomenclature.* Neuroimage, 2010. **53**(1): p. 1-15.
31.  Buch, E.R., S.L. Liew, and L.G. Cohen, *Plasticity of Sensorimotor Networks: Multiple Overlapping Mechanisms.* Neuroscientist, 2017. **23**(2): p. 185-196.
32.  Lisman, J. and G. Buzsaki, *A neural coding scheme formed by the combined function of gamma and theta oscillations.* Schizophr Bull, 2008. **34**(5): p. 974-80.
33.  Van Der Maaten, L., E.O. Postma, and H.J. van den Herik, *Dimensionality reduction: A comparative review.* Journal of Machine Learning Research, 2009. **10**(66-71): p. 13-13.
34.  Lemon, R.N., *Descending pathways in motor control.* Annu Rev Neurosci, 2008. **31**: p. 195-218.
35.  Zimerman, M., et al., *Disrupting the Ipsilateral Motor Cortex Interferes with Training of a Complex Motor Task in Older Adults.* Cereb Cortex, 2012.
36.  Waters, S., T. Wiestler, and J. Diedrichsen, *Cooperation Not Competition: Bihemispheric tDCS and fMRI Show Role for Ipsilateral Hemisphere in Motor Learning.* J Neurosci, 2017. **37**(31): p. 7500-7512.
37.  Sawamura, D., et al., *Acquisition of chopstick-operation skills with the non-dominant hand and concomitant changes in brain activity.* Sci Rep, 2019. **9**(1): p. 20397.
38.  Lee, S.H., S.H. Jin, and J. An, *The difference in cortical activation pattern for complex motor skills: A functional near- infrared spectroscopy study.* Sci Rep, 2019. **9**(1): p. 14066.
39.  Grafton, S.T., E. Hazeltine, and R.B. Ivry, *Motor sequence learning with the nondominant left hand. A PET functional imaging study.* Exp Brain Res, 2002. **146**(3): p. 369-78.
40.  Liao, K., et al., *Decoding individual finger movements from one hand using human EEG signals.* PloS one, 2014. **9**(1): p. e85192-e85192.
41.  Quandt, F., et al., *Single trial discrimination of individual finger movements on one hand: a combined MEG and EEG study.* NeuroImage, 2012. **59**(4): p. 3316-3324.
42.  Kornysheva, K., et al., *Neural Competitive Queuing of Ordinal Structure Underlies Skilled Sequential Action.* Neuron, 2019. **101**(6): p. 1166-1180 e3.
43.  Reddy, L., et al., *Theta-phase dependent neuronal coding during sequence learning in human single neurons.* Nat Commun, 2021. **12**(1): p. 4839.
44.  Bansal, A.K., et al., *Relationships among low-frequency local field potentials, spiking activity, and three-dimensional reach and grasp kinematics in primary motor and ventral premotor cortices.* J Neurophysiol, 2011. **105**(4): p. 1603-19.
45.  Mollazadeh, M., et al., *Spatiotemporal variation of multiple neurophysiological signals in the primary motor cortex during dexterous reach-to-grasp movements.* J Neurosci, 2011. **31**(43): p. 15531-43.

46.  Bönstrup, M., et al., *Low-Frequency Brain Oscillations Track Motor Recovery in Human Stroke.* Ann
Neurol, 2019. **86**(6): p. 853-865.
47.  Cruikshank, L.C., et al., *Theta oscillations reflect a putative neural mechanism for human*
*sensorimotor integration.* J Neurophysiol, 2012. **107**(1): p. 65-77.
48.  Tomassini, A., et al., *Theta oscillations locked to intended actions rhythmically modulate*
*perception.* Elife, 2017. **6**.
49.  Ramanathan, D.S., et al., *Low-frequency cortical activity is a neuromodulatory target that tracks*
*recovery after stroke.* Nat Med, 2018. **24**(8): p. 1257-1267.
50.  Hall, T.M., K. Nazarpour, and A. Jackson, *Real-time estimation and biofeedback of single-neuron*
*firing rates using local field potentials.* Nat Commun, 2014. **5**: p. 5462.
51.  Stefanics, G., et al., *Phase entrainment of human delta oscillations can mediate the effects of*
*expectation on reaction speed.* J Neurosci, 2010. **30**(41): p. 13578-85.
52.  Flint, R.D., et al., *Local field potentials allow accurate decoding of muscle activity.* J Neurophysiol,
2012. **108**(1): p. 18-24.
53.  Krasoulis, A., et al., *Generalizability of EMG decoding using local field potentials.* Annu Int Conf
IEEE Eng Med Biol Soc, 2014. **2014**: p. 1630-3.
54.  Churchland, M.M., et al., *Neural population dynamics during reaching.* Nature, 2012. **487**(7405):
p. 51-6.
55.  Frohlich, J., D. Toker, and M.M. Monti, *Consciousness among delta waves: a paradox?* Brain, 2021.
**144**(8): p. 2257-2277.
56.  Classen, J., et al., *Rapid plasticity of human cortical movement representation induced by practice.*
J Neurophysiol, 1998. **79**(2): p. 1117-23.
57.  Kleim, J.A., S. Barbay, and R.J. Nudo, *Functional reorganization of the rat motor cortex following*
*motor skill learning.* J Neurophysiol, 1998. **80**: p. 3321-5.
58.  Kumar, N., T.F. Manning, and D.J. Ostry, *Somatosensory cortex participates in the consolidation of*
*human motor memory.* PLoS Biol, 2019. **17**(10): p. e3000469.
59.  Pavlides, C., E. Miyashita, and H. Asanuma, *Projection from the sensory to the motor cortex is*
*important in learning motor skills in the monkey.* J Neurophysiol, 1993. **70**(2): p. 733-41.
60.  Dayan, E. and L.G. Cohen, *Neuroplasticity subserving motor skill learning.* Neuron, 2011. **72**(3): p.
443-54.
61.  Robertson, E.M. and D.A. Cohen, *Understanding consolidation through the architecture of*
*memories.* Neuroscientist, 2006. **12**(3): p. 261-71.
62.  Komorowski, R.W., J.R. Manns, and H. Eichenbaum, *Robust conjunctive item-place coding by*
*hippocampal neurons parallels learning what happens where.* J Neurosci, 2009. **29**(31): p. 9918-
29.
63.  Georgopoulos, A.P., *Population activity in the control of movement.* Int Rev Neurobiol, 1994.
**37**(103): p. 103-19.
64.  Georgopoulos, A.P., et al., *On the relations between the direction of two-dimensional arm*
*movements and cell discharge in primate motor cortex.* J Neurosci, 1982. **2**(11): p. 1527-37.
65.  Das, A., et al., *"Micro-offline gains" convey no benefit for motor skill learning.* bioRxiv, 2024: p.
2024.07.11.602795.
66.  Gupta, M.W. and T.C. Rickard, *Dissipation of reactive inhibition is sufficient to explain post-rest*
*improvements in motor sequence learning.* NPJ Sci Learn, 2022. **7**(1): p. 25.
67.  Ruiz, M.H., H.-C. Jabusch, and E. Altenmüller, *Detecting wrong notes in advance: neuronal*
*correlates of error monitoring in pianists.* Cerebral cortex, 2009. **19**(11): p. 2625-2639.
68.  Maidhof, C., et al., *Nobody is perfect: ERP effects prior to performance errors in musicians indicate*
*fast monitoring processes.* PLoS One, 2009. **4**(4): p. e5032.

69.    Censor, N., S.G. Horovitz, and L.G. Cohen, *Interference with existing memories alters offline*
1158           *intrinsic functional brain connectivity.* Neuron, 2014. **81**(1): p. 69-76.
1159    70.    Brawn, T.P., et al., *Consolidating the effects of waking and sleep on motor-sequence learning.* J
1160           Neurosci, 2010. **30**(42): p. 13977-82.
1161    71.    Rickard, T.C., et al., *Sleep does not enhance motor sequence learning.* J Exp Psychol Learn Mem
1162           Cogn, 2008. **34**(4): p. 834-42.
1163    72.    Walker, M.P., et al., *Practice with sleep makes perfect: sleep-dependent motor skill learning.*
1164           Neuron, 2002. **35**(1): p. 205-11.
1165    73.    Oostenveld, R., et al., *FieldTrip: open source software for advanced analysis of MEG, EEG, and*
1166           *invasive electrophysiological data.* Computational intelligence and neuroscience, 2011. **2011**: p.
1167           1-9.
1168    74.    Delorme, A. and S. Makeig, *EEGLAB: an open source toolbox for analysis of single-trial EEG*
1169           *dynamics including independent component analysis.* Journal of neuroscience methods, 2004.
1170           **134**(1): p. 9-21.
1171    75.    Gramfort, A., et al., *MEG and EEG data analysis with MNE-Python.* Front Neurosci, 2013. **7**: p. 267.
1172    76.    Rijsbergen, V., *Information retrieval.* J. Librariansh., 1979. **11**: p. 237.
1173    77.    Schütze, H., C.D. Manning, and P. Raghavan, *Introduction to information retrieval*. 2008:
1174           Cambridge University Press.
1175    78.    Ariani, G., M. Shahbazi, and J. Diedrichsen, *Cortical areas for planning sequences before and*
1176           *during movement.* J Neurosci, 2024.
1177    79.    Ariani, G. and J. Diedrichsen, *Sequence learning is driven by improvements in motor planning.* J
1178           Neurophysiol, 2019. **121**(6): p. 2088-2100.

1179