Mispitools: An R package for comprehensive statistical methods in Kinship Inference

by Franco L. Marsico

Abstract The search for missing persons is a complex process that involves the comparison of data from two entities: unidentified persons (UP), who may be alive or deceased, and missing persons (MP), whose whereabouts are unknown. Although existing tools support DNA-based kinship analyses for the search, they typically do not integrate or statistically evaluate diverse lines of evidence collected throughout the investigative process. Examples of alternative lines of evidence are pigmentation traits, biological sex, and age, among others. The package **Mispitools** fills this gap by providing comprehensive statistical methods adapted to a holistic investigation workflow. **Mispitools** systematically assesses the data from each investigative stage, computing the statistical weight of various types of evidence through a likelihood ratio (LR) approach. It also provides models for combining obtained LRs. Furthermore, **Mispitools** offers customized visualizations and a user-friendly interface, broadening its applicability among forensic practitioners and genealogical researchers.

Introduction

The search for missing persons involves several steps, including preliminary investigation, archaeological research, obtaining DNA samples, analyzing DNA profiles, performing a statistical evaluation of evidence, and communicating the results (Puerto et al., 2021). The main aim of the search is to link two entities, the Missing Person (MP) and the Unidentified Person (UP). The MP represents an identity without a body. The UP refers to a body without identity, whether it corresponds to an individual whose biological identity is unknown, who is alive, or to unidentified human remains that are dead. In recent years, Forensic Investigative Genetic Genealogy (FGG) has been used to search for missing persons (Kling et al., 2021). In this area, dense SNP data are used in large databases to identify distant relatives of MPs (beyond first cousins). Historical records are combined with results from genetic analyses to assist in the search. This approach is also implemented in criminal investigations, where UP genetic data could correspond to DNA present in a crime scene, suspected to be from the perpetrator.

During the search, genetic and non-genetic data from both entities are collected as evidence. Testimonies, historical records, judicial documentation, interviews with families, and dental and medical records are some of the evidence that contribute to the MP's data, collected during the preliminary investigation. Generally, due to the absence of DNA data for MP, genetic information from relatives is used to perform a kinship test. Data about UP are collected from unidentified human remains and the surrounding context of the remains. For example, cemetery books could provide the date of inhumation and sometimes the date of death. In addition, different forensic techniques can contribute to estimating the time since death (Calla et al., 2021) and clues related to the crime scene, such as the analysis of bloodstain patterns and the estimation of the time since deposition (Vale et al., 2023). In some specific cases, such as child abductions and related cases, the UP is a living person who requires their biological identity to be proven (Puerto et al., 2021; Marsico et al., 2021).

In a DNA-database search, each UP is compared to the MP's relatives using a statistical DNA kinship test based on the likelihood ratio (LR). A potential match is declared if the LR exceeds a specified threshold T (Kruijver et al., 2014). With recent advances in DNA genotyping and database search software, forensic professionals have incorporated DNA database search as a common practice in human identification cases. This area has been the target of multiple developments and guidelines to address opportunities and challenges. More recently, different methodologies such as Open Source Intelligence Techniques and social network analysis have allowed, in some cases, the rapid construction of preliminary investigation databases used in forensic settings (Dincelli et al., 2023). However, opportunities and challenges for these databases have not been studied as thoroughly as those of DNA databases. Moreover, despite their crucial importance in identifications, only some approaches mathematically formalize the possibility of non-genetic data, usually gathered during the preliminary investigation step, in the search process (Marsico and Caridi, 2023).

Typically, results obtained in any step of the search could lead to more investigation in another. For example, in a case where the work is done with samples from burned remains, with insufficient DNA data, DNA-database searches are hampered by low statistical power. Statistical power refers to the probability of reaching a conclusion when testing a specific hypothesis with the available data

(Kling et al., 2017). More data must be collected if the statistical power is deemed too low. For example, this can be done by recruiting additional family members (Vigeland et al., 2020). This implies doing more research in the preliminary investigation step to find more relatives in the familial pedigree. In addition, low statistical power usually leads to a high number of false positives. This implies the need to rationally select a subset of UPs (potential matches) to collect more genetic data (Marsico et al., 2021). In these cases, other information collected during the preliminary investigation, such as biological sex, age, and pigmentation traits, also becomes useful. Moreover, there are cases where genetic data alone is not enough to reach a conclusion. Such cases include paternity tests where DNA-based kinship can establish a parent-offspring relationship, but not the direction; that is, it cannot resolve who is the parent and who is the child. This is a common situation in mass graves and FGG. Another example involves individuals found to be siblings, but based on DNA data, we cannot distinguish the younger from the older. These aspects elucidate the requirement for an integrative approach when considering missing persons search, where different lines of evidence must be taken into account.

On the Comprehensive R Archive Network (CRAN), there are several packages to compute kinship testing and statistical power. We describe some of them: **Familias** comprises the open-source R code of the widely used Familias software (Kling et al., 2014). **dvir** package is oriented towards computing kinship testing in disaster victim identification cases (Vigeland, 2021). **pedprob** package allows for computing genetic marker probabilities and pedigree probabilities by implementing the Elston-Stewart algorithm (Elston and Stewart, 1971). **forrel** is a package with functions oriented towards missing person cases (Vigeland et al., 2020). **forensit** and **fbnet** offer an information-theoretic approach for kinship testing (Marsico et al., 2024; Chernomoretz et al., 2022). **kinship2** package allows for computing the kinship coefficient matrix and provides useful functions for the plotting of pedigrees (Sinnwell et al., 2014). However, there is a lack of statistical tools for incorporating other, non-genetic, data into the search workflow.

In this paper, we introduce our R package of missing person identification tools, named **mispitools**. This package implements methods for computing the LR based on preliminary investigation characteristics, LR thresholds, error rates analysis, models for combining evidence, and others. These methods are based on computational simulations, also provided by **mispitools**, which allow researchers to study the expected outcomes of the search process based on a wide range of evidences (DNA, pigmentation traits, age, etc.). This package and its details are available on CRAN at `https://CRAN.R-project.org/package=mispitools`. The **mispitools** functions implement the methods described previously in several publications (Marsico et al., 2021; Marsico and Caridi, 2023; Marsico et al., 2024; Marsico and Egeland, 2024), and new functions have also been incorporated. Some of these methods have been developed to deal with specific contexts, such as DNA-based missing person identification cases hampered by low statistical power. Here we show a wider applicability of the methods, extending the field in which they can be used. Importantly, we show how to combine approaches that previously haven't been jointly considered, elucidating their utility in examples. Last but not least, all the methods described have been used in real cases, so this package also summarizes the cumulative experience in the missing person search field.

The paper is structured as follows. First, we introduce the methodology regarding the search process for missing persons, DNA kinship tests, likelihoods calculations for non-genetic data, error rates, LR threshold selection, and performance metrics. Then, we describe the **mispitools** package and illustrate its use in two examples. Finally, we provide a summary.

Methodology and background

In this section, the methodological background and statistical approach are described. The main aim is to provide a gentle introduction to the key concepts. We will deal with the basic mathematical formalization required to understand the application of the methods, which we will show in the following section. For more mathematical details, we suggest that the reader consult (Marsico et al., 2021) for threshold selection; (Marsico and Caridi, 2023) and (Marsico and Egeland, 2024) for non-genetic data LR models; and (Marsico et al., 2024) for analysis of information content. All of these works present the theoretical foundations for the methods implemented in **mispitools**.

Overview of the search

In a missing person case, data from the MP and UP are collected and compared. It usually involves several steps, where different types of data are obtained. Figure 1 presents a general overview of the entire process. Generally, data collection begins with the preliminary investigation step. Preliminary investigation data may come from different sources, such as legal documentation, testimonies from relatives and witnesses, social media information, and direct observation. Some of these data, for

example, pigmentation traits, can be compared between UP and MP. Others could be obtained only from one of the entities, for example, the date of disappearance for MP. For those that can be easily compared, we name their analysis PIE (preliminary investigation evidence analysis). The other cases could be useful for studying non-evident patterns that can help in the search. This package does not address these last variables; however, useful approaches can be found in (Caridi et al., 2011, 2020).

Figure 1: An overview of the search process for both missing person cases and criminal investigations. In missing person cases, data from unidentified persons (UP) and missing persons (MP) are collected and compared. Similarly, in criminal investigations, data from suspects (or their relatives in cases involving familial DNA searching) and evidence from the crime scene are gathered and analyzed using the same workflow. The statistical weight of both genetic evidence and preliminary investigative data (such as physical traits) is assessed through a likelihood ratio. The results are then combined to identify potential matches, generating a list of MPs or suspects who may correspond to the UP or to the individual whose traces were found at the crime scene.

During the laboratory step, through DNA analysis, genetic data from MP's relatives (the reference pedigree) and UP are collected. DNA data consist of genetic markers for STR and/or SNP. These data can be compared using a DNA-based kinship test. We name this process FDE analysis (forensic DNA evidence analysis). In addition, in the laboratory step, techniques such as DNA phenotyping, anthropological, and entomological analysis can be used to infer traits of individuals, generally from the remains of UP (Vidaki et al., 2017). Usually, these data are compared with the preliminary investigation data from the MP.

All data collected is integrated and compared to declare an identification, both PIE and FDE. When possible, a statistical weight of the evidence is measured using the LR approach. This is the standard in genetic data, but less common in other types of evidence. Finally, results are reported.

Statistical weight of the evidence

One important concept in forensic science is the statistical weight of the evidence. It allows us to compare the probability of observing the data given competing propositions through the LR. In missing person cases, the propositions are the following: H_1 : UP is the MP, and H_2 : UP is not the MP, and is a random person taken from the reference population not related to MP. The general formula for computing the LR is presented below.

$$LR = \frac{P(data|H_1)}{P(data|H_2)} \tag{1}$$

Here, *data* refers to different lines of evidence that could be mathematically formalized and compared. For example, we are searching for a missing person, named MP_i. The color of MP_i's eyes is brown. We are analyzing a specific unidentified person (named UP_j), whose eye color is also brown.

Evaluating the statistical weight of the evidence, in this case, the color of the eye, implies computing the probability of observing the brown eye color of UP_i, given that UP_i is MP_i, and comparing it with the probability of observing the same given that UP_i is not MP_i. In a simple example, we would expect that if UP_i is MP_i (H_1 is true), both colors must be the same, and therefore this probability is 1. In contrast, if they are not the same person and UP_i is a random person from the reference population, the probability of observing the eye color of UP_i is the frequency of brown eyes in the reference population. If that frequency is, for example, 0.5, we have

$$LR = \frac{1}{0.5} = 2$$

This value is interpreted as: it is 2 times more probable to observe the data given that H_1 is true than if H_2 is true. Intuitively, it could be guessed that a higher LR favors H_1 against H_2. In another example, both UP and MP have blue eye colors. The probability of observing this, given H_1, is the same. But because the blue color is less frequent, with a probability of 0.1, we have

$$LR = \frac{1}{0.1} = 10$$

This example elucidates one of the characteristics of the search: rarer attributes can provide more statistical weight. This property has been studied through information-theoretic approaches (Marsico et al., 2024). In more realistic scenarios, the LR computation is more difficult. For PIE, different phenomena such as typing errors, uncertainty in testimonies, and technical problems in techniques such as DNA phenotyping need to be incorporated into the model. For FDE, mutations, drop-in and drop-out, as well as other population genetic processes, are also incorporated. In the following subsection, specific LR models for different lines of evidence are described.

Preliminary Investigation Evidence

We define several variables from PIE: biological sex (S), age (A), and pigmentation traits (C). S is categorized as female (F) or male (M). Age is a continuous variable from 0 to 100 years. The composite variable C includes hair color (C_H), skin tone (C_S), and eye color (C_Y), according to the HIrisPlex system (Walsh et al., 2013). Specifically, $C_H = 1, 2, 3, 4$ (with 1 for blonde hair, 2 for brown hair, 3 for red hair, and 4 for black hair), $C_S = 1, 2, 3, 4, 5$ (representing skin tones from very pale to dark or black), and $C_Y = 1, 2, 3$ (with 1 for blue, 2 for intermediate, and 3 for brown eyes).

For S, we present the LR model, named LR_S:

$$LR_S = \frac{P(S_{UP}|S_{MP}, H_1)}{P(S_{UP}|S_{MP}, H_2)} = \begin{cases} \frac{1-\epsilon_S}{P(S_{UP})} & \text{if } S_{UP} = S_{MP} \\ \frac{\epsilon_S}{P(S_{UP})} & \text{if } S_{UP} \neq S_{MP} \end{cases} \tag{2}$$

In this model, S_{UP} and S_{MP} represent the biological sexes of unidentified and missing persons, respectively. The analysis considers scenarios of sex concordance ($S_{UP} = S_{MP}$) and discordance ($S_{UP} \neq S_{MP}$). An error parameter, ϵ_S, compensates for possible inaccuracies due to erroneous testimony, data entry errors, or laboratory misinterpretations.

The age variable A is continuous, integrating uncertainties in A_{MP} from inaccurate testimony and A_{UP} from laboratory estimates, including DNA predictions or anthropological analyzes (Vidaki et al., 2017). These uncertainties define the age ranges $A_{UP} = \{UP_{\min}, UP_{\max}\}$ and $A_{MP} = \{MP_{\min}, MP_{\max}\}$, detailed in (Cunha et al., 2009). An overlap in these ranges, indicating concordance, is measured by the Boolean variable ψ, where $\psi = 1$ denotes overlap and $\psi = 0$ does no overlap. The LR model for A is described below:

$$LR_A = \frac{P(\psi|A_{UP}, A_{MP}, H_1)}{P(\psi|A_{UP}, A_{MP}, H_2)} = \begin{cases} \frac{1-\epsilon_A}{P_1} & \text{if } \psi = 1 \\ \frac{\epsilon_A}{P_0} & \text{if } \psi = 0 \end{cases} \tag{3}$$

In this model, ϵ_A denotes the error rate of data entry and uncertainties in estimating age ranges using laboratory analyzes. P_1 and P_0 represent the frequencies of the ψ values in the reference population, where P_1 is the frequency of individuals who meet the age overlap with MP, and P_0 is the frequency of those who do not. Hence, $P_1 + P_0 = 1$.

In the case that we are dealing with a single pigmentation trait, for example, hair color (C_H), we can avoid conditional dependency on others. Therefore, the LR is defined as follows:

$$LR_C = \begin{cases} \frac{\lambda_i}{P(C_{UP})}, & \text{if } C_{UP} = C_{MP} \\ \frac{\lambda_i \epsilon_{ij}}{P(C_{UP})}, & \text{if } C_{UP} \neq C_{MP} \end{cases} \qquad (4)$$

The error rate for hair color is defined for each $C_{UP_j} - C_{MP_i}$ pair, reflecting the classification difficulty between colors. For instance, the error rate differs between more similar colors like blonde and red compared to distinctly different colors like black and red. A normalization constant λ_i ensures the total probability for a given MP equals 1.

For multiple pigmentation traits, the conditional dependency must be taken into account. Given the phenotypic characteristics (C) of an MP and UP, including hair, skin, and eye color, and the defined error rates e_h, e_s, and e_y, the LR equation integrates error rates and concordance indicators ($\delta_h, \delta_s, \delta_y$):

$$LR_C = \frac{((1 - \delta_h \cdot e_h - \delta_s \cdot e_s - \delta_y \cdot e_y) \cdot e_h^{1-\delta_h} \cdot e_s^{1-\delta_s} \cdot e_y^{1-\delta_y}) \cdot \varphi}{f_{h,s,y}} \qquad (5)$$

The normalization factor φ ensures that the probabilities sum to one and $f_{h,s,y}$ adjusts for the observed frequency using Laplace smoothing.

Forensic DNA evidence

For genetic evidence in Missing Persons Identification (MPI) scenarios, the genetic profile G_α consists of a set of markers $M_{\alpha,i}$, which capture the genotypes of UP and any potential relatives of MP. Using parameters such as mutation rates and population structure, the LR for this scenario is defined as follows.

$$LR_G = \frac{P(G_{UP}, G_R | H_1)}{P(G_{UP}, G_R | H_2)} \qquad (6)$$

Here, $\{G_{UP}, G_R\}$ represents the genotype data for UP and MP relatives, with $P(G_{UP}, G_R | H_i)$ indicating the likelihood of observing the specific genetic profiles under the hypothesis H_i. The LR quantifies the comparative likelihood of the evidence under hypothesis H_1 versus H_2.

Combining evidence

We assume that genetic and non-genetic evidence are independent. Thus, for a specific scenario a, the combined Likelihood Ratio (LR) is modeled as:

$$LR = LR_G \cdot LR_C \cdot LR_A \cdot LR_S \qquad (7)$$

This formulation presumes the conditional independence of the genetic, color, age, and sex variables for the calculation of LR. However, it accounts for the interdependence among color traits, specifically between hair, skin, and eye color, thus refining the model to better reflect the nuances of phenotypic characteristics.

Computational simulations

The methodology to perform simulations of both FDE and PIE is described in this section. Several approaches have previously been proposed for FDE simulations (Vigeland et al., 2020; Marsico et al., 2021; Kling et al., 2017). However, there is a lack of implementations with regard to PIE simulations. Taking into account both types of evidence, complete missing person search scenarios can be explored and different downstream analyzes can be performed using simulated data (Vigeland et al., 2020). We describe a general approach for performing simulations for PIE and FDE below, accompanied by a pseudocode for implementing these simulations.

The algorithm outlines that for each MP_i, a set of N UPs is simulated, and for each UP_j, data (either genetic or nongenetic) are generated assuming hypotheses H_1 or H_2. Typically, simulations include 10,000 UPs for each hypothesis. As a practical example, we can simulate the sex variable S for an MP identified as female ($S_{MP} = F$) with an error rate $\epsilon_S = 0.05$, resulting in two lists of UPs: one under H_1 with an expected female proportion of 0.95 (9,500 out of 10,000), and another under H_2 reflecting the frequency of the general population $P(F)$. This method can be extended to other data types. Once simulated, the PIE and FDE data can be used to compute LRs.

Algorithm 1 Evidence Simulations

---

for j in $(MP_1, MP_2, \ldots, MP_K)$ **do**
    Simulate N UPs
    for i in $(UP_1, UP_2, UP_3, \ldots, UP_N)$ **do**
        Simulate *data* considering $P(data|H)$
    end for
end for

Performance metrics

In this section, we introduce performance metrics used for both FDE and PIE (and the combination of both). Performance studies allow forensic practitioners to evaluate the expected results of the search considering available data and LR models. This means that researchers can study, for example, the number of expected cases above a LR threshold. This could be used to decide between advancing the search with available data or putting more effort into gathering more evidence (Marsico et al., 2021), among other applications. Here, we define two general approaches for performance analysis, one based on computational simulations and the other on information theory metrics.

The first method utilizes the output of the simulations to obtain $Log_{10}(LR)$ distributions considering that H_1 or H_2 is true. This allows for defining the false negative rate (FNR) as a function of the threshold T,

$$\text{FNR}(T) = P(LR < T \mid H1) \tag{8}$$

and similarly for the false positive rate (FPR):

$$\text{FPR}(T) = P(LR > T \mid H2) \tag{9}$$

For each pedigree, with conditional simulations, we estimated FNR and FPR for each integer T between 1 and 1,000. The Decision Threshold (DT) approach can be used to select that subset of UPs for which gathering more FDE and PIE data could help in solving the case. DT is the value of T that minimizes the following weighted Euclidean distance (WED) to the theoretical optimum:

$$DT = \min WED(T) \tag{10}$$

$$\text{WED} = \sqrt{(W_1\text{FPR})^2 + (W_2\text{FNR})^2} \tag{11}$$

The choice of weights W_1 and W_2 reflects the relative importance of false positives and negatives. In this case, we used $W_1 = 10$, and $W_2 = 1$ (see Marsico et al. (Marsico et al., 2021) for more details). The Matthews correlation coefficient (MCC) can be employed as a summary measure considering all defined error rates.

Other metrics based on information theory (IT) have been proposed (Ramos et al., 2020). One of the main advances is that they use the conditional probability tables $P(data|H_1)$ and $P(data|H_2)$ as input, therefore, they can be directly computed avoiding computational simulations. In particular, the Kullback-Leibler metric has recently been proposed as a way to study the improvement of the addition of a new relative to a pedigree (Marsico et al., 2024). It quantifies the difference between two probability distributions, $P_1(G)$ and $P_2(G)$, as follows:

$$KL \equiv D_{KL}(P_1(G) \| P_2(G)) = \sum_i P_1(g_i) \log_{10}\left(\frac{P_1(g_i)}{P_2(g_i)}\right) \tag{12}$$

KL measures the expected logarithmic difference between the distributions, highlighting deviations that occur frequently in P_1. It is zero when the distributions are identical, indicating that there is no evidence of impact. The asymmetry of D_{KL} suggests analyzing the reverse divergence:

$$\overline{KL} \equiv D_{KL}(P_2(G) \| P_1(G)) = \sum_i P_2(g_i) \log_{10}\left(\frac{P_2(g_i)}{P_1(g_i)}\right) \tag{13}$$

This simplifies to a sum of individual marker contributions under the assumption of independence. Metrics are expressed in dits (decimal digits), directly applying the base 10 logarithm.

Using Mispitools

In this section, we first summarize the main functions and data structures present in **Mispitools** R Package. Then, two examples of missing person search are analyzed. The purpose of these examples is to show how **Mispitools** can be used to assist in the decision making in complex large-scale kinship testing cases.

Overview of R package Mispitools

Here are some functions and their descriptions at a glance. First, functions for simulating likelihood ratios are presented.

- *simLRgen*: Calculates likelihoods ratios (LRs) based on genetic simulations. It is a function for obtaining expected LR values considering H_1 or H_2 as true.
- *LRsex*: Calculates LRs based on biological sex simulations. It allows for obtaining expected LR values considering H_1 or H_2 as true.
- *LRcol*: Calculates LRs based on pigmentation color (one-variable model) simulations. It allows for obtaining expected LR values under H_1 and H_2.
- *LRage*: Calculates LRs based on age simulations. It allows for obtaining expected LR values under H_1 and H_2.
- *combLR*: Combines LRs from different variables simulated under the indicated scenarios.
- *compute_LR_colors*: Computes LR distribution for all combinations of multiple pigmentation variables.
- *LRcols*: Calculates LRs based on multiple pigmentation color simulations. It allows for obtaining expected LR values under H_1 and H_2.

Other functions allow for simulating missing person search databases with both PIE and FDE.

- *makePOIgen*: Generates a genetic database for UPs. It samples genotypes from the allele frequency database.
- *makePOIprelim*: Produces preliminary investigation data for UPs. Different database models are available for different missing person search scenarios.
- *makeMPprelim*: Produces preliminary investigation data for MPs. Different database models are available for different missing person search scenarios.

Some functions allow for performance computation and LR threshold selection and performance metrics.

- *Trates*: Calculates error rates and accuracy for specific thresholds. It uses as input the simulated likelihood ratio distributions.
- *DeT*: Calculates the optimal threshold using the DT approach. It requires weights as input.
- *bidirectionalKL*: Kullback-Leibler Divergence Calculation for Genetic Markers. Calculates KL using two allele frequency databases.
- *klPIE*: Computes the Kullback-Leibler Divergence between H_1 and H_2 PIE likelihood matrices.

The functions presented below aim to provide graphical utilities.

- *LRdist*: Calculates the likelihood ratio based on PIE. Different models are available for different variables.
- *CondPlot*: Generates a general plot for conditioned probabilities and LR combining non-genetic variables.
- *deplot*: Displays the decision plot showing false negative and false positive rates for each LR threshold. It is an interactive chart.
- *mispiApp*: Launches a Shiny app that implements some of the core functionalities of **Mispitools**, providing a user-friendly interface.

In addition, a set of DNA databases from various countries around the world are integrated. A specialized function is implemented to manage database formats.

- *Allele frequency databases*: **Mispitools** provides a set of short tandem repeat (STR) allele frequency databases from different countries around the world. Some of these are: Argentina, China, USA, Bosnia and Herzegovina, and others.
- *getFreqs*: Allows for the use of allele frequency databases for genetic simulation. It adapts the database format.

Example 1. How to establish an LR threshold for each pedigree in missing person cases?

This first example aims to show how it is possible to establish an LR threshold in the DNA database search when it is hampered by low statistical power. Consider the balance between false positive and false negative rates, obtained from computational simulations. Firstly, the **mispitools** package must be installed:

```
install.packages("mispitools")
library(mispitools)
library(pedtools)
library(forrel)
```

Then, STRs allele frequency databases are incorporated. Also, the pedigree information is read. For pedigree construction, **pedtools** package is used. It can read .fam and .ped formats with genetic information, and also define genotypes to the members from command line. In this example, we assign genotypes to specific members in order to have reproducibility. The command for this task is presented below:

```
set.seed(1234)
f <-getfreqs(Argentina)
ped1 <-linearPed(3)
ped1 <-setMarkers(ped1,locusAttributes = f)
ped1 <-profileSim(ped1,N = 1,ids = c(2,4))
ped2 <-cousinPed(1)
ped2 <-setMarkers(ped2,locusAttributes = f)
ped2 <-profileSim(ped2,N = 1,ids = 8)
datasimx = simLRgen(ped1,missing = 7,numsims = 500,seed = 1234)
datasimy = simLRgen(ped2,missing = 7,numsims = 500,seed = 1234)
```

In the first line, the STRs allele frequency database from Argentina is loaded, with 23 STR markers. Then a two-generation pedigree structure is generated using the `profileSim` function. Genotypes of members of the pedigree are generated. In one case, for pedigree 1, IDs 2 (great grandmother) and 4 (grandmother) are the genotyped members. In the other case, for pedigree 2, the genotype for 8 (cousin) is defined with `profileSim`. Pedigrees can be plotted as follows:

```
plot(ped1,hatched = typedMembers(ped1))
plot(ped2,hatched = typedMembers(ped2))
```

Figure 2: Pedigrees 1 and 2. Genotyped relatives of MP are dashed. Missing persons are in red. Id number for members is denoted.

SimLRgen allows obtaining LR values considering available genetic data in the pedigree. In this particular case, 500 genotypes for the UP are simulated considering that UP is the MP, with H_1 as true. This means that genotypes compatible with available genotyped members in each pedigree are simulated. Additionally, 500 genotypes for the UP considering H_2 as true are simulated. This is obtained from random sampling using the allele frequency database. For each UP genotype, the LR is computed. Therefore, 500 LR values considering H_1 and 500 more considering H_2 as true are obtained. These data are stored in a data frame. In the next steps, this information will be used for performance metrics.

```
LRdist(datasimx)
```

```
deplot(datasimx)
LRdist(datasimy)
deplot(datasimy)
```

LRdist plot the Log_{10} distributions when H1 or H2 is true. Deplot allows looking for false positive and false negative rates for each LR threshold from 1 to 10.000.

Figure 3: Log10(LR) distributions (left). Decision plots (right) indicate FPR and FNR for each T from 1 to 10.00. A. Present results for Ped 1, B. Corresponds to Ped 2.

At this point, there are some clues for evaluating the statistical power of the pedigrees and rationally choosing an LR threshold based on error rates. However, some metrics could be computed to take a more precise decision:

```
DeT(datasimx, weight = 10)
"Decision threshold is: 4"

Trates(datasimx, threshold = 4)
"FNR = 0.088 ;  FPR = 0.01 ;  MCC = 0.904756468160616"

DeT(datasimy, weight = 10)
"Decision threshold is: 5"

Trates(datasimy, threshold = 5)
 "FNR = 0.572 ;  FPR = 0.03 ;  MCC = 0.473596131451164"
```

DT computes the decision threshold based on the approach described previously (Eq. 10). It takes into account the balance between FPR and FNR. Trates specifies some metrics for the indicated threshold, such as error rates and Matthews correlation coefficient (MCC). The results show that Pedigree 1, as expected, has better performance due to having more and closer relatives to the MP. However, $FPR = 0.01$ can be unmanageable in large databases. For example, analyzing 30,000 individuals could lead to 300 potential matches. Here, other information must be collected to prioritize the cases in which further genetic analyses can be performed to arrive at a conclusion.

This simple example shows how **mispitools** can be used in missing person search cases not only to compute the expected LR values considering H_1 and H_2, but also to provide a method to select an LR threshold. In this case, only genetic data are considered; in the following, we introduce one of the core functionalities in **mispitools**, which is its ability to compute and combine LRs from different lines of evidence.

Example 2. Combining genetic with preliminary investigation-based LRs

In this example, we will introduce the LR calculation for PIE and show how, combined with DNA-based LRs, search performance metrics can be improved. The first case considers only conditionally independent PIE variables. First, we generate the reference population data with the following command:

```
POP1 <- CPT_POP(propS = c(0.5, 0.5),
                MPa = 40,
                MPr = 6,
                propC = c(0.3, 0.2, 0.25, 0.15, 0.1))
```

The parameter `propS` is used to indicate the proportion of biological sex, female or male. Here, we select a uniform distribution for our reference population. `MPa` and `MPr` are the age of the MP and the error range, respectively, so the age of the MP is defined between [MPa - MPr ; MPa + MPr]. Note that in this case, MP values are important for defining the population reference distribution because they are used to compute the proportion of individuals that fall within the MP's age range and those that are outside it. The age distribution model for the reference population is uniform in this case, for simplicity, but it can be manually customized. Finally, `propC` indicates the proportion of one pigmentation trait (single model, without considering the dependency between multiple traits). The output of this function, stored in `POP1`, is the following:

```
POP1

        [,1]   [,2]    [,3]    [,4]    [,5]
 F-T1 0.0225 0.015 0.01875 0.01125 0.0075
 F-T0 0.1275 0.085 0.10625 0.06375 0.0425
 M-T1 0.0225 0.015 0.01875 0.01125 0.0075
 M-T0 0.1275 0.085 0.10625 0.06375 0.0425
```

The matrix obtained represents the probabilities of the phenotypes in the reference population and therefore the probability considering H_2, $P(D|H_2)$, for each specific combination of characteristics. F-T1 represents a woman whose age is matched with the age of MP. F-T0 represents a woman with a mismatch in age with MP. M-T1 and M-T0 correspond to the same age categories in association with male. The numbers (columns) represent different hair colors.

To obtain the conditioned probabilities of the phenotypes considering H_1 as true ($P(D|H_1)$), we can use the following command:

```
MP1 <- CPT_MP(MPs = "F", MPc = 1,
              eps = 0.05, epa = 0.05,
              epc = Cmodel())
```

The parameters `MPs` and `MPc` indicate the biological sex and the pigmentation trait color (in this case hair), for MP. On the other hand, `eps`, `epa` and `epc` are the error rates. For `epc`, a function named `Cmodel` is used to define specific error rates for each pair of colors. In this case, default values are used, but they can be customized as indicated in the documentation. The output, stored in `MP1`, is the following:

```
MP1

               1            2            3            4            5
 F-T1 0.877918288 8.779183e-03 4.389591e-03 8.779183e-03 2.633755e-03
 F-T0 0.046206226 4.620623e-04 2.310311e-04 4.620623e-04 1.386187e-04
 M-T1 0.046206226 4.620623e-04 2.310311e-04 4.620623e-04 1.386187e-04
 M-T0 0.002431907 2.431907e-05 1.215953e-05 2.431907e-05 7.295720e-06
```

At this point, for each combination of preliminary investigation variables, we have the likelihoods of H_1 and H_2. Therefore, LR can be easily computed as following:

```
MP1/POP1
```

Obtaining the following output:

```
             1            2            3            4            5
F-T1 39.01859058 0.5852788586 0.2341115435 0.7803718115 0.351167315
F-T0  0.36240177 0.0054360266 0.0021744106 0.0072480354 0.003261616
M-T1  2.05361003 0.0308041505 0.0123216602 0.0410722006 0.018482490
M-T0  0.01907378 0.0002861067 0.0001144427 0.0003814755 0.000171664
```

This indicates the LR values for each combination of characteristics, considering the MP and reference population data. With these tables, each UP can be easily evaluated. For example, if we have a UP with the same characteristics as the MP (hair color = 1, female, and within the age range), we would obtain LR = 39. If we have a UP with the same hair color and age range but a different sex, the LR would be around 2. If we have a complete mismatch in the characteristics, for example, hair color = 5, outside the age range, and female, the LR would drastically fall to 0.00017.

The package **mispitools** also provides a customized plotting function to visualize likelihoods and LRs.

```
CondPlot(MP1,POP1)
```

The following plot is obtained:

Figure 4: Log10(LR) distributions for pedigree 1 (upper, left) and pedigree 2 (upper, right). Decision plots (right) indicate FPR and FNR for each T from 1 to 10.000.

These tables are useful for several applications. On one hand, they allow us to know the expected values when we face a case where UP is MP. Also, if we consider Figure 4A, we can obtain the probabilities of each phenotype when H_2 is true. If we combine these probabilities with the LR values for each characteristic (Figure 4C), we can obtain the probability distribution of LR given H_2, $P(LR|H_2)$. In the same way, if we use Figure 4B, we can obtain $P(LR|H_1)$. This approach can be used to perform computational simulations and also to measure the statistical power. In fact, to directly measure the content of the information provided by the MP and reference population data, we can compute, through the klPIE function, the Kullback-Leibler divergence between $P(D|H_2)$ and $P(D|H_1)$.

```
klPIE(POP1, MP1)
```

In this case, we obtain:

$$D_{KL}(P_{H_2}||P_{H_1}) = 2.155$$
$$D_{KL}(P_{H_1}||P_{H_2}) = 1.374$$

The direct interpretation of the *KL* divergence in this context is: for $D_{KL}(P_{H_1}||P_{H_2})$, the $Log_{10}(LR)$ is expected when H_1 is true; and for $D_{KL}(P_{H_1}||P_{H_2})$, the $Log_{10}(LR^{-1})$ is expected when H_2 is true. Therefore, having higher *KL* values in both directions implies an increasing difference between the mean $Log_{10}(LR)$ values expected, lower for H_2 and higher for H_1.

In this sense, forensic professionals might be tempted to explore different values for both parameters and characteristics and study how they affect performance. For this reason, **mispitools** incorporates a user-friendly interface that allows them to interactively change the values and analyze the tables present in Figure 4. To launch the interface, the following command must be executed:

```
mispiApp()
```

Moreover, as previously mentioned, conditional probability tables can be used to perform simulations of expected LR distributions considering H_1 and H_2 as true. Assuming mutual independence between DNA STR markers, sex, age, and hair color, the LRs can be combined given that the same hypotheses are tested. LR simulations can be performed with the following command:

Figure 5: Screenshot of mispiApp, showing the sidebar with the options for the different parameters and the likelihoods and LR distribution tables. Iteratively, the user can change parameters and analyze how the likelihoods and LR change.

```
sex_H1 <- LRsex("F", H = 1, LR = TRUE, seed = 123, nsims = 500)
sex_H2 <- LRsex("F", H = 2, LR = TRUE, seed = 123, nsims = 500)
col_H1 <- LRcol(1, H = 1, LR = TRUE, seed = 123, nsims = 500)
col_H2 <- LRcol(1, H = 2, LR = TRUE, seed = 123, nsims = 500)
age_H1 <- LRage(40, H = 1, LR = TRUE, seed = 123, nsims = 500)
age_H2 <- LRage(40, H = 2, LR = TRUE, seed = 123, nsims = 500)
```

Once simulated, we can combine the LRs obtained from the PIE with those calculated in the previous example (only FDE). In order to simplify the example, we will assume that MP in Ped1 and MP in Ped2 share the same characteristics, and the reference population is the same, therefore the same non-genetic LR distribution can be used with both examples. That is, we can compute the combined LRs as follows:

```
datasimx2 <- simLR2dataframe(datasimx)
combinedx_H1 <- datasimx2$Related * sex_H1$LRs * col_H1$LRc * age_H1$LRa
combinedx_H2 <- datasimx2$Unrelated * sex_H2$LRs * col_H2$LRc * age_H2$LRa
combined_datasimx <- as.data.frame(cbind(combinedx_H2, combinedx_H1))
names(combined_datasimx) <- c("Unrelated", "Related")
combined_datasimx
```

```
     Unrelated       Related
  8.109142e-04 142668.8035
  5.033040e-07   3739.3775
  1.322667e-11   2774.3613
  3.567114e-06  92513.6636
  5.578832e-06    361.9391
  1.631195e+00  22997.6685
```

For Ped2, we will proceed in a similar way:

```
datasimy2 <- simLR2dataframe(datasimy)
combinedy_H1 <- datasimy2$Related * sex_H1$LRs * col_H1$LRc * age_H1$LRa
combinedy_H2 <- datasimy2$Unrelated * sex_H2$LRs * col_H2$LRc * age_H2$LRa
combined_datasimy <- as.data.frame(cbind(combinedy_H2, combinedy_H1))
names(combined_datasimy) <- c("Unrelated", "Related")
combined_datasimy
```

```
    Unrelated      Related
 1.188810e-02 672.604173
 1.171118e-03    6.638100
 9.179705e-05    8.274109
 7.344176e-03   35.083415
 4.571806e-03   88.665734
 8.449938e-02    4.778942
```

After combining the LRs, we can use the `combined_datasimx` and `combined_datasimy` as we did in the previous example with `datasimx` and `datasimy`. This means that we can plot the LR distributions, error rates per threshold, and DT. For comparative purposes, we will show the results of the performance analyzes and DT selection:

```
DeT(combined_datasimx, 10)
"Decision threshold is: 3"
Trates(combined_datasimx, 3)
"FNR = 0.04 ;  FPR = 0 ;  MCC = 0.960768922830523"

DeT(combined_datasimy, 10)
"Decision threshold is: 6"
Trates(combined_datasimy, 6)
[1] "FNR = 0.048 ;  FPR = 0 ;  MCC = 0.953098602750463"
```

It can be demonstrated how adding LRs based on non-genetic information results in a performance improvement. Finally, if we have multiple pigmentation traits, we can use the model that takes into account the conditional dependency between them. This implies having parameters and population data for all three variables: hair, eye, and skin color. This can be evaluated with the following function:

```
data <- simRef()
conditioned <- conditionedProp(data, 1, 1, 1, 0.01, 0.01, 0.01)
unconditioned <- refProp(data)
likelihoods <- compute_LRs_colors(conditioned, unconditioned)
LRcols <- LRcolors(likelihoods)

    Unrelated      Related
 8.345434e-04 40.4032073
 4.040321e+01  1.7348387
 4.165279e-05  0.8674194
 4.040321e+01 40.4032073
 1.387871e+00 40.4032073
 4.081974e-01  0.1309312
```

These values can substitute the LR based on a unique color, such as the following:

```
datasimx2 <- simLR2dataframe(datasimx)
combinedx_H1 <- datasimx2$Related * sex_H1$LRs * LRcols$Related * age_H1$LRa
combinedx_H2 <- datasimx2$Unrelated * sex_H2$LRs * LRcols$Unrelated * age_H2$LRa
combined_datasimx2 <- as.data.frame(cbind(combinedx_H2, combinedx_H1))
names(combined_datasimx2) <- c("Unrelated", "Related")
combined_datasimx2

    Unrelated      Related
 2.087076e-07 1777703.1042
 3.135672e-04    2000.6577
 2.831768e-14     742.1753
 2.222374e-03 1152752.5498
 2.653165e-04    4509.8880
 2.053480e-01     928.6272
```

Given these values, we can compute the DT and performance, now considering both PIE and FDE.

```
DeT(combined_datasimx2, 10)
"Decision threshold is: 3"

Trates(combined_datasimx2, 3)
"FNR = 0.02 ;  FPR = 0 ;  MCC = 0.980196058819607"
```

Here we can analyze and quantify the improvement in the search performance of adding PIE based LRs.

Summary

This paper introduces an R package of missing person search statistical tools named **mispitools**. The package is available on the Comprehensive R Archive Network (CRAN) at http://CRAN.R-project.org/package=mispitools. It contains functions to calculate likelihood ratios (LRs) based on genetic (FDE) or preliminary investigation data (PIE). In addition, it can perform simulations of the databases for the search of missing persons. This package implements previously developed methodologies for likelihood ratio threshold, error rates, and MCC coefficient estimations. It also incorporates new functions, allowing the methodologies to be combined. The functions are described and implemented using two examples. Through these examples, we show that the incorporation of likelihood ratios based on non-genetic data can be useful in large-scale missing person searches, especially when hindered by low statistical power.

Acknowledgements

The development of these methods has been greatly influenced by extensive discussions with colleagues and professionals in forensic investigations. We particularly acknowledge Thore Egeland and Magnus Vigeland for their insightful discussions and contributions to open-source forensic packages, which are integral to this work. We are also deeply grateful to Inés Caridi and Ariel Salgado for their invaluable input, which significantly improved the conceptual and practical aspects of the methods. Furthermore, we extend our thanks to all contributors who provided suggestions and pull requests to the open source **mispitools** project, with special recognition given to Martin Amigo, Alina Hordiienko, Yike Cheng, Ozcan Mirray and Maja Ostrowska.

Bibliography

L. Calla, C. Bohun, and H. LeBlanc. Advancing the forensic estimation of time since death. *Pure and Applied Geophysics*, 178(3):705–715, 2021. [p1]

I. Caridi, C. O. Dorso, P. Gallo, and C. Somigliana. A framework to approach problems of forensic anthropology using complex networks. *Physica A: Statistical Mechanics and its Applications*, 390(9): 1662–1676, 2011. [p3]

I. Caridi, E. E. Alvarez, C. Somigliana, and M. S. Puerto. Using already-solved cases of a mass disaster event for prioritizing the search among remaining victims: a bayesian approach. *Scientific reports*, 10 (1):1–11, 2020. [p3]

A. Chernomoretz, F. Marsico, J. Iserte, M. H. Piñero, M. S. Escobar, M. Balparda, and G. Sibilla. Bayesian networks for dna-based kinship analysis: Functionality and validation of the genis missing person identification module. *Forensic Science International: Genetics Supplement Series*, 8:131–132, 2022. [p2]

E. Cunha, E. Baccino, L. Martrille, F. Ramsthaler, J. Prieto, Y. Schuliar, N. Lynnerup, and C. Cattaneo. The problem of aging human remains and living individuals: a review. *Forensic science international*, 193(1-3):1–13, 2009. [p4]

E. Dincelli, C. Van Slyke, and A. Yayla. Ethical hacking for a good cause: Finding missing people using crowdsourcing and open-source intelligence (osint) tools. *Communications of the Association for Information Systems*, 53(1):1052–1071, 2023. [p1]

R. C. Elston and J. Stewart. A general model for the genetic analysis of pedigree data. *Human heredity*, 21(6):523–542, 1971. [p2]

D. Kling, A. O. Tillmar, and T. Egeland. Familias 3–extensions and new functionality. *Forensic Science International: Genetics*, 13:121–127, 2014. [p2]

D. Kling, T. Egeland, M. H. Piñero, and M. D. Vigeland. Evaluating the statistical power of dna-based identification, exemplified by 'the missing grandchildren of argentina'. *Forensic Science International: Genetics*, 31:57–66, 2017. [p2, 5]

D. Kling, C. Phillips, D. Kennett, and A. Tillmar. Investigative genetic genealogy: Current methods, knowledge and practice. *Forensic Science International: Genetics*, 52:102474, 2021. [p1]

M. Kruijver, R. Meester, and K. Slooten. Optimal strategies for familial searching. *Forensic Science International: Genetics*, 13:90–103, 2014. [p1]

F. Marsico and T. Egeland. Likelihood ratios for physical traits in forensic investigations. *bioRxiv*, pages 2024–05, 2024. [p2]

F. Marsico, G. Sibilla, M. S. Escobar, and A. Chernomoretz. The missing person problem through the lens of information theory. *Forensic Science International: Genetics*, 70:103025, 2024. [p2, 4, 6]

F. L. Marsico and I. Caridi. Incorporating non-genetic evidence in large scale missing person searches: A general approach beyond filtering. *Forensic Science International: Genetics*, 66:102891, 2023. [p1, 2]

F. L. Marsico, M. D. Vigeland, T. Egeland, and M. H. Piñero. Making decisions in missing person identification cases with low statistical power. *Forensic science international: genetics*, 54:102519, 2021. [p1, 2, 5, 6]

M. S. Puerto, D. Abboud, J. P. Baraybar, A. Carracedo, S. Fonseca, W. Goodwin, P. Guyomarc'h, A. Jimenez, U. Krenzer, M. D. M. Mendez, et al. The search process: Integrating the investigation and identification of missing and unidentified persons. *Forensic Science International: Synergy*, 3: 100154, 2021. [p1]

D. Ramos, D. Meuwly, R. Haraksim, and C. E. Berger. Validation of forensic automatic likelihood ratio methods. In *Handbook of forensic statistics*, pages 143–162. Chapman and Hall/CRC, 2020. [p6]

J. P. Sinnwell, T. M. Therneau, and D. J. Schaid. The kinship2 r package for pedigree data. *Human heredity*, 78(2):91–93, 2014. [p2]

B. Vale, A. Orr, C. Elliott, and T. Stotesbury. Optical profilometry for forensic bloodstain imaging. *Microscopy Research and Technique*, 86(10):1401–1408, 2023. [p1]

A. Vidaki, D. Ballard, A. Aliferi, T. H. Miller, L. P. Barron, and D. S. Court. Dna methylation-based forensic age prediction using artificial neural networks and next generation sequencing. *Forensic Science International: Genetics*, 28:225–236, 2017. [p3, 4]

M. D. Vigeland. *Pedigree analysis in R*. Academic Press, 2021. [p2]

M. D. Vigeland, F. L. Marsico, M. H. Pinero, and T. Egeland. Prioritising family members for genotyping in missing person cases: a general approach combining the statistical power of exclusion and inclusion. *Forensic Science International: Genetics*, 49:102376, 2020. [p2, 5]

S. Walsh, F. Liu, A. Wollstein, L. Kovatsi, A. Ralf, A. Kosiniak-Kamysz, W. Branicki, and M. Kayser. The hirisplex system for simultaneous prediction of hair and eye colour from dna. *Forensic Science International: Genetics*, 7(1):98–115, 2013. [p4]

Marsico F. L.
University of Buenos Aires
Argentina franco.lmarsico@gmail.com