Boundaries in the eyes: measure event segmentation during naturalistic video watching using eye tracking

Jiashen Li [1,2], Zhengyue, Chen [1,2], Xin Hao [1,2*], Wei Liu [1,2*]

1. Key Laboratory of Adolescent Cyberpsychology and Behavior (CCNU), Ministry of Education, Wuhan, China

2. Key Laboratory of Human Development and Mental Health of Hubei Province, School of Psychology, Central China Normal University, Wuhan, China

Correspondence:

Dr. Xin Hao, School of Psychology, Central China Normal University

Address: the 8th floor, Nanhu Complex Building, No 152 Luoyu Road, Wuhan.

Postal Code: 430079

E-mail: psyhaoxin@ccnu.edu.cn

Dr. Wei Liu, School of Psychology, Central China Normal University

Address: the 8th floor, Nanhu Complex Building, No 152 Luoyu Road, Wuhan.

Postal Code: 430079

E-mail: weiliu1991@ccnu.edu.cn

Abstract

During naturalistic information processing, individuals spontaneously segment their continuous experiences into discrete events, a phenomenon known as event segmentation. Traditional methods for assessing this process, which include subjective reports and neuroimaging techniques, often disrupt real-time segmentation or are costly and time intensive. Our study investigated the potential of measuring event segmentation by recording and analyzing eye movements while participants view naturalistic videos. We collected eye movement data from healthy young adults as they watched commercial films (N=104), or online Science, Technology, Engineering, and Mathematics (STEM) educational courses (N=44). We analyzed changes in *pupil size* and *eye movement speed* near event boundaries and employed *inter-subject correlation analysis* (ISC) and *hidden Markov models* (HMM) to identify patterns indicative of event segmentation. We observed that both the speed of eye movements and pupil size dynamically responded to event boundaries, exhibiting heightened sensitivity to high-strength boundaries. Our analyses further revealed that event boundaries synchronized eye movements across participants. These boundaries, can be effectively identified by HMM, yielded higher within-event similarity values and aligned with human-annotated boundaries. Importantly, HMM-based event segmentation metrics responded to experimental manipulations and predicted learning outcomes. This study provided a comprehensive computational framework for measuring event segmentation using eye-tracking. With the widespread accessibility of low-cost eye-tracking devices, the ability to measure event segmentation from eye movement data promises to deepen our understanding of this process in diverse real-world settings.

Keywords: event segmentation; naturalistic information processing; eye tracking; inter-subject correlation analysis; hidden Markov model

1. Introduction

In fields such as cognitive psychology and neuroscience (including both human and animal subjects), experiments are commonly conducted on a trial-by-trial basis. However, our everyday life requires the processing of continuous information: we spontaneously segment continuous information into smaller units (i.e., event segmentation[1–4]). Recently, there has been a growing interest among researchers in investigating cognitive processing during the continuous intake of information, such as watching movies[5], sports[6] or listening to audiobooks[7] and speech[8]. This focus is primarily due to the crucial role that event segmentation in continuous information processing plays in bridging perception and memory[9–11]. However, isolating and measuring event segmentation presents challenges given its simultaneous occurrence with various cognitive processes such as perception, attention, language understanding, and memory formation. In this study, we investigated whether human eye movements during continuous information processing, specifically during naturalistic video viewing, can serve as a novel signature for event segmentation.

Traditional methods of studying event segmentation, while informative, have their limitations. One common method to study event segmentation requires participants to mark event boundaries either during movie watching or retrospectively[12]. Despite its frequent use in prior studies[13–15], this method has limitations: marking boundaries in real-time may interfere with the ongoing segmentation process, and retrospective reporting may not accurately reflect immediate responses. An alternate behavioral approach employs an independent cohort to determine event boundaries, which are then used to analyze another group's data[10,16–18]. Nonetheless, individual performance on the segmentation task can vary significantly,

potentially reflecting either true individual differences in segmentation or unaccounted systematic variances between groups[19]. Shifting focus to neural methods, researchers anticipate that neural activity may offer objective markers of event segmentation. Univariate analyses revealed that hippocampal activity increases near event boundaries during continuous experiences[10,20–22]. Furthermore, multivariate analyses demonstrated that hippocampal and medial prefrontal regions form distinct event representations at these boundaries[9]. These representational changes can be effectively captured using data-driven machine learning approaches[10]. Nevertheless, the identification of neural-based event segmentation signatures still relies on predefined 'ground truth' event boundaries, which remain contentious at the behavioral level for the reasons we discussed above. Moreover, neuroimaging is expensive and logistically complex to collect, particularly among special populations such as psychiatric patients, infants, and older adults. To further validate the correspondence between event segmentation at the self-report and neural levels, and to facilitate large-scale data collection across varied populations, it is crucial to identify an easily measurable signature of event segmentation that can be concurrently assessed alongside behavioral and neural responses.

In this study, we investigated an alternative method, notably eye tracking, to measure event segmentation during naturalistic video viewing, extending beyond conventional self-report[23] and neural approach[10,24]. Besides neural activity, previous studies already showed that continuous information processing can modulate various biological measures in humans, such as synchronizing heart rates across individuals[25], but we selected the eye-tracking as our candidate measure for three reasons. First, eye tracking is capable of recording eye movements and pupil responses at the speed of cognition and neural activity[26], and has been extensively

used in research involving complex visual stimuli such as user interfaces[27], advertising[28], and education[29]. Secondly, eye movement methods have been successfully combined with cognitive neuroscience techniques including fMRI, single-unit recording, and magnetoencephalography, allowing for more sophisticated investigations into memory that correlate discrete neural, memory, and eye movement events at fine temporal scale[30]. Lastly, in a sequence-learning task, Clewett and colleagues demonstrated that pupil dilation tracks changes in event structure [31]. Although this study did not use naturalistic videos but rather simple pictures and sounds to establish event structure, it highlights the potential of eye tracking to monitor complex event segmentation during naturalistic video viewing. Importantly, in Clewett's research, due to the use of simple pictures as stimuli, only pupil responses were analyzed as signals of event segmentation. In our study, we concurrently consider pupil size and eye movement patterns including both their speed and trajectory.

In the analysis of pupil responses and eye movements elicited by naturalistic videos, our goal was to identify a signature of event segmentation using eye-tracking data. To this end, we went beyond the standard metrics of pupil diameter and movement speed, incorporating two advanced computational methods from neuroimaging into our eye-tracking analysis. The first method is the Hidden Markov Model (HMM)[32], a recently introduced data-driven event segmentation model that was initially tested on fMRI data[10] and later confirmed using EEG data[33]. The underlying assumption of the HMM is that discrete event representations can be treated as hidden states during the processing of a continuous narrative stimulus, where each event possesses a distinct signature that persists for the duration of the event. By fitting the HMM to eye-tracking data, which encompasses time series for pupil size and the x and y

coordinates of fixation points, we can ascertain the optimal number of events as generated by the model, the characteristic eye-tracking pattern for each event, and the precise moments of event transitions. Subsequent studies have demonstrated that the HMM-based event segmentation model is sensitive to population characteristics, such as developmental changes[34] and infant behaviors[35], as well as experimental manipulations, including anticipation[36] and schema[37]. The second approach is the inter-subject correlation analysis (ISC)[38], which quantifies the consistency of neural and biological responses among subjects. ISC was initially conceived to assess the correlation of fMRI responses to identical movie[5] and robust correlations have since been observed across different data types, such as electroencephalogram (EEG)[39], magnetoencephalography (MEG)[40], functional near-infrared spectroscopy (fNIRS)[41], heart rate[25], and eye movement[29]. Notably, studies have revealed that the degree of shared responses correlates positively with subsequent memory performance[29,42,43]. We proposed and tested the hypothesis that event boundaries can synchronize eye movements across participants. Consequently, ISC near these boundaries may serve as a distinctive signature for event segmentation.

To overcome the inherent limitations of self-report and neural measures of event segmentation, this study systematically investigated the efficacy of eye-tracking-based metrics in quantifying event segmentation (**Figure 1**). We analyzed eye movement data from participants viewing two types of continuous naturalistic videos (i.e., commercial films, N=104 and STEM educational content, N=45). This design offers replication across two datasets and provide initial generalizability tests for different video types. First, we investigated the potential of both straightforward metrics (i.e., *pupil size* and *speed of moving*) and sophisticated

computational techniques (i.e., *ISC*[38] *and HMM*[32]), to measure the event segmentation process. Specifically, we examined changes in these metrics before, during and after event boundaries and the correspondence of ISC and HMM-generated boundaries with human-annotated boundaries. Second, we explored how agreement on boundary locations among participants—termed boundary strength—affects these segmentation metrics. Third, recognizing the critical role of event segmentation in memory encoding, we investigated the influence of experimental manipulations on these indicators and their predictive power for subsequent memory performance. Ultimately, our goal was to identify an optimal eye-tracking signature for event segmentation that (1) is responsive to human-annotated boundaries, (2) sensitive to boundary strength and (3) experimental manipulation, (4) predictive of memory outcomes, and (5) generalizable across various naturalistic video stimuli.

Figure1 Analyzed Eye-Tracking Datasets, Candidate Metrics, and Analyses to Test the Relevance of Certain Metrics for Event Segmentation. We analyzed eye movement data from healthy participants (N=133) viewing either a commercial film, "*Sherlock Season 1, Episode 1*," or an online educational clip, "*Introduction to Statistics* (Left Panel)." We examined the response of four eye-tracking-based metrics to event boundaries: pupil size, movement speed, Inter-Subject Correlation analysis (ISC), and Hidden Markov Model (HMM) (Middle Panel). For each metric in each dataset, we posed four questions to identify the optimal eye-tracking signature for event segmentation (Right Panel): (1) Is the metric responsive to human-annotated boundaries? (2) Is it sensitive to boundary strength? (3) Is it affected by experimental manipulation? (4) Is it predictive of memory outcomes?

2. Methods

2.1 Participants

Commercial Movie Dataset

A total of 112 right-handed, healthy university students (64 females, 40 males; age: (M = 20.54) years, (SD = 2.04)) participated in this study. All participants had normal or corrected-to-normal vision, no hearing impairments, scores below 11 on the Beck Depression Inventory (BDI), indicating no current depression, and no history of neurological or psychiatric disorders. Furthermore, they confirmed having no prior exposure to the movie clip (i.e., Sherlock Season 1 Episode 1 "A Study in Pink") used in this study. Recruitment was conducted via advertisements, and participants received compensation for their involvement. All participants provided written informed consent before the start of experimental procedure.

From the initial sample, eight subjects were excluded from the analysis due to six instances of data extraction failure and two programming errors, resulting in a final sample size of 104. Participants were randomly assigned to one of four groups to undergo different experimental manipulations (for details, see the experimental design section). Prior to viewing the film, the group assignments in the final sample were as follows: Short-R Group (N=30; 11 males, mean age = 20.32 years, SD = 2.08); Short-P Group (N=23; 8 males, mean age = 20.98 years, SD = 1.99); Long Group (N=25; 9 males, mean age = 20.18 years, SD = 2.11); and Schema Group (N=26; 12 males, mean age = 20.77 years, SD = 1.96). There were no significant differences among the groups in terms of age (F=0.57, p=0.63) or gender (χ^2=0.88, p=0.82).

Notably, all participants viewed the same movie clip, and their eye movements were recorded using the same eye-tracking device. We aggregated the data to examine the general

event segmentation process and conducted between-group analyses to understand how experimental manipulations affect event segmentation signatures. Experimental procedures were approved by the University Institutional Review Board for Human Subjects.

STEM Course Dataset

A total of 45 right-handed, healthy university students participated in this component of the study. All participants had normal or corrected-to-normal vision, no hearing impairments, and no history of neurological or psychiatric disorders. Participants watched a self-produced lecture tailored for STEM courses (i.e., Statistics) while their eye movements were tracked. Following the standard protocol, a subset of participants (N=11) was tasked with identifying and reporting event boundaries in the video. Additionally, an independent group of participants (N=15) viewed the video without undergoing memory tests or eye tracking. In total, data on eye-tracking and subsequent memory performance were collected from 29 participants, and 26 participants provided feedback on event boundaries. All participants affirmed they had not previously seen or learned the course material (i.e., Introduction to Statistics) in any format. Recruitment was executed through advertisements, with participants being compensated for their involvement. Experimental procedures were approved by the University Institutional Review Board for Human Subjects. All subjects provided written informed consent before the start of experimental procedure.

Sample Size Justification

As the first computational investigation to identify eye-tracking signatures for event segmentation during naturistic video viewing, precise effect size estimation prior to data collection was unfeasible. Our sample size was informed by prior studies on event boundaries,

typically involving 20-30 participants and incorporating additional methodologies such as EEG and fMRI. A closely related study, which used pupil size to track event structures[31], involved 34 participants and estimated a requirement of 25 participants to detect a large effect size (d=0.8) with an α of 0.05 and a power of 0.80. For each experimental group in our study, we aimed to collected at least 25 usable participants with complete memory and eye movement records. All our main and subgroup analyses involved more than 25 participants, except for the Short-P group, which included 23 participants following quality control procedures.

2.2   Materials and Design

2.2.1 Commercial Movie Dataset

Experimental design

The experimental protocol was structured into three phases: the manipulation phase, the main video-watching phase, and the free recall phase. Initially, participants were instructed to watch approximately 45 minutes of video content attentively, with the objective of remembering the content for a subsequent memory test.

During the manipulation phase, the objective was to modulate the event segmentation process for the ensuing video-watching phase. In the Short-Random (R) group, participants watched 400 TikTok clips encompassing a variety of themes—humans, animals, objects, and scenes—with each category consisting of 100 clips. These clips, ranging from 1 to 5 seconds in duration, were pre-selected and sourced from a generic account to mitigate biases from the personalized recommendation algorithm. Conversely, participants in the Short-Personalized (P) group watched clips from their own accounts, suggested by personalized recommendation

algorithms. The number of clips was not fixed, but the total viewing duration was maintained at 20 minutes, consistent with other groups. Additionally, the Long group viewed a 20-minute segment of the documentary "BBC Ocean," and the Schema group watched a distinct 20-minute segment from the "Sherlock" film, which preceded the storyline of the main video content.

During the main viewing phase, all participants, regardless of group assignment, watched a 25-minute segment of "BBC Sherlock." This choice was informed by its prevalent use in prior event segmentation research, known to elicit distinct event-specific neural representations, as evidenced by EEG and fMRI studies[9,10,18,33].

Following the main video-watching phase, during the free recall phase, participants were asked to provide a detailed verbal recount of the content viewed during the main phase, focusing on the richness of detail. Although the manipulation phase content was not directly assessed, participants were informed it would be tested to ensure sustained attention to the materials throughout the experiment. Video presentations during both phases were managed using Experiment Builder software (SR Research), and participants' responses were initially recorded on smartphones before being transcribed for further memory analyses.

Human-labelled event boundaries and memory measures

We used the video stimuli from "Sherlock Season 1 Episode 1 'A Study in Pink'", which has been previously used in event segmentation studies[9,10,18], thereby we do not need to generate new event boundaries. Instead, we adopted the event boundaries delineated by Chen[18], encompassing 20 events within a 25-minute segment (i.e., 19 boundary locations). The audio recordings from the free recall phase were transcribed verbatim and subsequently assessed by

two independent raters. Each participant's recall was evaluated across three dimensions: (1) remember score: the quantity of events a participant could recall, (2) detail score: the comprehensiveness of details recalled for any given event, and (3) order: the accuracy of the event order recalled by the participant. Since order memory was not the primary focus of our study, remember and detail scores served as the principal metrics for memory performance, correlating with the eye-tracking-based event segmentation indexes. Initially, raters independently reviewed free recall responses. Discrepancies in their assessments, such as divergent event recollections or detail scores for the same event, were subsequently reconciled through discussion, culminating in a consensus that informed our subsequent data analysis.

2.2.2 STEM Course Dataset

Experimental design

The experimental protocol included both studying and testing phase. Before the beginning of the study phase, participants were briefed to watch the STEM learning material, specifically an introduction to statistics covering topics such as variables, constants, measuring scales, and the one-sample Z-test, under eye movement monitoring in anticipation of an immediate memory test thereafter. This STEM learning video, crafted by our lab members, lasts 12 minutes and 54 seconds. The presentation of the video during the studying phase was managed by the Experiment Builder (SR Research). Following the video, the testing phase evaluated participants' learning and memory across three dimensions (See details below). Notably, the 'remember score' and 'test score' from the memory tests served as the primary metrics for assessing video learning and correlated with eye-tracking data.

Human-labelled event boundaries and memory measures

To generate human-annotated event boundaries for this video, we recruited a sample of 26 participants who were tasked with identifying event boundaries and reporting them in minutes and seconds. Notably, boundary responses within a 3-second window were considered identical. It was generally observed that participants shared a consistent evaluation of event boundaries. Consequently, we selected 11 event boundaries corresponding to 12 distinct events for our main analyses based on the number of concepts taught in the video. This decision was made by the experimenters who prepared the course and slides. Additionally, we developed an index for each boundary, named "*boundary strength*," to quantify the consensus on segmentation among participants. Event boundaries were categorized into three levels based on the degree of agreement: high strength (17 to 26 participants concurred), middle strength (2 to 16 participants concurred), and low strength (marked by only one participant). Each category included an equal number of eight boundaries to ensure comparable statistical power in subsequent analyses.

For the memory measure, all participant finished following memory tasks: (1) Image Recognition Task: Participants determined whether displayed images had appeared in the video amidst interference from similar internet-sourced images. This task's performance was not analyzed in this study. (2) Free Recall Task: Participants wrote down key video points on a blank sheet. Performance was quantified as a 'remember score'. (3) Exam-like Memory Recall Task: Comprising retention and transfer tests, the retention test assessed direct recall of video content, while the transfer test measured comprehension through the application of learned concepts. Test items were derived from actual statistical exams to bolster ecological validity. The 'test score' quantified performance.

2.3 Eye-tracking data acquisition

Participants in both the *Commercial Movie Dataset* and *STEM Course Dataset* were seated in the same room, with videos displayed on an identical monitor and eye movements tracked using the same device. To reduce the impact of lighting conditions on pupil size, the experimental room was shielded from outdoor sunlight with curtains, ensuring consistent luminance provided by indoor lighting regardless of the time of day. Eye movements were precisely monitored using a table-mounted, video-based EyeLink 1000 system (SR Research Ltd., Mississauga, Ontario, Canada) at a sampling rate of 1000 Hz, employing a 35-mm lens. Participants' head movements were restricted throughout the experiment by a SR Research head and chin rest. Participants were informed about the eye movement calibration adjustment process and the setup of the eye tracker before starting experiments. This included focusing the camera to ensure clear visibility of eyelashes and adjusting the camera's infrared sensitivity threshold. The calibration process involved having participants look at the four corners of a computer monitor to ensure comprehensive tracking of pupil and corneal reflexes across the monitor's surface. Calibration started with the participant focusing on nine fixed points (black dots) displayed in random order on the monitor at known locations. The number of fixed points adjusted based on the screen size occupied by the stimulus task, using a 9-point pattern for calibration. Participants were instructed to focus on each point until it disappeared, avoiding any attempt to anticipate the point's movement. Following calibration, its accuracy was validated by having participants look at the same nine points, comparing the calculated fixation positions with the known fixed positions to assess visual error. The software then provided data on the degree of visual error for each fixation point, the average error across all points, and the

maximum error observed. The experiment formally started once acceptable calibration was achieved, with participants instructed to remain silent during stimulus presentation.

2.6   Eye-tracking data preprocessing and analysis

Preprocessing

We used Matlab software to pre-process the eye movement data. Since the duration of the video material is known, we limited the length of the data sequence and made it uniform while ensuring its integrity. In addition, the invalid data of subjects' blinks were replaced, and the complete data sequence of each subject was finally extracted, including screen fixation point X, Y and pupil size.

Pupil size and speed of moving

We extracted raw pupil size data from eye-tracking recordings and analyzed them without baseline correction, focusing primarily on dynamic changes within participants. The speed of movement was calculated using the x and y coordinates at the current and subsequent time points. Distances were computed using the Pythagorean theorem and subsequently converted to speed measurements. For each event boundary, we analyzed pupil size and movement speed within a 4-second window (i.e., from -2 to +2 seconds, with 0 representing the event boundary). To assess the effects of event boundaries on pupil size and movement speed, we conducted repeated-measures ANOVA to compare average pupil dilation responses and speeds at the time points of -2, -1, 0, 1, and 2.

Pattern similarity analysis of eye movements

To analyze eye movement pattern similarity before and after event boundaries, we conducted a similarity analysis using eye-tracking data during video viewing. This analysis

involved calculating similarity scores within 10-second intervals, initially based on pupil size and later including both pupil size and gaze coordinates (vertical and horizontal). Specifically, we derived a pupil size time series for each participant and computed correlations between two segments of data (50 points before vs. 50 points after the boundary) is calculated. The average of all these values provided an overall similarity measure for pupil size. This process was repeated for pupil size, vertical, and horizontal gaze. Finally, we computed a composite similarity measure by averaging the three similarity values, defined as similarity = (similarity$_x$ + similarity$_y$ + similarity$_{pupil}$) / 3. Based on the selection of time window, we computed three types of similarity measures: (1) Between-event correlations were analyzed from -5 to 0 seconds and 0 to 5 seconds, with 0 indicating the event boundary. (2) Within-event post-boundary correlations were assessed from 0 to 10 seconds after the boundary. (3) Within-event pre-boundary correlations were analyzed from -10 to 0 seconds before the boundary. Statistical differences among these measures were evaluated using a repeated-measures ANOVA, which included event type as a three-level factor: pre-boundary, between-event, and post-boundary.

Interject-correlation analyses (ISC) of eye movements

To investigate the influence of event boundaries on the inter-subject correlation (ISC) of eye movements, we calculated the ISC for eye movements within specific temporal windows: before, during, and after an event boundary. Firstly, we calculated ISC within certain time window by 1) computing Pearson's correlation coefficient between the vertical gaze positions of a single subject and those of all other participants as they viewed a video; 2) deriving an ISC value for each participant by averaging the correlation coefficients across all comparisons; and 3) replicating the above steps for every participant to obtain an individual ISC score per

participant. We repeated this procedure for pupil size, vertical, and horizontal gaze. Subsequently, we computed a composite ISC score by averaging these three ISC values, defined as $ISC = (ISC_x + ISC_y + ISC_{pupil}) / 3$. For each event boundary, ISC was evaluated under three different conditions: 10 seconds prior to the boundary (pre-boundary condition), 5 seconds before and after the boundary (boundary condition), and 10 seconds subsequent to the boundary (post-boundary condition). We then calculated the average ISC for each condition and participant, assessing differences using repeated-measures ANOVA.

Eye-tracking-based Hidden Markov Models (HMM)

We adapted the HMM approach previously used in fMRI[10] and EEG[33] to assess its efficacy in identifying latent eye-tracking states during video viewing, based on the event segmentation theory. Unlike fMRI and EEG data, the eye tracking method produced only three time series: X-axis and Y-axis coordinates of screen annotation points, and pupil size. Our objective is to deduce both the specific eye movement patterns and the structure of events, including the location of event boundaries. To this end, we reformulated our approach as a variant of the Hidden Markov Model. Using a leave-one-out procedure, we first applied this model with the predefine optimal K to both the *Commercial Movie Dataset* (K=20) and the *STEM Course Dataset* (K=12) to determine optimal event boundaries for each test participant.

To evaluate the efficacy of the eye-tracking-based HMM in generating meaningful event structure, we employed two methods: (1) We assessed the fit of the eye-tracking data to the model by comparing both human-annotated and HMM-generated event boundaries using a within-event similarity measure with the null model. This measure's group-averaged value was then tested against a null distribution, created by randomizing the event sequence 1000 times,

to ascertain if it significantly exceeded the expected under random conditions. (2) We also compared the HMM-generated boundaries to human annotations by shuffling the event boundaries while preserving their duration to generate 1000 null distributions, and calculated a z-score that was transformed into a p-value to evaluate the significance of the match.

Furthermore, we investigated the performance of the HMM event segmentation across a range of k values (i.e., predefined number of events). Additionally, we examined whether individual differences in the model-defined optimal k values among participants signify significant variations in the event segmentation process. In the *Commercial Movie Dataset*, with an established ground truth of 20 events, we ran the HMM across k values from 15 to 25 and evaluated the resulting boundaries for their ability to model eye movement patterns, calculating within-event pattern similarity for each k and averaging these values across participants to assess whether the most accurate event structures yielded higher similarity scores. This analysis was also performed in the STEM dataset with the range of 8-16, because the ground truth is 12 events.

2.8 Data and code availability

Processed behavioral and eye-tracking data, as well as custom-made video stimuli, are available at OSF (https://osf.io/n7k45/?view_only=673d89b23720410799b5daec1f5d511e) Raw eye-tracking data is available upon reasonable request to the corresponding authors. Due to copyright restrictions, videos from the Commercial Movie Dataset are not accessible. Scripts for performing all eye-tracking analyses are located in the same repository as the data and stimuli. Data analyses were conducted using MATLAB or Python. Our HMM event

segmentation model, was developed using the BrainIAK toolbox[44] (https://github.com/intelpni/brainiak). Inter-subject correlation analyses were performed using in-house scripts, inspired by Pauline' study[25] (https://doi.org/10.17605/OSF.IO/MHVY7). Within-event and cross-event similarity analyses were conducted using in-house scripts, inspired by Sliva's study[33].

3. Results

3.1 Dynamics of pupil size and speed of eye movement in response to event boundaries

We investigated the changes in pupil size and the speed of eye movement around event boundaries, considering these dynamics as potential markers of event segmentation. Our analyses were first conducted with the *Commercial Movie Dataset* and was subsequently extended to the *STEM Course Dataset*. The latter serves as a conceptual replication, differing from a direct replication, due to the distinct characteristics of the two videos. Notably, the *STEM Course video* features pronounced visual transitions between slides and periods of static imagery while a scientific concept is explained.

When analyzing the *Commercial Movie Dataset,* we observed a pattern where pupil size increased immediately preceding the event boundary, peaking one second before (Max = 2108.2), followed by a sharp decrease shortly after the boundary (Min = 2080.54.7, $F_{(4,412)}$ = 9.137, $p<0.001$; **Figure2a**). A corresponding pattern emerged for eye movement speed: an increase approaching the boundary, peaking at the boundary, and then a marked decrease thereafter ($F_{(4,412)}$ = 150.806, $p<0.001$; **Figure2b**).

When participants watched the *STEM course video*, pupil size decreased as it neared the event boundary, peaked at the boundary, and then reaching its lowest point a second after the boundary (Max = 978.516, Min = 937.125, F(4,112) = 13.392, *p*<0.001; **Figure2c**). This post-boundary reduction in pupil size aligns with the patterns noted in the *Commercial Movie Dataset*. The movement speed analysis for the *STEM Course dataset* echoed these findings, with the highest speeds recorded at the event boundary (F(4,112) = 41.576, *p*<0.001; **Figure2d**).

Further analysis using a boundary strength measure was conducted exclusively on the *Commercial Movie Dataset* to explore how pupil size and movement speed varied with boundary strength. Specifically, we performed interaction analyses between category of boundary strength and time for pupil size (F(2,8)=1.256, *p*=0.266; **Figure 2E**) and movement speed (F(2,8)=1.971, *p*=0.049; **Figure 2F**). Pupil size responded significantly to high-strength boundaries (F(4,112)=4.866, *p*<0.001) and medium-strength boundaries (F(4,112)=2.957, *p*=0.023), but not to low-strength boundaries (F(4,112)=2.076, *p*=0.089). Movement speed responded significantly to high-strength boundaries (F(4,112)=3.657, *p*=0.008), but not to medium (F(4,112)=1.497, *p*=0.208) or low strength boundaries (F(4,112)=1.67, p=0.167). Our findings reveal that dynamic patterns in pupil size and movement speed in response to high-strength boundaries align with our main analyses. Conversely, responses to medium and low-strength boundaries are occasionally absent.

Figure 2 Pupil Size and Eye Movement Speed in Response to Event Boundaries and Their Modulation by Boundary Strength. (A) Pupil size dynamics around event boundaries in the Commercial Movie Dataset. (B) Eye movement speed dynamics around event boundaries in the Commercial Movie Dataset. (C) Pupil size changes around event boundaries in the STEM Course Dataset. (D) Eye movement speed dynamics around event boundaries in the STEM Course Dataset. (E) Impact of event boundary strength on pupil size adjustments in the Commercial Movie Dataset. (F) Influence of event boundary strength on eye movement speed patterns in the Commercial Movie Dataset.

3.2 Eye movement pattern similarity within and across event boundaries

Event Segmentation Theory suggests that mental representations within an event are more stable than those across events, indicating dynamic changes in representations at detected boundaries. This concept is supported by EEG neural pattern similarity analyses[33]. We explored this prediction using eye-tracking data, initially with the *Commercial Movie Dataset* and subsequently with the *STEM Course Dataset*. Specifically, we conducted a point-to-point similarity analysis of eye-tracking segments from −10 to +10 seconds around the boundary time point, using pupil size or together with vertical and horizontal gaze coordinates. We performed this analysis between three distinct pairs of temporal intervals: the within-event pre-boundary condition (−10 to −5 s and −5 to 0 s relative to the boundary), the between-event condition (−5 to 0 and 0 to 5 s relative to the boundary), and the within-event post-boundary condition (0 to 5 s and 5 to 10 s relative to the boundary). We then calculated the average similarity values for each condition and subject, with differences assessed using repeated-measures ANOVA.

In the *Commercial Movie Dataset*, analyses of pupil size alone revealed no significant differences in similarity measures across within-event pre-boundary, between-event, and within-event post-boundary conditions ($F(2,206) = 2.264$, $p = 0.107$; **Figure 3A**). However, when pupil size was analyzed in conjunction with vertical and horizontal gaze, a higher similarity measure was observed for the between-event condition ($F(2,206) = 3.676$, $p = 0.027$; **Figure 3B**), indicating that combining eye movements with pupil size more effectively captures event segmentation processes.

Replication analyses using the *STEM Course Dataset* produced similar, nearly

significant results for analyses of pupil size alone ($F(2,56) = 2.534$, $p = 0.088$; **Figure 3C**) and in combination with gaze ($F(2,56) = 2.861$, $p = 0.066$; **Figure 3D**). Notably, no interaction was found between boundary strength and time in the analyses of pupil size alone ($F(2,4) = 0.529$, $p = 0.715$; **Figure 3E**). However, an interaction was observed in the analysis combining pupil size with gaze metrics ($F(2,4) = 3.385$, $p = 0.011$; **Figure 3F**). Specifically, when analyzing high-strength event boundaries, there was a significant increase in similarity measures between low-strength boundaries ($F(2,56) = 3.822$, $p = 0.028$). However, this was not observed for high-strength ($F(2,56) = 1.756$, $p = 0.182$) or middle-strength boundaries ($F(2,56) = 2.515$, $p = 0.09$).

Figure 3 Eye movement pattern similarity within and across event boundaries during continuous video watching. (A) We analyzed three similarity measures derived from pupil size—within events before the boundary, across events separated by boundaries, and within events after the boundary—using the *Commercial Movie Dataset*. (B) Higher similarity measure, incorporating both pupil size and vertical and horizontal gaze, was calculated in the across-event condition, compared to two within-event conditions, using the *Commercial Movie Dataset*. (C) Participant's three similarity measures derived from pupil size for three event conditions, analyzed with the *STEM Course Dataset*. (D) Participants' similarity measures, calculated from both pupil size and vertical and horizontal gaze, were evaluated for three event conditions with the *STEM Course Dataset*. (E) Influence of event boundary strength on the analysis of similarity measure based on pupil size. (F) Effects of event boundary strength on similarity analyses that included both pupil size and vertical and horizontal gaze.

3.3   Event boundaries synchronized eye movements across participants

We applied inter-subject correlation (ISC) analysis to two eye-tracking datasets to assess whether and how eye movements synchronize across participants in response to an event boundary during continuous video viewing. Using both vertical and horizontal gaze coordinates along with pupil sizes, we analyzed ISC across three conditions (**Figure 4A**): 10 seconds before the boundary (pre-boundary condition), 5 seconds before and after the boundary (boundary condition), and 10 seconds following the boundary (post-boundary condition).

In the *Commercial Movie Dataset*, distinct ISC patterns emerged for three different ISCs (F=81.16, p<0.001; **Figure 4B**): boundary ISC is significantly higher than pre-boundary ISC (t=5.37, p<0.001, Cohen's d=0.52), with a continued increase to post-boundary ISC (t=6.88, p<0.001, Cohen's d=0.67). Similarly, in the *STEM Course Dataset*, we confirmed significant ISC variations across conditions (F=29.28, p<0.001; **Figure 4C**): boundary ISC is significantly higher than pre-boundary ISC C (t=5.96, p<0.001, Cohen's d=1.11), but it decreased post-boundary (t=-2.55, p=0.017, Cohen's d=-0.47), though remaining higher than baseline level (i.e., pre-boundary) (t=11.31, p<0.001, Cohen's d=2.1).

Additionally, we demonstrated that boundary strength influenced boundary ISC levels (F=22.48, p<0.001; **Figure 4D**): high and middle strength boundaries led to greater synchronization of eye movements than low strength boundaries, as shown by significant t-tests (t=4.81, p<0.001, Cohen's d=0.89 for high strength; t=7.33, p<0.001, Cohen's d=1.36 for medium strength), suggesting that stronger boundaries are more likely to induce synchronized eye movements across participants during event boundaries.

Figure 4 Synchronized Eye Movements in Response to Event Boundaries. (A) Synchronized eye movements—specifically, the positions (X and Y coordinates) and pupil sizes—of two participants (S1 and S2) while continuously watching two distinct events separated by an event boundary. Intersubject correlation (ISC) is quantified as the mean correlation between both vertical and horizontal gaze positions and pupil sizes across participants. We analyze three ISC metrics: pre-boundary ISC, calculated during the final 10 seconds before the event boundary; boundary ISC, derived from 5 seconds of eye-tracking data from each event; and post-boundary ISC, measured during the initial 10 seconds following the event boundary. **(B)** Comparison of three kinds of ISC within the *Commercial Movie Dataset*. **(C)** Comparison of three kinds of ISC within the *STEM Course Dataset*. **(D)** Comparison of boundary ISC associated with event boundaries characterized by high, medium, and low boundary strengths.

3.4 Discovering event structures in continuous eye-tracking recordings from humans

We employed two approaches to test the hypothesis that meaningful event structure information can be extracted from eye-tracking data using a Hidden Markov Model (HMM) event segmentation model when participants watched continuous video. First, we examined whether and to what extent the eye-tracking data fitted the model based on human-annotated or HMM-generated event boundaries. To do this, we conducted the similarity analysis of the eye-tracking data at each time point during video watching and calculated the degree of similarity within each event. We then tested this group-averaged similarity value against a null distribution generated by running the same analysis 1000 times with a shuffled temporal order of events. Second, we employed the HMM-based event segmentation method to automatically discover event-tracking-based signatures and temporal boundaries in the dataset. Then, we validated our model by comparing HMM-generated event boundaries to human annotations.

In the *Commercial Movie Dataset*, we firstly showed a higher degree of similarity values within events from the human-annotated event boundary model compared to correlation value from their null distribution at the group level ($p<0.001$; **Figure 5A**). This is also true for event boundaries generated by HMM ($p<0.001$; **Figure 5B)**. Next, we then measured, what fraction of its HMM-generated boundaries were close to human annotations. At the group level, the HMM-generated boundaries showed an above-chance match to human annotations ($p<0.001$; **Figure 5C**).

In the *STEM Course dataset,* however, we did not find significant higher degree of similarity values within events from the human-annotated event boundary model compared to correlation value from their null distribution at the group level ($p=0.453$; **Figure 5D**). Instead,

we found the eye-tracking data fit the model generated by HMM ($p<0.001$; **Figure 5E),** suggested by a higher degree of similarity compared to null model. Secondly, the HMM-generated boundaries showed marginally above-chance match to human annotations ($p=0.0688$; **Figure 5F**). However, when we examined the influence of boundary strength on the congruence of HMM-defined and human-annotated boundaries, we found that the HMM was more effective in identifying boundaries of high strength compared to those of middle and low strength. The HMM pinpointed the optimal timing for events with high-strength boundaries ($p<0.001$; **Figure 5G**), but not for events with medium ($p=0.2861$; **Figure 5H**) or low-strength boundaries ($p=0.8074$; **Figure 5I**).

The HMM event segmentation model can autonomously determine the optimal number of events within time series data. We aimed to use the model-derived optimal event number (i.e., the k value) to represent individual differences in the event segmentation process. Before assessing the cognitive significance of the k value, we validated it using similarity analyses. Within a specified range of candidate k values (See Methods for details), we instructed the HMM to rank these k values from most to least optimal and used various k values along with its corresponding boundary locations to compute similarity metrics within our eye-tracking data. We observed that the application of the optimal k value yielded the highest similarity values. Moreover, as the k value deviated from the optimal, the similarity scores decreased significantly. This trend was consistent across both the *Commercial Movie Dataset* (r=0.17, $p<0.001$; **Figure 5J**) and the *STEM Course dataset* (r=0.3, $p<0.001$; **Figure 5K)**.

Figure5 Hidden Markov Model (HMM)-based Event Segmentation Model for Eye-Tracking Data. (A) Using human-annotated event boundaries, we calculated the average correlation values (similarity values) for pairs of time points within each event. The light blue circle denotes the true participant average. For the *Commercial Movie dataset*, the blue-green histogram shows the null distribution of participant averages, derived from random event boundary shuffling in the segmentation model. **(B)** Similar similarity analyses as Figure5A were conducted using HMM-generated event boundaries, comparing them to the null distribution. **(C)** Comparison between event boundaries from the HMM model and human-annotated event boundaries in the Commercial Movie dataset revealed an above-chance match (light blue circle denotes true

participant average; null distribution shown in blue-green). **(D)** Similar data analyses as in Figure 5A were performed for the *STEM Course dataset*. The orange histogram represents the null distribution of participant averages. **(E)** Similar data analyses as in Figure 5B were performed for the *STEM Course dataset*. **(F)** Similar data analyses as in Figure 5A were performed for the *STEM Course dataset*. **(G-I)** How boundary strength modulates the HMM-human boundary matching. The HMM effectively identified high-strength boundaries but not medium- and low-strength boundaries. **(J)** Investigation into the relationship between the optimal K value determined by the HMM model and similarity values in the *Commercial Movie Dataset*. **(K)** Investigation into the relationship between the optimal K value determined by the HMM model and similarity values in the *STEM Course Dataset*.

3.5 HMM-based event segmentation are sensitive to experimental manipulations and predict learning outcomes

The optimal event segmentation measures derived from eye-tracking data should be sensitive to experimental manipulations, facilitating their application across diverse experimental conditions or populations. Our study used the *Commercial Movie Dataset* to investigate this validation. Participants were divided into two experimental subgroups who viewed short TikTok video clips (Short-R for random videos and Short-P for personalized videos) before watching a continuous movie clip. Two control groups included participants who watched a movie-unrelated documentary clip (Long group) or a movie-related movie clip (Schema group).

We hypothesized that exposure to short video clips might impair subsequent event segmentation during movie watching, as indicated by altered eye-tracking-derived event segmentation metrics. The analysis focused on assessing differences in the individual optimal

K value and p value, reflecting whether eye-tracking data fit the model based on HMM-generated event boundaries. After determining the optimal K value for each participant, we compared K values across groups and found a significant group difference (F=7.25, p<0.001; **Figure6A**). Notably, watching randomly selected TikTok videos, compared to the Long group, resulted in higher K values (t=2.18, p=0.034, Cohen's d=0.28), suggesting the more fragmented event segmentation during video watching. Contrary to our prediction, watching personalized TikTok video clips (Short-P) before movie watching, compared to the Long group, resulted in significantly lower K values (t=-2.9, p=0.006, Cohen's d=-0.31). Additionally, we analyzed p-values as an index for event segmentation and found the effect of experimental manipulations before movie watching on p-values (F=4.14, p=0.008; **Figure 6B**). The two experimental groups did not differ from each other (t=0.71, p=0.48, Cohen's d=0.19). Both the Schema and Long group demonstrated lower p values compared to the Short-P (Schema: t=-2.69, p=0.01, Cohen's d=-0.77; Long: t=-2.32, p=0.02, Cohen's d=-0.67) and Short-R (Schema: t=-2.62, p=0.01, Cohen's d=-0.70; Long: t=-2.13, p=0.03, Cohen's d=-057) group.

We then examined whether HMM-based event segmentation measures, specifically optimal K values and p-values, could predict learning outcomes in both the *Commercial Movie* and *STEM Course datasets*. For the *Commercial Movie Dataset*, memory performance for each participant was quantified using "remember" and "detail" scores from their speech-based free recall recordings. Across all participants, we found that the optimal K value was not associated with the number of events recalled (i.e., "remember" Score) (F=0.23, p=0.87; **Figure6C**), but was associated with the number of details recalled ("detail" Score) (F=7.36, p<0.001; **Figure6D**). The optimal K value was negatively correlated with the detail score (r=-0.42,

p<0.001). No relationships were found between p values and memory performance (remember score: r=-0.07, *p*=0.45; detail score: r=0.04, *p*=0.63). For the *STEM Course dataset*, memory performance for each participant was quantified using "remember" and "test" scores. Across all participants, we found that the optimal K value was not associated with the Remember Score (F=1.02, *p*=0.39; **Figure 6E**) but was marginally associated with the test score: test scores decreased as the K value increased (r=-0.34, p=0.067; **Figure 6D**). We further found that as the p-value decreased, participants demonstrated higher test scores (r=-0.35, *p*=0.058), but not remember scores (r=-0.15, *p*=0.42).

Additionally, we assessed whether predictive effects were limited to HMM-driven event segmentation measures by examining correlations between *pupil size* and *moving speed* and memory performance. In the *Commercial Movie Dataset*, moving speed did not correlate with remember (r=-0.02, *p*=0.81) or detail score (r=-0.15, *p*=0.11). Pupil size did not correlate with remember score (r=-0.02, *p*=0.81), but negatively correlated with detail score (r=-0.21, *p*=0.032). In the *STEM course dataset*, neither the speed of movement (remember score: r=0.08, *p*=0.66; test score: r=0.20, *p*=0.28) nor pupil size (remember score: r=-0.19, *p*=0.31; test score: r=-0.22, *p*=0.24) showed significant correlations with learning outcomes. Consequently, we conclude that metrics derived from HMM event segmentation model, as opposed to simpler indices such as movement speed and pupil size, provide a stronger predictive value for learning outcomes as assessed by memory tests following video-based learning.

Figure 6 Validity of HMM-Based Event Segmentation Measures: Sensitivity to Experimental Manipulations and Prediction of Learning Outcomes. (A) Effects of experimental manipulations on Hidden Markov Model (HMM)-derived optimal K values. (B) Impact of experimental manipulations on p-values from inter-subject correlation analyses. (C) Association between K values and subsequent memory performance, quantified as Remember Score, within the *Commercial Movie Dataset*. (D) Association

between K values and detailed subsequent memory performance, quantified as Detail Score, within the *Commercial Movie Dataset*. (E) Replication analyses examining the association between K values and memory performance, quantified as Remember Score, *in the STEM Course Dataset*. (F) Replication analyses examining the association between K values and memory performance, quantified as Test Score, in the *STEM Course Dataset*.

Discussion

Using eye-tracking data from two distinct naturalistic viewing contexts—specifically, the viewing of a commercial movie and a STEM learning video—we demonstrated the efficacy of eye-tracking in measuring event segmentation during continuous naturalistic viewing. Our analysis began with basic metrics of *pupil size* and *movement speed*, and progressively incorporated advanced computational techniques, including *similarity analyses*, *intersubject correlation* (ISC), and *Hidden Markov Model* (HMM) analyses. Notably, these computational markers of event segmentation responded to event boundaries, were sensitive to experimental manipulations, and were able to predict learning outcomes effectively. Therefore, we concluded that eye-tracking provides a robust measure of event segmentation. Moreover, the integration of eye-tracking with neuroscientific techniques such as fMRI and EEG, alongside its applicability using common devices like laptops or smartphones, not only sheds new light on the fundamental theories of event segmentation but also holds substantial implications for industries like film production and online education.

Our initial investigation focused on the ability of basic eye-tracking metrics, specifically pupil size and movement speed, to track event boundaries during naturalistic viewing. We discovered that movement speed, in contrast to pupil size, serves as a more

sensitive and reliable indicator for segregating events across movie and STEM learning video. Historically, pupil size has been a metric for assessing fluctuations in arousal related to ongoing cognitive and memory processes, serving as an insight into the neural underpinnings of cognition[45,46]. Relevant to the current study, there is growing evidence that arousal responses are attuned to the structure of temporally unfolding experiences, potentially indicating the event segmentation[31,47,48]. However, studies in this area have typically used auditory cues to demarcate event boundaries, which, although present, do not represent the primary method of segmenting information flow in the films and STEM materials in our study. Given the rich visual context of our naturalistic viewing conditions, we opted for movement speed as an alternative method for tracking event segmentation. This approach has been validated across two independent datasets and has demonstrated the modulatory effects of boundary strength on movement speed near event boundaries. In addition, we argue that movement speed is a more apt metric for measuring event segmentation during naturalistic viewing tasks, as it is less influenced by environmental factors such as lighting[49] or the participants' internal states, including emotions and stress levels[50].

Our pattern similarity analyses of eye movements (i.e., comparison between within and across event boundaries), revealed a notable reversal compared to a previous EEG study: pattern similarity was higher across event boundaries than within a single event. In contrast, Silva and colleagues, using EEG pattern similarity analyses, found that similarity within events exceeded that between events. They interpreted this finding as indicative of changes in neural representations upon detecting boundaries[33]. Their finding was interpreted as indicating that neural representations of events change upon the detection of boundaries. The increased

similarity around boundaries suggests its potential as an additional eye-tracking-based marker for event segmentation, although the underlying cognitive mechanisms remain unclear. The discrepancy between EEG and eye-tracking patterns warrants further investigation, possibly by applying the same analyses to fMRI data or by conducting simultaneous EEG and eye-tracking recordings during conditions of continuous video viewing.

Importantly, our ISC analyses of eye movements provided evidence that participants' eye movements were more synchronized at event boundaries than during the event. It is a well-documented phenomenon that shared experiences can synchronize gaze positions and pupil sizes among individuals[29,51,52]. The shared neural and biological responses, captured by ISC and event segmentation, represent two major cognitive processes during naturalistic conditions, such as watching a movie or listening to music. However, few studies have linked these processes. One example could be: Clara and colleagues investigated variations in neural event boundary locations among individuals and demonstrated that those with more similar neural event boundaries in certain regions during movie-watching tended to have more similar movie appraisals[53]. Our eye-tracking data provide direct evidence that event boundaries can synchronize eye movements across participants, thus potentially serving as a major source of intersubject similarity. Considering the role of intersubject correlation and event segmentation in naturalistic perception and memory, we propose that the previously reported higher ISC values may predict successful memory formation[29,42,54], at least partly, through enhanced event segmentation mechanisms.

Inspired by the application HMM in neuroimaging[10], our study is the first investigation to whether determine if HMM can delineate event structure representation through eye-tracking

data. Cross two distinct video stimuli (i.e., commercial movie and STEM educational video), our findings indicate a significant correspondence between event boundaries identified by eye-tracking & HMM and those annotated by humans. This alignment echoes the alignment observed in studies employing fMRI[10,24,35,55] and EEG[33,56], and the alignment led to significant higher similarity values in the eye-tracking data. Given the affordability and accessibility of eye-tracking technology, this confirmation opens new avenues for future research that might integrate neural-based event segmentation studies with eye-tracking methodologies. Importantly, our analysis revealed considerable variability in the concordance between HMM model predictions and human annotations, as well as the influence of boundary strength (i.e., event boundaries with higher strength are more easily identified by the HMM). The variation in HMM predictions should not be dismissed as mere noise but rather considered as a potential objective indicator for event segmentation, extending beyond traditional neural markers such as hippocampal responses[21,22,57,58].

Employing data from experimental manipulations preceding video viewing and subsequent memory assessments, we conducted a comprehensive examination of how pupil diameter, movement speed, k value from HMM, and the P-value of similarity analyses vary as a function of experimental conditions and their predictive capability regarding learning outcomes. Previous studies have indicated that factors such as development[35], age[58], anticipation[36], and schema[37] can influence fMRI markers of event segmentation. Our results suggest that compared to pupil size and moving speed, metrics derived from HMM display enhanced sensitivity to various psychological states, potentially augmenting or impairing event segmentation. This insight is pivotal for investigating event segmentation across different

demographics and experimental conditions in future studies. Eye-tracking-based ISC has been recognized for its ability to predict learning outcomes[29,52,54]. Here, we augment the predictive scope of eye-tracking metrics by demonstrating that metrics associated with HMM event segmentation model can also foresee subsequent memory performance. Unlike ISC analyses, whose underlying cognitive theories remain ambiguous, event segmentation has long been hypothesized to play a critical role in memory formation[2,3]. The eye-tracking-based event segmentation index offers a more interpretable metric for delineating underlying mechanisms and identifying targets for specific cognitive and/or neural modulation-based learning strategies. Why does the event segmentation-based index, as opposed to merely pupil size and movement speed, predict learning outcomes? We hypothesize that HMM-derived metrics more precisely delineate the conceptual dimensions of event segmentation, while measures of pupil size and movement speed are more reflective of perceptual processes. Therefore, we advocate for prioritizing HMM-derived metrics in future cognitive research on the link between event segmentation and memory formation.

Our investigation is the initial endeavor to measure event segmentation through eye-tracking data, with certain limitations noted. Firstly, event segmentation's occurrence across diverse video stimuli is acknowledged. Our analysis of two distinct eye-tracking datasets—captured while participants viewed either a commercial movie or a STEM course video—aims to broaden our study's applicability and act as a conceptual replication. They represent typical daily activities but possess distinct editing features (e.g., cuts, scene changes, switch of slides) that may facilitate event segmentation detection through eye-tracking[59,60]. Conversely, everyday activity videos, like personal vlogs (e.g., purchasing coffee at Starbucks), may lack

these editing traits, possibly limiting eye-tracking's efficacy in event segmentation analysis. Secondly, our data were gathered advanced eye-tracking technology within controlled laboratory settings to ensure data quality. Nevertheless, the application of event segmentation identification in real-world settings might rely on data from cost-effective cameras and less regulated environments, posing challenges that future research must address. A notable study used ISC to analyze eye movements captured by standard web cameras in classroom and home setting, and successfully predicted tests scores during online education[29]. This study may suggest that eye movement metrics might be robust against variations in measurement tools and environmental disturbances compared to neuroimaging benchmarks. Thirdly, our participant pool consisted of healthy young adults from a university setting, generally exhibiting good attention and comprehension of the videos. While event segmentation has been effectively studied in other demographics, including older adults[58] and infants[35], eye tracking data from a broader demographic spectrum may exhibit higher blink rates and tracking loss, adversely affecting measurement accuracy[61,62]. We argue that research extending to diverse groups or psychiatric patients should consider extended recording times or increased sample sizes to effectively analyze event segmentation processes through eye-tracking.

In conclusion, eye-tracking offers an alternative methodology for researchers investigating the event segmentation process during naturalistic video viewing. This approach can be employed concurrently with other neuroscientific techniques, such as EEG and fMRI, to explore eye-brain interactions during event segmentation. Furthermore, it can be used in online experiments using laptop or smartphone cameras to enable large-scale studies of event segmentation in real-world settings.

Competing Interests

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgments and Funding

W.L was supported by the National Natural Science Foundation of China (grant No. 32300879), Humanities and Social Sciences Fund, Ministry of Education (grant No. 22YJCZH109), Natural Science Foundation of Hubei (grant No. 2022CFB793), Open Research Fund of the State Key Laboratory of Cognitive Neuroscience and Learning (CNLYB2103), Open Research Fund of the Key Laboratory of Adolescent Cyber Psychology and Behavior (grant No. CCNUCYPSYLAB2022B10), the Major Program of the National Social Science Foundation of China (grant No. 22&ZD187) and self-determined research funds of CCNU from the colleges'basic research and operation of MOE(CCNU22QN020).

Contributions

W.L. and X.H conceived the Study; J.S.L and Z.Y.C collected the data; W.L. and J.S.L analyzed the data; W.L., X.H, and J.S.L prepared the first draft. W.L. and X.H reviewed and edited the manuscript, provided supervision, and obtained funding.

Reference

1. Zacks, J. M. & Tversky, B. Event structure in perception and conception. *Psychol Bull* **127**, 3–21 (2001).

2. Zacks, J. M. Event Perception and Memory. *Annu Rev Psychol* **71**, 165–191 (2020).

3. Kurby, C. A. & Zacks, J. M. Segmentation in the perception and memory of events. *Trends Cogn Sci* **12**, 72–79 (2008).

4. Sun, C., Yang, W., Martin, J. & Tonegawa, S. Hippocampal neurons represent events as transferable units of experience. *Nat Neurosci* **23**, 651–663 (2020).

5. Hasson, U., Nir, Y., Levy, I., Fuhrmann, G. & Malach, R. Intersubject Synchronization of Cortical Activity During Natural Vision. *Science (1979)* **303**, 1634–1640 (2004).

6. Antony, J. W. *et al.* Behavioral, Physiological, and Neural Signatures of Surprise during Naturalistic Sports Viewing. *Neuron* **109**, 377-390.e7 (2021).

7. Yeshurun, Y. *et al.* Same Story, Different Story: The Neural Representation of Interpretive Frameworks. *Psychol Sci* **28**, 307–319 (2017).

8. Raccah, O., Doelling, K. B., Davachi, L. & Poeppel, D. Acoustic features drive event segmentation in speech. *J Exp Psychol Learn Mem Cogn* **49**, 1494–1504 (2023).

9. Liu, W., Shi, Y., Cousins, J. N., Kohn, N. & Fernández, G. Hippocampal-Medial Prefrontal Event Segmentation and Integration Contribute to Episodic Memory Formation. *Cerebral Cortex* **32**, 949–969 (2022).

10. Baldassano, C. *et al.* Discovering Event Structure in Continuous Narrative Perception and Memory. *Neuron* **95**, 709-721.e5 (2017).

11. Hasson, U., Chen, J. & Honey, C. J. Hierarchical process memory: memory as an integral component of information processing. *Trends Cogn Sci* **19**, 304–313 (2015).

12. Sasmita, K. & Swallow, K. M. Measuring event segmentation: An investigation into the stability of event boundary agreement across groups. *Behav Res Methods* **55**, 428–447 (2022).

13. Zacks, J. M. *et al.* Human brain activity time-locked to perceptual event boundaries. *Nat Neurosci* **4**, 651–655 (2001).

14. Zacks, J. M., Tversky, B. & Iyer, G. Perceiving, remembering, and communicating structure in events. *J Exp Psychol Gen* **130**, 29–58 (2001).

15. Kurby, C. A. & Zacks, J. M. Age differences in the perception of hierarchical structure in events. *Mem Cognit* **39**, 75–91 (2011).

16. Faber, M., Radvansky, G. A. & D'Mello, S. K. Driven to distraction: A lack of change gives rise to mind wandering. *Cognition* **173**, 133–137 (2018).

17. Swallow, K. M., Zacks, J. M. & Abrams, R. A. Event boundaries in perception affect memory encoding and updating. *J Exp Psychol Gen* **138**, 236–257 (2009).

18. Chen, J. *et al.* Shared memories reveal shared structure in neural activity across individuals. *Nat Neurosci* **20**, 115–125 (2017).

19. Sasmita, K. & Swallow, K. M. Measuring event segmentation: An investigation into the stability of event boundary agreement across groups. *Behav Res Methods* **55**, 428–447 (2022).

20. Ben-Yakov, A. & Dudai, Y. Constructing Realistic Engrams: Poststimulus Activity of Hippocampus and Dorsal Striatum Predicts Subsequent Episodic Memory. *Journal of Neuroscience* **31**, 9032–9042 (2011).

21. Ben-Yakov, A. & Henson, R. N. The hippocampal film editor: Sensitivity and specificity to event

boundaries in continuous experience. *Journal of Neuroscience* **38**, 10057–10068 (2018).

22. Ben-Yakov, A., Eshel, N. & Dudai, Y. Hippocampal immediate poststimulus activity in the encoding of consecutive naturalistic episodes. *J Exp Psychol Gen* **142**, 1255–1263 (2013).

23. Sasmita, K. & Swallow, K. M. Measuring event segmentation: An investigation into the stability of event boundary agreement across groups. *Behav Res Methods* **55**, 428–447 (2022).

24. Geerligs, L., van Gerven, M. & Güçlü, U. Detecting neural state transitions underlying event segmentation. *Neuroimage* **236**, 118085 (2021).

25. Pérez, P. *et al.* Conscious processing of narrative stimuli synchronizes heart rate between individuals. *Cell Rep* **36**, 109692 (2021).

26. Kragel, J. E. & Voss, J. L. Looking for the neural basis of memory. *Trends Cogn Sci* **26**, 53–65 (2022).

27. Lorigo, L. *et al.* Eye tracking and online search: Lessons learned and challenges ahead. *Journal of the American Society for Information Science and Technology* **59**, 1041–1052 (2008).

28. Bucher, H.-J. & Schumacher, P. The relevance of attention for selecting news content. An eye-tracking study on attention patterns in the reception of print and online media. *comm* **31**, 347–368 (2006).

29. Madsen, J., Júlio, S. U., Gucik, P. J., Steinberg, R. & Parra, L. C. Synchronized eye movements predict test scores in online video education. *Proceedings of the National Academy of Sciences* **118**, (2021).

30. Ryan, J. D. & Shen, K. The eyes are a window into memory. *Curr Opin Behav Sci* **32**, 1–6 (2020).

31. Clewett, D., Gasser, C. & Davachi, L. Pupil-linked arousal signals track the temporal organization of events in memory. *Nat Commun* **11**, 4007 (2020).

32. Eddy, S. R. What is a hidden Markov model? *Nat Biotechnol* **22**, 1315–1316 (2004).

33. Silva, M., Baldassano, C. & Fuentemilla, L. Rapid Memory Reactivation at Movie Event Boundaries Promotes Episodic Encoding. *The Journal of Neuroscience* **39**, 8538–8548 (2019).

34. Cohen, S. S., Tottenham, N. & Baldassano, C. Developmental changes in story-evoked responses in the neocortex and hippocampus. *Elife* **11**, (2022).

35. Yates, T. S. *et al.* Neural event segmentation of continuous experience in human infants. *Proceedings of the National Academy of Sciences* **119**, (2022).

36. Lee, C. S., Aly, M. & Baldassano, C. Anticipation of temporally structured events in the brain. *Elife* **10**, (2021).

37. Masís-Obando, R., Norman, K. A. & Baldassano, C. Schema representations in distinct brain networks support narrative memory during encoding and retrieval. *Elife* **11**, (2022).

38. Nastase, S. A., Gazzola, V., Hasson, U. & Keysers, C. Measuring shared responses across subjects using intersubject correlation. *Soc Cogn Affect Neurosci* (2019) doi:10.1093/scan/nsz037.

39. Dmochowski, J. P. *et al.* Audience preferences are predicted by temporal reliability of neural processing. *Nat Commun* **5**, 4567 (2014).

40. Lankinen, K., Saari, J., Hari, R. & Koskinen, M. Intersubject consistency of cortical MEG signals during movie viewing. *Neuroimage* **92**, 217–224 (2014).

41. Liu, Y. *et al.* Measuring speaker–listener neural coupling with functional near infrared spectroscopy. *Sci Rep* **7**, 43293 (2017).

42. Hasson, U., Furman, O., Clark, D., Dudai, Y. & Davachi, L. Enhanced Intersubject Correlations during Movie Viewing Correlate with Successful Episodic Encoding. *Neuron* **57**, 452–462 (2008).

43. Meshulam, M. *et al.* Neural alignment predicts learning outcomes in students taking an introduction to computer science course. *Nat Commun* **12**, 1922 (2021).

44. Kumar, M. *et al.* BrainIAK tutorials: User-friendly learning materials for advanced fMRI analysis. *PLoS Comput Biol* **16**, e1007549 (2020).

45. Sara, S. J. The locus coeruleus and noradrenergic modulation of cognition. *Nat Rev Neurosci* **10**, 211–223 (2009).

46. Joshi, S. & Gold, J. I. Pupil Size as a Window on Neural Substrates of Cognition. *Trends Cogn Sci* **24**, 466–480 (2020).

47. Bianco, R., Ptaszynski, L. E. & Omigie, D. Pupil responses to pitch deviants reflect predictability of melodic sequences. *Brain Cogn* **138**, 103621 (2020).

48. Zhao, S. *et al.* Pupil-linked phasic arousal evoked by violation but not emergence of regularity within rapid sound sequences. *Nat Commun* **10**, 4030 (2019).

49. Choi, J.-H. Investigation of human eye pupil sizes as a measure of visual sensation in the workplace environment with a high lighting colour temperature. *Indoor and Built Environment* **26**, 488–501 (2017).

50. Partala, T. & Surakka, V. Pupil size variation as an indication of affective processing. *Int J Hum Comput Stud* **59**, 185–198 (2003).

51. Hasson, U. *et al.* Neurocinematics: The Neuroscience of Film. *Projections* **2**, 1–26 (2008).

52. Madsen, J. & Parra, L. C. Cognitive processing of a common stimulus synchronizes brains, hearts, and eyes. *PNAS Nexus* **1**, (2022).

53. Sava-Segal, C., Richards, C., Leung, M. & Finn, E. S. Individual differences in neural event segmentation of continuous experiences. *Cerebral Cortex* **33**, 8164–8178 (2023).

54. Gu, C., Peng, Y., Nastase, S. A., Mayer, R. E. & Li, P. Onscreen presence of instructors in video lectures affects learners' neural synchrony and visual attention during multimedia learning. *Proceedings of the National Academy of Sciences* **121**, (2024).

55. Geerligs, L. *et al.* A partially nested cortical hierarchy of neural states underlies event segmentation in the human brain. *Elife* **11**, (2022).

56. Sols, I., DuBrow, S., Davachi, L. & Fuentemilla, L. Event Boundaries Trigger Rapid Memory Reinstatement of the Prior Events to Promote Their Representation in Long-Term Memory. *Current Biology* **27**, 3499-3504.e4 (2017).

57. Cohn-Sheehy, B. I. *et al.* The hippocampus constructs narrative memories across distant events. *Current Biology* **31**, 4935-4945.e7 (2021).

58. Reagh, Z. M., Delarazan, A. I., Garber, A. & Ranganath, C. Aging alters neural activity at event boundaries in the hippocampus and Posterior Medial network. *Nat Commun* **11**, 3980 (2020).

59. Magliano, J. P., Kurby, C. A., Ackerman, T., Garlitch, S. M. & Stewart, J. Mac. Lights, camera, action: the role of editing and framing on the processing of filmed events. *Journal of Cognitive Psychology* **32**, 506–525 (2020).

60. Magliano, J. P. & Zacks, J. M. The Impact of Continuity Editing in Narrative Film on Event Segmentation. *Cogn Sci* **35**, 1489–1517 (2011).

61. Dalrymple, K. A., Manner, M. D., Harmelink, K. A., Teska, E. P. & Elison, J. T. An Examination of Recording Accuracy and Precision From Eye Tracking Data From Toddlerhood to Adulthood. *Front Psychol* **9**, (2018).

62. Davis, R. The Feasibility of Using Virtual Reality and Eye Tracking in Research With Older Adults With and Without Alzheimer's Disease. *Front Aging Neurosci* **13**, (2021).