A long-context RNA foundation model for predicting transcriptome architecture

Ali Saberi[1,2,*], Benedict Choi[3,4,5,6,*], Simai Wang[7], Aldo Hernández-Corchado[1,8], Mohsen Naghipourfar[9], Arsham Mikaeili Namini[1,8], Vijay Ramani[3,7,†], Amin Emad[2,10,11,†], Hamed S. Najafabadi[1,8,12,†], Hani Goodarzi[3,14,†]

[1] Victor P. Dahdaleh Institute of Genomic Medicine, Montreal, QC, Canada

[2] Department of Electrical and Computer Engineering, McGill University, Montreal, Canada

[3] Department of Biochemistry and Biophysics, University of California, San Francisco, San Francisco, CA, USA

[4] Department of Urology, University of California, San Francisco, San Francisco, CA, USA

[5] Helen Diller Family Comprehensive Cancer Center, University of California, San Francisco, San Francisco, CA, USA

[6] Bakar Computational Health Sciences Institute, University of California, San Francisco, San Francisco, CA, USA

[7] Gladstone Institute for Data Science & Biotechnology, San Francisco, CA 94158

[8] Department of Human Genetics, McGill University, Montreal, QC, Canada

[9] Department of Bioengineering, University of California, Berkeley, CA USA

[10] Mila, Quebec AI Institute, Montreal, QC, Canada

[11] The Rosalind and Morris Goodman Cancer Institute, Montreal, QC, Canada

[12] McGill Centre for RNA Sciences, McGill University, Montreal, Canada

[14] Arc Institute, Palo Alto 94305, USA

*These authors contributed equally

†Correspondence: hani.goodarzi@arcinstitute.org, hamed.najafabadi@mcgill.ca, amin.emad@mcgill.ca, vijay.ramani@gladstone.ucsf.edu

Abstract

Linking DNA sequence to genomic function remains one of the grand challenges in genetics and genomics. Here, we combine large-scale single-molecule transcriptome sequencing of diverse cancer cell lines with cutting-edge machine learning to build LoRNA[SH], an RNA foundation model that learns how the nucleotide sequence of unspliced pre-mRNA dictates transcriptome architecture—the relative abundances and molecular structures of mRNA isoforms. Owing to its use of the StripedHyena architecture, LoRNA[SH] handles extremely long sequence inputs at base-pair resolution (~65 kilobase pairs), allowing for quantitative, zero-shot prediction of all aspects of transcriptome architecture, including isoform abundance, isoform structure, and the impact of DNA sequence variants on transcript structure and abundance. We anticipate that our public data release and the accompanying frontier model will accelerate many aspects of RNA biotechnology. More broadly, we envision the use

of LoRNA[SH] as a foundation for fine-tuning of any transcriptome-related downstream prediction task, including cell-type specific gene expression, splicing, and general RNA processing.

Introduction

Cell identity and behavior in higher eukaryotes is chiefly determined by transcriptome architecture—the quantitative levels (i.e., transcript abundances) and molecular structures (i.e., constitutively and alternatively spliced exons) of RNA isoforms. Transcriptome architecture is ultimately dictated by genomic sequence, as noncoding *cis*-regulatory elements within and outside transcribed genes dictate the starts, ends, splicing events, and expression levels of RNA molecules. Transcriptome architecture is heavily perturbed in diseases such as cancer, raising the need for technologies capable of learning how the genomic sequence and other factors shape transcriptomes.

Recent advances in deep representation learning have significantly advanced computational biology, enabling models that capture complex biological processes such as protein-DNA binding, chromatin accessibility, RNA splicing, alternative polyadenylation of transcripts, and post-transcriptional regulation. Large-scale pre-trained (i.e., 'foundation') models have further enhanced these capabilities, offering versatile tools to model data across various domains; in genomics specifically, foundation models like the Nucleotide Transformer (NucT) and DNABERT have shown potential in analyzing DNA sequences, enabling tasks such as sequence classification and variant effect prediction (1,2). To date, however, a model for joint representation of the full-context genomic sequence and associated RNA molecular structures, at nucleotide resolution, is lacking.

To build an RNA foundation model that addresses this gap, two critical components are needed: a comprehensive knowledgebase of RNA molecular structures produced from different genomic sequences, to be used as training data, and a model architecture that can capture the length and complexity of these molecular structures. To date, short read RNA sequencing has been the dominant source of data for inference of the transcriptome architecture. This type of data, however, does not capture the connectivity of transcription start sites, spliced exons, and 3' end sites, owing to the limited length of the reads (order of ~10^2 bp). Consequently, models trained on short read data fail to accurately model transcriptome architecture from end-to-end. In this study, we first report a new transcriptomic dataset, comprising high-quality long-read data from 26 cancer cell lines derived from ten distinct tissues (generated using PacBio IsoSeq platform). We combine our dataset with additional samples across mouse and human to build a large compendium of~100 million full-length reads with more than 7 billion training tokens, forming a strong foundation for building long-context models of transcriptome architecture directly from genomic sequence.

Two major architectures have been previously utilized to build RNA models. Convolutional neural networks, augmented by residual dilated convolution or attention layers (e.g., Borzoi (3) and

SpliceAI (4)), allow for long but coarse-grained modeling of gene expression and/or RNA processing as prediction tasks. Apart from the reliance of these models on short-read data for training, their convolutional blocks also limit the resolution at which long-range sequence interactions can be captured. Models based on the transformer architecture have emerged in recent years as alternatives, such as SpliceBERT (5), which leverages masked language modeling to learn RNA grammar solely from gene annotations. However, since attention mechanisms scale quadratically with sequence length, these models fail to handle full-length pre-mRNA. While Hyena operators (e.g., HyenaDNA (6), Evo (7)) have offered improvements for processing long stretches of sequence, they are genome models at their core, and are not designed to model transcriptome architecture.

In this study, we describe LoRNA[SH] (long-read RNA model with StripedHyena), the first self-supervised RNA foundation model that learns and predicts transcriptome architecture solely from long-context sequences. We use causal language modeling and an expanded RNA token set to train LoRNA[SH] on our large-scale full-length transcriptome architecture dataset. We demonstrate that LoRNA[SH] is capable of predicting the transcriptome architecture (i.e.the combination of transcript start/end sites, positions, lengths, combinatorial usage of exons, and abundances) in its entirety. LoRNA[SH] generates informative representations (embeddings) and calculates meaningful likelihoods for transcript isoforms, addressing the limitations of DNA-focused models in representing RNA transcript diversity. We also report the ability of LoRNA[SH] to surpass existing long-context genome models in several zero-shot prediction tasks: (1) absolute and relative isoform abundances for a given pre-mRNA sequence; (2) in-silico exon trapping frequencies, mimicking classic exon trapping assays in cells, and (3) nucleotide variant effects while controlling isoform structure. Furthermore, we utilized the isoform embeddings of LoRNA[SH] to train downstream predictive models for isoform abundance and cell-line specific isoform expression across multiple cell lines, demonstrating that these embeddings capture the *cis* and *trans* programs that control RNA regulation. Finally, given that LoRNA[SH] is a generative model, we show that synthetic transcripts generated by LoRNA[SH] mimic real-world transcript structure, with generated sequences showing coding and non-coding sequence properties similar to those of reference mRNAs. Our results, taken together, establish LoRNA[SH] as an RNA frontier model that effectively learns the grammar underlying the complex transcriptome architecture.

Results

Building a map of cancer cell-line transcriptomes using long-read RNA sequencing

To obtain a comprehensive snapshot of the transcriptomic architecture of the human genome, we generated a large IsoSeq (isoform-sequencing) dataset using the PacBio long-read RNA sequencing platform (8). Specifically, we profiled 26 cell lines representing cancers of ten distinct

tissues, including skin, lung, breast, liver, kidney, pancreas, colon, prostate, bone, and bone marrow (**Figure 1A**); we refer to the data generated from this collection as the Cancer Cell-Line Long-read (C2L2) compendium. C2L2 contains 35 million long-reads with a median read length of 3 kilobases and a maximum read length of 16 kilobases (**Figure 1B**), corresponding to an average of 1.5 million reads per sample (**Figure 1C**). In parallel, we also performed RNA-matched short-read RNA sequencing for all samples, with an average of 55 million reads per sample. This large dataset of matched long- and short-read data enabled systematic annotation and quantification of transcripts at isoform-resolution (see Methods).

As expected, we observed a high detection rate of polyA transcripts, including protein-coding genes and long non-coding RNAs (lncRNAs), in addition to expressed pseudogenes (**Figure 1D**). The majority of transcripts we identified from our compendium match previously annotated transcripts (**Figure 1E**). Nonetheless, we identified 1,307 novel genes alongside 23,691 known ones, and 10,139 novel transcripts in addition to the known 90,826 isoforms. Notably, most of these novel transcripts are composed of novel combinations of known annotated splice junctions, highlighting long-range interactions in RNA processing uncovered by IsoSeq (**Figure 1E**).

Figure 1. Overview of the Cancer Cell-Line Long-Read Compendium
(A) Visualization of the sampled cancer cell lines, mapped to their tissue of origin, with different colors representing distinct tissue types.
(B) Boxplot of read lengths across cell lines. The mid-line within each box represents the median read length, while the edges of the box indicate the first and third quartiles, encompassing the interquartile range (IQR). The whiskers extend to 1.5 times the IQR, capturing the range of most data points, and any data points outside this range are considered outliers and are not shown for clarity.
(C) Barplot of library sizes for each cell line, indicating the total number of reads obtained, in log10 scale.

(D) Stacked barplot of gene biotypes expressed (i.e., with at least one observed long read) in each cell line. **(E)** Stacked barplot categorizing inferred transcripts by structure, including full splice match, novel in catalog (i.e., novel combination of annotated splice junctions), and novel not in catalog (i.e., transcripts with at least one unannotated splice junction, following the notation used in (9)).

Transcript quantification using our data revealed highly reproducible transcriptomic profiles between biological replicates of each cell line (mean Pearson correlation 0.94). In contrast, different cell lines showed markedly different transcriptomic profiles (mean Pearson correlation 0.60; **Figure 2A**). The divergence of cell lines was also supported by pairwise differential isoform abundance analysis of cell lines, which revealed widespread differential expression of transcripts (**Figure 2B**). In total, we found 14,085 transcripts that were differentially expressed, FDR<0.05 (Benjamini–Hochberg False Discovery Rate), between at least two cell lines, with many transcripts showing significant differential abundance in multiple pairwise cell line comparisons (**Figure 2B**). In addition to absolute transcript abundance differences, we also observed widespread differential transcript usage (DTU; transcript usage is defined as the abundance of a transcript isoform relative to the abundance of all isoforms of the same gene). Specifically, we identified 3,658 transcripts whose relative usage was significantly different across cell lines (beta-binomial likelihood ratio test FDR<0.05, and DTU>0.5 between at least two cell lines; **Figure 2C**). Together, these observations underline the reproducibility of our cell line transcriptomic profiles and the extent of cell line-specificity of gene expression and isoform usage profiles across different cancer cell lines.

Figure 2. Overview of Transcriptome Diversity Across the Cancer Cell Line Long-Read Compendium
(A) Correlation heatmap showing the similarities and divergences across different cancer cell lines. Side bars represent the long-read library size and tissue of origin of each cell line. Here, columns of the heatmap are ordered the same as the rows. **(B)** Histogram of transcripts found to be differentially expressed between cell lines. The x-axis represents the number of pairwise cell line comparisons with significant differential abundance. **(C)** Summary of differential transcript usage (DTU) test. The x-axis represents the maximum transcript usage difference between any two samples. The y-axis shows the P-value of DTU in at least one cell line (likelihood ratio test based on beta-binomial regression). The upper-right quartile represents transcripts with a usage difference of at least 0.5 across the samples that are significant at FDR < 0.05.

Training a long-context RNA foundation model using causal language modeling

We designed LoRNA[SH] as a transcriptomic model capable of handling full-length pre-mRNA sequences at nucleotide resolution, along with the molecular structure of resulting mature mRNAs (**Figure 3A**). The architecture of LoRNA[SH] is based on the StripedHyena model, which combines multiple Hyena layers—data-controlled convolutional operators—with multi-head attention layers enhanced by rotary position embeddings, allowing LoRNA[SH] to handle sequences up to 64K nucleotides in length, a sufficiently long context to capture most pre-mRNAs (191,273 of 263,073 isoforms in our compendium). In addition to its long-context modeling capability, and unlike previous StripedHyena-based genome foundation models (7), LoRNA[SH] is a splice-aware model, owing to a number of key modifications. A key step in training LoRNA[SH] was our tokenization strategy, which allows the model to operate at single-nucleotide resolution, while capturing the overall RNA molecular structure by distinguishing between exonic, intronic, and untranscribed regions. LoRNA[SH] employs a specialized vocabulary of 16 effective tokens. In this vocabulary, exonic regions are encoded in uppercase (A, C, U, G), intronic regions in lowercase (a, c, u, g), special tokens (W, X, Y, Z) encode non-RNA flanking sequences, tokens H and M)represent human versus mouse species, and tokens S and P represent the transcription start site (TSS) and polyA site (PAS), respectively. To standardize the lengths of all isoforms of a gene by the longest isoform, LoRNA[SH] adds flanking upstream and downstream DNA sequences, making them identical in length and enabling more accurate and comparable likelihood assessments across different isoforms (**Figure 3B**).

LoRNA[SH] was trained using causal language modeling (CLM) with a next-token-prediction (NTP) objective (**Figure 3C**), allowing it to learn the sequential dependencies inherent to RNA sequences by predicting each nucleotide based on its preceding context, which is crucial for tasks like isoform abundance prediction and variant effect analysis. To pre-train LoRNA[SH], as mentioned above, we compiled a comprehensive dataset by aggregating long-read RNA-seq data across a compendium of human cancer cell lines. This dataset includes 52 samples (2 biological replicates for 26 cell lines) from the C2L2 project. In addition, we incorporated 149 other human and mouse samples from various long-read RNA-seq projects, including those involving normal tissues, different cancer types, COVID-19 studies, control groups, and drug-treated conditions. Altogether, our training dataset comprised 201 human samples, yielding 85 million Full-Length Non-Chimeric (FLNC) reads and resulting in 277,481 unique transcripts, of which 191,273 had more than one exon and a maximum standardized length of 64K nucleotides. To further augment our training dataset and enhance LoRNA[SH]'s ability to capture sequence conservation across species, we also included 46 mouse samples, contributing 9.5 million FLNC reads and 153,133 unique transcripts, of which 106,453 had more than one exon and a maximum standardized length of 64K nucleotides (**Table S1**). Altogether,

LoRNA[SH] was trained on 297,726 unique transcripts, comprising more than 7 billion training tokens (**Figure 3D**), each tokenized at the single-nucleotide level using our expanded RNA alphabet and annotated with species-specific identifiers.

We first carried out a systematic analysis of scaling laws to gain insights into the optimal balance between model size, training data size, and computational resources. This analysis revealed that, consistent with previous observations (7), performance improves with increasing model size up to a certain point, after which further scaling yields diminishing returns (**Figure 3E**). Additionally, we benchmarked LoRNA[SH]'s StripedHyena architecture against alternative architectures, including attention-only models and Hyena-only models. LoRNA[SH] consistently outperformed these alternatives, demonstrating its ability to process long RNA sequences while maintaining a strong contextual understanding, crucial for accurate splicing-aware RNA sequence modeling (**Figure 1F** and **Figure S1**). Based on this analysis, we selected a model consisting of 16 blocks with a width of 256 dimensions, totaling 6.5 million parameters. The architecture includes 13 Hyena layers interspersed with 3 rotary self-attention layers at regular intervals, providing an optimal balance of efficiency and performance (**Figure 3G**, also see Methods).

Figure 3. LoRNA^{SH} Model Architecture, Training, and Performance

(A) Schematic illustrating the transcription of pre-mRNA and the role of splicing machinery, which recognizes specific sequence features across the pre-mRNA to detect splice sites. The machinery then removes introns and joins exons to form mature mRNA.

(B) A toy example demonstrating LoRNA^{SH}'s tokenization approach given the genomic sequence and the exon-intron structure of different isoforms.

(C) Schematic of the causal language modeling used to train LoRNA^{SH}, integrating Hyena layers with attention mechanisms to accommodate long sequence inputs.

(D) Summary of training data, displaying number of transcripts and tokens for human and mouse datasets.

(E) Bar plot comparing model performance for StripedHyena, Hyena-only, or attention-only architectures. PPL: Perplexity. A lower perplexity indicates better performance.

(F) Plot showing scaling laws, where evaluation perplexity decreases with increasing model size, measured in a natural log number of parameters (ranging from 0.5 to 40 million). The x-axis represents the model size, while the y-axis shows evaluation perplexity (PPL). Different curves correspond to varying training budgets in FLOPs (Floating Point Operations, ranging from 1×10^{16} to 1×10^{17}), highlighting the balance between model size and computational resources. Beyond an optimal point, further increases in model size leads to overfitting and reduces performance.

LoRNA^{SH} Learns Splice Sites and Cis-regulatory Sequence Elements

To further evaluate the capabilities of LoRNA^{SH}, we explored its ability to identify key splicing sites and recognize regulatory sequence features involved in exon inclusion. We observed that, as expected, the isoform likelihoods predicted by LoRNA^{SH} are highly sensitive to splicing signals, particularly sequences around splice junctions. To evaluate the model's understanding of splicing signals and their regulatory elements, we analyzed an experimentally validated exon in the Grin1 gene in mice, which is known to be critically regulated by two downstream Rbfox1 motifs (10). Our analysis showed that the likelihoods assigned to splice site signals and Rbfox1 motifs were significantly higher in transcripts that included the exon compared to those that excluded it. This suggests that LoRNA^{SH} effectively recognizes not only the splice sites but also the associated elements that are crucial for splicing regulation (**Figure 4A, Figure S2**).

To evaluate LoRNA^{SH}'s understanding of the splicing code in a more systematic and comprehensive manner, we extracted all alternatively spliced cassette exon events from our inferred transcriptome based on the C2L2 dataset. For each cassette exon event, we selected two major isoforms: (1) the highest-expression isoform that includes the exon and (2) the highest-expression isoform that excludes the exon. For both donor and acceptor splice sites, we ablated the corresponding two-nucleotide splice site signals(*i.e.* GU and AG respectively), by replacing them with N (any nucleotide), and calculated the change in log-likelihood (Δlog-likelihood) between the mutant and reference isoform sequences. As expected, the decrease in log-likelihood was significantly greater ($p < 10^{-20}$; one-sided Wilcoxon signed-rank test) for isoforms that included the cassette exon compared to those that excluded it, for both donor and acceptor splice sites (**Figure 4B**). This indicates that the model is sensitive to exon-intron boundaries and effectively distinguishes between different splicing outcomes.

To further explore the model's recognition of splicing-related regulatory elements, we analyzed the impact of known RNA-binding protein (RBP) binding sites on isoform likelihoods. Using data from ENCODE, we selected binding sites of RBPs for two cell lines, K562 and HepG2 (11,12). For each cassette exon event and for each cell line, we selected the major isoform containing the exon. We selected the RBP binding sites that fall on the cassette exon or its flanking introns. Since we had already established that our model captures the importance of donor/acceptor splice sequences, we excluded binding sites falling within 5 nucleotides of the splice donor/acceptor. Then, to simulate the impact of RBP binding loss, we ablated each binding site via N replacement and subsequently calculated Δlog-likelihood versus unaltered isoform sequences. As a negative control, we selected random regions of similar length within each cell line that did not overlap known binding sites and similarly calculated Δlog-likelihoods (**Figure 4C, Figure S3**). The analysis revealed that sites with high Δlog-likelihood were significantly enriched for binding by known splicing factors, suggesting that the model has learned their essential role in exon inclusion or exclusion (**Figure 4D**).

Since the ENCODE dataset contains the binding sites for a subset of RNA-binding proteins, we sought to perform a more systematic search for other *cis*-regulatory elements that underlie LoRNA[SH]'s predictions. For this, we applied a sliding window analysis (a 20-nucleotide window with a stride of 10 nucleotides) to cassette exons and their flanking 256-bp intronic regions excluding splice sites ±5 nucleotides. For each window, the content was replaced with N and the Δlog-likelihood between the mutant and reference sequences was calculated (**Figure 4E**). The windows with the top 50% decrease in log-likelihood were used for de novo motif discovery using the MEME suite (13). Eight significantly enriched motifs were identified, and using Tomtom (14), we assigned these motifs to likely-RBPs that are known to impact splicing. Among the enriched motifs, three were similar to binding preferences of well-known splicing factors,including SRSF1, PCBP2, and a U-rich motif that matches the sequence recognized by U2AF2 and TIA1. The analysis demonstrated that sites with high Δlog-likelihood values exhibited a significant overrepresentation of these motifs, indicating that the model effectively captures the functional relevance of the splicing factors binding to them (**Figure 4F**).

In addition to the expanded nucleotide token set and the special species tokens, we also included tokens for s TSS and PAS. We used the PAS token embedding from LoRNA[SH] as a representative of the entire transcript isoform sequence because it encapsulates the contextual information from all preceding tokens that build the totality of a transcript isoform. Interestingly, these embeddings revealed distinct clusters of transcripts, which may be driven by the presence of different regulatory elements along the transcript. Some clusters were enriched for the presence of canonical polyadenylation-related signals, such as the well known upstream AAUAAA sequence and the downstream U-rich and GU-rich elements (15). We also identified enrichment of other, less characterized, motifs in other clusters, such as CUCC and AUCAA motifs at the polyA site (**Figure**

3F). Together, our observations highlight the ability of LoRNA^SH in capturing regulatory information underlying RNA processing.

Figure 4. Inspection of Model's Estimated Likelihoods and Learned Embeddings

(A) Heatmaps showing average likelihoods for splice site signals and the Rbfox1 motif (+8 and +262 nucleotides upstream) matches in the Grin1 gene, comparing transcripts with exon inclusion versus exclusion. In this experiment, each nucleotide in the sequence was systematically mutated into all possible alternatives, generating seven mutated sequences plus the original reference sequencl. LoRNA^{SH} estimated the likelihood of each sequence, which was then normalized into a categorical probability distribution using the softmax function. The distribution highlights the probability of each sequence, where the only variation is a single nucleotide. A higher probability assigned to the sequence with the original reference nucleotide indicates that this nucleotide is critical for the model's predictions, demonstrating the model's sensitivity to specific nucleotide positions within RNA sequences.

(B) Scatter plot illustrating the Δlog-likelihood (ΔLL) for the deletion of donor (right) and acceptor (left) splice site signals in isoforms that include a cassette exon (x-axis) versus those that exclude the exon (y-axis). Attached to each scatter plot is a histogram representing the ΔLL distribution for each axis. The color scale of the scatter plot points represents density, with red indicating high density and blue indicating low density. P-values are calculated using a one-sided Wilcoxon signed-rank test.

(C) A schematic representation illustrating the methodology used to evaluate the impact of RNA-binding protein (RBP) motifs on splicing regulation. The positive set (top panel) shows the identification of RBP binding sites that overlap cassette exons and their flanking introns (excluding splice sites and ±5 nucleotides). Each binding site was then ablated (replaced with 'N'), and the corresponding change in log-likelihood (ΔLL) of the isoform sequence was calculated. The negative set (bottom panel) involved selecting random regions of similar length that did not overlap with known RBP binding sites, which were also deleted to calculate ΔLL. This allowed comparison between RBP-associated ΔLL and random sequence effects.

(D) Enrichment and depletion of splicing factors, as a gene-set, across the range of median Δlog-likelihood (ΔLL) across all RBPs. The heatmap displays the enrichment score (measured by log-transformed hypergeometric *p*-values (16)) of splicing-related RBPs as a function of increasing ΔLL. The ΔLL values were divided into 12 equally populated bins, with each heatmap entry representing either enrichment or depletion of splicing factors within the corresponding ΔLL bin. Colors indicate the magnitude of enrichment or depletion: gold signifies enrichment, while light blue signifies depletion. Statistically significant (adjusted *p*-value < 0.05) enrichments are outlined in red, and significant depletions are outlined in dark blue. The mutual information (MI) value and associated Z-score are provided to measure the association between the presence of specific gene-sets and changes in ΔLL. The Z-score represents the number of standard deviations of the actual MI compared to MIs obtained from randomly shuffled gene-sets, highlighting the strength of the relationship between gene-set presence and the effects of RBP binding site removal

(E) Top: A schematic representation illustrating the sliding window approach used on a cassette exon and its flanking 256-bp intronic regions, excluding splice sites and ±5 nucleotides. A 20-bp window slides with a stride of 10 nucleotides over these regions, and for each window, the content is replaced with 'N'. The Δlog-likelihood between the mutant (altered) and reference (unaltered) isoform sequences is calculated. Bottom: Among the eight significantly enriched motifs discovered, three were significantly matched (*q*-value < 0.05) to known splicing factors. The sequence logos represent these motifs and their associated splicing factors: SRSF1, PCBP2, and a combination of U2AF2 and TIA1.

(F) Motif Enrichment Analysis Based on Δlog-likelihood Scores. Heatmaps display the enrichment (representation) of motifs from sliding windows with significant Δlog-likelihood decreases, with scores shown on a blue (underrepresented) to gold (overrepresented) color scale. Motif discovery identified three motifs matching known splicing factor binding preferences—SRSF1, PCBP2, and U2AF2/TIA1—accompanied by sequence logos. Mutual information (MI) values and Z-scores quantify the strength of association between motif presence and Δlog-likelihood changes, with Z-scores indicating how far the observed MI deviates from random expectations. The enrichment analysis is described in D.

(G) UMAP visualization of PAS embeddings. For a few example clusters, the top enriched motifs near the poly(A) sites are shown, along with their positional biases. The e-values (E) indicate the statistical significance of motif enrichment, where lower values suggest stronger enrichment. The e-value, as reported by MEME, estimates the expected number of motifs with the same or higher log likelihood ratio, width, and site count in a similarly sized set of random sequences. Random sequences assume independent positions with letters chosen according to background frequencies.

LoRNA^SH Excels in Zero-Shot Prediction Across Diverse Transcriptomic Tasks

Zero-shot prediction is the ability of a model to make predictions on tasks it has not previously encountered during training. This capability indicates the model's ability to extract important, functional features of a sequence and understand their interactions, which in turn underlie the observations that are being predicted. To evaluate LoRNA^SH's zero-shot prediction performance, we tested the model on three distinct downstream tasks: isoform absolute abundance or relative usage prediction, in-silico exon trapping prediction, and pathogenicity prediction for non-coding variants.

Absolute Isoform Abundance Prediction

Transcript abundance is determined by a combination of *cis*-regulatory features in the genomic sequence (which may act at the DNA or RNA level). We evaluated LoRNA^SH's ability to predict the mean abundance across cancer cell lines using the PAS token likelihood, which encapsulates the model's understanding of the entire transcript. We reasoned that isoforms with higher likelihood represent combinations of sequence and molecular structure that, based on LoRNA^SH's internal model, are more consistent with expressed mRNAs; such isoforms are expected to be processed more frequently, which in turn results in higher mean isoform abundance. Indeed, we observed a significant correlation between LoRNA^SH likelihoods and absolute mRNA abundance (Pearson correlation of 0.15, *p*-value = 8.6e-237, **Figure 5A**). In contrast, two other state-of-the-art long-context genome models, HyenaDNA (6) and Nucleotide Transformer (1) showed poor correlation (Pearson correlations 0.01 and 0.02, respectively). We specifically benchmarked LoRNA^SH against these two models as, to our knowledge, they were the only models with a sufficiently long input context to enable whole isoform-level predictions. Interestingly, when the correlations are calculated for each gene separately, we see, on average, an even higher correlation between LoRNA^SH likelihoods and isoform abundances (mean Pearson correlation 0.19, **Figure 5A**), reflecting the ability to predict relative transcript usage across isoforms of each gene. These results underscore LoRNA^SH's ability to model transcript-level features that govern isoform abundance. It is notable that this performance is achieved without any task-specific fine-tuning. For instance, training a simple downstream linear model on PAS token embeddings as representations of isoform sequences increased the Pearson correlation with absolute mRNA abundances to 0.38 (**Figure S4**), without the need for fine-tuning LoRNA^SH end-to-end on this task .

Trapped Exon Abundance Prediction

Using exon trapping, a recent genome-wide study identified approximately 1.25 million genomic fragments across the human genome with the ability to act as autonomous exons, suggesting that many genomic sequences (far more than the set of annotated exons within known genes) can be

spliced if expressed in the right pre-mRNA sequence context (17). This dataset offers a unique opportunity to go beyond known genes and annotated exons and evaluate the rules of splicing learned by models in an entirely held-out dataset. To evaluate LoRNA^{SH}'s performance in predicting the abundances of these trapped exons, we performed an *in silico* exon trapping experiment by inserting each reported trapped exon along with 500 nucleotides upstream and downstream into the vector sequences used in the study. We then calculated the likelihood of the entire vector sequence, together with the RNA molecular structure expected from a successfully spliced trapped exon, using LoRNA^{SH}, and compared to the likelihood of the same sequence but with the RNA molecular structure expected from exon skipping. The resulting Δlog-likelihoods were indeed significantly correlated with experimentally observed trapped exon abundances (Pearson correlation 0.20, *p*-value = 2.1e-28, Figure **S5**), substantially higher than Nucleotide Transformer, SpliceAI (4) (a model specifically trained to predict splice junctions from pre-mRNA sequence), and HyenaDNA, which had correlations of 0.14, 0.13, and 0.03, respectively (**Figure 5B**).

Pathogenicity Prediction for Non-coding Variants

Unlike coding genetic variation, which may lead to altered protein sequence and function, pathogenic non-coding variants impact human health through regulatory processes that govern gene expression. There are many non-coding variants that fall within intronic sequences or untranslated regions of the gene—if functional, these variants can influence RNA processing and splicing, which may lead to pathogenic phenotypes. Accurate prediction of non-coding variants can directly impact our understanding of specific human diseases, can help interpret the results of genome-wide association studies, and even guide clinical diagnostics and/or therapeutic development (18,19).

To examine LoRNA^{SH}'s zero-shot ability to predict the pathogenicity of non-coding variants, we used a high-confidence subset of variants in the ClinVar dataset (2+ star-rated variants), excluding variants located in splice sites and the ±5 nucleotide flanking regions, and evaluated our ability to differentiate pathogenic/likely pathogenic variants from all other variants (variants of uncertain significance (VUS) and benign) based on the difference in likelihoods between reference and mutant sequences. LoRNA^{SH} achieved a strong area under the receiver operating characteristic curve (AUROC) of 0.98 and an area under the precision-recall curve (AUPRC) of 0.55 in this task. In comparison, SpliceAI scored an AUROC of 0.97 and an AUPRC of 0.45, while Nucleotide Transformer and HyenaDNA achieved AUROCs of 0.56 and 0.39, and AUPRCs of 0.013 and 0.011, respectively, **Figure 5C**). These results, obtained solely with next-token-prediction and without any task-specific fine-tuning, further highlight LoRNA^{SH}'s zero-shot performance abilities and its internal understanding of the splicing code.

Predicting Cis-Regulatory Effects of Somatic Mutations on Transcript Abundance

To assess LoRNA[SH]'s ability to predict the impact of somatic mutations on the transcriptome architecture, specifically through induction of new alternative splicing patterns and transcripts, we leveraged cell line-specific somatic mutations available in the DepMap database for our C2L2 cell line panel (20). Our goal was to determine how these mutations influence the likelihood of transcript isoforms in each cell line as their direct consequence. For this, we used LoRNA[SH]'s zero-shot prediction, without any additional training specific to the cell lines. Using SUPPA2 (21), we identified differentially spliced exons between pairs of cell lines within each tissue type. Focusing on mutations occurring near these differentially spliced events, we observed that the effect of the mutation on isoform likelihood was strongly associated with the observed changes in isoform expression. Our analysis revealed a significant Pearson correlation of 0.65 (p-value = 0.006) between the changes in likelihood and the changes in abundance for novel alternative splicing events (**Figure 5D**). For example, we noted a somatic mutation in the splice acceptor site of the *PRPS1* gene in the *H23* lung cancer cell line. LoRNA[SH] predicted that this mutation would favor intron retention, a prediction that was subsequently corroborated by long-read RNA sequencing data. The mutation-induced isoform, characterized by the retained intron, was specifically observed in *H23* cells but absent in *H1299* cells, consistent with LoRNA[SH]'s prediction of increased relative likelihood for the intron-retained isoform in *H23* cells (**Figure 5E**).

Figure 5. Model's Zero-Shot and Trained Models Prediction Performance on Downstream Tasks

(A) Top: Schematic of the experiment for predicting isoform absolute abundance based on the PAS token likelihood, illustrating how the model estimates the probability of isoform sequences. Bottom: The bar plots show the Pearson correlation coefficient (PCC) of our model's PAS token likelihood vs absolute isoform abundances across all transcripts (all isoforms in the C2L2 dataset), as well as those obtained using two other models. The boxplots show the correlation of the relative isoform usage versus likelihood within each gene. P-values are calculated using a one-sided Wilcoxon signed-rank test.

(B) Top: Schematic of the experiment for predicting trapped exon absolute abundance, detailing how the model evaluates exon inclusion. Bottom: The correlation between the Δlog-likelihood and the absolute abundance of trapped exons.

(C) Top: Schematic of the experiment for predicting variant pathogenicity based on the difference in likelihoods between wild-type and mutant sequences. Bottom: The bar plots show the AUROC (left) and AUPRC (right).In each panel, LoRNA[SH] is compared to other models on the same task.

(D) Correlation between changes in normalized isoform likelihood (ΔLL) and changes in exon inclusion (ΔPSI) for novel alternative splicing events caused by somatic mutations in various cell lines. Each point represents a novel transcript with a distinct alternative splicing event type (A3, A5, AF, AL, or RI).

(E) Comparison of isoform expression in *H23* and *H1299* lung cancer cell lines based on long-reads coverage for *PRPS1*. The sashimi plot (top) illustrates coverage differences between two *PRPS1* isoforms in *H23* (blue)

and *H1299* (yellow). The mutation that increases the relative likelihood of the isoform with the retained intron, based on LoRNA[SH] predictions is shown at the bottom.

(F) Pearson correlation coefficients between observed and predicted isoform abundance for 26 different cell lines, each represented by a distinct gradient boosting regressor trained on PAS token embeddings. Correlation coefficients are calculated only for isoforms encoded by chromosome 8, which were held out as a test set during model training and validation. Cell lines are colored according to their tissue of origin, which includes ten tissue types in total.

(G) Scatter plot of predicted versus observed isoform abundance for the *SW480* cell line test set. The intensity of points indicates density, with darker regions representing higher densities.

(H) Heatmaps showing the AUROC scores for prediction of differential expression of chromosome 8 isoforms (test set), determining whether an isoform is highly expressed in a particular cell line (row) compared to another cell line (column). Colors represent AUROC values ranging from 0.5 (red) to 1 (green). (Top) Results for lung tissue cell lines. (Bottom) Results for colon tissue cell lines.

Leveraging LoRNA[SH] Embeddings for Cell Line-Specific Transcriptomic Predictions

LoRNA[SH] was trained on human and mouse transcriptomes derived from diverse long-read RNA-seq datasets across multiple cell lines and tissues. To assess the model's generalization capacity and biological relevance, we developed cell line-specific predictive models utilizing the learned LoRNA[SH] embeddings as feature representations. Through this approach, we investigated the utility of LoRNA[SH]-generated sequence embeddings in representing biologically meaningful features that enable accurate cell type-specific predictions.

Our hypothesis, which is consistent with our earlier observations, was that a collection of splicing factors are responsible for regulating RNA processing in each cell line, and LoRNA[SH] has learned the underlying *cis*-regulatory elements that allows accurate prediction of isoform likelihoods. To demonstrate that this *cis*-regulatory grammar is captured by LoRNA[SH] and therefore can be linked to the *trans* factors active in every cell line, we used the PAS token embeddings of isoforms to train downstream cell line-specific models. Specifically, for each cell line, we trained a gradient boosting regressor to predict isoform abundance in that cell line based on its PAS token embeddings. The Pearson correlation coefficient between the observed abundance (logTPM) and the predicted abundance for different cell lines is depicted in **Figure 5E**. The correlations ranged from 0.34 for *H358* to 0.53 for *SW480* (**Figure 5F**), all statistically significant with a maximum p-value of 5e-11.

To further evaluate LoRNA[SH]'s ability to predict *trans*-acting effects, we conducted a differential expression analysis between pairs of cell lines within each tissue type (considering tissues with more than one cell line). We then trained, for each cell line pair (e.g., cell line A vs. cell line B), a downstream classifier that uses the PAS token embeddings to predict whether a transcript is significantly upregulated in cell line A compared to B (ground truth determined based on DESeq2 FDR < 0.05 and $\log_2$-fc > 1) The AUROC scores for all pairwise classification tasks within lung and colon tissues are depicted in **Figure 5G**, as examples. Results for other tissues are shown in **Figure S6**. As shown here, LoRNA[SH]'s embeddings can be used to learn the regulatory grammar shared by cell-line specific isoforms.

Sequences generated using LoRNA^{SH} capture the architecture of human transcriptome

To assess LoRNA^{SH}'s capability in capturing the structural characteristics of transcript isoform sequences and producing synthetic exons and introns, we tasked the model with generating 1,000 transcripts. The model was prompted with 'HS', where the 'H' token directed it to simulate human transcripts, and the 'S' token instructed it to initiate from the transcription start site (TSS) and continue until reaching the 'P' token, which denotes the polyA site (PAS) (**Figure 6A**). For comparative purposes, we also sampled 1,000 transcript sequences from the annotated human transcriptome.

The analysis of exon and intron lengths between the generated and reference sequences revealed that LoRNA^{SH} recapitulates the overall structural features of human isoforms (**Figure 6B,C**). Additionally, the comparison of exon counts (**Figure 6D**) indicates that the model accurately reproduces exon-intron architecture, effectively switching between these regions in a manner consistent with naturally occurring sequences. Overall sequence length distributions (**Figure 6E**) also suggest that LoRNA^{SH} generates full-length transcripts resembling those found in the human transcriptome. Moreover, we observed that SpliceAI-based scoring of splice junctions could not distinguish synthetic and real transcripts with a high degree of certainty (Wilcoxon rank-sum test, *p*-value = 0.06, **Figure 6F**), suggesting that LoRNA^{SH} is able to generate transcripts that, even based on other splicing models, are expected to be processed properly. It should be noted that these results were achieved without hyperparameter tuning for sequence generation.

Additionally, we processed the generated sequences by performing *in silico* splicing to remove intronic regions and connect exonic segments, thereby reconstructing the resulting mature mRNAs. We then searched for open reading frames (ORFs) within each sequence and analyzed the codon usage of the generated ORF sequences and compared it to that of human coding sequences. A Pearson correlation of 0.63 and a Spearman correlation of 0.63 were observed between the codon usage of the generated sequences and the reference human genome, indicating that, despite the low relative abundance of exonic tokens in the training data, LoRNA^{SH} has learned the overall structure of the human coding sequences in addition to the transcriptome architecture (**Figure 6G**). When comparing the lengths of ORFs from the generated sequences to those from reference human transcripts, we found that 46.76% of the generated sequences overlap with the reference ORF lengths (**Figure S7**). Although LoRNA^{SH} currently generates smaller sequences, it's important to note that this is achieved in a zero-shot generation setting, without any hyperparameter tuning for optimized sequence generation, with regards to transcript length of the resulting ORF lengths.

Figure 6. Comparison of Generated and Reference Transcript Sequences
(A) Schematic illustration of the procedure for transcript sequence generation using LoRNA[SH]. The process begins with providing a prompt to the model, either H or M, to condition the model on the species (human or mouse, respectively). The first token (nucleotide) is generated based on the prompt. Subsequently, each next token is generated based on the previously generated tokens, continuing this sequence until the model generates the token P, indicating the transcript's 3' end site, at which point the generation stops.
(B-F) Violin plots comparing key structural features between LoRNA[SH]-generated transcripts (red) and real human transcripts (gray). **(B)** Exon lengths, **(C)** intron lengths, **(D)** number of exons, **(E)** total sequence lengths, and **(F)** SpliceAI-predicted splice site probabilities are shown.
(G) Scatter plot comparing the codon usage in ORFs of generated transcript sequences versus reference human transcript sequences. Each point represents a distinct codon, with the x-axis representing codon usage in generated sequences and the y-axis representing codon usage in reference sequences. Outlier codons are labeled for clarity. The red line represents the trend of correlation, with a Pearson correlation of 0.63.

Discussion

Our results present LoRNA[SH] as a long-context RNA foundation model that accurately predicts transcriptome architecture directly from input genomic sequences. Building on a large number of prior efforts to model the transcriptome using deep learning (3–5,22), LoRNA[SH] innovates in two key ways: first, via training on the high-quality C2L2 long-read transcriptomic dataset spanning 26 different cancer cell lines (along with additional datasets); second, by incorporating StripedHyena operators

that enable input scaling to >60,000 tokens. The resulting model excels at a variety of zero-shot tasks currently unaddressed by existing models, including the prediction of isoform abundance and structure, prediction of trapped exon inclusion in a given sequence of interest, and prediction of pathogenic non-coding variants.

A key aspect of transcriptome architecture is the relative expression of all constituent isoforms. Here, LoRNA[SH]'s ability to predict isoform abundance suggests it has learned key sequence determinants of isoform splicing and abundance. Although the current iteration of our model is agnostic to cell type, we anticipate the broad usage of LoRNA[SH] as a foundation for future inquiries into the major drivers of cell-type specificity in transcriptome structure, including *cis-* and *trans-*acting regulatory factors governing alternative transcript start/end sites, exon usage, and isoform abundance. In this context, we leveraged LoRNA[SH]-generated embeddings to train cell line-specific models for predicting isoform abundance and differential expression. The results indicate that these embeddings capture not only general transcriptomic information but also cell line-specific nuances.

Another distinguishing feature of LoRNA[SH], compared to other existing models relevant to RNA processing, is its generative capability. Leveraging this, we demonstrated that prompting our model with the species and transcription start site tokens generates mRNA sequences with expected length distributions of exons and introns, splice junctions, and codon usage that closely resemble real transcripts. There are many possible future directions unlocked by this, including the design of transgenes with desirable splicing regulation patterns and expression levels.

Importantly, there are limitations to this current iteration of LoRNA[SH]. First, our model has a maximum context length of 64k nucleotides – this length covers ~80% of transcripts, excluding longer transcriptional units. Second, our training, though performed on long-read RNA sequencing data, only covers datasets from human and mouse. As operators like StripedHyena become more efficient, we anticipate both expanding context lengths beyond 64 kbp, and extending our long-read corpus of data across a broad range of evolutionary distinct species. Predictive models hold much promise for biological research, but there are both molecular and computational challenges that must be addressed before they become a standard component of molecular biology research workflows. Here, we addressed two of these issues, by training a computational model with increased context length, and by making it aware of pre-mRNA and spliced RNA sequence/structure, using molecular biological data that captures the full context of transcriptomes. Our resulting model, thus, represents a powerful starting ground for new inquiries into the factors that shape human transcriptomes during development and in disease.

Methods

Data Collection

Cell culture

All cells were cultured in a 37 °C 5% CO_2 humidified incubator and in growth medium supplemented with antibiotics including penicillin (100 units/mL), streptomycin (100 μg/mL) and amphotericin B (1 μg/mL). The following cell lines were cultured in DMEM high-glucose medium (Gibco) supplemented with 10% fetal bovine serum (FBS), glucose (4.5 g/L), L-glutamine (4 mM) and sodium pyruvate (1 mM): MCF7 (ATCC HTB-22), MDA-MB-231 (ATCC HTB-26), MDA-MB-453 (ATCC HTB-131), LS174T (ATCC CL-188), A375 (CRL-1619), PANC-1 (ATCC CRL-1469), C4-2B (ATCC CRL-3315), Hs 707(A).T (ATCC CRL-7448), HEK-293 (ATCC CRL-1573) and A2058 (ATCC CRL-3601). The next cell lines were cultured in RPMI-1640 medium (Gibco) supplemented with 10% FBS, L-glutamine (2 mM) and HEPES (25 mM): BxPC-3 (ATCC CRL-1687), LNCaP (ATCC CRL-1740), ZR-75-1 (ATCC CRL-1500), H358 (ATCC CRL-5807), H1299 (ATCC CRL-5803), Colo320 (DZMC ACC-144), H23 (ATCC CRL-5800), HCC44 (DZMC ACC-534), MIA PaCa-2 (ATCC CRL-1420) and K562 (ATCC CCL-243). The cell lines including HCT116 (ATCC CCL-247), SW480 (ATCC CCL-228) and SW620 (ATCC CCL-227) were cultured in McCoy's 5A (modified) medium (Gibco) with 10% FBS, glucose (3 g/L) and L-glutamine (1.5 mM). The lines A549 (ATCC CCL-185) and PC-3 (CRL-1435) were cultured in Ham's F-12K medium (Gibco) supplemented with 10% FBS and L-glutamine (2 mM). The HEPG2 line (ATCC HB-8065) was cultured in Eagle's Minimum Essential Medium (ATCC) supplemented with 10% FBS, L-glutamine (2 mM) and sodium pyruvate (1 mM). All cell lines were routinely screened for mycoplasma with a PCR-based assay and tested negative. They were also routinely authenticated using STR profiling at UC Berkeley Sequencing Facility.

RNA isolation

Cells were collected and lysed in TRIzol reagent (ThermoFisher). The lysate was mixed with chloroform and phase-separated in a phaselock gel tube heavy (Quantabio) by centrifugation. The aqueous phase containing RNA was then mixed with one volume of 100% ethanol, and column-purified using Zymo QuickRNA Miniprep kit with in-column DNase treatment per the manufacturer's protocol. RNA integrity (RIN ≥ 9) was confirmed using the 4200 Tapestation System (Agilent) prior to library construction.

Short-read and long-read RNA-seq

Short-read RNA-seq libraries were prepared using the SMARTer Stranded Total RNA-seq kit v3 (TaKaRa Bio) following the manufacturer's instructions. The libraries were sequenced on a NovaSeq 6000 instrument at UCSF Center for Advanced Technology. Long-read RNA-seq libraries were constructed using the NEBNext Single Cell/Low Input cDNA Synthesis & Amplification Module, PacBio Iso-Seq Express Oligo Kit and SMRTbell express template prep kit 3.0 according to the manufacturer's protocol. The libraries were sequenced on a PacBio Revio at UCSF.

Data Preprocessing

We used an in-house pipeline for long-read RNA-seq data processing, incorporating several critical tools within *Nextflow* to ensure reproducible data preparation. The workflow began with the IsoSeq pipeline, starting with *pbccs*, which was used to generate HiFi reads using raw subreads through circular consensus sequencing (CCS). These high-quality reads were then processed using *lima* to demultiplex the sequences based on barcodes and to remove cDNA primers. The *isoseq-refine* tool was subsequently applied for further refinement, including polyA tail trimming and concatemer removal, resulting in Full-Length Non-Chimeric (FLNC) reads that capture complete transcript structures. Following the generation of FLNC reads, the data were aligned to the reference genome using *minimap2* (23), employing the splice preset optimized for long-read spliced alignment. After alignment, *samtools* (24) was used to sort and index the BAM files. For transcript isoform quantification, we utilized *bambu* (25), a tool specifically designed for long-read RNA-seq data, operating in both discovery and quantification modes. In the discovery mode, *bambu* performed error correction on the reads and extended existing annotations to identify novel transcripts, effectively inferring the transcriptome by discovering previously unannotated isoforms. In the subsequent quantification mode, *bambu* quantified transcript abundance by associating read classes with specific transcripts, including both known and novel isoforms. By orchestrating these tools within *Nextflow*, we were able to automate and streamline the entire data processing workflow to ensure greater consistency and reproducibility.

Training Data

We curated a comprehensive dataset of transcript isoforms by aggregating long-read RNA-seq data from multiple sources. This dataset includes 52 samples (two biological replicates for 26 cell lines) from the C2L2 project, along with 149 additional human and mouse samples from other long-read RNA-seq projects. These projects span diverse biological conditions, including normal tissues, various cancer types, COVID-19 studies, control groups, and drug-treated conditions. In total, the dataset comprises 201 human samples with 191,273 multi-exon transcripts, and 46 mouse

samples with 106,453 multi-exon transcripts, each with a maximum standardized length of 65,536 nucleotides. The final dataset for LoRNASH training included 297,726 unique transcripts, providing over 7 billion single-nucleotide tokens annotated with species-specific identifiers (**Table 1**)

Table 1.Transcripts and tokens used to develop LoRNA[SH]

Each row shows the number of unique transcripts and nucleotide tokens from each species.

Species	Num. Transcripts	Num. Tokens
human	191,273	4,985,385,906
mouse	106,453	2,299,348,935
total	297,726	7,284,734,841

To assess LoRNA[SH]'s generalization performance, the data was split into training, validation, and test sets based on chromosome assignment (**Table 2**), with chromosome 10 reserved for validation and chromosome 8 designated as the test set.

Table 2. Training, validation, and test sets for LoRNA[SH]

This table shows the distribution of transcripts and tokens used for training, validation, and testing of LoRNA[SH], organized by species and chromosome assignment. Each row provides the number of transcripts and tokens in each split, along with the percentage of total tokens contributed by each set.

Species	Split	Chromosome	Num. Transcripts	Num. Tokens	% of Tokens
human	train	1–7,9,11–22,X,Y,M	179,089	4,653,411,260	93.34
human	validation	10	6,169	177,889,685	3.57
human	test	8	6,015	154,084,961	3.09
mouse	train	1–7,9,11–19,X,Y	96,504	2,084,601,665	90.66
mouse	validation	10	4,510	93,748,826	4.08
mouse	test	8	5,439	120,998,444	5.26

Model Architecture

StripedHyena architecture

LoRNA[SH] is based on StripedHyena (26), an architecture for long-sequence language modeling (27) that combines Hyena (28) and rotary self-attention operators (29). The StripedHyena architecture

can be described as a sequence of transformations applied to an input sequence $X \in \mathbb{R}^{L \times d}$ where L is the sequence length and d is the dimensionality of the model's hidden states. Each layer (block) in StripedHyena is either a Hyena layer or a rotary self-attention layer, interleaved to balance the strengths of convolutional and attention mechanisms. LoRNA[SH] consists of 16 blocks with a model width of 256 dimensions, where each block features sequence mixing and channel mixing layers to process information along the sequence and model width dimensions, respectively. Within the sequence mixing layers, LoRNA[SH] utilizes 13 hyena layers, alternated with 3 rotary self-attention layers at regular intervals. The channel mixing layers in LoRNA[SH] use gated linear units. Additionally, LoRNA[SH] applies root mean square layer normalization to the inputs of each layer.

Hyena layers

The Hyena layers in LoRNA[SH] are pivotal for efficiently capturing long-range dependencies in sequence data, offering a computationally efficient alternative to traditional attention mechanisms. The layers employ a blend of implicitly parametrized long convolutions and data-controlled gating functions, allowing them to process sequences with a computational complexity that scales sub-quadratically with the sequence length. While the self-attention mechanism captures global dependencies by computing pairwise interactions between all elements in a sequence—a powerful but computationally expensive approach with a complexity of $O(L^2)$—the Hyena mechanism achieves similar outcomes using a combination of implicit long convolutions and data-controlled gating mechanism. These convolutions can be efficiently computed using the fast Fourier transform (FFT), allowing the Hyena mechanism to model dependencies over varying scales without explicit pairwise comparisons. This approach results in a more scalable complexity of $O(NDL(\log L + D))$, where N is the order of the Hyena operator, D is the model width, and L is the sequence length. Additionally, while self-attention requires explicit positional encodings to maintain the order of tokens in a sequence, Hyena uses a combination of positional encoding and windowed convolutions to encode positional information implicitly, offering greater flexibility in handling sequences of varying lengths. Detailed information of the architecture can be found in Poli et al. (28).

Self-Attention Layers

Self-attention mechanisms are integral to LoRNA[SH]'s ability to model intricate dependencies between tokens in a sequence, regardless of their positions. Originally introduced in the Transformer architecture (29), self-attention computes the importance of each token in the sequence relative to others, enabling the model to focus on relevant parts of the sequence for a given task.

Given an input sequence $X \in \mathbb{R}^{L \times d}$, self-attention operates by computing three matrices: queries Q, keys K, and values V:

$$Q = XW_Q, \quad K = XW_K, \quad V = XW_V$$

where $W_Q, W_K, W_V \in \mathbb{R}^{d \times d_k}$ are learnable weight matrices, and d_k is the dimensionality of the queries and keys. The attention scores are computed as:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right) V$$

The softmax function ensures that the attention weights sum to one, allowing the model to distribute its focus across the sequence. The division by d_k is a scaling factor that stabilizes gradients during training.

In LoRNA[SH], the attention mechanism is enhanced by rotary position embeddings (RoPE) (30), which encode positional information by rotating the query and key vectors:

$$Q_i' = Q_i \cdot \cos(\theta_i) + K_i \cdot \sin(\theta_i), \quad K_i' = K_i \cdot \cos(\theta_i) - Q_i \cdot \sin(\theta_i)$$

where θ_i is a rotation angle that depends on the relative position of token i in the sequence. RoPE effectively captures relative positional relationships, allowing the model to distinguish between different token orders while maintaining position invariance.

Tokenization

In LoRNA[SH], RNA sequences are tokenized at a single-nucleotide resolution, with an effective vocabulary of 16 tokens from a total of 32 characters. The tokenization process can be described mathematically as follows: Given an RNA sequence $S = (s_1, s_2, \ldots, s_L)$ of length L, each nucleotide s_i is mapped to a token t_i from the vocabulary V. The tokenization function $f : S \to T$ maps the sequence S to a sequence of tokens $T = (t_1, t_2, \ldots, t_L)$, where $t_i \in V$.

For exonic sequences, the nucleotides are encoded using uppercase tokens A, C, G, U, while intronic sequences use lowercase tokens a, c, g, u. Additionally, special tokens W, X, Y, Z are used to encode non-RNA (DNA) sequences flanking the transcripts, representing nucleotides A, C, G, and T, respectively. Tokens S and P mark the transcription start site (TSS) and polyA site (PAS), respectively. The tokens H and M are used to specify whether the sequence belongs to a human or mouse, respectively.

Training Procedure

LoRNA[SH] was pre-trained using causal language modeling (CLM) with a next token prediction (NTP) objective. This task involves predicting the next token in a sequence based on its preceding context, a process critical for learning the sequential dependencies inherent in RNA sequences. The

training objective is to minimize the cross-entropy loss, which measures the divergence between the predicted token distribution and the actual distribution:

$$L_{\mathrm{CE}} = -\frac{1}{N} \sum_{i=1}^{N} \log p(y_i | x_i)$$

Here, L_{CE} is the cross-entropy loss, N is the number of tokens in the sequence, y_i is the true token at position i, and $p(y_i | x_i)$ is the predicted probability of token y_i given the input context x_i.

From a probabilistic standpoint, cross-entropy measures the difference between two probability distributions: the true distribution and the predicted distribution. In the context of LoRNA[SH], the true distribution is the actual sequence of tokens in the RNA sequence, while the predicted distribution is the model's output probabilities for each token. Cross-entropy quantifies how well the probability distribution predicted by the model matches the true distribution. A lower cross-entropy value indicates that the predicted probabilities are closer to the true labels, reflecting higher confidence and accuracy in the model's predictions. In statistical terms, minimizing the cross-entropy loss is equivalent to maximizing the likelihood of the observed data under the model, a principle known as Maximum Likelihood Estimation (MLE). The MLE approach seeks to find the model parameters θ that maximize the likelihood function:

$$\hat{\theta} = \arg \max_{\theta} \prod_{i=1}^{N} p(y_i | x_i; \theta)$$

Taking the negative log of the likelihood gives us the cross-entropy loss:

$$L_{\mathrm{CE}}(\theta) = -\sum_{i=1}^{N} \log p(y_i | x_i; \theta)$$

Minimizing this loss function is equivalent to finding the parameter set θ that makes the observed data most probable under the model, thereby optimizing the model's predictions.

Perplexity, derived from cross-entropy, is a commonly used metric for evaluating language models. It is defined as:

$$\mathrm{Perplexity} = 2^{L_{\mathrm{CE}}}$$

Perplexity can be interpreted as the exponential of the average log-loss per token, measuring the model's uncertainty in predicting the next token.

Scaling Laws and Comparison with All-Hyena and All-Attention Architectures

In our study, we conducted a comprehensive scaling law analysis to compare the performance of various model architectures under a compute-optimized protocol. The primary objective was to determine the optimal balance between model size and dataset size to maximize the efficiency of computational resources. Our experiments explored model sizes ranging from 0.5 million to 40 million

parameters, maintaining a fixed context length of 65,536 tokens. To ensure the reliability of our results, we gradually reduced the learning rate and repeated the experiments until convergence was achieved. Model performance was evaluated using the perplexity metric, which measures the model's accuracy in predicting the next token in a sequence—a lower perplexity indicates better performance.

To carry out the scaling law analysis, we defined a series of compute budgets ranging from 1×10^{16} to 1×10^{17} FLOPs. For each budget, we calculated the FLOPs required to process a fixed input size, representing the "cost" of running the model. We then identified the compute-optimal allocation by selecting a range of model sizes and determining the number of training tokens needed to fully utilize the compute budget. To pinpoint the optimal compute allocation, we fitted a second-order polynomial to the relationship between log model size and perplexity. The minimum point of this function indicated the compute-optimal point, which signifies the most efficient allocation of model size and training tokens for a given compute budget. This methodical approach enabled us to predict performance trends as model size, dataset size, and compute resources scale, offering valuable insights into the relative efficiencies of different architectures. For further details, please refer to (7,31).

To further evaluate the performance of LoRNA[SH], after identifying the optimal architecture—comprising 13 Hyena layers interleaved with 3 attention layers (totaling 16 layers)—we compared it against two other configurations: an All-Hyena model and an All-Attention model. The All-Hyena model replaces the attention layers with Hyena layers, resulting in 16 Hyena layers similar to the HyenaDNA architecture (6). Conversely, the All-Attention model replaces the Hyena layers with attention layers, resulting in 16 attention layers akin to the GPT architecture (32). All models were trained using the same hyperparameters and were allowed to train until the validation loss reached a plateau.

Motif Discovery Across PAS Embeddings Clusters

LoRNA[SH] is composed of 16 layers, with each layer progressively encapsulating more complex and abstract information from the input sequences. As the model deepens, it learns increasingly sophisticated concepts, patterns, and dependencies. To understand the type of information encoded within each layer, the embeddings from different layers can be analyzed to observe how the samples (transcripts) are distributed across these embeddings in the hidden space. Specifically, we focused on the penultimate layer's embeddings of the PAS token for each input sequence, using these embeddings as representations of the entire sequence.

To identify distinct patterns within these embeddings, we performed k-means clustering on the first 50 principal components of the embeddings, using a range of cluster numbers to identify the optimal number of clusters (by maximizing the silhouette value)—we found that the PAS embeddings were best described by 18 distinct clusters. To examine whether these clusters correspond to distinct

sequence features, we used *MEME-ChIP* (33) in the differential enrichment mode to identify motifs that were significantly enriched in each cluster compared to sequences of all other clusters, along with their localization profiles relative to the poly(A) site.

Grin1 Splice Sites and Rbfox1 Motifs Likelihood Analysis

LoRNA[SH] was trained using a next-token (nucleotide) prediction task, leveraging causal language modeling to develop a deep understanding of the biological language of pre-mRNA transcripts. This approach enables LoRNA[SH] to become a splice-aware RNA foundation model, capable of generating sequence embeddings and estimating their likelihoods. To evaluate how effectively the model understands regulatory elements, an *in silico* mutational scanning experiment was conducted to identify which input tokens (nucleotides) are critical for the model's likelihood estimation.

In this experiment, each token in the sequence was mutated into all possible alternatives, resulting in seven mutated sequences plus the original reference sequence—eight sequences in total. LoRNA[SH] then estimated the likelihood of each sequence. These likelihoods were normalized into a categorical probability distribution using the softmax function, where each element of the distribution represents the probability of the corresponding sequence. Since the only difference between the sequences is one token, the resulting probability distribution indicates the importance of the reference nucleotide to the model. A higher probability for the sequence with the reference token suggests that this nucleotide is critical for the model's predictions.

This experiment was performed on all tokens across all transcripts of the Grin1 gene in the mouse genome. Grin1 was chosen because previous research (10) had investigated Rbfox1 motifs located downstream of one of the cassette exons in Grin1 transcript isoforms. The analysis revealed that LoRNA[SH] assigns high likelihood scores to splice site signals across the gene. Furthermore, when examining the +8 and +262 tokens downstream of the exon reported in the referenced study, it was observed that the model recognizes the regulatory significance of Rbfox1 motifs, both in proximity to and at a distance from the cassette exon of interest. This demonstrates the model's capability to understand and predict key regulatory elements within transcript sequences.

Systematic Analysis of LoRNA[SH] Sensitivity to Splice Site Mutations

To systematically assess LoRNA[SH]'s sensitivity to splice site mutations, we first identified cassette exon events using *SUPPA2* (21) and selected representative isoforms that support the inclusion or exclusion of each event. For each cassette exon, we chose the isoforms with the highest coverage—one representing inclusion and one representing exclusion. For each representative isoform, we then removed (replaced with 'N') the splice site signal (two nucleotides in the intronic region) upstream or downstream of the cassette exon, representing acceptor or donor sites,

respectively, and calculated the corresponding Δlog-Likelihood. For all donor or acceptor splice sites, we obtained paired Δlog-Likelihoods for isoforms supporting cassette exon inclusion and those supporting exclusion. These pairs were plotted as points in scatter plots of Δlog-Likelihood in transcripts excluding versus including the exon (Figure B). The statistical significance of the differences in Δlog-Likelihoods between exon-inclusion and exon-exclusion isoforms was assessed using the one-sided Wilcoxon signed-rank test.

Systematic Analysis of LoRNA^{SH} Sensitivity to RBP Binding Sites

We obtained peak calling BED files (narrowPeak format) for 150 RNA-binding proteins (RBPs) in two cell lines, K562 and HepG2. The list of RBPs includes: AARS, AATF, ABCF1, AGGF1, AKAP1, AKAP8L, APOBEC3C, AQR, BCCIP, BCLAF1, BUD13, CDC40, CPEB4, CPSF6, CSTF2, CSTF2T, DDX21, DDX24, DDX3X, DDX42, DDX51, DDX52, DDX55, DDX59, DDX6, DGCR8, DHX30, DKC1, DROSHA, EFTUD2, EIF3D, EIF3G, EIF3H, EIF4G2, EWSR1, EXOSC5, FAM120A, FASTKD2, FKBP4, FMR1, FTO, FUBP3, FUS, FXR1, FXR2, G3BP1, GEMIN5, GNL3, GPKOW, GRSF1, GRWD1, GTF2F1, HLTF, HNRNPA1, HNRNPC, HNRNPK, HNRNPL, HNRNPM, HNRNPU, HNRNPUL1, IGF2BP1, IGF2BP2, IGF2BP3, ILF3, KHDRBS1, KHSRP, LARP4, LARP7, LIN28B, LSM11, MATR3, METAP2, MTPAP, NCBP2, NIP7, NIPBL, NKRF, NOL12, NOLC1, NONO, NPM1, NSUN2, PABPC4, PABPN1, PCBP1, PCBP2, PHF6, POLR2G, PPIG, PPIL4, PRPF4, PRPF8, PTBP1, PUM1, PUM2, PUS1, QKI, RBFOX2, RBM15, RBM22, RBM5, RPS11, RPS3, SAFB, SAFB2, SBDS, SDAD1, SERBP1, SF3A3, SF3B1, SF3B4, SFPQ, SLBP, SLTM, SMNDC1, SND1, SRSF1, SRSF7, SRSF9, SSB, STAU2, SUB1, SUGP2, SUPV3L1, TAF15, TARDBP, TBRG4, TIA1, TIAL1, TRA2A, TROVE2, U2AF1, U2AF2, UCHL5, UPF1, UTP18, UTP3, WDR3, WDR43, WRN, XPO5, XRCC6, XRN2, YBX3, YWHAG, ZC3H11A, ZC3H8, ZNF622, ZNF800, ZRANB2.

Using *SUPPA2*, we identified cassette exon events in our inferred transcriptome and selected the isoform with the highest expression in either K562 or HepG2 (depending on the cell line used in the narrowPeak data) to represent exon inclusion for each cassette exon. We then determined the overlap between RBP-bound regions and the regions of cassette exons, including their flanking introns but excluding splice sites and ±5 flanking nucleotides. To quantify the impact of RBPs on cassette exon inclusion, we mutated (replaced with 'N') each RBP-bound region, one at a time, within the representative isoform and calculated the Δlog-Likelihood between the mutant and reference (unaltered) isoform sequences. To serve as a negative control, we also randomly selected non-RBP regions of similar length distribution that did not overlap with any RBP-bound regions. These randomly chosen regions were mutated in a similar fashion, and the Δlog-Likelihood was calculated. For each RBP and non-RBP control region, we generated boxplots of Δlog-Likelihoods. We then sorted RBPs based on their median Δlog-Likelihood, showing that RBPs with a higher median Δlog-Likelihood were

more significantly enriched in the splicing gene set (splicing factors), indicating their crucial role in splicing regulation.

Discovery of Sequence Features (Motifs) to which LoRNA[SH] is Sensitive

For all identified cassette exon events, we focused on the cassette exon itself along with 256 bp of its flanking regions (both upstream and downstream), while excluding the splice site signals and the ±5 nucleotides surrounding them. We chose 256 bp as the flanking region length because it was computationally feasible while providing sufficient context for analysis. To determine which features contribute most significantly to cassette exon inclusion, we selected the isoform with the highest expression supporting exon inclusion as the representative isoform. We used a sliding window approach to systematically analyze the specific regions of interest. A window size of 20 nucleotides with a stride of 10 nucleotides was applied across the target regions. For each window, the content was replaced with 'N', and we calculated the Δlog-Likelihood between the mutant isoform (altered) and the reference isoform (unaltered). In total, we analyzed over 250,000 windows with corresponding Δlog-Likelihood values. We sorted the regions based on Δlog-Likelihood and selected the top 50% (those with Δlog-Likelihood values above the median) for further analysis. We then used the MEME suite to perform motif discovery within these high-impact regions. This analysis identified eight enriched sequence motifs, three of which were found to match known RBP binding sites using the Tomtom tool in conjunction with the Ray2013 dataset (34).

Zero-shot Prediction Tasks

Isoform Absolute Abundance

To assess LoRNA[SH]'s zero-shot prediction performance for isoform absolute abundance, we provided the entire pre-mRNA sequence of each transcript isoform into LoRNA[SH] and calculated the likelihood of the PAS (transcription termination site) token, denoted as "P", and compared to the average isoform abundance across all cell lines.

It is important to highlight that models like LoRNA[SH] and HyenaDNA, which utilize causal language modeling, compute likelihoods directly. In contrast, for models trained with masked language modeling (e.g., BERT), the pseudo-likelihood method is employed. Pseudo-likelihood assesses pretrained masked language models by sequentially masking each token in a sequence and calculating the log probability of the masked token given the remaining context, providing an estimate of the pseudo-log-likelihood (PLL) for that token. To determine the PLL for an entire sequence, these individual log probabilities are summed, yielding a comprehensive pseudo-log-likelihood score. In this analysis, we applied the pseudo-likelihood approach to calculate the PLL of the PAS token for the Nucleotide Transformer.

Trapped Exons Abundance Task

In exon trapping experiments, a vector sequence is used to contain a region into which an arbitrary sequence of nucleotides can be inserted. For this task, we utilized the exact vector sequence employed by (17) in their experiments. Their study reported approximately 1.25 million randomly fragmented genome sequences that were trapped as exons, with the abundance of these trapped exons measured and documented. This provided us with a comprehensive list of genomic regions and their corresponding potential to be spliced as exons.

To estimate the likelihood of a sequence fragment being trapped as an exon, we generated two sequences for each fragment. In both sequences, the vector sequence remained identical; however, in the first sequence, the genomic fragment was included as an intron (represented in lowercase, e.g., acgt), and in the second sequence, it was included as an exon (represented in uppercase, e.g., ACGT). We then fed both sequences into LoRNA^{SH} and computed their log-likelihoods.

The log-likelihood of the entire sequence was calculated by summing the log-likelihood of each token (nucleotide) given the preceding token. Next, we calculated the Δlog-Likelihood, which is the difference between the log-likelihood of the sequence with the exon versus the sequence with the intron. This Δlog-Likelihood was used as an estimator for the likelihood of the exon being trapped. We then compared the trapped exon's log-absolute abundance with the Δlog-Likelihood and measured the correlation between these values.

For the HyenaDNA and Nucleotide Transformer models, we could only estimate the likelihood (or pseudo-likelihood) of a single sequence, due to their identical tokenization for exonic and intronic regions.

Pathogenicity Prediction for Non-coding Variants

The ClinVar dataset (35) contains variants submitted by individuals, with each variant's significance described in terms of pathogenicity. Among the 2,743,456 variants in ClinVar, 2,490,892 are single nucleotide variants (SNVs). Of these, 382,645 SNVs have a review status of at least two stars, indicating that multiple submitters have provided criteria with no conflicts, and some variants may have been reviewed by an expert panel. Of these, 10,456 variants are located in intronic regions, with 6,867 of them positioned outside of splice sites and the ±5 nucleotide flanking regions. Our evaluation focuses on these intronic non-splice-site variants. In ClinVar, the clinical significance of a variant is classified into five categories: pathogenic, likely pathogenic, variant of uncertain significance (VUS), likely benign, and benign. By definition, "likely pathogenic" indicates a probability of 95% or higher that the variant is pathogenic, while "likely benign" suggests a similar probability of being benign. For our analysis, we merged the "pathogenic" and "likely pathogenic" labels into a single "pathogenic" category and combined the "likely benign" and "benign" labels into a "benign" category.

This resulted in three clinical significance labels for each variant: pathogenic, VUS, and benign. Among the 6,867 intronic non-splice-site variants in our dataset, 70 are classified as pathogenic, 352 as VUS, and 6,445 as benign. Given that VUS variants lack sufficient evidence to be categorized as either pathogenic or benign, distinguishing confirmed pathogenic variants from the rest is of practical importance. Therefore, we framed our task as a binary classification problem: identifying whether a variant is pathogenic or not, where "not" includes both VUS and benign variants. This classification task involved 70 pathogenic variants and 6,797 non-pathogenic variants.

For each variant in our evaluation set, we generated two transcript sequences: one with the reference allele and the other with the mutant allele. We input both sequences into LoRNA^{SH} to estimate the log-likelihood of the entire sequences and then calculate the Δlog-Likelihood, defined as the difference between the log-likelihoods of the reference and mutant transcript sequences. This Δlog-Likelihood was used as a score to classify the clinical significance of the variants. We then calculated the area under the receiver operating characteristic curve (AUROC) and the area under the precision-recall curve (AUPRC) based on these scores. For the Nucleotide Transformer model, it was not feasible to input the entire transcript sequence. Instead, we input the 1,024 nucleotides flanking the mutant site and estimated the delta-log-pseudo-likelihood for this model. Additionally, for the SpliceAI model, we obtained SpliceAI scores for all the variants and used these scores for classification.

Assessing Mutation Effects on Isoform Expression Using LoRNA^{SH} in a Zero-Shot Scenario

To evaluate LoRNA^{SH}'s capacity to predict the impact of somatic mutations on transcriptome architecture, we utilized cell line-specific mutation data from the DepMap database. Our analysis focused on assessing the model's ability to predict mutation-induced changes in transcript expression and alternative splicing patterns without additional cell line-specific training, implementing a zero-shot prediction framework. Initially, we employed SUPPA2 to identify differentially spliced exons between cell line pairs within each tissue type, concentrating our analysis on splicing events near the somatic mutation sites. The identified novel alternative splicing events were categorized into five distinct types: alternative 3' splice site (A3), alternative 5' splice site (A5), alternative first exon (AF), alternative last exon (AL), and retained intron (RI). For each identified mutation, we computed the normalized change in isoform likelihood (ΔLL) between reference and mutant sequences using LoRNA^{SH}. To validate these predictions, we quantified changes in exon inclusion levels (ΔPSI). The relationship between ΔLL and ΔPSI was evaluated using Pearson correlation analysis.

Predicting Isoform Abundance Using LoRNA^{SH} Embeddings

To assess the utility of the embeddings generated by LoRNA^{SH}, we used PAS token embeddings of isoforms to train downstream cell line-specific models for predicting isoform abundance. The

abundance data was obtained using MPAQT (36), which integrated long-read and short-read RNA-seq data from the C2L2 dataset. The target for prediction was the log-transformed TPM (transcripts per million) values. For each cell line, we trained a gradient boosting regressor using the *scikit-learn* library in Python. The PAS token embeddings generated by LoRNA[SH] served as the feature set, and the observed log-TPM values were used as the target. Each gradient boosting regressor was trained to predict the abundance of isoforms in its respective cell line, allowing us to evaluate the predictive capability of the embeddings. The regressor was trained with a data split strategy involving all chromosomes except 10 and 8 for training, chromosome 10 for validation, and chromosome 8 for testing. The performance of the models was evaluated by calculating the Pearson correlation coefficient between the predicted and observed isoform abundance values for each cell line on test (chromosome 8) isoforms.

Predicting Differential Isoform Expression Using LoRNA[SH] Embeddings

To evaluate LoRNA[SH]'s ability to predict differential isoform expression, we conducted differential expression analysis between pairs of cell lines within each tissue type, focusing on tissues with more than one cell line. Differential expression was determined using long-read RNA-seq data and analyzed with DESeq2 (37). For each pair of cell lines (e.g., cell line A vs. cell line B), we used DESeq2 to identify differentially expressed transcripts, labeling isoforms that were significantly upregulated (adjusted *p*-value < 0.05 and log2FoldChange > 1) in one cell line as positive and the rest as negative. We then formulated a binary classification task for each cell line pair, aiming to predict whether an isoform was significantly upregulated in cell line A compared to cell line B using the PAS token embeddings generated by LoRNA[SH]. It is important to note that these classification tasks were not symmetric—predicting highly expressed isoforms in cell line A versus cell line B represented a distinct task from predicting highly expressed isoforms in cell line B versus cell line A. We trained a random forest classifier using *scikit-learn* in Python for these prediction tasks. The classifier was trained with a data split strategy involving all chromosomes except 10 and 8 for training, chromosome 10 for validation, and chromosome 8 for testing. The Area Under the Receiver Operating Characteristic (AUROC) scores for the binary classification tasks were obtained for the test set (isoforms on chromosome 8).

Transcript Sequence Generation

To generate transcript sequences, we utilized a causal language modeling approach with the LoRNA[SH] model. Causal language models operate in an autoregressive manner, predicting the next token in a sequence based on the preceding context. This autoregressive nature allows these models to generate sequences in a coherent, step-by-step manner, maintaining both logical and semantic consistency throughout the sequence.

In our workflow, sequences were sampled from LoRNA[SH] using standard techniques for autoregressive models, such as top-k sampling and temperature-based decoding. These methods help strike a balance between exploration and exploitation, allowing the model to produce diverse yet meaningful outputs. LoRNA[SH] particularly benefits from the fast recurrent mode of its Hyena layers, which enhances computational efficiency by reducing both latency and memory requirements during sequence generation (38).

To guide the sequence generation process, we employed standard language model prompting techniques. This involved conditioning the model with a given prefix, which served as the initial context for generating the subsequent output. For species-conditional generation, we used a single token representing the desired species (H for human or M for mouse) as the prompt, enabling the model to generate transcript sequences specific to the chosen species.

While we have yet to extensively fine-tune and integrate advanced causal language modeling techniques and optimizations, our approach has already proven effective in generating coherent and biologically relevant transcript sequences. The generated sequences maintain key properties such as exon and intron lengths, the number of exons, and accurate splice site signals, showcasing the potential of LoRNA[SH] in transcript sequence generation.

Codon Usage Analysis of Generated Sequences

To evaluate the codon usage of sequences generated by LoRNA[SH], we prompted the model to generate over 12,000 human transcript-like sequences. Each generated sequence contained intronic regions represented in lowercase. To identify open reading frames (ORFs) within these sequences, we first performed in-silico splicing by removing the intronic (lowercase) regions. After splicing, we utilized the *orfipy* package in Python to identify ORFs within the sequences. We then extracted the codons from the identified ORFs and analyzed their usage within the generated sequence dataset. Codon usage was compared to that in human reference transcripts to assess how closely the generated sequences resembled natural human transcripts.

Code and Data Availability

Raw short- and long-read RNA-sequencing data generated in this study are available via GEO (accession numbers X and X). Reproducible notebooks, source data for the figures, and other processed data are available at https://github.com/csglab/lorna-manuscript. LoRNA[SH] is available at https://github.com/goodarzilab/lorna-sh.

Bibliography

1.   Dalla-Torre H, Gonzalez L, Mendoza Revilla J, Lopez Carranza N, Henryk Grywaczewski A, Oteri F, et al. The nucleotide transformer: building and evaluating robust foundation models for

human genomics. BioRxiv. 2023 Jan 15;

2. Zhou Z, Ji Y, Li W, Dutta P, Davuluri R, Liu H. DNABERT-2: Efficient Foundation Model and Benchmark For Multi-Species Genome. arXiv. 2023;

3. Linder J, Srivastava D, Yuan H, Agarwal V, Kelley DR. Predicting RNA-seq coverage from DNA sequence as a unifying model of gene regulation. BioRxiv. 2023 Sep 1;

4. Jaganathan K, Kyriazopoulou Panagiotopoulou S, McRae JF, Darbandi SF, Knowles D, Li YI, et al. Predicting Splicing from Primary Sequence with Deep Learning. Cell. 2019 Jan 24;176(3):535-548.e24.

5. Chen K, Zhou Y, Ding M, Wang Y, Ren Z, Yang Y. Self-supervised learning on millions of primary RNA sequences from 72 vertebrates improves sequence-based RNA splicing prediction. Brief Bioinformatics. 2024 Mar 27;25(3).

6. Nguyen E, Poli M, Faizi M, Thomas A, Birch-Sykes C, Wornow M, et al. HyenaDNA: Long-Range Genomic Sequence Modeling at Single Nucleotide Resolution. arXiv. 2023 Nov 14;

7. Nguyen E, Poli M, Durrant MG, Thomas AW, Kang B, Sullivan J, et al. Sequence modeling and design from molecular to genome scale with Evo. BioRxiv. 2024 Feb 27;

8. Au KF, Sebastiano V, Afshar PT, Durruthy JD, Lee L, Williams BA, et al. Characterization of the human ESC transcriptome by hybrid sequencing. Proc Natl Acad Sci USA. 2013 Dec 10;110(50):E4821-30.

9. Pardo-Palacios FJ, Arzalluz-Luque A, Kondratova L, Salguero P, Mestre-Tomás J, Amorín R, et al. SQANTI3: curation of long-read transcriptomes for accurate identification of known and novel isoforms. Nat Methods. 2024 May;21(5):793–7.

10. Gehman LT, Stoilov P, Maguire J, Damianov A, Lin C-H, Shiue L, et al. The splicing regulator Rbfox1 (A2BP1) controls neuronal excitation in the mammalian brain. Nat Genet. 2011 May 29;43(7):706–11.

11. Van Nostrand EL, Pratt GA, Shishkin AA, Gelboin-Burkhart C, Fang MY, Sundararaman B, et al. Robust transcriptome-wide discovery of RNA-binding protein binding sites with enhanced CLIP (eCLIP). Nat Methods. 2016 Jun;13(6):508–14.

12. Van Nostrand EL, Freese P, Pratt GA, Wang X, Wei X, Xiao R, et al. A large-scale binding and functional map of human RNA-binding proteins. Nature. 2020 Jul 29;583(7818):711–9.

13. Bailey TL, Elkan C. Fitting a mixture model by expectation maximization to discover motifs in biopolymers. Proc Int Conf Intell Syst Mol Biol. 1994;2:28–36.

14. Gupta S, Stamatoyannopoulos JA, Bailey TL, Noble WS. Quantifying similarity between motifs. Genome Biol. 2007;8(2):R24.

15. Tian B, Manley JL. Alternative polyadenylation of mRNA precursors. Nat Rev Mol Cell Biol. 2017 Jan;18(1):18–30.

16. Elemento O, Slonim N, Tavazoie S. A universal framework for regulatory element discovery across all genomes and data types. Mol Cell. 2007 Oct 26;28(2):337–50.

17. Stepankiw N, Yang AWH, Hughes TR. The human genome contains over a million autonomous exons. Genome Res. 2023 Dec 1;33(11):1865–78.

18. Gallagher MD, Chen-Plotkin AS. The Post-GWAS Era: From Association to Function. Am J Hum

Genet. 2018 May 3;102(5):717–30.

19. Peña-Martínez EG, Rodríguez-Martínez JA. Decoding Non-coding Variants: Recent Approaches to Studying Their Role in Gene Regulation and Human Diseases. Front Biosci (Schol Ed). 2024 Mar 1;16(1):4.

20. Tsherniak A, Vazquez F, Montgomery PG, Weir BA, Kryukov G, Cowley GS, et al. Defining a cancer dependency map. Cell. 2017 Jul 27;170(3):564-576.e16.

21. Trincado JL, Entizne JC, Hysenaj G, Singh B, Skalic M, Elliott DJ, et al. SUPPA2: fast, accurate, and uncertainty-aware differential splicing analysis across multiple conditions. Genome Biol. 2018 Mar 23;19(1):40.

22. Celaj A, Gao AJ, Lau TTY, Holgersen EM, Lo A, Lodaya V, et al. An RNA foundation model enables discovery of disease mechanisms and candidate therapeutics. BioRxiv. 2023 Sep 26;

23. Li H. Minimap2: pairwise alignment for nucleotide sequences. Bioinformatics. 2018 Sep 15;34(18):3094–100.

24. Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, et al. The Sequence Alignment/Map format and SAMtools. Bioinformatics. 2009 Aug 15;25(16):2078–9.

25. Chen Y, Sim A, Wan YK, Yeo K, Lee JJX, Ling MH, et al. Context-aware transcript quantification from long-read RNA-seq data with Bambu. Nat Methods. 2023 Aug;20(8):1187–95.

26. Poli M, Wang J, Massaroli S, Quesnelle J, Carlow R. StripedHyena: Moving Beyond Transformers with Hybrid Signal Processing Models.

27. Paving the way to efficient architectures: StripedHyena-7B, open source models offering a glimpse into a world beyond Transformers [Internet]. [cited 2024 Aug 22]. Available from: https://www.together.ai/blog/stripedhyena-7b

28. Poli M, Massaroli S, Nguyen E, Fu DY, Dao T, Baccus S, et al. Hyena Hierarchy: Towards Larger Convolutional Language Models. arXiv. 2023;

29. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention is all you need. arXiv. 2017;

30. Su J, Lu Y, Pan S, Wen B, Liu Y. RoFormer: Enhanced Transformer with Rotary Position Embedding. arXiv. 2021;

31. Kaplan J, McCandlish S, Henighan T, Brown TB, Chess B, Child R, et al. Scaling laws for neural language models. arXiv. 2020;

32. Brown TB, Mann B, Ryder N, Subbiah M, Kaplan J, Dhariwal P, et al. Language models are few-shot learners. arXiv. 2020;

33. Machanick P, Bailey TL. MEME-ChIP: motif analysis of large DNA datasets. Bioinformatics. 2011 Jun 15;27(12):1696–7.

34. Ray D, Kazan H, Cook KB, Weirauch MT, Najafabadi HS, Li X, et al. A compendium of RNA-binding motifs for decoding gene regulation. Nature. 2013 Jul 11;499(7457):172–7.

35. Landrum MJ, Lee JM, Riley GR, Jang W, Rubinstein WS, Church DM, et al. ClinVar: public archive of relationships among sequence variation and human phenotype. Nucleic Acids Res. 2014 Jan;42(Database issue):D980-5.

36.   Apostolides M, Choi B, Navickas A, Saberi A, Soto LM, Goodarzi H, et al. Accurate isoform quantification by joint short- and long-read RNA-sequencing. BioRxiv. 2024 Jul 13;

37.   Love MI, Huber W, Anders S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2. Genome Biol. 2014;15(12):550.

38.   [2310.18780] Laughing Hyena Distillery: Extracting Compact Recurrences From Convolutions [Internet]. [cited 2024 Aug 22]. Available from: https://arxiv.org/abs/2310.18780

Acknowledgements

This work was supported by grants from the Canadian Institutes of Health Research (CIHR) [PJT-173317] to HSN, Natural Sciences and Engineering Research Council of Canada (NSERC) [RGPIN-2019-04460] and the Canada Foundation for Innovation (CFI) JELF [project 40781] to AE, support by the Arc Institute to HG, and resources provided by Calcul Québec (calculquebec.ca) and the Digital Research Alliance of Canada (alliancecan.ca) to HSN and AE. HSN holds a CIHR Canada Research Chair. HG is an Arc Institute Core Investigator. Research in the lab of HG is supported by the Arc Institute. AS holds a Doctoral Training Scholarship from Fonds de recherche du Québec – Nature et technologies (FRQNT).

Supplementary material

Figure S1. Evaluation Loss Curves for LoRNA[SH], All-Hyena, and All-Attention Architectures
This figure presents the evaluation loss curves for three different architectures: LoRNA[SH] (blue), which utilizes the StripedHyena configuration with 13 Hyena layers and 3 interleaved attention layers; All-Hyena (green), consisting of 16 Hyena layers; and All-Attention (red), composed of 16 attention layers. The x-axis represents the training steps, while the y-axis shows the evaluation loss. As the training progresses, LoRNA[SH] continues to decrease in loss, ultimately achieving the lowest evaluation loss. In contrast, the All-Hyena and All-Attention architectures reach a plateau at higher loss values, indicating that they have converged but with less optimal performance compared to the StripedHyena architecture in LoRNA[SH]. The dashed horizontal lines mark the points where each model's loss stabilizes, illustrating the superior convergence and lower loss of LoRNA[SH] relative to the other two models.

Figure S2. Likelihood of Nucleotide Positions in Grin1 Transcripts
This figure presents the likelihoods associated with each nucleotide position for all existing splice sites across eight transcripts of the *Grin1* gene in mouse. Each row corresponds to a specific transcript, and each column represents a nucleotide position within that transcript. The color scale reflects the likelihood of the entire sequence with the specific nucleotide at that position. Higher likelihoods (toward red) indicate that the nucleotide is critical for maintaining the sequence's overall likelihood, meaning that mutations at these positions would significantly reduce the sequence's likelihood. Positions with borders represent actual splice sites in the corresponding transcript, emphasizing their importance in splice site recognition and sequence stability.

Species	Project	Sample Name	Replicate	Cell Line	Tissue	Disease	Long-read Library Size (FLNC)	Matched Short-read	Short-read Library Size
human	210222_AH_IsoSeq	MDA_MB_231_1	Rep1	MDA-MB-231	Breast	Adenocarcinoma	215,480	Yes	78,619,497
human	210222_AH_IsoSeq	MDA_MB_231_2	Rep2	MDA-MB-231	Breast	Adenocarcinoma	21,764	Yes	61,129,519
human	210222_AH_IsoSeq	MDA_MB_231_LM2_1	Rep1	MDA-MB-231	Breast	Adenocarcinoma	188,469	Yes	46,542,662
human	210222_AH_IsoSeq	MDA_MB_231_LM2_2	Rep2	MDA-MB-231	Breast	Adenocarcinoma	297,809	Yes	51,777,684
human	210222_AH_IsoSeq	SW480tr_1	Rep1	SW480	Colon	Adenocarcinoma	170,607	Yes	91,491,910
human	210222_AH_IsoSeq	SW480tr_2	Rep2	SW480	Colon	Adenocarcinoma	144,349	Yes	17,711,573
human	210222_AH_IsoSeq	SW480tr_LVM2_1	Rep1	SW480	Colon	Adenocarcinoma	144,479	Yes	85,970,880
human	210222_AH_IsoSeq	SW480tr_LVM2_2	Rep2	SW480	Colon	Adenocarcinoma	217,188	Yes	70,846,292
human	20220415_neurondiff_IsoSeq	hESC_Day0_1	Rep1	hESC	Embryo		485,819	Yes	82,999,812
human	20220415_neurondiff_IsoSeq	hESC_Day0_2	Rep2	hESC	Embryo		1,311,078	Yes	77,792,645
human	20220415_neurondiff_IsoSeq	SOX10_Day41_1	Rep1				478,909	Yes	87,092,630
human	20220415_neurondiff_IsoSeq	SOX10_Day41_2	Rep2				1,636,498	Yes	89,362,340
human	20220415_neurondiff_IsoSeq	SOX10_Day61_1	Rep1				2,108,768	Yes	77,316,444
human	20220415_neurondiff_IsoSeq	SOX10_Day61_2	Rep2				811,637	Yes	84,619,618

Table S1. Summary of Long-Read RNA-seq Data Across Human and Mouse Samples
This table provides a comprehensive overview of the long-read RNA-seq datasets generated from various human and mouse samples. Each row represents a sample, detailing the species, project name, sample name, replicate number, cell line, tissue type, and associated disease. For samples with matched short-read data, the short-read library size is also provided. Here, the first rows are shown and the full Table (248 rows) is provided as a supplemental table.

Figure S3: Δlog-Likelihood Distribution for RNA-Binding Proteins (RBPs) Across K562 and HepG2 Cell Lines

The plot displays the Δlog-likelihood (left) and the number of affected transcripts (right) for various RNA-binding proteins (RBPs) in K562 and HepG2 cell lines. To assess the impact of RBP binding sites on transcript splicing, we identified overlaps between RBP binding sites and cassette exons, as well as their flanking introns (excluding splice sites ±5 nucleotides). We then removed these binding site sequences (replacing them with 'N') and calculated the Δlog-likelihood compared to unaltered isoform sequences. As a negative control (indicated as NonRBP), random regions of similar length that did not overlap with known binding sites were selected for the same procedure. The Δlog-likelihood values indicate the influence of RBP binding on exon inclusion or exclusion. High Δlog-likelihoods are particularly enriched for known splicing factors, underscoring their role in alternative splicing regulation.

Figure S4. Correlation Between Predicted and Observed Expression Using PAS Embeddings
This figure demonstrates the predictive power of transcription termination site (PAS) embeddings for gene expression. By training a simple linear model on PAS embeddings to predict gene expression, we achieve a correlation of 0.38 in a leave-one-chromosome-out cross-validation. The x-axis represents the predicted expression values, while the y-axis represents the observed (log10) expression values. The density of points highlights the relationship between predicted and observed expression, showing that PAS embeddings are highly informative for this task.

Figure S5. Correlation Between Trapped Exon Abundance and Sequence Likelihood
LoRNA^{SH} outperformed state-of-the-art models with a correlation of 0.20 between the delta log-likelihood of vector sequences when the trapped sequence is considered as an intron (lowercase tokenization) versus when it is considered as a trapped exon (uppercase tokenization) and the log of the absolute abundance counts. This smooth scatter plot visualizes the relationship between the change in log-likelihood (x-axis) and the log of exon abundance (y-axis), demonstrating LoRNA^{SH}'s ability to effectively predict trapped exon abundance based on sequence likelihood.

Figure S6: AUROC Scores for Predicting Upregulated Isoforms Across Cell Line Pairs

Heatmap showing the Area Under the Receiver Operating Characteristic (AUROC) scores for binary classification tasks predicting trans-acting effects across cell line pairs from different tissues. For each cell line pair (e.g., cell line A vs. cell line B), isoforms that were significantly upregulated in cell line A (adjusted p-value < 0.05 and log2FoldChange > 1) were labeled as positive, while the rest were labeled as negative. Using PAS token embeddings generated by LoRNA[SH], we performed classification tasks to predict whether an isoform was upregulated in one cell line compared to another. Notably, the tasks are not symmetric, meaning that predicting upregulated isoforms in cell line B compared to cell line A is a distinct task from the reverse. The AUROC values for cell lines from tissues such as skin, prostate, pancreas, and breast are shown. The comparison between MIA PaCa-2 and BxPC-3 is unavailable due to a lack of positive samples (upregulated isoforms) in the dataset.

ORF Length Histograms

Figure S7: Comparison of ORF Lengths Between Generated and Reference Human Transcripts
The overlaid histogram compares the length distribution of open reading frames (ORFs) in generated transcript sequences (red) and reference human transcript sequences (blue). The x-axis represents the log10-transformed ORF length, while the y-axis indicates the frequency of ORFs at each length. Approximately 46.76% of the generated sequences overlap with the reference human transcript ORF lengths. LoRNASH tends to generate smaller sequences, but this is without any hyperparameter tuning for optimized sequence generation.