LexicMap: efficient sequence alignment against millions of prokaryotic genomes

Wei Shen[1,2,*], John A. Lees[2], Zamin Iqbal[2,3,*]

[1] Department of Infectious Diseases, Key Laboratory of Molecular Biology for Infectious Diseases (Ministry of Education), Institute for Viral Hepatitis, the Second Affiliated Hospital, Chongqing Medical University, Chongqing, China

[2] European Molecular Biology Laboratory - European Bioinformatics Institute, Hinxton, UK

[3] Milner Centre for Evolution, University of Bath, UK

*Correspondence: shenwei356@cqmu.edu.cn (W.S.) and zi245@bath.ac.uk (Z.I.)

Abstract

Alignment against a database of genomes is a fundamental operation in bioinformatics, popularized by BLAST. However, the rate at which microbial genomes are sequenced has continued to increase, and there are now datasets in the millions, far beyond the abilities of existing alignment tools. We introduce LexicMap, a nucleotide sequence alignment tool for efficiently querying moderate length sequences (>250 bp) such as a gene, plasmid or long read against up to millions of prokaryotic genomes. A key innovation is to construct a small set of probe k-mers (e.g. n = 20,000) which are selected to efficiently sample the entire database to be indexed, such that every 250 bp window of each database genome contains multiple seed k-mers each with a shared prefix with one of the probes. Storing these seeds in a hierarchical index enables fast and low-memory alignment. We benchmark both accuracy as the query diverges from the match in the database, and potential to scale to databases of millions of bacterial genomes, showing that LexicMap achieves comparable accuracy with state-of-the-art, but with greater speed and lower memory use. We then benchmark LexicMap on small/diverse (GTDB) and large/redundant (AllTheBacteria and GenBank+RefSeq) databases. Alignment of a single gene against 2.34 million prokaryotic genomes from GenBank and RefSeq takes 3 (rare gene) to 33 (16S rRNA gene) minutes. Full alignment against all bacterial genomes is now possible in minutes with modest resources, supporting querying at scale which will be useful for many biological applications across epidemiology, ecology and evolution.

LexicMap produces output in standard formats including that of BLAST and is available under MIT license at https://github.com/shenwei356/LexicMap.

Keywords: sequence alignment, prokaryotic genomes, microbial genomes, large-scale data

Introduction

Alignment of sequences to a single reference genome is a well-studied problem[1-4]. For specified gap and mismatch costs, dynamic programming is guaranteed to obtain the optimal solution[5-7], but processing time scales as the produce of the reference genome size and the query size. This is too slow in practice, so the challenge is to find faster shortcuts that ideally are still guaranteed to give the optimal solution. Rapid progress has recently been made on this front[8-12].

The problem we set out to address is that of aligning to a database of genomes from across the
bacterial phylogeny, as popularised by BLAST[1]. As the amount of publicly available bacterial
sequence has grown over recent years, the proportion of bacterial genomes which web BLAST is
able to search has dropped exponentially[13]. The primary use cases of alignment to either all bacterial
genomes or a representative set are: determining where a specific sequence has been seen before,
finding the host range of a mobile element or gene, or locating probable orthologs for further
analysis. More broadly, the power to do this alignment against all prior prokaryotic sequences will
enable a wide range of specific analyses, just as BLAST has done with smaller datasets. Some
concrete examples were seen in how the approximate (k-mer based) matching to the 661k dataset[14]
has been used to search for plasmids[15-19], adhesins[19], diversity of vaccine targets[20], mutations of
interest[21], and phages[22].

This use-case differs from mapping-to-one-reference in two regards. First, the scale of the intended
database in terms of number and diversity. For example, the GTDB r214 representative set[23], one
genome for each of ~85 thousand bacterial species, contains 242 billion unique k-mers - about 65
thousand times more than in one genome. The diversity of gene content of bacteria is very large
because many have "open" pangenomes[24,25], so every new genome adds novel sequence content.
Other natural databases to query are larger, but heavily oversample pathogen species - combined
GenBank[26] and RefSeq[27] contain 2.3 million genomes, and AllTheBacteria[28] contains 1.8 million
high-quality genomes. Thus, there is a computational challenge to index these large databases.
Secondly, if mapping to one reference, one try to find the single most likely source of a query, but
rarely report all alignments; by contrast, in the BLAST-search use-case, a sequence could truly come
from multiple genomes, and all alignments would potentially be wanted by the user.

There are a number of high-performance tools which are good options for large-scale alignment.
MMseqs2[29] supports sensitive and scalable search of nucleotide sequences by searching translated
nucleotide databases using a translated nucleotide query. Minimap2[4], a long-read alignment tool
mainly designed for single large reference genome, can also be used for alignment against large
scale of microbial genomes, as it can partition input sequences and sequentially index and search
each partition. Two tools have demonstrated ability to scale to huge databases, each with a caveat
we would want to transcend. First, Phylign[13] compresses genomes by leveraging phylogenetic
information and then given a query, employs a k-mer based method COBS[30] to prefilter genomes
before performing base-level alignment with Minimap2. However, as we will show below,
prefiltering based on matching 31-mers is only effective for highly similar sequences; as the
divergence of the query increases beyond 10%, it becomes very likely to fail the prefilter[31]. It is
therefore essential for most useful searches to avoid this limitation. Second, it was shown that by
restricting to the 179/11264 species in AllTheBacteria[28] that have >200 genomes (which is 94% of
the data), a new BWT implementation, Ropebwt3[32], can leverage the within-species redundancy
and compress the data from ~2.8 TB (gzip-compressed) to just 27.6 GB. However, for our use case
it is important to be able to align to all the species in the dataset.

In this study, we look at the problem from a fresh perspective. In order to be able to do alignment,
we need to be able to find anchoring matches shared between a query and a genome, between which
we can do straightforward alignment. We create a relatively small set of probes (20,000 k-mers,

much smaller than the 59 billion *k*-mers in AllTheBacteria, or 292 billion in GTDB complete dataset)

that "cover" the genomes in the database in the sense that every 250 bp window contains several

(median 5) *k*-mers, each with a 7 bp prefix-match with one of our probes. Combining this core idea

with a range of computational innovations, detailed below, we are able to develop a standalone

alignment tool, LexicMap, which is able to align a gene to millions of genomes in minutes.

Results

Accurate seeding algorithm

In LexicMap, we first reimplement the sequence sketching method LexicHash[33], which supports

variable-length substring matches (prefix matching) rather than fixed-length *k*-mers, and use this to

compute alignment seeds. We outline the approach here and give full details in the Methods. First,

twenty thousand 31-mers (called "probes") are generated (Fig.1a), which can "capture" any DNA

sequence via prefix matching, as the probes contain all possible 7-bp prefixes. Then, for every

reference genome, each probe captures one *k*-mer across the genome as a seed – this is done via the

LexicHash, which chooses the *k*-mer that shares the longest prefix with the probe (Fig.1b, Fig.S2).

The number 20,000 above was chosen as a trade-off between index size, alignment accuracy and

performance (details below, and Table.S1, Table.S2, and Fig.S1).

However, since the captured *k*-mers (seeds) are randomly distributed across a genome, the distances

between seeds vary, and there is initially no distance guarantee for successive seeds (Fig.S3a). As a

result, some genome regions might not be covered with any seed, creating "seed deserts" or

sketching deserts[34], where sequences homologous to these regions could fail to align. Generally,

seed deserts sizes and numbers increase with larger genome sizes (Fig.S3a). To address this issue,

a second round of seed capture is performed for each seed desert region longer than 100 bp. New

seeds spaced about 50 bp apart are added to the seed list of the corresponding probe (Fig.1c and

Fig.1d). After filling these seed deserts, a seed distance of 100 bp is guaranteed (Fig.S3b) for non-

low-complexity regions, ensuring that all 250-bp sliding windows contain a minimum of 2 seeds,

with a median of 5 in practice (Fig.S3c). Additionally, the seed number of a genome may in practice

be lower or higher than the number of probes; the seed number is generally linearly correlated with

genome size (Fig.S4). Finally, by allowing variable length prefix-matches, we significantly increase

sensitivity compared with a *k*-mer-exact-matching approach, but the method remains vulnerable to

variation within the prefix region; we therefore extended LexicMap to additionally support suffix-

matching (see Methods).

119
Fig.1 | Seeding scheme of LexicMap for reference database. **a)** A fixed set of 20,000 31-mers (called
"probes") are generated, ensuring that their prefixes include every possible 7-mer. Seeds, each prefix-
matching one of these, will be found distributed across all database genomes, and chosen in such a way
as to have a window guarantee. **b)** LexicHash creates one hash function per probe and when applied to
a genome, it finds the *k*-mer with the longest prefix match, which is then stored as a seed. **c)** Each
genome is scanned to find seed deserts (regions longer than 100 bp with no seed); every *k*-mer within
this region has a 7-mer prefix match with at least one probe (because the probes cover all possible 7-
mers), and so seeds can be chosen with spacing of *x* bp (50 by default). **d)** Seeds are stored in a
hierarchical index. In fact, although not shown here for simplicity, the number of seeds is doubled to
support both prefix and suffix matching (details in Methods).

Scalable indexing strategies

To scale to millions of prokaryotic genomes, input genomes are indexed in batches to limit memory
consumption, with all batches merged at the end (Fig.S5a). Within each batch, multiple sequences
(contigs or scaffolds) of a genome are concatenated with 1-kb intervals of N's to reduce the sequence
scale for indexing. Original coordinates and sequence identifiers are restored after sequence
alignment. The complete genome or the concatenated contigs are then used to compute seeds using
the generated probes as described above, with intervals and gap regions skipped. Genome sequences
are saved in a bit-packed format along with genome information for fast random subsequence
extraction. After indexing all reference genomes, each probe captures up to millions of *k*-mers,
including position information (genome ID, coordinate, and strand). A scalable hierarchical index
compresses and stores seed data for all probes (see Methods and Fig.S5a) and supports fast, low-
memory variable-length seed matching, including both prefix and suffix matching (Methods and
Fig.S5b).

Efficient variable-length seed matching and alignment

In the searching step, probes from the LexicMap index are used to capture *k*-mers from the query
sequence (Fig.2a). Each captured *k*-mer is then searched in the seed data of the corresponding probe
to identify seeds that share prefixes or suffixes of at least 15 bp (chosen as a tradeoff between
alignment accuracy and efficiency, see Table.S3 and Fig.S6), using a fast and low-memory approach
(Methods, Fig.2b). The common prefix or suffix of the query and target seed, along with the position

information, constitutes an anchor. These anchors are grouped by genome ID before chaining. The
minimum anchor length of 15 bp ensures search sensitivity, while longer anchors (up to 31 bp)
provide higher specificity. Unlike minimizer-based methods such as Minimap2, which use fixed-
length anchors with a small window guarantee between anchors, LexicMap employs variable-length
anchors and does not guarantee a fixed window size between anchors. Consequently, the chaining
function (Function 1 in Methods section Chaining) assigns more weight to longer anchors and does
not consider anchor distance (see Methods). Next, a pseudo-alignment is performed to identify
similar regions from the extended chained regions (Fig.2d). Finally, the Wavefront alignment
algorithm is used for base-level alignment (Fig.2e). LexicMap's default output is a tab-delimited
table providing alignment details (Table.S4) for filtration or further analysis, and it also supports an
intuitive Blast-style pairwise alignment format (Fig.S7).

162
Fig.2 | LexicMap alignment workflow. **a)** The same LexicHash hash functions (one per probe) used
in the indexing step, are used here, applied to the query to capture one prefix-matching *k*-mer per
probe. **b)** For each probe, scan the seed data for that probe, to find prefix or suffix matches ≥ 15bp. The
common prefix or suffix constitutes an anchor. **c)** Chain the variable-length anchors using a modified
version of the Minimap2 algorithm. **d)** Fast pseudoalignment is followed by **e)** base-level alignment
using the Wavefront alignment algorithm. Note that in (b), only prefix matching is illustrated, and
suffix matching is not shown for simplicity.

Robustness to sequence divergence
LexicMap supports variable-length seed matches through prefix and suffix matching, allowing
greater tolerance to mutations compared to fixed-length seeding methods. To evaluate LexicMap's
robustness to sequence divergence, ten bacterial genomes from common species with sizes ranging
from 2.1 to 6.3 Mb (more details in Table.S5) were used to simulate queries of varying lengths and
similarities by introducing SNPs and indels with Badread[35] (see Methods). Blastn (with word sizes
of both the default 28 and 15), MMseqs2, Minimap2, Ropebwt3, were compared with LexicMap.
Additionally, COBS was compared as it is used in the prefilter step of Phylign, with a high
sensitivity setting (minimum fraction of aligned *k*-mers: 0.33).

Generally, as query identity increases, alignment rates of all tools improve, reaching nearly 100%

for query identities ≥ 95% when query length is ≥ 500 bp (Fig.3 and Table.S7). For queries of 1000
bp and 2000 bp, Blastn with a word size of 15 bp (abbreviated as Blastn (ws=15)) consistently
achieves the highest alignment rates at lower query identities, followed by MMseqs2, Ropebwt3,
Minimap2, LexicMap, and Blastn with the default word size of 28 bp. COBS shows a steeper drop-
off in alignment rates at query identities below 95%, which is expected given that it relies on
comparing fractions of matched k-mers ($k = 31$). For 250 and 500 bp queries, LexicMap outperforms
default Blastn at query identities below 93% and 92%, and surpasses Minimap2 at query identities
below 88 and 83% respectively. Performance for mutation-free queries is shown in Fig.S8.

Fig.3 | Robustness of aligners to sequence divergence. This is measured by simulating 250, 500,
1000, and 2000 bp reads with coverage of 30× from 10 bacterial genomes, adding mutations to achieve
sequence divergence between 0 and 20%, and then aligning back to the source genome. COBS is a k-
mer index, so here we show what proportion of the "reads" was detected as being present in the source
genome (rather than being aligned); this falls off very rapidly as similarity drops because each base
disagreement loses an entire 31-mer. For the other tools, we measure the proportion of reads that are
correctly aligned back to the source genome. Blastn (ws=15) stands for Blastn with a word size of 15.
Blastn (with no brackets) refers to the default setting of Blastn, with word size of 28. All data are
available in Table.S7.

Scalability to 1 million genomes
To evaluate the scalability of the above sequence alignment and search tools to increasing
prokaryotic genomes, we created seven genome sets at varying scales (ranging from one to one
million genomes) by randomly selecting non-overlapping prokaryotic genomes from GenBank and
RefSeq databases. Next, we built an index per set with each tool and then performed searches using
a query set containing a rare gene (SecY) and a 16S rRNA gene sequence (see methods).

For index building, generally, the index sizes of all tools are linear correlated with the number of

genomes (Fig.4a). In terms of memory requirements to index 1 million genomes, Ropebwt3 requires
the most memory (1,013 GB), followed by COBS (382 GB), Minimap2 (85 GB), LexicMap (75
GB), MMseqs2 (20 GB), and Blastn (2 GB). The indexing time of all tools vary (details in Table.S8),
ranging from 2.6 hours (MMseqs2) to 23.3 days (Ropebwt3). For databases larger than 10,000
genomes, LexicMap outperforms all other alignment tools in terms of alignment time and memory
usage. Note the log scale on the Y axis of Fig.4. For databases of 1 million genomes, LexicMap is
3× faster than the second fast alignment tool (Ropebwt3) while using only 1/115 of the memory (6.2
GB vs 717 GB); it is 89x faster than MMseqs2 and 39x faster than Minimap2.

217
Fig.4 | Scalability of sequence alignment/search tools. Benchmarking Blastn, COBS, LexicMap,
MMseqs2, Minimap2 and ropebwt3 at construction and then querying of indexes of datasets ranging
from 1 genome to 1 million genome**s. a)** Index size and memory requirements for index construction.
b) Search (meaning alignment for Blastn, LexicMap, MMseqs2, Minimap2, Ropebwt3, and search for
COBS) time and memory use. The query set consists of a rare gene (SecY) and a 16S rRNA gene
sequence. All tools return all possible matches. Performance data are in Table.S8 and S9.

224
Indexing performance on large databases
We further evaluated the performance and accuracy of LexicMap in the three largest and most
diverse datasets (see Methods): the GTDB r214 complete dataset with 402,538 prokaryotic
assemblies, the AllTheBacteria v0.2 high-quality dataset with 1,858,610 bacterial assemblies, and
GenBank+RefSeq with 2,340,672 prokaryotic assemblies (downloaded on February 15, 2024). We
benchmarked against Blastn, Minimap2, MMseqs2 and Phylign. Ropebwt3 was excluded from this
benchmark because it does not scale to this dataset (see memory use for indexing and querying in
the scaling section above) or return all alignments.

233
234   In terms of index sizes for AllTheBacteria, Phylign has the smallest size (Table 1), followed by
235   Blastn. LexicMap, MMseqs2, and Minimap2 have index sizes approximately 2.5, 4, and 8 times

larger than Blastn, respectively. For indexing time, MMseqs2 is the fastest, followed by Blastn, Minimap2, and LexicMap. For indexing memory, Blastn uses the minimum memory, followed by MMseqs2, Minimap2, and LexicMap. LexicMap uses almost twice as much memory for the GenBank+RefSeq dataset compared to the AllTheBacteria dataset, as the genomes in the former are more diverse.

Table 1 | LexicMap indexing performance on three datasets. Tbp: terabase; MB: megabyte (base 1000); GB: gigabyte (base 1000). LexicMap built indexes with the genome batch size of 5,000 for GTDB and 25,000 for the AllTheBacteria dataset and the GenBank+RefSeq dataset.

Dataset	Assemblies	Bases	Tool	Index size	Time	RAM
GTDB complete	402,538	1.5 Tbp	LexicMap	972 GB	9 h 39 m	71.6 GB
			Blastn	387 GB	3 h 11 m	718 MB
			MMseqs2	1,555 GB	55 m	7.6 GB
			Minimap2	3,409 GB	6 h 51 m	69.7 GB
AllTheBacteria	1,858,610	7.5 Tbp	LexicMap	4,305 GB	40 h 22 m	97.7 GB
			Blastn	1,932 GB	14 h 03 m	2.9 GB
			MMseqs2	7,551 GB	5 h 14 m	8.2 GB
			Minimap2	15,541 GB	32 h 08 m	76.5 GB
			Phylign	248 GB	/	/
GenBank+RefSeq	2,340,672	9.2 Tbp	LexicMap	5,455 GB	58 h 52 m	174.4 GB
			Blastn	2,368 GB	14 h 04 m	4.3 GB
			MMseqs2	9,259 GB	6 h 41 m	8.1 GB
			Minimap2	20,283 GB	42 h 30 m	76.2 GB

Alignment accuracy and performance on large databases

Four different types of queries were used to evaluate alignment performance (see Methods): a) a comparatively rare gene (Blastn returns seven thousand genome hits in GTDB r214 complete dataset with 402,538 genomes) - SecY from *Enterococcus faecalis*, b) a 16S rRNA gene from *Escherichia coli* , c) a 53kb plasmid, and d) 1033 different AMR genes (batch queries).

First, we aligned the queries with LexicMap, Blastn, MMseqs2, and Minimap2 against the GTDB complete index. For clearer comparison, we divided all alignment results into three groups (high, medium and low similarity) according to the query coverage and percentage identities and counted the number of correctly matched genomes (genome hits) – see Table 2.

In short – all tools find very similar numbers of high-similarity alignments, but LexicMap reports fewer low-similarity/fragmentary alignments. For the rare gene all tools return almost identical numbers of high-similarity alignments, but MMseqs2 and Blastn report about 10× more low similarity alignments than other tools. For the 16S rRNA gene, where we expect to find many alignments, LexicMap, Blastn (both settings) and MMseqs2 report ~61k high-similarity alignments, whereas Minimap2 only report ~16k. Counting all (high/medium/low-similarity) alignments, again all tools except Minimap2 found around 300k alignments (MMseqs2 found the most, 324k), whereas Minimap2 reports ~18k. In contrast, the 53kb plasmid, which is likely to present a different type of challenge, with many small fragmentary hits and some long hits with large deletions,

revealed other differences between the tools. LexicMap and Blastn (both settings) find 21 high-similarity matches, and Minimap2 finds 35, but MMseqs2 finds only 7. However Blastn (ws=15) and MMseqs2 find many more low-similarity alignments than other tools. Finally for the AMR genes, LexicMap, Blastn (both settings) and MMseqs2 find around 1.1 million alignments, whereas Minimap2 finds 943k. However again Blastn (ws=15) and MMseqs2 report 4× more low-similarity alignments.

In terms of speed, LexicMap is significantly faster than other tools for single queries, being 72×, 9×, and 4× faster than the second fastest tool Blastn, on the rare gene, 16S rRNA gene and plasmid respectively. Compared with MMseqs2, LexicMap is 872×, 103×, 83× faster for the same queries. For batch queries, LexicMap is 1.8× slower than Blastn. Regarding memory usage, LexicMap required less than 7 GB for single queries and 11 GB for 1033 AMR genes, whereas Minimap2 uses 20.2 GB and Blastn and MMseqs2 use more than 300 GB across all queries.

Table 2 | Alignment performance benchmarks on GTDB complete dataset. Hits stand for genome hits. Hits (high), hits (medium), and hits (low) mean the number of genomes with high-, medium-, and low-similarity matches, respectively. The details of alignment result grouping are available in Methods.

Query (length)	Tool	Hits (total)	Hits (high)	Hits (medium)	Hits (low)	Time	RAM
A rare gene	LexicMap	6,255	2,311	46	3,898	30 s	2.1 GB
1,299 bp	Blastn	7,121	2,311	47	4,763	2,171 s	351.2 GB
	Blastn(ws=15)	57,741	2,311	47	55,383	3,171 s	324.1 GB
	MMseqs2	67,537	2,304	54	65,179	26,174 s	400.7 GB
	Minimap2	2,312	2,312	0	0	17,208 s	20.2 GB
A 16S rRNA gene	LexicMap	306,064	60,999	69,293	175,772	303 s	5.2 GB
1,542 bp	Blastn	301,197	61,878	109,477	129,842	2,760 s	378.4 GB
	Blastn(ws=15)	301,197	61,878	109,477	129,842	3,291 s	378.4 GB
	MMseqs2	324,364	60,915	89,874	173,575	31,140 s	400.7 GB
	Minimap2	17,656	15,998	1,652	6	17,313 s	20.2 GB
A plasmid	LexicMap	65,029	21	2,808	62,200	539 s	6.8 GB
52,830 bp	Blastn	69,311	21	2,865	66,425	2,262 s	364.7 GB
	Blastn(ws=15)	91,847	21	2,865	88,961	3,082 s	142.8 GB
	MMseqs2	90,277	7	1,650	88,620	44,710 s	400.7 GB
	Minimap2	3,033	35	1,873	1,125	19,715 s	20.2 GB
1033 AMR genes	LexicMap	4,665,317	1,123,251	776,153	2,765,913	8,620 s	10.7 GB
1 kb (median)	Blastn	5,357,772	1,150,407	772,858	3,434,507	4,686 s	442.1 GB
	Blastn(ws=15)	10,877,544	1,150,410	840,464	8,886,670	4,561 s	311.9 GB
	MMseqs2	10,137,345	1,148,942	808,177	8,180,226	184,470 s	406.9 GB
	Minimap2	2,078,490	943,516	39,529	815,445	38,058 s	20.2 GB

Next, we compared LexicMap with Phylign on the AllTheBacteria dataset, which contains 1,858,610 bacterial genomes, including some species that are highly over-sampled. Here, Blastn could not be run due to its requirement of more than 2000 GB of memory. MMseqs2 was not included for its slow speed, and Minimap2 was not included for its slow speed and lower sensitivity for medium- and low-similarity matches. Across all queries, if including all (high/medium/low-

similarity) hits, LexicMap returns more genome hits than Phylign, but for high-similarity matches,
the number of alignments is very similar. These observations are as expected given the effect of
Phylign using a *k*-mer filter on diverged hits (see Fig.3). In terms of computation efficiency, for
single queries, LexicMap takes much less time than Phylign both in local and cluster mode (using
up to 100 nodes), while also using much less memory. However for batch querying, LexicMap is
much slower than Phylign in local and cluster modes, although in both cases LexicMap returns more
alignments.
296
297 Finally, we tested LexicMap on GenBank+Refseq, where it achieved similar performance on the
298 GenBank+RefSeq dataset (234 million prokaryotic genomes) as it does on the AllTheBacteria
299 dataset (Table S6).
300
301 **Table 3 | Alignment performance benchmarks on AllTheBacteria high-quality dataset[*].**

Query (length)	Tool	Hits (total)	Hits (high)	Hits (medi)	Hits (low)	Time	RAM
A rare gene	LexicMap	38,062	7,935	18	30,109	112 s	3.8 GB
1,299 bp	Phylign_local	7,937	7,935	1	1	1,848 s	77.6 GB
	Phylign_cluster	7,937	7,935	1	1	1,713 s	/
A 16S rRNA gene	LexicMap	1,857,974	496,867	556,951	804,156	1,552 s	14.8 GB
1,542 bp	Phylign_local	1,017,766	483,054	434,105	100,607	7,833 s	77.0 GB
	Phylign_cluster	1,017,766	483,054	434,105	100,607	5,141 s	/
A plasmid	LexicMap	485,295	25	9,201	476,069	1,891 s	15.2 GB
52,830 bp	Phylign_local	46,822	27	9,832	36,963	2,853 s	82.6 GB
	Phylign_cluster	46,822	27	9,832	36,963	2,374 s	/
1033 AMR genes	LexicMap	25,563,227	6,693,084	3,814,828	15,055,315	44,231 s	17.7 GB
1 kb (median)	Phylign_local	11,742,865	5,796,412	2,871,952	3,074,501	9,488 s	85.9 GB
	Phylign_cluster	11,742,865	5,796,412	2,871,952	3,074,501	8,029 s	/

302 * Alignment memory can not be accurately measured for Phylign running in multiple cluster nodes.
303

Discussion

BLAST was not the first tool to enable DNA alignment against a database, but its speed and
accessibility revolutionised bioinformatics. However since then, NCBI BLAST has been querying
an exponentially smaller fraction of public data[13]. The vast majority of the cellular tree of life
consists of bacteria and archaea; we continue to expand the tree through metagenomic sequencing,
and although the rate of discovery of new phyla has dropped, this is not the case for lower taxa[25].
Taken together with the prevalence of horizontal gene transfer in prokaryotes and a high number of
mobile genetic elements and their cargo, the levels of diversity are extremely high and continue to
grow. Further, the amount of clinical sequencing and deposition in archives continues to grow our
collection of pathogen sequence data, providing a year-by-year perspective on real-time evolution
and horizontal gene transfer. Thus now more than ever, the ability to align a query against a database
of representative genomes, or all genomes, is vital to modern biology and public health. Developers
of new antibiotics who find specific mutations confer resistance should be able to find out whether

those SNPs have been seen before, representing pre-existing resistance[36]. Genomic epidemiologists should be able to query a drug-resistance plasmid from a hospital outbreak against recently sequenced genomes from across the world[15] or track down any global samples containing outbreak informative SNPs[37]. Just as BLAST enabled hundreds of different studies that could not have been predicted at the time, re-enabling alignment against all bacteria will surely potentiate a wide range of new applications.

We have introduced our solution to this problem here. LexicMap takes a novel approach, constructing a fixed set of 20,000 probes (k-mers) which are guaranteed to have multiple (around 5 in this study) prefix matches in every 250 bp window of every genome in the database. The k-mer with the best prefix match for each probe in each genome is (called a seed and) stored in a hierarchical index, which can be used for alignment. This use of variable-length prefix-and-suffix-matching enables sensitive nucleotide alignment for queries above 250 bp long (though this is a user-tunable threshold). Our results show (Fig. 4) that LexicMap achieves a superior scalability to the other benchmarked alignment tools, with the fastest speed and the lowest memory usage, while maintaining a moderate index size and indexing efficiency. While achieving this scalability, LexicMap maintains a comparable sensitivity (meaning robustness to divergence of the query from the target) to state-of-the-art aligners.

In terms of user experience, the main advantages of LexicMap compared with current approaches include: 1) It provides direct alignment without a lossy prefilter step. 2) All possible matches, including multiple copies of genes in a genome, are returned. 3) The alignment is fast and memory efficient. 4) Unlike minimizer-based methods, seeds in LexicMap are interpretable and several utility commands are available to interpret probe (probe k-mers) and seed data (seed sequences and positions). 5) LexicMap is easy to install on multiple operating systems and can be used as a standalone tool without needing a workflow manager or compute cluster. LexicMap mainly supports small genomes including complete or partially assembled prokaryotic, viral, and fungi genomes. The maximum supported sequence length is 268,435,456 bp (2^{28}), so it can in principle also be applied to bigger genomes like human genomes with a maximum chromosome size of 248 Mb.

In terms of limitations, LexicMap only supports queries longer than 250 bp. It achieves a low memory footprint by storing a very large index on disk (5.46 TB for 2.34 million prokaryotic assemblies in GenBank+RefSeq), although we do note that the corresponding index for MMseqs2 or Minimap2 would be larger. Nevertheless, it would be desirable in future to reduce the size of this index. Finally, LexicMap is optimized for a small number of queries; improving batch searching speed is planned in the future.

Large-scale alignment against representative and complete genome databases has been a vital part of biology for decades, and as sequencing has accelerated, the need for scalable solutions has grown. LexicMap marks a step-change in scalability, achieving low-memory queries of the global corpus of bacterial data in minutes. Coupled with its ease-of-installation and use, without the need for workflow managers or a cluster, it has the potential to enable a wide range of analyses from ecology, evolution and epidemiology.

Online Methods

Probe generation

Probes, also referred to as "masks" in the LexicHash paper, consist of a fixed number ($m = 20,000$ by default) of k-mers ($k \leq 32$, $k = 31$ by default), which "capture" DNA sequences via prefix matching. A probe consists of two parts – the p-bp prefix and the remaining bases. To enable probes to match all possible reference and query sequences via prefix matching, all permutations of p-mers are generated as the base prefix set. The length of the prefix (p) is calculated to ensure that the total number of possible prefixes (4^p) does not exceed the total number of probes (m). For instance, when $m = 20,000$, p equals 7. Then, the base prefixes are duplicated to reach the number of probes m. Next, the suffixes of probes are randomly generated. The p'-bp ($p' = p + 1$) prefixes are required to be distinct to enable fast locating of the probe via the prefix of a k-mer through an array data structure. Finally, these m k-mers serve as probes that can match all potential sequence regions in both reference genomes and query sequences.

Seed computation

K-mers are encoded as 64-bit unsigned integers, with a binary coding scheme of A=00, C=01, G=10, and T=11. Following the original implementation of LexicHash, the hash value between a probe and a k-mer is computed using a bitwise XOR operation. The value of this hash is that smaller hash values indicate longer common prefixes between the probe and the k-mer, while a hash value of zero means the probe and the k-mer are identical.

For each reference genome or query sequence, all k-mers from both forward and backward strands are compared with probes that share the same p-bp prefix. Each probe retains only the k-mer with the minimum hash value, which might in principle be located at more than one position. K-mers of low-complexity are discarded by DUST algorithm[38] with a loose score threshold of 50. A 64-bit integer encodes each position's information, including the genome batch index (17 bits, see "indexing" section), genome index (17 bits), position (28 bits), the strand (1 bit), and the seed direction flag (1 bit, see "Seed data storage and variable-length seed matching" section). Ultimately, each probe captures one k-mer (as a seed) across the entire reference genome or query sequence, which shares the longest prefix with the probe.

However, due to the random distribution of captured k-mers (seeds), the distances between these seeds vary, and there is no guarantee of consistent distance between successive seeds. Consequently, some regions of the sequence might remain uncovered by seeds, leading to what are known as "seed deserts". These deserts are problematic because they can cause sequences homologous to the regions to fail to align. To address this issue, regions identified as seed deserts, which are longer than a certain threshold (100 bp by default), are extended by 1 kb both upstream and downstream. A second round of seed capture is then performed in these extended regions, and new seeds spaced about x (50 by default) bp apart within the region are added to the index of the corresponding probes. After filling these seed deserts, the total number of seeds may exceed the initial value of m.

Indexing

The input of LexicMap is a list of microbial genomes, with the sequences of each genome stored in separate FASTA files. These files can be in plain or compressed formats such as gzip, xz, zstd, or

405   bzip2. Each file must have a distinct genome identifier in the file name. To limit memory
406   consumption, genomes are indexed in batches, and all batches are merged at the end (Fig.S5a).
407
In each batch, genomes with any sequence larger than a genome size threshold (15 Mb by default),
such as non-isolate assemblies, are skipped. While if only the total length of sequences exceeds the
threshold, the genomes are split into multiple chunks and alignments from these chunks will be
merged in the searching step. Additionally, unwanted sequences within genomes, such as plasmids,
can be optionally discarded using regular expressions to match sequence names. Multiple sequences
(contigs or scaffolds) of a genome are concatenated with 1-kb intervals of N's, to reduce the scale
of sequences to be indexed. The original coordinates will be restored after sequence alignment. The
complete genome or the concatenated contigs are then used to compute seeds with generated probes,
as described above. Before this, any degenerated bases are converted to their corresponding
alphabet-first bases (e.g., N is converted to A). The genome sequence is then saved in a bit-packed
format (2 bits per base), along with associated genome information (genome ID, size, and sequence
IDs and lengths of all contigs) to enable fast random subsequence extraction. Simultaneously, seeds
and their positional information are appended to their corresponding probes and saved as seed files.
After processing all genomes in the batch, these seed files are merged using an external sorting
method once all batches have been indexed.
423
Seed data storage and variable-length seed matching
After indexing with all n reference genomes, each probe captured n or more seeds (k-mers, encoded
as 64-bit integers), with each seed potentially having one or more positions (also represented as 64-
bit integers), and there are m probes in total (20,000 by default). To scale to millions of prokaryotic
genomes, the storage of seed data needs to be both compact and efficient for querying. Since the
seeds of different probes are independent, the seed data are saved into c chunk files to enable parallel
querying (Fig.S5a). In each chunk file, the seed data of approximately m/c probes are simply
concatenated. For each probe, all seeds are sorted in alphabetical order, and the varint-GB[39]
algorithm is used to compress every two seeds along with their associated position counts. Since
seeds captured by the same probe share common prefixes, the differences between two successive
seeds are small, as are the position counts. As a result, these values can be stored using as little as
two bytes instead of 16 bytes.
436
Unlike the approach in the LexicHash paper, where captured k-mers from each probe are stored in
a prefix tree in main memory, here they are alphabetically sorted and saved in a list-like structure
within files. To enable efficient variable-length prefix matching of seeds, an index is created for
each seed data file (Fig.S5b). This index functions similarly to a table of contents in a dictionary,
storing a list of marker k-mers along with their offsets (pages) in the seed data file. Each marker k-
mer is the first one with a specific p''-bp subsequence ($p'' = 6$ by default) following the p-bp prefix
(all seeds of a probe share the same p-bp prefix). For a query sequence, one k-mer is captured by
each probe and searched within the corresponding probe's seed data to return seeds that share a
minimum length of prefix with the query k-mer. For example, searching with CATGCT for seeds
(with $p = 2$, $p'' = 1$) that have at least 4 bp common prefixes is equivalent to finding seeds in the
range of <u>CATG</u>AA to <u>CATG</u>TT. The process starts by extracting the p''-bp subsequence from
<u>CATG</u>AA (in this case, T) to locate the marker k-mer (e.g., CA<u>T</u>CAC) with the same p''-bp

subsequence in the same region. The offset information (page) of this marker k-mer is then used as
the starting point for scanning seeds within the k-mer range.
451
The index structure described above is extended to support the suffix matching of seeds. During the
indexing phase, after a seed k-mer is saved into the seed data of its corresponding probe, the k-mer
is reversed and added to the seed data of the probe that shares the longest prefix with the reversed
k-mer. Additionally, the last bit of each position data is used as a seed direction flag, indicating that
the seed k-mer is reversed. As a result, all seeds are doubled: there are "forward seeds" for prefix
matching and "reversed seeds" for suffix matching, which is achieved through prefix matching of
the reversed seeds. In the seed matching process, two rounds of matching are performed. The first
round involves prefix matching (as described above) in the forward seed data. In the second round,
the query k-mer is reversed and searched in the reversed seed data of the probe that shares the longest
prefix with the reversed k-mer.
462

Chaining
After searching all captured k-mers from a query in the seed data of all probes, seed pairs (anchors)
with different matched prefix/suffix lengths l are returned. These anchors indicate matched regions
between the query sequences $[y, y + l - 1]$ on the strand s_y and reference genome $[x, x + l - 1]$ on
strand s_x. First, the anchors are grouped by the genome IDs. Within each group, the anchors are
sorted by the following criteria: 1) Ascending order of start positions in the query sequence. 2)
Descending order of end positions in the query sequence. 3) Ascending order of start positions in
the target genome. Only one anchor is kept for duplicated anchors, and any inner anchors that are
nested within other anchors are removed. Then, overlapped anchors with no gaps are merged to a
longer one, while for these with gaps, only the non-overlapped part of the second anchor is used to
compute the weight (see below). Next, a chaining function modified from Minimap2 is applied to
chain all possible colinear anchors:

475
$$f(i) = \max\{ \max_{\substack{i>j\geq1 \\ x_i-G<x_j\leq x_i \\ y_i-G<y_j\leq y_i \\ d_{ji}\leq D}} \{f(j) + w_i - \gamma(g_{ji})\}, w_i\} \tag{1}$$

Here, $f(i)$, $f(j)$ are scores for anchors a_i and a_j, respectively. The anchor weight $w_i =$
$0.1 \times l_i^2$, where l_i is the length of the anchor a_i and $P \leq l_i \leq k$, with P being the minimum
anchor length (15 by default). The seed distance $d_{ji} = \max\{|y_i - y_j|, |x_i - x_j|\}$ and D is the
maximum seed distance (1,000 by default). The seed gap $g_{ji} = \left||y_i - y_j| - |x_i - x_j|\right|$, and G is the
maximum gap (50 by default). The gap penalty is calculated as $\gamma(g) = 0.1 \times g + 0.5 \log_2(g)$.
Additionally, a filter is applied to avoid non-monotonic increase or decrease in coordinates. For
cases where there is only one anchor, the length of the anchor must be no less than a threshold P'
(17 by default).
484

Alignment
In contrast to the case of minimizers or closed syncmers[40], seeds in LexicMap do not have a small
window guarantee. Hence a pseudo alignment algorithm is further used to find similar regions from
the chained region, extended by 1-kb in the upstream and downstream directions. K-mers ($k = 31$)

on both strands of the query sequence are stored in a prefix tree, and *k*-mers of a target region are
queried in the prefix tree to return matches of l_i' $(11 \leq l_i' \leq 31)$ in the extended chained region.
After removing duplicated anchors as above, the anchors are chained with the score function:

492
$$f'(i) = \max\{ \max_{\substack{i>j\geq 1 \\ x_i-G'<x_j\leq x_i \\ y_i-G'<y_j\leq y_i}} \{f'(j) + l'_i - g'_{ji}\}, l'_i\} \tag{2}$$

where G' is the maximum gap (20 by default), seed distance $g'_{ji} = \left| |y_i - y_j| - |x_i - x_j| \right|$. And

the chaining is banded (100 bp or 50 anchors by default). Besides, chained regions across the interval
regions between contigs are split. Next, regions are further extended in both ends, via a similar
pseudo alignment algorithm based on 2-mer matches.

Similar regions between the reference and query sequences are further aligned with a reimplemented
Wavefront alignment algorithm (https://github.com/shenwei356/wfa, v0.4.0), with a gap-affine
penalty (match: 0, mismatch: 4, gap opening: 6, gap extension: 2) and the adaptive reduction
heuristic (minimum wavefront length: 10, maximum distance: 50). Each alignment's bit score and
expect value (e-value) are computed with Karlin-Altschul parameter values for substitution score 2
and -3 (gap opening cost: 5, gap extension cost: 2, lambda: 0.625, K: 0.41) from Blastn's source
code.

Tools, reference genome datasets and query sequences
LexicMap v0.7.0, Blast++ v2.15.0, MMseqs2 v16.747c6, Minimap2 v2.28-r1209, Ropebwt3 v3.9-
r259, COBS (iqbal-lab-org fork v0.3.0, https://github.com/iqbal-lab-org/cobs), and Phylign
(AllTheBacteria fork https://github.com/AllTheBacteria/Phylign, commit 9fc65e6) were used for
testing. GTDB r214 complete dataset with 402,538 prokaryotic assemblies was downloaded with
genome_updater (https://github.com/pirovc/genome_updater, v0.6.3). GenBank+RefSeq dataset
with 2,340,672 prokaryotic assemblies was downloaded with genome_updater on February 15, 2024.
AllTheBacteria v0.2 high-quality genome dataset with 1,858,610 bacteria genomes and the Phylign
index were downloaded from https://github.com/AllTheBacteria/AllTheBacteria. Four query
datasets were used for evaluating alignment accuracy and performance: a preprotein translocase
subunit SecY gene CDS sequence from an *Enterococcus faecalis* strain
(NZ_CP064374.1_cds_WP_002359350.1_906), a 16S rRNA gene from *Escherichia coli* str. K-12
substr. MG1655 (NC_000913.3:4166659-4168200), a plasmid from a *Serratia nevei* strain
(CP115019.1), and 1033 AMR genes from the Bacterial Antimicrobial Resistance Reference Gene
Database (PRJNA313047). All files were stored on a network-attached storage server equipped with
HDD disks.

Simulating mutations
Ten bacterial genomes of common species (more details in Table.S5) with genome sizes ranging
from 2.1~6.3 Mb were used for simulating queries with Badread[35] v0.4.1 and SeqKit[41] v2.8.2. The
command, "badread simulate --seed 1 --reference $ref --quantity 30x --length $qlen,0 --identity
$ident,$ident,0 --error_model random --qscore_model ideal --glitches 0,0,0 --junk_reads 0 --
random_reads 0 --chimeras 0 --start_adapter_seq '' --end_adapter_seq '' | seqkit seq -g -m $qlen |
seqkit grep -i -s -v -p NNNNNNNNNNNNNNNNNNNNN -o $ref.i$ident.q$qlen.fastq.gz",

simulated reads with a genome coverage of 30×, a mean length of 250, 500, 1,000 or 2,000 bp and
mean percentage identities ranging from 80% to 100% with SNPs and indels. LexicMap, Blastn,
MMseqs2, Minimap2, Ropebwt3, and COBS were used to search simulated reads against the
reference genomes. Each tool built an index for each genome and searched or aligned reads with
the corresponding index. LexicMap built indexes and aligned with default parameters ($m = 20,000$,
$k = 31$, $P = 15$, $P' = 17$). Blast built indexes with default parameters and aligned reads with the
default task mode "megablast" using a word size of 28 (default) or 15, and the out format 6 was set
to output tabular results. MMseqs2 built indexes and aligned reads with the nucleotide mode, and
the format mode 4 was set to output tabular results. Minimap2 aligned reads with the "map-ont"
mode. Ropebwt3 built indexes (including .fmd, .ssa and .fmd.len.gz files) with default parameters
and aligned with the local alignment mode ("ropebwt3 sw"). COBS built compact indexes with $k =$
31 and a false positive rate of 0.3 and searched reads with a k-mer coverage threshold of 0.33.
Positions of alignment results from all tools except for COBS, were checked, and only those
overlapping with the source locations were counted for the computation of alignment rate. Unless
otherwise specified, all tests were performed in cluster nodes running with Intel(R) Xeon(R) Gold
6336Y CPU @ 2.40GHz with RAM of 500 or 2000 GB.
546
Scalability testing
Seven genome sets with 1, 10, 100, 1,000, 10,000, 100,000, and 1,000,000 non-overlapping
prokaryotic genomes randomly choosing from GenBank+RefSeq dataset were used for the
scalability test. The queries consist of a SecY and a 16S rRNA gene sequences mentioned above.
LexicMap, Blastn, MMseqs2, Minimap2, Ropebwt3, and COBS built an index for each genome set
and searched or aligned the queries against the corresponding index, with the options in the previous
tests. LexicMap returned all possible matches by default, while other tools were explicitly set to
return all matches. All tools used 48 CPUs. A Python script
(https://github.com/shenwei356/memusg) was used to record the time and peak memory usage.
Sequence alignment/searching was repeated four times on different cluster nodes over separate
weeks, and the average time and memory consumption were used for plotting.
558
Benchmarking
For indexing, LexicMap built indexes with the genome batch size 5,000 (default) for GTDB and
25,000 for the AllTheBacteria dataset. Blastn, MMseqs2, and Minimap2 build indexes with
parameters as mentioned above. The Phylign index was built with default parameters, including $k =$
31 and a false-positive rate of 0.3 for the COBS index; since the index building involved three
workflows with multiple steps in multiple cluster nodes, the memory and time could not be
measured accurately.
566
567 The four query datasets were used for sequence alignment. LexicMap returned all possible matches
568 by default and other tools were set to return all possible matches according to the sequence number
569 in a database. All tools used 48 CPUs. The main parameters of Phylign included threads=48,
570 cobs_kmer_thres=0.33, minimap_preset="asm20", nb_best_hits=5,000,000, max_ram_gb=100.
571 For the cluster mode, the maximum number of Slurm jobs was set to 100.
572
The four tools' sequence alignment results were divided into three categories according to query

coverage (qcov) and percentage of identity (pident), and the genome number of each category were
counted for comparison. The metrics of Minimap2 and Phylign were computed by sam2tsv.py
(https://gist.github.com/apcamargo/2b7ca3032c1e80333adc1e54f47a0966). Alignments of high
similarity are those with qcov≥90% (genes) or 70% (plasmids) and pident≥90%. Alignments of low
similarity are those with qcov<50% (genes) or 30% (plasmid) or pident < 80%. Left alignments are
marked as medium similarity.
580

Code availability

LexicMap is an open-source standalone tool implemented in Go under the MIT license at
https://github.com/shenwei356/LexicMap, with freely available statically linked executable binary
files for common operating systems and CPU types. The source code is also archived at
https://doi.org/10.5281/zenodo.15197523. Two main subcommands *index* and *search* are used to
create an index and perform searching, respectively, and several utility subcommands are available
for interpreting the index data and extracting indexed sequences.
588

Data availability

590 All analyses were done with data public genome databases; specifically GTDB r214 complete
591 dataset, GenBank+RefSeq dataset, downloaded on February 15, 2024, and AllTheBacteria v0.2.
592 Full details on how to reproduce all analyses, along with lists of accessions used, can be found in
593 this GitHub repository https://github.com/shenwei356/lexicmap-benchmark, and also in this
594 Zenodo archive: https://doi.org/10.5281/zenodo.15628530 .

Acknowledgements

596 This study was supported by grants from the National Natural Science Foundation of China
597 (82341112), Chinese Scholarship Council scholarship (202308500105), EMBL Visitor/Sabbatical
598 Programme fellowship, Remarkable Innovation-Clinical Research Project, Joint Project of Pinnacle
599 Disciplinary Group, and Kuanren Talents Program of The Second Affiliated Hospital of Chongqing
600 Medical University.
601

We thank Shuyi Wang (Peking University People's Hospital, China), Leah Roberts (Queensland
University of Technology, Australia), Songbai Cai and Liuyang Zhao (Chongqing Medical
University, China), and Rachel Colquhoun (Edinburgh University, UK) for using LexicMap and
giving valuable feedback during the development. We thank Daniel Anderson for suggesting test
datasets. We thank Pengfei Wang (University of Montpellier, France) for comments on the
manuscript and visualization. We thank Daniel Anderson, Martin Hunt, and Daria Frolova for
fruitful discussions.
609

Author contributions

611 W.S. and Z.I. designed the project. Z.I. managed the project. W.S. implemented the software. Z.I.
612 and J.L. provided computing resources. W.S. and Z.I. performed benchmarks and data interpretation.
613 W.S., Z.I., and J.L. wrote the manuscript. All authors reviewed and approved the manuscript.
614

Competing interests

The authors declare no competing interests.

References

1   Camacho, C. *et al.* BLAST+: architecture and applications. *BMC Bioinformatics* **10**, 421,
        doi:10.1186/1471-2105-10-421 (2009).
2   Li, H. & Durbin, R. Fast and accurate short read alignment with Burrows-Wheeler transform.
        Bioinformatics **25**, 1754-1760, doi:10.1093/bioinformatics/btp324 (2009).
3   Langmead, B. & Salzberg, S. L. Fast gapped-read alignment with Bowtie 2. *Nat Methods* **9**, 357-359,
        doi:10.1038/nmeth.1923 (2012).
4   Li, H. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**, 3094-3100,
        doi:10.1093/bioinformatics/bty191 (2018).
5   Needleman, S. B. & Wunsch, C. D. A general method applicable to the search for similarities in the
        amino acid sequence of two proteins. *J Mol Biol* **48**, 443-453, doi:10.1016/0022-2836(70)90057-4
        (1970).
6   Smith, T. F. & Waterman, M. S. Identification of common molecular subsequences. *J Mol Biol* **147**, 195-
        197, doi:10.1016/0022-2836(81)90087-5 (1981).
7   Gotoh, O. An improved algorithm for matching biological sequences. *J Mol Biol* **162**, 705-708,
        doi:10.1016/0022-2836(82)90398-9 (1982).
8   Marco-Sola, S., Moure, J. C., Moreto, M. & Espinosa, A. Fast gap-affine pairwise alignment using the
        wavefront algorithm. *Bioinformatics* **37**, 456-463, doi:10.1093/bioinformatics/btaa777 (2021).
9   Liu, D. & Steinegger, M. Block Aligner: an adaptive SIMD-accelerated aligner for sequences and
        position-specific scoring matrices. *Bioinformatics* **39**, doi:10.1093/bioinformatics/btad487 (2023).
10   Groot Koerkamp, R. & Ivanov, P. Exact global alignment using A* with chaining seed heuristic and
        match pruning. *Bioinformatics* **40**, doi:10.1093/bioinformatics/btae032 (2024).
11   Bzikadze, A. V. & Pevzner, P. A. UniAligner: a parameter-free framework for fast sequence alignment.
        Nat Methods **20**, 1346-1354, doi:10.1038/s41592-023-01970-4 (2023).
12   Shao, H. & Ruan, J. BSAlign: A Library for Nucleotide Sequence Alignment. *Genomics, Proteomics &*
        Bioinformatics, qzae025, doi:10.1093/gpbjnl/qzae025 (2024).
13   Břinda, K. *et al.* Efficient and robust search of microbial genomes via phylogenetic compression. *Nature*
        Methods **22**, 692-697, doi:10.1038/s41592-025-02625-2 (2025).
14   Blackwell, G. A. *et al.* Exploring bacterial diversity via a curated and searchable snapshot of archived
        DNA sequences. *PLOS Biology* **19**, e3001421, doi:10.1371/journal.pbio.3001421 (2021).
15   Lassalle, F. *et al.* Genomic epidemiology reveals multidrug resistant plasmid spread between Vibrio
        cholerae lineages in Yemen. *Nat Microbiol* **8**, 1787-1798, doi:10.1038/s41564-023-01472-1 (2023).
16   Mason, L. C. E. *et al.* The evolution and international spread of extensively drug resistant Shigella
        sonnei. *Nat Commun* **14**, 1983, doi:10.1038/s41467-023-37672-w (2023).
17   Hu, Y., Moran, R. A., Blackwell, G. A., McNally, A. & Zong, Z. Fine-Scale Reconstruction of the
        Evolution of FII-33 Multidrug Resistance Plasmids Enables High-Resolution Genomic Surveillance.
        mSystems **7**, e0083121, doi:10.1128/msystems.00831-21 (2022).
18   Smits, W. K. *et al.* Sequence-Based Identification of Metronidazole-Resistant Clostridioides difficile

Isolates. *Emerg Infect Dis* **28**, 2308-2311, doi:10.3201/eid2811.220615 (2022).

19   Malaka De Silva, P. *et al.* A tale of two plasmids: contributions of plasmid associated phenotypes to
epidemiological success among Shigella. *Proc Biol Sci* **289**, 20220581, doi:10.1098/rspb.2022.0581
(2022).

20   Croucher, N. J. Immune interface interference vaccines: An evolution-informed approach to anti-
bacterial vaccine design. *Microb Biotechnol* **17**, e14446, doi:10.1111/1751-7915.14446 (2024).

21   Smith, T. M. *et al.* Rapid adaptation of a complex trait during experimental evolution of Mycobacterium
tuberculosis. *Elife* **11**, doi:10.7554/eLife.78454 (2022).

22   Lassalle, F. *et al.* Genomic epidemiology of the cholera outbreak in Yemen reveals the spread of a multi-
drug resistance plasmid between diverse lineages of Vibrio cholerae *bioRxiv*,
2022.2008.2024.504966, doi:10.1101/2022.08.24.504966 (2022).

23   Parks, D. H. *et al.* GTDB: an ongoing census of bacterial and archaeal diversity through a
phylogenetically consistent, rank normalized and complete genome-based taxonomy. *Nucleic Acids Res*
50, D785-D794, doi:10.1093/nar/gkab776 (2022).

24   Colquhoun, R. M. *et al.* Pandora: nucleotide-resolution bacterial pan-genomics with reference graphs.
Genome Biol **22**, 267, doi:10.1186/s13059-021-02473-1 (2021).

25   Schmidt, T. S. B. *et al.* SPIRE: a Searchable, Planetary-scale mIcrobiome REsource. *Nucleic Acids*
Research **52**, D777-D783, doi:10.1093/nar/gkad943 (2024).

26   Sayers, E. W. *et al.* GenBank 2024 Update. *Nucleic Acids Res* **52**, D134-D137, doi:10.1093/nar/gkad903
(2024).

27   Haft, D. H. *et al.* RefSeq and the prokaryotic genome annotation pipeline in the age of metagenomes.
Nucleic Acids Res **52**, D762-D769, doi:10.1093/nar/gkad988 (2024).

28   Hunt, M., Lima, L., Shen, W., Lees, J. & Iqbal, Z. AllTheBacteria - all bacterial genomes assembled,
available and searchable. *bioRxiv*, 2024.2003.2008.584059, doi:10.1101/2024.03.08.584059 (2024).

29   Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence searching for the analysis of
massive data sets. *Nature Biotechnology* **35**, 1026-1028, doi:10.1038/nbt.3988 (2017).

30   Bingmann, T., Bradley, P., Gauger, F. & Iqbal, Z. in *String Processing and Information Retrieval.* (eds
Nieves R. Brisaboa & Simon J. Puglisi) 285-303 (Springer International Publishing).

31   Shen, W. *et al.* KMCP: accurate metagenomic profiling of both prokaryotic and viral populations by
pseudo-mapping. *Bioinformatics* **39**, doi:10.1093/bioinformatics/btac845 (2023).

32   Li, H. BWT construction and search at the terabase scale. *Bioinformatics* **40**, btae717,
doi:10.1093/bioinformatics/btae717 (2024).

33   Greenberg, G., Ravi, A. N. & Shomorony, I. LexicHash: sequence similarity estimation via lexicographic
comparison of hashes. *Bioinformatics* **39**, btad652, doi:10.1093/bioinformatics/btad652 (2023).

34   Marçais, G., Elder, C. S. & Kingsford, C. k-nonical space: sketching with reverse complements.
Bioinformatics **40**, btae629, doi:10.1093/bioinformatics/btae629 (2024).

35   Wick, R. R. Badread: simulation of error-prone long reads. *Journal of Open Source Software* **4**, 1316,
doi:10.21105/joss.01316 (2019).

36   Brockhurst, M. A. *et al.* Assessing evolutionary risks of resistance for new antimicrobial therapies.
Nature Ecology & Evolution **3**, 515-517, doi:10.1038/s41559-019-0854-x (2019).

Extended Data

Table.S1 | Index sizes and indexing performances with different numbers of probes. The reference genomes were 402,538 prokaryotic assemblies from GTDB r214 complete dataset. LexicMap `index` command used default parameters except for the number of probes. The tests were performed on a server with Intel(R) Xeon(R) Gold 6248 CPU @ 2.50GHz and all files are stored on HDD disks.

Probes	Index size	Indexing time	Indexing memory
10,000	955 GB	10 h 11 m	69.77 GB
20,000	972 GB	12 h 11 m	77.03 GB
40,000	1,029 GB	19 h 50 m	86.59 GB

Table.S2 | Search performance on GTDB r214 complete dataset on three queries with different numbers of probes. We used 3 queries. Gene SecY (termed a rare gene), a 16s rRNA gene, and a plasmid (accessions are available in Methods). We report the number of genomes with alignments (genome his), and how many of these matched specific criteria. QcovHSP is the query coverage per High-scoring Segment Pair (HSP). Pident is the percentage identity. LexicMap `search` command used default parameters. The computation environment was the same as Table S1.

Query (length)	Probes	Search time	Search memory	Genome hits	Genome hits (qcovHSP≥70)	Genome hits (qcovHSP≥70 and pident≥80)
A rare gene	10,000	67 s	1.77 GB	6,100	6,068	2,355
1,299 bp	20,000	70 s	2.42 GB	6,230	6,197	2,356
	40,000	64 s	3.96 GB	5,882	5,848	2,356
A 16S rRNA gene	10,000	749 s	3.35 GB	303,037	227,095	117,104
1,542 bp	20,000	723 s	4.31 GB	303,664	227,275	117,105
	40,000	714 s	6.14 GB	305,360	227,264	117,107
A plasmid	10,000	483 s	4.31 GB	60,800	755	755
52,830 bp	20,000	627 s	5.86 GB	63,517	1,191	1,191
	40,000	732 s	7.52 GB	64,970	1,191	1,191

713 **Table.S3 | Searching performance on three queries with different paired minimum anchor length**

714 **thresholds.** The index was built with 20,000 probes from 402,538 prokaryotic assemblies from GTDB

715 r214 complete dataset. LexicMap `search` command used default parameters except for the paired

716 minimum anchor length thresholds (P and P', see methods). The computation environment was the

717 same as Table S1.

Query (length)	Minimum anchor length pair	Searching time	Searching memory	Genome Hits	Genome hits (qcovHSP≥70)	Genome hits (qcovHSP≥70 and pident≥80)
A rare gene	15-15	330 s	2.19 GB	6,505	6,269	2,356
1,299 bp	15-17	67 s	2.11 GB	6,230	6,197	2,356
	17-17	66 s	1.97 GB	6,211	6,078	2,356
	17-19	34 s	1.88 GB	6,111	6,081	2,356
	19-19	34 s	1.93 GB	6,084	6,055	2,355
	19-21	29 s	1.90 GB	5,510	5,487	2,352
A 16S rRNA gene	15-15	821 s	4.19 GB	304,867	227,285	117,105
1,542 bp	15-17	723 s	4.29 GB	303,664	227,275	117,105
	17-17	721 s	4.18 GB	303,353	227,212	117,105
	17-19	710 s	4.11 GB	302,071	227,137	117,105
	19-19	708 s	4.11 GB	301,867	227,053	117,104
	19-21	700 s	4.04 GB	300,413	226,953	117,104
A Plasmid	15-15	1,191 s	6.06 GB	64,328	1,191	1,191
52,830 bp	15-17	627 s	6.08 GB	63,517	1,191	1,191
	17-17	622 s	5.74 GB	63,489	1,191	1,191
	17-19	362 s	5.85 GB	62,002	1,191	1,191
	19-19	363 s	6.24 GB	61,938	1,191	1,191
	19-21	327 s	5.67 GB	60,756	1,191	1,191

720 **Table.S4 | LexicMap alignment output format details.**

#	Column	Description
1	query	Query sequence ID
2	qlen	Query sequence length
3	hits	Number of subject genomes
4	sgenome	Subject genome ID
5	sseqid	Subject sequence ID
6	qcovGnm	Query coverage (percentage) per genome: $(aligned bases in the genome)/$qlen
7	cls	Nth HSP cluster in the genome
8	hsp	Nth HSP in the genome
9	qcovHSP	Query coverage (percentage) per HSP: $(aligned bases in a HSP)/$qlen
10	alenHSP	Aligned length in the current HSP
11	pident	Percentage of identical matches in the current HSP
12	gaps	Gaps in the current HSP
13	qstart	Start of alignment in query sequence
14	qend	End of alignment in query sequence
15	sstart	Start of alignment in subject sequence
16	send	End of alignment in subject sequence
17	sstr	Subject strand
18	slen	Subject sequence length
19	evalue	Expect value
20	bitscore	Bit score
21	cigar	CIGAR string of the alignment. (optional with -a/--all)
22	qseq	Aligned part of query sequence. (optional with -a/--all)
23	sseq	Aligned part of subject sequence. (optional with -a/--all)
24	align	Alignment text ("|" and " ") between qseq and sseq. (optional with -a/--all)

723 **Table.S5 | Details of 10 bacterial genomes for the alignment rate comparison.**

Assembly	TaxID	Species	Contigs	Genome size
GCF_000005845.2	562	*Escherichia coli*	1	4,641,652
GCF_000240185.1	573	*Klebsiella pneumoniae*	7	5,682,322
GCF_000013425.1	1280	*Staphylococcus aureus*	1	2,821,361
GCF_000006945.2	28901	*Salmonella enterica*	2	4,951,383
GCF_001457635.1	1313	*Streptococcus pneumoniae*	1	2,110,968
GCF_000195955.2	1773	*Mycobacterium tuberculosis*	1	4,411,532
GCF_000006765.1	287	*Pseudomonas aeruginosa*	1	6,264,404
GCF_008632635.1	470	*Acinetobacter baumannii*	2	3,980,230
GCF_018885085.1	1496	*Clostridioides difficile*	2	4,095,894
GCF_022869705.1	1351	*Enterococcus faecalis*	1	2,866,948

725 **Table.S6 | Alignment performance of LexicMap on GenBank+RefSeq dataset.** Sequence identifiers
726 are available in Methods.

Query	Query length	Hits (total)	Hits (high)	Hits (medi)	Hits (low)	Time	RAM
A rare gene	1,299 bp	41,718	11,746	115	29,857	3m:06s	4.0 GB
A 16S rRNA gene	1,542 bp	1,955,167	245,884	501,691	1,207,592	32m:59s	11.1 GB
A plasmid	52,830 bp	560,330	96	15,370	544,864	52m:22s	14.5 GB
1033 AMR genes	1 kb (median)	30,967,882	7,636,386	4,858,063	18,473,433	15h:52m:08s	24.9 GB

729 **Fig.S1 | Performance of LexicMap with different numbers of probes and seed densities. a)**

730 Robustness to sequence divergence. **b)** Average index sizes of single genomes and indexing

731 performances. The same 10 reference genomes and simulated queries are the same as those in Fig.3.

Fig.S2 | Histogram of shared prefix lengths between probes and the captured *k*-mers. Using a

LexicMap index of GTDB r214 representative genomes (n=85,205), we show the lengths of shared

prefixes between the 20,000 fixed probes and the captured *k*-mers..

Fig.S3 | Histograms of seed distance and seed number in sliding windows. Three genomes of

different genome sizes are used for illustration. a) Histograms of seed distance before filling seed

deserts. b) Histograms of seed distance after filling deserts. Note that in assemblies GCF_002949675.1

and GCF_000017205.1, the two maximum seed distances larger than 100 bp resulted from low-

complexity regions. c) Histograms of seed number in 250-bp sliding windows after filling deserts.

Fig.S4 | **Number of seeds vs genome size.** A LexicMap index was built from 85,205 GTDB r214
representative genomes with default parameters and "--save-seed-pos". The plot shows the number of
seeds in each genome, versus the genome size (number of bases in Megabases).

Fig.S5 | **Architecture of LexicMap.** a) Indexing and searching workflow. b) Variable-length seed
matching.

Fig.S6 | Robustness of LexicMap and Blastn to sequence divergence. LexicMap uses different

paired minimum anchor length thresholds, and Blastn uses a range of word sizes. The 10 reference

genomes and simulated queries are the same as those in Fig.3.

```
Query = GCF_003697165.2_r40
Length = 186

[Subject genome #1/2] = GCF_002950215.1 Shigella flexneri
Query coverage per genome = 93.548%

>NZ_CP026788.1
Length = 4659463

 HSP cluster #1, HSP #1
 Score = 279 bits, Expect = 9.66e -75
 Query coverage per seq = 93.548%, Aligned length = 177, Identities = 88.701%, Gaps = 6
 Query range = 13 -186, Subject range = 1124816 -1124989, Strand = Plus/Plus

Query   13      CGGAAACTGAAACA -CCAGATTCTACGATGATTATGATGATTTA -TGCTTTCTTTACTAA   70
                |||||||||||||| |||||||||| | |||||||||||||| |||||||| ||||
Sbjct   1124816 CGGAAACTGAAACAACCAGATTCTATGTTGATTATGATGATTTAATGCTTTCTTTGCTAA  1124875

Query   71      AAAGTAAGCGGCCAAAAAAATGAT -AACACCTGTAATGAGTATCAGAAAAGACACGGTAA   129
                ||  ||||||||||||||||||| |||||||||||||||||||||||||||||||||
Sbjct   1124876 AA--GCAGCGGCCAAAAAAATGATTAACACCTGTAATGAGTATCAGAAAAGACACGGTAA  1124933

Query   130     GAAAACACTCTTTTGGATACCTAGAGTCTGATAAGCGATTATTCTCTCTATGTTACT   186
                ||  |||||||| |||||  |||||||||||||||||||||||||||| |||| |||
Sbjct   1124934 AAAGACACTCTTTGAAGTACCTGAAGTCTGATAAGCGATTATTCTCTCCATGT -ACT  1124989
```

Fig.S7 | Blast-style pairwise output format in LexicMap. Note that, in addition to data that BLAST

outputs, LexicMap also provides subject genome information (here *Shigella flexneri*) and query

 coverage per genome.

Fig.S8 | **Alignment rates of simulated mutation-free queries.** Queries with 100% identity (a subset
of the experiment shown in in Fig.3) are aligned; the proportion of these which are aligned to the right
place are shown here. Text labels are the mean alignment rates.