Weakly Supervised Vector Quantization for Whole Slide Images Classification

Dawei Shen
Division of Health Medical Intelligence
Institute of Medical Science
The University of Tokyo
Tokyo, Japan
coalball@g.ecc.u-tokyo.ac.jp

Yaozhong Zhang*
Division of Health Medical Intelligence
Institute of Medical Science
The University of Tokyo
Tokyo, Japan
yaozhong@ims.u-tokyo.ac.jp

Seiya Imoto*
Division of Health Medical Intelligence
Institute of Medical Science
The University of Tokyo
Tokyo, Japan
imoto@hgc.jp

Abstract—Whole Slide Images (WSIs) are high-resolution digital scans of entire microscope slides, extensively used in pathology to enable detailed examination of tissue samples. WSI tumor classification is a classic application of Multiple Instance Learning (MIL). In this process, a WSI is first divided into image tiles, and each tile is encoded into an embedding vector using a pretrained vision encoder. A lightweight MIL model then aggregates all the embeddings in a WSI for classification. A key factor affecting the performance of this classification is the quality of the embedding vectors. However, the embedding vectors generated by the pretrained vision encoder are continuous and not task-specific, causing them to contain significant noise and resulting in low distinguishability between tumor tiles and normal tiles. This weakens the model's capability. In this work, inspired by VQ-VAE, we propose VQ-MIL, where each continuous embedding vector is mapped to a discrete, task-specific space using weakly supervised vector quantization. This approach effectively separates tumor instances from normal instances and reduces the noise associated with each instance. Our experiments demonstrate that our method achieves state-of-the-art classification results on two benchmark datasets. The source code is available at https://github.com/aCoalBall/VQMIL.

Index Terms—WSI, Multipile Instance Learning, Vector Quantization

I. Introduction

Whole Slide Images (WSIs) are high-resolution digital scans of entire microscope slides commonly utilized in pathology, allowing for the comprehensive examination of tissue samples.[1] The task of WSI tumor classification involves determining the presence of tumor tissues within these slides.

This tumor classification task is particularly suited to Multiple Instance Learning (MIL)[2, 3], a type of weakly supervised machine learning where data is structured into labeled bags, each containing multiple instances. In the MIL context, a bag (or slide) is labeled positive if it contains at least one positive instance (tumor tissue) and negative if all instances are negative (tumor-free). This method is advantageous for WSI tumor classification for two reasons. First, the gigapixel size of WSIs makes it infeasible for current hardware and algorithms to process them directly. This necessitates dividing each WSI into numerous smaller image tiles and compressing each tile into a small embedding vector. Second, detailed annotations for WSIs are scarce, as providing pixel-level annotations for each slide is costly and time-consuming for pathologists.[4, 5] Hence, training usually utilizes slide-level labels rather than detailed instance labels.

The current MIL process for WSIs begins with a pretrained vision encoder, such as ResNet [6] or Vision Transformer [7], which compresses each image tile into an embedding vector. These vectors represent the instances in the MIL framework. A lightweight MIL model is then trained on these embedding vectors to perform slide classification. Most current MIL models incorporate the attention mechanisms introduced in the classic AB-MIL [8] approach. In these models, each instance (embedding vector) in a slide is assigned a learnable attention score. The MIL model aggregates all instances using these scores to form a slide embedding vector, which is subsequently used for making the final classification prediction. This process efficiently addresses the challenges of size and annotation scarcity inherent in WSI tumor classification.

A key factor affecting the performance of WSI tumor classification of this process is the quality of the embedding vectors. Ideally, the distinguishability between the embedding vectors of tumor instances and normal instances should be as large as possible. This would ensure that the slide embedding vectors of tumor and normal slides are more distinct, enabling the MIL model to make better predictions. However, the embedding vectors obtained from pretrained vision encoders have two characteristics that reduce this distinguishability. The first issue is that the embeddings are not task-specific. The pretraining framework is usually designed to learn general features from a large and diverse dataset, rather than focusing on a specific task like tumor classification. Currently, two common types of pretrained vision encoders are used in this field: general-purpose vision encoders, which are supervisedly pretrained on common image datasets like ImageNet [6, 9], and vision encoders that are self-supervisedly pretrained on unlabeled WSI datasets [10, 11, 12]. Neither type emphasizes task-specific features of tumor or normal image tiles. As a result, the MIL model may struggle to differentiate tumor instances from normal instances due to the significant noise in the embedding vectors. The second issue is the continuity of the embedding space. Ideally, in MIL, the class of each instance, which is a set of discrete values, is the primary information

needed to determine the class of the bag. Therefore, MIL inherently has a discrete nature. Continuous embeddings from the vision encoder introduce unnecessary noise, impairing the MIL model's ability to perform accurate classification.

To address these two issues, we propose VQ-MIL, which incorporates a weakly supervised vector quantization module between the vision encoder and the MIL model. The vector quantization module uses techniques similar to those in VQ-VAE [13] but replaces the reconstruction loss with a weakly supervised slide-level classification loss. The module contains a learnable codebook with a fixed number of codewords. During training, input embedding vectors are mapped to the nearest codewords. These discretized codewords, rather than the original embedding vectors, are passed to the MIL model. This process helps separate challenging tumor instances from normal instances and significantly reduces the dimensionality of the embedding space, thereby enhancing the MIL model's classification performance. Additionally, the trained codebook has fixed attention scores, providing clearer and more accurate visualizations compared to continuous embedding vectors used in previous methods like AB-MIL.

Furthermore, we argue that one bottleneck for WSI classification is the lack of slide-level labels. To address this, we randomly select image tiles from tumor and normal slides to create positive and negative pseudo-bags as a simple data augmentation method.

We evaluated our method on two representative datasets, Camelyon16 [14] and TCGA lung cancer dataset, and the experimental results show that our model achieves state-of-the-art slide-level performance compared with the previous methods.

II. RELATED WORKS

A. MIL methods for WSI classification

To address the challenges of gigapixel size and the lack of precise annotations in WSIs, current deep learning methods typically employ a two-stage approach that consists of a vision encoder followed by a MIL model. In this process, a WSI is initially divided into many smaller image tiles. A pretrained and frozen vision encoder is then used to convert each of these tiles into one-dimensional embedding vectors. There are two main types of pretrained vision encoders. The first type is a general-purpose vision encoder pretrained on datasets like ImageNet. However, there is a significant domain gap between ImageNet images and pathological images. To address this issue, some research [10, 11, 12, 15] has focused on using a large number of unlabeled WSIs to pretrain vision encoders within self-supervised learning frameworks such as SimCLR [16]or DINO [17, 18].

After extracting the embedding vectors, all vectors from each WSI are collected to train a MIL model that acts as a slide-level classifier. There has been significant work in developing efficient MIL models for WSI classification. AB-MIL [8] introduces an attention mechanism to aggregate features using attention scores. CLAM [19] is a variant of AB-MIL that clusters instances with the top-k highest and lowest

attention scores. DS-MIL [10] combines embedding vectors from multiple scales and selects the most representative instance as a query to identify other instances. TransMIL [20] utilizes the self-attention mechanism from Transformers[21] to consider the relationships between instances in a slide. DTFD-MIL[22] resamples instances within a slide to increase the number of available labels. All of these methods demonstrate reliable performance in slide-level classification.

Recently, there have been some impressive efforts[23, 24, 25] to attempt to finetune the vision encoders to address the issue that the embeddings generated by the vision encoder are not task-specific. Considering the powerful capabilities of vision encoders, this approach has great potential. However, due to the enormous size of WSIs, it is not feasible to finetune the vision encoder using entire WSIs. To mitigate this issue, some studies[24] finetune the model by assigning the slide-level label to each instance within the slide, while some other studies[23, 25] reduce the input size by sampling instances using methods like K-Means[26] or deep variational information bottleneck[27]. However, these methods inevitably result in incomplete or incorrect data, which can impair the model's performance comparing with fully-supervised finetuning.

B. VQ-VAE

Vector Quantized Variational Autoencoder (VQ-VAE)[13] is a variant of variational autoencoder (VAE)[28] that utilizes vector quantization. It encodes input data into discrete latent space by mapping continuous features to the nearest codeword in a learnable codebook. Then this discrete representation is used to generate high-quality reconstructions. VQ-VAE is particularly useful for tasks like image generation and speech synthesis, where capturing discrete underlying structures can improve the model's performance and interpretability.

Let $Q \in \mathbb{R}^{K \times D}$ be the codebook, where K is the size of the codebook and D is the dimension of codewords. For an input x, an encoder Z_e encodes x to feature $Z_e(x)$. $Z_e(x)$ is then mapped to the nearest codeword c that:

$$c = argmin_{q_j} \|Z_e(x) - q_j\|_2, \forall q_j \in Q$$

After that, a decoder Z_D decodes the codewords to reconstruct the original input x. Since the mapping process for vector quantization is not differentiable, VQ-VAE directly copies the gradient of the codeword c to $Z_e(x)$ during back propagation. Thus the output of VQ-VAE $\hat{x}$ is:

$$\hat{x} = Z_D(sg(c - Z_e(x)) + Z_e(x))$$

where $sg(x) = x$ during forward propagation and $sg(x) = 0$ during back propagation.

As an autoencoder, VQ-VAE uses the reconstruction loss $logP(x|\hat{x})$ to update the output $\hat{x}$ as a reconstruction of the input x. Besides minimizing the reconstruction loss, VQ-VAE also tries to minimize the distance between the output of the encoder $Z_e(x)$ and the codewords c. The author of VQ-VAE argued that the encoder Z_e and the codewords would better

have different learning pace. Therefore the loss function of VQ-VAE contains three components:

$$L = logP(x|\hat{x}) + \|sg(Z_e(x)) - c\| + \alpha\|Z_e(x) - sg(c)\|$$

where α is a coefficient. The first term of L is the reconstruction loss. The second and third term are called VQ loss, which aim to minimize the distance between the outputs of the encoder and the codewords, but the difference is that the second loss only updates the codewords and the third loss only updates the encoder Z_e.

III. METHODS

A. Formulation of MIL Methods for WSI

To formalize the process of WSI deep learning analysis,denote the frozen vision encoder as V. For an input WSI $X = \{x_1, x_2, ...\}$, where x_i is the i_{th} tile that cropped from the WSI. The set of embedding vectors $\mathbf{F} = \{f_1, f_2, ...\}$ is generated by V that $f_i = V(x_i)$. $\mathbf{F}$ is regarded as the instances of slide X in the settings of MIL. Then the slide label Y of X, is determined by the instance labels $\mathbf{y} = \{y_1, y_2, ...\}$:

$$Y = \begin{cases} 0 & \text{if } \sum \mathbf{y} = 0 \\ 1 & \text{otherwise} \end{cases}$$

Since the labels of instances $\mathbf{y}$ are unknown, usually a MIL model A is applied on $\mathbf{F}$ to produce slide-level prediction $\hat{p} = A(\mathbf{F})$. For an attention based MIL model like AB-MIL[8], a learnable attention score a_i is calculated for each instance f_i in the following way:

$$a_i = \frac{\exp\left(w^T(\tanh\left(vf_i^T\right) \circ \text{sigmoid}\left(uf_i^T\right))\right)}{\sum_{j=1}^{N} \exp\left(w^T(\tanh\left(vf_j^T\right) \circ \text{sigmoid}\left(uf_j^T\right))\right)}$$

where w, u and v are learnable parameters.

All instances in a slide are then aggregated as a slide-level embedding and a linear head is used to do the prediction. the model could be described as :

$$A(\mathbf{F}) = \sigma(\sum_{i=1}^{N} a_i f_i)$$

where σ is the linear classifier head.

B. VQ-MIL

In this section we introduce our model VQ-MIL, especially the vector quantization module in it and how it maps the embedding vectors to a discrete and task-specific space. The overview workflow of our method is shown in Figure 1. We split our workflow into three modules, the vision encoding module, the vector quantization module and the MIL module. In the vision encoding module, the input WSI X is first divided into N tiles. A vision encoder V independently encodes these N tiles into N embedding vectors. These N embedding vectors are then passed to the vector quantization module, where

a trainable encoder Z_e furthur encodes these N embedding vectors. Then there is a learnable codebook Q that contains K discretized codewords. All these N embedding vectors are respectively mapped to the nearest codeword. Then it is the mapped codewords instead of the embedding vectors are passed to the MIL module. Here we simply apply the classic ABMIL as the MIL model A, in which an attention score is calculated for each codeword and all codewords are aggregated as a slide embedding by the weight of attention scores. A linear layer is applied on the slide embedding to do slide prediction.

1) Vector Quantization Module: Inspired by VQ-VAE, we tried to apply vector quantization in MIL to map the continuous embedding vectors to a discrete space to further reduce the noise. Here, to apply the vector quantization method on WSI classification problems, we add an additional vector quantization module after the conventional vision encoding module and before the MIL module.

In the vector quantization module, a codebook is defined as $Q \in R^{K \times D}$, where K is the size of the codebook and D is the dimension of each codewords. For a WSI $\mathbf{X}$, the generated embedding vectors $\mathbf{F}$ are passed through the vector quantization module, where an additional encoder Z_e furtherly encodes the embeddings as $\mathbf{E} = \{e_1, e_2, ...\}$, where $e_i = Z_e(f_i)$. Then the set of codewords $\mathbf{C} = \{c_1, c_2, ...\}$ is calculated in the way that for each e_i, c_i is the nearest codeword from it:

$$c_i = argmin_{q_j}\|e_i - q_j\|_2, \forall q_j \in Q$$

Then it is the calculated set of code words $\mathbf{C}$ instead of $\mathbf{F}$ is passed through the MIL model A to do the prediction $\hat{p} = A(\mathbf{C})$. $\mathbf{C}$ is in a discrete space since it is a set of codewords from the codebook.

Similar to VQ-VAE[13], here we face the problem that the vector quantization process is not differentiable. We apply the same method as in VQ-VAE that directly copying the gradient from $\mathbf{C}$ to $\mathbf{E}$. Thus the actual expression of the workflow is:

$$\hat{p} = A(sg(\mathbf{C} - \mathbf{E}) + \mathbf{E})$$

where $\mathbf{E} = Z_e(\mathbf{F})$. $sg(x) = x$ during forward propagation and $sg(x) = 0$ during back propagation.

Besides the classification loss, we also add VQ loss similar to which in VQ-VAE that updates both the outputs of the encoder and the codewords to make them closer.

Therefore the loss function is:

$$L = L_{cls}(\hat{p}, Y) + \|sg(\mathbf{E}) - \mathbf{C}\| + \alpha\|\mathbf{E} - sg(\mathbf{C})\|$$

where Y is the slide label and α is a coefficient. The first term is the slide-level cross-entropy loss, the second and the third term are VQ loss. During the training, the parameters of the vector quantization module and the MIL module are updated simultaneously.

Fig. 1: The workflow of VQ-MIL, which have three modules. The vision encoding module converts a WSI to embedding vectors. The vector quantization module mapped embedding vectors to discrete and task-specific codewords. The MIL module aggregates all codewords to make the prediction.

Note that compared with VQ-VAE[13], our VQ-MIL replaces the decoder with the MIL model and replaces the reconstruction loss from the decoder with the weakly supervised slide-level classification loss from the MIL model.

Algotithm1 is the pseudo code of the workflow.

Algorithm 1 pseudo-code of VQ-MIL

$Q \in R^{K \times D}$ #the codebook Q
$X = \{x_1, x_2, ...\}$ #one WSI
$V.freeze$ #freeze the vision encoder V
$F = V(X)$ #get embeddings of X by V
$E = Z_e(F)$ #encodes F to E
for $e_i \in E$ **do**
    $c_i = argmin_{q_j} \|Z_e(x) - q_j\|_2, \forall q_j \in Q$
end for
$C = \{c_1, c_2, ..., c_k\}$ #the set of codewords C
$\hat{Y} = A(C)$ #make the prediction by the MIL model A
$ClsLoss = CELoss(\hat{Y}, Y)$
$Loss = ClsLoss + VQLoss$
$Loss.backpropagate(A, Q, Z_e)$ #update Z_e, the codebook and the MIL model.

C. Random Pseudo Bags

One challenge in training an efficient model for WSI classification is the scarcity of labels. Given the rich and varied content within WSIs, having only one label per slide provides too little information for the MIL model to effectively exploit useful features. For instance, in the Camelyon16 dataset, which contains WSIs of lymph node sections, there are 270 slides for training and 400 slides in total. Usually, thousands of image tiles can be cropped from a single slide, resulting in only 270 labels for hundreds of thousands of tiles in Camelyon16. This lack of labels means that, in attention-based MIL models, only a subset of positive tiles may be identified from the slide. This limitation hampers the MIL model's ability to fully learn and distinguish the features of tumor tissues.

Inspired by previous methods[22, 29, 30], we randomly select M instances each time from each slide type (e.g., tumor and normal) to create a large number of pseudo-bags. This approach helps our model explore as many potential instances as possible.

IV. Experiments

A. Datasets and Preprocessing

We report our results on two commonly used WSI datasets: Camelyon16[14] and the TCGA lung cancer dataset.

Camelyon16. The Camelyon16 dataset is a benchmark in computational pathology, used for developing algorithms to detect breast cancer metastases in lymph node tissue sections. It includes 400 whole-slide images with detailed annotations provided by expert pathologists. The dataset is divided into 270 training slides from two medical centers and 130 test slides from another center. This dataset was created for the Camelyon16 Grand Challenge to evaluate the performance of automated systems in improving cancer diagnosis. Camelyon16 also provides pixel-level annotation for each slides for detailed evaluation.

TCGA lung cancer. This dataset includes WSIs for two major subtypes of lung cancer: lung adenocarcinoma (LUAD) and lung squamous cell carcinoma (LUSC). It contains a total of 1,054 slides, with 531 from LUAD and 513 from LUSC. The dataset can be downloaded from the National Cancer Institute Data Portal.

For data preprocessing, we followed the CLAM[19] library guidelines, using the OTSU[31] algorithm for segmentation

TABLE I: Comparison of MIL workflows on Camelyon16

Model	Accuracy	AUC
ABMIL	0.8326 ($\pm$0.043)	0.8382 ($\pm$0.021)
CLAM	0.8465 ($\pm$0.029)	0.8766 ($\pm$0.030)
TransMIL	0.8775 ($\pm$0.014)	0.8883 ($\pm$0.017)
DTFD-MIL	**0.8837** ($\pm$0.010)	0.9147 ($\pm$0.011)
Ours	**0.8837** ($\pm$0.022)	**0.9248** ($\pm$0.014)

TABLE II: Comparison of MIL workflows on TCGA Lung Cancer Dataset

Model	Accuracy	AUC
ABMIL	0.8474 ($\pm$0.021)	0.9111 ($\pm$0.021)
CLAM	0.8676 ($\pm$0.036)	0.9489 ($\pm$0.013)
TransMIL	0.8877 ($\pm$0.057)	0.9618 ($\pm$0.027)
DTFD-MIL	0.8809 ($\pm$0.022)	0.9349 ($\pm$0.012)
Ours	**0.8884** ($\pm$0.016)	**0.9647** ($\pm$0.010)

Fig. 2: The relationship between the proportion of tumor instances of each codeword and the attention scores. Codewords with higher attention scores are red, and codewords with lower attention scores are green.

and tile cropping. The tile size was set to 224 × 224 at 20× magnification.

B. Evaluation Metrics

For Camelyon16, the provided training set was split into training and validation sets with a ratio of 0.9:0.1. We conducted five cross-validation experiments for a fair comparison. For the TCGA lung cancer dataset, we randomly split the dataset into training, validation, and test sets with ratios of 0.65, 0.1, and 0.25, respectively. We conducted three cross-validation experiments for this dataset. We report the mean and standard deviation of accuracy and AUC of our method alongside all baselines on both datasets.

C. Implementation Details

For a fair comparison, we use an ImageNet-pretrained ResNet50[6] as the frozen vision encoder to generate embedding vectors for our method and all baselines. It encodes image tiles of size 224 × 224 into embedding vectors of size 1024.

For all baselines, we used the same settings as described in their respective papers and source code.

For our method, we use a 3-layer MLP as the encoder Z_e, which projects the embedding vectors from size 1024 to size 512. We set the number of codewords in the codebook to 32, resulting in a codebook size of 32 × 512. The optimizer used is AdamW[32] with a learning rate of 0.0001. The batch size is set to 1, meaning only one slide is processed per iteration. Due to the different sizes of the datasets, we trained our model for 400 epochs on Camelyon16 and 100 epochs on the TCGA lung cancer dataset. We use pseudo-bags of size 256 as an additional data augmentation technique.

D. Slide-Level Performance

We compare our models with the following baselines: (1) attention-based methods, including the classic AB-MIL[8] and its two variants, CLAM[19] and DTFD-MIL[22]; and (2) the transformer-based method, TransMIL[20].

Table I summarize the slide-level performance of the baseline models and our method on Camelyon16. The results show that our method improved accuracy by 5.11% and AUC by 8.66% compared to the classic AB-MIL. Our method also outperforms CLAM and TransMIL. Compared to DTFD-MIL, our method achieved similar accuracy but improved AUC by 1.01%.

For TCGA lung cancer dataset, table II summarizes the slide-level results. Our method achieved the best performance, with an improvement in accuracy of 4.11% and AUC of 5.36% compared to the classic AB-MIL.

E. Distinguishability between the Tumor Instances and Normal Instances

We further tested the ability of the vector quantization module to distinguish between tumor and normal instances. We calculated the proportion of tumor instances corresponding to the 32 codewords of VQ-MIL trained on Camelyon16 and examined the attention scores associated with these codewords. The results are shown in Figure 2. We can see that different codewords have vastly different proportions of tumor instances. Some codewords contain more than 90% tumor instances, while many others consist almost entirely of normal instances. This indicates that codewords can effectively provide the task-specific information like distinguishing between tumor and normal instances. Additionally, there is a strong correlation between the proportion of tumor instances corresponding to a codeword and its attention score. Codewords with a high proportion of tumor instances correspond to high attention scores, whereas those with a low proportion correspond to low attention scores. This suggests that the model could effectively notice the codewords with higher tumor proportions for classification prediction.

(a) Embedding vectors of a WSI (tumor_093) in Camelyon16. The red points represent tumor instances and the cyan are normal. Left figure is the embedding vectors by the pretrained ResNet50. Right figure is the mapped discrete codewords after vector quantization, where the size of each point represents the number of instances that are mapped to this codeword. We can see that after the mapping, some tumor insances are separated from the normal ones.

(b) The aggregated slide embedding vectors. Left figure is the result of ABMIL. Right figure is the result of our proposed method. The cyan points represent normal slides and the pink are tumor slides. The red point is the WSI in (a), we can see that the ABMIL cannot predict this WSI correctly while our proposed method successfully do the classification.

Fig. 3: The t-SNE plot of embedding vectors in Camelyon16.

Figure 3a and 3b show the t-SNE plots of instance embedding vectors from a WSI in Camelyon16 and the slide embedding vectors obtained from all WSIs in the training set, respectively. In 3a, we observe that the instance embedding vectors generated by the vision encoder contain significant noise, with tumor instances buried among normal instances, making them difficult to distinguish. However, after being discretely mapped to codewords by the vector quantization module, some tumor instances are separated from the normal instances. This separation allows the MIL model to notice these distinct tumor instances, leading to stronger distinguishability in the slide embedding vectors, as reflected in 3b.

F. Instance-Level Annotation and Visualization

In this section, we demonstrate that our method provides better visualization for instance-level annotation of WSIs compared to previous models. Currently, drawing heatmaps of attention scores using attention-based MIL models is the common method for instance-level visualization in WSI classification. Compared to the previous attention-based models, our method has an advantage for visualization. In our model, the attention scores derived from the codewords are fixed. In most models, attention scores has to be normalized in the model

so that the sum of the attention scores for all instances in a slide is 1. This process can be detrimental to visualization. For example, higher attention scores usually should indicate a higher likelihood of being a tumor instance. However, due to normalization, there is no clear threshold for this likelihood, even normal slides may have many instances with high attention scores. In our model, although normalization is applied during prediction, the codebook is fixed after training. Thus we can use this codebook as a bag with K instances (codewords) and input it into the MIL model to obtain fixed attention scores. This approach results in better visualization outcomes. Figure 4 illustrates the difference in visualization performance.

G. Ablation Study

For analyzing of the contribution of each components in VQ-MIL, we conducted ablation study.

We tested the three components of our VQ-MIL: the encoder Z_e, the vector quantization process, and the data augmentation through pseudo bags.

Table III summarize the contribution of each component. In this table, the first row represents the basic AB-MIL model, which shows the lowest performance. The second row features AB-MIL with an additional encoder Z_e. The encoder Z_e encodes the embedding vectors to be more task-specific, although there is no vector quantization process to map the vectors to a discrete space. This addition improved the AUC by 2.77% and accuracy by 2.96% compared to the basic AB-MIL, indicating the importance of converting embedding vectors to be more task-specific. The third row represents VQ-MIL without additional data augmentation. Compared to the second row, it further improved the AUC by nearly 3% and accuracy by 1.24%, suggesting that a discrete embedding space is beneficial. The last row is the full version of our method, which achieves the best performance, highlighting the contribution of data augmentation through pseudo-bags. In conclusion, we find that each component significantly contributes to the overall performance.

Table IV shows the slide-level performance on the Camelyon16 dataset concerning different codebook sizes. For binary classification tasks, it might seem intuitive to set the codebook size to two; however, the performance is unsatisfactory because the encoder of the vector quantization module struggles to accurately cluster all instances into just two codewords. Increasing the size of the codebook improves performance. We also find that there is almost no difference in performance when the codebook size exceeds 16.

Table V shows the slide-level performance on Camelyon16 concerning different sizes of pseudo-bags. When the pseudo-bag size is too small, performance decreases rapidly. Since slides in Camelyon16 usually contain only a tiny fraction of tumor tissues, a small pseudo-bag may not include any positive instances. The best performance is achieved when the pseudo-bag size is 256. Performance decreases when the size of the pseudo-bags becomes larger because larger bags contain

(a) The visualization of a normal WSI in Camelyon16

(b) The visualization of a tumor WSI in Camelyon16

Fig. 4: Two visualization examples in Camelyon16. The left column is the provided ground truth annotation. The middle column is the heatmap from the classic AB-MIL. The right column is the heatmap from our method.

TABLE III: Contribution of different components of VQ-MIL on Camelyon16

	Accuracy	AUC
ABMIL	0.8326	0.8382
Encoder+ABMIL	0.8682	0.8659
VQ+ABMIL	0.8806	0.8955
VQ+ABMIL+pseudo-bags (ours)	**0.8837**	**0.9248**

TABLE IV: Different size of the codebook on Camelyon16

size	Accuracy	AUC
2	0.8465	0.8432
8	0.8202	0.7842
16	0.8620	0.9080
32	0.8806	0.8955
64	0.8806	0.8885
128	0.8744	0.8881
256	0.8806	0.9002
512	0.8760	0.8954

TABLE V: Different size of the pseudo bags on Camelyon16

size	Accuracy	AUC
128	0.8031	0.8119
256	0.8837	0.9248
512	0.8589	0.8859
8192	0.8558	0.8294

many simple instances, which are not helpful for the model to identify challenging instances.

V. CONCLUSION AND FUTURE WORKS

In this paper, we propose a new workflow VQ-MIL, which incorporating weakly supervised vector quantization into the previous workflow of WSI classification problems, allowing the embedding vectors extracted by a pre-trained vision encoder to be further encoded as discrete and task-specific codewords. Our model achieved superior results on Camelyon16 and TCGA lung cancer datasets. Additionally, the discretized codewords in our model provide clearer visualization effects. In future work, we look forward to further exploring the applications of discretized codewords in MIL, particularly in exploring how to use codewords for accurate instance-level classification.

ACKNOWLEDGMENT

The computing resources in this work were provided by Human Genome Center, the Institute of Medical Science, the University of Tokyo.

REFERENCES

[1] T. C. Cornish, R. E. Swapp, and K. J. Kaplan, "Whole-slide imaging: Routine pathologic diagnosis," *Advances in Anatomic Pathology*, vol. 19, no. 3, 2012.

[2] L. Qu, S. Liu, X. Liu, M. Wang, and Z. Song, "Towards label-efficient automatic diagnosis and analysis: a comprehensive survey of advanced deep learning-based weakly-supervised, semi-supervised and self-supervised techniques in histopathological image analysis," *Physics in Medicine & Biology*, vol. 67, no. 20, p. 20TR01, Oct. 2022. [Online]. Available: http://dx.doi.org/10.1088/1361-6560/ac910a

[3] C. L. Srinidhi, O. Ciga, and A. L. Martel, "Deep neural network models for computational histopathology: A survey," *Medical Image Analysis*, vol. 67, p. 101813, Jan. 2021. [Online]. Available: http://dx.doi.org/10.1016/j.media.2020.101813

[4] J. Rony, S. Belharbi, J. Dolz, I. Ben Ayed, L. McCaffrey, and E. Granger, "Deep weakly-supervised learning methods for classification and localization in histology images: A survey," *Machine Learning for Biomedical Imaging*, vol. 2, no. March 2023, p. 96–150, Mar. 2023. [Online]. Available: http://dx.doi.org/10.59275/j.melba.2023-5g54

[5] V. Cheplygina, M. de Bruijne, and J. P. Pluim, "Not-so-supervised: A survey of semi-supervised, multi-instance, and transfer learning in medical image analysis," *Medical Image Analysis*, vol. 54, pp. 280–296, 2019.

[6] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," 2015. [Online]. Available: https://arxiv.org/abs/1512.03385

[7] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, J. Uszkoreit, and N. Houlsby, "An image is worth 16x16 words: Transformers for image recognition at scale," 2021. [Online]. Available: https://arxiv.org/abs/2010.11929

[8] M. Ilse, J. M. Tomczak, and M. Welling, "Attention-based deep multiple instance learning," 2018. [Online]. Available: https://arxiv.org/abs/1802.04712

[9] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei, "Imagenet: A large-scale hierarchical image database," in *2009 IEEE Conference on Computer Vision and Pattern Recognition*, 2009, pp. 248–255.

[10] B. Li, Y. Li, and K. W. Eliceiri, "Dual-stream multiple instance learning network for whole slide image classification with self-supervised contrastive learning," 2021. [Online]. Available: https://arxiv.org/abs/2011.08939

[11] R. J. Chen, C. Chen, Y. Li, T. Y. Chen, A. D. Trister, R. G. Krishnan, and F. Mahmood, "Scaling vision transformers to gigapixel images via hierarchical self-supervised learning," 2022. [Online]. Available: https://arxiv.org/abs/2206.02647

[12] H. Xu, N. Usuyama, J. Bagga, S. Zhang, R. Rao, T. Naumann, C. Wong, Z. Gero, J. González, Y. Gu, Y. Xu, M. Wei, W. Wang, S. Ma, F. Wei, J. Yang, C. Li, J. Gao, J. Rosemon, T. Bower, S. Lee, R. Weerasinghe, B. J. Wright, A. Robicsek, B. Piening, C. Bifulco, S. Wang, and H. Poon, "A whole-slide foundation model for digital pathology from real-world data," *Nature*, vol. 630, no. 8015, pp. 181–188, Jun 2024. [Online]. Available: https://doi.org/10.1038/s41586-024-07441-w

[13] A. van den Oord, O. Vinyals, and K. Kavukcuoglu, "Neural discrete representation learning," 2018. [Online]. Available: https://arxiv.org/abs/1711.00937

[14] B. Ehteshami Bejnordi, M. Veta, P. Johannes van Diest, B. van Ginneken, N. Karssemeijer, G. Litjens, J. A. W. M. van der Laak, , and the CAMELYON16 Consortium, "Diagnostic Assessment of Deep Learning Algorithms for Detection of Lymph Node Metastases in Women With Breast Cancer," *JAMA*, vol. 318, no. 22, pp. 2199–2210, 12 2017. [Online]. Available: https://doi.org/10.1001/jama.2017.14585

[15] X. Wang, S. Yang, J. Zhang, M. Wang, J. Zhang, W. Yang, J. Huang, and X. Han, "Transformer-based unsupervised contrastive learning for histopathological image classification," *Medical Image Analysis*, vol. 81, p. 102559, 2022.

[16] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton, "A simple framework for contrastive learning of visual representations," 2020. [Online]. Available: https://arxiv.org/abs/2002.05709

[17] M. Caron, H. Touvron, I. Misra, H. Jégou, J. Mairal, P. Bojanowski, and A. Joulin, "Emerging properties in self-supervised vision transformers," 2021. [Online]. Available: https://arxiv.org/abs/2104.14294

[18] M. Oquab, T. Darcet, T. Moutakanni, H. Vo, M. Szafraniec, V. Khalidov, P. Fernandez, D. Haziza, F. Massa, A. El-Nouby, M. Assran, N. Ballas, W. Galuba, R. Howes, P.-Y. Huang, S.-W. Li, I. Misra, M. Rabbat, V. Sharma, G. Synnaeve, H. Xu, H. Jegou, J. Mairal, P. Labatut, A. Joulin, and P. Bojanowski, "Dinov2: Learning robust visual features without supervision," 2024. [Online]. Available: https://arxiv.org/abs/2304.07193

[19] M. Y. Lu, D. F. K. Williamson, T. Y. Chen, R. J. Chen, M. Barbieri, and F. Mahmood, "Data efficient and weakly supervised computational pathology on whole slide images," 2020. [Online]. Available: https://arxiv.org/abs/2004.09666

[20] Z. Shao, H. Bian, Y. Chen, Y. Wang, J. Zhang, X. Ji, and Y. Zhang, "Transmil: Transformer based correlated multiple instance learning for whole slide image classification," 2021. [Online]. Available: https://arxiv.org/abs/2106.00908

[21] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit,

L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," 2023. [Online]. Available: https://arxiv.org/abs/1706.03762

[22] H. Zhang, Y. Meng, Y. Zhao, Y. Qiao, X. Yang, S. E. Coupland, and Y. Zheng, "Dtfd-mil: Double-tier feature distillation multiple instance learning for histopathology whole slide image classification," 2022. [Online]. Available: https://arxiv.org/abs/2203.12081

[23] Y. Sharma, A. Shrivastava, L. Ehsan, C. A. Moskaluk, S. Syed, and D. E. Brown, "Cluster-to-conquer: A framework for end-to-end multi-instance learning for whole slide image classification," 2021. [Online]. Available: https://arxiv.org/abs/2103.10626

[24] Y. Zhou, S. Che, F. Lu, S. Liu, Z. Yan, J. Wei, Y. Li, X. Ding, and Y. Lu, "Iterative multiple instance learning for weakly annotated whole slide image classification," *Physics in Medicine & Biology*, vol. 68, no. 15, p. 155007, jul 2023. [Online]. Available: https://dx.doi.org/10.1088/1361-6560/acde3f

[25] H. Li, C. Zhu, Y. Zhang, Y. Sun, Z. Shui, W. Kuang, S. Zheng, and L. Yang, "Task-specific fine-tuning via variational information bottleneck for weakly-supervised pathology whole slide image classification," 2023. [Online]. Available: https://arxiv.org/abs/2303.08446

[26] J. Wu, *Advances in K-means clustering: a data mining thinking*. Springer Science & Business Media, 2012.

[27] A. A. Alemi, I. Fischer, J. V. Dillon, and K. Murphy, "Deep variational information bottleneck," 2019. [Online]. Available: https://arxiv.org/abs/1612.00410

[28] D. P. Kingma and M. Welling, "Auto-encoding variational bayes," 2022. [Online]. Available: https://arxiv.org/abs/1312.6114

[29] P. Liu, L. Ji, X. Zhang, and F. Ye, "Pseudo-bag mixup augmentation for multiple instance learning-based whole slide image classification," *IEEE Transactions on Medical Imaging*, vol. 43, no. 5, p. 1841–1852, May 2024. [Online]. Available: http://dx.doi.org/10.1109/TMI.2024.3351213

[30] A. Tarkhan, T. K. Nguyen, N. Simon, and J. Dai, "Investigation of training multiple instance learning networks with instance sampling," in *Resource-Efficient Medical Image Analysis*, X. Xu, X. Li, D. Mahapatra, L. Cheng, C. Petitjean, and H. Fu, Eds. Cham: Springer Nature Switzerland, 2022, pp. 95–104.

[31] N. Otsu, "A threshold selection method from gray-level histograms," *IEEE Transactions on Systems, Man, and Cybernetics*, vol. 9, no. 1, pp. 62–66, 1979.

[32] I. Loshchilov and F. Hutter, "Decoupled weight decay regularization," 2019. [Online]. Available: https://arxiv.org/abs/1711.05101