CV.eDNA: A hybrid approach to invertebrate biomonitoring using computer vision and DNA metabarcoding

Keywords: Machine Learning; Deep Learning; Computer Vision; Image Classification; Convolutional Neural Networks; Ecological Monitoring; Species Identification; Macroecology

Jarrett D. Blair [1,2], Michael D. Weiser [3], Cameron Siler [3,4], Michael Kaspari [3,5], Sierra N. Smith [3,4,6], Jessica F. McLaughlin [3,4], Katie E. Marshall[1]

[1] Department of Zoology, University of British Columbia, Vancouver, BC V6T 1Z4, Canada
[2] Department of Ecoscience, Aarhus University, 8000 Aarhus C, Denmark
[3] School of Biological Sciences, University of Oklahoma, Norman, OK 73019-0235, USA
[4] Sam Noble Oklahoma Museum of Natural History, University of Oklahoma, Norman, OK 73072-7029, USA
[5] Conservation Ecology Center, Smithsonian's National Zoo and Conservation
[6] Department of Biology Institute, Front Royal, VA 22630, University of Texas at Arlington, Arlington, TX, 76019, USA.

Corresponding author: Jarrett Blair, Department of Ecoscience, Aarhus University, C.F. Møllers Allé 8, 8000 Aarhus C, Denmark, jarrett@ecos.au.dk

Abstract

1.   Automated invertebrate classification using computer vision has shown significant potential to improve specimen processing efficiency. However, challenges such as invertebrate diversity and morphological similarity among taxa can make it difficult to infer fine-scale taxonomic classifications using computer vision. As a result, many invertebrate computer vision models are forced to make classifications at coarser levels, such as at family or order.

2.   Here we propose a novel modular method to combine computer vision and bulk DNA metabarcoding specimen processing pipelines to improve the accuracy and taxonomic granularity of individual specimen classifications. To improve specimen classification accuracy, our methods use multimodal fusion models that combine image data with DNA-based assemblage data. To refine the taxonomic granularity of the model's classifications, our methods cross-references the classifications with DNA metabarcoding detections from bulk samples. We demonstrated these methods using a continental-scale, invertebrate bycatch dataset collected by the National Ecological Observatory Network. We also introduce the CV.eDNA R package, which aims to assist practitioners looking to implement our methods.

3.   Using our methods, we reached a classification accuracy of 79.6% across the 17 taxa using real DNA assemblage data, and 83.6% when the assemblage data was "error-free", resulting in a 2.2% and 6.2% increase in accuracy when compared to a model trained using only images. After cross-referencing with the DNA metabarcoding detections, we improved taxonomic granularity in up to 72.2% of classifications, with up to 5.7% reaching species-level.

4. By providing computer vision models with coincident DNA assemblage data, and

refining individual classifications using DNA metabarcoding detections, our methods the

potential to greatly expand the capabilities of biological computer vision classifiers. Our

methods allow computer vision classifiers to infer taxonomically fine-grained

classifications when it would otherwise be difficult or impossible due to challenges of

morphologic similarity or data scarcity. These methods are not limited to terrestrial

invertebrates and could be applied in any instance where image and DNA metabarcoding

data are concurrently collected.

1. Introduction

Computer vision has the potential to transform invertebrate ecology by automating estimations of invertebrate abundance, biomass, and diversity (Høye *et al.*, 2021; Schneider *et al.*, 2022; Blair *et al.*, 2024). However, accurately classifying invertebrate species using computer vision is challenging. This is partly due to the sheer diversity of invertebrates, as there are an estimated 7.5 million (~1.5 million named) terrestrial invertebrates species globally (Stork, 2018). This has led most invertebrate classification models to opt for coarser taxonomic granularity (e.g. order-level instead of species-level classifications) with relatively few unique classification groups (usually <50; (Ärje *et al.*, 2020; Blair *et al.*, 2022; Schneider *et al.*, 2022). However, ecology studies can involve hundreds or thousands of species, which poses a challenge for simpler machine vision techniques.

One way computer vision models have overcome the challenge of handling many thousands or millions of classification labels is by including additional data modalities such as contextual metadata (e.g. collection location) in computer vision models. The mobile app iNaturalist uses this spatiotemporal data in combination with user-submitted photos to classify nearly 80,000 taxa across the tree of life (Leary *et al.*, 2023). Other studies have also found substantial improvements to classification accuracy with multimodal models that include both metadata and images (Berg *et al.*, 2014; Terry, Roy and August, 2020; Blair *et al.*, 2022). However, despite the potential improvements in accuracy, there are several pitfalls to consider when including spatiotemporal metadata in a computer vision model. For one, spatiotemporal metadata is a lagging indicator of species habitat occupancy (i.e. the presence or absence of a species at a given place and time), and as such it is susceptible to data drift over time (Friedland, 2024). That is, spatiotemporal distributions of taxa change over time, but computer vision models can only

learn from past data. Unless a computer vision model is updated frequently with more recent

data, the species range distributions it has learned may quickly become outdated. Finally, when

dealing with many machine learning classes, spatiotemporal metadata does not solve the

challenge of gathering enough training data to sufficiently train a computer vision model (Beery

et al., 2020). In short, studies that incorporate spatiotemporal metadata have shown that

supplemental, non-visual data can improve ecological computer vision models, but

spatiotemporal metadata itself has several potential drawbacks. In this study, we leverage an

alternative data stream that does not pose the same challenges associated with spatiotemporal

metadata: DNA metabarcoding.

DNA metabarcoding is an established tool in ecological research that allows for multiple species

to be identified from a single sample using high-throughput sequencing (Taberlet *et al.*, 2012;

Liu *et al.*, 2020). Using this method, DNA can be collected from the environment (eDNA) or

from preservative media (e.g. ethanol in insect bycatch samples), sequenced, and then used to

infer ecological metrics such as species richness and community composition (Marquina *et al.*,

2019; Weiser *et al.*, 2022). Due to its improved cost-effectiveness, DNA metabarcoding is

becoming more frequently used in large-scale studies where traditional morphological

identification techniques cannot keep up financially or logistically (Liu et al., 2020). However,

despite being an excellent tool for detecting occurrence at fine taxonomic granularity (even

below species-level; Stewart and Taylor, 2020), DNA metabarcoding cannot be used to reliably

estimate species abundance or biomass (Lamb *et al.*, 2019). Instead, eDNA metabarcoding is

more suitable for binary presence/absence detections of species. Additionally, while DNA

metabarcoding is generally reliable for taxonomic identifications, it is not exempt from false

positive and false negative detections (Guillera-Arroita *et al.*, 2017). Some examples of how this

may occur include DNA contamination and primer mis-priming (false-positives), or DNA

degradation and insufficient sampling effort (false-negatives) (Guillera-Arroita *et al.*, 2017; Liu

et al., 2020). Therefore, while DNA metabarcoding offers considerable advantages for

biodiversity assessment (e.g., species inventories, species richness) its limitations often

necessitate the use of complementary indicators such as visual observations for other metrics

(e.g., abundance, biomass) (Schneider et al., 2022).

Given DNA metabarcoding's ability to produce reliable fine-scale community composition data,

and computer vision's ability to measure abundance and biomass at coarse taxonomic

granularity, several studies have called for a synergistic classification pipeline that takes

advantage of the strengths of each tool (Schneider *et al.*, 2022; Sys *et al.*, 2022; Badirli *et al.*,

2023). In theory, such a pipeline could leverage DNA metabarcoding's fine taxonomic

granularity against computer vision's ability to infer specimen-level characteristics (identity,

morphology, etc.) to make ecological inferences that would not be possible using either data

stream on their own. DNA might also be a favourable alternative to spatiotemporal metadata, as

it is a more direct and coincident indicator of species habitat occupancy, likely making it more

resistant to data drift over time (Taberlet *et al.*, 2018). Despite the potential benefits of

multimodal image-DNA classification models for ecological research, few studies have explored

this approach. Additionally, proposed hybrid classification pipelines either leave the DNA and

image data streams separate (Sys *et al.*, 2022), or sequence specimens individually, and thus do

not take advantage of metabarcoding's ability to process bulk samples (Badirli *et al.*, 2023; Gong

et al., 2024).

Here we present a novel modular method for classifying invertebrate taxa that integrates DNA

metabarcoding and computer vision. The objective of this hybrid approach is to improve the

accuracy and taxonomic granularity of computer vision classifications by adding concurrent

community assemblage data derived from DNA metabarcoding into a bulk specimen

classification pipeline (Figure 1). The combination of DNA and image data occurs twice

throughout the pipeline: first during classification inference in the computer vision model, and

then again as a post-processing step for the model's classifications. While developing this

approach, we ask two primary questions: (1) How does error in DNA metabarcoding data affect

the accuracy of the computer vision classification model? (2) What are the strengths and

limitations of different classification granularity refinement methods? In addition to the case

study we present here, we have also developed a GitHub repository to allow our methods to

easily be adapted to other study systems (Blair, 2024). The repository introduces the CV.eDNA

R package, which contains functions that assist with the implementation of our methods. The

repository also includes demonstrative vignettes that walk through the data preparation, model

training, and classification granularity refinement steps.

114
Figure 1: An overview of our methods for combining computer vision and DNA metabarcoding to
improve the accuracy and taxonomic granularity of classifications. (a) Images and DNA metabarcoding
data are collected concurrently from bulk samples. (b) Images and DNA assemblage data are used as
input for a multimodal classification model. The features of the image input are extracted using a
convolutional neural network. The DNA assemblage data provides presence/absence information for the
model's known classes and is input as a binary vector into a dense neural network. The image features
and the DNA features are concatenated and passed through one more dense layer before final
classification in the softmax layer. The visual proportions of each layer have been simplified to ease
interpretation and are not meant to be interpreted as 1:1 representations of the exact layer sizes. (c) By
interpreting the DNA metabarcoding detections hierarchically and cross-referencing them with the
model's classifications, the taxonomic granularity of the classifications can be refined.

2. Methods

2.1 Data collection

2.1.1 Specimen collection

Each year, the National Ecological Observatory Network (NEON) performs standardized pitfall

trap array sampling across the United States, including Alaska, Hawaii, and Puerto Rico

(Hoekman et al. 2017). The focal taxon of the pitfall trap array project are ground beetles

(Coleoptera: Carabidae), which are collected, identified, and counted by NEON staff members

once every two weeks during the growing season (defined as "the weeks when average minimum

temperatures exceed 4 °C for 10 days and ending when temperatures remain below 4 °C for the

same period", Kaspari et al., 2022). The remaining pitfall trap contents are set aside as

'Invertebrate Bycatch' and archived in 95% ethanol-filled 50 mL centrifuge tubes. Hereon, a

single collection period from a pitfall trap plot is referred to as a "sampling event".

The invertebrate bycatch specimens used in this research were taken from 56 NEON trap plots

from 27 sites (usually two plots per site; Figure S.1, S.2). Generally, we used three sampling

events per plot, selected at the beginning, middle, and end of each site's growing season. This

resulted in a total of 150 sampling events. All sampling events used here were collected in 2016

and processed in 2019. The focus of this project was to classify the invertebrate bycatch, so

ground beetles and non-invertebrate specimens were not considered.

2.1.2 Imaging

The contents of each 50mL centrifuge tube were spread out across a 20.32 cm ✖ 30.48 cm (8" ✖

12") white ceramic tile and photographed at a resolution of 729 pixels per mm^2, as described by

Weiser et al., 2021 (Figure S.3). Using the FIJI implementation of ImageJ (Schindelin et al.,

2012), each specimen was detected and cropped to its bounding box to produce a final image.

2.1.3 DNA extraction and metabarcoding

The DNA metabarcoding data used in this study was collected for Weiser et al., 2022, which

used the same sampling events described in Section 2.1.1. In brief, DNA metabarcoding was

conducted on a per-tube basis (Figure S.1). Ethanol from each falcon tube was filtered

individually (i.e., one filter per tube) and DNA was extracted from the filters using established

protocols (Weiser et al., 2022). The cytochrome c oxidase I (COI) barcode region (141-254 base

pairs) was then amplified using a two-step polymerase chain reaction (PCR) protocol and

sequenced on an Illumina MiSeq. Three COI primers were used: 157, LCO, and Lep (Rennstam

Rubbmark *et al.*, 2018, 2018; Hajibabaei *et al.*, 2019; Weiser *et al.*, 2022). Sequences were

clustered into Operational Taxonomic Units (OTUs) and each OTU was assigned a taxonomic

classification using NCBI BLASTn (Altschul *et al.*, 1990) and Integrated Taxonomic

Information System (ITIS) (U.S. Geological Survey, 2013). Only sequences with $\geq 97\%$

similarity between the OTU consensus sequence and the BLASTn search were used. See Weiser

et al., 2022 for the full DNA extraction and metabarcoding methods.

In total, across all sampling events, there were 10,212 DNA metabarcoding detections. To align

the DNA data with the imaging data, we removed any DNA detections from sampling events not

included in the image dataset, as well as duplicate detections (i.e. multiple detections of the same

taxon in a single sampling event, for example due to amplification using multiple primers). This

yielded a final DNA metabarcoding dataset with 3,361 detections and 1,212 unique taxa,

primarily consisting of family (369 detections; 85 unique), genus (468 detections; 183 unique),

and species-level (2,471 detections; 922 unique) detections.

2.2 Data and labelling

2.2.1 Computer vision class labels

The taxonomic scope of the image and DNA metabarcoding data spanned three invertebrate

phyla: Annelida, Arthropoda, and Mollusca. The specimen images were labelled by a single

technician to the best of their ability (as described in Blair *et al.*, 2022). The final labels used for

our study ranged from order to phylum-level. Classes with a taxonomic granularity coarser than

order-level but with no subtaxa present in the dataset (e.g. Phylum: Annelida) were included.

Specimens labelled as nested classes at a taxonomic granularity coarser than order-level

(Phylum: Arthropoda, Class: Insecta, and Class: Arachnida) were excluded, as these classes were

primarily composed of "low quality" specimens (highly degraded, low image quality, partial

specimens, etc.) that could not confidently be assigned finer level labels. Classes with fewer than

100 specimens in the dataset were also excluded. This resulted in a final image dataset with a

total of 36,998 specimens across 17 machine learning classes (13 orders and one subclass, class,

subphylum, and phylum; Figure S.4).

2.2.2 Hierarchical labels

Hierarchical labels created by the `refhier` and `longhier` functions in the CV.eDNA package

contain taxonomic information at multiple levels (e.g. phylum to species) and can be assigned to

images and sampling events (Table S.1, Table S.2). These labels are used as input for the

classification granularity refinement methods (see Section 2.5).

In our case study, our image-based hierarchical labels contained taxonomic information at six

levels from phylum to order-level for individual specimens (Table S.1). Our DNA-based

hierarchical labels contained information at 13 levels from phylum to species for all DNA

metabarcoding detections in each sampling event (Table S.2). The levels in the DNA-based

hierarchical labels were phylum, subphylum, class, subclass, superorder, order, suborder,

infraorder, superfamily, family, subfamily, genus, and species.

2.2.3 Binary assemblage data

The `get_assemblage` function in the CV.eDNA package generates binary assemblage data for

sampling events. This assemblage data can then be used as class priors or input features for

classification models (see Section 2.4). To generate this assemblage data, the function receives

DNA metabarcoding data or ground truth image metadata as input and outputs an n-element long

binary vector for each sampling event, where n is the number of classes known by the computer

vision model. If a given class is detected in a sampling event, its corresponding element is

assigned a score of 1, whereas it is assigned a score of 0 if it was not detected.

For our case study we generated two sets of binary assemblage data containing our 17 known

classes: one using detections from the image labels and one using detections from the DNA class

labels.

2.3 Training and testing data split

Quasi-replication occurs in machine learning datasets when the same or very similar data occur

in both the training and testing datasets. This violates the assumption of independence between

training and testing data and should be avoided to make valid inferences on the test data. The

DNA-based assemblage data presented a quasi-replication risk, as specimens from the same

sampling event would have the same assemblage data. To avoid quasi-replication, we split the

training and testing such that all specimens from a given sampling event were only included in

either the training or testing data. We set our target training:testing ratio to 85:15, and we

randomly added sampling events to the test dataset until the test dataset contained >15% of the

total number of specimens. The final train:test split was 31,381: 5,617 specimens and 122:28

sampling events.

2.4 Classification models

The objective of all the classification models was to accurately classify the class labels of

individual specimen photos. Classification masks (Section 2.4.2) and multimodal fusion

approaches (Section 2.4.3) were used to assess how classification accuracy changes when DNA-

based assemblage data was added to the specimen classification pipeline. Both the classification

masks and multimodal fusion models included "oracle" experiments, which used image-based

assemblage data to simulate the performance of these methods under optimal conditions. We

trained each classification model until the test dataset loss had not improved for 10 epochs (this

does not include the classification masks, which did not go through the training process).

Performance of each classification model was assessed using the original image labels as a

ground truth. All code required for running these models can be found in the "Model_Scripts"

subdirectory of our GitHub repository (Blair, 2024). All models were trained using an AMD

Ryzen 7 5800X CPU, an NVIDIA GeForce RTX 4070 Ti GPU and 32 GB of RAM.

<u>2.4.1 Baseline model</u>

To evaluate model performance in the absence of DNA-based assemblage data, we trained a

ResNet-50 (He et al., 2016) as a baseline model using only image data. The model was pre-

trained using the ImageNet weights from He et al. (2016), and then fine-tuned using the NEON

invertebrate bycatch image data. The ImageNet classification layer was removed and replaced

with a new classification layer for our 17 classes. A batch normalization and dropout step were

also implemented before the final classification layer. The model was trained using the Adam

optimizer. The baseline model took 45 seconds per epoch to train, and 7 seconds to run inference

on the test dataset.

<u>2.4.2 Classification masks</u>

If *a priori* probabilities for classes in a classification model are known, the outputs of the model

can be adjusted according to those probabilities to improve classification accuracy (Saerens,

Latinne and Decaestecker, 2002). We implement two variations of this technique which we call

"Naïve masks" (Section 2.4.2.1) and "Weighted Masks" (Section 2.4.2.2), whereby the class

priors are derived from a sample's DNA metabarcoding assemblage data. To apply classification

masks to our case study, each test dataset specimen's classification probabilities (i.e. softmax

layer values) from the baseline model were multiplied by their sampling event's classification

mask values. The class with the highest classification probability after applying the mask was

used as the final classification.

2.4.2.1 Naïve mask

When using a naïve mask, the softmax layer values for a given specimen are multiplied by the

specimen's sampling event's binary DNA metabarcoding assemblage data (generated using the

`get_assemblage` function). Thus, any classes not detected by the DNA metabarcoding in a

given sampling event have their respective softmax values set to 0, whereas the remaining

classes are unaffected. Naïve masks essentially operate as a "hard filter", where only classes

detected by the DNA metabarcoding can be classified by the model.

2.4.2.2 Weighted mask

"Hard" masks like the naïve mask, which set the softmax values of undetected classes to 0,

assume the DNA metabarcoding data is error-free. However, in reality, DNA metabarcoding can

have false positive and/or false negative detections (Taberlet *et al.*, 2018). A weighted mask is a

"softer" version of a naïve mask that allows classes not detected by the DNA metabarcoding to

still be classified. The weights for a weighted mask can be generated using the `get_weights`

function of the CV.eDNA package, and are calculated using the metabarcoding's true positive

rate (precision) and false negative rate (1 - recall) for each class. The DNA metabarcoding

precision and recall are calculated by comparing the DNA-based assemblage data to ground-truth

assemblage data (e.g. manually assigned image-based assemblage data). The weight that is

assigned to any given class in a sample is determined by whether or not the class was detected by

the DNA metabarcoding. Classes which have their DNA detected are assigned their

metabarcoding precision value, while classes which do not have their DNA detected are assigned

their 1 – recall value.

2.4.2.3 Oracle mask

As an oracle experiment to simulate a scenario where the DNA detections were in perfect

alignment with the image-based detections, we created a naive classification mask using the

image-based assemblage data. This mask was then applied to the classification output of the

baseline model. We did this to provide an upper-bound for the classification mask accuracy, and

to understand how DNA detection accuracy impacts specimen classification accuracy when

using classification masks.

2.4.3 Multimodal fusion

In deep learning, multimodal models can receive data from multiple modalities as input to

inform their classifications (Ramachandram and Taylor, 2017). For example, previous studies

have described multimodal classification models that receive images and raw DNA barcode

sequence data for individual specimens (Badirli *et al.*, 2023; Gong *et al.*, 2024). However, no

previous studies have described a multimodal model that combines specimen images with DNA

metabarcoding data from bulk samples. We achieve this by inputting DNA metabarcoding data

as tabular binary assemblage data, which is then combined with specimen image features using

intermediate fusion (Figure 1b). Intermediate fusion is an approach to building multimodal

models where data from each modality is input separately. The features from each input are then

extracted and concatenated prior to classification (Boulahia *et al.*, 2021). This allows the model

to contextualize a specimen's image features with class presence-absence data from the

specimen's sample. However, similar to the weighted mask approach (Section 2.4.2.2), the DNA

metabarcoding data does not act as a "hard filter", and the model can still make classifications

not detected by DNA metabarcoding. Additionally, because the assemblage data contains all

class detections for a given sample, the model can learn patterns of class co-occurrence to inform

its classifications.

In our case study, we paired our DNA metabarcoding assemblage data with individual specimens

based on their sampling event (the same approach as the classification masks described in

Section 2.4.2). After being input, features of the assemblage data were extracted using a single

fully-connected layer with batch normalization and dropout. Specimen images were fed through

the ResNet-50 architecture, which ultimately producing a flat feature layer. The image and

assemblage feature layers were then concatenated and passed through another fully-connected

layer with batch normalization and dropout before reaching the final classification layer. During

training, both sides of the multimodal model were trained simultaneously using the Adam

optimizer.

To understand the effect that DNA detection accuracy has on classification performance, we ran

three versions of the multimodal model using different types of assemblage data as input: (1)

using the DNA-based assemblage data, (2) using the image-based assemblage data, and (3) using

'zero-filled' assemblage data (all values in the assemblage data are set to zero). In all three

experiments the training and testing datasets used the same assemblage data type (i.e. DNA-

based, image-based, or zero-filled). All three experiments used the same overall model

architecture as described in Figure 1b. The purpose of the image-based assemblage experiment

was to simulate the results of a model where the DNA detections perfectly aligned with the

ground truth labels (i.e. an oracle experiment). The purpose of the zero-filled assemblage

experiment was to control for differences in model architecture when comparing the multimodal

models to models trained without DNA-based assemblage data, as the zero-filled data would

provide no informative value to the model. The zero-filled assemblage data had the same

dimensions as the other assemblage data (17 values for each sampling event). The multimodal

models took 105 seconds per epoch to train, and 16 seconds to run inference on the test dataset.

2.5 Refining taxonomic granularity using DNA-based assemblage data

A strength of DNA metabarcoding is its ability to produce species-level detections. The

`modelbias` and `dnabias` functions in our CV.eDNA package take advantage of this strength to

refine the taxonomic granularity computer vision model classifications by cross-referencing them

with the DNA metabarcoding detections (Figure 2). When using either function in cases where

the model classifications and DNA metabarcoding detections agree on the presence of a class,

the granularity of the classification improves until the number of subtaxa detected by the DNA

metabarcoding was greater than 1 or the granularity reached species-level (Figure 2a,b). The

functions differ in cases where the model classifications and DNA detections disagree on the

presence of a class classified by the model. The model-biased method of the `modelbias`

function is simple. In cases where the model and DNA metabarcoding disagree, the model

classification remains unchanged (Figure 2c). When using the DNA-biased method of the

`dnabias` function, the hierarchical label of the classified specimen is cross referenced with the

DNA metabarcoding hierarchical labels of the sampling event (Figure 2d, Table S.1, Table S.2).

Starting from the original classification level, the granularity of the label is coarsened until an

agreement between the model and DNA metabarcoding is reached. The taxonomic name at this

level becomes an intermediate label, which is refined until the number of subtaxa detected by the

DNA metabarcoding is greater than 1 or the granularity reached species-level.

To test the effectiveness of each method, we applied the model-biased and DNA-biased methods

to the classifications of our DNA multimodal fusion model. A vignette for these methods can be

found on our GitHub repository (Blair, 2024).

338
Figure 2: Four methods of changing a label's granularity using DNA detections. (a,b) When the
classification label and DNA detections are in agreement about the presence of a class, granularity will be
refined until the number of subtaxa detected by the DNA metabarcoding is > 1 or the classification
reaches species level. (c) Under the model-biased approach, when the classification label and DNA
metabarcoding do not agree on the presence of a class, the classification label remains unchanged. (d)
Under the DNA-biased approach, when the classification label and DNA metabarcoding do not agree on
the presence of a class, the granularity of the classification label is coarsened until a DNA detection for
the class is found ("intermediate label"). The granularity of the intermediate label is then refined using the
same rules as (a,b).

3. Results

3.1 DNA metabarcoding precision and recall

To generate the weights for the weighted mask, we calculated the DNA-based assemblage data's

precision and recall for each class using the image-based assemblage data as the ground truth.

This calculation only included sampling events from the training dataset. Across the 17 predicted

classes, recall ranged from 0.905 to 0.000, with an average recall of 0.570. The weight for a

negative detection was 1 - recall, so negative detection weights ranged from 1.000 to 0.095, with

an average of 0.430. Two classes (Opilioacarida and Zygentoma) were never detected by the

DNA. Across the 15 classes detected by the DNA, the average precision was 0.761. The

precision and recall values per class are reported in Table S.3.

3.2 Classification accuracy

Compared to the baseline model, the DNA multimodal fusion model improved accuracy by 2.2%

(79.6% vs 77.4%; Table 1). However, the DNA multimodal fusion model's accuracy was 1.0%

lower than the zero-filled model's accuracy (80.6%). This suggests that some of the performance

improvements seen in the multimodal fusion models could come from changes to the model

architecture. The naïve classification mask recorded the lowest classification metrics, with an

accuracy 22.6% below the baseline model (54.8%), and a top-3 accuracy of only 64.0%.

Our oracle experiments with image-based assemblage data performed better, with the

multimodal fusion model reaching an average accuracy of 83.6% and a balanced accuracy (i.e.

macro-averaged recall) of 0.713 (Table 2). The image-based naive mask accuracy was 25.8%

better than the DNA-based naive mask, and 3.2% better than the baseline model. It also had the

highest top-3 accuracy across all experiments at 93.2%. Training dataset accuracy results for all

non-mask experiments are reported in Table S.4.

Table 1: Performance metrics for experiments trained using DNA-based assemblage data, other than the
baseline model, which was trained only using images, and the 'zero-filled' experiment, which replaced all
assemblage data values with zero to control for the impact of model architecture. Underlined scores
indicate they are the highest for a given metric.

Experiment	Accuracy	Balanced Accuracy	Top-3 Accuracy
Baseline	0.774	0.674	0.952
Naive mask	0.548	0.509	0.640
Weighted mask	0.764	0.666	0.950
Multimodal fusion	0.796	0.680	0.957
Multimodal fusion (zero-filled)	0.806	0.670	0.952

375 Table 2: Performance metrics for the oracle experiments using image-based assemblage data. These
376 experiments used binary assemblage data taken from the ground truth specimen labels. Underlined scores
377 indicate they are the highest for a given metric.

Experiment	Accuracy	Balanced Accuracy	Top-3 Accuracy
Mask	0.806	0.690	0.959
Multimodal fusion	0.836	0.713	0.963

3.3 Taxonomic granularity

Of the DNA multimodal fusion model classifications, 68.2% (3833/5617) were present in their

corresponding sampling event's DNA assemblage data. Nonetheless, both approaches for

handling disagreements between the DNA and classification model (model-biased or DNA-

biased) improved the average taxonomic granularity of the classifications (Figure 3). Despite

starting with no classifications finer than order-level, the DNA-biased approach resulted in 5.7%

of classifications improving to species-level and the model-biased approach resulted in 5.1% of

the classifications improving to species-level. The DNA-biased approach was more effective

overall at refining the granularity of classifications, with 72.2% of classifications becoming finer

than their original classification, and 43.1% reaching at least family-level. In the model-biased

approach, 51.7% of classifications improved their granularity, and 31.0% reached family-level or

lower. When looking exclusively at classifications where the DNA assemblage data and

multimodal fusion model classifications agreed on the presence of a class, 7.5% reached species

level, 45.4% reached family-level or lower, and 75.7% became finer than their original

classifications. Both the DNA-biased and model-biased approaches produced 89 unique final

labels (Table S.5).

Figure 3: Sankey diagrams showing the change in taxonomic granularity before (left) and after (right)
cross-referencing labels with the DNA detections. (a) DNA-biased approach. (b) Model-biased approach.
(c) Results when the model classification and DNA detections agree on the presence of the labelled class.

4 Discussion

Here we show that combining concurrent DNA metabarcoding assemblage data with computer

vision can improve the accuracy and taxonomic granularity of computer vision classifications.

Unlike most classification pipeline enhancements which only focus on improving the ability to

classify classes on which it was trained ("known classes"), this approach adds the ability for the

pipeline to infer classifications beyond the model's usual taxonomic scope ("unknown classes").

Our methods could be applied to any study system where images and DNA metabarcoding data

are collected concurrently, provided that the practitioners have labelled data to train their own

classification model. To thoroughly explore the benefits and implications of our hybrid approach,

we focused on the following two research questions.

4.1 How does DNA metabarcoding accuracy affect specimen classification accuracy?

The effect of metabarcoding accuracy on classification accuracy differed between the

classification masks and the multimodal fusion models, illuminating a key difference between

them: classification masks (as used in this study) do not take class co-occurrence into

consideration, whereas the multimodal models do. Put another way, in a classification mask the

only factor that directly influences the weight given to a class is the presence or absence of the

class itself. Conversely, the neural networks of multimodal fusion models—with their fully-

connected structure—allow the presence or absence of all classes to holistically influence each

class's classification probability. This allows the model to use patterns of class co-occurrence to

inform its classification decisions.

The different mechanisms used by classification masks and multimodal models are best

demonstrated in Table 2, where the assemblage data was derived from the ground-truth image

labels. In the classification mask, the model's original classifications were exclusively based on

image data, and any classifications that did not match their respective assemblage data were

reclassified as the class with the highest softmax score that was present in the specimen's

assemblage. Given that the assemblage data was derived from the ground truth labels, this mask

acted as a sieve that filtered out any classes that could not possibly be the correct classification

based on the assemblage data. As a result, it could only have a positive impact on accuracy.

However, despite this, the multimodal fusion model still scored higher on all three metrics

measured (top-1 accuracy, balanced accuracy, and top-3 accuracy). This implies that the

multimodal fusion model was not just using the assemblage data as a filter, but that it provided

additional contextual information (such as class co-occurrence or class exclusion) that further

improved accuracy. Thus, due to the multimodal fusion model's ability to holistically evaluate

occurrence data, and as illustrated through its superior performance compared to classification

masks even under ideal conditions, multimodal fusion models are likely to be preferable in most

use cases. This conclusion is reinforced by the results of Table 1, where both naïve and weighted

masks showed negative effects on all classification performance metrics when the DNA-based

assemblage data contained substantial amounts of error.

4.2 What are the strengths and limitations of each granularity refinement method?

Here we proposed two approaches for cross-referencing DNA metabarcoding data to achieve the

novel ability of refining the taxonomic granularity of computer vision classifications. The two

approaches differ in how they resolve disagreements between the detections of the DNA

metabarcoding and computer vision classifications, with the model-biased approach favouring

the computer vision classifications, and the DNA-biased approach favouring the DNA

detections. As such, each approach has its own set of advantages and limitations.

Through the ability to coarsen granularity before refining it, the DNA-biased method can make

classifications outside of the taxonomy of the original classification model (Figure S.5).

Explained another way, the model-biased approach and traditional hierarchical classifiers (e.g.

Badirli *et al.*, 2023) can only adjust classifications "vertically" (i.e. to supertaxa or subtaxa of the

original classifications), but the DNA-biased approach can also adjust classifications "laterally"

to out-of-distribution taxa through a combination of classification coarsening and refining.

Classification of out-of-distribution taxa is usually only possible using feature embedding

learning methods such as zero-shot learning (Badirli *et al.*, 2021). An illustrative example of this

comes from the DNA-biased approach's detection of taxa within the insect order Psocodea (e.g.

Valenzuela flavidus; Table S.5). As Psocodea was not included as a class in our model, and our

model's finest taxonomic granularity was order-level, Psocodea's branch of the taxonomy was

only accessible through a "lateral" taxonomic adjustment (Figure S.5). As such, it was only

detected by the DNA-biased approach, and not the model-biased approach (Table S.5). In theory,

this extends the range of possible classifications to the full taxonomic scope of the genetic

reference database being used (e.g. GenBank, Barcode of Life, etc.) (Ratnasingham and Hebert,

2007; Sayers *et al.*, 2024). In practice, it is likely best to self-impose limits on how much the

DNA-biased method can coarsen granularity. In our case we limited ourselves to phylum, as we

were only interested in classifications within our three focal phyla.

While it does not have the same potential taxonomic scope of the DNA-biased approach, an

advantage of the model-biased approach is that the taxonomic granularity of the final

classification cannot be coarser than the original classification. Applied to the DNA multimodal

fusion model classifications, 9.9% of all classifications became coarser when the DNA-biased

method was used (Figure 3). While the DNA-biased method classified more specimens at

family-level or finer (43.1% vs 31.0%), the ability to coarsen granularity resulted in more

classifications above order-level (11.7% vs 6.4%).

Even when granularity does not reach species, classifications that match with the DNA-based

assemblage data still provide more information than what is typically output from a classification

model. This is because we can also see the number and identity of subtaxa that the specimen

could be according to the DNA metabarcoding detections. For example, if the DNA

metabarcoding detected three species of the cricket genus *Gryllus* in a sample, we could say the

label of a specimen that would otherwise be classified simply as "*Gryllus* indet." is actually one

of three possible species of *Gryllus*, as detected by the DNA metabarcoding (e.g. *G.*

pennsylvanicus, *G. rubens*, or *G. veletis*). This might also be useful for future developments to

these methods, as the number of subtaxa detected by the DNA metabarcoding could be used to

inform clustering algorithms that separate the specimens into morphotaxa.

Of course, the granularity of classifications matters little if they are not accurate. A caveat of our

study is that we cannot verify the accuracy of granularity-refined classifications, as they are at

lower taxonomic levels than our ground truth (human-classified) labels. However, we know that

our classification models were more accurate than the DNA assemblage data when compared to

our ground-truth labels. Thus, the DNA-biased method of refining granularity will likely add

more error to the classifications than the model-biased approach. When deciding between the

two methods, this is likely to be a determining factor: does the computer vision model or DNA

metabarcoding contain more error?

4.3 Caveats and areas for future exploration

In an applied context, we cannot definitively conclude that image-DNA multimodal fusion

models as we present here improve specimen classification accuracy. This is primarily due to the

high rates of disagreement (or "error") between our DNA metabarcoding detections and image-

based detections. When comparing our three multimodal fusion experiments, the zero-filled

experiment had a top-1 accuracy 1.0% higher than the DNA-based assemblage data experiment,

but 3.0% less than the oracle experiment. This suggests that in an ideal situation where the DNA-

based assemblage data has low amounts of error (i.e. it is more similar to the image-based

assemblage data), image-DNA multimodal fusion models will positively impact classification

accuracy. However, when the DNA-based assemblage data contains substantial error, differences

in performance between the baseline and multimodal fusion models likely arise from changes in

the model's architecture.

Reconciling genetic-based and morphology-based data—the two chief methods for invertebrate

biodiversity monitoring—is a pressing need as previous studies have shown that assemblages

determined by visual classification usually differ from assemblages determined using DNA

metabarcoding. For example, Emmons *et al.* (2023) found that NEON benthic macroinvertebrate

samples classified by taxonomists only shared 59% of order-level detections with DNA

metabarcoding data derived from homogenized blends of the same samples. Similar results have

also been produced in other studies comparing metabarcoding methods to morphologic

identification (Remmel *et al.*, 2024; Salis *et al.*, 2024). Marquina *et al.*, (2019) also found that

different DNA sampling protocols can produce inconsistent assemblage data, as DNA

metabarcoded from ethanol vs homogenized blends of the same samples yielded significantly

different assemblage data, with both methods detecting taxa not detected by the other. Despite

these challenges, solutions to improve invertebrate detections using DNA metabarcoding are

being investigated. Proposed solutions range from changes in sampling methodology (e.g.

strategically subsetting bulk samples; (Remmel *et al.*, 2024) to improvements in the

completeness of publicly available DNA reference databases (Salis *et al.*, 2024). For the image-

DNA multimodal fusion methods we propose here to be maximally effective, advances will need

to be made in DNA metabarcoding methodology to limit false positive and false negative

detections.

Beyond DNA metabarcoding accuracy, there are likely other factors that can impact the efficacy

of our methods, such as the alpha and beta diversity of the sample assemblages. Lower alpha

diversity and higher beta diversity should yield models with greater classification performance.

Higher beta diversity would improve classification performance because the composition of the

assemblages would be more heterogeneous, which is required for learnable patterns to emerge in

the data. For example, our zero-filled assemblage experiment used data that was completely

homogenous, as every sampling event had the same assemblage data, thus allowing no learnable

patterns to emerge from the assemblage data. Conversely, lower alpha diversity would improve

classification performance because more classes to be filtered out by the model. This is partially

demonstrated by comparing the results of Blair *et al.* (2020) to the results we present here. In

their study, which built classification models for NEON's carabid beetles, the authors applied

classification masks to their models based on the detected ground beetle assemblages at each

sampling site. On average, 2.93 out of 25 potential species (11.7%) were detected per site,

resulting in an accuracy improvement of 10.9% (84.7% → 95.6%) after applying the

classification masks. Comparatively, our image-based assemblages detected an average of 9.09

out of 17 potential classes (53.5%) per sampling event. When compared to the baseline model,

this resulted in an accuracy improvement of 3.2% when using the classification mask and 6.2%

in the multimodal fusion model (Table 1, Table 2). Sample alpha diversity also has an impact on

the efficacy of the classification granularity refinement step. Higher alpha diversity increases the

odds that related taxa could present in the same sample, which can force our granularity

refinement methods to stop at a coarser taxonomic rank (Figure 2). Thus, sampling methods that

increase sample beta diversity (e.g. finer-grain class labels; Terlizzi *et al.*, 2009) and reduce

sample alpha diversity (e.g. smaller sample size; Chiu, 2023) will likely increase the efficacy of

image-DNA metabarcoding multimodal fusion classification pipelines.

4.4 Broader applications and implications

In this study, we used assemblage data derived from DNA metabarcoding to improve computer

vision classifications of terrestrial invertebrates. Previous studies (Badirli *et al.*, 2023; Gong *et*

al., 2024) have paired images of specimens with their DNA barcode sequence as input for

multimodal classification models. However, this technique cannot be applied to DNA

metabarcoding data because samples are metabarcoded in bulk, so the metabarcoded sequences

cannot be paired with individual specimens. Our methods overcome this challenge by converting

DNA metabarcoding data to binary assemblage data, which can then be input to a multimodal

classification model. This advancement has several practical implications, as DNA

metabarcoding's ability to process bulk samples means that it is more time efficient, less

expensive, and produces less waste than individual specimen barcoding (Gueuning *et al.*, 2019).

Our method's ability to refine classification granularity, which is typically not possible in

computer vision, could improve the feasibility of building broad-scope, fine-grain classification

models (e.g. models spanning entire classes or phyla and capable of producing species-level

classifications). This typically requires vast amounts of training data, as training examples need

to be provided for every species. Using the approach that we present here, classifiers could be

trained at coarser taxonomic levels such as order or family and still have the potential to produce

species-level classifications. This would decrease the number of classes in the model, and thus

data needed to train it, by orders of magnitude. Hence, the synergy between DNA metabarcoding

and computer vision outlined in this study paves the way for new possibilities in computer vision

classification of taxa, with the potential for improved accuracy and granularity with far less data

dependency.

Author contributions

JDB and KEM conceived the ideas and designed methodology; JDB, MDW, CS, SNS, and JFM

collected data and helped refine ideas; JDB analysed the data and led the writing of the

manuscript. KEM and MK were principal investigators. All authors contributed critically to the

drafts and gave final approval for publication.

References

Altschul, S.F. *et al.* (1990) 'Basic local alignment search tool', *Journal of Molecular Biology*, 215(3), pp. 403–410. https://doi.org/10.1016/S0022-2836(05)80360-2.

Ärje, J. *et al.* (2020) 'Automatic image-based identification and biomass estimation of invertebrates', *Methods in Ecology and Evolution*, 11(8), pp. 922–931. https://doi.org/10.1111/2041-210X.13428.

Badirli, S. *et al.* (2021) 'Fine-Grained Zero-Shot Learning with DNA as Side Information', in *Advances in Neural Information Processing Systems*. Curran Associates, Inc., pp. 19352–19362. https://proceedings.neurips.cc/paper_files/paper/2021/hash/a18630ab1c3b9f14454cf70dc711483 4-Abstract.html (Accessed: 24 July 2024).

Badirli, S. *et al.* (2023) 'Classifying the unknown: Insect identification with deep hierarchical Bayesian learning', *Methods in Ecology and Evolution*, 14(6), pp. 1515–1530. https://doi.org/10.1111/2041-210X.14104.

Beery, S. *et al.* (2020) 'Synthetic examples improve generalization for rare classes', in *Proceedings - 2020 IEEE Winter Conference on Applications of Computer Vision, WACV 2020*. https://doi.org/10.1109/WACV45572.2020.9093570.

Berg, T. *et al.* (2014) 'Birdsnap: Large-scale fine-grained visual categorization of birds', in *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pp. 2011–2018. https://doi.org/10.1109/CVPR.2014.259.

Blair, J. D. (2024) 'CV-eDNA-Hybrid'. https://github.com/Jarrett-Blair/CV-eDNA-Hybrid.

Blair, J.D. *et al.* (2020) 'Robust and simplified machine learning identification of pitfall trap-collected ground beetles at the continental scale', *Ecology and Evolution*, 10(23), pp. 13143–13153. https://doi.org/10.1002/ece3.6905.

Blair, J.D. *et al.* (2022) 'Embracing imperfection: Machine-assisted invertebrate classification in real-world datasets', *Ecological Informatics*, 72, p. 101896. https://doi.org/10.1016/j.ecoinf.2022.101896.

Blair, J.D. *et al.* (2024) 'A gentle introduction to computer vision-based specimen classification in ecological datasets', *Journal of Animal Ecology*, pp. 1365-2656.14042. https://doi.org/10.1111/1365-2656.14042.

Boulahia, S.Y. *et al.* (2021) 'Early, intermediate and late fusion strategies for robust deep learning-based multimodal action recognition', *Machine Vision and Applications*, 32(6), p. 121. https://doi.org/10.1007/s00138-021-01249-8.

Chiu, C. (2023) 'Sample coverage estimation, rarefaction, and extrapolation based on sample-based abundance data', *Ecology*, 104(8), p. e4099. https://doi.org/10.1002/ecy.4099.

Emmons, S.C. *et al.* (2023) 'DNA metabarcoding captures different macroinvertebrate
biodiversity than morphological identification approaches across a continental scale',
Environmental DNA, p. edn3.453. https://doi.org/10.1002/edn3.453.

Friedland, G. (2024) *Information-Driven Machine Learning: Data Science as an Engineering*
Discipline. 1st ed. Cham: Springer International Publishing AG.

Gong, Z. *et al.* (2024) 'CLIBD: Bridging Vision and Genomics for Biodiversity Monitoring at
Scale'. arXiv. https://doi.org/10.48550/ARXIV.2405.17537.

Gueuning, M. *et al.* (2019) 'Evaluating next-generation sequencing (NGS) methods for routine
monitoring of wild bees: Metabarcoding, mitogenomics or NGS barcoding', *Molecular Ecology*
Resources, 19(4), pp. 847–862. https://doi.org/10.1111/1755-0998.13013.

Guillera-Arroita, G. *et al.* (2017) 'Dealing with false-positive and false-negative errors about
species occurrence at multiple levels', *Methods in Ecology and Evolution*. Edited by R. McCrea,
8(9), pp. 1081–1091. https://doi.org/10.1111/2041-210X.12743.

Hajibabaei, M. *et al.* (2019) 'COI metabarcoding primer choice affects richness and recovery of
indicator taxa in freshwater systems', *PLOS ONE*. Edited by A. Ramaiah, 14(9), p. e0220953.
https://doi.org/10.1371/journal.pone.0220953.

He, K. *et al.* (2016) 'Deep residual learning for image recognition', in *Proceedings of the IEEE*
Computer Society Conference on Computer Vision and Pattern Recognition.
https://doi.org/10.1109/CVPR.2016.90.

Høye, T.T. *et al.* (2021) 'Deep learning and computer vision will transform entomology',
Proceedings of the National Academy of Sciences of the United States of America, 118(2).
https://doi.org/10.1073/PNAS.2002545117.

Kaspari, M. *et al.* (2022) 'Activity density at a continental scale: What drives invertebrate
biomass moving across the soil surface?', *Ecology*, 103(1), p. e03542.
https://doi.org/10.1002/ecy.3542.

Lamb, P.D. *et al.* (2019) 'How quantitative is metabarcoding: A meta-analytical approach',
Molecular Ecology, 28(2), pp. 420–430. https://doi.org/10.1111/mec.14920.

Leary, P. *et al.* (2023) 'inatVisionAPI'. https://github.com/inaturalist/inatVisionAPI (Accessed:
26 September 2023).

Liu, M. *et al.* (2020) 'A practical guide to DNA metabarcoding for entomological ecologists',
Ecological Entomology, 45(3), pp. 373–385. https://doi.org/10.1111/een.12831.

Marquina, D. *et al.* (2019) 'Establishing arthropod community composition using
metabarcoding: Surprising inconsistencies between soil samples and preservative ethanol and
homogenate from Malaise trap catches', *Molecular Ecology Resources*, 19(6), pp. 1516–1530.
https://doi.org/10.1111/1755-0998.13071.

Ramachandram, D. and Taylor, G.W. (2017) 'Deep Multimodal Learning: A Survey on Recent
Advances and Trends', *IEEE Signal Processing Magazine*, 34(6), pp. 96–108.
https://doi.org/10.1109/MSP.2017.2738401.

Ratnasingham, S. and Hebert, P.D.N. (2007) 'BOLD : The Barcode of Life Data System
(http://www.barcodinglife.org)', *Molecular Ecology Notes*, 7(3), pp. 355–364.
https://doi.org/10.1111/j.1471-8286.2007.01678.x.

Remmel, N. *et al.* (2024) 'DNA metabarcoding and morphological identification reveal similar
richness, taxonomic composition and body size patterns among flying insect communities',
Insect Conservation and Diversity, 17(3), pp. 449–463. https://doi.org/10.1111/icad.12710.

Rennstam Rubbmark, O. *et al.* (2018) 'A broadly applicable COI primer pair and an efficient
single-tube amplicon library preparation protocol for metabarcoding', *Ecology and Evolution*,
8(24), pp. 12335–12350. https://doi.org/10.1002/ece3.4520.

Saerens, M., Latinne, P. and Decaestecker, C. (2002) 'Adjusting the Outputs of a Classifier to
New a *Priori* Probabilities: A Simple Procedure', *Neural Computation*, 14(1), pp. 21–41.
https://doi.org/10.1162/089976602753284446.

Salis, R. *et al.* (2024) 'Performance of DNA metabarcoding, standard barcoding and
morphological approaches in the identification of insect biodiversity', *Molecular Ecology*
Resources, 24(8), p. e14018. https://doi.org/10.1111/1755-0998.14018.

Sayers, E.W. *et al.* (2024) 'GenBank 2024 Update', *Nucleic Acids Research*, 52(D1), pp. D134–
D137. https://doi.org/10.1093/nar/gkad903.

Schneider, S. *et al.* (2022) 'Bulk arthropod abundance, biomass and diversity estimation using
deep learning for computer vision', *Methods in Ecology and Evolution*, 13(2), pp. 346–357.
https://doi.org/10.1111/2041-210X.13769.

Stewart, K.A. and Taylor, S.A. (2020) 'Leveraging eDNA to expand the study of hybrid zones',
Molecular Ecology, 29(15), pp. 2768–2776. https://doi.org/10.1111/mec.15514.

Stork, N.E. (2018) 'How Many Species of Insects and Other Terrestrial Arthropods Are There on
Earth?', *Annual Review of Entomology*, 63(1), pp. 31–45. https://doi.org/10.1146/annurev-ento-
020117-043348.

Sys, S. *et al.* (2022) 'COLLEMBOLAI , a macrophotography and computer vision workflow to
digitize and characterize samples of soil invertebrate communities preserved in fluid', *Methods*
in Ecology and Evolution, 13(12), pp. 2729–2742. https://doi.org/10.1111/2041-210X.14001.

Taberlet, P. *et al.* (2012) 'Towards next-generation biodiversity assessment using DNA
metabarcoding', *Molecular Ecology*, 21(8), pp. 2045–2050. https://doi.org/10.1111/j.1365-
294X.2012.05470.x.

Taberlet, P. *et al.* (2018) *Environmental DNA: for biodiversity research and monitoring*. First
edition. Oxford, United Kingdom: Oxford University Press.

Terlizzi, A. *et al.* (2009) 'Beta diversity and taxonomic sufficiency: Do higher-level taxa reflect
heterogeneity in species composition?', *Diversity and Distributions*, 15(3), pp. 450–458.
https://doi.org/10.1111/j.1472-4642.2008.00551.x.

Terry, J.C.D., Roy, H.E. and August, T.A. (2020) 'Thinking like a naturalist: Enhancing
computer vision of citizen science images by harnessing contextual data', *Methods in Ecology*
and Evolution, 11(2), pp. 303–315. https://doi.org/10.1111/2041-210X.13335.

U.S. Geological Survey (2013) 'Integrated Taxonomic Information System (ITIS)'.
https://doi.org/10.5066/F7KH0KBK.

Weiser, M.D. *et al.* (2021) *Batch extraction of morphological and color metrics from*
invertebrate samples, *protocols.io*. https://doi.org/dx.doi.org/10.17504/protocols.io.byt4pwqw.

Weiser, M.D. *et al.* (2022) 'Robust metagenomic evidence that local assemblage richness
increases with latitude in ground-active invertebrates of North America', *Oikos*, 2022(8), p.
e08791. https://doi.org/10.1111/oik.08791.