Spatiotemporal dynamics and substates underlie emotional signalling in facial movements

Hélio Clemente José Cuve[1][*], Sophie Sowden-Carvalho[2], Jennifer Cook[2]

[1]School of Psychology and Neuroscience, University of Bristol, Bristol, United Kingdom

[2]School of Psychology, Centre for Human Brain Health, University of Birmingham, Birmingham, United Kingdom

[*] Corresponding author

e-mail: helio.cuve@bristol.ac.uk

School of Psychology and Neuroscience

University of Bristol

12a, Priory Road

Bristol BS8 1TU

United Kingdom

Abstract

From overt emotional displays to a subtle eyebrow raise during speech, facial expressions are key cues for social interaction. How these inherently dynamic facial signals encode emotion across non-verbal expression and speech remains only partially understood. In Study 1 we recorded participants' facial movements signalling happy, sad and angry emotions in *Expression-only* and *Emotive-speech* conditions. We employed a data-driven pipeline integrating facial motion quantification, spatiotemporal classification and clustering to investigate the structure and function of facial dynamics in signalling emotion. Results reveal that a few spatiotemporal patterns reliably differentiated emotion in non-verbal expressions and emotive speech facial signals. Furthermore, we identified transient substates – or dynamic phases – that are diagnostic of emotion intent and conditions. A perceptual validation with naïve observers (Study 2) showed that the low-dimensional spatiotemporal structure captures meaningful cues that closely predict human emotion categorisations. We discuss theoretical implications of a low-dimensional spatiotemporal structure for optimal transmission and perception of dynamic facial emotion signals and face-to-face interaction. This work also provides a framework for modelling dynamic social cues and insights for the design of expressive emotive capabilities in social agents.

Keywords: Facial expressions, movement, spatiotemporal, dimensionality reduction, emotion, signalling.

Introduction

The human face is an incredibly versatile signalling tool for social interaction [1]
capable of producing a rich array of non-verbal signals through the coordination of
basic motor facial action units (AUs) [2]. For example, frowning (AU4) combined with
pursed lips (AU24) can convey a prototypical facial expression of anger, while raised
cheeks (AU6) and pulling back the lip corners (AU12) can signal a smile. In addition
to ostensive non-verbal emotional cues, in real-life social interaction, facial
expressions simultaneously modulate verbal communication. A slight tightening of
the eyelids (AU7) for example, can make a "neutral" verbal utterance appear slightly
angrier. However, while much of the contemporary theoretical debate continues to
focus on how specific AUs signal emotion (see [3–5] for a review), the mechanisms that
afford such flexible expressive capabilities to facial signals remain only partly
understood.

One overlooked aspect in previous research is the dynamic features of facial
expression signalling, with a large focus instead on the static aspects of facial
behaviour or approaches that ignore temporal dynamics [6]. Moreover, although most
face-to-face interactions naturally involve speech, the role of speech-related facial
dynamics in emotion signalling has been largely neglected. Yet these dynamic cues
in conversational or speech-related facial expressions can enhance the
simultaneously transmission of visual signals for emotion and verbal communication
[6–9]. Nonetheless, there is growing research providing important insights on the role of
facial expression dynamics to emotion signalling. Psychophysics inspired
approaches have combined generative synthesis of facial movements [10] and
reverse correlation to parametrically map the spatiotemporal features of AUs to

perceptual representations of emotion categories[11], valence-arousal dimensions [12]

and even social traits[13]. Similarly, a recent production and perception study recorded

participants' facial movement signals of anger, happiness, and sadness, during

expression only production and during spoken sentences conveying the same

emotions [14]. Kinematic analysis revealed faster movements for high-arousal

emotions (happiness, anger) compared to slower movements for low-arousal

emotions (sadness). Thus, suggesting that dynamic features of facial signals carry

fundamental diagnostic spatiotemporal information for differentiating emotional

expressions at both the production and perception stages.

Nevertheless, an account of the spatiotemporal structure of facial signals – how AUs

dynamically combine and unfold to signal emotions and simultaneously convey

speech-related information – remains lacking (see [1,15]). One significant challenge to

studying the role of spatiotemporal structure in facial expression signalling is the lack

of an integrated theoretical and methodological framework. Such a framework should

ideally integrate the dynamic nature of facial expression signals with their socio-

communicative functions and provide an appropriate modelling strategy – see [1,10]. In

this work, we build on the observation that facial expressions are controlled by an

underlying motor system [16,17]. Specifically, we explore the application of theoretical

and analytical principles drawn from the motor control literature to understand the

spatiotemporal structure and function of dynamics in facial expressions for signalling

emotion.

A motor control perspective provides two useful theoretical insights that may be

applicable to studying the spatiotemporal structure and function of facial expression

dynamics. First, a longstanding motor control idea suggests that body movements

are generated by a low-dimensional mechanism that underpins their effective neural

control and physical execution [18–20]. Such low-dimensionality of motor control and

execution might reflect the brain's solution to the problem of controlling numerous

muscles and components of the motor system whilst minimising computational

demands - often referred to as the "degrees of freedom" problem [21–23]. Such low

dimensionality has been shown to describe motion patterns during walking [24], whole

body pointing [25], eye movements [26] and articulatory speech movements [27]. Crucially,

these movements also convey emotion-related information [28–30] providing theoretical

basis and experimental evidence for the potential of shared control principles for

social and non-social aspects of movement. Similarly, dynamics underlying facial

expressions, and their ability to multiplex information (e.g., visually signal emotion

and speech), may be structured around low-dimensional spatiotemporal patterns.

Such structure could be optimal for flexible and precise spatiotemporal control of

Action Units (AUs) and to signal emotion adaptively in social interactions[31].

Additionally, given that social interaction often involve continuous verbal exchanges

which impose articulatory demands to facial movements, a low-dimensional

spatiotemporal mechanism may also support the simultaneous layering of emotion

cues in speech-related facial dynamics[32]. This perspective also suggests a

methodological framework to model spatiotemporal nature of movement, which is

rare in the study of facial expression production. For instance, spatiotemporal

dimensions can be explored using data-driven models that learn the underlying

latent patterns of dynamic facial behaviour [33].

A second insight from the motor-control literature stems from the empirical

observation that although outwardly fluid, body movements can often be segmented

into distinct 'substates' often seen in differential modulation of kinematics (e.g.,

speed, displacement of motor actions). For instance, walking movements can be

segmented into 'swing' or 'stance' phases [24] or eye movements into 'fixations' and

'saccades' [34], and even more fine-grained states (sub movements) have been

described [35]. As a class of motor actions, facial expressions are likely to exhibit

analogous substates shaped by the biomechanics of how they are produced and

controlled, encompassing 'transitions' where AUs are initiated or inhibited, and

'stability' where AUs are sustained [31]. Indeed, previous descriptions of facial motion

and AU dynamics have noted such temporal segmentation during expressions [36,37]

and emotive speech [32]. However, substates of facial expressions and emotive

speech-driven dynamics have not yet been formally characterised, and whether and

how they relate to emotional signalling is unknown. Similar to spatiotemporal

components, substates can be explored in a data-driven fashion, using methods

such as spatiotemporal clustering [33,38,39] which is particularly suitable given that lack

of *apriori* defined profiles for facial expression dynamics.

Probing the underlying spatiotemporal structure and substates in facial expressions

would enable a richer characterisation of facial dynamics that is both holistic, i.e.,

captures overall spatiotemporal patterns, but also focal as it can capture micro

spatiotemporal patterns. We hypothesise that these underlying patterns are not

merely incidental; rather, they are diagnostic of emotional content, reflecting how

facial movements are optimised for social signalling. In this context, diagnostic

means that the spatiotemporal features provide reliable cues for inference of the

emotion being expressed from both a production and a perceptual perspective.

While some prior work has proposed similar motor-centric approaches to model

facial expression signalling, these have largely focused on perception e.g. [11,40] rather

than production. Notwithstanding, a few recent studies have employed

spatiotemporal dimensionality reduction approaches to identify dynamic motifs in

facial expression production data (e.g. [22,41,42]). Nonetheless, the reliance on only a

single to a handful signallers or actors limits the dynamic range and variability the

facial signals analysed in prior work. Hence, it's unclear whether the observed

dimensionality in these studies, genuinely reflect the underlying mechanisms for

facial expression signalling or simply results from restricted variability in signal

dynamics. It is also unclear how well these findings generalise to other emotional

expressions and conditions (e.g., emotive speech facial dynamics). Furthermore,

previous work also relied on averaging across the spatiotemporal dimensions when

comparing expressions and conditions, which re-introduces the problem of

overlooking how features of facial dynamics relate to emotion signalling (see

Methods). Consequently, the functional role of facial dynamics (both low-dimensional

spatiotemporal patterns and substates) remains only partially explored.

The current study therefore aimed to (1) describe the spatiotemporal structure

underlying facial expression production; (2) explore and characterise putative facial

expression substates, and 3) evaluate the diagnostic value of spatiotemporal

structure and substates for emotion signalling. To capture wider facial dynamics

relevant for social interaction, in study 1 we recorded 43 participants facial

movements while they signalled happy, sad and angry emotions in a) *Expression*

only and b) *Emotive speech* conditions across two separate sessions, building on

validated facial expression production paradigms [14,32,43]. We used automated Facial

Action Coding System (FACS) analysis to describe the spatiotemporal patterns of

the facial AUs (e.g., mouth widening, eyebrow raise, etc). We then employed a novel

data-driven pipeline combining dimensionality reduction, dynamic feature extraction,

and spatiotemporal classification and clustering; to identify diagnostic latent

spatiotemporal patterns (groups of co-activated AUs and salient temporal patterns)

underlying optimal emotion signalling through facial dynamics - see Methods.

To precis our results, we find that *Expression only* and *Emotive speech* facial

dynamics can be distilled into a of small set of "fundamental" spatiotemporal

components. The three emotions (happy, angry, sad) and two conditions

(*Expression only* and *Emotive speech*) studied are differentiated by synergistic

mixing of components and subtle local substate differences related to expression

transitions. In Study 2, an independent perceptual validation with naïve observers

showed that the low-dimensional spatiotemporal structure is strongly predictive of

human emotion categorisations.

Our key contributions are two-fold. First, we provide new insights into the complex

and flexible signalling of emotion through facial movements, suggesting that it is

achieved through variations in a small number of functional and perceptually relevant

spatiotemporal patterns and substates. Second, we provide a versatile data-driven

pipeline to model the structure and function of facial dynamics in emotion signalling,

which can be extended to other dynamic social signalling modalities.

Results

<u>Facial expression production, perceptual validation check.</u> A perceptual validation of

the facial expression production task recordings was conducted with 45 naïve

participants in a separate study. Results show that the perceptual ratings of emotion

are reliably aligned with the predicted facial expression signals from the facial

production task. Variability in perceptual ratings indicate that the facial expression

recordings contain sufficient diversity, with no evidence of ceiling or floor effects. Full

details and figures for this validation are provided in the SI - "Perceptual Validation

Study" and Fig. S1).

Spatiotemporal components for facial expression production.

We report results for *Expression only* and *Emotive speech* expressions separately

for clarity, however we note that these patterns were consistent when analysed

together (see SI - Comparison of joint vs separate spatiotemporal analysis of

Expression only and *Emotive speech*, and Fig. S8-9).

<u>Spatiotemporal patterns during facial *Expression only* condition</u>

We first looked at the spatiotemporal components identified via a Non-Negative

Matrix Factorization (NMF) analysis, which represents the underlying (reduced)

diagnostic spatiotemporal patterns (e.g., groups of AUs with common activation

timecourses and salient temporal patterns). The optimal number of spatiotemporal

components (k) optimising for various fit indices (see Methods) – was consistently

three (see Fig 1 – top panel) (see also *Expression only* condition - NMF validation

analysis in Supplementary Information(SI) – Fig S2-4).

Figure 1. Spatiotemporal components for facial dynamics in *Expressions only production.*

The top panel (a) shows that expression production can be summarised by three components, capturing key spatiotemporal patterns for upper face AUs (component 1), lower face AUs (component 2) and a combination of both lower and upper face AUS (component 3). Top - middle and right columns show approximate spatial distribution of components in an average face model and how it changes over time, respectively. The bottom panel (b) highlight spatiotemporal profiles (averaged) for angry, happy and sad expressions. Coef = Coefficient, brighter colours indicate stronger activation. Note that face maps are drawn for visualisation purposes only to provide a rough visual representation of the AU-component profiles. Faces maps are derived from an approximate pls regression predicting aligned and normalised facial landmark changes from AUs based on facial production data (see methods).

Evaluation of the spatiotemporal patterns revealed that component 1 (C1) had

stronger activation of the upper face-related AUs (e.g., AU4 brow lowerer, AU7 lid

tightener) compared to other AUs. Component 2 (C2) had strong activation of both

lower and upper face-related AUs (e.g., AU25 lips part, AU14 dimpler). Component 3

(C3) was mostly dominated by lower face actions (e.g., AU17 chin raiser) with some

small activation of upper face AUs (e.g. AU45 blink). For clarity of presentation, we

name these components, upper face AUs (C1), lower face AUs (C2) and lower-to-

upper face AUs (C3). The averaged temporal profile of these components across

videos is shown in Fig 1 B. C1 (upper face AUs) and C2 (lower face AUS) had a

common inverted-U shape with a clear singular peak, whereas C3 (lower to upper

face AUs) had a less pronounced but more dynamic pattern (e.g. bimodal peaks).

Next, we formally assessed the diagnostic value of the spatiotemporal components,

by analysing how features capturing dynamics differed between expressions and

validated it in a held-out test set (see Methods - *Multivariate Timeseries*

Classification). When assessing spatiotemporal components' ability to classify

expressions we achieved significantly above chance accuracy (ACC (accuracy)=

0.91 [Bal.Acc. (balanced accuracy) = .93], Cohens Kappa (classification reliability) =

0.87; AUC(Area Under the Curve) mean = 0.98, $p < .001$; note chance is .33 for a 3-

way classification). These results indicate strong agreement between prediction from

spatiotemporal model and ground-truth (from facial expression production task) –

see Fig 2 below.

Figure 2. Spatiotemporal classification of facial expressions only production.
Notes: The left panels show decision boundaries (filled backgrounds) across
spatiotemporal components (comp1: upper AUs, comp2: lower face AUs; comp3:
lower to upper face AUs) estimated on a training set to predict emotion classes
(angry, happy, sad). Coloured dots represent individual ground-truth expressions
from both training and held-out test data. Dots within a matching background indicate
correct classifications, while mismatches indicate misclassifications. The results
demonstrate robust classification, with at least a pair of component combinations
separating a target expression from the rest, e.g. comp1 vs 2 and comp-2 vs 3
robustly distinguishes happy expressions. The top right panel presents Receiver
Observer Characteristic (ROC) curves, showing good model performance (higher
True Positive Rate [TPR] and lower False Positive Rate [FPR]) with the diagonal
dashed line representing chance). The bottom right panel displays a confusion
matrix. Brighter colours indicate higher accuracy along the diagonal elements, with
off-diagonal showing little to no confusions (darker colours).

We also found distinct temporal profiles for each emotion. Angry expressions

(Bal.Acc. = .91, AUC=.97, p < .001) were characterised by strong temporal

coactivation of C1 (upper face AUS) and C2 (lower face AUS). Happy expressions

(Bal.Acc. = .98, AUC = .99, p < .001) were dominated by C2 (lower face AUs); and

sad (Bal.Acc. = .98, AUC = .90, p < .001) characterised by moderate changes in all

three components. To further validate our model, we conducted a Fisher's exact test

on the confusion matrix (see Methods), which confirmed significant pairwise

differentiation of all expressions on the basis of their spatiotemporal patterns (angry

vs happy; angry vs sad; and happy vs sad: p.corrected < .001). These results

reinforce the robustness of our classification model, demonstrating that

spatiotemporal patterns capture reliable differences between emotional expressions.

For detailed sensitivity analysis and metrics see SI Fig S2-S4 and Table S1-2.

<u>Spatiotemporal patterns for *Emotive speech* facial expressions</u>

Similar to the *Expression only* condition, we found that three components effectively

represented the spatiotemporal patterns of facial AUs signalling emotion in *Emotive*

speech (see Fig 3). However, there were some notable differences in the spatial and

temporal patterns, which likely reflect the fact that, in contrast with the *Expression*

only videos, the *Emotive speech* videos comprise a combination of facial expression

and speech AUs. Specifically, the *Emotive speech* components comprised a mix of

both lower and upper face AUs, in comparison to mostly lower vs upper face AUs for

Expression only conditions

Figure 3. Spatiotemporal components for *Emotive speech* facial expression production. The top panel (A) shows that *Emotive speech* facial expression production can be summarised by three underlying components, capturing synergies between upper to lower face AUs (Component 1), lower-mid-upper AUs (component 2) and lower to upper face AUs (component 3). Top - middle and right columns show approximate spatial distribution of components in an average face model and how it changes over time, respectively. Note patterns are averaged across videos for visualisation. The bottom panels (B) show how components change over time, highlighting different profiles for angry, happy and sad expressions. Coef = coefficient from the NMF, brighter colours indicate stronger activation. Note while matrix heatmaps are a true representation of the model, face maps are not a one-to-one map and are drawn for visualisation purposes only. Face maps only provide a rough visual representation, derived from an approximate pls regression predicting aligned and normalised facial landmarks change from AU data based on facial production data (see methods).

Component 1 included strong activation of upper and lower face AUs (e.g., AU4 -

brow lowerer; AU17 - chin raiser) peaking at both early and late time points.

Component 2 (lower-mid-upper face AUs) combined strong activation of AUs in the

lower (e.g., AU25 - lips part), middle (e.g., AU14 - dimpler) and upper face areas

(e.g., AU7 - lid tightener). Component 3 primarily featured activation of lower face

AUs, such as AU25 (lips part) and AU26 (jaw drop), plus additional moderate

activation for AU45 (blink). Henceforth component 3 is referred to as lower to upper

face AUs (see Fig 3). C2 (lower-mid-upper face AUS) and C3 (lower to upper face

AUs) had an inverted-U shape with C3 peaking earlier than C2 (Fig 3C).

As with facial *Expression only* production, *Emotive speech* expressions were also

characterised by distinct spatiotemporal patterns. That is, a classifier trained on

timeseries features of the spatiotemporal components (e.g., curvature, complexity)

achieved significant accuracy in classifying expressions on a held-out test set, with

performance at 70% (ACC = 0.69; Bal.Acc. = .76, Kappa = 0.53, $p < 0.001$). These

results indicate moderate to strong agreement between prediction and ground-truth

emotional expression labels (see Fig 4).

Class-wise, the spatiotemporal components significantly distinguished all

expressions. Happy had the highest accuracy (Bal.Acc. = 0.91, AUC = 0.97, $p <$

.001), suggesting a clear and distinct spatiotemporal profile, notable in the increased

activation in C2 (lower-mid-upper face AUs) over time. For detailed validation and

statistics see SI Fig S5-S7 and Table S3-4

Figure 4. Spatiotemporal classification of *Emotive speech* facial expressions.
The left panels show decision boundaries (filled backgrounds) across spatiotemporal
components (comp1: upper to lower face AUs, comp2: lower to upper face AUs;
comp3: upper-to-lower face AUs) estimated on a training set to predict emotion
classes (angry, happy, sad). Coloured dots represent individual ground-truth
expressions from both training and unseen test data. Dots within a matching
background indicate correct classifications, while mismatches indicate
misclassifications. The results demonstrate robust classification, with component
combinations effectively separating the expressions in at least one combination.
The top right panel presents ROC curves, showing good model performance (higher
True Positive Rate [TPR] and lower False Positive Rate [FPR]), with the diagonal
dashed line representing chance. The bottom right panel displays a confusion matrix.
Brighter colours indicate higher accuracy along the diagonal elements, and
confusion off-diagonal (e.g., happy shows high accuracy and low confusion, whereas
angry shows higher confusion than all expressions).

Angry had the lowest classification accuracy compared to all other expressions, yet

still significantly above chance (Bal.Acc. = 0.67, AUC = 0.83, p = .01), reflecting a

more complex and less distinct pattern across all components. Similar to happy, sad

expressions were classified reliably above chance (Bal.Acc. = 0.72, AUC = 0.84, p =

0.001). Fisher's exact test on the confusion matrix confirmed significant pairwise

differentiation between happy and sad expressions (p < .001) and between angry

and happy (p < .001). However, it suggested confusions between and angry and sad

(p = 0.12) (see Fig 4; SI1 - Table S3-4).

In summary, we found three latent spatiotemporal components that reliably

described the dynamics of facial expressions during *Expression only* and *Emotive*

speech conditions. Robust train-test classification on unseen held-out data, indicates

that spatiotemporal components carry fundamental diagnostic emotional cues with

good generalisability.

Perceptual validation of the spatiotemporal components for emotion signalling

We also conducted an independent perceptual validation with 45 naïve observers

who judged point-light (PLFD) animations isolating facial motion of the produced

stimuli, following a validated protocol from our previous work [14] (See methods and

SI). Results showed that the low-dimensional spatiotemporal structure is strongly

predictive of human emotion categorisations in the holdout test-set. Specifically, we

found (a) strong correspondence between our model's spatiotemporal classification

predictions and human observers' categorisations (*Expression only,* X^2 = 33.125, p <

.001, *Emotive Speech*, X^2 = 15.622, p = .002) and (b) high predictive accuracy of

human observers' emotion categorisation based solely on these spatiotemporal

components (Accuracy consistently above 60% across stimuli and participants, and

conditions; all p <. 001). For full details and statistics see SI: Perceptual validation of

the spatiotemporal components for emotion signalling; and Fig 5).

Figure 5. A. Mean standardised ratings for *angry* (green), *happy* (orange), and *sad* (purple) expression in the *Expression only* (left) and *Emotive speech* (right) conditions. The horizontal axis reflects the expression predicted by the spatiotemporal model. Each point indicates a single video's average rating across participants. Data shows that the model predictions differentiate emotion ratings, despite some variability.
B. Leave-one-participant-out cross-validation accuracy for the *Expression only* (left) and *Emotive speech* (right) conditions. Each bar shows the accuracy when a single participant's data are held out of training. The red dashed line indicates the empirical chance level (i.e. majority class prediction), while the pink dotted line represents the theoretical chance level for a three-way classification.

Substates reveal emotion diagnostic transitory patterns in facial signals

The second objective of this study was to identify and characterise facial expression substates. While these are likely driven by articulatory and biomechanical nature of activating AUs, we aimed to explore whether they are additionally modulated by emotional intent (i.e., they may differ between happy, angry and sad expressions and conditions). We identified three primary substates through spatiotemporal clustering that segmented periods with robust local dynamics within the underlying spatiotemporal components (see Methods: *Spatiotemporal clustering for substates*

401 *analyses*). Visual representation of the kinematic profiles of each substate (Fig 6A-B)

402 suggest the substates correspond to relaxed, transition, and sustain periods for

403 spatiotemporal components. The overall pattern of substates is also consistent

404 across participants, suggesting that this is not an artifact of methodology or driven by

405 specific inputs (see Fig 6 C-D).

407
Figure 6. Illustration of facial expression substate profiles.
A-B. Example of substate clusters (1 (green) = relaxed, 2 (peach) = transition; 3
(purple) = sustain). C-D show overall the speed distribution for *Expression only* and
Emotive speech expressions for all subjects.

Because the clustering algorithm returns only cluster partitions, it does not inherently

explain why these clusters emerge or how they may differentiate emotion (anger,

sadness and happy) and conditions (*Expression only vs Emotive speech*). To

address this, we quantified cluster (substate) patterns using two metrics, which were

selected following exploratory visual inspection of the substate profiles (see Fig. 6):

(1) speed as the input to the clustering analysis, provides a kinematic

characterisation of each substate; (2) entropy, which provides a view of overall

dynamics of substates (e.g., how they change over time) (see Fig 6 and Methods).

Similar measures have also been shown to capture diagnostic information in facial

expression movement and AU actuation [11,14]. As this analysis is intended to

characterise substates clusters rather than classification per se, we used a linear

mixed-effects model - LMM (see Methods) to statistically explore differences in these

metrics between emotion and conditions. Our overarching hypothesis, outlined in the

Introduction, was that substates would differentiate emotional signals in line with the

idea that local facial dynamics optimise the motor encoding of emotion cues.

However, no specific directional effects were predicted a priori, as the substates

were derived in a data-driven manner, and as such the results should be interpreted

as exploratory, aimed at characterising the substate–emotion patterns.

<u>Transition substate speeds differentiate emotional expressions</u>

An LMM used to predict speed from emotion (happy, angry, sad), condition

(*Expression only, Emotive speech*), and substate (relaxed, transition, sustain)

showed strong total explanatory power (conditional R2 = 0.6 (66%)) with the fixed

effects alone (marginal R2) accounting for 0.63 (63%) of the variance. All main

effects were significant. First, there was a small significant effect of emotion

(F(2,1990) = 12.89, p < .001). Pairwise tests showed that angry expressions were

significantly slower than happy expressions (angry < happy; beta = -0.028, SE =

0.008, t(1207) = -3.398, p.corrected = 0.002). Happy expressions were faster than

sad expressions (happy > sad; beta = 0.041, SE = 0.008, t(1207) = 4.92, p.corrected

< 0.001). There were no significant differences in speed between angry and sad

expressions (beta = 0.012, SE = 0.008, t(1207) = 1.53, p.corrected = 0.38). There

was a significant main effect of condition (F(1, 1190) = 369.41, p < .001) with

Expression only condition moving faster than spoken (beta = 0.13, SE = 0.007,

t(1207) = 19.08, p < .001). Finally, there was a main effect of substate (F(2, 1190) =

687.90, p < .001) where sustain had higher speed than relaxed (beta = -0.16, SE =

0.008, t(1207) = -19.52, p.corrected < .001); transition had higher speed than relaxed

(beta = -0.307, SE = 0.008, t(1207) = -36.80, p.corrected < .001) and transition had

higher speed than sustain (beta = -0.144, SE = 0.008, t(1207) = -17.28, p.corrected

< .001). In summary, facial movement speed varied by emotion, condition, and

substate, with happy expressions, the Expression only condition and transition

phases being the most dynamic overall.

All two-way interactions were significant. First, there was a significant interaction

between emotion and substate (F(4, 1190) = 15.24, p < .001). Pairwise tests showed

that differences in speed between happy, angry and sad emotional expressions were

statistically significant for the transition substate only (happy>anger, beta = -0.077

SE = 0.014, t(1207) = -5.36, p.corrected < .001; sad< angry, beta = 0.053, SE =

0.014, t(1207) = 3.64, p.corrected < 0.001; sad< happy, beta = 0.130, SE = 0.014,

t(1207) = 9.005, p.corrected < .001). There were no speed differences between

emotions for the relaxed substate (angry vs. happy, beta = -0.005, SE = 0.014,

t(1207) = -0.348, p.corrected = 1.0; angry vs. sad, beta = 0.007, SE = 0.014, t(1207)

= 0.498, p.corrected = 1.0; happy vs. sad, beta = 0.012, SE = 0.014, t(1207) = 0.846,

p.corrected = 1.0) nor the sustain substate (angry vs. happy, beta = -0.003, SE =

0.014, t(1207) = -0.177, p.corrected = 1.0; angry vs. sad, beta = -0.022, SE = 0.014,

t(1207) = -1.501, p = 0.40, p.corrected; happy vs. sad, beta = -0.01913, SE = 0.0144,

t(1207) = -1.325, p.corrected = 0.5567). These results suggest that transition

substate (but not relaxation or sustainment) carry diagnostic information about the

emotional content of facial expressions (Fig 7).

473
Figure 7: Summary of speed and entropy of substate patterns.
Substate cluster: 1-relaxed, 2-sustained, 3-transition. *Expression only* condition has
faster than *Emotive speech*, with transition substates being faster; Entropy mainly
differentiates *Expression only* and vs. *Emotive speech* condition, with the latter
exhibiting more complex patterns. Entropy also differed between happy and all other
expressions, with substate patterns being more predictable for former.
480

Finally, there was a significant two-way interaction between condition and substate

(F(2) = 183.65, p < .001). For the *Expression only* condition, there were significant

differences in speed between all substates such that sustain was faster than relaxed

(relaxed < sustain, beta = -0.153, SE = 0.012, t(1207) = -12.96, p.corrected < .001);

transition was faster than relaxed (relaxed < transition, beta = -0.439, SE = 0.012,

t(1207) = -37.23, p.corrected < .001), and faster than sustain (beta = -0.286, SE =

0.0118, t(1207) = -24.271, p.corrected < .001). These patterns were overall similar

for the *Emotive speech* condition where relaxed periods were significantly slower

than sustain (beta = -0.173, SE = 0.0118, t(1207) = -14.647, p.corrected < .001) and

transition periods (beta = -0.175, SE = 0.012, t(1207) = -14.82, p < .001). However,

there was no statistically significant difference between sustain and transition speeds

(beta = -0.002, SE = 0.012, t(1207) = -0.169, p.corrected = 1.00). In summary,

substate differences were more apparent in the *Expression only* condition than in

Emotive speech, reflecting stronger optimisation of facial dynamics for expressive

signalling when speech demands are absent.

In sum, substate clusters are associated with differences in speed suggesting

periods of transition, relaxation and sustainment of expressions. Interestingly, these

micro-dynamic patterns differ between expressions and between *Expression only*

and *Emotive speech* signals, suggesting that facial production phases may enhance

the signalling of the emotional intent during speech.

<u>Substate dynamics differentiate emotion content</u>

Here we used entropy as to statistically describe the dynamics of facial expression

substates in terms of how temporally structured/predictable they are ([44]. see

Methods). High entropy equates with high complexity in substate patterns, and low

entropy with low complexity. Fig 6, for example, illustrates that substate transitions

are more complex (i.e., high entropy, less predictable) in the *Emotive speech*

condition where visual pattern differences between emotions are harder to discern

than in the *Expression only* condition (see Methods: *Spatiotemporal clustering for*

substates analyses). Note entropy was log transformed to correct for non-normal residuals.

The entropy model explained 67% of the variance ($R^2 = 0.67$). The fixed effects alone (emotion, and expression condition) accounted for 57% of the variance (marginal $R^2 = 0.57$). The main effect of emotion was statistically significant ($F_{(2, 340)} = 12.27$, $p < 0.001$). Pairwise contrasts revealed that sad expressions had a significantly higher entropy (more unpredictable substate sequences) compared to happy expressions (estimate = -0.027, SE = 0.0055, $t(344) = -4.897$, $p < 0.0001$). There were no statistically significant differences in entropy between angry and happy expressions (estimate = 0.011, SE = 0.006, $t(344) = 1.996$, $p = 0.14$), but there was a significant difference between angry and sad expressions (estimate = -0.016, SE = 0.0055, $t(344) = -2.90$, $p = 0.012$) – see Fig 7.

The largest effect was the main effect of condition ($F_{(1, 34)} = 429.10$, $p < 0.001$), with the *Expression only* condition demonstrating significantly lower entropy than *Emotive speech* expressions ($\beta = -0.208$, SE = 0.017, $t(35) = -12.594$, $p < 0.001$). This suggests more complex movement dynamics in the *Emotive speech* compared to the *Expression only* condition (see heatmaps in Fig 6). There was no significant interaction between emotion and condition ($F_{(2, 340)} = 0.03$, $p = 0.970$).

In summary, *Expression only* substates (relaxation, transitions, and sustainment of expressions) are more temporally structured than those in *Emotive speech* expressions, likely reflecting the increased dynamic complexity associated with facial movements during speech. Substates patterns also differentiate expressions, with sad expressions having a more complex dynamics than happy and angry expressions.

To summarise, in addition to the low-dimensional spatiotemporal patterns that are

diagnostic of emotion and expression condition, we also identified substates

reflecting periods of relaxation, transition, and sustainment of facial actions. These

substates are distinguished by their unique kinematic and dynamic (complexity)

profiles which provide cues for differentiating emotional expressions in *Expression*

only and *Emotive speech* conditions.

Discussion

The current study investigated how the underlying dynamics of facial movements

relate to their expressive emotional signalling function. Building on a motor-theoretic

framework we employed a data-driven pipeline - integrating spatiotemporal

dimensionality reduction, timeseries feature extraction, classification and clustering;

to identify diagnostic patterns underlying emotion signalling in both *Expression only*

and *Emotive speech*. Our work contribute two key insights. First, we consistently

identified a small number of spatiotemporal components that reliably described the

time courses and covariance patterns of AUs. The identification of these components

suggests that emotion signalling through facial expressions and speech-related facial

cues can be achieved by just a few fundamental dynamic patterns; combinations of

these dynamic patterns differentiate production and perception of angry, happy and

sad expressions. Second, we showed that these spatiotemporal patterns exhibit a

substate-like structure, which reflect transient periods of relaxation, transition, and

sustainment of expressions. The profiles of these substates differed by emotion

category as well as between *Expression only* and *Emotive speech* conditions,

indicating they partly reflect the encoding of dynamic facial emotion cues.

The low dimensionality of the spatiotemporal patterns of facial expressions, that we

have uncovered, is intriguing given the various combinations of AUs that can

contribute to the same expressions [6] as well as the variability in how people produce

expressions [45]. Such low-dimensional spatiotemporal structure may reflect flexibility

for signalling, as a variety of expressions can be rapidly produced (and perceived) by

relying on just a few interchangeable dynamic patterns. Theoretically, such flexibility

is likely beneficial in face-to-face interaction, where facial expressions may need to

be quickly adapted according to interaction demands [6,46]. Similarly, this flexibility

might be necessary to accentuate emotional information during conditions which

impose dynamic constraints on facial movements, such as speech[7,46]. These

findings are consistent with the observation of low-dimensional spatiotemporal

patterns facial [22,42] as well as other body movements [21,23,25] which also have the

capacity to signal emotion information [28,47]. This suggests the potential for shared

control mechanisms for social and non-social aspects of movement including speech

related facial movements.

An important question concerns whether our results are representative of facial

expression signalling in general, or simply an outcome of the particular methodology

we employed. For example, it could be argued that we identified a small number of

spatiotemporal components because we asked participants to demonstrate relatively

simplistic expressions which can be signalled by activating just a few action units.

We argue that this is not the case because a) the *Emotive speech* condition was also

specifically designed to dissuade participants from relying on overly simple and

caricatured expressions and to introduce dynamic variability and b) compared to

previous work [22,42] we provide a substantially wider range of signallers to capture

wider idiosyncrasies and variability in facial dynamics (see SI- Fig S10). It could also

be argued that our results are simply a consequence of dimensionality reduction, as

any set of data can in theory be represented by a lower-dimensional structure. Yet,

as we showed in a series of validation and sensitivity analyses, the components

learned carry diagnostic information about emotions, which is robust to comparisons

against appropriate randomised dynamic patterns and generalises to unseen data.

Thus, we have not generated a "non-sense" low dimensional structure but rather a

meaningful way to represent diagnostic dynamic cues for emotion signalling.

An intriguing question concerns why this low-dimensional spatiotemporal structure

emerges. One possibility is that receivers only attend to a reduced subset of

spatiotemporal patterns and correspondingly, signallers tend to only accentuate a

subset of features to produce predictably diagnostic facial movements. Relevant to

this argument, our perceptual validation indicates that there is overlap between

model-based spatiotemporal emotion classification predictions, and human

categorisation (see Fig 5). Moreover, the robust prediction of participants'

categorisations directly from these components suggests that these low-dimensional

patterns are at least in part, functionally and perceptually relevant for signalling

emotion. These results are also consistent with previous psychophysical approaches

showing that when observers are presented with dozens of biologically plausible

face movements, their perceptual representations suggest that they only rely on a

reduced subset of dynamic patterns [40]. However, there have not been systematic

studies assessing the correspondence of these perceptual signals to those actually

produced by observers. Furthermore, as human infants learn to produce and

recognise facial expressions throughout a protracted period of development [48], it is

possible that humans learn to optimise signals based on how these are optimally

perceived and responded to, creating a reciprocal dynamic interaction between

these processes. Thus, the low-dimensional organisation of facial expressions may

reflect the optimisation of social signals according to perceptual demands and these

perceptual demands, themselves, may be influenced by the low-dimensional

organisation of facial expressions [49]. An additional possibility is that there are

savings (e.g., energy/computational, cognitive) to be had from producing and

interpreting facial expressions according to only a small number of key informative

spatiotemporal patterns.

The identification of substates in emotional facial dynamics also goes beyond

previous work on facial expression production. On the one hand substates likely

reflect the biomechanical features of articulating facial expressions, which inevitably

result in periods of relaxation, transition and sustainment of the underlying motor

units [50,51]. Yet, the fact that the patterns of these substates vary with different

expressive emotions and conditions even under the simultaneous production of the

same verbal utterances, suggests that these local dynamics provide a medium for

optimising the signalling of emotion.

Additionally, in real-life interaction, facial movements subserving verbal and

nonverbal expressions are often seamlessly integrated. Our findings in the *Emotive*

speech condition raise the possibility that verbal and nonverbal facial dynamics when

signalling emotion can be integrated by differential modulation of spatiotemporal

structure. For example, during speech, lip movement might covary with articulation

635 and sound production while simultaneously, the tightening of the lips and lowering

636 the eyebrows can accentuate the emotion signal. Indeed, the observation of mostly

637 part-based profiles (e.g., lower vs upper face AUs) in *Expression only* conditions,

638 contrasting the involvement of both mouth and non-mouth-related components in

639 *Emotive speech* expressions supports this assertion. Similarly, the reduced substate

640 differentiation and higher entropy observed in the substate patterns of *Emotive*

641 *speech* may reflect the increasing demands placed on facial dynamics by speech

642 articulation and emotional expression, resulting in more complex spatiotemporal

643 patterns needed to differentiate emotion. However, given that social signalling is

644 inherently multimodal - with tone of voice, vocal prosody, and facial expressions

645 capable of conveying emotion both independently and in combination - a future

646 challenge is to understand the extent to which these modalities act redundantly

647 (conveying the same information) or synergistically (combining to produce

648 qualitatively richer meaning) when signalling emotion [1,12,52].

650 There are several limitations and considerations that point towards valuable

651 directions for future work. First, including more detailed descriptors of face

652 movements (including head motion see [42]), speech-optimised facial dynamics and

653 the use of more naturalistic signalling paradigms, may require additional dimensions

654 to capture the full complexity of dynamic emotion signalling. Similarly, while this

655 study had no specific predictions about dynasticity of dynamics cues for individual

656 emotions, we observed baseline differences in decoding accuracy. It would be

657 informative for future studies to explore potential spatiotemporal features which may

658 underlie such differences and potential emotional confusions at both the production

659 and perceptual levels. Emerging computational and experimental approaches

enabling controlled manipulation of spatial and temporal facial dynamics in real or

near-real-time interactive settings offer promising routes for causal modelling of

spatiotemporal mechanisms of production and perception of facial emotion signals

[53,54]. Second, a different number of substates might be discovered using

physiological approaches, such as electromyography (EMG). Such approaches are

sensitive to subtle motor potentials and therefore may reveal more substates,

including preparatory or corrective movement impulses not apparent in FACS

resolution, which may carry both invariant and variant cues for emotional signalling.

Finally, our approach focuses on exhaustively describing spatiotemporal

components and how dynamic features that describe facial motion may optimally

encode emotion. However it does not isolate specific components, features (or

groups of features) nor assess their individual diagnostic value of select AU

activations. Our sensitivity analyses however, showed that models based on discrete

AUs were generally less reliable in decoding production and perceptual data than

those based on component structure. Even so, given that some AUs may be more

dominant and exhibit a broader dynamic range, whereas others are more subtle or

infrequently expressed, more systematic investigation of how different AUs dynamics

contribute to emotional signalling is warranted.

Despite these considerations, our results and approach provide new insights into the

dynamic mechanisms of face-to-face emotional signalling. This framework also

offers a promising model for understanding clinical conditions such as autism and

depression, particularly in relation to the role of atypical facial expression production

in social interaction difficulties [55,56]. These findings also have practical applications in

fields such as social robotics and human-computer interaction. A significant

challenge in these fields relates to endowing social agents (robots, digital agents)

with convincing and adaptable repertoires of social behaviour, including facial

signalling [57]. Spatiotemporal components and substates underlying facial expression

production could provide actionable building blocks without the need to painstakingly

design each facial expression into the architecture of these systems.

Conclusion

Conclusion

In conclusion, this study identifies a low-dimensional spatiotemporal structure and a

set of substates that underpin emotional signalling and perception of *Expression only*

and *Emotive speech* facial dynamics. It also provides a data-driven pipeline to

support the development of theoretical accounts of the structure and function of

expressive facial dynamics. This framework can be extended and compared to other

spatiotemporal models of facial dynamics and modalities to further elucidate the

dynamic and multimodal nature of emotion signalling in face-to-face interaction.

Methods

Methods

Participants

43 volunteers from the university community (24 female; mean age = 26), took part

in the facial expression production study for course credit or monetary incentive. A

separate sample of 45 participants from the general population, naïve to the

production task, took part in a perceptual validation experiment (see SI Perceptual

Validation Study). All participants gave informed consent, and all procedures of the

study were approved by the School of Psychological Science Research Ethics

Committee at both the University of Bristol and University of Birmingham (ref 21918).

All procedures also adhered to the revised 2013 Declaration of Helsinki and relevant

national and international guidelines on research involving human subjects. The

dataset in the facial expression production study was collected as part of a larger

project investigating facial expression production kinematics and perception – see [14].

However, all the variables and analyses reported here are specific to this study and

not discussed in any previous papers. Furthermore, data from perceptual validation

study was exclusively collected and analysed for this paper.

Experimental procedure

Facial expression production task. Our protocol was based on our previous work [14]

which has shown to yield reliable communicative emotional signals when considering

both signal dynamics and perceptual inference of emotion. In two separate sessions,

across two days, participants' facial movements were recorded during a facial

expression production task. Participants were asked to signal three emotions (anger,

happiness, and sadness) as they would naturally use their everyday interactions.

This was done in two counterbalanced conditions. An *Expression only* condition

where participants simply produced non-verbal facial expressions to signal each

emotion, In the *Emotive speech* condition where, they were asked to express the

same emotions while verbalising a "neutral" sentence ("Hi, my name is Jo, and I am

a scientist"). This ensured that facial dynamic differences across emotions weren't

necessarily driven by the actual spoken content, but rather reflective of the target

emotion dynamics. Similar approaches have been also used in the literature to

generate datasets to study emotional production and perception stimuli with both

linguistic and pseudo-linguistic (nonsense) expressive utterances [43]. The conditions

are motivated by the fact that in social interaction, facial expressions can be

signalled both in isolation and embedded within *Emotive speech*, meaning that facial

movements might signal information relevant to emotion and speech simultaneously,

yet how speech and emotional cues are layered in facial dynamics is achieved is

unclear. We focused on those expressions because they represent emotion signals

which are often expressed in social interaction and communication [58]. While we

focus on three emotions only, the inclusion of a wider range of participants, speech

and non-speech conditions, and data across multiple days provides richer

representations of facial dynamics and variability compared to previous work in this

area, which is often restricted to a few signallers, emotions, and conditions.

Facial movements were recorded with participants seated with their head at the

centre of a rectangular frame to ensure central positioning towards the camera,

positioned 1 meter from a tripod-mounted video camcorder, sampling at 60Hz f/s

(Sony Handycam HDR-CX240E). The start and end points were signalled using an

audible beep, which allowed us to custom-align the recordings of facial expressions -

see the schematic illustration in Fig 8. The *Expression only* videos had consistent

duration of around 10 seconds, with some videos in the *Emotive speech* condition

being slightly shorter (see analytical approach section below for time matching and

alignment procedures).

<u>A separate perceptual validation study</u> was conducted online with participants naive

to the facial expression production task. Building on our validated protocol[14], we

used point-light recreations of the stimuli to isolate only spatiotemporal facial

expression dynamics and explore correspondence with human observers'' ratings

and categorisation of emotion signals (see SI- Perceptual Validation Study)

Analytical approach

Data processing. Facial expression production videos were processed using

OpenFace [59], an open-source suite for automated face-tracking, landmarking and

facial action unit detection based on the facial action coding system (FACS) [2]. We

focused on Action Units (AUs), which code for the observable presence and intensity

of basic face actions (e.g., blinking, mouth widening, eyebrow-raising) that can be

used to produce almost any facial expression movement. We estimated the temporal

activation weights for 18 AUs. Only videos with a tracking accuracy of over 90% and

with participant data across two sessions were used, resulting in a total of 532

videos with approximately 240 time points each. Based on visual inspection of the

movement profiles, we applied a moving average (window = 3 frames) to smooth out

the slight jitter inherent in face tracking and AU estimation, while preserving the

underlying trends and dynamic range. To ensure an equal temporal window for

spatiotemporal analyses, AU timeseries were reduced into 100-time bins for each

video. Binning was preferred over more computationally expensive alternatives such

as dynamic time-warping (DTW) for practicality since the overall timeseries duration

was very similar across videos, and visual comparisons between binning and DTW

tests on our data showed negligible differences – see Fig S11 in SI.

Figure 8. Schematic illustration of methodological and analytical approach.
1. illustrates the facial expression production task, where participants facial
expressions (angry, happy sad) were recorded in two conditions (*Expression only*
and *Emotive speech*). Expressions were perceptually validated in separate study
and sample. 2. OpenFace was used to quantify AU patterns over time and align
motion patterns. 3. summarises the procedure for the concatenation of AU
timeseries and the application of Non-Negative Matrix Factorization (NMF) to learn
an underlying low-dimensional spatiotemporal representation of the data. 4. The
accuracy and effectiveness of this lower-dimensional representation were validated
through a series of sensitivity and classification analysis. These relied on extracting
timeseries features (e.g. curvature, complexity) from spatiotemporal components and
using PCA to summarise them into a score per video, used for training the random
forest classification model validated in an unseen set. 5. Time series clustering was
used to identify substates or 'phases' in facial movement components.

Spatiotemporal analysis

Timeseries of AU weights for the full facial expression production task were analysed

using Non-Negative Matrix Factorization (NMF) [60]. NMF is a multivariate

dimensionality reduction method that decomposes a high-dimensional dataset into

two non-negative matrices that form a part-based representation of the data (i.e., the

original data is achieved by combining/adding components). The non-negativity

constraint is particularly well suited for representing movement and AU data, which is

typically positive, and the two-matrix part-based decomposition can intuitively

represent spatial vs time-varying aspects in the data – see Fig 8 (see also: [22,40,60]).

The NMF takes the concatenated AU timeseries as input, denoted by a matrix **M,**

which is a product of two low-dimensional matrices (**T** and **S**), **T** represents the

temporal weights (basis values for time bins), and **S** represents the spatial weights

(face action activation weights). The product of **T** and **S** matrices denoted by **M'**

represents an approximation of the full original matrix such that **M~M' = T * S.** The

algorithm works by initialising the values for **T** and **S** (e.g., with random values) and

using an iterative multiplicative update rule to sequentially update T and S by a factor

that minimises the approximation error (i.e., residuals). While the initialisation and

iterative nature of NMF means that the solution is non-deterministic (i.e., you can

learn multiple equally effective part-based representations), these update rules have

been shown to guarantee convergence (i.e., stability of the cost function) after a

relatively low number of iterations [61]. The optimal number of spatiotemporal

components (k) was assessed computationally by fitting a range of values (k = 2 to

6) and choosing a k that optimised various model fit and reconstruction metrics (e.g.,

residual sum of squares, silhouette for clustering cohesion, cophenetic coefficient,

see below). We also evaluated the final solution against NMF results on a

permutated dataset, using block-based time shuffling. This resulted in an appropriate

null dataset that destroyed the inherent spatiotemporal pattern in the data but

retained some temporal ordering. We then compared fit metrics between original and

permutated NMF (see also *Classification and clustering analysis*). We used the NMF

decomposition functions in the NMF package for R [62]. To visualise our NMF results

in an intuitive manner, we trained a custom model to predict aligned Facial Landmark

displacements (through Procrustes analysis) from AUs using partial least squares

regression. Note however that the AU to Landmark face model is not a perfect one to

one map between NMF results and visualisation, given the inherent many-to-one

relationship between facial landmarks and AUs [51].

For clarity of presentation and interpretation, we report the NMF components fitted

separately for the *Expression only* and *Emotive Speech conditions*. However,

sensitivity analyses confirm that these results are consistent with those obtained

from a joint analysis of both conditions, thereby showing reliability of the identified

spatiotemporal patterns, and that the results are not arbitrarily biased by the input

data.

Multivariate timeseries classification

We used a supervised classification approach to validate the diagnostic value of

spatiotemporal components for emotion expression. This involved five steps:

(1) Data splitting: We began by splitting the original pre-NMF data into training

(80%) and testing (20%) sets, ensuring that each set contained complete AU time

series for each video. This resulted in a matrix with approximately 183 videos x 100

time points and 18 AUs for train, and 45 x 100 x 18 for test set, where emotions were

all equally balanced (61 per category: angry, sad, and happy for train, and 15 each

for testing).

This split was performed before any further analyses, and all subsequent steps

maintained this separation ensuring further processing and model training was only

done on the training set and then applying results to the test set [63,64]. Hence any

mention of "training", always refers to operations on the respective training set.

(2) NMF re-training and projection: We then re-trained the NMF model using only

the training set data and projected the test set onto the trained NMF model space to

ensure consistency of components for classification.

(3) Feature extraction: Because standard classification approaches do not account

for inherent spatiotemporal features of the NMF components, we opted for an

approach that represents the spatiotemporal structure via interpretable theoretic time

series features (e.g., curvature, complexity) in line with best practices and

established computational frameworks for multivariate timeseries features extraction

classification [65,66]. This led to a total of 40 features extracted per component.

However because it is impractical to detail the individual computation of every single

feature, for completeness we provide a full list of extracted features with a brief

description in the Supplementary Information (Table S5).

The focus on timeseries features is motivated by previous research showing the role

of timeseries features in capturing diagnostic dynamics for classification of facial

expressions and body movements [11,14,67,68].

Given the large dimensionality of the data, a Principal Component Analysis (PCA)

was used to summarise the timeseries features based on variance in the train set

while retaining a number of dimensions equal to the number of NMF components for

consistency. The test set features were then transformed using the PCA model fitted

on the training set features to be used in the next step. The matrix provided to PCA

mirrors the number of videos from the original NMF analysis and the total number of

extracted spatiotemporal features per component. Specifically, for the training sets

under each condition (*Expression only* and *Emotive speech*), the matrix was 183

videos by 114 features (38 features for each of the three spatiotemporal

components), while the test sets are 45 by 114. The component scores were used

as inputs for classification analysis in the next step. Conceptually, each principal

component (PC) captures the temporal dynamics inherent in the original NMF

components, effectively consolidating the complex features patterns into a single

feature score per spatiotemporal dimension. On average, the first three PCs account

for between 34% and 40% of the variance in the data across both the *Expression*

only and *Emotive speech* conditions, in both the training and test sets, showing that

they capture structure without overfitting the facial behaviour data.

881
(4) Classification training and testing. We then trained a classifier on

spatiotemporal component features derived from step 3 and applied to predict

emotion expression in the held-out test set. Specifically, we used a Random Forests

(RF) Classifier - a supervised statistical learning method that learns a discriminant

model between a set of input variables (e.g., spatiotemporal component features)

and a set of target classes (expressions). Note, that we achieved similar results with

different methods (e.g., Support Vector Machine, Linear Discriminant Analysis), thus

our results are not a function of the analytical approach. The Random Forests

Classifier has the advantage of being relatively more robust to overfitting and able to

capture non-linear relationships and therefore was preferred. We used cross-

validation during training, where multiple training sets are created, and the data not

included in the test set is used to test the accuracy and tune the model parameters.

Reliable classification on the test set would indicate that the underlying

spatiotemporal components (identified by the NMF analysis) carry diagnostic

information for differentiating expressions. Note that the theoretical chance level for

our three-way classification problem (i.e. happy, sad, and angry expressions) is

defined as 33%, and because the datasets are balanced, this is also the empirical

"no-information rate" or null rate. In addition, we derived significance tests for our

classification results using binomial tests to determine whether the model's accuracy

on the test set was significantly greater than what would be expected by random

guessing (by comparing it to the no information rate). These binomial p-values were

compared with permutation-based p-values, which were generated by comparing the

observed accuracy to the distribution of accuracies obtained from shuffling the labels

(expressions) in the test set (N = 1000). The negligible differences between the

binomial and permutation-based p-values for our dataset validated the robustness of

our results, so we primarily report the binomial p-values.

As an additional sensitivity test, we used Fisher's Exact Test to assess the statistical

significance of the confusion matrix, by comparing pairwise expression differentiation

with adjustments for multiple comparisons. The null hypothesis is that there is no

association between rows and columns, or in other words differences in cell values

(frequency) are due to chance. A low p-value in Fisher's exact test indicates

statistically significant differences between pairs, meaning the pattern in the

confusion matrix is unlikely to have occurred by chance.

While a handful of previous studies previous work has employed elements of our

proposed pipeline such as the dimensionality reduction of facial movement data

across entire datasets, our approach is unique in that it explicitly builds in the

generalisability and robustness of the spatiotemporal patterns we uncover.

Furthermore, the spatiotemporal classification pipeline enables us to directly link the

inherent dynamics (represented through the extracted features) to their diagnostic

value in differentiating emotions. We also used the same general approach above

(from step 4) to analyse the perceptual validation data, linking our spatiotemporal

components and human observers' perceptual emotion ratings, for the held-out test

set – see [69,70,71]. Full details are provided in the SI - Perceptual validation of the

spatiotemporal components for emotion signalling.

Spatiotemporal clustering for substates analyses

We investigated whether substates could be extracted from the spatiotemporal

patterns of *Expression only* and *Emotive speech* facial movements. We considered

substates as local intervals where the components exhibit salient signatures that are

consistent across expression timeseries. We operationalised this as a segmentation

of a multivariate timeseries into finer temporal segments with arbitrary lengths. To do

this we first derived speed and displacement for spatiotemporal components (from

step 2 above - NMF re-training and projection), as these features are sensitive to

segments local characteristics of other body movements (e.g., swing and stance

signatures in walking, fixation and saccades in eye movements) [23,34,35,72]. These

were computed using standard approaches from the kinematic literature. Speed was

computed as the first derivative of the time series, approximated by the bin-wise

difference between consecutive values and normalised by the corresponding time

interval. Displacement was derived as the differencing of the timeseries over time

relative to the starting values (baseline).

Second, we applied spatiotemporal clustering using the *dtwclust* package in R, using

the component speed and displacement metrics as inputs. This was motivated by

the fact that, unlike other movements with well-established kinematic profiles, we

have no *a priori* knowledge regarding the characteristics of facial expression

substates. Given the computational complexity of DTW, we first tested cluster sizes

on a smaller subset of *Expression only and Emotive speech* data. We used

exploratory visualisations (e.g. Fig 6) which suggested two to three interpretable

segments described transition and stability phases in spatiotemporal components of

facial expressions in line with the hypothesised patterns of transition, sustainment

and relaxation of AUS. Note that because the substate clustering inputs are based

on spatiotemporal components representing AUs, and because AUs are equally

valid descriptors of facial behaviour in both non-verbal expression and emotive

speech, substate analysis are equally valid for both conditions. Therefore, any

differences in substate patterns are reflective of condition-specific nuances, rather

than a bias to specific condition.

Because the clustering results are mostly descriptive and return only cluster labels

for partitioning the input data, it does not inherently provide a statistical

characterisation for why these clusters emerge. To facilitate intuitive interpretation of

clusters, we therefore visualise the pattern of clusters and the input data (Fig 6). For

example, it became apparent that clusters had distinct speed signatures but also

apparent sequences that are more prominent in *Expression only* and more dynamic

in *Emotive speech* conditions. To statistically assess these patterns, and explore

how they differentiate emotion and conditions, we computed two metrics: (1) speed

within the substate and (2) entropy; both which have been shown to capture

diagnostic information about facial expression movement patterns [11,14]. Specifically

given that speed contributes to the clustering as an input, statistically comparing

speed gives direct insights into how the clusters were generated (see Fig 6).

Entropy, is on the other hand is an information-theoretic measure of complexity,

directly related the dynamics of state transitions (or sequences) within a system [44]. In

this context, entropy provides a suitable summary of the dynamics of substates that

can be computed post hoc (after cluster generation) and summarised in a single

statistic, describing how complex or unpredictable the sequence of these substates

is (e.g., how much information about the current substate can predict the next

substate). This statistic aimed at exploring the apparent differences in the temporal

patterns of substates between expressions and conditions (see Fig 6). We computed

entropy using the transition entropy function (for state change entropy) from the

GrpString package for R [73] but for simplicity we refer it as entropy. To improve

interpretability, entropy was normalised by dividing it by the maximum theoretical

entropy for a system with the same number of substates.

Both speed and entropy measures were computed for each individual expression

and analysed using a mixed-effects model to test the effect of emotion (happy,

angry, sad), condition (*Expression only*, *Emotive speech*), and substate (relaxed,

transition, sustain) as fixed effects and subject (face id) as a random effect (random

intercept). Fixed effects terms were also initially included as random effects (slope

terms for expression and condition), however, random structure was simplified in line

with best practice for parsimonious mixed models [74,75] which revealed that "maximal

models" (full complex slope models) tended to overfit (according to AIC and BIC

indices) and lead to instability in convergence.

As such the final models had the form:

speed (or entropy) ~ emotion × condition × substate + (1 + condition | face ID)

We used a linear mixed models as opposed to the classification pipeline described

earlier given the primary aim to characterise substates and statistically assess

differences between emotion and conditions on the basis of substate patterns.

Additionally, the more complex and nested structure of the substate data makes

classification overly complex to structure and present. Linear mixed models were

fitted using the lme4 package for R [76] with inferential tests derived from lmerTest[77]

using the Satterthwaite's approximations for degrees of freedom from the covariance

structure and report Type III tests of fixed effects, in line with best practice

recommendations [74,75]. Pairwise and interactions post-hoc were all adjusted for

multiple comparison using Bonferroni corrections.

1006

Perceptual validation experiment

<u>Participants.</u> An additional sample of 45 naïve participants (22 female, age range: 23-

40), took part in an online study to validate the stimuli from the facial expression

production study described in the main manuscript. Participants were recruited via

Prolific (an online testing platform) and were compensated at £9 per hour. Participants

were selected to have English as their first language and residing in the UK, with no

current mental health conditions or autism diagnosis [78].

<u>Stimuli and perceptual validation task.</u> Given the online format and the large number

of stimuli derived from the facial expression production task, it was not feasible for

participants to rate every single video. 90 selected videos from the spatiotemporal

analyses (held-out test-set), were used as a representative subset of the stimuli in the

study (45 for *Expression only* and 45 from the *Emotive speech* conditions, with 15

videos per emotion: happy, angry, and sad). To isolate the motion characteristics of

the original stimuli, we used face landmarks from openFace (see Methods)[79] to

generate the stimuli for the perceptual validation. Specifically, we used the aligned

facial landmarks to generate point-light face display (PLFDs) animations, building on

a validated protocol used in our previous work [14]. To correct for inherent jitter in facial

landmarking, a slight smoothing was applied to facial landmarks using a moving

average with a window of 2 frames.

<u>Task.</u> To ensure attentiveness and authenticity of participants, we implemented

random video checks throughout the task using their webcam (with their consent) to

capture snapshots of participants while they completed the task, in addition to a self-

report survey in the end of the experiment. Each video was displayed for its original

duration (approximately 10 seconds). For each video, participants rated the intensity

of three emotions (anger, happy, and sad) on a scale from 0 to 100. An additional

"other emotion" rating was included to ensure variability and complexity, thus reducing

the likelihood that participants would simply eliminate options rather than provide

genuine ratings. To reduce parity in the different ratings, participants were instructed

to assign their highest rating to the emotion they perceived as most dominant in each

video. The presentation order for each condition (*Expression only* and *Emotive*
speech) was counterbalanced across participants and videos were presented
randomly. On average, the entire task took about 35 minutes to complete.

1039

<u>Perceptual validation of facial expression production.</u> For each video, and participant,
we assigned the perceived emotion categorisation based on the highest rating given
by the participant. For instance, if the highest rating was 70 for "happy" and lower for
all other options, that trial was categorised as "happy". This categorisation was
performed both on the full dataset and on the aggregated dataset where ratings were
averaged per stimulus across participants. To assess the alignment between
perceptual ratings for emotion and the facial expression production categories, we
tested for the correspondence between perceptual derived emotion categorisations,
and the intended "ground-truth" emotion from the facial production task. This was
tested using Pearson's Chi-squared tests - conducted with 2000 simulated replicates.
A significant test, indicate that the perceptually derived categories closely reflect the
production-based "ground-truth", thereby providing strong validation for the stimuli.

1052

<u>Correspondence between spatiotemporal models and human observers.</u> Building on
the data described above, in study 2, we conducted two additional analyses to validate
the predictive value of spatiotemporal components to perceptual processing of
emotion from facial signal dynamics. First, we conducted a correspondence analysis
to test the relationship between emotion classification predictions derived from our
spatiotemporal-based approach and those provided by human observers on the held-
out test set. The use of held-out data (not used in the training of the NMF analysis)
inherently provides a generalisability test, ensuring that any correspondence is not
simply driven by overfitting to characteristics that differentiate the expressions in the
data.
Second, similar to the use of the spatiotemporal components to predict emotion
categories in the held-out test set from production only data (see Multivariate
timeseries classification, step 4 in the manuscript), we used the spatiotemporal
components to directly predict human emotion categorisation. This complementary
analysis allows us to test not only whether our model's predictions align with
participants' ratings, but also whether the spatiotemporal features themselves are
directly predictive of perceptual judgments. Both approaches described above align

with the current practice in linking model-based performance with human behaviour in neuroscience and machine learning, which has been used in modelling human visual processes [69,70] – although see [71].

For consistency we use the similar classification approach described in the spatiotemporal classification section, relying on a Random Forest classifier. However, to ensure reliability and generalisability of these findings, we employed two validation approaches: (a) Leave-One-Stimulus-Out (LOSO)**:** For the data averaged across participants, the model was iteratively trained on all data except for one stimulus at a time. This procedure ensures that prediction of human observers' emotion categorisations generalise across different stimuli; (b) Leave-One-Participant-Out (LOPO): In this approach, the model was trained on data from all participants except one and then tested on the held-out participant. This process was repeated until every participant had served as both training and test data, confirming that the results are robust to variability in individual participants ratings.

High accuracy scores indicate that the spatiotemporal components robustly predict perceptual ratings. Although the theoretical chance level for a three-way classification (angry, happy, sad) is 33%, the empirical chance level may be higher if participant responses are skewed toward a majority category (e.g., happy). In such cases, using the majority response as the baseline provides a more stringent and data-specific test of model performance.

Data availability statement

Supporting data is available in the Open Science Framework (OSF):

https://osf.io/3nzk7/?view_only=db7d9467423f42b794385e549b6aa96a

All code for pre-processing and models is available at https://github.com/hcuve/spat-tmp-emo-faces

Acknowledgments

We would like to thank Professor Rachael Jack for her insights during the initial discussions on facial signalling dynamics and dimensionality reduction. We would

1100   also like to thank Katherine Lane and Tahniyyat Bokhari, for their assistance with

1101   data collection for a portion of the study.

1102

Author Contributions (CRediT)

HCC, Conceptualisation, Data Curation, Formal Analysis, Funding Acquisition,

Investigation, Methodology, Software, Supervision, Validation, Visualisation, Writing

– Original Draft Preparation, Writing – Review & Editing, Resources

SSC, Methodology, Validation, Writing – Review & Editing

JC, Conceptualization, Funding Acquisition, Methodology, Writing – Review &

Editing, Resources

1110

Funding Statement

HCJC was funded by an Experimental Psychology Society Postdoctoral Fellowship

and a Wellcome Trust Accelerator Award.

This project was also partly funded by a grant from the European Union's Horizon

2020 Research and Innovation Programme under ERC-2017-STG Grant Agreement

No 757583.

1117

References

1118

1119   1.   Jack, R. E. & Schyns, P. G. The human face as a dynamic tool for social

1120   communication. *Curr. Biol.* **25**, R621-34 (2015).

1121   2.   Ekman, P. & Friesen, W. V. Facial action coding system. *Environmental*

1122   *Psychology & Nonverbal* (1978).

1123   3.   Barrett, L. F., Adolphs, R., Marsella, S., Martinez, A. M. & Pollak, S. D.

1124   Emotional expressions reconsidered: challenges to inferring emotion from

1125   human facial movements. *Psychol. Sci. Public Interest* **20**, 1–68 (2019).

1126   4.   Jack, R. E., Garrod, O. G. B., Yu, H., Caldara, R. & Schyns, P. G. Facial

1127   expressions of emotion are not culturally universal. *Proc Natl Acad Sci USA*

1128   **109**, 7241–7244 (2012).

1129   5.   Ekman, P. & Keltner, D. Universal facial expressions of emotion. *Segerstrale*

1130   *U*.

1131   6.   Krumhuber, E. G., Skora, L. I., Hill, H. C. H. & Lander, K. The role of facial

1132   movements in emotion recognition. *Nat. Rev. Psychol.* (2023)

1133   doi:10.1038/s44159-023-00172-1.

1134   7.   Scherer, K. R. & Ellgring, H. Multimodal expression of emotion: affect

1135   programs or componential appraisal patterns? *Emotion* **7**, 158–171 (2007).

1136   8.   Ghazanfar, A. A. & Takahashi, D. Y. Facial expressions and the evolution of

1137   the speech rhythm. *J. Cogn. Neurosci.* **26**, 1196–1207 (2014).

9.   Chandrasekaran, C., Trubanova, A., Stillittano, S., Caplier, A. & Ghazanfar,

A. A. The natural statistics of audiovisual speech. *PLoS Comput. Biol.* **5**,

e1000436 (2009).

10. Jack, R. E. & Schyns, P. G. Toward a social psychophysics of face

communication. *Annu. Rev. Psychol.* **68**, 269–297 (2017).

11. Jack, R. E., Garrod, O. G. B. & Schyns, P. G. Dynamic facial expressions of

emotion transmit an evolving hierarchy of signals over time. *Curr. Biol.* **24**,

187–192 (2014).

12. Liu, M. *et al.* Facial expressions elicit multiplexed perceptions of emotion

categories and dimensions. *Curr. Biol.* **32**, 200-209.e6 (2022).

13. Gill, D., Garrod, O. G. B., Jack, R. E. & Schyns, P. G. Facial movements

strategically camouflage involuntary social signals of face morphology.

Psychol. Sci. **25**, 1079–1086 (2014).

14. Sowden, S., Schuster, B. A., Keating, C. T., Fraser, D. S. & Cook, J. L. The

role of movement kinematics in facial emotion expression production and

recognition. *Emotion* **21**, 1041–1061 (2021).

15. Dobs, K., Bülthoff, I. & Schultz, J. Use and Usefulness of Dynamic Face

Stimuli for Face Perception Studies-a Review of Behavioral Findings and

Methodology. *Front. Psychol.* **9**, 1355 (2018).

16. Burrows, A. M. The facial expression musculature in primates and its

evolutionary significance. *Bioessays* **30**, 212–225 (2008).

17.   Sherwood, C. C. Comparative anatomy of the facial motor nucleus in

1160   mammals, with an analysis of neuron numbers in primates. *Anat. Rec. A*

1161   *Discov. Mol. Cell. Evol. Biol.* **287**, 1067–1079 (2005).

1162   18.   Todorov, E. Optimality principles in sensorimotor control. *Nat. Neurosci.* **7**,

1163   907–915 (2004).

1164   19.   Pang, R., Lansdell, B. J. & Fairhall, A. L. Dimensionality reduction in

1165   neuroscience. *Curr. Biol.* **26**, R656-60 (2016).

1166   20.   Latash, M. L., Scholz, J. P. & Schöner, G. Toward a new theory of motor

1167   synergies. *Motor Control* **11**, 276–308 (2007).

1168   21.   Chiovetto, E., Salatiello, A., d'Avella, A. & Giese, M. A. Toward a unifying

1169   framework for the modeling and identification of motor primitives. *Front.*

1170   *Comput. Neurosci.* **16**, 926345 (2022).

1171   22.   Chiovetto, E., Curio, C., Endres, D. & Giese, M. Perceptual integration of

1172   kinematic components in the recognition of emotional facial expressions. *J.*

1173   *Vis.* **18**, 13 (2018).

1174   23.   Labaune, O., Deroche, T., Teulier, C. & Berret, B. Vigor of reaching, walking,

1175   and gazing movements: on the consistency of interindividual differences. *J.*

1176   *Neurophysiol.* **123**, 234–242 (2020).

1177   24.   Ivanenko, Y. P., Poppele, R. E. & Lacquaniti, F. Five basic muscle activation

1178   patterns account for muscle activity during human locomotion. *J Physiol*

1179   *(Lond)* **556**, 267–282 (2004).

1180   25.   Chiovetto, E., Berret, B. & Pozzo, T. Tri-dimensional and triphasic muscle

1181   organization of whole-body pointing movements. *Neuroscience* **170**, 1223–

1182   1238 (2010).

1183   26.   Zangrossi, A., Cona, G., Celli, M., Zorzi, M. & Corbetta, M. Visual exploration

1184   dynamics are low-dimensional and driven by intrinsic factors. *Commun. Biol.*

1185   **4**, 1100 (2021).

1186   27.   Ramanarayanan, V., Goldstein, L. & Narayanan, S. S. Spatio-temporal

1187   articulatory movement primitives during speech production: extraction,

1188   interpretation, and validation. *J. Acoust. Soc. Am.* **134**, 1378–1394 (2013).

1189   28.   Barliya, A., Omlor, L., Giese, M. A., Berthoz, A. & Flash, T. Expression of

1190   emotion in the kinematics of locomotion. *Exp. Brain Res.* **225**, 159–176

1191   (2013).

1192   29.   Montepare, J. M., Goldstein, S. B. & Clausen, A. The identification of

1193   emotions from gait information. *J. Nonverbal Behav.* **11**, 33–42 (1987).

1194   30.   Dalmaijer, E. S., Lee, A., Leiter, R., Brown, Z. & Armstrong, T. Forever yuck:

1195   Oculomotor avoidance of disgusting stimuli resists habituation. *J. Exp.*

1196   *Psychol. Gen.* **150**, 1598–1611 (2021).

1197   31.   Bress, K. S. & Cascio, C. J. Sensorimotor regulation of facial expression - An

1198   untouched frontier. *Neurosci. Biobehav. Rev.* **162**, 105684 (2024).

1199   32.   Livingstone, S. R., Thompson, W. F., Wanderley, M. M. & Palmer, C.

1200   Common cues to emotion in the dynamic facial expressions of speech and

1201   song. *Q J Exp Psychol (Colchester)* **68**, 952–970 (2015).

33.   Mackevicius, E. L. *et al.* Unsupervised discovery of temporal sequences in

high-dimensional datasets, with applications to neuroscience. *eLife* **8**, (2019).

34.   Rucci, M. & Poletti, M. Control and Functions of Fixational Eye Movements.

Annu. Rev. Vis. Sci. **1**, 499–518 (2015).

35.   Torricelli, F. *et al.* Motor invariants in action execution and perception. *Phys.*

Life Rev. **44**, 13–47 (2023).

36.   Krumhuber, E. G. & Scherer, K. R. Affect bursts: dynamic patterns of facial

expression. *Emotion* **11**, 825–841 (2011).

37.   Schmidt, K. L., Cohn, J. F. & Tian, Y. Signal characteristics of spontaneous

facial expressions: automatic movement in solitary and social smiles. *Biol.*

Psychol. **65**, 49–66 (2003).

38.   Aghabozorgi, S., Seyed Shirkhorshidi, A. & Ying Wah, T. Time-series

clustering – A decade review. *Inf. Syst.* **53**, 16–38 (2015).

39.   Aggarwal, C. C. An introduction to cluster analysis. in *Data clustering:*

algorithms and applications (eds. Aggarwal, C. C. & Reddy, C. K.) 1–28

(Chapman and Hall/CRC, 2018). doi:10.1201/9781315373515-1.

40.   Delis, I. *et al.* Space-by-time manifold representation of dynamic facial

expressions for emotion categorization. *J. Vis.* **16**, 14 (2016).

41.   Namba, S., Nakamura, K. & Watanabe, K. The spatio-temporal features of

perceived-as-genuine and deliberate expressions. *PLoS ONE* **17**, e0271047

(2022).

42. Watson, D. M., Brown, B. B. & Johnston, A. A data-driven characterisation of

natural facial expressions when giving good and bad news. *PLoS Comput.*

Biol. **16**, e1008335 (2020).

43. Bänziger, T., Mortillaro, M. & Scherer, K. R. Introducing the Geneva

Multimodal expression corpus for experimental research on emotion

perception. *Emotion* **12**, 1161–1179 (2012).

44. Shannon, C. E. & Weaver, W. *The mathematical theory of communication*.

(University of Illinois Press, 1998).

45. Le Mau, T. *et al.* Professional actors demonstrate variability, not stereotypical

expressions, when portraying emotional states in photographs. *Nat. Commun.*

12, 5037 (2021).

46. *Multichannel integrations of nonverbal behavior*. (Psychology Press, 2014).

doi:10.4324/9781315802305.

47. Wolpert, D. M., Doya, K. & Kawato, M. A unifying computational framework

for motor control and social interaction. *Philos. Trans. R. Soc. Lond. B Biol.*

Sci. **358**, 593–602 (2003).

48. Bell, S. M. & Ainsworth, M. D. Infant crying and maternal responsiveness.

Child Dev. **43**, 1171–1190 (1972).

49. Rowe, C. Receiver psychology and the evolution of multicomponent signals.

Anim. Behav. **58**, 921–931 (1999).

50. Duchenne de Boulogne, G. B. *The mechanism of human facial expression*.

(Cambridge University Press, 1990). doi:10.1017/CBO9780511752841.

51. Mavadati, S. M., Mahoor, M. H., Bartlett, K., Trinh, P. & Cohn, J. F. DISFA: A

spontaneous facial action intensity database. *IEEE Trans. Affect. Comput.* **4**,

151–160 (2013).

52. Hebets, E. A. *et al.* A systems approach to animal communication. *Proc. Biol.*

Sci. **283**, 20152889 (2016).

53. Arias-Sarah, P. *et al.* Aligning the smiles of dating dyads causally increases

attraction. *Proc Natl Acad Sci USA* **121**, e2400369121 (2024).

54. Various authors. SeamlessInteraction: Dyadic Audiovisual Motion Modeling

and Large-Scale Dataset. https://arxiv.org/abs/2506.22554 (2025).

55. Brewer, R. *et al.* Can neurotypical individuals read autistic facial expressions?

atypical production of emotional facial expressions in autism spectrum

disorders. *Autism Res.* **9**, 262–271 (2016).

56. Haque, A., Fei-Fei, L., Guo, M. & Miner, A. S. Measuring Depression

Symptom Severity from Spoken Language and 3D Facial Expressions.

Machine Learning for Health (ML4H) Workshop at NeurIPS 2018, Montréal,

Canada (2018).

57. Rawal, N. & Stock-Homburg, R. M. Facial emotion expressions in human–

robot interaction: A survey. *Int. J. Soc. Robot.* **14**, 1583–1604 (2022).

58.   Calvo, M. G., Gutiérrez-García, A., Fernández-Martín, A. & Nummenmaa, L.

Recognition of Facial Expressions of Emotion is Related to their Frequency in

Everyday Life. *J. Nonverbal Behav.* **38**, 549–567 (2014).

59.   Baltrušaitis, T. & Robinson, P. Openface: an open source facial behavior

analysis toolkit. *2016 IEEE Winter* (2016).

60.   Lee, D. D. & Seung, H. S. Learning the parts of objects by non-negative

matrix factorization. *Nature* **401**, 788–791 (1999).

61.   Fu, X., Huang, K., Sidiropoulos, N. D. & Ma, W.-K. Nonnegative matrix

factorization for signal and data analytics: identifiability, algorithms, and

applications. *IEEE Signal Process. Mag.* **36**, 59–80 (2019).

62.   Gaujoux, R. & Seoighe, C. A flexible R package for nonnegative matrix

factorization. *BMC Bioinformatics* **11**, 367 (2010).

63.   Kriegeskorte, N., Simmons, W. K., Bellgowan, P. S. F. & Baker, C. I. Circular

analysis in systems neuroscience: the dangers of double dipping. *Nat.*

Neurosci. **12**, 535–540 (2009).

64.   Varoquaux, G. & Colliot, O. Evaluating machine learning models and their

diagnostic value. in *Machine learning for brain disorders* (ed. Colliot, O.)

(Humana, 2023). doi:10.1007/978-1-0716-3195-9_20.

65.   Baldán, F. J. & Benítez, J. M. Multivariate times series classification through

an interpretable representation. *Inf Sci (Ny)* **569**, 596–614 (2021).

66. Fulcher, B. D., Little, M. A. & Jones, N. S. Highly comparative time-series

analysis: the empirical structure of time series and their methods. *J. R. Soc.*

Interface **10**, 20130048 (2013).

67. Dobs, K. *et al.* Quantifying human sensitivity to spatio-temporal information in

dynamic faces. *Vision Res.* **100**, 78–87 (2014).

68. Furl, N. *et al.* Face space representations of movement. *Neuroimage* **212**,

116676 (2020).

69. Schrimpf, M. *et al.* Brain-Score: Which Artificial Neural Network for Object

Recognition is most Brain-Like? *BioRxiv* (2018) doi:10.1101/407007.

70. Daube, C. *et al.* Grounding deep neural network predictions of human

categorization behavior in understandable functional features: The case of

face identity. *Patterns (N Y)* **2**, 100348 (2021).

71. Schyns, P. G., Snoek, L. & Daube, C. Degrees of algorithmic equivalence

between the brain and its DNN models. *Trends Cogn Sci (Regul Ed)* **26**,

1090–1102 (2022).

72. Miranda, J. G. V. *et al.* Complex Upper-Limb Movements Are Generated by

Combining Motor Primitives that Scale with the Movement Size. *Sci. Rep.* **8**,

12918 (2018).

73. Hooge, I. & Camps, G. Scan path entropy and arrow plots: capturing

scanning behavior of multiple observers. *Front. Psychol.* **4**, 996 (2013).

74.   Meteyard, L. & Davies, R. A. I. Best practice guidance for linear mixed-effects

models in psychological science. *J. Mem. Lang.* **112**, 104092 (2020).

75.   Bates, D., Kliegl, R., Vasishth, S. & Baayen, H. Parsimonious mixed models.

arXiv preprint arXiv:1506.04967 (2015).

76.   Bates, D., Mächler, M., Bolker, B. & Walker, S. Fitting linear mixed-effects

models using lme4. *arXiv preprint arXiv:1406.5823* (2014).

77.   Kuznetsova, A., Brockhoff, P. B. & Christensen, R. H. B. lmertest package:

tests in linear mixed effects models. *J. Stat. Softw.* **82**, 1–26 (2017).

78.   Cuve, H. C., Gao, Y. & Fuse, A. Is it avoidance or hypoarousal? A systematic

review of emotion recognition, eye-tracking, and psychophysiological studies

in young adults with autism spectrum conditions. *Res. Autism Spectr. Disord.*

55, 1–13 (2018).

79.   Baltrusaitis, T., Zadeh, A. & Lim, Y. C. Openface 2.0: Facial behavior analysis

toolkit. *2018 13th IEEE* (2018).