Spatiotemporal structure and substates underly emotional signalling in facial

expressions and speech movements

Hélio Clemente José Cuve[1*], Sophie Sowden-Carvalho[2], Jennifer Cook[2]

[1]School of Psychological Science, University of Bristol, Bristol, United Kingdom

[2]School of Psychology, University of Birmingham, Birmingham, United Kingdom

[*]Corresponding author

e-mail: helio.cuve@bristol.ac.uk

School of Psychological Science

University of Bristol

12a, Priory Road

Bristol BS8 1TU

United Kingdom

Abstract

From overt emotional displays to a subtle eyebrow raise during speech, facial

expressions are key cues for social interaction. How these inherently dynamic

signals encode emotion remains only partially understood. Moreover, despite the

ubiquity of speech in face-to-face interactions, the dynamics of facial emotion signals

during speech have been overlooked. In Study 1 we recorded participants' facial

movements signalling happy, sad and angry emotions in *Expression-only* and

Emotive-speech conditions. We then employed a data-driven pipeline integrating

facial motion quantification, spatiotemporal classification and clustering to investigate

the structure and function of facial dynamics in signalling emotion. Results reveal

that a few fundamental spatiotemporal patterns reliably differentiated emotion in non-

verbal expressions and emotive speech facial signals. Furthermore, we identified

transient substates – or dynamic phases- that are diagnostic of emotion and

conditions. A perceptual validation with naive observers (Study 2) showed that the

low-dimensional spatiotemporal structure captures meaningful cues that closely

predicts human emotion categorisations. We argue that this low-dimensional

spatiotemporal structure optimises both the transmission and perception of dynamic

facial emotion signals. This work contributes insights into face-to-face emotion

signalling and provide a versatile framework for modelling dynamic social cues and

can inform the design of expressive emotive capabilities in social agents.

Keywords: Facial expressions, movement, spatiotemporal, dimensionality reduction,

emotion, signalling.

Introduction

The human face is an incredibly versatile signalling tool for social interaction [1] capable of producing a rich array of non-verbal signals through the coordination of basic motor facial action units (AUs) [2]. For example, frowning (AU4) combined with pursed lips (AU24) can convey a prototypical facial expression of anger; while raising the cheeks (AU6) and pulling back the lip corners (AU12) can signal a smile. In addition to ostensive non-verbal emotional cues, in real-life social interaction, facial expressions simultaneously modulate verbal communication. A slight tightening of the eyelids (AU7) for example, can make a "neutral" verbal utterance appear slightly angrier. The mechanisms that afford such flexible expressive capabilities to facial signals remain only partly understood.

One overlooked aspect in previous research is the dynamic nature of facial expression signalling, with a large focus instead on the static aspects of facial behaviour or approaches ignore temporal dynamics [3]. Moreover, although most face-to-face interactions naturally involve speech, the role of speech-related facial dynamics in emotion signalling has been largely neglected. Yet these dynamic cues in conversational or speech-related facial expressions can enhance the simultaneously transmission of visual signals for emotion and verbal communication [3–6]. Nonetheless, a few key studies have provided important insights on the role of facial expression dynamics to emotion signalling. Psychophysics inspired approaches have combined generative synthesis of facial movements [7] and reverse correlation to parametrically map the spatiotemporal features of AUs to perceptual representations of emotion categories[8], valence-arousal dimensions [9] and even social traits[10]. Similarly, a recent production and perception study recorded

participants' facial movement signals of anger, happiness, and sadness, as well as

during spoken sentences conveying the same emotions [11]. Kinematic analysis

revealed faster movements for high-arousal emotions (happiness, anger) compared

to slower movements for low-arousal emotions (sadness). Thus, suggesting that

facial dynamics carry fundamental diagnostic spatiotemporal information for

differentiating emotional expressions at both the production and perception stages.

Nevertheless, a detailed account of the spatiotemporal structure of facial signals—

how AUs dynamically combine and unfold to signal emotions and simultaneously

convey speech-related information—remains lacking. One significant challenge to

studying the role of spatiotemporal structure in facial expression signalling is the lack

of an integrated theoretical and methodological framework. Such a framework should

ideally integrate the dynamic nature of facial expression signals with their socio-

communicative functions and provide an appropriate modelling strategy – see [1,7]. In

this work, we build on the observation that facial expressions, like other facial and

bodily movements, are controlled by an underlying motor system [12,13]. We explore

the application of theoretical and analytical principles drawn from the motor control

literature to understand the spatiotemporal structure and function of dynamics in

facial expressions for signalling emotion.

A motor control perspective provides two useful theoretical insights that are

applicable to studying the spatiotemporal structure and function of facial expression

dynamics. First, a longstanding motor control hypothesis suggests that body

movements are generated by a low-dimensional mechanism that underpins their

effective neural control and physical execution [14–16]. Such low-dimensionality of

motor control and execution might reflect the brain's solution to the problem of

controlling numerous muscles and components of the motor system whilst

minimising computational demands - often referred to as the "degrees of freedom"

problem [17–19]. Crucially, such low dimensionality has been shown to describe motion

patterns during walking [20], whole body pointing [21], eye movements [22] and articulatory

speech movements [23]. These movements also convey emotion-related information

[24–26] providing theoretical basis and experimental evidence for shared control

mechanisms for social and non-social aspects of movement. Similarly, dynamics

underlying facial expressions, and their ability to multiplex information (e.g., visually

signal emotion and speech), may be structured around low-dimensional

spatiotemporal patterns. Such structure could be optimal for flexible and precise

spatiotemporal control of Action Units (AUs) and to signal emotion adaptively in

social interactions. Additionally, given that social interaction often involve continuous

verbal exchanges a low-dimensional spatiotemporal mechanism may also support

the simultaneous layering of emotion cues in speech-related facial dynamics. This

perspective also suggests a methodological framework to model spatiotemporal

nature of movement, which is rare in the study of facial expression production. For

instance, this can be explored using data-driven models that learn a the underlying

patterns of high-dimensional AU movement data [27].

A second insight from the motor-control literature is the empirical observation that

although outwardly fluid, body movements can often be segmented into distinct

'substates' often seen in differential modulation of kinematics (e.g., speed,

displacement of motor actions). For instance, walking movements can be segmented

into 'swing' or 'stance' phases [20] or eye movements into 'fixations' and 'saccades' [28],

and even more fine-grained states (sub movements) [29]. Facial expressions are likely

to have substates related to the biomechanics of how they are produced,

encompassing 'transitions'—where AUs are initiated or inhibited, - and 'stability' –

where AUs are sustained [30,31]. However, to date substates of facial expressions and

speech movements have not been formally characterised, and whether and how

they relate to emotional signalling is unknown. Similar to spatiotemporal

components, substates can be explored in a data-driven fashion, using methods

such as spatiotemporal clustering [27,32,33] given that lack of *apriori* well-defined

profiles for facial expression dynamics.

Probing the underlying spatiotemporal structure and substates in facial expressions

would enable a richer characterisation of facial dynamics that is both holistic, i.e.,

captures overall spatiotemporal patterns, but also focal as it can capture micro

spatiotemporal patterns. We hypothesise that these underlying patterns are not

merely incidental; rather, they are diagnostic of emotional content, reflecting how

facial movements are optimised for social signalling.

While some prior work has proposed similar motor-centric theoretical and

methodological approaches to model facial expression signalling, these have largely

focused on perception e.g. [8,34] rather than production. Notwithstanding, a few recent

study have employed motor-informed spatiotemporal dimensionality reduction

approaches to identify dynamic motifs in facial expression production data (e.g.

[18,35,36]. Nonetheless, the reliance on only single to a handful signallers or actors limits

the dynamic range and variability the facial signals analysed in prior work. Hence, it's

unclear whether the observed low dimensionality in these studies, genuinely reflect

the underlying mechanisms for facial expression signalling or simply results from

restricted variability in signal dynamics. It is also unclear how well these findings

generalise to other emotional expressions and conditions (e.g., emotive speech

facial dynamics). Furthermore, previous work also relied on averaging across the

spatiotemporal dimensions when comparing expressions and conditions, potentially

overlooking how inherent facial dynamics relate to emotion signalling (see Methods).

Consequently, the functional role of facial dynamics—including both low-dimensional

spatiotemporal patterns and substates remains only partially explored.

The current study therefore aimed to (1) describe the spatiotemporal structure

underlying facial expression production; (2) explore and characterise potential facial

expression substates, and 3) evaluate the diagnostic value of spatiotemporal

structure and substates for emotion signalling. To capture wider facial dynamics

relevant for social interaction, in study 1 we recorded 43 participants facial

movements while they signalled happy, sad and angry emotions in a) *Expression*

only and b) *Emotive speech* conditions across two separate sessions, building on

our previous validated facial expression production task [11]. We used automated

Facial Action Coding System (FACS) to describe the spatiotemporal patterns of the

facial AUs (e.g., mouth widening, eyebrow raise, etc). We then employed a novel

data-driven pipeline combining dimensionality reduction, dynamic feature extraction,

and spatiotemporal classification and clustering; to identify diagnostic latent

spatiotemporal patterns (groups of co-activated AUs and salient temporal patterns)

underlying optimal emotion signalling through facial dynamics - see Methods.

To precis our results, we find that *Expression only* and *Emotive speech* facial

dynamics can be distilled into a of small set of "fundamental" spatiotemporal

components that form the basis for flexible signalling. Specifically, the three

emotions (happy, angry, sad) and two conditions (*Expression only* and *Emotive*

speech) studied are differentiated by synergistic mixing of components and subtle

local substate differences related to expression transitions. In Study 2, an

independent perceptual validation with naïve observers showed that the low-

dimensional spatiotemporal structure is strongly predictive of human emotion

categorisations.

Our key contributions are two-fold. First, we provide new insights into the complex

and flexible signalling of emotion through facial movements, suggesting that it is

achieved through variations in a small number of functional and perceptually relevant

spatiotemporal patterns and substates. Second, we provide a versatile data-driven

pipeline to model the structure and function of facial dynamics in emotion signalling,

which can be extended to other dynamic social signalling modalities.

Results

<u>Facial expression production, perceptual validation check.</u> A perceptual validation of

the facial expression production task recordings was conducted with 45 naïve

participants in a separate study. Results show that the perceptual ratings of emotion

are reliably aligned with the predicted facial expression signals from the facial

production task. Adequate variability in perceptual ratings indicate that the facial

expression recordings contain sufficient diversity, with no evidence of ceiling or floor

effects. Full details and figures for this validation are provided in the SI - "Perceptual

Validation Study" and Fig. S1).

Spatiotemporal components for facial expression production.

We report results for *Expression only* and *Emotive speech* expressions separately

for clarity, however we note that these patterns were consistent when analysed

together (see SI - Comparison of joint vs separate spatiotemporal analysis of

Expression only and *Emotive speech*, and Fig. S8-9).

Spatiotemporal patterns during facial *Expression only* condition

We first looked at the spatiotemporal components identified via the Non-Negative

Matrix Factorization (NMF), which represent the underlying (reduced) diagnostic

spatiotemporal patterns (e.g., groups of AUs with common activation timecourses

and salient temporal patterns). The optimal number of spatiotemporal components

(k) optimising for various fit indices (see Methods) – was consistently three (see Fig

1 – top panel) (see also *Expression only* condition - NMF validation analysis in

Supplementary Information(SI) – Fig S2-4).

Figure 1. Spatiotemporal components for facial dynamics in *Expressions only* production.

The top panel (a) shows that expression production can be summarised by three
components, capturing spatiotemporal patterns for upper face AUs (component 1),
lower face AUs (component 2) and a combination of both lower and upper face AUS
(component 3). Top - middle and right columns show approximate spatial distribution
of components in an average face model and how it changes over time, respectively.
The bottom panel (b) highlight spatiotemporal profiles (averaged) for angry, happy
and sad expressions. Coef = coefficient, brighter colours indicate stronger activation.
Note that face maps are drawn for visualisation purposes only to provide a rough
visual representation of the AU-component profiles. Faces maps are derived from an
approximate pls regression predicting aligned and normalised facial landmark
changes from AUs based on facial production data (see methods).

Evaluation of the spatiotemporal patterns revealed that component 1 (C1) had

stronger activation of the upper face-related AUs (e.g., AU4 brow lowerer, AU7 lid

tightener) compared to other AUs. Component 2 (C2) had strong activation of both

lower and upper face-related AUs (e.g., AU25 lips part, AU14 dimpler). Component 3

(C3) was mostly dominated by lower face actions (e.g., AU17 chin raiser) with some

small activation of upper face AUs (e.g. AU45 blink). For clarity of presentation, we

name these components, upper face AUs (C1), lower face AUs (C2) and lower-to-

upper face AUs (C3). The averaged temporal profile of these components across

videos is shown in Fig 1 B. C1 (upper face AUs) and C2 (lower face AUS) had a

common inverted-U shape with a clear singular peak, whereas C3 (lower to upper

face AUs) had a less pronounced but more dynamic pattern (e.g. bimodal peaks).

Next, we formally assessed the diagnostic value of the spatiotemporal components,

by analysing how their dynamic features for differed between expressions and

validated it in a held-out test set (see Methods - *Multivariate Timeseries*

Classification). When assessing spatiotemporal components' ability to classify

expressions we achieved significantly above chance accuracy of over 90% (ACC

(accuracy)= 0.91 [BalACC (balanced accuracy) = .93], Kappa = 0.87; AUC(Area

Under the Curve) mean = 0.98, $p < .001$; note chance is .33 for a 3-way

classification). These results indicate strong agreement between prediction from

spatiotemporal model and ground-truth (from facial expression production task) –

see Fig 2 below.

Figure 2. Spatiotemporal classification of facial expressions only production.
Notes: The left panels show decision boundaries (filled backgrounds) across
spatiotemporal components (comp1: upper AUs, comp2: lower face AUs; comp3:
lower to upper face AUs) estimated on a training set to predict emotion classes
(angry, happy, sad). Coloured dots represent individual ground-truth expressions
from both training and held-out test data. Dots within a matching background indicate
correct classifications, while mismatches indicate misclassifications. The results
demonstrate robust classification, with at least a pair of component combinations
separating a target expression from the rest, e.g. comp1 vs 2 and comp-2 vs 3
robustly distinguishes happy expressions. The top right panel presents Receiver
Observer Characteristics (ROC) curves, showing good model performance (higher
True Positive Rate [TPR] and lower False Positive Rate [FPR]) with the diagonal
dashed line representing chance). The bottom right panel displays a confusion
matrix. Brighter colours indicate higher accuracy along the diagonal elements, with
off-diagonal showing little to no confusions (darker colours).

We also found distinct temporal profiles for each emotion. Angry expressions

(BalACC = .91, AUC=.97, p < .001) were characterised by strong temporal

coactivation of C1 (upper face AUS) and C2 (lower face AUS). Happy expressions

(BalACC = .98, AUC = .99, p < .001) were dominated by C2 (lower face AUs); and

sad (BalACC = .98, AUC = .90, p<.001) characterised by moderate changes in all

three components. To further validate our model, we conducted a Fisher's exact test

on the confusion matrix (see Methods), which confirmed significant pairwise

differentiation of all expressions on the basis of their spatiotemporal patterns (angry

vs happy; angry vs sad; and happy vs sad: p.corrected < .001). These results

reinforce the robustness of our classification model, demonstrating that

spatiotemporal patterns capture reliable differences between emotional expressions.

For detailed validation and statistics see SI Fig S2-S4 and Table S1-2

Spatiotemporal patterns for *Emotive speech* facial expressions

Similar to the *Expression only* condition, we found that three components effectively

represented the spatiotemporal patterns of facial AUs signalling emotion in *Emotive*

speech (see Fig 3). However, there were some notable differences in the spatial and

temporal patterns, which likely reflect the fact that, in contrast with the *Expression*

only videos, the *Emotive speech* videos comprise a combination of facial expression

and speech AUs. Specifically, the *Emotive speech* components comprised a mix of

both lower and upper face AUs, in comparison to mostly lower vs upper face AUs for

Expression only conditions

Figure 3. Spatiotemporal components for *Emotive speech* facial expression production. The top panel (A) shows that *Emotive speech* facial expression production can be summarised by three underlying components, capturing synergies between upper to lower face AUs (Component 1), lower-mid-upper AUs (component 2) and lower to upper face AUs (component 3). Top - middle and right columns show approximate spatial distribution of components in an average face model and how it changes over time, respectively. Note patterns are averaged across videos for visualisation. The bottom panels (B) show how components change over time, highlighting different profiles for angry, happy and sad expressions. Coef = coefficient from the NMF, brighter colours indicate stronger activation. Note while matrix heatmaps are a true representation of the model, face maps are not a one-to-one map and are drawn for visualisation purposes only. Face maps only provide a rough visual representation, derived from an approximate pls regression predicting aligned and normalised facial landmarks change from AU data based on facial production data (see methods).

Component 1 included strong activation of upper and lower face Aus (e.g., AU4 -

brow lowerer; AU17 - chin raiser) peaking at both early and late time points.

Component 2 (lower-mid-upper face AUs) combined strong activation of AUs in the

lower (e.g., AU25 - lips part), middle (e.g., AU14 - dimpler) and upper face areas

(e.g., AU7 - lid tightener). Component 3 primarily featured activation of lower face

AUs, such as AU25 (lips part) and AU26 (jaw drop), plus additional moderate

activation for AU 45 (blink). Henceforth component 3 is referred to as lower to upper

face AUs (see Fig 3). C2 (lower-mid-upper face AUS) and C3 (lower to upper face

AUs) had an inverted-U shape with C3 peaking earlier than C2 (Fig 3C).

As with facial *Expression only* production, *Emotive speech* expressions were also

characterised by distinct spatiotemporal patterns. That is, a classifier trained on

timeseries-based features of the spatiotemporal components (e.g., curvature,

complexity) achieved significant accuracy in classifying expressions on a held-out

test set, with performance at 70% (ACC = 0.69, 95% CI: 0.53, 0.81; BalAcc = .76

Kappa = 0.53, p < 0.001). These results indicate moderate to strong agreement

between prediction and ground-truth emotional expression labels (see Fig 4).

Class-wise, the spatiotemporal components significantly distinguished all

expressions. Happy had the highest accuracy (BalACC = 0.91, AUC = 0.97, p <

.001), suggesting a clear and distinct spatiotemporal profile, notable in the increased

activation in C2 (lower-mid-upper face AUs) over time. For detailed validation and

statistics see SI Fig S5-S7 and Table S3-4

Figure 4. Spatiotemporal classification of _Emotive speech_ facial expressions.
The left panels show decision boundaries (filled backgrounds) across spatiotemporal
components (comp1: upper to lower face AUs, comp2: lower to upper face AUs;
comp3: upper-to-lower face AUs) estimated on a training set to predict emotion
classes (angry, happy, sad). Coloured dots represent individual ground-truth
expressions from both training and unseen test data. Dots within a matching
background indicate correct classifications, while mismatches indicate
misclassifications. The results demonstrate robust classification, with component
combinations effectively separating the expressions in at least one combination.
The top right panel presents ROC curves, showing good model performance (higher
True Positive Rate [TPR] and lower False Positive Rate [FPR]), with the diagonal
dashed line representing chance. The bottom right panel displays a confusion matrix.
Brighter colours indicate higher accuracy along the diagonal elements, and
confusion off-diagonal (e.g., happy shows high accuracy and low confusion, whereas
angry shows higher confusion than all expressions).

Angry had the lowest classification accuracy compared to all other expressions, yet

still significantly above chance (BalACC = 0.67, AUC = 0.83, p = .01), reflecting a

more complex and less distinct pattern across all components. Similar to happy, sad

expressions were classified reliably above chance (BalACC = 0.72, AUC = 0.84, p =

0.001). Fisher's exact test on the confusion matrix confirmed significant pairwise

differentiation between happy and sad expressions (p < .001) and between angry

and happy (p < .001). However, it suggested confusions between and angry and sad

(p = 0.12) (see Fig 4; SI1 - Table S3-4).

In summary, we found three latent spatiotemporal components that reliably

described the dynamics of facial expressions during *Expression only* and *Emotive*

speech conditions. Robust train-test classification on unseen held-out data, indicates

that spatiotemporal components carry fundamental diagnostic emotional cues with

good generalisability. Additionally, independent perceptual validation with 45 naïve

observers showed that the low-dimensional spatiotemporal structure is strongly

predictive of human emotion categorisations in the holdout test-set. Specifically, we

found (a) a strong correspondence between our model's spatiotemporal

classification predictions and human observers' categorisations (*Expression only,* X^2

= 33.125, p < .001, *Emotive Speech*, X^2 = 15.622, p = .002) and (b) high predictive

accuracy of human observers' emotion categorisation based solely on these

spatiotemporal components (Accuracy consistently above 60% across stimuli and

participants, and conditions; all p<.001). For full details and statistics see SI:

Perceptual validation of the spatiotemporal components for emotion signalling; and

Fig S10-11).

Substates reveal emotion diagnostic transitory patterns in facial signals

The second objective of this study was to identify and characterise facial expression

substates, potentially reflecting transition and sustain periods that may be

diagnostically relevant for emotion signalling (i.e., they may differ between happy,

angry and sad expressions and conditions). We identified three primary substates

through spatiotemporal clustering that segmented periods with robust local dynamics

within the underlying spatiotemporal components (see Methods: *Spatiotemporal*

clustering for substates analyses). Visual representation of the kinematic profiles of

each substate (Fig 5A-B) suggest the substates correspond to relaxed, transition,

and sustain periods for spatiotemporal components. The overall pattern of substates

is also consistent across participants, suggesting that this is not an artifact of

methodology or driven by specific inputs (see Fig 5 C-D).

385
Figure 5. Illustration of facial expression substate profiles.

A-B. Example of substate clusters (1 (green) = relaxed, 2 (peach) = transition; 3

(purple) = sustain). C-D show overall the speed distribution for *Expression only* and

Emotive speech expressions for all subjects.

Because the clustering algorithm returns only cluster partitions, it does not inherently

explain why these clusters emerge or how they may differentiate emotion (anger,

sadness and happy) and conditions (*Expression only vs Emotive speech*). To

address this, we quantify cluster (substate) patterns using two metrics: (1) speed,

and the input to the clustering analysis it provides a kinematic characterisation of

each substate which gives insights into the differences between substages; (2)

entropy, which provides a view of overall dynamics of substates (e.g., how they

change over time) (see Fig 5) – see also Methods. Similar measures have been

shown to capture diagnostic information about facial expression movement patterns

[8,11]. As this analysis is intended to characterise substates clusters rather than

classification per se, we used a linear mixed-effects model - LMM (see Methods) to

statistically assess differences in these metrics between emotion and conditions.

<u>Transition substate speeds differentiate emotional expressions</u>

An LMM used to predict speed from emotion (happy, angry, sad), condition

(*Expression only, Emotive speech*), and substate (relaxed, transition, sustain)

showed strong total explanatory power (conditional R2 = 0.6 (66%)) with the fixed

effects alone (marginal R2) accounting for 0.63 (63%) of the variance. All main

effects were significant. First, there was a small significant effect of emotion

($F(2,1990) = 12.89$, $p < .001$; $\eta_p^2 = 0.02$, 95% CI [0.009, 0.10]). Pairwise tests

showed that angry expressions were significantly slower than happy expressions

(angry < happy; beta = -0.028, SE = 0.008, t(1207) = -3.398, p = 0.002). Happy

expressions were faster than sad expressions (happy > sad; beta = 0.041, SE =

0.008, t(1207) = 4.92, p < 0.001). There were no significant differences in speed

between angry and sad expressions (beta = 0.012, SE = 0.008, t(1207) = 1.53,

p.corrected = 0.38). There was a significant main effect of condition (F(1, 1190) =

369.41, p < .001; η_p^2 = 0.24, 95% CI [0.20, 1.00]) with *Expression only* condition

moving faster than spoken (beta = 0.13, SE = 0.007, t(1207) = 19.08, p < .001).

Finally, there was a main effect of substate (F(2, 1190) = 687.90, p < .001; η_p^2 =

0.54, 95% CI [0.51, 1.00]) where sustain had higher speed than relaxed (beta = -

0.16, SE = 0.008, t(1207) = -19.52, p.corrected < .001); transition had higher speed

than relaxed (beta = -0.307, SE = 0.008, t(1207) = -36.80, p.corrected < .001) and

transition had higher speed than sustain (beta = -0.144, SE = 0.008, t(1207) = -

17.28, p.corrected < .001).

All two-way interactions were significant. First, there was a significant interaction

between emotion and substate (F(4, 1190) = 15.24, p < .001; η_p^2 = 0.05, 95% CI

[0.03, 1.00]). Pairwise tests showed that differences in speed between happy, angry

and sad emotional expressions were statistically significant for the transition substate

only (happy>anger, beta = -0.077 SE = 0.014, t(1207) = -5.36, p.corrected < .001;

sad< angry, beta = 0.053, SE = 0.014, t(1207) = 3.64, p.corrected < 0.001; sad<

happy, beta = 0.130, SE = 0.014, t(1207) = 9.005, p.corrected < .001). There were

no speed differences between emotions for the relaxed substate (angry vs. happy,

beta = -0.005, SE = 0.014, t(1207) = -0.348, p.corrected = 1.0; angry vs. sad, beta =

0.007, SE = 0.014, t(1207) = 0.498, p.corrected = 1.0; happy vs. sad, beta = 0.012,

SE = 0.014, t(1207) = 0.846, p.corrected = 1.0) nor the sustain substate (angry vs.

happy, beta = -0.003, SE = 0.014, t(1207) = -0.177, p.corrected = 1.0; angry vs. sad,

beta = -0.022, SE = 0.014, t(1207) = -1.501, p = 0.40, p.corrected; happy vs. sad,

beta = -0.01913, SE = 0.0144, t(1207) = -1.325, p.corrected = 0.5567). These results

suggest that transition substate kinematics (but not relaxation or sustainment

kinematics) carry diagnostic information about the emotional content of facial

expressions (Fig 6).

445
Figure 6: Summary of speed and entropy of substate patterns.
446
Substate cluster: 1-relaxed, 2-sustained, 3-transition. *Expression only* condition has
faster than *Emotive speech*, with transition substates being faster; Entropy mainly
differentiates *Expression only* and vs*. Emotive speech* condition, with the latter
exhibiting more complex patterns. Entropy also differed between happy and all other
expressions, with substate patterns being more predictable for former.

In addition, there was a significant two-way interaction between emotion and

condition (F(2) = 3.54, p = 0.029; η_p^2 = 0.006, 95% CI [3.15e-04, 1.00]). For the

Expression only condition, there were significant speed differences between two out

of the three emotion expression pairs: specifically, happy > angry (beta = -0.045, SE

= 0.012, t(1207) = -3.84, p.corrected < 0.001); happy > sad (beta = 0.06171, SE =

0.0118, t(1207) = 5.232, p.corrected < .001); and no differences between angry vs.

sad (beta = 0.016, SE = 0.012, t(1207) = 1.39, p.corrected = 0.492). In contrast, for

the *Emotive speech* condition, there were no significant differences in speed

between the emotional expressions (angry versus happy, beta = -0.011, SE = 0.012,

t(1207) = -0.97, p.corrected = 1.0; angry versus sad, beta = 0.009, SE = 0.012,

t(1207) = 0.77, p.corrected = 1.0; happy versus sad, beta = 0.020, SE = 0.012,

t(1207) = 1.73, p.corrected = 0.25).

Finally, there was a significant two-way interaction between condition and substate

(F(2) = 183.65, p < .001; η_p^2 = 0.24, 95% CI [0.20, 1.00]). For the *Expression only*

condition, there were significant differences in speed between all substates such that

sustain was faster than relaxed (relaxed < sustain, beta = -0.153, SE = 0.012,

t(1207) = -12.96, p.corrected < .001); transition was faster than relaxed (relaxed <

transition, beta = -0.439, SE = 0.012, t(1207) = -37.23, p.corrected < .001), and

faster than sustain (beta = -0.286, SE = 0.0118, t(1207) = -24.271, p.corrected <

.001). These patterns were overall similar for the *Emotive speech* condition where

relaxed periods were significantly slower than sustain (beta = -0.173, SE = 0.0118,

t(1207) = -14.647, p.corrected < .001) and transition periods (beta = -0.175, SE =

0.012, t(1207) = -14.82, p < .001). However, there was no statistically significant

difference between sustain and transition speeds (beta = -0.002, SE = 0.012, t(1207)

= -0.169, p.corrected = 1.00).

In sum, substate clusters are associated with differences in speed suggesting

periods of transition, relation and sustainment of expressions. Interestingly, these

micro-dynamic patterns differ between expressions and between *Expression only*

and *Emotive speech* signals, suggesting that how expressions are generated is

finely tuned both to the emotional content and to enhancing emotion cues during

speech.

<u>Substate dynamics differentiate emotion content</u>

Here we used entropy as a metric to statistically describe the dynamics of facial

expression substates in terms of how temporally structured/predictable they are ([37].

see Methods). High entropy equates with high complexity in substate patterns, and

low entropy with low complexity. Fig 5, for example, illustrates that substate

transitions are more complex (i.e., high entropy, less predictable) in the *Emotive*

speech condition where visual pattern differences between emotions are harder to

discern than in the *Expression only* condition (see Methods: *Spatiotemporal*

clustering for substates analyses).

The entropy model explained 67% of the variance (R^2 = 0.67). The fixed effects

alone (emotion, and expression condition) accounted for 57% of the variance

(marginal R^2 = 0.57). The main effect of emotion was statistically significant ($F_{(2,}$

$_{340)}$ = 12.27, $p < 0.001$; ηp^2 = 0.07, 95% CI [0.03, 1.00]). Pairwise contrasts

revealed that sad expressions had a significantly higher entropy (more unpredictable

substate sequences) compared to happy expressions (estimate = -0.027, SE =

0.0055, $t(344)$ = -4.897, $p < 0.0001$). There were no statistically significant

differences in entropy between angry and happy expressions (estimate = 0.011, SE

= 0.006, $t(344)$ = 1.996, p = 0.14), but there was a significant difference between

angry and sad expressions (estimate = -0.016, SE = 0.0055, $t(344)$ = -2.90, p =

0.012) – see Fig 6.

The largest effect was the main effect of condition ($F_{(1, 34)}$ = 429.10, $p < 0.001$; ηp^2

= 0.93, 95% CI [0.89, 1.00]), with the *Expression only* condition demonstrating

significantly lower entropy than *Emotive speech* expressions (β = -0.208, SE =

0.017, $t(35)$ = -12.594, $p < 0.001$). This suggests more complex movement dynamics

in the *Emotive speech* compared to the *Expression only* condition (see heatmaps in

Fig 5). There was no significant interaction between emotion and condition (F(2, 340)

= 0.03, p = 0.970; ηp² = 0.0002, 95% CI [0.00, 1.00]).

In summary, *Expression only* substates (relaxation, transitions, and sustainment of

expressions) are more temporally structured than those in *Emotive speech*

expressions, likely reflecting the increased dynamic complexity associated with

speech. Nonetheless, substates patterns differentiate expressions with sad

expressions having a more complex dynamics than happy and angry expressions.

To summarise, in addition to the low-dimensional spatiotemporal patterns that are

diagnostic of emotion and expression condition, we also identified three substates

reflecting periods of relaxation, transition, and sustainment of facial actions. These

substates are distinguished by their unique kinematic and dynamic (complexity)

profiles which provide encode local dynamics cues for differentiating emotional

expressions in *Expression only* and *Emotive speech* conditions.

Discussion

The current study explored how the underlying dynamics of facial movements relate

to their emotional signalling function. Building on a motor-theoretic framework we

employed a unique data-driven pipeline - integrating spatiotemporal dimensionality

reduction, timeseries feature extraction, classification and clustering; to identify

diagnostic patterns underlying emotion signalling in both *Expression only* and

Emotive speech. Our work contribute two key insights. First, we consistently

identified a small number of spatiotemporal components that reliably described the

time courses and covariance patterns of over a dozen action units. The identification

of these components suggests that emotion signalling through facial expressions

and speech-related cues is achieved by just a few fundamental dynamic patterns;

combinations of these dynamic patterns differentiate production and perception of

angry, happy and sad expressions. Second, we showed that these spatiotemporal

patterns exhibit substate-like structure, which reflect transient periods of relaxation,

transition, and sustainment of expressions. The profiles of these substates differed

by emotion category as well as between *Expression only* and *Emotive speech*

conditions, indicating they likely optimise the encoding of dynamic facial emotion

cues.

The low dimensionality of the spatiotemporal patterns of facial expressions, that we

have uncovered, is intriguing given the various combinations of AUs that can

contribute to the same expressions [3] as well as the variability in how people produce

expressions [38]. A low-dimensional spatiotemporal structure may reflect flexibility for

signalling, as a variety of expressions can be rapidly produced by relying on just a

few interchangeable dynamic patterns. Such flexibility is likely beneficial in face-to-

face interaction, where facial expressions may need to be quickly adapted according

to interaction demands [3,39]. Similarly, this flexibility might be necessary to accentuate

emotional information during speech which also impose dynamic constraints on

facial movements[4,40]. These findings are consistent with the observation of low-

dimensional spatiotemporal patterns facial [18,36] as well as other body movements

[17,19,21] which also have the capacity to signal emotion information [24,41,42]. Thus, it

suggests the potential for shared control mechanisms for social and non-social

aspects of movement including speech movements.

An important question concerns whether our results are representative of facial

expression signalling in general, or simply an outcome of the particular methodology

we employed. For example, it could be argued that we identified a small number of

spatiotemporal components because we asked participants to demonstrate relatively

simplistic expressions which can be signalled by activating just a few action units.

We argue that this is not the case because a) the *Emotive speech* condition was also

specifically designed to dissuade participants from relying on overly simple and

caricatured expressions and to introduce dynamic variability and b) compared to

previous work [18,36] we provide a substantially wider range of signallers to capture

wider idiosyncrasies and variability in facial dynamics. It could also be argued that

our results are simply a consequence of dimensionality reduction, as any set of data

can in theory be represented by a lower-dimensional structure. Yet, as we showed in

a series of validation and sensitivity analyses, the components learned carry

diagnostic information about emotions, which is robust to comparisons against

appropriate randomised dynamic patterns and generalises to unseen data. Thus, we

have not generated a "non-sense" low dimensional structure but rather a meaningful

way to represent diagnostic dynamic cues for emotion.

An intriguing question concerns why this low-dimensional spatiotemporal structure

emerges. One possibility is that receivers only attend to a reduced subset of

spatiotemporal patterns and so, correspondingly, signallers tend to only move a

reduced subset of features, or to move them in predictable ways. Our perceptual

validation indicates that there is overlap between spatiotemporal emotion

classification predictions, and human categorisation (see Fig S10-11SM). Moreover,

the robust prediction of participants' categorisations directly from these components

suggests that these low-dimensional patterns are at least in part, functionally and

perceptually relevant for signalling emotion. These results are consistent with

previous psychophysical approaches showing when observers are presented with

dozens of biologically plausible face movements, their perceptual representations

suggest that they only rely on a reduced subset of dynamic patterns [34]. Furthermore,

as human infants learn to produce and recognise facial expressions throughout a

protracted period of development [43], it is possible that humans learn to optimise

signals based on how these are optimally perceived and responded to, creating a

reciprocal dynamic interaction between these processes. Thus, the low-dimensional

organisation of facial expressions may reflect the optimisation of social signals

according to perceptual demands and these perceptual demands, themselves, may

be influenced by the low-dimensional organisation of facial expressions [44]. An

additional possibility is that there are savings (e.g., energy/computational, cognitive)

to be had from producing and interpreting facial expressions according to only a

small number of key informative spatiotemporal patterns.

The identification of substates in emotional facial dynamics also goes beyond

previous work on facial expression production. On the one hand substates likely

reflect the biomechanics features of articulating facial expressions, which inevitably

result in periods of relaxation, transition and sustainment of the underlying motor

units [45,46]. Yet, the fact that the patterns of these substates vary with different

emotions and expressive conditions, suggests that these local dynamics may

inherently provide a medium for optimal and efficient signalling of emotion as

discussed previously.

In real-life interaction, facial movements subserving verbal and nonverbal

expressions are often seamlessly integrated. Our findings in the *Emotive speech*

condition raise the possibility that verbal and nonverbal face dynamics when

signalling emotion can be integrated by differential modulation of spatiotemporal

components. For example, during speech, lip movement might covary with

articulation and sound production while simultaneously, the tightening of the lips and

lowering the eyebrows can accentuate the emotion signal. Indeed, the observation of

mostly part-based profiles (e.g., lower vs upper face AUs) in *Expression only*

conditions, contrasting the involvement of both mouth and non-mouth-related

components in *Emotive speech* expressions supports this assertion. Similarly, the

higher entropy observed in the substate patterns of *Emotive speech* may reflect the

increasing demands placed on facial dynamics by speech articulation and emotional

expression, resulting in more complex spatiotemporal patterns needed to

differentiate emotion. However, given that social signalling is inherently multimodal—

with tone of voice, vocal prosody, and facial expressions capable of conveying

emotion both independently and in combination— a future challenge is to understand

the extent to which these modalities act redundantly (conveying the same

information) or synergistically (combining to produce qualitatively richer meaning)

when signalling emotion [1,9,47].

There are three important caveats that warrant consideration. First, including more

detailed descriptors of face movements (including head motion see [36]) and speech-

optimised facial dynamics, may require additional dimensions to capture the full

complexity of dynamic emotion signalling. Similarly, different emotional expressions

(e.g., surprise, fear, disgust), the use of uncontrolled conversational contexts, and

inclusion of multimodal cues may also demand higher-dimensional representations.

Second, a different number of substates might be discovered using physiological

approaches, such as electromyography (EMG). Such approaches are sensitive to

subtle motor potentials and therefore may capture more substates including

preparatory or corrective movement impulses not apparent in FACS resolution.

Lastly, our approach focuses on exhaustively describing spatiotemporal components

and dynamic features, such as curvature patterns and entropy. However, it does not

isolate specific component, features (or groups of features) nor assess their

individual diagnostic value for encoding and decoding emotions. While such analysis

is beyond the scope of this study, it can be easily integrated with our approach in the

future.

Despite these caveats, our results and approach contributes new insights into

dynamic face-to-face social signalling. Spatiotemporal structure and substates might

reveal the mechanisms underlying differences in social signalling. This may provide

useful insight into clinical conditions such as autism and depression particularly in

exploring the potential role of atypical facial expression production in social

interaction difficulties [48,49]. These findings also have practical applications in fields

such as social robotics and human-computer interaction. A significant challenge in

these fields relates to endowing social agents (robots, digital agents) with convincing

and adaptable repertoires of social behaviour, including facial signalling [50].

Spatiotemporal components and substates underlying facial expression production

could provide actionable targets to enhance the design of flexible realistic and

expressive agents without the need to painstakingly craft each signal feature into the

architecture of these systems.

Conclusion

In conclusion, we revealed a low-dimensional spatiotemporal structure with distinct

substates that underpin emotional signalling and perception of *Expression only* and

Emotive speech facial dynamics. We also provide a data-driven pipeline to advance

the development of theoretical and methodological accounts of the structure and

function of expressive facial dynamics. This framework can be extended to other

modalities and has practical implications for modelling emotional signalling and

perception in human and machine systems.

Methods

Participants

43 volunteers from the university community (24 female; mean age = 26), took part

in the facial expression production study for course credit or monetary incentive. A

separate sample of 45 participants from the general population, naïve to the

production task, took part in a perceptual validation experiment (see SI Perceptual

Validation Study). All participants gave informed consent, and all procedures of the

study were approved by the School of Psychological Science Research Ethics

Committee at both the University of Bristol and University of Birmingham (ref 21918).

All procedures also adhered to the revised 2013 Declaration of Helsinki and relevant

national and international guidelines on research involving human subjects. The

dataset in the facial expression production study was collected as part of a larger

project investigating facial expression production kinematics and perception – see [11].

However, all the variables and analyses reported here are specific to this study and

not discussed in any previous papers. Furthermore, data from perceptual validation

study was specially collected and analysed for this paper and not reported

elsewhere.

Experimental procedure

Facial expression production task. Our protocol was based on our previous work [11]

which has shown to yield reliable emotional signals when considering both signal

dynamics and perceptual inference of emotion. In two separate sessions, across two

days, participants' facial movements were recorded during a facial expression

production task. Participants were asked to signal three emotions (anger, happiness,

and sadness) as they would naturally use their everyday interactions. This was done

in two counterbalanced conditions. An *Expression only* condition where participants

simply produced non-verbal facial expressions to signal each emotion, In the

Emotive speech condition where, they were asked to express the same emotions

while verbalising a "neutral" sentence ("Hi, my name is Jo, and I am a scientist").

This ensured that facial dynamic differences across emotions weren't necessarily

driven by the actual spoken content, but rather reflective of the target emotion

dynamics. The conditions are motivated by the fact that in social interaction, facial

expressions can be signalled both in isolation and embedded within *Emotive speech*,

meaning that facial movements might signal information relevant to emotion and

speech simultaneously, yet how speech and emotional cues are layered in facial

dynamics is achieved in unclear. We focused on those expressions because they

represent basic emotion signals which are often expressed in social interaction and

communication [51]. While we focus on three emotions only, the inclusion of a wider

range of participants, speech and non-speech conditions, and data across multiple

days provides richer representations of facial dynamics and variability compared to

previous work in this area, which is often restricted to a few signallers, emotions, and

conditions.

Facial movements were recorded with participants seated with their head at the

centre of a polystyrene frame to ensure central positioning towards the camera,

positioned 1 meter from a tripod-mounted video camcorder, sampling at 60Hz f/s

(Sony Handicap HDR-CX240E). The start and end points were signalled using an

audible beep, which allowed us to align the recordings of facial expressions. See the

schematic illustration in Fig 7. The expression only videos had consistent duration of

around 10 seconds, with some videos in the *Emotive speech* condition being slightly

shorter (see analytical approach section below for time matching and alignment

procedures).

A separate perceptual validation study was conducted online with participants naive

to the facial expression production task. Building on our validated protocol[11], we

used point-light recreations of the stimuli to isolate only spatiotemporal facial

expression dynamics and explore correspondence with human observers'' ratings

and categorisation of emotion signals (see SI- Perceptual Validation Study)

Analytical approach

Data processing. Facial expression production videos were processed using

OpenFace [52], an open-source suite for automated face-tracking, landmarking and

facial action unit detection based on the facial action coding system (FACS) [2]. We

focused on Action Units (AUs), which code for the observable presence and intensity

of basic face actions (e.g., blinking, mouth widening, eyebrow-raising) that can be

used to produce almost any facial expression movement. We estimated the temporal

activation weights for 18 AUs. Only videos with a tracking accuracy of over 90% and

with participant data across two sessions were used, resulting in a total of 532

videos with approximately 240 time points each. Based on visual inspection of the

movement profiles, we applied a moving average (window = 3 frames) to smooth out

the slight jitter inherent in face tracking and AU estimation, while preserving the

underlying trends and dynamic range. To ensure an equal temporal window for

spatiotemporal analyses, AU timeseries were reduced into 100-time bins for each

video. Binning was preferred over more computationally expensive alternatives such

as dynamic time-warping (DTW) for practicality since the overall timeseries duration

was very similar across videos, and visual comparisons between binning and DTW

tests on our data showed negligible differences – see Fig S13 in SI.

Figure 7. Schematic illustration of methodological and analytical approach.
1. illustrates the facial expression production task, where participants facial
expressions (angry, happy sad) were recorded in two conditions (expression only
and emotive speech). Expressions were perceptually validated in separate study and
sample. 2. OpenFace was used to quantify AU patterns over time and align motion
patterns. 3. summarises the procedure for the concatenation of AU timeseries and
the application of Non-Negative Matrix Factorization (NMF) to learn an underlying
low-dimensional spatiotemporal representation of the data. 4. The accuracy and
effectiveness of this lower-dimensional representation were validated through a
series of sensitivity and classification analysis. These relied on extracting timeseries

759 features (e.g. curvature, complexity) from spatiotemporal components and using
760 PCA to summarise them into a score per video, used for training the random forest
761 classification model validated in an unseen set. 5. Time series clustering was used
762 to identify substates or 'phases' in facial movement components.
763

Spatiotemporal analysis

Timeseries of AU weights for the full facial expression production task were analysed

using Non-Negative Matrix Factorization (NMF) [53]. NMF is a multivariate

dimensionality reduction method that decomposes a high-dimensional dataset into

two non-negative matrices that form a part-based representation of the data (i.e., the

original data is achieved by combining/adding components). The non-negativity

constraint is particularly well suited for representing movement and AU data, which is

typically positive, and the two-matrix part-based decomposition can intuitively

represent spatial vs time-varying aspects in the data – see Fig 7 (see also: [18,34,53]).

The NMF takes the concatenated AU timeseries as input, denoted by a matrix M,

which is a product of two low-dimensional matrices (T and S), T represents the

temporal weights (basis values for time bins), and S represents the spatial weights

(face action activation weights). The product of T and S matrices denoted by M'

represents an approximation of the full original matrix such that $M \sim M' = T * S$. The

algorithm works by initialising the values for T and S (e.g., with random values) and

using an iterative multiplicative update rule to sequentially update T and S by a factor

that minimises the approximation error (i.e., residuals). While the initialisation and

iterative nature of NMF means that the solution is non-deterministic (i.e., you can

learn multiple equally effective part-based representations), these update rules have

been shown to guarantee convergence (i.e., stability of the cost function) after a

relatively low number of iterations [54]. The optimal number of spatiotemporal

components (k) was assessed computationally by fitting a range of values (k = 2 to

6) and choosing a *k* that optimised various model fit and reconstruction metrics (e.g.,

residual sum of squares, silhouette for clustering cohesion, cophenetic coefficient,

see below). We also evaluated the final solution against NMF results on a

permutated dataset, using block-based time shuffling. This resulted in an appropriate

null dataset that destroyed the inherent spatiotemporal pattern in the data but

retained some temporal ordering. We then compared fit metrics between original and

permutated NMF (see also *Classification and clustering analysis*). We used the NMF

decomposition functions in the NMF package for R [55]. To visualise our NMF results

in an intuitive manner, we trained a custom model to predict aligned Facial Landmark

displacements (through Procrustes analysis) from AUs using partial least squares

regression. Note however that the AU to Landmark face model is not a perfect one to

one map between NMF results and visualisation, given the inherent many-to-one

relationship between facial landmarks and AUs [46].

For clarity of presentation and interpretation, we report the NMF components fitted

separately for the *Expression only* and *Emotive Speech conditions*. However,

sensitivity analyses confirm that these results are consistent with those obtained

from a joint analysis of both conditions, thereby showing reliability of the identified

spatiotemporal patterns, and that the results are not arbitrarily biased by the input

data.

Multivariate timeseries classification

We used a supervised classification approach to validate the diagnostic value of

spatiotemporal components for emotion expression. This involved five steps:

(1) Data splitting: We began by splitting the original pre-NMF data into training

(80%) and testing (20%) sets, ensuring that each set contained complete AU time

series for each video. This resulted in a matrix with approximately 183 videos x 100

time points and 18 AUs for train, and 45 x 100 x 18 for test set, where emotions were

all equally balanced (61 per category: angry, sad, and happy for train, and 15 each

for testing).

This split was performed before any further analyses, and all subsequent steps

maintained this separation ensuring further processing and model training was only

done on the training set and then applying results to the test set [56,57]. Hence any

mention of "training", always refers to operations on the respective training set.

(**2) NMF re-training and projection:** We then re-trained the NMF model using only

the training set data and projected the test set onto the trained NMF model space to

ensure consistency of components for classification.

(**3) Feature extraction:** Because standard classification approaches do not account

for inherent spatiotemporal structure of the NMF components, we opted for an

approach that represents the spatiotemporal structure via interpretable theoretic time

series features (e.g., curvature, complexity) in line with best practices and

established computational frameworks for multivariate timeseries features extraction

classification [58,59]. This led to a total of 40 features extracted per component.

However because it is impractical to detail the individual computation of every single

feature, for completeness we provide a full list of extracted features with a brief

description in the Supplementary Information (Table S5).

The focus on timeseries features is motivated by previous research showing the role

of timeseries features in capturing diagnostic dynamics for classification of facial

expressions and body movements [8,11,60,61].

Given the large dimensionality of the data, a Principal Component Analysis (PCA)

was used to summarise the timeseries features based on variance in the train set

while retaining a number of dimensions equal to the number of NMF components for

consistency. The test set features were then transformed using the PCA model fitted

on the training set features to be used in the next step. The matrix provided to PCA

mirrors the number of videos from the original NMF analysis and the total number of

extracted spatiotemporal features per component. Specifically, for the training sets

under each condition (*Expression only* and *Emotive speech*), the matrix was 183

videos by 114 features (38 features for each of the three spatiotemporal

components), while the test sets are 45 by 114. The component scores were used

as inputs for classification analysis in the next step. Conceptually, each principal

component (PC) captures the temporal dynamics inherent in the original NMF

components, effectively consolidating complex spatiotemporal patterns into a single

score per dimension. On average, the first three PCs account for between 34% and

40% of the variance in the data across both the *Expression only* and *Emotive speech*

conditions, in both the training and test sets.

849
(4) Classification training and testing. We then trained a classifier on

spatiotemporal component features derived from step 3 and applied to predict

emotion expression in the held-out test set. Specifically, we used a Random Forests

(RF) Classifier - a supervised statistical learning method that learns a discriminant

model between a set of input variables (e.g., spatiotemporal component features)

and a set of target classes (expressions). Note, that we achieved similar results with

different methods (e.g., Support Vector Machine, Linear Discriminant Analysis), thus

our results are not a function of the analytical approach. The Random Forests

Classifier has the advantage of being relatively more robust to overfitting and able to

capture non-linear relationships and therefore was preferred. We used cross-

validation during training, where multiple training sets are created, and the data not

included in the test set is used to test the accuracy and tune the model parameters.

Reliable classification on the test set would indicate that the underlying

spatiotemporal components (identified by the NMF analysis) carry diagnostic

information for differentiating expressions. Note that the theoretical chance level for

our three-way classification problem (i.e. happy, sad, and angry expressions) is

defined as 33%, and because the datasets are balanced, this is also the empirical

"no-information rate" or null rate. In addition, we derived significance tests for our

classification results using binomial tests to determine whether the model's accuracy

on the test set was significantly greater than what would be expected by random

guessing (by comparing it to the no information rate). These binomial p-values were

compared with permutation-based p-values, which were generated by comparing the

observed accuracy to the distribution of accuracies obtained from shuffling the labels

(expressions) in the test set (N = 1000). The negligible differences between the

binomial and permutation-based p-values for our dataset validated the robustness of

our results, so we primarily report the binomial p-values.

As an additional sensitivity test, we used Fisher's Exact Test to assess the statistical

significance of the confusion matrix, by comparing pairwise expression differentiation

with adjustments for multiple comparisons. The null hypothesis is that there is no

association between rows and columns, or in other words differences in cell values

(frequency) are due to chance. A low p-value in Fisher's exact test indicates

statistically significant differences between pairs, meaning the pattern in the

confusion matrix is unlikely to have occurred by chance.

While a handful of previous studies previous work has employed elements of our

proposed pipeline such as the dimensionality reduction of facial movement data

across entire datasets, our approach is unique in that it explicitly builds in the

generalisability and robustness of the spatiotemporal patterns we uncover.

Furthermore, the spatiotemporal classification pipeline enables us to directly link the

inherent dynamics (represented through the extracted features) to their diagnostic

value in differentiating emotions. We also used the same general approach above

(from step 4) to analyse the perceptual validation data, linking our spatiotemporal

components and human observers' perceptual emotion ratings, for the held-out test

set – see [62,63,64]. Full details are provided in the Supplementary Information -

Perceptual validation of the spatiotemporal components for emotion signalling.

Spatiotemporal clustering for substates analyses

We investigated whether reliable substates could be extracted from the

spatiotemporal patterns of *Expression only* and *Emotive speech* facial movements.

We considered substates as local intervals where the components exhibit salient

signatures that are consistent across expression timeseries. We operationalised this

as a segmentation of a multivariate timeseries into finer temporal segments with

arbitrary lengths. To do this we first derived speed and displacement for

spatiotemporal components (from step 2 above - NMF re-training and projection**)**, as

these features are sensitive to segments local characteristics of other body

movements (e.g., swing and stance signatures in walking, fixation and saccades in

eye movements) [19,28,29,65]. These were computed using the standard approach from

the kinematic literature. Speed was computed as the first derivative of the time

series, approximated by the bin‑wise difference between consecutive values and

normalised by the corresponding time interval. Displacement was derived as the

differencing of the timeseries over time relative to the starting values (baseline).

Second, we applied spatiotemporal clustering using the *dtwclust* package in R, using

the component speed and displacement metrics as inputs. This was motivated by

the fact that, unlike other movements with well-established kinematic profiles, we

have no *a priori* knowledge regarding the characteristics of facial expression

substates. Given the computational complexity of DTW, we first tested cluster sizes

on a smaller subset of *Expression only and Emotive speech* data. We used

visualisations (e.g. Fig 5) which suggested two to three interpretable segments

described transition and stability phases in spatiotemporal components of facial

expressions in line with the hypothesised patterns of transition, sustainment and

relaxation of AUS. Note that because the substate clustering inputs are based on

spatiotemporal components representing AUs—and because AUs are equally valid

descriptors of facial behaviour in both non-verbal expression and emotive speech,

substate analysis are equally valid for both conditions. Therefore, any differences in

substate patterns are reflective of condition-specific nuances, rather than a bias to

specific condition.

Because the clustering results are mostly descriptive generating cluster labels for

partitioning the input data, it does not inherently provide a statistical characterisation

for why these clusters emerge. To facilitate intuitive interpretation of clusters, we

therefore visualise the pattern of clusters and the input data (Fig 5). For example, it

became apparent that clusters had distinct speed signatures but also apparent

sequences that are more prominent in *Expression only* and more dynamic in

Emotive speech conditions. To statistically assess these patterns, and explore how

they differentiate emotion and conditions, we computed two metrics: (1) speed within

the substate and (2) entropy; both which have been shown to capture diagnostic

information about facial expression movement patterns [8,11]. Specifically given that

speed contributes to the clustering as an input, statistically comparing speed gives

direct insights into how the clusters were generated (see Fig 5). Entropy, is an

information-theoretic measure of complexity, is directly related the dynamics of state

transitions (or sequences) within a system [37]. In this context, entropy provides a

suitable summary of the dynamics of substates in a single statistic, describing how

complex or unpredictable the sequence of these substates is (e.g., how much

information about the current substate can predict the next substate). This statistic

aimed at quantifying, for example, the apparent differences in the temporal patterns

of substates between expressions and conditions (see Fig 5). We computed entropy

using the transition entropy function (for state change entropy) from the *GrpString*

package for R [66] but for simplicity we refer it as entropy. To improve interpretability,

entropy was normalised by dividing it by the maximum theoretical entropy for a

system with the same number of substates.

Both speed and entropy measures were computed for each individual expression

and analysed using a mixed-effects model to test the effect of emotion (happy,

angry, sad), condition (*Expression only*, *Emotive speech*), and substate (relaxed,

transition, sustain) as fixed effects and subject (face id) as a random effect. Entropy

was log transformed to correct for non-normal residuals. We used a linear mixed

models as opposed to the classification pipeline described earlier given the primary

aim to characterise substates and statistically assess differences between emotion

and conditions on the basis of substate patterns. Additionally, the more complex and

nested structure of the substate data makes classification overly complex to

structure and present. Linear mixed models were fitted using the lme4 package for R

[67] with inferential tests derived from lmerTest[68].

Data availability statement

Supporting data is available in the Open Science Framework (OSF):

https://osf.io/3nzk7/?view_only=db7d9467423f42b794385e549b6aa96a

All code for pre-processing and models is available at https://github.com/hcuve/spat-

tmp-emo-faces

Acknowledgments

We would like to thank Professor Rachael Jack for her insights during the initial

discussions on facial signalling dynamics and dimensionality reduction.

We would also like to thank Katherine Lane and Tahniyyat Bokhari, for their

assistance with data collection for a portion of the study.

Author Contributions (CRediT)

HCC, Conceptualisation, Data Curation, Formal Analysis, Funding Acquisition,

Investigation, Methodology, Software, Validation, Visualisation, Writing – Original

Draft Preparation, Writing – Review & Editing

SSC, Methodology, Validation, Writing – Review & Editing, Resources

JC, Conceptualization, Funding Acquisition, Methodology, Writing – Review &

Editing, Resources

Funding Statement

HCJC was funded by an Experimental Psychology Society Postdoctoral Fellowship

and a Wellcome Trust Accelerator Award.

986 This project was also partly funded by a grant from the European Union's Horizon

987 2020 Research and Innovation Programme under ERC-2017-STG Grant Agreement

988 No 757583.

References

1.   Jack, R. E. & Schyns, P. G. The human face as a dynamic tool for social

communication. *Curr. Biol.* **25**, R621-34 (2015).

2.   Ekman, P. & Friesen, W. V. Facial action coding system. *Environmental*

Psychology & Nonverbal (1978).

3.   Krumhuber, E. G., Skora, L. I., Hill, H. C. H. & Lander, K. The role of facial

movements in emotion recognition. *Nat. Rev. Psychol.* (2023)

doi:10.1038/s44159-023-00172-1.

4.   Scherer, K. R. & Ellgring, H. Multimodal expression of emotion: affect

programs or componential appraisal patterns? *Emotion* **7**, 158–171 (2007).

5.   Ghazanfar, A. A. & Takahashi, D. Y. Facial expressions and the evolution of

the speech rhythm. *J. Cogn. Neurosci.* **26**, 1196–1207 (2014).

6.   Chandrasekaran, C., Trubanova, A., Stillittano, S., Caplier, A. & Ghazanfar,

A. A. The natural statistics of audiovisual speech. *PLoS Comput. Biol.* **5**,

e1000436 (2009).

7.   Jack, R. E. & Schyns, P. G. Toward a social psychophysics of face

communication. *Annu. Rev. Psychol.* **68**, 269–297 (2017).

8.   Jack, R. E., Garrod, O. G. B. & Schyns, P. G. Dynamic facial expressions of

emotion transmit an evolving hierarchy of signals over time. *Curr. Biol.* **24**,

187–192 (2014).

9.   Liu, M. *et al.* Facial expressions elicit multiplexed perceptions of emotion
categories and dimensions. *Curr. Biol.* **32**, 200-209.e6 (2022).

10.   Gill, D., Garrod, O. G. B., Jack, R. E. & Schyns, P. G. Facial movements
strategically camouflage involuntary social signals of face morphology.
Psychol. Sci. **25**, 1079–1086 (2014).

11.   Sowden, S., Schuster, B. A., Keating, C. T., Fraser, D. S. & Cook, J. L. The
role of movement kinematics in facial emotion expression production and
recognition. *Emotion* **21**, 1041–1061 (2021).

12.   Burrows, A. M. The facial expression musculature in primates and its
evolutionary significance. *Bioessays* **30**, 212–225 (2008).

13.   Sherwood, C. C. Comparative anatomy of the facial motor nucleus in
mammals, with an analysis of neuron numbers in primates. *Anat. Rec. A*
Discov. Mol. Cell. Evol. Biol. **287**, 1067–1079 (2005).

14.   Todorov, E. Optimality principles in sensorimotor control. *Nat. Neurosci.* **7**,
907–915 (2004).

15.   Pang, R., Lansdell, B. J. & Fairhall, A. L. Dimensionality reduction in
neuroscience. *Curr. Biol.* **26**, R656-60 (2016).

16.   Latash, M. L., Scholz, J. P. & Schöner, G. Toward a new theory of motor
synergies. *Motor Control* **11**, 276–308 (2007).

17.   Chiovetto, E., Salatiello, A., d'Avella, A. & Giese, M. A. Toward a unifying

framework for the modeling and identification of motor primitives. *Front.*

Comput. Neurosci. **16**, 926345 (2022).

18.   Chiovetto, E., Curio, C., Endres, D. & Giese, M. Perceptual integration of

kinematic components in the recognition of emotional facial expressions. *J.*

Vis. **18**, 13 (2018).

19.   Labaune, O., Deroche, T., Teulier, C. & Berret, B. Vigor of reaching, walking,

and gazing movements: on the consistency of interindividual differences. *J.*

Neurophysiol. **123**, 234–242 (2020).

20.   Ivanenko, Y. P., Poppele, R. E. & Lacquaniti, F. Five basic muscle activation

patterns account for muscle activity during human locomotion. *J Physiol*

(Lond) **556**, 267–282 (2004).

21.   Chiovetto, E., Berret, B. & Pozzo, T. Tri-dimensional and triphasic muscle

organization of whole-body pointing movements. *Neuroscience* **170**, 1223–

1238 (2010).

22.   Zangrossi, A., Cona, G., Celli, M., Zorzi, M. & Corbetta, M. Visual exploration

dynamics are low-dimensional and driven by intrinsic factors. *Commun. Biol.*

4, 1100 (2021).

23.   Ramanarayanan, V., Goldstein, L. & Narayanan, S. S. Spatio-temporal

articulatory movement primitives during speech production: extraction,

interpretation, and validation. *J. Acoust. Soc. Am.* **134**, 1378–1394 (2013).

24. Barliya, A., Omlor, L., Giese, M. A., Berthoz, A. & Flash, T. Expression of

emotion in the kinematics of locomotion. *Exp. Brain Res.* **225**, 159–176

(2013).

25. Montepare, J. M., Goldstein, S. B. & Clausen, A. The identification of

emotions from gait information. *J. Nonverbal Behav.* **11**, 33–42 (1987).

26. Dalmaijer, E. S., Lee, A., Leiter, R., Brown, Z. & Armstrong, T. Forever yuck:

Oculomotor avoidance of disgusting stimuli resists habituation. *J. Exp.*

Psychol. Gen. **150**, 1598–1611 (2021).

27. Mackevicius, E. L. *et al.* Unsupervised discovery of temporal sequences in

high-dimensional datasets, with applications to neuroscience. *eLife* **8**, (2019).

28. Rucci, M. & Poletti, M. Control and Functions of Fixational Eye Movements.

Annu. Rev. Vis. Sci. **1**, 499–518 (2015).

29. Torricelli, F. *et al.* Motor invariants in action execution and perception. *Phys.*

Life Rev. **44**, 13–47 (2023).

30. Krumhuber, E. G. & Scherer, K. R. Affect bursts: dynamic patterns of facial

expression. *Emotion* **11**, 825–841 (2011).

31. Schmidt, K. L., Cohn, J. F. & Tian, Y. Signal characteristics of spontaneous

facial expressions: automatic movement in solitary and social smiles. *Biol.*

Psychol. **65**, 49–66 (2003).

32. Aghabozorgi, S., Seyed Shirkhorshidi, A. & Ying Wah, T. Time-series

clustering – A decade review. *Inf. Syst.* **53**, 16–38 (2015).

33. Aggarwal, C. C. An introduction to cluster analysis. in *Data clustering:*

algorithms and applications (eds. Aggarwal, C. C. & Reddy, C. K.) 1–28

(Chapman and Hall/CRC, 2018). doi:10.1201/9781315373515-1.

34. Delis, I. *et al.* Space-by-time manifold representation of dynamic facial

expressions for emotion categorization. *J. Vis.* **16**, 14 (2016).

35. Namba, S., Nakamura, K. & Watanabe, K. The spatio-temporal features of

perceived-as-genuine and deliberate expressions. *PLoS ONE* **17**, e0271047

(2022).

36. Watson, D. M., Brown, B. B. & Johnston, A. A data-driven characterisation of

natural facial expressions when giving good and bad news. *PLoS Comput.*

Biol. **16**, e1008335 (2020).

37. Shannon, C. E. & Weaver, W. *The mathematical theory of communication.*

(books.google.com, 1998).

38. Le Mau, T. *et al.* Professional actors demonstrate variability, not stereotypical

expressions, when portraying emotional states in photographs. *Nat. Commun.*

12, 5037 (2021).

39. Parkinson, B. Social Functions. in *Heart to heart: how your emotions affect*

other people 215–240 (Cambridge University Press, 2019).

doi:10.1017/9781108696234.006.

40. *Multichannel integrations of nonverbal behavior.* (Psychology Press, 2014).

doi:10.4324/9781315802305.

41.   Gobel, M. S., Kim, H. S. & Richardson, D. C. The dual function of social gaze.

1093   *Cognition* **136**, 359–364 (2015).

1094   42.   Wolpert, D. M., Doya, K. & Kawato, M. A unifying computational framework

1095   for motor control and social interaction. *Philos. Trans. R. Soc. Lond. B Biol.*

1096   *Sci.* **358**, 593–602 (2003).

1097   43.   Bell, S. M. & Ainsworth, M. D. Infant crying and maternal responsiveness.

1098   *Child Dev.* **43**, 1171–1190 (1972).

1099   44.   Rowe, C. Receiver psychology and the evolution of multicomponent signals.

1100   *Anim. Behav.* **58**, 921–931 (1999).

1101   45.   Duchenne de Boulogne, G. B. *The mechanism of human facial expression.*

1102   (Cambridge University Press, 1990). doi:10.1017/CBO9780511752841.

1103   46.   Mavadati, S. M., Mahoor, M. H., Bartlett, K., Trinh, P. & Cohn, J. F. DISFA: A

1104   spontaneous facial action intensity database. *IEEE Trans. Affect. Comput.* **4**,

1105   151–160 (2013).

1106   47.   Hebets, E. A. *et al.* A systems approach to animal communication. *Proc. Biol.*

1107   *Sci.* **283**, 20152889 (2016).

1108   48.   Brewer, R. *et al.* Can neurotypical individuals read autistic facial expressions?

1109   atypical production of emotional facial expressions in autism spectrum

1110   disorders. *Autism Res.* **9**, 262–271 (2016).

1111   49.   Haque, A., Fei-Fei, L., Guo, M. & Miner, A. S. Measuring Depression

1112   Symptom Severity from Spoken Language and 3D Facial Expressions.

Machine Learning for Health (ML4H) Workshop at NeurIPS 2018, Montréal, Canada (2018).

50. Rawal, N. & Stock-Homburg, R. M. Facial emotion expressions in human–robot interaction: A survey. *Int. J. Soc. Robot.* **14**, 1583–1604 (2022).

51. Calvo, M. G., Gutiérrez-García, A., Fernández-Martín, A. & Nummenmaa, L. Recognition of Facial Expressions of Emotion is Related to their Frequency in Everyday Life. *J. Nonverbal Behav.* **38**, 549–567 (2014).

52. Baltrušaitis, T. & Robinson, P. Openface: an open source facial behavior analysis toolkit. *2016 IEEE Winter* (2016).

53. Lee, D. D. & Seung, H. S. Learning the parts of objects by non-negative matrix factorization. *Nature* **401**, 788–791 (1999).

54. Fu, X., Huang, K., Sidiropoulos, N. D. & Ma, W.-K. Nonnegative matrix factorization for signal and data analytics: identifiability, algorithms, and applications. *IEEE Signal Process. Mag.* **36**, 59–80 (2019).

55. Gaujoux, R. & Seoighe, C. A flexible R package for nonnegative matrix factorization. *BMC Bioinformatics* **11**, 367 (2010).

56. Kriegeskorte, N., Simmons, W. K., Bellgowan, P. S. F. & Baker, C. I. Circular analysis in systems neuroscience: the dangers of double dipping. *Nat. Neurosci.* **12**, 535–540 (2009).

1132   57.   Varoquaux, G. & Colliot, O. Evaluating machine learning models and their

1133   diagnostic value. in *Machine learning for brain disorders* (ed. Colliot, O.)

1134   (Humana, 2023). doi:10.1007/978-1-0716-3195-9_20.

1135   58.   Baldán, F. J. & Benítez, J. M. Multivariate times series classification through

1136   an interpretable representation. *Inf Sci (Ny)* **569**, 596–614 (2021).

1137   59.   Fulcher, B. D., Little, M. A. & Jones, N. S. Highly comparative time-series

1138   analysis: the empirical structure of time series and their methods. *J. R. Soc.*

1139   *Interface* **10**, 20130048 (2013).

1140   60.   Dobs, K. *et al.* Quantifying human sensitivity to spatio-temporal information in

1141   dynamic faces. *Vision Res.* **100**, 78–87 (2014).

1142   61.   Furl, N. *et al.* Face space representations of movement. *Neuroimage* **212**,

1143   116676 (2020).

1144   62.   Schrimpf, M. *et al.* Brain-Score: Which Artificial Neural Network for Object

1145   Recognition is most Brain-Like? *BioRxiv* (2018) doi:10.1101/407007.

1146   63.   Daube, C. *et al.* Grounding deep neural network predictions of human

1147   categorization behavior in understandable functional features: The case of

1148   face identity. *Patterns (N Y)* **2**, 100348 (2021).

1149   64.   Schyns, P. G., Snoek, L. & Daube, C. Degrees of algorithmic equivalence

1150   between the brain and its DNN models. *Trends Cogn Sci (Regul Ed)* **26**,

1151   1090–1102 (2022).

65. Miranda, J. G. V. *et al.* Complex Upper-Limb Movements Are Generated by

Combining Motor Primitives that Scale with the Movement Size. *Sci. Rep.* **8**,

12918 (2018).

66. Hooge, I. & Camps, G. Scan path entropy and arrow plots: capturing

scanning behavior of multiple observers. *Front. Psychol.* **4**, 996 (2013).

67. Bates, D., Mächler, M., Bolker, B. & Walker, S. Fitting linear mixed-effects

models using lme4. *arXiv preprint arXiv:1406.5823* (2014).

68. Kuznetsova, A., Brockhoff, P. B. & Christensen, R. H. B. lmertest package:

tests in linear mixed effects models. *J. Stat. Softw.* **82**, 1–26 (2017).