# Dual-format attentional template during preparation in human visual cortex

Yilin Chen[1], Taosheng Liu[2], Ke Jia[3,4,5*], Jan Theeuwes[6], Mengyuan Gong[1*]

[1] Department of Psychology and Behavioral Sciences, Zhejiang University, Hangzhou, Zhejiang, China

[2] Department of Psychology, Michigan State University, East Lansing, Michigan, USA

[3] Liangzhu Laboratory, MOE Frontier Science Center for Brain Science and Brain-machine Integration, State Key Laboratory of Brain-machine Intelligence, Zhejiang University, Hangzhou, Zhejiang, China

[4] Department of Neurobiology, Affiliated Mental Health Center & Hangzhou Seventh People's Hospital, Zhejiang University School of Medicine, Hangzhou, Zhejiang, China

[5] NHC and CAMS Key Laboratory of Medical Neurobiology, Zhejiang University, Hangzhou, Zhejiang, China

[6] Department of Experimental and Applied Psychology, Vrije Universiteit Amsterdam, Amsterdam, the Netherlands

**\*Corresponding Author**

Dr. Mengyuan Gong

Department of Psychology and Behavioral Sciences, Zhejiang University

gongmy426@zju.edu.cn

Dr. Ke Jia

MOE Frontier Science Center for Brain Science and Brain-machine Integration, Zhejiang University

kjia@zju.edu.cn

**Abstract**

Goal-directed attention relies on forming internal templates of key information relevant for guiding

behavior, particularly when preparing for upcoming sensory inputs. However, evidence on how these

attentional templates is represented during preparation remains controversial. Here, we combine

functional magnetic resonance imaging (fMRI) with an orientation cueing task to isolate preparatory

activity from stimulus-evoked responses. Using multivariate pattern analysis, we found decodable

information of the to-be-attended orientation during preparation; yet preparatory activity patterns were

different from those evoked when actual orientations were perceived. When perturbing the neural activity

by means of a visual impulse ('pinging' technique), the preparatory activity patterns in visual cortex

resembled those associated with perceiving these orientations. The observed differential patterns with and

without the impulse perturbation suggest a predominantly non-sensory format and a latent, sensory-like

format of representation during preparation. Furthermore, the emergence of the sensory-like template

coincided with enhanced information connectivity between V1 and frontoparietal areas and was

associated with improved behavioral performance. This dual-format mechanism suggests that during

preparation the brain encodes more detailed template information beyond its immediate use, potentially

providing advantages for adaptive attentional control. Consistent with recent theories of non-veridical,

'good-enough' attentional template for initial guidance, our findings established a neural basis for

implementing two representational formats in different functional states during preparation: a

predominantly non-sensory format for guidance and a latent sensory-like format for prospective stimulus

processing.

**Keywords**

Attentional selection, representational format, fMRI, decoding, visual cortex, impulse perturbation

## Introduction

To address the challenge of processing the overwhelming amount of sensory inputs from the external environment, the brain must allocate attentional resources to prioritize the processing of task-relevant information. Importantly, humans can proactively prepare for stimulus selection before the arrival of sensory inputs (Summerfield & De Lange, 2014) . For example, when preparing to hail a taxi on the road, we tend to form a mental representation of the defining features of a taxi (e.g., yellow with a car-like shape). This ability relies on the formation of attentional templates — mental representations of the target — to accelerate stimulus selection and resolve perceptual competition by enhancing task-relevant information and suppressing irrelevant information (Desimone & Duncan, 1995; Kastner et al., 1999). While most attentional models posit that attentional templates during stimulus processing reflect veridical representations of the target (Jigo et al., 2018; Malcolm & Henderson, 2009), the nature of the template during preparation remains less understood.

A classical view suggests that attentional template during preparation may reflect veridical target features, analogous to the representational format during stimulus selection. However, evidence supporting this account has been mixed. For example, while some previous fMRI studies have demonstrated that preparatory activity contains target information similar to the sensory responses to the corresponding targets (Kok et al., 2014; Lewis-Peacock et al., 2015; Stokes et al., 2009), more recent electrophysiological studies suggest that, if anything, this template is engaged only shortly before the expected arrival of sensory input rather than being continuously active (Grubert & Eimer, 2018; Myers et al., 2015). Notably, in some cases the template is even largely undetectable during preparation (Wen et al., 2019). Alternatively, an emerging view suggests a non-veridical template suffices for guiding attention during preparation, where precise processing of stimuli may be unnecessary at this stage. Support for this notion comes from the identification of attentional signals during preparation that differ from neural signals observed during perceptual target processing (Gong et al., 2022). Recent theories of visual search also propose a non-veridical, "good-enough" template for early attentional guidance (Wolfe, 2021; Yu et

al., 2023). However, it remains unclear whether a "good-enough" template for search also applies to

preparatory attention.

The notion that there may be a sensory and non-sensory attentional template might not be as far-

fetched as it seems. Indeed, it is feasible that during preparation, following stimulus presentation,

attentional signals undergo a transformation from a non-sensory to a sensory-like template. Previous

behavioral (Hamblin-Frohman & Becker, 2021; Yu et al., 2022) and neural studies (Gong et al., 2022;

Jigo et al., 2018; Wen et al., 2019) are generally consistent with this idea of coarse-to-fine transitions,

suggesting that during preparation, a sensory-like template may not be initially necessary but only

becomes relevant when the stimulus needs to be identified. However, if and in what way the brain

coordinates these non-sensory and sensory-like templates remains unclear. Here, we propose that during

preparation, a sensory-like template may be stored in a latent (e.g., activity-silent) state concurrently with

a non-sensory template. This idea parallels recent findings from working memory studies, which suggest

that information intended for proactive use is kept in activity-silent traces to support future behavior

(Stokes, 2015; Wolff et al., 2015, 2017). The present study seeks to determine the possibility of the latent,

sensory-like template during the preparation for discriminating an upcoming stimulus.

To test these hypotheses, participants engaged in a cuing task in which they prepared during an

extended period of time for the presentation of a compound stimulus grating containing the cued

orientation and a distractor orientation. In addition, in order to be able to construct the sensory-format

representations (leftward and rightward orientation), single orientations were presented during the

perception task. Critically, we used a "pinging" technique combined with multivariate decoding methods,

which has been shown to be effective in retrieving information from latent brain states (Duncan et al.,

2023; Wolff et al., 2015, 2017; Zhang & Luo, 2023). In the standard condition (*No-Ping session*), the

preparation period was devoid of visual impulses. During preparation, the neural activity patterns in

visual and frontoparietal areas could discriminate between the orientations that participants were

preparing for. Yet, neural activity patterns evoked by the perception of orientations were distinct from

those evoked during preparation for upcoming orientations, suggesting a predominantly non-sensory

template during preparation. By contrast, when we presented a high-contrast, task-irrelevant impulse

stimulus during preparation (*Ping session*), neural activity patterns evoked by the perception of

orientations were similar to those activated by the preparation for orientations in the visual cortex,

suggesting the existence of a latent, sensory-like format of representation during preparatory attention.

Furthermore, the emergence of sensory-like template coincided with enhanced information connectivity

between V1 and frontoparietal areas and was associated with improved behavioral performance. Our

findings provide evidence for the co-existence of two formats of attentional templates (non-sensory vs.

sensory-like) during preparation, as well as a novel neural mechanism for their maintenance in different

functional states (active vs. latent). We propose that this dual-format representation may serve to increase

flexibility of attentional control.

**Results**

**Behavioral performance during the attention tasks**

In an orientation cueing task, participants were shown a color cue indicating the reference orientation (45°

or 135°) to attend to during preparation period (a delay of 5.5 s or 7.5 s) with or without the impulse

perturbation (Fig 1A). This was followed by the presentation of a compound stimulus consisting of two

oriented gratings. During the stimulus selection period (after the gratings appeared), participants were

tasked with discriminating a small angular offset of the cued grating from the cued reference orientation.

The angular offset was individually thresholded before the scanning sessions (mean offset = 2.50° in the

No-Ping session and 2.52° in the Ping session) without significant difference between two sessions

(independent t-test: $t(19) = 0.085$, $p = 0.932$, Cohen's d = -0.027). Participants' discrimination

performance showed no significant difference between two attended orientations in either the No-Ping

(paired t-test: $t(19) = 1.439$, p = 0.166, Cohen's d = -0.321) or the Ping session (paired t-test: $t(19) =$

0.494, p = 0.627, Cohen's d = 0.122; Fig 1C). A two-way mixed ANOVA (attended orientation × session)

revealed neither significant main effects (attended orientation: $F(1,38) = 0.392$, $p = 0.535$, $\eta_p^2 = 0.01$;

session: $F(1,38) = 0.001$, $p = 0.970$, $\eta_p^2 < 0.001$) nor interaction effect ($F(1,38) = 1.811$, $p = 0.186$, $\eta_p^2 =$

0.045). Bayesian analyses provided moderate evidence to support the null hypothesis ($BF_{excl} > 3.633$),

suggesting comparable performance levels between two sessions and two attended orientations.

**Fig 1. Experiment procedure and behavioral performance.** (A) Attention tasks. Note that only long-delay trials

are shown. A small proportion of short-delay trials (20%, with a delay of 1.5 s or 3.5 s) were included to create

temporal uncertainty and encourage consistent active preparation during the delay. Both component gratings were

flickering at 10 Hz between white and black, so that luminance could not confound either the task strategy (e.g.,

attending to luminance) or neural measures. The inset shows two sets of color-orientation mapping, which were

reversed halfway through the experiment to minimize the impact of cue-induced sensory difference on neural

activity. (B) Perception task. Similar to the attention task, the single-orientation grating also flickered at 10 Hz between white and black. (C) Behavioral accuracy in the attention tasks in the No-Ping and Ping sessions. Each dot represents one subject's data. Error bars denote standard error of the means (SEM).

**A default, non-sensory representation of attentional template during preparation**

The first aim of this study was to determine whether attentional signals during preparation are encoded in a sensory-like or non-sensory format. To address this, we first examined whether, in the attention task during the No-Ping condition, the distributed neural pattern contained feature-specific information. We trained and tested separate classifiers to predict the attended orientation during the preparation and stimulus selection periods (Fig 2A, "Attention decoding"; see Materials and Methods for details). This analysis was performed for each of the four regions along the visual hierarchy, including primary visual cortex (V1), extrastriate visual cortex (EVC), intraparietal sulcus (IPS) and prefrontal cortex (PFC). The average decoding accuracies for both preparation and stimulus selection periods were significantly above chance level in each region (Permutation analyses: $ps < 0.004$ across regions, Fig 2B), indicating that the brain maintained reliable information about the attended feature both before and after the onset of the compound grating. Next, we examined whether the preparatory activity reflected a sensory-like format of attentional template (Fig 2A, "Cross-task generalization", see Materials and Methods). We trained a classifier using data from the perception task (leftward vs. rightward orientation; Fig 1B) and tested its performance on data from the preparation period in the attention task (attend leftward vs. attend rightward). However, this cross-task generalization analysis yielded no significant effects ($ps > 0.132$ across the regions). In contrast, we observed above-chance generalization from the perception task to the stimulus selection period ($ps < 0.001$ across regions, Fig 2C), confirming previous findings of the sensory-like attentional template following stimulus presentation (Gong et al., 2022; Jigo et al., 2018; Wen et al., 2019).

**Fig 2. MVPA for the No-Ping session and Ping session.** (A) Schematic illustration of the decoding of attended orientation (attend leftward vs. attend rightward) in the attention task (left panel) and the cross-task generalization analysis from perception task to the attention task (right panel). The four regions are shown on a representative right hemisphere as colored areas: V1 is marked in red, EVC in yellow, IPS in cyan and PFC in purple. (B) Decoding accuracy during preparation and stimulus selection periods across regions in the No-Ping and (D) Ping session. (C) Cross-task generalization performance from the perception task to the preparatory periods and the stimulus selection periods across regions in the No-Ping and (E) Ping session. The dashed lines represent the theoretical chance level (0.5). Each dot represents one subject's data. Error bars denote SEM.

Before drawing conclusions based on the lack of generalization from the perception task to

preparatory attention, we considered two alternative explanations to rule out potential confounds. First,

the robust attention decoding during preparation ruled out the possibility that participants were not

actively engaged in the task during preparation (Fig 2B, unfilled bars). Second, the generalizable effect

from the perception task to the stimulus selection period across regions (Fig 2B, filled bars) argues

against the possibility of low statistical power. Overall, these findings suggest that the preparatory

attention and sensory processing of features have distinct formats, presumably reflecting a non-sensory

format of representation during the preparation. These results replicate those of a previous fMRI study

using motion stimuli with a similar design(Gong et al., 2022). Furthermore, consistent with previous

studies(Gong et al., 2022; Jigo et al., 2018), univariate analysis did not reveal any reliable difference in

overall BOLD responses between attention orientations (Supplementary Information and S1 Fig).

**A latent, sensory-like attentional template during preparation revealed by visual impulse**

The second aim of our study was to examine whether a latent, sensory-like template exists during

preparation. While this precise template may not be necessary for preparation, it is relevant for

subsequent target selection and discrimination (i.e., select the cued grating from the compound stimulus

and discriminate a small angular offset between the cued grating and the reference orientation). To test

this hypothesis, we perturbed the neural activity by means of a visual impulse during the preparation

period in the Ping session (Fig 1A, right panel). Using the same analyses as those performed in the No-

Ping session, robust attentional signals were observed during both preparation and stimulus selection

periods (Permutation analyses: $ps < 0.001$ across regions; Fig 2D). Importantly, the cross-task

generalization analyses indicated that the visual impulse led to above-chance generalization from the

perception task to preparation period (Fig 2E, unfilled bars) in V1 and EVC ($ps < 0.001$), but not in IPS

and PFC ($ps > 0.584$), along with generalizable effects from the perception task to the stimulus selection

periods ($ps < 0.036$ across regions; Fig 2E; filled bars). These results suggest that different brain areas are

involved in coding for sensory-like templates. To further evaluate whether the cross-task generalization

from the perception task to the preparation period was statistically different with and without visual

impulse, we conducted a two-way mixed ANOVA (session × region) on the generalization performance.

The analysis revealed main effects of region ($F(3,114) = 5.220$, $p = 0.002$, $\eta_p^2 = 0.121$), session ($F(1,38) =$

$7.321$, $p = 0.010$, $\eta_p^2 = 0.162$), and importantly, a significant interaction effect ($F(3,114) = 3.964$, $p =$

$0.010$, $\eta_p^2 = 0.094$), supporting the observation that the visual impulse led to significantly increased

decoding accuracy in V1 (independent t-test: $t(38) = 3.145$, $p = 0.003$; Cohen's d $= 0.995$) and EVC

(independent t-test: $t(38) = 2.153$, $p = 0.038$, Cohen's d $= 0.681$), but not in the frontoparietal regions ($ps >$

$0.374$). This dissociable result between the two sessions further supports the activation of a latent,

sensory-like template by the visual impulse during preparatory attention.

To further solidify this conclusion, following analyses were used to examine several alternative

possibilities. First, we examined whether the impulse-driven generalization resulted from stronger feature

information in the Ping compared to No-Ping session during the perception task. This was not the case, as

evidenced by comparable levels of decodable orientation information between the Ping and No-Ping

sessions (see Supplementary Information and S2 Fig). Next, we asked whether the increased

generalization was due to generally stronger attentional signals in the Ping session during the attention

tasks. This was not the case, as the two-way mixed ANOVAs (session × region) on attention decoding

accuracy revealed neither a significant main effect of session nor an interaction effect during both the

preparation ($ps > 0.519$; $BF_{excl} > 3.247$) and stimulus selection periods ($ps > 0.336$; $BF_{excl} > 3.297$),

suggesting comparable amount of attentional information between the two sessions. Therefore, the

findings of impulse-driven sensory-like template in the visual cortex during preparation cannot be

explained by general differences between two sessions.

**Matching preparatory attention to sensory template: impact on neural representation and**

**behavior**

The reported decoding accuracy from the cross-task generalization analysis quantifies the degree to which

differences in neural activity pattern between two conditions are shared across attention and perception

tasks. However, it does not directly measure how similar the neural patterns are when attending to an orientation compared to perceiving that orientation. Unlike decoding accuracies, Mahalanobis distance provides a continuous measure for characterizing representational geometries between different conditions (Mahalanobis, 1936). To further corroborate our findings of the impulse-driven sensory-like template, we calculated the Mahalanobis distance between each attention condition during preparation and each perception condition (see Materials and Methods). If the patterns of activity reflect a sensory-like template, we would expect greater pattern similarity (smaller distance) between "attend leftward" and "perceive leftward" than between "attend leftward" and "perceive rightward", and vice versa for the "attend rightward" conditions (see Fig 3A for a schematic of the four pair-wise distance measures), leading to an interaction between attended and perceived orientation conditions.

We used a two-way repeated-measures ANOVA (attended orientation × perceived orientation) on the Mahalanobis distance, separately for each session and each region. During the preparatory period in the No-Ping session, no significant interaction effects were observed across regions ($ps > 0.443$; Fig 3B). In contrast, the same analyses applied to the Ping session revealed significant interaction effects in visual areas (V1: $F(1,19) = 9.335$, $p = 0.007$, $\eta_p^2 = 0.329$; EVC: $F(1,19) = 8.563$, $p = 0.009$, $\eta_p^2 = 0.311$; Fig 3C), but not for frontoparietal regions ($ps > 0.213$). This cross-region difference is consistent with the function of sensory areas in encoding precise neural representations for basic visual features. To directly compare whether the attentional modulation on Mahalanobis distance was statistically different with and without the visual impulse, we used a three-way mixed ANOVA (session × attended orientation × perceived orientation). The analysis revealed a significant three-way interaction in V1 ($F(1,38) = 5.00$, $p = 0.031$, $\eta_p^2 = 0.116$), suggesting that by "pinging" the brain, the attentional template during preparation became more similar to the perception of corresponding orientation. We also calculated the Mahalanobis distance between neural patterns evoked by the superimposed gratings during the stimulus selection period and each condition in the perception task, finding similar results (see Supplementary Information and S3 Fig). This result was expected, as feature-based attention is known to selectively enhance the representation of task-relevant features while filtering out task-irrelevant ones.

**Fig 3. Orientation-selective attentional modulations on neural pattern distances during preparation.** (A) Schematic illustration of the representational distance (mean Mahalanobis distances) between each of the attention conditions and each of the perception conditions. Colored arrows indicate measures of the pair-wise Mahalanobis distance. The right panel shows two attention trials (red indicates attend-to-leftward and green indicates attend-to-rightward) to the distribution of each perception condition (shown in a cloud of light-colored dots). (B) Mahalanobis

distance between preparatory attention condition and perceived orientation condition in the No-Ping and (C) Ping sessions. (D) Behavioral performance (as indexed by reaction time) for "strong modulation" (high AMI) trials and "weak modulation" (low AMI) trials, sorted by V1 preparatory activity in the No-Ping and (E) Ping sessions. Each dot represents one subject's data. Error bars denote SEM. * $p < 0.05$, ** $p < 0.01$.

The continuous nature of the Mahalanobis distance also made it possible to further investigate potential neural-behavioral correlations. We examined whether activating a sensory-like template during preparation would benefit subsequent orientation processing. In particular, we calculated attentional modulation indices (AMIs) based on trialwise Mahalanobis distance in V1. The index was calculated as follows: $AMI = (D_{different} - D_{same})/(D_{different} + D_{same})$, where $D_{same}$ and $D_{different}$ are the measured distance (D) in the Same (e.g., attend and perceive the same orientation) and Different (e.g., attend and perceive different orientations) orientation condition, respectively (see Methods and Materials). We then sorted the AMI values in a descending order and selected the top-ranked 25% of trials (i.e., 36 trials) and bottom-ranked 25% of trials to represent "strong modulation" and "weak modulation" trials, respectively and calculated reaction time and accuracy for each group of trials. The analysis revealed a faster response in the "strong modulation" than "weak modulation" trials in Ping session (paired t-test: t(19) = -2.746, $p = 0.013$, Cohen's d = -0.614; Fig 3E), but not in the No-Ping session (paired t-test: t(19) = -1.487, $p = 0.154$, Cohen's d = -0.332; Fig 3D). These effects were not observed for accuracy (*ps* = 0.163). These results suggest that the impulse-driven sensory-like template in primary visual cortex is functionally relevant to subsequent attentional selection, providing evidence for the prospective use of sensory-like template in this task. In addition, we did not observe such behavioral differences in analogous analyses using data from the stimulus selection period in either session (*ps* > 0.230), which might due to the potential dilution by strong stimulus-evoked responses during the stimulus selection period.

**Activating sensory-like template strengthens the informational connectivity between sensory and frontoparietal areas**

Selective attention is generally believed to rely on coordinated network activity (Corbetta & Shulman,

2002). In particular, studies have shown that functional connectivity between sensory and frontoparietal

areas was modulated by attentional control (Bressler et al., 2008; Rosenberg et al., 2020). Given that the

impulse-driven sensory-like template facilitated behavior, we reasoned that it may also enhance network

communication. Thus, we examined informational connectivity measures to explore how the impulse

altered network function during the attention task. We used a method that allows inference based on

multivoxel pattern information rather than univariate BOLD response (Jia et al., 2020; Ng et al., 2021).

For each ROI, we calculated the cross-validated Mahalanobis distance from each attention trial (from one

left-out run) to the distribution of each attended orientation (all trials from remaining runs) during

preparation (see Methods and Materials). To quantify the degree of attentional modulation during

preparation, we calculated the AMI based on trialwise Mahalanobis distance and generated a time course

of AMI values across trials. Pearson correlation was used to estimate the covariation between each pair of

ROIs, the resulting correlation coefficients were transformed using Fisher's z-transform for statistical

inference (Fig 4A). The analysis revealed numerically higher levels of connectivity in Ping than in No-

Ping session, this impulse-driven increase in connectivity reached statistical significance in two pairs (Fig

4B): V1-IPS (independent t-test: t(38) = 2.566, $p$ = 0.014; Cohen's d = 0.812) and V1-PFC (independent

t-tests: t(38) = 3.158, $p$ = 0.003; Cohen's d = 0.999). The enhanced functional connectivity between V1

and frontoparietal areas driven by the impulse may potentially facilitate information flow among areas to

improve attentional control. Additionally, the same analysis of AMI based on cross-validated

Mahalanobis distance during the stimulus selection period showed no significant differences in

information connectivity between No-Ping and Ping sessions ($ps$ > 0.224; Supplementary Information and

S4A Fig). The lack of changes in long-range connectivity during stimulus selection period may be

attributed to a general rise in connectivity caused by strong sensory inputs in this period, which could

have attenuated any potential impacts of visual impulses. Furthermore, connectivity analysis based on

mean BOLD response over time did not reveal any significant changes in inter-cortical connections

between the two sessions ($ps$ > 0.136; S4B Fig), suggesting that the impulse-driven increased information

connectivity between V1 and higher-order areas was unlikely contributed by the overall changes of

BOLD response.

**Fig 4. Information connectivity analysis.** (A) Schematic illustration of the procedure for the information

connectivity analysis in the space of two hypothetical voxels. For each region, we calculated the Mahalanobis

distance of the attention trial (from one left-out run) from two attention distributions (all trials from remaining runs).

Red and green dots indicate activity patterns from two trials (right panel). The brain image shows an example pair of

intercortical information connectivity between V1 and PFC. The time series (lower-left panel) consisted of

attentional modulation index (AMI) based on the Mahalanobis distance. (B) Between-region information

connectivity in the No-Ping session and Ping session (left panel), and differences in connectivity between the two

sessions (right panel). $* p < 0.05$, $** p < 0.01$.

**Discussion**

While there is ample evidence that the brain can maintain an attentional template of an upcoming target before sensory information is presented (Desimone & Duncan, 1995; Kastner et al., 1999; Summerfield & De Lange, 2014), its representational format remains unclear. To address this, we used an orientation cueing paradigm with separated preparation and stimulus selection periods and applied MVPA to decode neural activity patterns associated with feature-specific attentional information of the upcoming target. The analyses showed robust attentional information both before and after the presentation of the compound grating, suggesting sustained maintenance of attentional templates throughout a trial. Importantly, while the decoders trained on the perception of single orientations could not generalize to preparation until the stimulus selection period (*No-Ping session*), perturbing the brain with a visual impulse resulted in generalizable activity patterns during preparation in the visual cortex (*Ping session*). These results suggest a predominantly non-sensory format of representation, with a sensory-like template in a latent state during feature-based preparation in the visual cortex. Furthermore, impulse-driven sensory-like template was accompanied by enhanced information connectivity between V1 and frontoparietal areas, as well as enhanced orientation-specific neural modulations of neural distances in the visual areas that predicted levels of behavioral performance. The differences between the Ping and No-Ping sessions could not be attributed to differences in sensory information from the perception task, overall strength of preparatory attention, or differences in eye position (S5 Fig). Therefore, our findings suggest dual-format neural representations (non-sensory vs. sensory-like) operating in different functional states (active vs. latent). This mechanism may give rise to flexible attentional control, allowing effective transition from coarse to fine attentional templates at various processing stages (initial guidance vs. precise discrimination).

Recent advances in theories of visual search differentiated between the "guiding template" and "target template" based on measures of behavioral performance and eye movements (Wolfe, 2021; Yu et al., 2023). According to these theories, early attentional guidance typically depends on a non-veridical

template that includes only the most diagnostic information, whereas later, target-match processes utilize

more precise codes to optimize decision accuracy (Kerzel, 2019; Scolari et al., 2012; Yu et al., 2022). Our

study reveals a parallel coding mechanism in the context of feature-based attention, expanding upon these

theoretical notions in three key aspects. First, we provide neural evidence for a default, predominantly

non-sensory template during preparation, indicating that the concept of a "guiding template", as proposed

by visual search theories (Wolfe, 2021; Yu et al., 2023), also applies to preparatory attention in a non-

search context. This highlights a shared functional role of a non-veridical attentional template in early

guidance across different scenarios. Second, despite the theoretical notion that the brain maintains a more

veridical template with detailed target information than is typically utilized to form the guiding template

(Wolfe, 2021; Yu et al., 2023), direct evidence supporting this hypothesis is currently lacking. We

provide evidence for this notion and propose a plausible neural implementation for preserving a more

veridical, sensory-like template in the latent state. A natural question is why the sensory-like template

remains latent during preparation. We note that our task requires both coarse and fine featural information.

Specifically, during preparation, the brain needs to establish a guiding template that aids in distinguishing

the target from the distinct distractor; hence a coarse, non-veridical template suffices. During stimulus

selection, the fine discrimination task (reporting the tilted direction of a small angular offset) necessitates

the representation of a precise template. It is thus both advantageous and efficient to maintain a sensory-

like template in a latent state during preparation, which could facilitate the processing of sensory stimulus

in the future. This idea is analogous to recent development in working memory research, which suggests

that mnemonic information intended for future use often remains in a latent, activity-silent state (Stokes et

al., 2020; Wolff et al., 2015, 2017).  Finally, information connectivity between visual and higher-order

frontoparietal regions was enhanced by visual impulse during preparation, suggesting improved

information flow across the relevant areas allowing enhanced attentional control. This enhanced

attentional control may contribute to refined sensory representations of target in early visual cortex,

facilitating transitions from a non-sensory to sensory-like format template. Future studies may adopt

layer-specific fMRI to infer the direction of this improved information flow (Jia et al., 2023) and explore

the relationship between long-range connections and the utilization of different versions of target
templates.

Our study reveals a latent, sensory-like attentional template that extends beyond previous findings
of latent working memory representations (Wolff et al., 2015, 2017). Unlike previous studies, which used
the "pinging technique" to differentiate active and latent representations of *different* items (e.g., attended
vs. unattended memory item), our study demonstrated the active and latent representations of a single
item in different formats (i.e., non-sensory vs. sensory-like). Moreover, while the "pinging technique" did
not evoke sensory-like neural patterns during memory retention (Wolff et al., 2017), we identified
sensory-like format of representations during preparatory attention. A potential neural mechanism for this
sensory-like template is via an "activity-silent" mechanism through short-term changes in synaptic
weights, originally proposed for working memory storage (Mongillo et al., 2008). However, whether
pinging identifies an activity-silent mechanism is currently debated (Barbosa et al., 2021; Schneegans &
Bays, 2017).   An alternative possibility is that the visual impulse amplified a subtle but active
representation of the sensory template during preparation. Distinguishing between these two accounts
likely requires neurophysiological measurements, which are beyond the scope of the current study.
Nevertheless, our findings provide evidence for dual-format attentional template including a latent,
sensory template and offer insights into how the brain encodes information beyond immediate uses to
support adaptive behavior.

The non-generalizable activity patterns from perception to preparatory attention, in the absence of
visual impulse, suggests a default, predominantly non-sensory template during preparation. This finding
is largely consistent with electrophysiological studies (Myers et al., 2015; Wen et al., 2019) and our prior
fMRI work on preparatory attention to motion directions (Gong et al., 2022), but differs from some
previous neuroimaging studies that demonstrated sensory-like templates during preparation (Kok et al.,
2014; Peelen & Kastner, 2011; Stokes et al., 2009). One potential account for these discrepancies is that
those studies used cue-only trials where the target was expected but not actually presented, contrasting
with our task where the target was shown on every trial with temporally separated preparation and

stimulus selection periods. This seemingly subtle difference may significantly impact the formats of the

neural representations. Because cue-only trials increased the likelihood of target appearance at the

subsequent time point, sensory template may be activated due to modulations of temporal expectations

(Grubert & Eimer, 2018). This explanation is consistent with theories suggesting differential influences of

expectation and attention on neural activity: expectation reflects visual interpretations of stimuli due to

sensory uncertainty, whereas attention is guided based on the task relevance of sensory information

(Rungratsameetaweemana & Serences, 2019; Summerfield & Egner, 2009, 2016). Our finding of a

predominantly non-sensory format may indicate an optimized coding strategy employed by the brain to

effectively and robustly represent information for future use. This aligns with the proposed role of

attention in modulating sensory representations to encode only currently relevant information at a

minimal cost.

We acknowledge that our findings cannot pinpoint the exact format of this non-sensory template.

Previous behavioral studies on visual search have suggested a candidate mechanism for target-defining

features. For instance, when searching for simple features, such as an orientation or a color (Kong et al.,

2017; Wolfe et al., 1992), participants tend to use categorical attributes (e.g., steep vs. shallow; left-tilted

vs. right-tilted) to enhance search efficiency. The categorical template is particularly advantageous when

features are consistent and predictable (Hout et al., 2017). In our task, the angular relations between the

target and distractor orientation were defined by categorical attributes (e.g., left-tilted vs. right-tilted) and

remained consistent across trials, making a categorical template feasible during preparatory attention.

Furthermore, employing a categorical template allows for greater tolerance of stimulus variability, which

is also useful in our study where the actual target orientation varied around the reference orientations

across trials. Future studies are needed to address the nature of the non-sensory template during

preparation as well as task parameters that might modulate them.

In summary, the current study suggests that there are two formats of attentional templates each

having a distinct functional state: a default, non-sensory format and a latent, sensory-like format. This

dual-format representation aligns with theories on the dual-function of attentional template for different

task goals (Hout & Goldinger, 2015; Yu et al., 2023). The current findings provide a plausible neural

implementation for these theories by demonstrating different formats in different functional states. This

mechanism likely reflects an optimized coding scheme that effectively balances processing efforts and

demands, particularly well-suited for flexible control and transitions from coarse to fine task demands in

visually guided behavior.

## **Materials and Methods**

### **Participants**

Twenty individuals participated in the No-Ping session (11 females, mean age = 22.9) and twenty

individuals participated in the Ping session (14 females, mean age = 23.7). Among them, 14 participants

took part in both sessions, while 12 of them took part in only one session. The sample size was

comparable to previous studies using similar attention tasks (Baldauf & Desimone, 2014; Gong & Liu,

2020a; 2020b; Guo et al., 2012; Jigo et al., 2018; Liu & Hou, 2013). Because our primary interest is the

generalization from the perception task to attention task, we used the minimal effect size of decoding

accuracy across regions (one-sample t-tests: $d$ = 0.868) from our previous study with a similar design

(Gong et al., 2022), and used G*Power (Version 3.1) (Faul et al., 2007)to confirm that this sample size is

sufficient to detect a cross-task generalization effect with a power greater than 95% (a = 0.05). All

participants were right-handed and had a normal or corrected-to-normal vision. Participants provided

written informed consent according to the study protocol approved by the Institutional Review Board at

Zhejiang University (2020-06-001). They were paid ¥200 (~$27.4) for their participation in each session.

### **Stimuli and Apparatus**

Stimuli were generated using Psychtoolbox (Brainard, 1997; Kleiner et al., 2007) implemented in

MATLAB. The stimuli were presented on an LCD monitor (resolution: 1920 × 1080, refresh rate: 60 Hz)

during behavioral training, at a viewing distance of 90 cm in a dark room. During the fMRI scans, stimuli

were projected to a screen via a MR-compatible LCD projector (PT-011, Jiexin Technology Co., Ltd.,

Shenzhen, China) with the same resolution and refresh rate as the LCD monitor during behavioral training.

Participants viewed the screen via an angled mirror attached to the head coil at a viewing distance of 115

cm. Angular stimulus size was the same across behavioral and fMRI sessions.

The orientation stimuli were square-wave gratings (1.3 cycles per deg, duty cycle: 10%) in a circular

aperture (inner radius: 1.5°; outer radius: 6°). The gratings flashed on a gray background at 10 Hz,

alternating between black and white. There were two types of stimuli: two overlapping gratings orientated

leftward (~135°) and rightward (~45°), or a single grating with one of the two orientations (~135° or

~45°). Here, we refer to the 45° and 135° orientations as the reference orientations. The impulse stimulus

was a high-contrast, white (at the maximum projector output level) circular disk that covered the same

area as the orientation stimulus (radius: 6°).

**Experimental Procedures and Tasks**

Each participant completed at least two fMRI sessions on different days. One session was used for

defining ROIs (see Definition of Regions of Interests), while the remaining sessions were used for the

main experiment (see Attention task and Perception task). Before the scanning sessions, participants were

trained to familiarize with the tasks in a separate behavioral session. The procedures and tasks were

similar to our previous work (Jigo et al., 2018; Gong et al., 2022).

*Attention task.* We used a cueing paradigm (Fig 1A). Each trial began with a color cue (red or

green) for 0.5 s to indicate the reference orientation of the upcoming target (leftward vs. rightward

orientation). In the No-Ping session, the cue was followed by a blank display during the preparation

period; in the Ping session, a task-irrelevant, high-luminance visual impulse ("ping", 0.1 s) occurred at

either 0.5 s (for short delays of 1.5 s and 3.5 s) or 2.5 s (for long delays of 5.5 s and 7.5 s) after the onset

of the cue display. The orders of these sessions were counterbalanced across participants who completed

both. Following the preparatory period, two superimposed gratings were then shown for 1 s. The target

grating was shown with a small angular offset with respect to the cued reference orientation, whereas the

distractor grating was shown in the uncued reference orientation (e.g., if rightward orientation was cued,

the rightward grating was shown in 45°± d and the leftward grating was shown in 135°). Note that the

angular offset was determined individually based on the threshold obtained during the training session (at

least 3 blocks, 30 trials/block), using a staircase procedure (Best Parameter Estimation by Sequential

Testing, Best PEST), as implemented in the Palamedes Toolbox (Prins & Kingdom, 2009). Participants

used a keypad to report whether the attended orientation was more leftward or rightward relative to the

reference orientation. Each trial was separated by an inter-trial interval of 3 s to 7 s (2 s per step). Trial-

by-trial feedback ("correct" or "incorrect") was provided in the training session but not during scanning.

Instead, the percentage of correct responses was provided at the end of each run in the scanning session to

avoid the impact of trial-level feedback on neural activity.

To prevent the cue-related sensory difference from contributing to neural activity, we reversed the

mapping between colors and orientations halfway through the experiment (e.g., red indicated "attend

leftward orientation" and green indicated "attend rightward orientation" in the first half of the runs, and

vice versa for the second half of the runs), with the order counterbalanced across subjects. The mapping

of colors and orientations was reversed only once in the middle of the experiment to prevent

misremembering of the color-orientation associations. To reduce temporal expectancy over a fixed period,

the preparatory period (i.e., cue-to-stimulus interval) varied from 1.5 s to 7.5 s with different probabilities

(10% for 1.5 s or 3.5 s each, 40% for 5.5 s or 7.5 s each). The long-delay trials (5.5 s or 7.5 s) were

selected for subsequent analyses, as they allow the separation of the preparatory activity from the grating-

evoked response during fMRI scanning. The short-delay trials were included to encourage a sustained

maintenance of attention throughout the entire preparation period.

*Perception task.* On each trial of the perception task (Fig 1B), a single grating was shown for 1 s,

followed by an inter-trial interval between 3 s to 7 s. To equate the sensory inputs between attention and

perception tasks, the orientation was shifted away from the reference orientation by the same angular

offset as that used in the attention task with each individual participant's own threshold. Participants

performed the same orientation discrimination task by comparing the single orientation to the reference

orientation. We provided the percentage of correct responses at the end of each run as feedback.

**Eye Tracking and Analysis**

To evaluate the stability of visual fixation, we used Eyelink Portable Duo system (SR Research, Ontario,

Canada) to monitor each observer's eye position during the training session at a sampling rate of 500 Hz.

One participant's data was not used due to the unstable recording of the eye. The data were then analyzed

using custom Matlab code.

To examine whether participants adopted a space-based strategy during the preparatory period in

the attention task, such as directing their gaze leftward in attend leftward trials, and vice versa for the

attend rightward trials, we analyzed the participants' eye positions recorded during the training session.

Horizontal and vertical eye positions were analyzed separately. Paired t-tests were performed to compare

horizontal and vertical eye positions between two attention conditions. A two-way mixed ANOVA (2

sessions $\times$ 2 attended orientations) was applied to the horizontal and vertical positions, respectively.

**fMRI Data Acquisition**

Imaging was performed on a Siemens 3T scanner (MAGNETOM Prisma, Siemens Healthcare, Erlangen,

Germany) using a 20-channel coil at Zhejiang University (Hangzhou, China). For each participant, we

acquired high-resolution T1-weighted anatomical images (field of view, 240 $\times$ 240 mm, 208 sagittal

slices; 0.9 mm$^3$ resolution), T2*-weighted echo-planar functional images consisting of 46 slices (TR, 2 s;

TE, 34 ms; flip angle, 50°; matrix size, 80 $\times$ 80; in-plane resolution, 3 $\times$ 3 mm; slice thickness, 3 mm,

interleaved, no gap) and a 2D T1-weighted anatomical image (0.8 $\times$ 0.8 $\times$ 3 mm) for aligning functional

data to high-resolution anatomical data.

**fMRI Data Preprocessing**

Data analyses were performed using mrTools (Gardner et al., 2018) and custom code in Matlab. For each

run, functional data were preprocessed with head motion correction, linear detrending and temporal high

pass filtering at 0.01 Hz. Data were converted to percentage signal change by dividing the time course of

each voxel by its mean signals in each run. We concatenated the 6 runs of the attention task and the 3 runs

of the perception task separately for further analysis. One of the attention runs in one subject was

excluded due to low accurate performance (<50%).

**Definition of Regions of Interests (ROI)**

**Visual and parietal ROIs.** Following previous work (Jigo et al., 2018; Gong et al., 2020b; Gong et al., 2022), for each observer, we ran a separate retinotopic mapping session to obtain ROIs in occipital and parietal areas. Observers viewed four runs of rotating wedges (i.e., clockwise and counterclockwise) and two runs of rings (i.e., expanding and contracting) to map the polar angle and radial components, respectively (DeYoe et al., 1996; Engel, 1997; Sereno et al., 1995). Borders between areas were defined as the phase reversals in a polar angle map of the visual field. Phase maps were visualized on computationally flattened representations of the cortical surface, which were generated from the high-resolution anatomical image using FreeSurfer (http://surfer.nmr.mgh.harvard.edu) and custom Matlab code.

To help identify the topographic areas in parietal areas, we ran 2 runs of memory-guided saccade task modeled after previous studies (Konen & Kastner, 2008; Schluppeck et al., 2006; Sereno et al., 2001). Observers fixated at the screen center while a peripheral (~10° radius) target dot was flashed for 500 ms. The flashed target was quickly masked by a ring of 100 distractor dots randomly positioned within an annulus (8.5° – 10.5°). The mask remained on screen for 3 s, after which participants were instructed to make a saccade to the memorized target position, then immediately saccade back to the central fixation. The position of the peripheral target shifted around the annulus from trial to trial in either a clockwise or counterclockwise order. Data from the memory-guided saccade task were analyzed using the same phase encoding method as the wedge and ring data. Therefore, the following regions of interest (ROIs) in each hemisphere were identified after the completion of this session: V1, V2, V3, V3A/B, V4, V7/IPS0, IPS1 to IPS4.

**Frontal ROIs.** Following previous work (Jigo et al., 2018; Gong et al., 2020b; Gong et al., 2022), we used a deconvolution approach by fitting each voxel's time series from the attention task with a general linear model (GLM) to determine the event-related activations in the brain (see Supplementary Materials: Deconvolution). For each voxel, we computed the goodness of fit measure ($r^2$ value), which indicates the amount of variance explained by the deconvolution model (Gardner et al., 2018). The $r^2$

value represents the degree to which the voxel's time series is correlated with the task events, regardless

of any differential responses among conditions. Based on the task-related activation (as indexed by $r^2$

value) and anatomical criteria, we defined two frontal areas in each hemisphere that were active during

the attention task: one is located superior to the precentral sulcus and near the superior frontal sulcus (FEF)

and the other is located towards the inferior precentral sulcus, close to the junction with the inferior

frontal sulcus (IFJ).

**Groups of Region.** To characterize the patterns of neural response across cortical hierarchy and

streamline data presentation, we grouped results from the nine areas into four groups based on functional

and anatomical considerations: primary visual cortex (V1); extrastriate visual cortex (EVC), consisting of

V2, V3, V3ab and V4; IPS, consisting of IPS0 to IPS4; prefrontal cortex (PFC), consisting of FEF and

IFJ. Individual areas within each group exhibited qualitatively similar results.

**Multivoxel Pattern Analysis (MVPA)**

**Decoding of attended orientation.** To test if multivariate patterns of activity represent

information of the attended orientation, separate MVPA analyses were applied on the activity patterns for

the preparation and stimulus selection periods. Following previous work (Jigo et al., 2018; Gong et al.,

2020b; Gong et al., 2022), for this analysis, we extracted fMRI signals from raw time series in the long

delay trials with correct behavioral responses (~72 trials per attention condition); short delay trials were

excluded as they could not provide enough data points to measure preparatory activity. We then obtained

averaged BOLD response in a 2 s window for each voxel and each trial in a given ROI, separately for

preparatory activity (4 to 6 s after the onset of the cue) and stimulus-evoked activity (4 to 6 s after the

onset of the gratings). The response amplitudes across two attention conditions in each ROI were further

z-normalized, separately for the preparation and stimulus-related activity. These normalized single-trial

BOLD responses were used for the MVPA. We trained a classifier using the Fisher linear discriminant

(FLD) analysis to discriminate between two attended orientations (leftward vs. rightward) and tested its

performance with a leave-one-run-out cross-validation scheme. This process was repeated until each run

was tested once and the decoding accuracy (i.e., the proportion of correctly classified trials) was averaged

across the cross-validation folds. The statistical significance of decoding accuracy was evaluated by

comparing it to the chance level obtained from a permutation test (see Permutation test). To assess if the

decoding accuracy differed between No-Ping and Ping experiments, we performed two-way mixed

ANOVAs (2 sessions $\times$ 4 regions) on the decoding accuracy.

**Cross-task generalization from the perception task to attention task.** Following previous

work (Jigo et al., 2018; Gong et al., 2022), to test whether the neural patterns in the preparatory and

stimulus selection periods from the attention task reflected sensory processing of isolated features, we

trained an FLD classifier using the normalized BOLD responses from the perception task (4 to 6 s after

the trial onset) to discriminate leftward vs. rightward orientation. Then, we tested this classifier on the

normalized response from the independent runs of attention task to discriminate between attend leftward

vs. attend rightward orientations, separately for preparation and stimulus selection periods. The

significance of decoding accuracy was compared to the chance level obtained from a permutation test (see

Permutation test). To assess if the generalization performance differed between No-Ping and Ping

sessions, we performed two-way mixed ANOVAs (2 sessions $\times$ 4 regions) on the decoding accuracy.

**Neural distance between attended and perceived orientations.** The decoding accuracy from

the cross-task generalization test reflects a discretized readout of the pattern similarity between different

conditions. However, employing continuous similarity measures, such as Mahalanobis distance

(Mahalanobis, 1936), could be more reliable compared to decoding accuracy (Walther et al., 2016).

Therefore, we calculated the Mahalanobis distance to quantify the pattern similarity between two attended

orientations and two perceived orientations. For each participant and each ROI, we have M points (i.e., M

trials for each attended orientation) in the N-dimensional space (N = 100, number of voxels). For each

data point in the attended orientation condition, we computed its distance to each of the orientation

distributions (from the perception task). Averaged distance values were then calculated for each

combination of attended orientation and perceived orientation pairs. A sensory-like hypothesis would

predict smaller distance between the distribution of the attended orientation (e.g., attend leftward) and the

distribution of corresponding orientation (e.g., perceive leftward) compared to the alternative orientation

(e.g., perceive rightward). Two-way repeated-measures ANOVA (2 attended orientations $\times$ 2 perceived

orientations) was applied on the Mahalanobis distance, separately for each region and each session.

**Neural-behavioral relationships.** We tested if the representation format during preparatory

attention was associated with subsequent behavior. For each trial, we calculated the Mahalanobis distance

between the attention conditions (attend leftward and attend rightward) and the perceived orientations

(leftward and rightward orientation). We estimated the attentional modulation index (AMI) based on these

distance values. This index measures how much attention modulated the pattern similarity for the Same

orientation condition (e.g., attend and perceive the same orientation) relative to the Different orientation

condition (e.g., attend and perceive different orientations). The index was calculated as follows: AMI =

$(D_{different} - D_{same})/(D_{different} + D_{same})$, where $D_{same}$ and $D_{different}$ are the measured distance (D) in the Same and

Different orientation condition, respectively. Next, we sorted the single-trial AMI values in descending

order and selected top-ranked 25% trials and bottom-ranked 25% trials to represent "strong modulation"

and "weak modulation" trials, respectively. We then extracted behavioral responses on these selected

trials and calculated the reaction time and accuracy for each trial type. Paired t-tests were used to compare

between "strong modulation" and "weak modulation" trials in each session.

**Informational connectivity analysis.** We used Informational Connectivity (IC) to examine

shared changes in pattern discriminability over time, a method that allows inference based on multivoxel

pattern information rather than overall BOLD response (Jia et al., 2020; Ng et al., 2021). To track the

flow of multivariate information across time (i.e., across trials), we measured the fluctuations (covariance)

in pattern-based discriminability by calculating the Mahalanobis distance of each trial to the two attended

orientations, using a leave-one-run-out cross-validation scheme. For each ROI, we calculated the

Mahalanobis distance between the pattern of activity for each attention trial from one left-out run and the

distribution of each attended orientation of the remaining runs. To quantify the degree of attentional

modulation, we calculated the AMI using the same formula as mentioned above, where $D_{same}$ and $D_{different}$

are the measured distance (D) in the Same and Different condition. This index measures how much the

pattern similarity increased for the same attention condition (e.g., attend leftward to attend leftward)

relative to the different attention condition (e.g., attend leftward to attend rightward). A positive AMI

indicates relative proximity to the same attention condition, whereas a negative AMI indicates relative

proximity to the different attention condition. A time course of AMI values was generated across runs and

pairwise correlated between ROIs using Pearson correlation analysis and Fisher z-transformed.

Independent t-tests were used to compare the connectivity between No-Ping and Ping sessions.

**Permutation test to evaluate classifier performance**

Following previous work (Jigo et al., 2018; Gong et al., 2022), for each brain area, we evaluated the

statistical significance of the observed decoding accuracy using a permutation test scheme. We first

shuffled the trial labels in the training data and trained the same FLD classifier on the shuffled data. We

then tested the classifier on the (unshuffled) test data to obtain decoding accuracy. For each ROI and each

participant, we repeated this procedure 1000 times to compute a null distribution of decoding accuracy.

To compute the group-level significance, we averaged the 20 null distributions to obtain a single null

distribution of 1000 values for each ROI. To determine if the observed decoding accuracy significantly

exceeds the chance level, we compared the observed value to the 95 percentiles of this group-level

distribution (corresponding to $p = 0.05$). Note that these ROIs were pre-defined with strong priors as their

activation in attention tasks has been consistently reported in the literature. Nevertheless, for those

analyses where multiple comparisons were performed across regions, we applied a Bonferroni-correction

to adjust the $p$-values.

**Bayesian analysis**

To evaluate the strength of evidence for the null hypothesis, we conducted Bayesian analyses

(Wagenmakers, 2007) using standard priors as implemented in JASP Version 0.17.1 (JASP Team, 2023).

We performed Bayesian t-tests and computed Bayes factor ($BF_{01}$) to compare between two attention

conditions (attend leftward vs. attend rightward). Additionally, we used Bayesian repeated-measures

ANOVA and computed the exclusion Bayes factors ($BF_{excl}$) to assess the evidence for excluding specific

effects across all models. A Bayes factor (BF) greater than 1 provides support for the null hypothesis.

Specifically, a BF between 1 and 3 indicates weak evidence, a BF between 3 and 10 indicates moderate

evidence, and a BF greater than 10 indicates strong evidence (Van Doorn et al., 2021).

**Approach to handle partially overlapped samples**

Our study used partially overlapping samples, with 14 out of 20 participants completing both No-Ping

and Ping sessions, while the remainder completed one of the two sessions. The most important analyses

entailed assessing whether decoding accuracy was above chance, for which we used the permutation-

based method (see above) within each session. Thus, these analyses were unaffected by the partially

overlapping samples. In a few analyses where we compared across sessions, we used statistical tests

treating "session" as a between-subject factor. We believe this is a reasonable approach, as a between-

subject test is more conservative than a within-subject test, such that any significant effect emerged

should be a genuine effect. To be certain, we also conducted additional analyses with "session" as a

within-subject factor on the subset of data from the 14 participants who completed both sessions in a

counterbalanced order. The results were highly similar to those reported in the main text.

**References**

Baldauf, D., & Desimone, R. (2014). Neural mechanisms of object-based attention. *Science*, *344*(6182), 424–427. https://doi.org/10.1126/science.1247003

Barbosa, J., Lozano-Soldevilla, D., & Compte, A. (2021). Pinging the brain with visual impulses reveals electrically active, not activity-silent, working memories. *PLOS Biology*, *19*(10), e3001436. https://doi.org/10.1371/journal.pbio.3001436

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436. https://doi.org/10.1163/156856897X00357

Bressler, S. L., Tang, W., Sylvester, C. M., Shulman, G. L., & Corbetta, M. (2008). Top-down control of human visual cortex by frontal and parietal cortex in anticipatory visual spatial attention. *The Journal of Neuroscience*, *28*(40), 10056–10061. https://doi.org/10.1523/JNEUROSCI.1776-08.2008

Corbetta, M., & Shulman, G. L. (2002). Control of goal-directed and stimulus-driven attention in the brain. *Nature Reviews Neuroscience*, *3*(3), 201–215. https://doi.org/10.1038/nrn755

Desimone, R., & Duncan, J. (1995). Neural mechanisms of selective visual attention. *Annual Review of Neuroscience*, *18*(1), 193–222. https://doi.org/10.1146/annurev.ne.18.030195.001205

DeYoe, E. A., Carman, G. J., Bandettini, P., Glickman, S., Wieser, J., Cox, R., Miller, D., & Neitz, J. (1996). Mapping striate and extrastriate visual areas in human cerebral cortex. *Proceedings of the National Academy of Sciences*, *93*(6), 2382–2386. https://doi.org/10.1073/pnas.93.6.2382

Duncan, D. H., van Moorselaar, D., & Theeuwes, J. (2023). Pinging the brain to reveal the hidden attentional priority map using encephalography. *Nature Communications*, *14*(1), 4749. https://doi.org/10.1038/s41467-023-40405-8

Engel, S. (1997). Retinotopic organization in human visual cortex and the spatial precision of functional MRI. *Cerebral Cortex*, *7*(2), 181–192. https://doi.org/10.1093/cercor/7.2.181

Faul, F., Erdfelder, E., Lang, A. G., & Buchner, A. (2007). G*Power 3: A flexible statistical power analysis program for the social, behavioral, and biomedical sciences. *Behavior Research Methods*, *39*(2), 175–191. https://doi.org/10.3758/BF03193146

Gardner, J. L., Merriam, E. P., Schluppeck, D., Besle, J., & Heeger, D. J. (2018). mrTools: Analysis and

visualization package for functional magnetic resonance imaging data (Version 4.7) [Computer

software]. Zenodo. https://doi.org/10.5281/ZENODO.1299483

Gong, M., Chen, Y., & Liu, T. (2022). Preparatory attention to visual features primarily relies on non-

sensory representation. *Scientific Reports*, *12*(1), 21726. https://doi.org/10.1038/s41598-022-26104-

2

Gong, M., & Liu, T. (2020a). Biased neural representation of feature-based attention in the human

frontoparietal network. *Journal of Neuroscience*, *40*(43), 8386-8395.

Gong, M., & Liu, T. (2020b). Continuous and discrete representations of feature-based attentional priority

in human frontoparietal network. *Cognitive Neuroscience*, *11*(1–2), 47–59.

https://doi.org/10.1080/17588928.2019.1601074

Grubert, A., & Eimer, M. (2018). The time course of target template activation processes during

preparation for visual search. *The Journal of Neuroscience*, *38*(44), 9527–9538.

https://doi.org/10.1523/JNEUROSCI.0409-18.2018

Guo, F., Preston, T. J., Das, K., Giesbrecht, B., & Eckstein, M. P. (2012). Feature-independent neural

coding of target detection during search of natural scenes. *Journal of Neuroscience*, *32*(28), 9499–

9510. https://doi.org/10.1523/JNEUROSCI.5876-11.2012

Hamblin-Frohman, Z., & Becker, S. I. (2021). The attentional template in high and low similarity search:

Optimal tuning or tuning to relations? *Cognition*, *212*, 104732.

https://doi.org/10.1016/j.cognition.2021.104732

Hout, M. C., & Goldinger, S. D. (2015). Target templates: The precision of mental representations affects

attentional guidance and decision-making in visual search. *Attention, Perception, & Psychophysics*,

*77*(1), 128–149. https://doi.org/10.3758/s13414-014-0764-6

Hout, M. C., Robbins, A., Godwin, H. J., Fitzsimmons, G., & Scarince, C. (2017). Categorical templates

are more useful when features are consistent: Evidence from eye movements during search for

societally important vehicles. *Attention, Perception, & Psychophysics*, *79*(6), 1578–1592.

https://doi.org/10.3758/s13414-017-1354-1

JASP Team. (2023). JASP (Version 0.17.1) [Computer software].

Jia, K., Goebel, R., & Kourtzi, Z. (2023). Ultra-high field imaging of human visual cognition. *Annual*

*Review of Vision Science*, *9*(1), 479–500. https://doi.org/10.1146/annurev-vision-111022-123830

Jia, K., Zamboni, E., Kemper, V., Rua, C., Goncalves, N. R., Ng, A. K. T., Rodgers, C. T., Williams, G.,

Goebel, R., & Kourtzi, Z. (2020). Recurrent processing drives perceptual plasticity. *Current Biology*,

*30*(21), 4177-4187.e4. https://doi.org/10.1016/j.cub.2020.08.016

Jigo, M., Gong, M., & Liu, T. (2018). Neural determinants of task performance during feature-based

attention in human cortex. *eNeuro*, *5*(1), 1–15. https://doi.org/10.1523/ENEURO.0375-17.2018

Kastner, S., Pinsk, M. A., De Weerd, P., Desimone, R., & Ungerleider, L. G. (1999). Increased activity in

human visual cortex during directed attention in the absence of visual stimulation. *Neuron*, *22*(4),

751–761. https://doi.org/10.1016/S0896-6273(00)80734-5

Kerzel, D. (2019). The precision of attentional selection is far worse than the precision of the underlying

memory representation. *Cognition*, *186*, 20–31. https://doi.org/10.1016/j.cognition.2019.02.001

Kleiner, M., Brainard, D., & Pelli, D. (2007). What's new in Psychtoolbox-3?

Kok, P., Failing, M. F., & De Lange, F. P. (2014). Prior expectations evoke stimulus templates in the

primary visual cortex. *Journal of Cognitive Neuroscience*, *26*(7), 1546–1554.

https://doi.org/10.1162/jocn_a_00562

Konen, C. S., & Kastner, S. (2008). Representation of eye movements and stimulus motion in

topographically organized areas of human posterior parietal cortex. *Journal of Neuroscience*, *28*(33),

8361–8375. https://doi.org/10.1523/JNEUROSCI.1930-08.2008

Kong, G., Alais, D., & Van Der Burg, E. (2017). Orientation categories used in guidance of attention in

visual search can differ in strength. *Attention, Perception, & Psychophysics*, *79*(8), 2246–2256.

https://doi.org/10.3758/s13414-017-1387-5

Lewis-Peacock, J. A., Drysdale, A. T., & Postle, B. R. (2015). Neural evidence for the flexible control of mental representations. *Cerebral Cortex*, *25*(10), 3303–3313. https://doi.org/10.1093/cercor/bhu130

Liu, T., & Hou, Y. (2013). A hierarchy of attentional priority signals in human frontoparietal cortex. *Journal of Neuroscience*, *33*(42), 16606–16616. https://doi.org/10.1523/JNEUROSCI.1780-13.2013

Mahalanobis, P. C. (1936). On generalised distance in statistics. *National Institute of Science — 3India, Proceedings*, *2*, 49–55.

Malcolm, G. L., & Henderson, J. M. (2009). The effects of target template specificity on visual search in real-world scenes: Evidence from eye movements. *Journal of Vision*, *9*(11), 8–8. https://doi.org/10.1167/9.11.8

Mongillo, G., Barak, O., & Tsodyks, M. (2008). Synaptic theory of working memory. *Science*, *319*(5869), 1543–1546. https://doi.org/10.1126/science.1150769

Myers, N. E., Walther, L., Wallis, G., Stokes, M. G., & Nobre, A. C. (2015). Temporal dynamics of attention during encoding versus maintenance of working memory: complementary views from event-related potentials and alpha-band oscillations. *Journal of Cognitive Neuroscience*, *27*(3), 492–508. https://doi.org/10.1162/jocn_a_00727

Ng, A. K. T., Jia, K., Goncalves, N. R., Zamboni, E., Kemper, V. G., Goebel, R., Welchman, A. E., & Kourtzi, Z. (2021). Ultra-High-Field neuroimaging reveals fine-scale processing for 3D perception. *The Journal of Neuroscience*, *41*(40), 8362–8374. https://doi.org/10.1523/JNEUROSCI.0065-21.2021

Peelen, M. V., & Kastner, S. (2011). A neural basis for real-world visual search in human occipitotemporal cortex. *Proceedings of the National Academy of Sciences of the United States of America*, *108*(29), 12125–12130. https://doi.org/10.1073/pnas.1101042108

Prins, N., & Kingdom, F. A. A. (2009). Palamedes: Matlab routines for analyzing psychophysical data. *Palamedes: Matlab Routines for Analyzing Psychophysical Data.*

Rosenberg, M. D., Scheinost, D., Greene, A. S., Avery, E. W., Kwon, Y. H., Finn, E. S., Ramani, R., Qiu, M., Constable, R. T., & Chun, M. M. (2020). Functional connectivity predicts changes in attention

observed across minutes, days, and months. *Proceedings of the National Academy of Sciences*,

*117*(7), 3797–3807. https://doi.org/10.1073/pnas.1912226117

Rungratsameetaweemana, N., & Serences, J. T. (2019). Dissociating the impact of attention and

expectation on early sensory processing. *Current Opinion in Psychology*, *29*, 181–186.

https://doi.org/10.1016/j.copsyc.2019.03.014

Schluppeck, D., Curtis, C. E., Glimcher, P. W., & Heeger, D. J. (2006). Sustained activity in topographic

areas of human posterior parietal cortex during memory-guided saccades. *The Journal of*

*Neuroscience*, *26*(19), 5098–5108. https://doi.org/10.1523/JNEUROSCI.5330-05.2006

Schneegans, S., & Bays, P. M. (2017). Restoration of fMRI decodability does not imply latent working

memory states. *Journal of Cognitive Neuroscience*, *29*(12), 1977–1994.

https://doi.org/10.1162/jocn_a_01180

Scolari, M., Byers, A., & Serences, J. T. (2012). Optimal deployment of attentional gain during fine

discriminations. *The Journal of Neuroscience*, *32*(22), 7723–7733.

https://doi.org/10.1523/JNEUROSCI.5558-11.2012

Sereno, M. I., Dale, A. M., Reppas, J. B., Kwong, K. K., Belliveau, J. W., Brady, T. J., Rosen, B. R., &

Tootell, R. B. H. (1995). Borders of multiple visual areas in humans revealed by functional magnetic

resonance imaging. *Science*, *268*(5212), 889–893. https://doi.org/10.1126/science.7754376

Sereno, M. I., Pitzalis, S., & Martinez, A. (2001). Mapping of contralateral space in retinotopic

coordinates by a parietal cortical area in humans. *Science*, *294*(5545), 1350–1354.

https://doi.org/10.1126/science.1063695

Stokes, M. G. (2015). 'Activity-silent' working memory in prefrontal cortex: A dynamic coding

framework. *Trends in Cognitive Sciences*, *19*(7), 394–405. https://doi.org/10.1016/j.tics.2015.05.004

Stokes, M. G., Muhle-Karbe, P. S., & Myers, N. E. (2020). Theoretical distinction between functional

states in working memory and their corresponding neural states. *Visual Cognition*, *28*(5–8), 420–432.

https://doi.org/10.1080/13506285.2020.1825141

Stokes, M., Thompson, R., Nobre, A. C., & Duncan, J. (2009). Shape-specific preparatory activity

mediates attention to targets in human visual cortex. *Proceedings of the National Academy of*

*Sciences*, *106*(46), 19569–19574. https://doi.org/10.1073/pnas.0905306106

Summerfield, C., & De Lange, F. P. (2014). Expectation in perceptual decision making: Neural and

computational mechanisms. *Nature Reviews Neuroscience*, *15*(11), 745–756.

https://doi.org/10.1038/nrn3838

Summerfield, C., & Egner, T. (2009). Expectation (and attention) in visual cognition. *Trends in Cognitive*

*Sciences*, *13*(9), 403–409. https://doi.org/10.1016/j.tics.2009.06.003

Summerfield, C., & Egner, T. (2016). Feature-based attention and feature-based expectation. *Trends in*

*Cognitive Sciences*, *20*(6), 401–404. https://doi.org/10.1016/j.tics.2016.03.008

Van Doorn, J., Van Den Bergh, D., Böhm, U., Dablander, F., Derks, K., Draws, T., Etz, A., Evans, N. J.,

Gronau, Q. F., Haaf, J. M., Hinne, M., Kucharský, Š., Ly, A., Marsman, M., Matzke, D., Gupta, A. R.

K. N., Sarafoglou, A., Stefan, A., Voelkel, J. G., & Wagenmakers, E.-J. (2021). The JASP guidelines

for conducting and reporting a Bayesian analysis. *Psychonomic Bulletin & Review*, *28*(3), 813–826.

https://doi.org/10.3758/s13423-020-01798-5

Wagenmakers, E.-J. (2007). A practical solution to the pervasive problems ofp values. *Psychonomic*

*Bulletin & Review*, *14*(5), 779–804. https://doi.org/10.3758/BF03194105

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016). Reliability of

dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, *137*, 188–200.

https://doi.org/10.1016/j.neuroimage.2015.12.012

Wen, T., Duncan, J., & Mitchell, D. J. (2019). The time-course of component processes of selective

attention. *NeuroImage*, *199*, 396–407. https://doi.org/10.1016/j.neuroimage.2019.05.067

Wolfe, J. M. (2021). Guided Search 6.0: An updated model of visual search. *Psychonomic Bulletin &*

*Review*, *28*(4), 1060–1092. https://doi.org/10.3758/s13423-020-01859-9

Wolfe, J. M., Friedman-Hill, S. R., Stewart, M. I., & O'Connell, K. M. (1992). The role of categorization

in visual search for orientation. *Journal of Experimental Psychology: Human Perception and*

*Performance*, *18*(1), 34–49. https://doi.org/10.1037/0096-1523.18.1.34

Wolff, M. J., Ding, J., Myers, N. E., & Stokes, M. G. (2015). Revealing hidden states in visual working

memory using electroencephalography. *Frontiers in Systems Neuroscience*, *9*.

https://doi.org/10.3389/fnsys.2015.00123

Wolff, M. J., Jochim, J., Akyürek, E. G., & Stokes, M. G. (2017). Dynamic hidden states underlying

working-memory-guided behavior. *Nature Neuroscience*, *20*(6), 864–871.

https://doi.org/10.1038/nn.4546

Yu, X., Hanks, T. D., & Geng, J. J. (2022). Attentional guidance and match decisions rely on different

template information during visual search. *Psychological Science*, *33*(1), 105–120.

https://doi.org/10.1177/09567976211032225

Yu, X., Zhou, Z., Becker, S. I., Boettcher, S. E. P., & Geng, J. J. (2023). Good-enough attentional

guidance. *Trends in Cognitive Sciences*, *27*(4), 391–403. https://doi.org/10.1016/j.tics.2023.01.007

Zhang, H., & Luo, H. (2023). Feature-specific reactivations of past information shift current neural

encoding thereby mediating serial bias behaviors. *PLOS Biology*, *21*(3), e3002056.

https://doi.org/10.1371/journal.pbio.3002056

**Acknowledgements**

This work was supported by National Science and Technology Innovation 2030—Major Project 2021ZD0200409, National Natural Science Foundation of China (32371087, 32300855, 3200784), Fundamental Research Funds for the Central University (226-2024-00118) and Non-profit Central Research Institute Fund of Chinese Academy of Medical Sciences 2023-PT310-01.

**Author contributions**

Original idea by K.J. and M.G. Experiment programmed by Y.C. Data collected by Y.C. Analysis programmed by Y.C., K.J. and M.G. Manuscript drafted by Y.C., T.L., and M.G. Manuscript edited and revised by T.L., J. T., K.J., and M.G.

**Data Availability**

All data, analyses, and task codes have been made publicly available via the Open Science Framework at https://osf.io/ghaxv/

**Competing interests**

The authors declare no competing interests.