Dual-format attentional template during preparation in human visual cortex

Yilin Chen[1], Taosheng Liu[2], Ke Jia[3,4,5*], Jan Theeuwes[6], Mengyuan Gong[1*]

[1] Department of Psychology and Behavioral Sciences, Zhejiang University, Hangzhou, Zhejiang, China

[2] Department of Psychology, Michigan State University, East Lansing, Michigan, USA

[3] Liangzhu Laboratory, MOE Frontier Science Center for Brain Science and Brain-machine Integration, State Key Laboratory of Brain-machine Intelligence, Zhejiang University, Hangzhou, Zhejiang, China

[4] Department of Neurobiology, Affiliated Mental Health Center & Hangzhou Seventh People's Hospital, Zhejiang University School of Medicine, Hangzhou, Zhejiang, China

[5] NHC and CAMS Key Laboratory of Medical Neurobiology, Zhejiang University, Hangzhou, Zhejiang, China

[6] Department of Experimental and Applied Psychology, Vrije Universiteit Amsterdam, Amsterdam, the Netherlands

*Corresponding Author

Dr. Mengyuan Gong

Department of Psychology and Behavioral Sciences, Zhejiang University

gongmy426@zju.edu.cn

Dr. Ke Jia

MOE Frontier Science Center for Brain Science and Brain-machine Integration, Zhejiang University

kjia@zju.edu.cn

Abstract

Goal-directed attention relies on forming internal templates of key information relevant for guiding behavior, particularly when preparing for upcoming sensory inputs. However, evidence on how these attentional templates is represented during preparation remains controversial. Here, we combine functional magnetic resonance imaging (fMRI) with an orientation cueing task to isolate preparatory activity from stimulus-evoked responses. Using multivariate pattern analysis, we found decodable information of the to-be-attended orientation during preparation; yet preparatory activity patterns were different from those evoked when actual orientations were perceived. When perturbing the neural activity by means of a visual impulse ('pinging' technique), the preparatory activity patterns in visual cortex resembled those associated with perceiving these orientations. The observed differential patterns with and without the impulse perturbation suggest a predominantly non-sensory format and a latent, sensory-like format of representation during preparation. Furthermore, the emergence of the sensory-like template coincided with enhanced information connectivity between V1 and frontoparietal areas and was associated with improved behavioral performance. By engaging this dual-format mechanism during preparation, the brain is able to encode both abstract, non-sensory information and more detailed, sensory information, potentially providing advantages for adaptive attentional control. For example, consistent with recent theories of visual search, a predominantly non-sensory template can support the initial guidance and a latent sensory-like format can support prospective stimulus processing.

Keywords

Attentional selection, representational format, fMRI, decoding, visual cortex, impulse perturbation

Introduction

To address the challenge of processing the overwhelming amounts of sensory inputs from the external environment, the brain must allocate attentional resources to prioritize the processing of task-relevant information. Importantly, humans can proactively prepare for stimulus selection before the arrival of sensory inputs (Summerfield & De Lange, 2014). For example, when preparing to hail a taxi on the road, we tend to form a mental representation of the defining features of a taxi (e.g., yellow with a car-like shape). This ability relies on the formation of attentional templates — mental representations of the target — to accelerate stimulus selection and resolve perceptual competition by enhancing task-relevant information and suppressing irrelevant information (Desimone & Duncan, 1995; Kastner et al., 1999). While most attentional models posit that attentional templates during stimulus processing reflect veridical representations of the target (Jigo et al., 2018; Malcolm & Henderson, 2009), the nature of the template during preparation remains less understood.

A classical view suggests that attentional template during preparation may reflect veridical target features, analogous to the representational format during stimulus selection. However, evidence supporting this account has been mixed. For example, while some previous fMRI studies have demonstrated that preparatory activity contains target information similar to the sensory responses to the corresponding targets (Kok et al., 2014; Lewis-Peacock et al., 2015; Stokes et al., 2009), more recent electrophysiological studies suggest that, if anything, this template is engaged only shortly before the expected arrival of sensory input rather than being continuously active (Grubert & Eimer, 2018; Myers et al., 2015). Notably, in some cases the template is even largely undetectable during preparation (Wen et al., 2019). Alternatively, an emerging view suggests a non-veridical template suffices for guiding attention during preparation, where precise processing of stimuli may be unnecessary at this stage. Support for this notion comes from the identification of attentional signals during preparation that differ from neural signals observed during perceptual target processing (Gong et al., 2022). Recent theories of visual search also propose a non-veridical, "good-enough"

template for early attentional guidance (Wolfe, 2021; Yu et al., 2023). However, it remains unclear whether

a "good-enough" template for search also applies to preparatory attention.

The notion that there may be a sensory and non-sensory attentional template might not be as far-

fetched as it seems. Indeed, it is feasible that during preparation, following stimulus presentation, attentional

signals undergo a transformation from a non-sensory to a sensory-like template. Previous behavioral

(Hamblin-Frohman & Becker, 2021; Yu et al., 2022) and neural studies (Gong et al., 2022; Jigo et al., 2018;

Wen et al., 2019) are generally consistent with this idea of coarse-to-fine transitions, suggesting that during

preparation, a sensory-like template may not be initially necessary but only becomes relevant when the

stimulus needs to be identified. However, if and in what way the brain coordinates these non-sensory and

sensory-like templates remains unclear. Here, we propose that during preparation, a sensory-like template

may be stored in a latent (e.g., activity-silent) state concurrently with a non-sensory template. This idea

parallels recent findings from working memory studies, which suggest that information intended for

proactive use is kept in activity-silent traces to support future behavior (Stokes, 2015; Wolff et al., 2015,

2017). The present study seeks to determine the possibility of the latent, sensory-like template during the

preparation for discriminating an upcoming stimulus.

To test these hypotheses, participants engaged in a cuing task in which they prepared during an

extended period of time for the presentation of a compound stimulus grating containing the cued orientation

and a distractor orientation. In addition, in order to be able to construct the sensory-format representations

(leftward and rightward orientation), single orientations were presented during the perception task.

Critically, we used a "pinging" technique combined with multivariate decoding methods, which has been

shown to be effective in retrieving information from latent brain states (Duncan et al., 2023; Wolff et al.,

2015, 2017; Zhang & Luo, 2023). In the standard condition (*No-Ping session*), the preparation period was

devoid of visual impulses. During preparation, the neural activity patterns in visual and frontoparietal areas

could discriminate between the orientations that participants were preparing for. Yet, neural activity

patterns evoked by the perception of orientations were distinct from those evoked during preparation for

upcoming orientations, suggesting a predominantly non-sensory template during preparation. By contrast,

when we presented a high-contrast, task-irrelevant impulse stimulus during preparation (*Ping session*),

neural activity patterns evoked by the perception of orientations were similar to those activated by the

preparation for orientations in the visual cortex, suggesting the existence of a latent, sensory-like format of

representation during preparatory attention. Furthermore, the emergence of sensory-like template coincided

with enhanced information connectivity between V1 and frontoparietal areas and was associated with

improved behavioral performance. Our findings provide evidence for the co-existence of two formats of

attentional templates (non-sensory vs. sensory-like) during preparation, as well as a novel neural

mechanism for their maintenance in different functional states (active vs. latent). We propose that this dual-

format representation may serve to increase flexibility of attentional control.

Results

Behavioral performance during the attention tasks

In an orientation cueing task, participants were shown a color cue indicating the reference orientation (45°

or 135°) to attend to during preparation period (a delay of 5.5 s or 7.5 s) with or without the impulse

perturbation (Fig 1A). This was followed by the presentation of a compound stimulus consisting of two

oriented gratings. During the stimulus selection period (after the gratings appeared), participants were

tasked with discriminating a small angular offset of the cued grating from the cued reference orientation.

The angular offset was individually thresholded before the scanning sessions (mean offset = 2.50° in the

No-Ping session and 2.52° in the Ping session) without significant difference between two sessions

(independent t-test: $t(19) = 0.085$, $p = 0.932$, Cohen's d = -0.027). Participants' discrimination performance

showed no significant difference between two attended orientations in either the No-Ping (paired t-test:

$t(19) = 1.439$, $p = 0.166$, Cohen's d = -0.321) or the Ping session (paired t-test: $t(19) = 0.494$, $p = 0.627$,

Cohen's d = 0.122; Fig 1C). A two-way mixed ANOVA (attended orientation × session) revealed neither

significant main effects (attended orientation: $F(1,38) = 0.392$, $p = 0.535$, $\eta_p^2 = 0.01$; session: $F(1,38) =$

0.001, $p = 0.970$, $\eta_p^2 < 0.001$) nor interaction effect ($F(1,38) = 1.811$, $p = 0.186$, $\eta_p^2 = 0.045$). Bayesian

analyses provided moderate evidence to support the null hypothesis (BF$_{excl}$ > 3.633), suggesting comparable

performance levels between two sessions and two attended orientations.

Fig 1. Experiment procedure and behavioral performance. (A) Attention tasks in the No-Ping and Ping sessions.

Note that only long-delay trials are shown. A small proportion of short-delay trials (20%, with a delay of 1.5 s or 3.5

s) were included to create temporal uncertainty and encourage consistent active preparation during the delay. Both

component gratings were flickering at 10 Hz between white and black, so that luminance could not confound either

the task strategy (e.g., attending to luminance) or neural measures. The inset shows two sets of color-orientation

mapping, which were reversed halfway through the experiment to minimize the impact of cue-induced sensory

difference on neural activity. A high-contrast impulse was presented during preparation period in the Ping session. (B)

Perception task. Similar to the attention task, the single-orientation grating also flickered at 10 Hz between white and

black. (C) Behavioral accuracy in the attention tasks in the No-Ping and Ping sessions. Each dot represents one

subject's data. Error bars denote standard error of the means (SEM).

A default, non-sensory representation of attentional template during preparation

The first aim of this study was to determine whether attentional signals during preparation are encoded in

a sensory-like or non-sensory format. To address this, we first examined whether, in the attention task

during the No-Ping condition, the distributed neural pattern contained feature-specific information. We

trained and tested separate classifiers to predict the attended orientation during the preparation and stimulus

selection periods (Fig 2A, "Attention decoding"; see Materials and Methods for details). This analysis was

performed for each of the four regions along the visual hierarchy, including primary visual cortex (V1),

extrastriate visual cortex (EVC), intraparietal sulcus (IPS) and prefrontal cortex (PFC). The average

decoding accuracies for both preparation and stimulus selection periods were significantly above chance

level in each region (Permutation analyses: $ps < 0.004$ across regions, Fig 2B), indicating that the brain

maintained reliable information about the attended feature both before and after the onset of the compound

grating. Next, we examined whether the preparatory activity reflected a sensory-like format of attentional

template (Fig 2A, "Cross-task generalization", see Materials and Methods). We trained a classifier using

data from the perception task (leftward vs. rightward orientation; Fig 1B) and tested its performance on

data from the preparation period in the attention task (attend leftward vs. attend rightward). However, this

cross-task generalization analysis yielded no significant effects ($ps > 0.132$ across the regions). In contrast,

we observed above-chance generalization from the perception task to the stimulus selection period ($ps <$

0.001 across regions, Fig 2C), confirming previous findings of the sensory-like attentional template

following stimulus presentation (Gong et al., 2022; Jigo et al., 2018; Wen et al., 2019).

Fig 2. MVPA for the No-Ping session and Ping session. (A) Schematic illustration of the decoding of attended orientation (attend leftward vs. attend rightward) in the attention task (left panel) and the cross-task generalization analysis from perception task to the attention task (right panel). The four regions are shown on a representative right hemisphere as colored areas: V1 is marked in red, EVC in yellow, IPS in cyan and PFC in purple. (B) Decoding accuracy during preparation and stimulus selection periods across regions in the No-Ping and (D) Ping session. (C) Cross-task generalization performance from the perception task to the preparatory periods and the stimulus selection periods across regions in the No-Ping and (E) Ping session. The dashed lines represent the theoretical chance level (0.5). Each dot represents one subject's data. Error bars denote SEM.

Before drawing conclusions based on the lack of generalization from the perception task to

preparatory attention, we considered two alternative explanations to rule out potential confounds. First, the

robust attention decoding during preparation ruled out the possibility that participants were not actively

engaged in the task during preparation (Fig 2B, unfilled bars). Second, the generalizable effect from the

perception task to the stimulus selection period across regions (Fig 2C, filled bars) argues against the

possibility of low statistical power. Overall, these findings suggest that the preparatory attention and

sensory processing of features have distinct formats, presumably reflecting a non-sensory format of

representation during the preparation. These results replicate those of a previous fMRI study using motion

stimuli with a similar design (Gong et al., 2022). Furthermore, consistent with previous studies (Gong et

al., 2022; Jigo et al., 2018), univariate analysis did not reveal any reliable difference in overall BOLD

responses between attention orientations (Supplementary Information and S1 Fig).

A latent, sensory-like attentional template during preparation revealed by visual impulse

The second aim of our study was to examine whether a latent, sensory-like template exists during

preparation. While this precise template may not be necessary for preparation, it is relevant for subsequent

target selection and discrimination (i.e., select the cued grating from the compound stimulus and

discriminate a small angular offset between the cued grating and the reference orientation). To test this

hypothesis, we perturbed the neural activity by means of a visual impulse during the preparation period in

the Ping session (Fig 1A, right panel). Using the same analyses as those performed in the No-Ping session,

robust attentional signals were observed during both preparation and stimulus selection periods

(Permutation analyses: $ps < 0.001$ across regions; Fig 2D). Importantly, the cross-task generalization

analyses indicated that the visual impulse led to above-chance generalization from the perception task to

preparation period (Fig 2E, unfilled bars) in V1 and EVC ($ps < 0.001$), but not in IPS and PFC ($ps > 0.584$),

along with generalizable effects from the perception task to the stimulus selection periods ($ps < 0.036$ across

regions; Fig 2E; filled bars). These results suggest that different brain areas are involved in coding for

sensory-like templates. To further evaluate whether the cross-task generalization from the perception task

to the preparation period was statistically different with and without visual impulse, we conducted a two-

way mixed ANOVA (session × region) on the generalization performance. The analysis revealed main

effects of region (F(3,114) = 5.220, p = 0.002, η_p^2 = 0.121), session (F(1,38) = 7.321, p = 0.010, η_p^2 = 0.162),

and importantly, a significant interaction effect (F(3,114) = 3.964, p = 0.010, η_p^2 = 0.094), supporting the

observation that the visual impulse led to significantly increased decoding accuracy in V1 (independent t-

test: t(38) = 3.145, p = 0.003, Cohen's d = 0.995) and EVC (independent t-test: t(38) = 2.153, p = 0.038,

Cohen's d = 0.681), but not in the frontoparietal regions (ps > 0.374). This dissociable result between the

two sessions further supports the activation of a latent, sensory-like template by the visual impulse during

preparatory attention.

To further solidify this conclusion, following analyses were used to examine several alternative

possibilities. First, we examined whether the impulse-driven generalization resulted from stronger feature

information in the Ping compared to No-Ping session during the perception task. This was not the case, as

evidenced by comparable levels of decodable orientation information between the Ping and No-Ping

sessions (see Supplementary Information and S2 Fig). Next, we asked whether the increased generalization

was due to generally stronger attentional signals in the Ping session during the attention tasks – for example,

if visual impulses simply refocused attention during long delays. This was not the case, as the two-way

mixed ANOVAs (session × region) on attention decoding accuracy revealed neither a significant main

effect of session nor an interaction effect during both the preparation (ps > 0.519; BF_{excl} > 3.247) and

stimulus selection periods (ps > 0.336; BF_{excl} > 3.297), suggesting comparable amount of attentional

information between the two sessions. Therefore, the findings of impulse-driven sensory-like template in

the visual cortex during preparation cannot be explained by general differences between two sessions.

Matching preparatory attention to sensory template: impact on neural representation and

behavior

The reported decoding accuracy from the cross-task generalization analysis quantifies the degree to which

differences in neural activity pattern between two conditions are shared across attention and perception

tasks. However, it does not directly measure how similar the neural patterns are when attending to an orientation compared to perceiving that orientation. Unlike decoding accuracies, Mahalanobis distance provides a continuous measure for characterizing representational geometries between different conditions (Mahalanobis, 1936). To further corroborate our findings of the impulse-driven sensory-like template, we calculated the Mahalanobis distance between each attention condition during preparation and each perception condition (see Materials and Methods). If the patterns of activity reflect a sensory-like template, we would expect greater pattern similarity (smaller distance) between "attend leftward" and "perceive leftward" than between "attend leftward" and "perceive rightward", and vice versa for the "attend rightward" conditions (see Fig 3A for a schematic of the four pair-wise distance measures), leading to an interaction between attended and perceived orientation conditions.

We used a two-way repeated-measures ANOVA (attended orientation × perceived orientation) on the Mahalanobis distance, separately for each session and each region. During the preparatory period in the No-Ping session, no significant interaction effects were observed across regions ($ps > 0.443$; Fig 3B). In contrast, the same analyses applied to the Ping session revealed significant interaction effects in visual areas (V1: $F_{(1,19)} = 9.335$, $p = 0.007$, $\eta_p^2 = 0.329$; EVC: $F_{(1,19)} = 8.563$, $p = 0.009$, $\eta_p^2 = 0.311$; Fig 3C; also see Supplementary Table 1), but not for frontoparietal regions ($ps > 0.213$). This cross-region difference is consistent with the function of sensory areas in encoding precise neural representations for basic visual features. Next, we directly compared whether attentional modulation of Mahalanobis distance was statistically different with and without the visual impulse. We defined a new condition label based on orientation consistency between attended and perceived orientations: (1) same orientation: averaging "attend leftward/perceive leftward" and "attend rightward/perceive rightward"; and (2) different orientation: averaging "attend leftward/perceive rightward" and "attend rightward/perceive leftward". A two-way mixed ANOVA (session × orientation consistency) on Mahalanobis distance revealed a main effect of orientation consistency in V1 ($F_{(1,38)} = 4.21$, $p = 0.047$, $\eta_p^2 = 0.100$), indicating that activity patterns were more similar when attended and perceived orientations matched. No significant main effect of session was found ($p = 0.923$). Importantly, a significant interaction was found in V1 ($F_{(1,38)} = 5.00$, $p = 0.031$, $\eta_p^2 =$

0.116), suggesting that visual impulse enhanced the similarity between preparatory attentional template and

the perception of corresponding orientation. In EVC, the same analysis revealed only a main effect of

orientation consistency ($F(1,38) = 5.87$, $p = 0.020$, $\eta_p^2 = 0.134$), with no other significant effects ($ps > 0.240$).

We also calculated the Mahalanobis distance between neural patterns evoked by superimposed gratings

during the stimulus selection period and each condition in the perception task, finding similar results (see

Supplementary Information and S4 Fig). This result was expected, as feature-based attention is known to

selectively enhance task-relevant features while filtering out task-irrelevant ones.

Fig 3. Orientation-selective attentional modulations on neural pattern distances during preparation. (A) Schematic illustration of the representational distance (mean Mahalanobis distances) between each of the attention conditions and each of the perception conditions. Colored arrows indicate measures of the pair-wise Mahalanobis distance. The right panel shows two attention trials (red indicates attend-to-leftward and green indicates attend-to-rightward) to the distribution of each perception condition (shown in a cloud of light-colored dots). (B) Mahalanobis

distance between preparatory attention condition and perceived orientation condition in the No-Ping and (C) Ping sessions. Error bars denote SEM. (D) Correlations between attentional modulation index (AMI) and reaction time (RT) in the No-Ping and (E) Ping sessions. Each dot represents one subject's data. The shaded area represents the confidence intervals of the regressed lines. * $p < 0.05$, ** $p < 0.01$.

The continuous nature of the Mahalanobis distance also made it possible to further investigate potential neural-behavioral correlations. We examined whether activating a sensory-like template during preparation would benefit subsequent orientation processing. In particular, we calculated attentional modulation indices (AMIs) based on trialwise Mahalanobis distance in V1. The index was calculated as follows: $AMI = (D_{different} - D_{same})/(D_{different} + D_{same})$, where D_{same} and $D_{different}$ are the measured distance (D) in the Same (e.g., attend and perceive the same orientation) and Different (e.g., attend and perceive different orientations) orientation condition, respectively (see Methods and Materials). Then, we calculated the correlation between AMI and both reaction time (RT) and accuracy across participants, separately for each session. In the No-Ping session, we observed no significant correlation between AMI in V1 and RT ($r = -0.366$, $p = 0.113$; Fig. 3D). By contrast, the same analysis in the Ping condition revealed a significantly negative correlation ($r = -0.518$, $p = 0.019$; Fig. 3E). These results indicate that the attentional modulations evoked by visual impulse was associated with faster RTs. These effects were not observed for accuracy ($ps > 0.550$). Furthermore, we also performed within-subject analysis by sorting trials as "strong modulation" and "weak modulation" trials based on each individual's AMI values, facilitated RTs were observed in "strong modulation" trials during the Ping session (Supplementary Information and S3 Fig). These results suggest that the impulse-driven sensory-like template in primary visual cortex is functionally relevant to subsequent attentional selection, providing evidence for the prospective use of sensory-like template in this task. In addition, we did not observe such behavioral differences in analogous analyses using data from the stimulus selection period in either session ($ps > 0.230$), which might due to the potential dilution by strong stimulus-evoked responses during the stimulus selection period.

Activating sensory-like template strengthens the informational connectivity between sensory and frontoparietal areas

Selective attention is generally believed to rely on coordinated network activity (Corbetta & Shulman, 2002). In particular, studies have shown that functional connectivity between sensory and frontoparietal areas was modulated by attentional control (Bressler et al., 2008; Rosenberg et al., 2020). Given that the impulse-driven sensory-like template facilitated behavior, we reasoned that it may also enhance network communication. Thus, we examined informational connectivity measures to explore how the impulse altered network function during the attention task.

We used a method that allows inference based on multivoxel pattern information rather than univariate BOLD response (Jia et al., 2020; Ng et al., 2021). For each ROI, we calculated the cross-validated Mahalanobis distance from each attention trial (from one left-out run) to the distribution of each attended orientation (all trials from remaining runs) during preparation (see Methods and Materials). To quantify the degree of attentional modulation during preparation, we calculated the AMI based on trial-wise Mahalanobis distance and generated a time course of AMI values across trials. Pearson correlation was used to estimate the covariation between each pair of ROIs, the resulting correlation coefficients were transformed using Fisher's z-transform for statistical inference (Fig 4A). The analysis revealed numerically higher levels of connectivity in Ping than in No-Ping session, this impulse-driven increase in connectivity reached statistical significance in two pairs (Fig 4B): V1-IPS (independent t-test: $t(38) = 2.566$, $p = 0.014$; Cohen's d = 0.812) and V1-PFC (independent t-tests: $t(38) = 3.158$, $p = 0.003$; Cohen's d = 0.999). The enhanced functional connectivity between V1 and frontoparietal areas driven by the impulse may potentially facilitate information flow among areas to improve attentional control, as implicated by a trend of ping-enhanced correlations between V1-PFC and RTs (Supplementary Information and S5 Fig). Additionally, the same analysis of AMI based on cross-validated Mahalanobis distance during the stimulus selection period showed no significant differences in information connectivity between No-Ping and Ping sessions ($ps > 0.224$; Supplementary Information and S6A Fig). The lack of changes in long-range

connectivity during stimulus selection period may be attributed to a general rise in connectivity caused by

strong sensory inputs in this period, which could have attenuated any potential impacts of visual impulses.

Furthermore, connectivity analysis based on mean BOLD response over time did not reveal any significant

changes in inter-cortical connections between the two sessions ($ps > 0.136$; S6B Fig), suggesting that the

impulse-driven increased information connectivity between V1 and higher-order areas was unlikely

contributed by the overall changes of BOLD response.

Fig 4. Information connectivity analysis. (A) Schematic illustration of the procedure for the information connectivity

analysis in the space of two hypothetical voxels. For each region, we calculated the Mahalanobis distance of the

attention trial (from one left-out run) from two attention distributions (all trials from remaining runs). Red and green

dots indicate activity patterns from two trials (right panel). The brain image shows an example pair of intercortical

information connectivity between V1 and PFC. The time series (lower-left panel) consisted of attentional modulation

index (AMI) based on the Mahalanobis distance. (B) Between-region information connectivity in the No-Ping and

Ping sessions. (C) The differences in connectivity between the Ping and No-Ping sessions. * $p < 0.05$, ** $p < 0.01$.

Discussion

While there is ample evidence that the brain can maintain an attentional template of an upcoming target

before sensory information is presented (Desimone & Duncan, 1995; Kastner et al., 1999; Summerfield &

De Lange, 2014), its representational format remains unclear. To address this, we used an orientation cueing

paradigm with separated preparation and stimulus selection periods and applied MVPA to decode neural

activity patterns associated with feature-specific attentional information of the upcoming target. The

analyses showed robust attentional information both before and after the presentation of the compound

grating, indicating a sustained maintenance of attentional templates throughout a trial. Importantly, while

the decoders trained on the perception of single orientations could not generalize to preparation until the

stimulus selection period (*No-Ping session*), perturbing the brain with a visual impulse resulted in

generalizable activity patterns during preparation in V1 and EVC (*Ping session*). These results suggest a

predominantly non-sensory format of representation, with a sensory-like template in a latent state during

feature-based preparation in the visual cortices. Furthermore, impulse-driven sensory-like template was

accompanied by enhanced information connectivity between V1 and frontoparietal areas, as well as

enhanced orientation-specific neural modulations of neural distances in the visual areas that predicted levels

of behavioral performance. We observed similar response profiles in V1 and EVC, with V1 exhibiting more

robust ping-evoked changes compared to EVC, consistent with its primary role in orientation processing

(Priebe, 2016). The differences between the Ping and No-Ping sessions could not be attributed to differences

in sensory information from the perception task, overall strength of preparatory attention, or differences in

eye position (S7 Fig). Therefore, our findings suggest a dual-format neural representation scheme (non-

sensory vs. sensory-like) operating in different functional states (active vs. latent). This mechanism may

give rise to flexible attentional control, allowing effective transition from coarse to fine attentional

templates at various processing stages (initial guidance vs. precise stimulus discrimination).

Recent advances in theories of visual search differentiated between the "guiding template" and

"target template" based on measures of behavioral performance and eye movements (Wolfe, 2021; Yu et

al., 2023). According to these theories, early attentional guidance typically depends on a non-veridical

codes that represent only the most diagnostic information, whereas later, target-match processes utilize

more precise codes to optimize decision accuracy (Kerzel, 2019; Scolari et al., 2012; Yu et al., 2022). Our

study reveals a parallel coding mechanism in the context of feature-based attention, expanding upon these

theoretical notions in three key aspects.

First, we provide neural evidence for a default, predominantly non-sensory template during

preparation, indicating that the concept of a "guiding template", as proposed by visual search theories

(Wolfe, 2021; Yu et al., 2023), also applies to preparatory attention in a non-search context. This highlights

a shared functional role of a non-veridical attentional template in early guidance across different scenarios.

Second, despite the theoretical notion that the brain maintains a more veridical template with detailed target

information than is typically utilized to form the guiding template (Wolfe, 2021; Yu et al., 2023), neural

evidence supporting this hypothesis is currently lacking. We provide evidence for this notion and propose

a plausible neural implementation for preserving a more veridical, sensory-like template in the latent state.

A natural question is why the sensory-like template remains latent during preparation. We note that our task

requires both coarse and fine featural information. During preparation, a coarse, non-veridical guiding

template suffices for target-distractor discrimination, while during stimulus selection, a precise template is

needed for the fine discrimination task (reporting the tilted direction of a small angular offset). Maintaining

a latent sensory-like template during preparation is thus efficient, as it facilitates future sensory processing

while conserving resources. Finally, information connectivity between visual and higher-order

frontoparietal regions was enhanced by visual impulse during preparation, which correlated with improved

behavioral performance in feature selection. This result suggests that improved information flow across the

relevant areas leads to enhanced attentional control, which in turn contributes to refined sensory

representations of target in early visual cortex, facilitating transitions from a non-sensory to sensory-like

template. Future studies may adopt layer-specific fMRI to infer the direction of this improved information

flow (Jia et al., 2023; Jia et al., 2024) and explore the relationship between long-range connections and the

utilization of different formats of target templates.

It could be argued that preparatory attention relies on the same mechanisms as working memory

maintenance (Bettencourt & Xu, 2016; Sheremata et al., 2018). While these functions are intuitively similar

and likely overlap, there is also evidence indicating that they can be dissociated (Battistoni et al., 2017). In

particular, we note that in our task, attention is guided by symbolic cues (color-orientation associations),

while working memory tasks typically present the actual visual stimulus as the memorandum. A central

finding in working memory studies is that neural signals during WM maintenance are sensory in nature, as

demonstrated by generalizable neural activity patterns from stimulus encoding to maintenance in visual

cortex (Harrison & Tong, 2009; Serences et al., 2009; Rademaker et al., 2019). However, in our task, neural

signals during preparation were non-sensory, as demonstrated by a lack of such generalization in the No-

Ping condition (see also Gong et al., 2022). We believe that the differences in cue format and task demand

in these studies may account for such differences. In addition to the difference in the sensory nature of the

preparatory versus delay-period activity, our ping-related results also exhibited divergence from working

memory studies (Wolff et al., 2015, 2017). While these studies used the visual impulse to differentiate

active and latent representations of *different items* (e.g., attended vs. unattended memory item), our study

demonstrated the active and latent representations of *a single item in different formats* (i.e., non-sensory vs.

sensory-like). Moreover, unlike our study, the impulse did not evoke sensory-like neural patterns during

memory retention (Wolff et al., 2017). These observations suggest that the cognitive and neural processes

underlying preparatory attention and working memory maintenance could very well diverge. Future studies

are necessary to delineate the relationship between these functions both at the behavioral and neural level.

While we found that the ping allowed us to detect a sensory-like template during preparation, the

underlying neural mechanism of such effects remains unclear. One possibility, as informed by theoretical

studies of working memory, is that the sensory-like template could be maintained via an "activity-silent"

mechanism through short-term changes in synaptic weights (Mongillo et al., 2008). In this framework, a

visual impulse may function as nonspecific inputs that momentarily convert latent traces into detectable

activity patterns (Rademaker & Serences, 2017). Related to our findings, it is unlikely that the orientation-

specific templates observed during the Ping session emerged *de novo* from purely non-sensory

representations and were entirely induced by an exogenous ping, which was devoid of any orientation signal.

Instead, the more parsimonious explanation is that visual impulse reactivated pre-existing latent sensory

signals, consistent with the models of "activity-silent" working memory. However, the detailed circuit-level

mechanism of such reactivation is still unclear, as well as whether this effect is modality-specific. Prior

work shows that only visual, but not auditory, impulses reactivate latent visual working memory (Wolff et

al., 2020), suggesting some degree of modality-specificity. However, this finding warrants direct

investigation in future studies. Furthermore, we acknowledge that whether pinging identifies an activity-

silent mechanism is currently debated (Barbosa et al., 2021; Schneegans & Bays, 2017). An alternative

possibility is that the visual impulse amplified a subtle but active representation of the sensory template

during preparation. Distinguishing between these alternatives likely requires future studies with more

detailed neurophysiological measurements. Regardless of the precise neural mechanism for the observed

latent, sensory representation, our results suggest that both sensory and non-sensory templates likely co-

exist.

The non-generalizable activity patterns from perception to preparatory attention, in the absence of

visual impulse, suggests a default, predominantly non-sensory template during preparation. This finding is

largely consistent with electrophysiological studies (Myers et al., 2015; Wen et al., 2019) and our prior

fMRI work on preparatory attention to motion directions (Gong et al., 2022), but differs from some previous

neuroimaging studies that demonstrated sensory-like templates during preparation (Kok et al., 2014; Peelen

& Kastner, 2011; Stokes et al., 2009). One potential account for these discrepancies is that those studies

used cue-only trials where the target was expected but not actually presented, in contrast to our task where

the target was shown on every trial with temporally separated preparation and stimulus selection periods.

This seemingly subtle difference may significantly impact the formats of the neural representations.

Because cue-only trials increased the likelihood of target appearance at the subsequent time point, sensory

template may be activated due to modulations of temporal expectations (Grubert & Eimer, 2018). This

explanation is consistent with theories suggesting differential influences of expectation and attention on

neural activity: expectation reflects visual interpretations of stimuli due to sensory uncertainty, whereas

attention is guided based on the task relevance of sensory information (Rungratsameetaweemana &

Serences, 2019; Summerfield & Egner, 2009, 2016). Our finding of a predominantly non-sensory format

may indicate an optimized coding strategy employed by the brain to effectively and robustly represent

information for future use. This aligns with the proposed role of attention in modulating sensory

representations to encode only currently relevant information at a minimal cost (Yu et al., 2023).

While our findings cannot pinpoint the exact format of this non-sensory template, we consider

categorical coding a plausible candidate based on previous findings. For instance, visual search studies

demonstrate that categorical attributes (e.g., steep vs. shallow; left-tilted vs. right-tilted) efficiently guide

attention for simple features, such as an orientation or a color (Kong et al., 2017; Wolfe et al., 1992),

particularly when features are consistent and predictable (Hout et al., 2017). In our task, the angular

relations between the target and distractor orientation were defined by categorical attributes (e.g., left-tilted

vs. right-tilted) and remained consistent across trials, making a categorical template feasible during

preparatory attention. Furthermore, categorical template allows for greater tolerance of stimulus variability,

which is also useful given the trial-by-trial variations in target orientation around the reference orientation

in our task. Future studies are needed to address the nature of the non-sensory template during preparation

as well as task parameters that might modulate them.

In summary, the current study suggests that there are two formats of attentional templates each

having a distinct functional state: a default, non-sensory format and a latent, sensory-like format. This dual-

format representation aligns with theories on the dual-function of attentional template for different task

goals (Hout & Goldinger, 2015; Yu et al., 2023). The current findings provide a plausible neural

implementation for these theories by demonstrating different formats in different functional states. This

mechanism likely reflects an optimized coding scheme that effectively balances processing efforts and

demands, particularly well-suited for flexible control and transitions from coarse to fine task demands in

visually guided behavior.

Materials and Methods

Participants

Twenty individuals participated in the No-Ping session (11 females, mean age = 22.9) and twenty individuals participated in the Ping session (14 females, mean age = 23.7). Among them, 14 participants took part in both sessions, while 12 of them took part in only one session. The sample size was comparable to previous studies using similar attention tasks (Baldauf & Desimone, 2014; Gong & Liu, 2020a; 2020b; Guo et al., 2012; Jigo et al., 2018; Liu & Hou, 2013). Because our primary interest is the generalization from the perception task to attention task, we used the minimal effect size of decoding accuracy across regions (one-sample t-tests: $d = 0.868$) from our previous study with a similar design (Gong et al., 2022), and used G*Power (Version 3.1) (Faul et al., 2007) to confirm that this sample size is sufficient to detect a cross-task generalization effect with a power greater than 95% (a = 0.05). All participants were right-handed and had a normal or corrected-to-normal vision. Participants provided written informed consent according to the study protocol approved by the Institutional Review Board at Zhejiang University (2020-06-001). They were paid ¥200 (~$27.4) for their participation in each session.

Stimuli and Apparatus

Stimuli were generated using Psychtoolbox (Brainard, 1997; Kleiner et al., 2007) implemented in MATLAB. The stimuli were presented on an LCD monitor (resolution: 1920 × 1080, refresh rate: 60 Hz) during behavioral training, at a viewing distance of 90 cm in a dark room. During the fMRI scans, stimuli were projected to a screen via a MR-compatible LCD projector (PT-011, Jiexin Technology Co., Ltd., Shenzhen, China) with the same resolution and refresh rate as the LCD monitor during behavioral training. Participants viewed the screen via an angled mirror attached to the head coil at a viewing distance of 115 cm. Angular stimulus size was the same across behavioral and fMRI sessions.

The orientation stimuli were square-wave gratings (1.3 cycles per deg, duty cycle: 10%) in a circular aperture (inner radius: 1.5°; outer radius: 6°). The gratings flashed on a gray background at 10 Hz, alternating between black and white. There were two types of stimuli: two overlapping gratings orientated

leftward (~135°) and rightward (~45°), or a single grating with one of the two orientations (~135° or ~45°).

Here, we refer to the 45° and 135° orientations as the reference orientations. The impulse stimulus was a

high-contrast, white (at the maximum projector output level) circular disk that covered the same area as the

orientation stimulus (radius: 6°).

Experimental Procedures and Tasks

Each participant completed at least two fMRI sessions on different days. One session was used for defining

ROIs (see Definition of Regions of Interests), while the remaining sessions were used for the main

experiment (see Attention task and Perception task). Before the scanning sessions, participants were trained

to familiarize with the tasks in a separate behavioral session. The procedures and tasks were similar to our

previous work (Jigo et al., 2018; Gong et al., 2022).

Attention task. We used a cueing paradigm (Fig 1A). Each trial began with a color cue (red or green)

for 0.5 s to indicate the reference orientation of the upcoming target (leftward vs. rightward orientation). In

the No-Ping session, the cue was followed by a blank display during the preparation period; in the Ping

session, a task-irrelevant, high-luminance visual impulse ("ping", 0.1 s) occurred at either 0.5 s (for short

delays of 1.5 s and 3.5 s) or 2.5 s (for long delays of 5.5 s and 7.5 s) after the onset of the cue display. The

orders of these sessions were counterbalanced across participants who completed both. Following the

preparatory period, two superimposed gratings were then shown for 1 s. The target grating was shown with

a small angular offset with respect to the cued reference orientation, whereas the distractor grating was

shown in the uncued reference orientation (e.g., if rightward orientation was cued, the rightward grating

was shown in 45°± d and the leftward grating was shown in 135°). Note that the angular offset was

determined individually based on the threshold obtained during the training session (at least 3 blocks, 30

trials/block), using a staircase procedure (Best Parameter Estimation by Sequential Testing, Best PEST), as

implemented in the Palamedes Toolbox (Prins & Kingdom, 2009). Participants used a keypad to report

whether the attended orientation was more leftward or rightward relative to the reference orientation. Each

trial was separated by an inter-trial interval of 3 s to 7 s (2 s per step). Trial-by-trial feedback ("correct" or

"incorrect") was provided in the training session but not during scanning. Instead, the percentage of correct

responses was provided at the end of each run in the scanning session to avoid the impact of trial-level

feedback on neural activity.

Given the need to maximize the number of trials for fMRI-based MVPA, we could not accomodate

additional conditions (e.g., neutral cue) to measure the behavioral effects of attention. However, our prior

work using similar feature cueing paradigms (Liu et al., 2007; Jigo et al., 2018) found that attentional cueing

improved behavioral performance relative to a neutral condition. Thus, it is highly likely that our well-

trained participants used the cue to direct their attention in the fMRI experiment. Furthermore, our neural

measures of attentional signals revealed feature-specific attentional modulations, further validating our

approach. To prevent the cue-related sensory difference from contributing to neural activity, we reversed

the mapping between colors and orientations halfway through the experiment (e.g., red indicated "attend

leftward orientation" and green indicated "attend rightward orientation" in the first half of the runs, and

vice versa for the second half of the runs), with the order counterbalanced across subjects. The mapping of

colors and orientations was reversed only once in the middle of the experiment to prevent misremembering

of the color-orientation associations. To reduce temporal expectancy over a fixed period, the preparatory

period (i.e., cue-to-stimulus interval) varied from 1.5 s to 7.5 s with different probabilities (10% for 1.5 s

or 3.5 s each, 40% for 5.5 s or 7.5 s each). The long-delay trials (5.5 s or 7.5 s) were selected for subsequent

analyses, as they allow the separation of the preparatory activity from the grating-evoked response during

fMRI scanning. The short-delay trials were included to encourage a sustained maintenance of attention

throughout the entire preparation period.

Perception task. On each trial of the perception task (Fig 1B), a single grating was shown for 1 s,

followed by an inter-trial interval between 3 s to 7 s. To equate the sensory inputs between attention and

perception tasks, the orientation was shifted away from the reference orientation by the same angular offset

as that used in the attention task with each individual participant's own threshold. Participants performed

the same orientation discrimination task by comparing the single orientation to the reference orientation.

We provided the percentage of correct responses at the end of each run as feedback.

Eye Tracking and Analysis

To evaluate the stability of visual fixation, we used Eyelink Portable Duo system (SR Research, Ontario,

Canada) to monitor each observer's eye position during the training session at a sampling rate of 500 Hz.

One participant's data was not used due to the unstable recording of the eye. The data were then analyzed

using custom Matlab code.

To examine whether participants adopted a space-based strategy during the preparatory period in

the attention task, such as directing their gaze leftward in attend leftward trials, and vice versa for the attend

rightward trials, we analyzed the participants' eye positions recorded during the training session. Horizontal

and vertical eye positions were analyzed separately. Paired t-tests were performed to compare horizontal

and vertical eye positions between two attention conditions. A two-way mixed ANOVA (2 sessions × 2

attended orientations) was applied to the horizontal and vertical positions, respectively.

fMRI Data Acquisition

Imaging was performed on a Siemens 3T scanner (MAGNETOM Prisma, Siemens Healthcare, Erlangen,

Germany) using a 20-channel coil at Zhejiang University (Hangzhou, China). For each participant, we

acquired high-resolution T1-weighted anatomical images (field of view, 240 × 240 mm, 208 sagittal slices;

0.9 mm^3 resolution), T2*-weighted echo-planar functional images consisting of 46 slices (TR, 2 s; TE, 34

ms; flip angle, 50°; matrix size, 80 × 80; in-plane resolution, 3 × 3 mm; slice thickness, 3 mm, interleaved,

no gap) and a 2D T1-weighted anatomical image (0.8 × 0.8 × 3 mm) for aligning functional data to high-

resolution anatomical data.

fMRI Data Preprocessing

Data analyses were performed using mrTools (Gardner et al., 2018) and custom code in Matlab. For each

run, functional data were preprocessed with head motion correction, linear detrending and temporal high

pass filtering at 0.01 Hz. Data were converted to percentage signal change by dividing the time course of

each voxel by its mean signals in each run. We concatenated the 6 runs of the attention task and the 3 runs

of the perception task separately for further analysis. One of the attention runs in one subject was excluded

due to low accurate performance (<50%).

Definition of Regions of Interests (ROI)

Visual and parietal ROIs. Following previous work (Jigo et al., 2018; Gong et al., 2020b; Gong et al., 2022), for each observer, we ran a separate retinotopic mapping session to obtain ROIs in occipital and parietal areas. Observers viewed four runs of rotating wedges (i.e., clockwise and counterclockwise) and two runs of rings (i.e., expanding and contracting) to map the polar angle and radial components, respectively (DeYoe et al., 1996; Engel, 1997; Sereno et al., 1995). Borders between areas were defined as the phase reversals in a polar angle map of the visual field. Phase maps were visualized on computationally flattened representations of the cortical surface, which were generated from the high-resolution anatomical image using FreeSurfer (http://surfer.nmr.mgh.harvard.edu) and custom Matlab code.

To help identify the topographic areas in parietal areas, we ran 2 runs of memory-guided saccade task modeled after previous studies (Konen & Kastner, 2008; Schluppeck et al., 2006; Sereno et al., 2001). Observers fixated at the screen center while a peripheral (~10° radius) target dot was flashed for 500 ms. The flashed target was quickly masked by a ring of 100 distractor dots randomly positioned within an annulus (8.5° – 10.5°). The mask remained on screen for 3 s, after which participants were instructed to make a saccade to the memorized target position, then immediately saccade back to the central fixation. The position of the peripheral target shifted around the annulus from trial to trial in either a clockwise or counterclockwise order. Data from the memory-guided saccade task were analyzed using the same phase encoding method as the wedge and ring data. Therefore, the following regions of interest (ROIs) in each hemisphere were identified after the completion of this session: V1, V2, V3, V3A/B, V4, V7/IPS0, IPS1 to IPS4.

Frontal ROIs. Following previous work (Jigo et al., 2018; Gong et al., 2020b; Gong et al., 2022), we used a deconvolution approach by fitting each voxel's time series from the attention task with a general linear model (GLM) to determine the event-related activations in the brain (see Supplementary Materials: Deconvolution). For each voxel, we computed the goodness of fit measure (r^2 value), which indicates the amount of variance explained by the deconvolution model (Gardner et al., 2018). The r^2 value represents the degree to which the voxel's time series is correlated with the task events, regardless of any differential

responses among conditions. Based on the task-related activation (as indexed by r^2 value) and anatomical

criteria, we defined two frontal areas in each hemisphere that were active during the attention task: one is

located superior to the precentral sulcus and near the superior frontal sulcus (FEF) and the other is located

towards the inferior precentral sulcus, close to the junction with the inferior frontal sulcus (IFJ).

Groups of Region. To characterize the patterns of neural response across cortical hierarchy and

streamline data presentation, we grouped results from the nine areas into four groups based on functional

and anatomical considerations: primary visual cortex (V1); extrastriate visual cortex (EVC), consisting of

V2, V3, V3ab and V4; IPS, consisting of IPS0 to IPS4; prefrontal cortex (PFC), consisting of FEF and IFJ.

Individual areas within each group exhibited qualitatively similar results.

Note that we analyzed V1 separately for two reasons. First, previous studies consistently identify

V1 as the main locus of sensory-like templates during feature-specific preparatory attention (Kok et al.,

2014; Aitken et al., 2020). Second, V1 shows the strongest orientation selectivity within the visual hierarchy

(Priebe, 2016). In contrast, the extrastriate visual cortex (EVC; comprising V2, V2, V3AB and V4)

demonstrates broader selectivity for complex features (Grill-Spector & Malach, 2004). Therefore, it would

be particularly informative to analyze V1 separately for our orientation-based attention paradigm.

Multivoxel Pattern Analysis (MVPA)

Decoding of attended orientation. To test if multivariate patterns of activity represent information

of the attended orientation, separate MVPA analyses were applied on the activity patterns for the

preparation and stimulus selection periods. Following previous work (Jigo et al., 2018; Gong et al., 2020b;

Gong et al., 2022), for this analysis, we extracted fMRI signals from raw time series in the long delay trials

with correct behavioral responses (~72 trials per attention condition); short delay trials were excluded as

they could not provide enough data points to measure preparatory activity. We then obtained averaged

BOLD response in a 2 s window for each voxel and each trial in a given ROI, separately for preparatory

activity (4 to 6 s after the onset of the cue) and stimulus-evoked activity (4 to 6 s after the onset of the

gratings). The response amplitudes across two attention conditions in each ROI were further z-normalized,

separately for the preparation and stimulus-related activity. These normalized single-trial BOLD responses

were used for the MVPA. We trained a classifier using the Fisher linear discriminant (FLD) analysis to

discriminate between two attended orientations (leftward vs. rightward) and tested its performance with a

leave-one-run-out cross-validation scheme. This process was repeated until each run was tested once and

the decoding accuracy (i.e., the proportion of correctly classified trials) was averaged across the cross-

validation folds. The statistical significance of decoding accuracy was evaluated by comparing it to the

chance level obtained from a permutation test (see Permutation test). To assess if the decoding accuracy

differed between No-Ping and Ping experiments, we performed two-way mixed ANOVAs (2 sessions × 4

regions) on the decoding accuracy.

Cross-task generalization from the perception task to attention task. Following previous work

(Jigo et al., 2018; Gong et al., 2022), to test whether the neural patterns in the preparatory and stimulus

selection periods from the attention task reflected sensory processing of isolated features, we trained an

FLD classifier using the normalized BOLD responses from the perception task (4 to 6 s after the trial onset)

to discriminate leftward vs. rightward orientation. Then, we tested this classifier on the normalized response

from the independent runs of attention task to discriminate between attend leftward vs. attend rightward

orientations, separately for preparation and stimulus selection periods. The significance of decoding

accuracy was compared to the chance level obtained from a permutation test (see Permutation test). To

assess if the generalization performance differed between No-Ping and Ping sessions, we performed two-

way mixed ANOVAs (2 sessions × 4 regions) on the decoding accuracy.

Neural distance between attended and perceived orientations. The decoding accuracy from the

cross-task generalization test reflects a discretized readout of the pattern similarity between different

conditions. However, employing continuous similarity measures, such as Mahalanobis distance

(Mahalanobis, 1936), could be more reliable compared to decoding accuracy (Walther et al., 2016).

Therefore, we calculated the Mahalanobis distance to quantify the pattern similarity between two attended

orientations and two perceived orientations. For each participant and each ROI, we have M points (i.e., M

trials for each attended orientation) in the N-dimensional space (N = 100, number of voxels). For each data

point in the attended orientation condition, we computed its distance to each of the orientation distributions

(from the perception task). Averaged distance values were then calculated for each combination of attended

orientation and perceived orientation pairs. A sensory-like hypothesis would predict smaller distance

between the distribution of the attended orientation (e.g., attend leftward) and the distribution of

corresponding orientation (e.g., perceive leftward) compared to the alternative orientation (e.g., perceive

rightward). Two-way repeated-measures ANOVA (2 attended orientations × 2 perceived orientations) was

applied on the Mahalanobis distance, separately for each region and each session.

Neural-behavioral relationships. We tested if the representation format during preparatory

attention was associated with subsequent behavior. For each trial, we calculated the Mahalanobis distance

between the attention conditions (attend leftward and attend rightward) and the perceived orientations

(leftward and rightward orientation). We estimated the attentional modulation index (AMI) based on these

distance values. This index measures how much attention modulated the pattern similarity for the Same

orientation condition (e.g., attend and perceive the same orientation) relative to the Different orientation

condition (e.g., attend and perceive different orientations). The index was calculated as follows: AMI =

$(D_{different} - D_{same})/(D_{different} + D_{same})$, where D_{same} and $D_{different}$ are the measured distance (D) in the Same and

Different orientation condition, respectively. Next, we tested the behavioral relevance of AMI in two ways:

(1) Inter-subject analysis: correlated AMI with RT and accuracy across participants, separately for each

session; (2) Within-subject analysis: for each participant, we sorted the single-trial AMI values in

descending order and selected top-ranked 25% trials and bottom-ranked 25% trials to represent "strong

modulation" and "weak modulation" trials, respectively. We then extracted behavioral responses on these

selected trials and calculated RT and accuracy for each trial type. Paired t-tests were used to compare

between "strong modulation" and "weak modulation" trials in each session.

Informational connectivity analysis. We used Informational Connectivity (IC) to examine shared

changes in pattern discriminability over time, a method that allows inference based on multivoxel pattern

information rather than overall BOLD response (Jia et al., 2020; Ng et al., 2021). To track the flow of

multivariate information across time (i.e., across trials), we measured the fluctuations (covariance) in

pattern-based discriminability by calculating the Mahalanobis distance of each trial to the two attended

orientations, using a leave-one-run-out cross-validation scheme. For each ROI, we calculated the

Mahalanobis distance between the pattern of activity for each attention trial from one left-out run and the

distribution of each attended orientation of the remaining runs. To quantify the degree of attentional

modulation, we calculated the AMI using the same formula as mentioned above, where D_{same} and $D_{different}$

are the measured distance (D) in the Same and Different condition. This index measures how much the

pattern similarity increased for the same attention condition (e.g., attend leftward to attend leftward) relative

to the different attention condition (e.g., attend leftward to attend rightward). A positive AMI indicates

relative proximity to the same attention condition, whereas a negative AMI indicates relative proximity to

the different attention condition. A time course of AMI values was generated across runs and pairwise

correlated between ROIs using Pearson correlation analysis and Fisher z-transformed. Independent t-tests

were used to compare the connectivity between No-Ping and Ping sessions. To assess the relationship

between ICs and behavior, we correlated ICs with RT and accuracy across participants, separately for each

session.

Permutation test to evaluate classifier performance

Following previous work (Jigo et al., 2018; Gong et al., 2022), for each brain area, we evaluated the

statistical significance of the observed decoding accuracy using a permutation test scheme. We first shuffled

the trial labels in the training data and trained the same FLD classifier on the shuffled data. We then tested

the classifier on the (unshuffled) test data to obtain decoding accuracy. For each ROI and each participant,

we repeated this procedure 1000 times to compute a null distribution of decoding accuracy. To compute

the group-level significance, we averaged the 20 null distributions to obtain a single null distribution of

1000 values for each ROI. To determine if the observed decoding accuracy significantly exceeds the chance

level, we compared the observed value to the 95 percentiles of this group-level distribution (corresponding

to $p = 0.05$). Note that these ROIs were pre-defined with strong priors as their activation in attention tasks

has been consistently reported in the literature. Nevertheless, for those analyses where multiple comparisons

were performed across regions, we applied a Bonferroni-correction to adjust the p-values.

Bayesian analysis

To evaluate the strength of evidence for the null hypothesis, we conducted Bayesian analyses (Wagenmakers, 2007) using standard priors as implemented in JASP Version 0.17.1 (JASP Team, 2023). We performed Bayesian t-tests and computed Bayes factor (BF_{01}) to compare between two attention conditions (attend leftward vs. attend rightward). Additionally, we used Bayesian repeated-measures ANOVA and computed the exclusion Bayes factors (BF_{excl}) to assess the evidence for excluding specific effects across all models. A Bayes factor (BF) greater than 1 provides support for the null hypothesis. Specifically, a BF between 1 and 3 indicates weak evidence, a BF between 3 and 10 indicates moderate evidence, and a BF greater than 10 indicates strong evidence (Van Doorn et al., 2021).

Approach to handle partially overlapped samples

Our study used partially overlapping samples, with 14 out of 20 participants completing both No-Ping and Ping sessions, while the remainder completed one of the two sessions. The most important analyses entailed assessing whether decoding accuracy was above chance, for which we used the permutation-based method (see above) within each session. Thus, these analyses were unaffected by the partially overlapping samples. In a few analyses where we compared across sessions, we used statistical tests treating "session" as a between-subject factor. We believe this is a reasonable approach, as a between-subject test is more conservative than a within-subject test, such that any significant effect emerged should be a genuine effect. To be certain, we also conducted additional analyses with "session" as a within-subject factor on the subset of data from the 14 participants who completed both sessions in a counterbalanced order. The results were highly similar to those reported in the main text.

References

Aitken, F., Menelaou, G., Warrington, O., Koolschijn, R. S., Corbin, N., Callaghan, M. F., & Kok, P.

(2020). Prior expectations evoke stimulus-specific activity in the deep layers of the primary visual

cortex. *PLOS Biology*, *18*(12), e3001023. https://doi.org/10.1371/journal.pbio.3001023

Bettencourt, K. C., & Xu, Y. (2016). Decoding the content of visual short-term memory under distraction

in occipital and parietal areas. *Nature Neuroscience*, 19(1), 150-157. https://doi.org/10.1038/nn.4174

Baldauf, D., & Desimone, R. (2014). Neural mechanisms of object-based attention. *Science*, *344*(6182),

424–427. https://doi.org/10.1126/science.1247003

Barbosa, J., Lozano-Soldevilla, D., & Compte, A. (2021). Pinging the brain with visual impulses reveals

electrically active, not activity-silent, working memories. *PLOS Biology*, *19*(10), e3001436.

https://doi.org/10.1371/journal.pbio.3001436

Battistoni, E., Stein, T., & Peelen, M. V. (2017). Preparatory attention in visual cortex. *Annals of the New*

York Academy of Sciences, *1396*(1), 92-107. https://doi.org/10.1111/nyas.13320

Brainard, D. H. (1997). The psychophysics toolbox. *Spatial Vision*, *10*(4), 433–436.

https://doi.org/10.1163/156856897X00357

Bressler, S. L., Tang, W., Sylvester, C. M., Shulman, G. L., & Corbetta, M. (2008). Top-down control of

human visual cortex by frontal and parietal cortex in anticipatory visual spatial attention. *The*

Journal of Neuroscience, *28*(40), 10056–10061. https://doi.org/10.1523/JNEUROSCI.1776-08.2008

Corbetta, M., & Shulman, G. L. (2002). Control of goal-directed and stimulus-driven attention in the

brain. *Nature Reviews Neuroscience*, *3*(3), 201–215. https://doi.org/10.1038/nrn755

Desimone, R., & Duncan, J. (1995). Neural mechanisms of selective visual attention. *Annual Review of*

Neuroscience, *18*(1), 193–222. https://doi.org/10.1146/annurev.ne.18.030195.001205

DeYoe, E. A., Carman, G. J., Bandettini, P., Glickman, S., Wieser, J., Cox, R., Miller, D., & Neitz, J.

(1996). Mapping striate and extrastriate visual areas in human cerebral cortex. *Proceedings of the*

National Academy of Sciences, *93*(6), 2382–2386. https://doi.org/10.1073/pnas.93.6.2382

722 Duncan, D. H., van Moorselaar, D., & Theeuwes, J. (2023). Pinging the brain to reveal the hidden

723   attentional priority map using encephalography. *Nature Communications*, *14*(1), 4749.

724   https://doi.org/10.1038/s41467-023-40405-8

725 Engel, S. (1997). Retinotopic organization in human visual cortex and the spatial precision of functional

726   MRI. *Cerebral Cortex*, *7*(2), 181–192. https://doi.org/10.1093/cercor/7.2.181

727 Faul, F., Erdfelder, E., Lang, A. G., & Buchner, A. (2007). G*Power 3: A flexible statistical power

728   analysis program for the social, behavioral, and biomedical sciences. *Behavior Research Methods*,

729   *39*(2), 175–191. https://doi.org/10.3758/BF03193146

730 Gardner, J. L., Merriam, E. P., Schluppeck, D., Besle, J., & Heeger, D. J. (2018). mrTools: Analysis and

731   visualization package for functional magnetic resonance imaging data (Version 4.7) [Computer

732   software]. Zenodo. https://doi.org/10.5281/ZENODO.1299483

733 Gong, M., Chen, Y., & Liu, T. (2022). Preparatory attention to visual features primarily relies on non-

734   sensory representation. *Scientific Reports*, *12*(1), 21726. https://doi.org/10.1038/s41598-022-26104-

735   2

736 Gong, M., & Liu, T. (2020a). Biased neural representation of feature-based attention in the human

737   frontoparietal network. *Journal of Neuroscience*, *40*(43), 8386-8395.

738   https://doi.org/10.1523/JNEUROSCI.0690-20.2020

739 Gong, M., & Liu, T. (2020b). Continuous and discrete representations of feature-based attentional priority

740   in human frontoparietal network. *Cognitive Neuroscience*, *11*(1–2), 47–59.

741   https://doi.org/10.1080/17588928.2019.1601074

742 Grill-Spector, K., & Malach, R. (2004). The human visual cortex. *Annual Review of Neuroscience*, *27*(1),

743   649-677. https://doi.org/10.1146/annurev.neuro.27.070203.144220

744 Grubert, A., & Eimer, M. (2018). The time course of target template activation processes during

745   preparation for visual search. *The Journal of Neuroscience*, *38*(44), 9527–9538.

746   https://doi.org/10.1523/JNEUROSCI.0409-18.2018

Guo, F., Preston, T. J., Das, K., Giesbrecht, B., & Eckstein, M. P. (2012). Feature-independent neural

coding of target detection during search of natural scenes. *Journal of Neuroscience*, *32*(28), 9499–

9510. https://doi.org/10.1523/JNEUROSCI.5876-11.2012

Hamblin-Frohman, Z., & Becker, S. I. (2021). The attentional template in high and low similarity search:

Optimal tuning or tuning to relations? *Cognition*, *212*, 104732.

https://doi.org/10.1016/j.cognition.2021.104732

Harrison, S. A., & Tong, F. (2009). Decoding reveals the contents of visual working memory in early

visual areas. *Nature*, *458*(7238), 632-635. https://doi.org/10.1038/nature07832

Hout, M. C., & Goldinger, S. D. (2015). Target templates: The precision of mental representations affects

attentional guidance and decision-making in visual search. *Attention, Perception, & Psychophysics*,

77(1), 128–149. https://doi.org/10.3758/s13414-014-0764-6

Hout, M. C., Robbins, A., Godwin, H. J., Fitzsimmons, G., & Scarince, C. (2017). Categorical templates

are more useful when features are consistent: Evidence from eye movements during search for

societally important vehicles. *Attention, Perception, & Psychophysics*, *79*(6), 1578–1592.

https://doi.org/10.3758/s13414-017-1354-1

JASP Team. (2023). JASP (Version 0.17.1) [Computer software]. https://jasp-stats.org/

Jia, K., Goebel, R., & Kourtzi, Z. (2023). Ultra-high field imaging of human visual cognition. *Annual*

Review of Vision Science, *9*(1), 479–500. https://doi.org/10.1146/annurev-vision-111022-123830

Jia, K., Zamboni, E., Kemper, V., Rua, C., Goncalves, N. R., Ng, A. K. T., Rodgers, C. T., Williams, G.,

Goebel, R., & Kourtzi, Z. (2020). Recurrent processing drives perceptual plasticity. *Current Biology*,

30(21), 4177-4187.e4. https://doi.org/10.1016/j.cub.2020.08.016

Jia, K., Wang, M., Steinwurzel, C., Ziminski, J. J., Xi, Y., Emir, U., & Kourtzi, Z. (2024). Recurrent

inhibition refines mental templates to optimize perceptual decisions. *Science Advances*, *10*(31),

eado7378. https://doi.org/10.1126/sciadv.ado7378

Jigo, M., Gong, M., & Liu, T. (2018). Neural determinants of task performance during feature-based

attention in human cortex. *eNeuro*, *5*(1), 1–15. https://doi.org/10.1523/ENEURO.0375-17.2018

Kastner, S., Pinsk, M. A., De Weerd, P., Desimone, R., & Ungerleider, L. G. (1999). Increased activity in

human visual cortex during directed attention in the absence of visual stimulation. *Neuron*, *22*(4),

751–761. https://doi.org/10.1016/S0896-6273(00)80734-5

Kerzel, D. (2019). The precision of attentional selection is far worse than the precision of the underlying

memory representation. *Cognition*, *186*, 20–31. https://doi.org/10.1016/j.cognition.2019.02.001

Kleiner, M., Brainard, D., & Pelli, D. (2007). What's new in Psychtoolbox-3? *Perception*, *36*, 1–16.

Kok, P., Failing, M. F., & De Lange, F. P. (2014). Prior expectations evoke stimulus templates in the

primary visual cortex. *Journal of Cognitive Neuroscience*, *26*(7), 1546–1554.

https://doi.org/10.1162/jocn_a_00562

Konen, C. S., & Kastner, S. (2008). Representation of eye movements and stimulus motion in

topographically organized areas of human posterior parietal cortex. *Journal of Neuroscience*, *28*(33),

8361–8375. https://doi.org/10.1523/JNEUROSCI.1930-08.2008

Kong, G., Alais, D., & Van Der Burg, E. (2017). Orientation categories used in guidance of attention in

visual search can differ in strength. *Attention, Perception, & Psychophysics*, *79*(8), 2246–2256.

https://doi.org/10.3758/s13414-017-1387-5

Lewis-Peacock, J. A., Drysdale, A. T., & Postle, B. R. (2015). Neural evidence for the flexible control of

mental representations. *Cerebral Cortex*, *25*(10), 3303–3313. https://doi.org/10.1093/cercor/bhu130

Liu, T., Larsson, J., & Carrasco, M. (2007). Feature-based attention modulates orientation-selective

responses in human visual cortex. *Neuron*, 55(2), 313-323.

https://doi.org/10.1016/j.neuron.2007.06.030

Liu, T., & Hou, Y. (2013). A hierarchy of attentional priority signals in human frontoparietal cortex.

Journal of Neuroscience, *33*(42), 16606–16616. https://doi.org/10.1523/JNEUROSCI.1780-13.2013

Mahalanobis, P. C. (1936). On the generalised distance in statistics. *Proceedings of the National Institute

of Sciences of India, 2*, 49-55.

Malcolm, G. L., & Henderson, J. M. (2009). The effects of target template specificity on visual search in

real-world scenes: Evidence from eye movements. *Journal of Vision*, *9*(11), 8–8.

https://doi.org/10.1167/9.11.8

Mongillo, G., Barak, O., & Tsodyks, M. (2008). Synaptic theory of working memory. *Science*,

319(5869), 1543–1546. https://doi.org/10.1126/science.1150769

Myers, N. E., Walther, L., Wallis, G., Stokes, M. G., & Nobre, A. C. (2015). Temporal dynamics of

attention during encoding versus maintenance of working memory: complementary views from

event-related potentials and alpha-band oscillations. *Journal of Cognitive Neuroscience*, *27*(3), 492–

508. https://doi.org/10.1162/jocn_a_00727

Ng, A. K. T., Jia, K., Goncalves, N. R., Zamboni, E., Kemper, V. G., Goebel, R., Welchman, A. E., &

Kourtzi, Z. (2021). Ultra-High-Field neuroimaging reveals fine-scale processing for 3D perception.

The Journal of Neuroscience, *41*(40), 8362–8374. https://doi.org/10.1523/JNEUROSCI.0065-

21.2021

Peelen, M. V., & Kastner, S. (2011). A neural basis for real-world visual search in human

occipitotemporal cortex. *Proceedings of the National Academy of Sciences of the United States of*

America, *108*(29), 12125–12130. https://doi.org/10.1073/pnas.1101042108

Priebe, N. J. (2016). Mechanisms of orientation selectivity in the primary visual cortex. *Annual Review of*

Vision Science, *2*(1), 85-107. https://doi.org/10.1146/annurev-vision-111815-114456

Prins, N., & Kingdom, F. A. A. (2009). Palamedes: Matlab routines for analyzing psychophysical data.

http://www.palamedestoolbox.org

Rademaker, R. L., & Serences, J. T. (2017). Pinging the brain to reveal hidden memories. *Nature*

Neuroscience, 20(6), 767-769. https://doi.org/10.1038/nn.4560

Rademaker, R. L., Chunharas, C., & Serences, J. T. (2019). Coexisting representations of sensory and

mnemonic information in human visual cortex. *Nature Neuroscience*, *22*(8), 1336-1344.

https://doi.org/10.1038/s41593-019-0428-x

Rosenberg, M. D., Scheinost, D., Greene, A. S., Avery, E. W., Kwon, Y. H., Finn, E. S., Ramani, R., Qiu,

M., Constable, R. T., & Chun, M. M. (2020). Functional connectivity predicts changes in attention

observed across minutes, days, and months. *Proceedings of the National Academy of Sciences*,

117(7), 3797–3807. https://doi.org/10.1073/pnas.1912226117

Rungratsameetaweemana, N., & Serences, J. T. (2019). Dissociating the impact of attention and

expectation on early sensory processing. *Current Opinion in Psychology*, *29*, 181–186.

https://doi.org/10.1016/j.copsyc.2019.03.014

Schluppeck, D., Curtis, C. E., Glimcher, P. W., & Heeger, D. J. (2006). Sustained activity in topographic

areas of human posterior parietal cortex during memory-guided saccades. *The Journal of

Neuroscience*, *26*(19), 5098–5108. https://doi.org/10.1523/JNEUROSCI.5330-05.2006

Schneegans, S., & Bays, P. M. (2017). Restoration of fMRI decodability does not imply latent working

memory states. *Journal of Cognitive Neuroscience*, *29*(12), 1977–1994.

https://doi.org/10.1162/jocn_a_01180

Scolari, M., Byers, A., & Serences, J. T. (2012). Optimal deployment of attentional gain during fine

discriminations. *The Journal of Neuroscience*, *32*(22), 7723–7733.

https://doi.org/10.1523/JNEUROSCI.5558-11.2012

Serences, J. T., Ester, E. F., Vogel, E. K., & Awh, E. (2009). Stimulus-specific delay activity in human

primary visual cortex. *Psychological Science*, *20*(2), 207-214. https://doi.org/10.1111/j.1467-

9280.2009.02276.x

Sereno, M. I., Dale, A. M., Reppas, J. B., Kwong, K. K., Belliveau, J. W., Brady, T. J., Rosen, B. R., &

Tootell, R. B. H. (1995). Borders of multiple visual areas in humans revealed by functional magnetic

resonance imaging. *Science*, *268*(5212), 889–893. https://doi.org/10.1126/science.7754376

Sereno, M. I., Pitzalis, S., & Martinez, A. (2001). Mapping of contralateral space in retinotopic

coordinates by a parietal cortical area in humans. *Science*, *294*(5545), 1350–1354.

https://doi.org/10.1126/science.1063695

Sheremata, S. L., Somers, D. C., & Shomstein, S. (2018). Visual short-term memory activity in parietal

lobe reflects cognitive processes beyond attentional selection. *Journal of Neuroscience*, 38(6), 1511-

1519. https://doi.org/10.1523/JNEUROSCI.1716-17.2017

Stokes, M. G. (2015). 'Activity-silent' working memory in prefrontal cortex: A dynamic coding

framework. *Trends in Cognitive Sciences*, *19*(7), 394–405. https://doi.org/10.1016/j.tics.2015.05.004

Stokes, M. G., Muhle-Karbe, P. S., & Myers, N. E. (2020). Theoretical distinction between functional

states in working memory and their corresponding neural states. *Visual Cognition*, *28*(5–8), 420–

432. https://doi.org/10.1080/13506285.2020.1825141

Stokes, M., Thompson, R., Nobre, A. C., & Duncan, J. (2009). Shape-specific preparatory activity

mediates attention to targets in human visual cortex. *Proceedings of the National Academy of*

Sciences, *106*(46), 19569–19574. https://doi.org/10.1073/pnas.0905306106

Summerfield, C., & De Lange, F. P. (2014). Expectation in perceptual decision making: Neural and

computational mechanisms. *Nature Reviews Neuroscience*, *15*(11), 745–756.

https://doi.org/10.1038/nrn3838

Summerfield, C., & Egner, T. (2009). Expectation (and attention) in visual cognition. *Trends in Cognitive*

Sciences, *13*(9), 403–409. https://doi.org/10.1016/j.tics.2009.06.003

Summerfield, C., & Egner, T. (2016). Feature-based attention and feature-based expectation. *Trends in*

Cognitive Sciences, *20*(6), 401–404. https://doi.org/10.1016/j.tics.2016.03.008

Van Doorn, J., Van Den Bergh, D., Böhm, U., Dablander, F., Derks, K., Draws, T., Etz, A., Evans, N. J.,

Gronau, Q. F., Haaf, J. M., Hinne, M., Kucharský, Š., Ly, A., Marsman, M., Matzke, D., Gupta, A.

R. K. N., Sarafoglou, A., Stefan, A., Voelkel, J. G., & Wagenmakers, E. J. (2021). The JASP

guidelines for conducting and reporting a Bayesian analysis. *Psychonomic Bulletin & Review*, *28*(3),

813–826. https://doi.org/10.3758/s13423-020-01798-5

Wagenmakers, E. J. (2007). A practical solution to the pervasive problems ofp values. *Psychonomic*

Bulletin & Review, *14*(5), 779–804. https://doi.org/10.3758/BF03194105

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016). Reliability of

dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, *137*, 188–200.

https://doi.org/10.1016/j.neuroimage.2015.12.012

Wen, T., Duncan, J., & Mitchell, D. J. (2019). The time-course of component processes of selective

attention. *NeuroImage*, *199*, 396–407. https://doi.org/10.1016/j.neuroimage.2019.05.067

Wolfe, J. M. (2021). Guided Search 6.0: An updated model of visual search. *Psychonomic Bulletin &*

Review, *28*(4), 1060–1092. https://doi.org/10.3758/s13423-020-01859-9

Wolfe, J. M., Friedman-Hill, S. R., Stewart, M. I., & O'Connell, K. M. (1992). The role of categorization

in visual search for orientation. *Journal of Experimental Psychology: Human Perception and*

Performance, *18*(1), 34–49. https://doi.org/10.1037/0096-1523.18.1.34

Wolff, M. J., Ding, J., Myers, N. E., & Stokes, M. G. (2015). Revealing hidden states in visual working

memory using electroencephalography. *Frontiers in Systems Neuroscience*, *9,* 123.

https://doi.org/10.3389/fnsys.2015.00123

Wolff, M. J., Jochim, J., Akyürek, E. G., & Stokes, M. G. (2017). Dynamic hidden states underlying

working-memory-guided behavior. *Nature Neuroscience*, *20*(6), 864–871.

https://doi.org/10.1038/nn.4546

Wolff, M. J., Kandemir, G., Stokes, M. G., & Akyürek, E. G. (2020). Unimodal and bimodal access to

sensory working memories by auditory and visual impulses. *Journal of Neuroscience*, 40(3), 671-

681. https://doi.org/10.1523/JNEUROSCI.1194-19.2019

Yu, X., Hanks, T. D., & Geng, J. J. (2022). Attentional guidance and match decisions rely on different

template information during visual search. *Psychological Science*, *33*(1), 105–120.

https://doi.org/10.1177/09567976211032225

Yu, X., Zhou, Z., Becker, S. I., Boettcher, S. E. P., & Geng, J. J. (2023). Good-enough attentional

guidance. *Trends in Cognitive Sciences*, *27*(4), 391–403. https://doi.org/10.1016/j.tics.2023.01.007

Zhang, H., & Luo, H. (2023). Feature-specific reactivations of past information shift current neural

encoding thereby mediating serial bias behaviors. *PLOS Biology*, *21*(3), e3002056.

https://doi.org/10.1371/journal.pbio.3002056

Acknowledgements

This work was supported by National Science and Technology Innovation 2030—Major Project 2021ZD0200409, National Natural Science Foundation of China (32371087, 32300855, 3200784), Fundamental Research Funds for the Central University (226-2024-00118), a grant from the MOE Frontiers Science Center for Brain Science & Brain- Machine Integration at Zhejiang University and Non-profit Central Research Institute Fund of Chinese Academy of Medical Sciences 2023-PT310-01.

Author contributions

Original idea by K.J. and M.G. Experiment programmed by Y.C. Data collected by Y.C. Analysis programmed by Y.C., K.J. and M.G. Manuscript drafted by Y.C., T.L., and M.G. Manuscript edited and revised by T.L., J. T., K.J., and M.G.

Data Availability

All data, analyses, and task codes have been made publicly available via the Open Science Framework at https://osf.io/ghaxv/

Competing interests

The authors declare no competing interests.

Supplementary Materials

<u>**Table of Content**</u>

Supplementary Methods

S1 Fig. Univariate BOLD results

S2 Fig. Sensory decoding in the perception task

Table 1. Descriptive statistics of Mahalanobis distance during preparatory attention

S3 Fig. Relationship between attentional modulation on Mahalanobis distance and RT

S4 Fig. Mahalanobis distance during stimulus selection period

S5 Fig. Relationship between information connectivity and RT

S6 Fig. Functional connectivity analysis

S7 Fig. Analysis of eye positions

Supplementary Methods

Univariate Analysis

    Deconvolution. For the data in the attention task, we used a deconvolution approach by fitting each voxel's time series with a general linear model (GLM) with seven regressors, four corresponding to the long delay (5.5 s and 7.5 s) trials with correct responses (attended orientation × delay), two corresponding to the short delay (1.5 s and 3.5 s) trials with correct responses, and the remaining four regressors corresponding to incorrect trials for each length of the delay. Each trial was modelled by a set of twelve finite impulse response functions (FIR) after the trial onset. For the perception task data, we used a GLM with two regressors, corresponding to two features (leftward vs. rightward). Each trial was modelled by a set of eight FIR after the trial onset. The design matrix was pseudo-inversed and multiplied by the time series to obtain an estimate of the hemodynamic response (HRF) evoked by each condition. Correct trials from the attention task and all trials from the perception task were entered into further univariate and multivariate analysis.

    Attentional modulations on BOLD response. To select active voxels during the task, we discarded noisy voxels with mean responses larger than 10% signal change. Because the stimuli were presented at the center of the display, areas across two hemispheres were combined. Using the r^2 values from the deconvolution analysis to index the relevance of each voxel to the task, voxels in each brain area were sorted in descending order of their r^2 values. The top-ranked 100 voxels in each combined ROI were then selected for further analyses. The results remained highly similar when using different numbers of voxels (e.g., 80 or 120).

    To assess whether feature-based attention modulated overall BOLD response during the preparatory and stimulus selection periods, we averaged the fMRI response across voxels for long delay trials of the attention task, separately for each ROI, each attention condition and each time point. Then, we averaged a time window of 4 to 6 s after the onset of the cue to index the preparatory activity, and averaged a time window of 4 to 6 s after the onset of superimposed gratings to index the stimulus-evoked response.

To test the influence of attention in different brain regions, we applied two-way repeated-measures

ANOVAs (attended orientation × region) on BOLD response, separately for activity during preparatory and

stimulus selection periods.

Univariate Results

During the No-Ping session, when examining the group-level fMRI time courses, we observed slightly

elevated activity during the preparation period, particularly in higher-order frontoparietal areas, followed

by a robust response to the superimposed gratings (S1A Fig). To examine whether feature-based attention

modulated overall BOLD in the attention task across regions, we conducted two-way repeated-measures

ANOVAs (attended orientation × region) on the BOLD response during preparation and stimulus periods,

separately. The results showed a main effect of region in the preparation period ($F(3,57) = 6.748$; $p = 0.001$;

$\eta_p^2 = 0.262$) and stimulus periods ($F(3,57) = 38.230$; $p < 0.001$; $\eta_p^2 = 0.668$). No other effects were

significant in both periods (preparation: $ps > 0.526$; stimulus: $ps > 0.135$). These results demonstrate

stronger response in higher-order frontoparietal areas than in sensory areas. The lack of attention

modulation on BOLD response suggests that attending to specific features did not influence mean neural

activity during the preparation and stimulus selection periods. These results are consistent with our previous

studies using similar paradigms.

The presence of visual impulse during preparation in the Ping session yielded a similar time course

of neural activity (S1B Fig). Consistent with the observation in No-Ping session, two-way repeated-

measures ANOVAs revealed a main effect of region in both the preparation ($F(3,57) = 3.445$; $p = 0.023$;

$\eta_p^2 = 0.153$) and stimulus periods ($F(3,57) = 29.911$; $p < 0.001$; $\eta_p^2 = 0.612$). No other effects were

significant in both periods (preparation: $ps > 0.462$; stimulus: $ps > 0.063$). These results suggest that a

briefly presented impulse stimulus caused little changes to the neural response amplitude and promoted us

to further investigate multivariate neural activity patterns.

Fig S1. Univariate BOLD results. (A). Mean fMRI time course from four regions (V1, EVC, IPS, PFC) for No-Ping

session and (B) Ping session. The gray triangle indicates the onset of superimposed gratings. The gray area indicates

a slightly elevated response in the presence of visual impulse. Error bars denote standard error of the means.

Multivariate Results

Orientation decoding in the perception task. The decoding accuracy was significantly above-

chance across regions in both sessions ($ps < 0.004$, S2 Fig). A two-way mixed ANOVA (sessions × region)

revealed a main effect of region (F(3,114) = 84.274, $p < 0.001$, $\eta_p^2 = 0.689$), Neither the main effect of

session (F(1,38) = 1.103, $p = 0.300$, $\eta_p^2 = 0.028$; $BF_{excl} = 2.605$) nor an interaction effect was significant

(F(3,114) = 0.592, $p = 0.621$, $\eta_p^2 = 0.015$; $BF_{excl} = 5.809$).

Fig S2. Sensory decoding in the perception task. (A) Decoding of orientations in No-Ping and (B) Ping sessions.

The dashed lines represent theoretical chance level (0.5). Each dot represents one participant. Error bars denote

standard error of the means.

997    **Attentional modulation on the Mahalanobis distance during preparatory period and its**

998 **relationship with behavior.** Analysis of Mahalanobis distance showed greater pattern similarity between

999 "attend leftward" and "perceived leftward" in the Ping session in comparison to the No-Ping session during

1000 preparatory attention in visual cortex. To enhance the understanding of the data, we summarized the

1001 descriptive statistics of Mahalanobis distance (data from Fig. 3B and 3C in the main text)) in Table 1.

1002

1003 Table 1. Descriptive statistics of Mahalanobis distance during preparatory attention

V1	No-Ping session		Ping session	
	Attend leftward	Attend rightward	Attend leftward	Attend rightward
Perceive leftward	6.73	6.81	6.55	6.92
Perceive rightward	6.84	6.95	7.04	6.67
EVC				
Perceive leftward	6.17	6.15	6.07	6.20
Perceive rightward	6.14	6.04	6.27	6.17

Using the attentional modulation index (AMI = $(D_{different} - D_{same})/(D_{different} + D_{same})$, see Methods)

calculated based on trial-wise Mahalanobis distance in V1, we sorted the AMI values in a descending order

and selected the top-ranked 25% of trials (i.e., 36 trials) and bottom-ranked 25% of trials to represent

"strong modulation" and "weak modulation" trials, respectively. We then extracted behavioral responses

on these selected trials and calculated RT and accuracy for each trial type in each session. The analysis

revealed faster responses in the "strong modulation" than "weak modulation" trials in Ping session (paired

t-test: $t(19) = -2.746$, $p = 0.013$, Cohen's d = -0.614; S3B Fig), but not in the No-Ping session (paired t-test:

$t(19) = -1.487$, $p = 0.154$, Cohen's d = -0.332; S3A Fig). These effects were not observed for accuracy (*ps* >

0.163).

1013

1014   **Fig S3. Relationship between attentional modulation on Mahalanobis distance and RT.** (A) Behavioral

1015   performance (as indexed by RT) for "strong modulation" (high AMI) trials and "weak modulation" (low AMI) trials,

1016   sorted by V1 preparatory activity in the No-Ping and (B) Ping sessions. Each dot represents one subject's data. Error

1017   bars denote SEM. * $p < 0.05$

1018

Attentional modulation on the Mahalanobis distance during stimulus selection. To examine

whether the neural representations during stimulus selection periods reflect a sensory-like template, we

used two-way repeated-measures ANOVAs (attended orientation × orientation) on the Mahalanobis

distance during stimulus selection. As shown in S4 Fig, we found significant interaction effects in both the

No-Ping session (V1: $F(1,19) = 12.470$, $p = 0.002$, $\eta_p^2 = 0.396$; EVC: $F(1,19) = 26.538$, $p < 0.001$, $\eta_p^2 =$

0.583; IPS: $F(1,19) = 4.250$, $p = 0.053$, $\eta_p^2 = 0.183$; PFC: $F(1,19) = 1.557$, $p = 0.227$, $\eta_p^2 = 0.076$) and Ping

session (V1: $F(1,19) = 11.698$, $p = 0.003$, $\eta_p^2 = 0.381$; EVC: $F(1,19) = 12.742$, $p = 0.002$, $\eta_p^2 = 0.401$; IPS:

$F(1,19) = 5.227$, $p = 0.034$, $\eta_p^2 = 0.216$; PFC: $F(1,19) = 0.087$, $p = 0.771$, $\eta_p^2 = 0.005$). These results support

the predicted role of attention in selectively enhancing the representation of task-relevant features while

filtering out task-irrelevant ones, leading to neural representations that closely resembled the perception of

single features.

Fig S4. Mahalanobis distance during stimulus selection period. (A) Attentional modulation on Mahalanobis

distance in No-Ping and (B) Ping sesions. Each dot represents one participant. Error bars denote standard error of the

means. † $p < 0.06$, * $p < 0.05$, ** $p < 0.01$, *** $p < 0.001$.

1034

Correlation between information connectivity (IC) and behavior. To assess whether ICs relate

to behavior, we computed Pearson correlations between ICs and both RT and accuracy across participants,

separately for each session (S5 Fig). We observed a trend of correlations between V1-PFC connectivity and

RTs in the Ping session (r = -0.394, p = 0.086), but not in the No-Ping session (r = -0.046, p = 0.846). No

significant correlations were found between V1-IPS and RTs (ps > 0.400) or between ICs and accuracy

(ps > 0.399).

1041

1042 **Fig S5. Relationship between information connectivity and RT.** (A) Correlations between V1-PFC connectivity

1043 and RTs in the No-Ping and (B) Ping sessions. Each dot represents one subject's data. The shaded area represents the

1044 confidence intervals of the regressed lines.

1045

Pattern-based and mean BOLD-based functional connectivity. To examine whether impulse

altered network function during the stimulus selection period, we conducted a pattern-based information

connectivity analysis (as Methods and Materials), using AMI based on cross-validated Mahalanobis

distance during the stimulus selection period. We found no significant differences in functional connectivity

between No-Ping and Ping sessions (ps > 0.224; S6A Fig). To further explore whether the impulse-driven

connectivity changes during preparation were influenced by overall changes in BOLD response, we

conducted a standard functional connectivity analysis based on mean BOLD response over time. This

analysis revealed no significant changes in inter-cortical connections between the two sessions ($ps > 0.136$;

S6B Fig).

1055

1056   **Fig S6. Functional connectivity analysis.** (A) Connectivity based on multivoxel patterns during stimulus selection

1057   period: between-region connectivity in the No-Ping session and Ping session based on cross-validated Mahalanobis

1058   distance (left panel) and the differences in connectivity between the two sessions (right panel). (B) Connectivity based

1059   on mean BOLD responses over time: between-region connectivity in the No-Ping session and Ping session based on

1060   raw time series (left panel) and the differences in connectivity between the two sessions (right panel).

1061

Analysis of Eye Movement

Although participants were required to maintain stable fixation in our experiment, they might have shifted

their spatial attention differently when preparing to attend different features (e.g., eyes moved towards

leftward or rightward). To assess the potential influence of overt spatial attention in our results, we analyzed

the participants' eye position recorded during the training session and observed no significant difference

between attended features during preparation in the No-Ping ($p = 0.328$, $BF_{01} = 2.760$ for

horizontal; $p = 0.231$, $BF_{01} = 2.210$ for vertical; S7A Fig) and Ping sessions ($p = 0.450$, $BF_{01} = 3.229$ for

horizontal; $p = 0.588$, $BF_{01} = 3.675$ for vertical; paired t-tests; S7B Fig). To examine whether there were

any differences in eye movement between two sessions, a two-way mixed ANOVA (sessions × attended

orientation) was applied to the eye position data. The analyses revealed neither main effects nor an

interaction effect for the horizontal ($ps > 0.222$, $BF_{excl} > 1.593$) and vertical eye movements ($ps > 0.158$,

$BF_{excl} > 1.185$). We note that we only collected eye-tracking data during behavioral training and not during

scanning due to technical limitations. However, it seems unlikely that the participants would adopt a

different eye fixation strategy after training, especially given the centrally presented stimulus configuration

that made eye movement an ineffective strategy.

1077

1078 **Fig S7. Analysis of eye positions**. (A) Group-level horizontal eye position and (B) vertical eye position for the

1079 preparation period during behavioral training in No-Ping and Ping sessions. Each dot represents one participant. Error

1080 bars denote standard error of the means.