Interpretable high-resolution dimension reduction of spatial transcriptomics data by DeepFuseNMF

Junjie Tang[1,2,9], Zihao Chen[1,9], Kun Qian[1,9], Siyuan Huang[3], Yang He[4], Shenyi Yin[5], Xinyu He[4], Buqing Ye[4], Yan Zhuang[6,7], Hongxue Meng[8,*], Jianzhong Jeff Xi[4,*], Ruibin Xi[1,10,*]

[1]School of Mathematical Sciences and Center for Statistical Science, Peking University, Beijing 100871, China

[2]School of Computer Science, Department of Computational Biology, Carnegie Mellon University, Pittsburgh, PA 15213, USA

[3]Academy for Advanced Interdisciplinary Studies, Peking University, Beijing 100871, China

[4]State Key Laboratory of Natural and Biomimetic Drugs, Department of Biomedical Engineering, College of Future Technology, Peking University, Beijing 100871, China

[5]Yangtze Center of Future Health Technology, Peking University, Beijing 100871, China

[6]Department of Colorectal, Tianjin Medical University Cancer Institute & Hospital, Tianjin 300060, China

[7]Tianjin's National Clinical Research Center for Cancer, Key Laboratory of Cancer Prevention and Therapy, Tianjin 300060, China

[8]Department of Pathology, Harbin Medical University Cancer Hospital, Harbin 150081, China

[9]These authors contributed equally

[10]Lead Contact

*Correspondence: ruibinxi@math.pku.edu.cn (R.X.), jzxi@pku.edu.cn (J.J.X.), menghongxue15@163.com (H.M.)

Abstract

Spatial transcriptomics (ST) technologies have revolutionized tissue architecture studies by capturing gene expression with spatial context. However, high-dimensional ST data often have limited spatial resolution and exhibit considerable noise and sparsity, posing significant challenges in deciphering subtle spatial structures and underlying biological activities. Here, we introduce DeepFuseNMF, a multi-modal dimension reduction framework that enhances spatial resolution by integrating ST gene

expression with high-resolution histology images. DeepFuseNMF incorporates non-negative matrix factorization into a neural network architecture, enabling the identification of interpretable, high-resolution embeddings. Furthermore, DeepFuseNMF can simultaneously analyze multiple samples and is compatible with various types of histology images. Extensive evaluations on synthetic and real ST datasets from various technologies and tissue types demonstrate that DeepFuseNMF can effectively produce highly interpretable, high-resolution embeddings, and detects refined spatial structures. DeepFuseNMF represents a powerful approach for integrating ST data and histology images, offering deeper insights into complex tissue structures and functions.

Introduction

The revolutionary spatial transcriptomics (ST) technologies have enabled the simultaneous capture of gene expression profiles and spatial locations of cells or spots within tissue samples[1-6]. These cutting-edge techniques have been widely applied across various fields to uncover complex tissue structures, organizations, and microenvironments[7-10]. However, the spatial resolution of commonly used platforms like 10X Visium remains limited. Each ST spot typically contains multiple cells, and large areas of tissue are not covered by sequencing spots. Newer technologies, such as Stereo-seq[2] and Xenium[3], achieve much higher resolution but produce much sparser and noisier data. Aggregating spots into larger meta-spots is often needed to increase the signal-to-noise ratio, which unfortunately significantly reduces spatial resolution[11].

ST data are high-dimensional and often exhibit considerable noise and sparsity, necessitating dimension reduction as a crucial step in their analysis. Since traditional dimension reduction methods do not account for spatial information, specialized methods tailored for ST data have recently been developed[12-17]. By leveraging spatial information, these methods generate spatially-aware, low-dimensional representations that better preserve spatial relationships between cells or spots. Several of these methods, such as NSFH[15] and SpiceMix[16], are based on Non-negative Matrix Factorization (NMF) and thus can provide more interpretable, parts-based representations of the high dimensional ST data. However, these available dimension reduction techniques for ST data are constrained by the resolution limitation, facing significant challenges in deciphering subtle expression patterns and complex spatial architectures. Further, when ST data contain multiple samples[18-20], spots between

samples may not have a spatial relationship. Methods that heavily rely on spatial information are not directly applicable to these multi-sample datasets.

ST data are often accompanied by high-resolution histology images, such as Hematoxylin-Eosin (H&E) stained images or immunofluorescence images, which provide valuable information about tissue morphology, cellular composition, and spatial organization at a higher resolution. Several methods that integrate ST gene expression and histology image patches around sequenced spots have been developed for dimension reduction and spatial domain detection[12, 21, 22]. To enhance spatial resolution in ST data, novel computational methods have been developed for high-resolution gene expression recovery and improved tissue architecture identification[23-28]. Nevertheless, these resolution-enhanced methods are designed to address gene expression recovery rather than dimension reduction at high resolution. Furthermore, they primarily focus on integrating H&E images, lacking support for other types of histology images, and do not support simultaneous analysis of multiple samples.

In this paper, we present DeepFuseNMF (Deep Learning Fused with NMF), a multi-modal dimension reduction framework to generate interpretable, high-resolution embeddings of ST data by leveraging histology images. DeepFuseNMF embeds the NMF of spatial gene expression into a multi-modal encoder-decoder architecture and learns high-resolution embeddings through the accurate recovery of both spatial gene expression and histology images. This versatile framework can seamlessly handle multiple samples simultaneously and support various types of histology images. We benchmarked DeepFuseNMF using 2 synthetic datasets and 12 real ST datasets from various technologies and tissue types, including 5 mouse brain datasets, 4 medulloblastoma datasets from patient-derived orthotopic xenograft (PDOX) mice, and 3 newly sequenced human colorectal cancer (CRC) datasets. These extensive benchmarking analyses demonstrated that DeepFuseNMF generates highly interpretable, high-resolution embeddings and helps uncover complex and fine spatial structures that were challenging for available methods.

Results

DeepFuseNMF fuses expression and histology image for high-resolution dimension reduction

DeepFuseNMF utilizes a multi-modal neural network that takes advantage of the high-dimensionality of transcriptomics data and the high resolution of histology image data to achieve interpretable high-resolution dimension reduction (Fig.1; Methods). The high-dimensional gene expression data enable refined functional annotations, while the histology image data help to enhance spatial resolution. After embedding learning, DeepFuseNMF can perform high-resolution downstream analyses, such as embedding-associated gene identification, high-resolution spatial domain detection, and gene expression recovery.

The DeepFuseNMF framework comprises two major components: feature representation and high-resolution embedding learning (Fig.1). (1) In the feature representation component, DeepFuseNMF independently learns a low-resolution embedding from the ST data and a pixel-wise visual feature from the image data (Fig.S1; Methods). The low-resolution embedding is learned by NMF coupled with a denoising graph convolutional network (GCN). For the image feature representation, DeepFuseNMF pretrains a multi-channel U-Net that recovers the image patches and then transfers its backbone to extract pixel-wise visual features. (2) DeepFuseNMF then leverages a multi-modal fusion encoder-decoder to learn a high-resolution embedding via simultaneously reconstructing the ST gene expression and histology images. The encoder (feature fusion module) fuses and maps the low-resolution embedding and the pixel-wise image features into a high-resolution embedding space. Then, the decoder (data reconstruction module) reconstructs gene expression and histology images based on the learned embedding. Similar to NMF, the entries of the embedding and the learnable loading matrix in the expression recovery module are all non-negative, thus allowing an interpretable parts-based high-resolution representation of the data. The reconstruction loss is a weighted sum of the losses for the gene expression and histology image reconstruction. Details of the DeepFuseNMF framework are provided in Methods.

DeepFuseNMF gives more accurate embeddings and spatial clustering in simulation

We evaluated the performance of DeepFuseNMF in comparison with available NMF-based methods, including NMF[29], NSFH[15], and SpiceMix[16], as well as Giotto[17], an interpretable dimension reduction method based on gene co-expression modules, using two simulation studies. Since these methods can only produce low-resolution embeddings, we thus included a high-resolution embedding method, TESLA+NMF, which employed TESLA[25] to recover high-resolution expression from images and then applied NMF to the imputed expression data to obtain high-resolution embeddings.

The first simulation utilized an H&E image of a mouse cerebellum for data generation (Fig.2a; Methods). The image was segmented into three regions based on manual annotation, and intensities for the embedding dimension of each region were generated. Gene expression at individual generated spots was simulated using the zero-inflated Poisson distributions, with parameters dependent on the spot's embedding intensities. We simulated different resolutions of ST data by randomly excluding spots or adjusting the spot radius. Additionally, we introduced additive noise or dropouts to simulate different levels of noise in the ST data (Methods).

In terms of the recovery of embedding intensities, DeepFuseNMF consistently demonstrated superior performance, often by a large margin compared to other methods, as measured by the mean absolute error (MAE) between the true and inferred embedding intensities (Fig. 2b; Fig. S2a, c-e; Methods). After obtaining the embedding, we proceeded to identify spatial domains by applying the K-means algorithm to the learned embedding and compared clustering accuracy using the Adjusted Rand Index (ARI) (Methods). Again, DeepFuseNMF achieved substantially higher ARIs than other methods in all simulation scenarios (Fig. 2c; Fig. S2b), demonstrating the effectiveness of DeepFuseNMF's integration of ST expression data and histology images. Figures 2d and 2e show the local embedding and clustering result from a simulation dataset (spot radius: 107 pixels) within a refined region of interest (ROI) (Fig. 2a). Even though the resolution of ST expression data was low, the spatial fine structures could still be faithfully captured by DeepFuseNMF's embedding (Fig. 2d), leading to significantly more accurate clustering than other methods (Fig. 2e), especially in the sub-regions with very fine structures (light blue boxes in Fig.2d,e).

The second simulation generated synthetic data from a human breast cancer dataset sequenced by

10X Xenium[3], which comprises single-cell expression data for 313 genes. We aggregated expressions

from neighboring single-cells to create low-resolution spot-level ST data with varying spatial

resolutions (Fig. 2f; Fig. S3a, b; Methods). Comparing the embeddings given by different methods

with the single-cell-level NMF embedding from the original Xenium dataset (Fig. S3a),

DeepFuseNMF consistently produced more accurate embeddings (Fig. S3c). To further assess

DeepFuseNMF's capability in recovering fine structures, we conducted a challenging simulation

scenario by excluding spots in three ROIs that contained local fine structures (Fig. 2g; Fig. S3d).

Although several methods could recover these local patterns when the spots in the ROIs were not

excluded, only DeepFuseNMF and TESLA+NMF were able to provide embeddings for all three ROIs

in this challenging scenario (Fig. 2g; Fig. S3e). Notably, only DeepFuseNMF could recover the local

pattern for the extremely refined ROI 3.

DeepFuseNMF robustly recovered interpretable high-resolution embeddings in mouse brain datasets

DeepFuseNMF robustly recovered interpretable high-resolution embeddings in mouse brain

datasets

We applied DeepFuseNMF to the 10X Visium ST dataset MBC-01 from an adult mouse brain coronal

section, comprising three immunohistochemistry (IHC) stained images (Fig. S4a; Methods). The

embeddings identified by DeepFuseNMF were enriched in known specific brain regions (Fig. S4). For

example, E15 was mainly enriched in isocortex layers 1, 2/3 and 4, E18 in isocortex layers 4 and 5,

and E9 in isocortex layers 6a and 6b, E10 in the dentate gyrus (DG), E14 in the pyramidal layers CA1

and CA2, E16 in the pyramidal layers CA2 and CA3 (Fig. 3a, b). Many of these embeddings were also

identified by other methods (Fig. S5). However, most embeddings given by other methods were of low

resolution. TESLA+NMF could give high-resolution embeddings, but several of its embeddings did

not correspond well to the known brain regions (e.g., TESLA+NMF's embedding dimensions E1 and

E18 in Fig. S5). Zoomed-in views of DeepFuseNMF's embedding dimensions E1 and E6 in four

selected ROIs showed that local fine structures unveiled by these embeddings were well-supported by

staining for neuron-specific nuclear binding protein (NeuN) or glial fibrillary acidic protein (GFAP)

(Fig. 3c,d). In comparison, TESLA+NMF could only identify the local fine structure in ROI 1, and

other methods could hardly detect any due to their low resolution (Fig. S6).

To further investigate the enrichment of embedding dimensions in specific brain regions, we obtained genes upregulated in different brain regions from the Allen Mouse Brain Atlas[30] and investigated their rankings in DeepFuseNMF's embedding dimensions (Methods; Supplementary Table 2). The marker genes of different brain regions ranked high in only a few embeddings, implying that the embeddings were associated with specific brain regions (Fig. 3e). For example, marker genes of olfactory areas were only enriched in embedding E20, those of cerebral nuclei in E13, and those of thalamus in E3. Isocortex markers ranked high in three embedding dimensions (E15, E18 and E9). We further obtained marker genes of the sublayers of the isocortex and found that isocortex layers 1, 2&3 and 4 were enriched in embedding E15, layer 5 in E18 and layer 6a/6b in E9 (Fig. 3f), demonstrating that E15, E18 and E9 were associated with the sublayers of the isocortex. Similarly, hippocampal formation markers were enriched in three embeddings (E10, E14 and E16), and these embeddings were associated with subregions of the hippocampal formation (Fig. 3g).

Next, we applied DeepFuseNMF to another two mouse brain coronal sections, MBC-02 and MBC-03, where MBC-02 contained two IHC images and MBC-03 contained one H&E image (Methods; Fig. S7a). Note that the image data of these two datasets differed from the image data of the previous MBC-01 dataset (Fig. S7a). We found that the embeddings learned from the MBC-02 and MBC-03 datasets aligned well with the embeddings learned from the MBC-01 dataset at high resolution (Fig. S7b), and their gene ranks were also highly correlated with embeddings learned from the MBC-01 dataset (Fig.S8a, b; Supplementary Table 2). Gene enrichment analysis further confirmed that the embeddings learned from the MBC-02 and MBC-03 datasets were associated with specific brain regions (Fig.S8c-f). In addition, we analyzed two adjacent mouse posterior brain sagittal section datasets (MPBS-01 and MPBS-02) sequenced by the 10X Visium with H&E images (Methods; Fig.S9a). Again, both slices consistently exhibited enrichment of embeddings in specific brain regions (Fig.S9b, c), marker genes of the brain regions consistently ranked high in their respective embeddings (Fig.S9d; Supplementary Table 2), and the embeddings learned from both slices showed strong correspondence (Fig.S9e). These results demonstrate that DeepFuseNMF can robustly identify high-resolution, interpretable embeddings from ST data with various types of histology images.

DeepFuseNMF identified fine-grained spatial structures in mouse brain data

Using the embeddings from the mouse brain dataset MBC-01, we performed clustering analysis to detect spatial domains (Fig.4; Fig.S10; Methods). For comparison, we further included three state-of-the-art spatial domain detection methods, iStar, SpaGCN and stLearn, that also utilized images. DeepFuseNMF, TESLA+NMF, and iStar achieved the highest spatial resolution in spatial domain detection. Although SpaGCN and stLearn also leveraged image data, their spatial resolutions still remained at the spot level. Overall, spatial domains identified by DeepFuseNMF showed better concordance with known mouse brain domains[31] compared to other methods, and this concordance was robust to the resolution parameter of the Louvain clustering algorithm (Fig. 3a; Fig.S10).

The advantage of DeepFuseNMF was particularly evident in the hippocampal formation region that contained fine-grained spatial structures (Fig. 4a, b). Only DeepFuseNMF successfully identified and clearly delineated subregions of hippocampal formation and their complex topological relationships (Fig. 4a, b). Among the low-resolution methods, stLearn and SpiceMix performed the best in detecting these local subregions. However, due to their lower resolution, the complex topological relationships between the subregions identified by these methods were much less clear. The high-resolution methods, iStar and TESLA+NMF, largely recovered the pyramidal layers CA1, CA2 & CA3, and the granule cell layer of the dentate gyrus (DG). However, iStar incorrectly separated each pyramidal layer of CA1 and the granule cell layer of DG into two clusters, TESLA+NMF misclassified many points in pyramidal layers to another cluster, and both methods merged stratum layers CA1, CA2 & CA3 and the molecular layer DG into a single cluster (Fig. 4a). Known marker genes[32, 33] of the hippocampal pyramidal layers CA1, pyramidal layers CA2 and CA3, and the granule cell layer DG were highly expressed in these three subregions identified by DeepFuseNMF (Fig. 4c; Fig. S11a). Moreover, spatial expression patterns of these genes were clearer in the recovered high-resolution expression by DeepFuseNMF than in the raw expression (Fig. 4c; Fig. S11).

DeepFuseNMF detected a thin cluster C9 located at the meninges (Fig. 4d; Fig. S12a). The meninges are important protective membranes that envelop the brain and consist of three layers: dura, arachnoid, and pia mater[34, 35]. The arachnoid and pia mater together form the leptomeninges. Beneath the pia mater lies the glia limitans, a thin membrane layer primarily composed of astrocyte end-feet[36]. Within

the meninges, a network of cerebral arteries and veins traverses inward to the brain[37, 38]. Cluster C9

highly expressed marker genes of astrocytes and major cell types in the leptomeninges[36], including

meningeal fibroblasts subtype 1 (FB1) in the pia mater, FB2, FB3 in the arachnoid mater, as well as

endothelial cells and vascular smooth muscle cells (VSMCs) within blood vessels, but not marker

genes of cell types in the dura mater (Fig. 4e; Fig. S12b,c). GFAP, the protein marker of astrocytes,

showed a higher IHC intensity in cluster C9 than in other clusters (Fig. 4f). These data suggested that

cluster C9 was composed of the leptomeninges and the glia limitans. Several other methods also

detected clusters located near the meninges (Fig. S12d). However, cluster C9 was much thinner and

exhibited higher IHC intensity of GFAP (Fig.4g) as well as higher expression levels of FB1, FB2, and

endothelial cell markers than other methods (Fig. 4h; Fig. S12e), demonstrating that C9 matched better

to the thin structure of the leptomeninges and glia limitans. These results highlight DeepFuseNMF's

capability to enhance embedding resolution and capture fine-scale spatial structures.

DeepFuseNMF recovered condition-specific embeddings across multiple tumor samples

We applied DeepFuseNMF to a 10X Visium dataset of sonic hedgehog (SHH) medulloblastoma

derived from PDOX mouse models[39]. The dataset consisted of two Palbociclib-treated samples

(Palbociclib A and B) and two untreated samples (Control C and D) (Fig. 5a). Joint analysis of these

four samples using DeepFuseNMF yielded 20 embedding dimensions (Methods): ten enriched in

normal mouse brains, five in implanted tumors and five in tumor-normal interfaces, as indicated by

their respective high intensity at the mouse, human and human-mouse mix spots, as well as their

rankings of mouse and human genes (Fig. 5a, b; Fig. S13; Supplementary Table 2). The normal

embeddings aligned well with known mouse brain structures, such as the Purkinje layer (E4), granular

layer (E8), and molecular layer (E9) in the cerebellar cortex (CBX) (Fig. 5b; Fig. S13). Astrocytes and

microglia (resident macrophages in brains) have been reported to be enriched at the tumor-mouse brain

interface[39]. Consistently, the interface embedding dimensions E11 and E15 were enriched with marker

genes of astrocytes and microglia, respectively (Fig. 5b; Fig. S13).

Hovestadt et al.[40] identified three important transcriptional signatures in SSH medulloblastoma: cell

cycle activity (SHH-A), undifferentiated progenitors (SHH-B) and differentiated neuronal-like programs (SHH-C). We found that embedding dimension E13 was enriched with SSH-A and E2F target genes, E5 with SSH-B genes, and E6 with SSH-C and neuronal differentiation genes (Fig. 5b; Fig. S14). Notably, E6 showed increased intensities in Palbociclib-treated samples compared with untreated samples. In contrast, E13 and E5 exhibited reduced intensities in Palbociclib-treated samples, and the reduction largely only occurred in the interior regions of the tumors but not at the tumor boundaries (Fig. 5c). These results were consistent with the observation that Palbociclib could enhance neuronal differentiation and reduce cell proliferation, but have less impact at tumor boundaries[39], and consistent with the fact that the CDK4/6 inhibitor Palbociclib can downregulate E2F-mediated transcription of cell cycle genes, thereby inducing G1 arrest and inhibiting cancer cell proliferation[41].

Using DeepFuseNMF's embeddings, we performed a joint cluster analysis of the four samples (Fig. S15a). As expected, normal brain regions shared highly similar clusters across all samples, while tumor regions were more heterogeneous. In tumor regions, samples with the same treatment had more shared clusters than samples with different treatments. In comparison with spatial clustering of available methods, DeepFuseNMF and SpiceMix allowed joint analysis of multiple samples, resulting in naturally aligned clusters between samples. For other methods, aligning clusters across samples was more challenging (Fig. S15a). Furthermore, DeepFuseNMF clearly characterized the ordered layers of the CBX (Fig. 5d; Fig. S15a-d), including the molecular layer (C17, C9), Purkinje layer (C13) and granular layer (C5). In comparison, other methods could not clearly delineate these layers, especially the fine Purkinje layer (black dotted area in Fig. 5d and Fig. S15b). Among the low-resolution methods, SpiceMix performed the best in detecting the CBX layers, possibly due to its ability to integrate multiple samples. Interestingly, the molecular layer cluster C17 was adjacent to tumor regions and thus more susceptible to tumor cell infiltration (Fig. S15e). Consistently, C17 was significantly enriched with human genes and exhibited higher invasion and proliferation activity compared to other normal clusters (Fig. 5e). Additionally, the C17 areas decreased in Palbociclib-treated samples compared with untreated samples, likely due to Palbociclib's effect on reducing tumor cell proliferation and invasion (Fig. S15e). These analyses demonstrate that joint high-resolution embedding learning by DeepFuseNMF can effectively capture multi-sample fine-scale structures and enable comparative analysis between multiple samples.

DeepFuseNMF depicts tumor heterogeneity and immune activities in CRC samples

We applied DeepFuseNMF to three newly profiled ST CRC samples (CRC-01, 02, 03) for spatial cluster detection. Pathologist annotations indicated that sample CRC-01 comprised four major spatial clusters: tumor, stroma, necrosis, and muscle (Fig. 6a). DeepFuseNMF identified 16 refined spatial subclusters within these broader categories, including 6 tumor, 7 stromal, 1 necrotic, and 2 muscle subclusters (Fig. 6b; Fig. S16a). Compared with spatial clusters given by available methods, clusters given by DeepFuseNMF agreed better with the H&E image (Fig. 6a-c; Fig. S16b-d; Supplementary Note 1). For example, only DeepFuseNMF accurately distinguished necrosis from tumor in ROI 1, and tumor from stroma in ROI 2 and ROI 3 (Fig. 6d; Fig. S16c).

Among the tumor clusters, T1, T2 and T3 resembled the CMS2 subtype of colorectal cancer, T6 was similar to the CMS4 subtype, and T4 and T5 appeared to be intermediate states between CMS2 and CMS4[42, 43] (Fig. S17a; Supplementary Note 1), suggesting distinct tumor spatial subclusters. Notably, in ROI 1, the tumor clusters T1 and T3 had a clear boundary on the H&E image (indicated by the blue line in Fig.6d), which were only detected by DeepFuseNMF (Fig. 6d; Fig.S16c). The H&E image showed that T1 was more enriched with fibroblast than T3 (Fig. S17b). Consistently, T1 showed significantly higher expressions of fibroblast and extracellular matrix (ECM) genes than T3 (Fig. 6e). Deconvolution analysis by RCTD[44] (Methods) also revealed lower tumor purity in T1 (0.56) compared with T3 (0.70). Further, T1 had significantly higher cancer-associated ECM[45] (C-ECM) and invasion scores (Fig. 6e), indicating that T1 might be more aggressive and invasive. In fact, genes upregulated in T1 relative to T3 were predictive of overall worse survival of colorectal patients in the TCGA data[46] (Fig. S17c). Taken together, these results supported that T1 and T3 were distinct tumor clusters with important clinical implications. Similarly, DeepFuseNMF accurately detected fine structures in sample CRC-02 (Fig. S18; Supplementary Note 1).

Sample CRC-03 was sequenced by Stereo-seq technology without a paired histology image. To apply DeepFuseNMF and other image-dependent methods, we generated a pseudo-image from the noisy subcellular Stereo-seq data (Fig. S19a; Methods). DeepFuseNMF identified 5 tumor subclusters

and 2 stroma subclusters through integrating low-resolution bin-level expression data with the pseudo-image (Fig.6f, g; Fig. S19a, b; Supplementary Note 1). Compared with other high-resolution methods iStar and TESLA+NMF (Fig. 6h; Fig. S19c), clusters given by DeepFuseNMF agreed better with the H&E image of a nearby tissue slice (Fig. 6f). For example, in an ROI (black-box region in Fig. 6f-h; Fig. S19c, d), DeepFuseNMF and spot-level methods correctly distinguished stroma and tumor regions. In contrast, iStar and TESLA+NMF misclassified large tumor regions as stroma, possibly because they were designed for integrating H&E images and may not be suitable for analyzing pseudo-image generated from Stereo-seq data.

Moreover, DeepFuseNMF identified a refined cluster S1 around the tumor boundary (Fig. 6g). Compared with the nearby stroma cluster S2, cluster S1 was more enriched with *C1QC+* macrophages[47] (Fig. 6i; Fig. S19e). *C1QC+* macrophages were known to have increased antigen-presenting activities[47]. Consistently, genes highly related to S1 were significantly enriched with antigen-presenting genes (Fig. 6j), suggesting S1's potential role in tumor-associated inflammation. Additionally, genes highly expressed in S1 were associated with overall better survival of colorectal patients in the TCGA dataset (Fig. S19f), indicating the potential clinical relevance of this refined cluster. These analyses demonstrate the superior performance of DeepFuseNMF in accurately identifying fine spatial structures of tumor samples at high resolution, even in the absence of a paired histology image.

Discussion

In this paper, we developed DeepFuseNMF which generates high-resolution, interpretable embeddings and identifies spatial structures by effectively integrating ST gene expression data with high-resolution histology images. DeepFuseNMF enables joint analysis of multiple samples and supports various types of histology images. This novel approach opens up new possibilities for uncovering fine-grained spatial patterns and biological insights that were previously unattainable due to the resolution limitations of ST technologies. Extensive benchmarking analyses using simulated and real ST datasets demonstrated that DeepFuseNMF consistently outperformed state-of-the-art methods in embedding

learning and spatial domain detection, particularly in challenging scenarios with complex spatial structures. DeepFuseNMF is comparable to available methods in terms of computational speed, but requires slightly more memory usage (Fig. S20).

Deep learning methods have been widely used for dimension reduction or clustering analysis of single-cell RNA-seq and ST data, often outperforming traditional statistics and machine learning methods[48-51]. However, their black-box nature often hinders the interpretability of the learned features, which is crucial for understanding important structures in high-dimensional single-cell RNA-seq or ST data. To address this limitation, DeepFuseNMF introduces a framework that fuses NMF with a deep neural network, enabling interpretable dimension reduction while leveraging the power of deep learning and rendering higher resolution. As demonstrated in applications to mouse brain and PDOX datasets, the learned embeddings, along with the associated genes, represented unique spatial expression patterns or known tissue structures, and could even reveal important transcriptional signatures related to tumor treatment, thus facilitating a more straightforward data interpretation. The NMF component can also be replaced with other spatially-aware dimension reduction methods, such as NSFH[15] or SpatialPCA[13], which might enable more accurate embedding estimation with spatial patterns.

Based on the high-resolution embeddings, DeepFuseNMF enables the identification of refined spatial structures. In the mouse brain data, DeepFuseNMF identified fine-grained structures in hippocampal formation and the thin structure of the leptomeninges and glia limitans (cluster C9). Beyond physical protection, the meninges play important roles in central nervous system homeostasis, development, immunity, and pathology[34, 37]. Accurate meningeal detection is crucial for understanding their diverse functions and involvement in brain health and disease. DeepFuseNMF's ability to resolve the intricate anatomy of leptomeningeal and glia limitans highlights its potential for enhancing the study of these important delicate brain structures. One potential limitation is that DeepFuseNMF could not separate the two sublayers of the leptomeninges and the glia limitans, as the pia mater and the glia limitans are extremely thin, comprising only one or two layers of cells, making their delineation highly challenging.

In CRC-01, we identified two spatially adjacent tumor clusters, T1 and T3, with significantly different levels of invasiveness and fibroblast infiltration, despite having similar copy number profiles (Fig. S17e). This suggests that the difference in invasiveness is more likely associated with varying fibroblast infiltration levels rather than genetic differences. Cancer-associated fibroblasts (CAFs) can modify ECM proteins to produce stiff and intricated fiber organization, thus increasing invasion potential and may even hinder drug delivery[52]. The presence of adjacent tumor clusters like T1 and T3, with differences in fibroblast infiltration, highlights the potential impact of CAFs on the local tumor microenvironment and the resulting heterogeneity in invasiveness. Analyzing cohorts with larger samples using DeepFuseNMF could further explore the prevalence and significance of adjacent tumor clusters with distinct fibroblast infiltration levels and their association with various tumor phenotypes.

In CRC-03, we identified a stroma cluster S1 near the tumor boundary that was enriched with *C1QC+* macrophages. Previous studies have shown that *C1QC+* macrophages are pro-inflammatory, and interact with other immune cells, particularly playing a role in recruiting or activating T cells[47]. However, we did not observe elevated expression of T cell genes in S1, suggesting that *C1QC+* macrophages' role in T cell recruitment or activation might depend on additional factors in the tumor microenvironment. Consistently, *C1QC+* macrophages could be identified in healthy individuals, again indicating that their presence alone may not be sufficient to trigger a robust T cell response[53].

DeepFuseNMF could be further improved in several directions. First, DeepFuseNMF currently requires matched ST gene expression and histology images. However, certain ST technologies, such as Stereo-seq, do not provide paired data from the same tissue slice. Extending DeepFuseNMF to handle ST data with images from adjacent tissue slices would broaden its applicability. This extension would involve simultaneous embedding learning and alignment of adjacent slices. Second, with the rapid development of ST technologies, ST datasets are becoming increasingly larger. There is an urgent need for computational methods that can effectively handle large-scale ST datasets. By leveraging information from large-scale samples, such methods could enable the identification of important spatial structures or patterns that are hard to detect with only a few samples. Third, the interpretability of DeepFuseNMF is currently achieved by extracting gene signatures for each embedding dimension, which may represent complex biological processes. Incorporating prior

knowledge of known biological pathways into DeepFuseNMF would enhance interpretability by breaking down these multifaceted processes into specific pathway-related gene signatures.

Methods

DeepFuseNMF algorithm

Data preprocessing. DeepFuseNMF takes spatial transcriptomics (ST) data and histology images as input. Let $\Omega = \{1,2,\dots,h\} \times \{1,2,\dots,w\}$ be the sequenced tissue with $h \times w$ pixels (height h, width w), $I \in \mathbb{R}^{h \times w \times c}$ be the corresponding normalized image data (scaled to $[0,1]$) with c channels within the sequenced tissue, and $X_0 \in \mathbb{R}^{N \times G_0}$ be the unique molecular identifier (UMI) count data with G_0 genes at N sequenced spots. For spot n ($n = 1,2,\dots,N$), let $S_n = \{(x,y) \in \Omega :$ (x,y) belongs to spot $n\}$ stands for the set of pixels located in this spot. For each spot, the count expression data are normalized by dividing the total UMI count of the spot, multiplying 10,000, and then transforming to the natural-log-scale. After normalization, we select the top G spatially variable genes (default $G = 3000$) with the highest Moran's I[54] for downstream analyses. The resulting gene expression matrix, $X \in \mathbb{R}^{N \times G}$, and image I are used as the preprocessed input for DeepFuseNMF.

Image feature representation learning via U-Net-DeepFuseNMF. DeepFuseNMF pretrains a neural network, U-Net-DeepFuseNMF, for ST image feature representation learning based on the U-Net architecture, a widely used architecture for semantic segmentation[55] and image restoration[56]. Specifically, U-Net-DeepFuseNMF first encodes 256×256 image patches $I \in \mathbb{R}^{256 \times 256 \times c}$, centered on given pixels from the ST images, using a series of convolution and down-sampling operations to extract multi-scale image features. This process results in a semantically rich representation $\hat{Z} \in \mathbb{R}^{16 \times 16 \times 128}$. Next, U-Net-DeepFuseNMF uses a series of convolution and up-sampling operations to gradually merge the multi-scale image features into a pixel-wise image feature representation $Z \in \mathbb{R}^{256 \times 256 \times 32}$. Finally, a convolution operation and an element-wise Sigmoid function is used to reconstruct the image patches $\tilde{I} \in \mathbb{R}^{256 \times 256 \times c}$. The training data is taken as sliding

overlapping 256×256 image patches from the ST images (15% overlap between neighboring patches). The reconstruction loss is the mean squared error (MSE) between the input and the reconstructed images, minimized by the Adam optimizer with a weight decay of 1×10^{-5}. The initial learning rate is set as 4×10^{-4} and decayed to 1×10^{-6} using the cosine annealing strategy[57]. The mini-batch size is 32, with 5000 iterations by default.

Low-resolution embedding learning. DeepFuseNMF first learns a denoised, low-resolution embedding from the ST expression and image data. Let $M > 0$ be the dimension of the embedding space. By applying NMF to the normalized gene expression data $X \in \mathbb{R}^{N \times G}$, we obtain an interpretable embedding of the expression data. That is, we derive a factor matrix (i.e., embedding) $F \in \mathbb{R}^{N \times M}$ and a loading matrix $W \in \mathbb{R}^{M \times G}$ $(F \geq 0, W \geq 0)$, such that

$$(W, F) = \underset{W \geq 0, F \geq 0}{\mathrm{Argmin}} \frac{1}{2} ||X - FW||_{\mathrm{F}}^2, \tag{1}$$

where $||\cdot||_{\mathrm{F}}$ represents the Frobenius norm. However, standard NMF can only provide embeddings for the sequenced spots, which are spatially sparse, and cannot provide any information for other locations. Moreover, this basic NMF embedding relies solely on the noisy expression data, neglecting spatial and image information, making it prone to noise and less effective at capturing fine spatial structures. To address these limitations, DeepFuseNMF integrates expression data, image data and spatial information using the following procedure to learn a denoised, low-resolution embedding that covers the entire sequenced tissue (Fig. S1).

In NMF, each column F_j $(j = 1, \cdots, M)$ of the factor matrix F represents a noisy estimate of the spatial expression pattern j at the N sequenced spots. Note that the spatial expression pattern j corresponds to embedding dimension j. We aim to denoise F_j and recover the low-resolution expression pattern j across all locations within the sequenced tissue. This is achieved using a two-step procedure: firstly, we denoise and recover the expression patterns for locations that are much denser than the sequenced spots (denoise-and-recovery step), and secondly, we extend these expression patterns to the entire sequenced tissue by Voronoi tessellations[58] and rasterization (extension step).

The denoise-and-recovery step uses a graph convolutional network (GCN). We first construct an attributed graph $G(V, E, H)$, where V represents vertices, E represents edges, and H represents vertex attributes. The vertex set V consists of all N sequenced spots and R randomly sampled pseudo-spots (default: $R = 5N$). The attribute $H_v \in \mathbb{R}^M$ represents expression patterns at spot v. For a sequenced spot v, H_v is the corresponding row of the factor matrix F. For a pseudo-spot v', $H_{v'}$ is unknown and needs to be learned. Edges are constructed based on spatial proximity and nearby image similarities between spots. More specifically, for each sequenced spot $v \in V$, we first identify K_0 sequenced spots that are spatially closest to v (excluding v itself), and then connect v to the top K of these K_0 spots whose nearby images are the most similar to the image near v (default: $K = 2$, $K_0 = 50$). Similarly, the same procedure is used to connect v to K neighboring pseudo-spots. Thus, each sequenced spot is connected to K sequenced spots and K pseudo-spots. To measure the similarity between images near spots, we extract the semantically rich image representation $\hat{Z}_v \in \mathbb{R}^{16 \times 16 \times 128}$ by passing the square images (256×256 pixels) centered at each spot through the pretrained U-Net-DeepFuseNMF model. Then, by averaging $\hat{Z}_v$ across all pixel locations $\left(\frac{1}{256} \sum_{x=1}^{16} \sum_{y=1}^{16} (\hat{Z}_v)_{x,y,:} \right)$, we obtain a 128-dimensional image representation for each spot and use the Pearson correlation to measure the image similarity.

Let A be the adjacency matrix of the graph $G(V, E, H)$ and $\tilde{A} = D^{-1}A$ be its normalized adjacency matrix, where D is the out-degree matrix of A with $D_{ii} = \sum_{j=1}^{(N+R)} A_{ij}$. Denote $h_i^{(0)} = H_i$ ($i = 1, \ldots, N + R$) and $H^{(0)} = \left(h_1^{(0)}, \cdots, h_{N+R}^{(0)} \right)^T$. The l-th layer of the GCN is updated using

$$H^{(l)} = f^{(l)} \left(\tilde{A} H^{(l-1)} W_l + b_l \right),$$

where $f^{(l)}$ is the nonlinear activation function, W_l is the learnable weight matrix, and b_l is the learnable bias vector. The encoder of this GCN network consists of two graph convolution layers with dimension $M \rightarrow 64 \rightarrow 256$, while the decoder consists of two graph convolution layers with dimension $256 \rightarrow 64 \rightarrow M$. The activation function for the first three layers is the rectified linear unit (ReLU), and the activation function for the final layer is the Sigmoid function. The GCN output, $H^{(4)} \in \mathbb{R}^{(N+R) \times M}$, is the predicted embedding for both observed spots and pseudo spots.

The loss function is the MSE between predicted and input low-resolution embedding for the observed spots:

$$L = \frac{1}{NM} \left\| H^{(4)}_{obs} - H^{(0)}_{obs} \right\|^2_F,$$

where $H^{(j)}_{obs}$ is the submatrix of $H^{(j)}$ ($j = 0,4$) corresponding to the observed spots. An Adam optimizer, with a weight decay of 1×10^{-5}, is used to minimize the reconstruction loss. The initial learning rate is set as 5×10^{-3} and decayed to 1×10^{-3} with the cosine annealing strategy. The number of iterations is set as 5000 by default.

Finally, we use Voronoi tessellations and rasterization to extend the learned low-resolution embedding $H^{(4)}$ to all pixels in the sequenced tissue, resulting in an entire-tissue-wide low-resolution embedding $F^{low} \in \mathbb{R}^{h \times w \times M}$. Specifically, the entire tissue Ω is segmented into multiple multi-pixel tiles by expanding the central spatial coordinates of all observed and pseudo spots using Voronoi tessellations. Then, for the m-th embedding dimension ($m = 1,2,\dots,M$), the corresponding tissue-wide low-resolution embedding $F^{low}_{:,:,m}$ is constructed by associating the spot-wise embedding $H^{(4)}_{:,m}$ to their respective tiles.

High-resolution embedding learning. DeepFuseNMF combines the pretrained U-Net-DeepFuseNMF model with two modules, the feature fusion module (encoder) and the data reconstruction module (decoder), to learn high-resolution embedding. Given that ST image data are extremely high-resolution (usually with hundreds of millions of pixels), directly learning embeddings and reconstructing gene expression and image intensities for every pixel is computationally too expensive. To address this, DeepFuseNMF first divides the ST data into small patches, learns embeddings for each patch, and finally assembles all patches to get the entire-tissue-wide embedding. To create data patches, the sequenced tissue Ω is segmented into tissue patches $\Omega^{(j)} \subset \Omega$ ($j = 1,\dots,J$) using sliding 256×256 rectangular with an 15% overlap between adjacent patches. Data patch $\mathcal{D}^{(j)}$ for the j-th tissue patch $\Omega^{(j)}$ ($j = 1,\dots,J$) includes the normalized expression data $X^{(j)}$ at the spots within $\Omega^{(j)}$, the image data $I^{(j)} \in \mathbb{R}^{256 \times 256 \times c}$ and the pre-

estimated low-resolution embedding $F^{(j,\text{low})} \in \mathbb{R}^{256 \times 256 \times M}$ within $\Omega^{(j)}$, i.e., $\mathcal{D}^{(j)} = \{\Omega^{(j)}, X^{(j)}, I^{(j)}, F^{(j,\text{low})}\}$.

For each data patch $\mathcal{D}^{(j)}$, the feature fusion module fuses the low-resolution embedding $F^{(j,\text{low})} \in \mathbb{R}^{256 \times 256 \times M}$ with the pixel-wise image features $Z^{(j)} \in \mathbb{R}^{256 \times 256 \times 32}$ of $I^{(j)}$ derived from U-Net-DeepFuseNMF. This fusion process generates patch embedding $\tilde{F}^{(j)}$, which has the same shape as $F^{(j,\text{low})}$:

$$\tau^{(j)} = f_{\text{CNN}}\left(Z^{(j)}\right) \in \mathbb{R}^{256 \times 256 \times M},$$

$$\tilde{F}^{(j)} = \text{Sigmoid}[\tau^{(j)} + \text{Logit}(F^{(j,\text{low})})],$$

where $f_{\text{CNN}}(\cdot)$ is a two-layer convolutional neural network (CNN), Sigmoid($\cdot$) and Logit($\cdot$) are the element-wise Sigmoid function and Logit function, respectively.

The data reconstruction module takes the high-resolution patch embeddings $\tilde{F}^{(j)}$ ($j = 1, \dots, J$) to simultaneously reconstruct both the gene expression and the image data. To reconstruct the normalized gene expression of the n-th sequenced spot within the j-th data patch $\mathcal{D}^{(j)}$ (requiring $S_n \cap \Omega^{(j)} \neq \emptyset$), DeepFuseNMF first aggregates the patch embeddings $\tilde{F}^{(j)}$ at the pixels located within the n-th spot to obtain spot-level embeddings, that is:

$$\hat{F}^{(j)}_{n,m} = \frac{1}{|S_n \cap \Omega^{(j)}|} \sum_{(x,y) \in S_n \cap \Omega^{(j)}} \tilde{F}^{(j)}_{x,y,m}, \quad m = 1, 2, \dots, M,$$

where $|S_n \cap \Omega^{(j)}|$ is the number of pixels within the intersecting area between the n-th spot and the j-th tissue patch. If the j-th data patch $\mathcal{D}^{(j)}$ does not contain any sequenced spot, it is simply ignored in the reconstruction of gene expression. Then, DeepFuseNMF reconstructs the normalized gene expression profile of the n-th spot in the j-th tissue patch using a non-negative linear combination of the spot embedding $\hat{F}^{(j)}_{n,m}$ ($m = 1, 2, \dots, M$) as follows:

$$\hat{X}^{(j)}_{n,g} = \sum_{m=1}^{M} \hat{F}^{(j)}_{n,m} \hat{W}_{m,g}, \quad g = 1, 2, \dots, G, \tag{2}$$

where $\hat{X}_{n,g}^{(j)}$ denotes the reconstructed normalized gene expression profile of the g-th gene at the n-th spot in the j-th tissue patch, and $\hat{W} \in \mathbb{R}^{M \times G}$ is a non-negative loading matrix that needs to be learned. The loss function for reconstructing the expression is taken as the following negative log-likelihood of Poisson distributions:

$$\mathcal{L}_{\text{exp}} = \sum_{j=1}^{J} \frac{1}{|A_j| \cdot G} \sum_{n \in A_j} \sum_{g=1}^{G} \left(\hat{X}_{n,g}^{(j)} - X_{n,g}^{(j)} \log \left(\hat{X}_{n,g}^{(j)} + \epsilon \right) \right),$$

where $A_j = \{n: S_n \cap \Omega^{(j)} \neq \emptyset\}$ stands for spots belonging to the j-th tissue patch and $\epsilon = 1 \times 10^{-8}$.

For the reconstruction of the images $I^{(j)}$ in the j-th patch, DeepFuseNMF uses a two-layer CNN followed by an element-wise Sigmoid function to produce the reconstructed images $\hat{I}^{(j)}$ from the j-th patch embeddings $\tilde{F}^{(j)}$. The image reconstruction loss is taken as the MSE:

$$\mathcal{L}_{\text{img}} = \sum_{j=1}^{J} \frac{1}{256 \cdot 256 \cdot c} \sum_{x=1}^{256} \sum_{y=1}^{256} \sum_{k=1}^{c} \left(\hat{I}_{x,y,k}^{(j)} - I_{x,y,k}^{(j)} \right)^2.$$

The overall reconstruction loss function is a weighted sum of the expression reconstruction loss and the image reconstruction loss

$$\mathcal{L} = \lambda \mathcal{L}_{\text{exp}} + (1 - \lambda) \mathcal{L}_{\text{img}}, \tag{3}$$

where $\lambda \in [0,1]$ is the weight balancing the two loss functions, with a default value of 1/3. An Adam optimizer, with a weight decay of 1×10^{-5}, is used to minimize the overall reconstruction loss. The mini-batch size is set as 32 and the number of iterations is set as 2,000 by default. During the first 1,000 iterations, parameters in U-Net-DeepFuseNMF are fixed, and only the feature fusion module and the image reconstruction module are updated, starting with an initial learning rate of 5×10^{-3} and decaying to 1×10^{-6} with the cosine annealing strategy. In the final 1000 iterations, all parameters in DeepFuseNMF are fine-tuned with a smaller initial learning rate, 4×10^{-4}, then decaying to 1×10^{-6} with the cosine annealing strategy.

Finally, DeepFuseNMF outputs pixel-wise embeddings $F^{\text{high}} \in \mathbb{R}^{h \times w \times M}$ by averaging the patch embeddings $\tilde{F}^{(j)}(j = 1, \dots, J)$ that contain the pixel (x, y)

$$F_{x,y,m}^{\text{high}} = \frac{1}{\sum_{j=1}^{J} \mathbf{1}\big((x,y) \in \Omega^{(j)}\big)} \sum_{j=1}^{J} \left[\tilde{F}_{x,y,m}^{(j)} \cdot \mathbf{1}\big((x,y) \in \Omega^{(j)}\big) \right],$$

where $\mathbf{1}(\cdot)$ is the indicator function.

Ranking and identification of genes associated with embedding dimensions. DeepFuseNMF ranks genes' contribution to each high-resolution embedding dimension $F_{:,:,m}^{\text{high}}$ based on the m-th row of the non-negative loading matrix $\widehat{W} \in \mathbb{R}^{M \times G}$ $\big(\widehat{W} \geq 0\big)$ obtained from the expression reconstruction module. Specifically, the loading matrix $\widehat{W}$ is first row-normalized to $\widetilde{W} \geq 0$ with $\widetilde{W}_{m,g} = \widehat{W}_{m,g}/\big(\sum_{m=1}^{M} \widehat{W}_{m,g}\big)$. Then, for a given embedding dimension m, DeepFuseNMF ranks the genes in the decreasing order of $\widetilde{W}_{m,g}$ and takes the top genes as those associated with this embedding dimension.

High-resolution spatial domain detection. DeepFuseNMF clusters pixels (x, y) based on the learned embeddings $F^{\text{high}} \in \mathbb{R}^{h \times w \times M}$ to identify high-resolution spatial domains. Considering the extremely large number of pixels in tissue, direct pixel clustering would be computational expensive. Therefore, DeepFuseNMF first divides the tissue into fixed-size squares, termed as meta-pixels. Then, the pixel embeddings within each meta-pixel are averaged to produce meta-pixel embeddings, and the K-means algorithm is then applied to cluster these meta-pixels. The initial value for the K-means algorithm is taken as the Louvain clustering results based on the spot embeddings. Here, the spot embeddings are obtained using a procedure similar to that of the meta-pixel embeddings. The size of the meta-pixel is usually much smaller than the sequenced spots, and can be adjusted by users. Specifically, for the 10X Visium mouse brain coronal slices with IHC images, the size of the meta-pixel is 50 pixels, and the spot diameter is 178 pixels. For the four 10X Visium SHH medulloblastoma slices stained with H&E images, the meta-pixel size is 10 pixels, and the spot diameter is 118 pixels. For CRC-01 and CRC-02, the meta-pixel size is 20 pixels, and the spot diameter is 150 pixels. Lastly,

for CRC-03, the meta-pixel size is 10 pixels, and the spot diameter is 100 pixels.

Ranking and identification of genes associated with detected high-resolution spatial domain. Based on the D detected high-resolution spatial domains, we first calculate the mean embedding intensity for each spatial domain $\bar{E} \in \mathbb{R}^{D \times M}$, and then extract the non-negative loading matrix for spatial domain $\widehat{W}^D \in \mathbb{R}^{D \times G}$ by $\widehat{W}^D = \bar{E}\,\widehat{W}$. The column-normalization and gene ranking are performed similarly to the procedure described in the section, "Ranking and identification of genes associated with embedding dimensions".

High-resolution gene expression recovery. For the g-th gene, DeepFuseNMF recovers its high-resolution normalized expression $X_g^{\text{high}} \in \mathbb{R}^{h \times w}$ by computing a weighted sum of the learned embeddings F^{high},

$$X_g^{\text{high}} = \sum_{m=1}^{M} W_{m,g} F_{:,:,m}^{\text{high}} \ .$$

Note that X_g^{high} quantifies the expression of the g-th gene for every pixel in the tissue, and thus essentially imputes the sparse expression quantification given by the original ST expression data.

Joint analysis of multi-sample ST data. In the case of multiple ST samples, the DeepFuseNMF framework remains similar as before, with the addition of learnable batch parameters to account for potential batch effects across different samples. Specifically, let Ω_b be the sequenced tissue of the b-th sample ($b = 1,2,\dots,B$). Similar to Equation (2), DeepFuseNMF reconstructs the normalized gene expression $\widehat{X}_{n,:}^{(j,b)}$ of the n-th spot in the j-th tissue patch from the b-th sample by employing a non-negative linear combination component alongside an additional batch effect term as follows:

$$\widehat{X}_{n,g}^{(j,b)} = \text{ReLu}\left(\sum_{m=1}^{M} \widehat{F}_{n,m}^{(j,b)} \, \widehat{W}_{m,g} + \gamma_{b,g} \right), \ g = 1,2,\dots,G. \tag{4}$$

Here, $\widehat{W} \in \mathbb{R}^{M \times G}$ is a non-negative loading matrix to be learned, $\gamma_{b,g} \in \mathbb{R}$ denotes the learnable mean batch effect parameter of batch b on gene g. For identifiability, we set the first batch as the reference batch, i.e., $\gamma_{1,g} = 0$. Further, the spot-wise low-resolution factor matrix $F^{(b)}$ of batch b, derived from Equation (1), is replaced by

$$\check{F}_{n,m}^{(b)} = \text{ReLu}\left(F_{n,m}^{(b)} - \frac{1}{N_b} \sum_{i=1}^{N_b} F_{i,m}^{(1)} \right), m = 1, \dots, M,$$

where N_b is the number of spots in the reference batch.

For samples from C biologically different experimental conditions (e.g., Palbociclib-treated and untreated conditions in the SHH medulloblastoma dataset), where there are B_c batches for condition c, we replace $\gamma_{b,g}$ in Equation (4) with $\gamma_{c,b,g} \in \mathbb{R}$ ($c = 1, \dots, C$; $b = 1, \dots, B_c$) as follows:

$$\widehat{X}_{n,g}^{(j,c,b)} = \text{ReLu}\left(\sum_{m=1}^{M} \widehat{F}_{n,m}^{(j,c,b)} \, \widehat{W}_{m,g} + \gamma_{c,b,g} \right), \ g = 1,2,\dots,G.$$

For identifiability, we set the first batch in each condition as the reference batch, i.e., $\gamma_{c,1,g} = 0$. All parameters are trained using the Adam optimizer to minimize the overall reconstruction loss (3).

Generation and analysis of simulated datasets

Two methods are used to generate simulation datasets. The first method utilizes an H&E image of a mouse cerebellum and generates low-resolution ST expression data using the zero-inflated Poisson distributions, where the distribution parameters are dependent on the given H&E image. The second method uses a real single-cell-resolution ST dataset sequenced by the 10X Xenium to generate low-resolution ST expression data.

Simulation data generation using an H&E image of mouse cerebellum. We utilize an H&E image of a mouse posterior brain sagittal section (4000×4000 pixels) sequenced by 10X Visium(https://www.10xgenomics.com/resources/datasets/mouse-brain-serial-section-1-sagittal-posterior-1-standard-1-1-0) to simulate ST expression data. The image is first segmented into four regions: fiber tracts, granular layer of the cerebellum, molecular layer of the cerebellum, and background area. We introduce $M = 3$ true pixel-wise embedding dimensions, denoted as $F^* \in \mathbb{R}^{h \times w \times M}$, where

$h = 4000$ and $w = 4000$ are the height and width of the image, respectively. Each dimension corresponds to and is only enriched in one specific segmented region, excluding the background area.

We generate N spots with radius r using a 10X Visium-style meshgrid. Denote the pixel set located in the n-th spot as S_n ($n = 1, \ldots, N$). Using the pixel-wise embedding F^*, we induce the spot-level embedding dimension intensity $F_{n,m}^{*,\text{spot}}$ ($n = 1, \ldots, N$; $m = 1,2,3$) as follows,

$$F_{n,m}^{*,\text{spot}} = \frac{F_{n,m}^{*,1}}{\sum_{m'=1}^{3} F_{n,m'}^{*,1}},$$

$$F_{n,m}^{*,1} = \left| F_{n,m}^{*,0} + \varepsilon_{n,m} \right|, \qquad F_{n,m}^{*,0} = \frac{1}{|S_n|} \sum_{(x,y) \in S_n} F_{x,y,m}^*,$$

where $\varepsilon_{n,m} \sim \mathcal{N}(0, 0.05^2)$ is a Gaussian random variable that controls spot-specific variation of the embedding intensity. Then, we generate the loading matrix $W^* \in \mathbb{R}_+^{G \times M}$ as follows. We divide the G genes into 3 gene sets, and assign each gene set to one embedding as its associated gene set. The loading $W_{g,m}^*$ is generated from a Gamma distribution with a scale parameter of 0.05. The shape parameter of the Gamma distribution is set to 15 if the gene is associated with the dimension, and 5 otherwise.

Given the generated spot-level embedding $F^{*,\text{spot}}$ and the loading matrix W^*, we first generate the true underlying log-transformed gene expression $X_{n,g}$ for spot n and gene g as $X_{n,g} = \sum_{m=1}^{M} F_{n,m}^{*,\text{spot}} W_{g,m}^* + \xi_{n,g}$, where $\xi_{n,g}$ is independently generated from $\mathcal{N}(0, \sigma^2)$. Then, we generate the observed count expression $X_{n,g}^0$ for spot n and gene g from a zero-inflated Poisson distribution. The zero-inflation parameter of the zero-inflated Poisson distribution is π and the mean parameter is $\lambda = l_n \{\exp(X_{n,g}) - 1\}$, where l_n represents the spot-specific library size and is generated using $\log(l_n) \sim \mathcal{N}(10, 0.05^2)$. After generating the count expression data, we also randomly exclude a proportion ρ of the spots to simulate different spot densities.

In the simulation, we set the number of genes as $G = 3000$. We vary the spot exclusion percentage ρ, the spot radius r, the expression variance σ, and the zero-inflation parameter π to generate different simulation scenarios. For each scenario, we generate 30 replicates.

Simulation based on a real single-cell-level ST dataset. We use a single-cell-level Xenium ST dataset

from a human breast carcinoma tissue[3] to generate simulated spot-level ST expression profiles. This

Xenium ST dataset contained an expression profile for 313 genes across 167,780 sequenced cells, and

an H&E image with 5478×7526 pixels. To generate the simulated spot-level ST expression data, we

first generate spots S_n $(n = 1, \dots, N)$ with a radius r using a 10X Visium-style meshgrid and sum the

expression counts of cells within each spot as the spot-level expression. Then, a proportion ρ of the

generated spots are excluded along with their spatial coordinates and gene expression.

Considering that the number of annotated cell types for this Xenium dataset is 19, we set the number

of embedding dimensions as $M = 20$ in this simulation. The underlying true single-cell-level

embedding is derived from applying NMF to the original Xenium ST dataset. We vary the spot

exclusion proportion ρ and the spot radius r to generate different simulation scenarios, generating 30

replicates for each scenario.

Evaluation criteria of the embedding learning methods. We use the MAE between the true

embedding intensity F^* and the inferred embedding intensity $\hat{F}$ to evaluate each method's

performance on embedding learning. The MAE for one simulated dataset is defined as

17
$$\mathrm{MAE}(F^*, \hat{F}) = \frac{1}{h \times w \times M} \sum_{x=1}^{h} \sum_{y=1}^{w} \sum_{m=1}^{M} \left| F^*_{x,y,m} - \hat{F}_{x,y,m} \right|.$$

For methods that only give spot-level embeddings, we extend their spot-level embeddings to entire-

tissue-wide embeddings using Voronoi tessellations and rasterization before calculating their MAEs. To

assess the accuracy of the spatial domain assignment in simulation data generated from mouse

cerebellum, we cluster the pixels into three regions by applying the K-means algorithm to the inferred

embedding of each method, and then compare the inferred region label with the three true regions using

the ARI metric.

Comparison with available methods

We compare DeepFuseNMF with various interpretable embedding learning and spatial domain detection methods. The interpretable embedding learning methods include NMF (via the *decomposition.NMF* function in the Python *scikit-learn* package, v1.5.1), NSFH, SpiceMix, Giotto (v4.0.0) and TESLA (v1.2.4)+NMF. The spatial domain detection methods include iStar, stLearn (v0.4.12) and SpaGCN (v1.2.7). NMF, NSFH, SpiceMix and Giotto only require ST expression data, while iStar, stLearn, TESLA and SpaGCN require both ST expression data and histology image. The available methods that utilize histology images all require RGB images as input. Thus, for datasets with H&E images, we directly provide the H&E images to these methods, while for datasets with IHC images, we first convert the IHC images to RGB images and provide the obtained RGB images.

In terms of embedding learning, for TESLA+NMF, we first use TESLA to enhance the spatial resolution of gene expression based on the histology image and spatial expression profile. The default meta-pixel size of 50×50 pixels is used for TESLA. Then, we learn an embedding using the standard NMF based on the resolution-enhanced expression. For other embedding learning methods, their default parameters are used.

In terms of the spatial domain detection, for the embedding learning methods, we first apply these methods to obtain the embeddings. Then, for the spot-level embedding methods, we apply the Louvain algorithm[59] to their embeddings for spot clustering. For the high-resolution embedding methods including DeepFuseNMF and TESLA+NMF, we first apply the Louvain algorithm to cluster the spots and then apply the K-means algorithm to cluster the meta-pixels with the clustering results given by Louvain as the initial values. Across all embedding methods, we use the same resolution parameter for the Louvain algorithm and the same cluster number of the K-means algorithm for clustering. For the spatial domain detection methods, we employ their default parameters and specify the same number of clusters as that of the embedding methods for spatial domain identification.

Sample collection and library preparation of colorectal cancer

CRC-01 was sampled from the abdominal wall of a metastatic colorectal cancer patient, while CRC-02 was sampled from the ovarian metastasis site of another colorectal cancer patient. Formalin-fixed paraffin-embedded (FFPE) samples of CRC-01 and CRC-02 were sectioned into 5 μm slices by Leica HistoCore BIOCUT and were affixed to adhesive slides. Subsequently, the FFPE sections underwent spatial transcriptomics profiling using Visium CytAssist Spatial Gene Expression Reagent Kits (10X Genomics, USA) following the manufacturer's protocols and recommended third party reagents. Visium spatial libraries were sequenced in paired-end with Illumina NovaSeq 6000 according to manufacturer instructions.

CRC-03 was sampled from a primary colorectal cancer patient. Fresh tissue sample of CRC-03 was obtained and embedded in Tissue-Teck OCT within 30 minutes of resection, with extra fluid being wiped out. The sample was then frozen in dry ice and transferred to a -80℃ freezer for storage. Freezing and OCT-embedding of the tissue sample were sectioned to 10μm slices by Leica CM1950 cryostat, and immediately attached to Stereo-seq chips. The target tissue section was fixed with formaldehyde, and stained using nucleic acid dye (Thermo fisher, Q10212). The section was permeabilized for RNA release at the selected time to capture the mRNA molecules from the target tissue cells on the microarray for cDNA synthesis. The indexed cDNA libraries were constructed and sequenced in paired-end with MGI DNBSEQ-T7 sequencer according to manufacturer instructions.

Generation of the pseudo-image for the colorectal cancer Stereo-seq dataset

The Stereo-seq dataset CRC-03 lacks paired histology images. To apply DeepFuseNMF and other image-depended methods, we first generated a high-resolution pseudo-image based on the subcellular expression profile of Stereo-seq data. Specifically, we first extracted the high-resolution bin-level expression counts using the *io.read_gef* function from the Python *Stereopy* package with a bin size of 10. This bin size is significantly smaller than the bin size commonly used for Stereo-seq data analysis (i.e., bin size = 100). Next, the bin-level expression counts were log-transformed and normalized using the total sum count as the library size. Principal Component Analysis (PCA) was then performed on the bin-level normalized expression. Finally, we summarized the top 30 PCs into three UMAP

components and visualized the three-dimensional components using red, green, and blue (RGB) colors

through an RGB plot. This process resulted in a pseudo-image that captures the high-resolution spatial

structure of the tissue (Fig. S19a).

Analysis of colorectal cancer samples

Cell type proportion deconvolution was performed using RCTD[44] in the R package *spacexr* (v2.2.1).

The reference single-cell RNA-seq data for RCTD was downloaded from the National Center for

Biotechnology Information (NCBI) Gene Expression Omnibus (GEO) under accession code

GSE183202[60].

To characterize different biological activities, we computed the mean expression of gene lists

provided in Supplementary Table 3 using the *AddModuleScore* function in the R package *Seurat*

(v4.0.0). Given the embeddings from DeepFuseNMF, we calculated the mean ranks of the given gene

lists in each high-resolution cluster. The gene lists include genes related to CMS subtypes[42, 43],

functional states of cancer cells from CancerSEA[61] and cell-type markers[47] (Supplementary Table 3).

Copy number variation detection was carried out using the R package *infercnv* (v1.20.0,

https://github.com/broadinstitute/inferCNV).

For survival analysis, we downloaded TCGA[46] expression and survival data using the R package

cBioPortalData[62-64]. For each gene, we standardized its expression to have a mean of 0 and standard

deviation of 1 across samples. Given a list of genes, we first calculated their mean expression for each

patient and the upper and lower quantiles of its mean expressions across the patients. Patients with a

mean expression larger than the upper quantile were assigned to the high expression group, while

patients with a mean expression smaller than the lower quantile were assigned to the low expression

group. Kaplan-Meier curves and log rank tests were carried out using the *survfit* and *ggsurvplot*

functions in the R packages *survival* and *survminer,* respectively.

CMS classification was performed using the R package *CMSclassifier* (v1.0.0)[42]. Briefly, the raw

count matrix of RNA-seq was transformed by variance stabilizing transformation[65] (*SCTransform*).

Then, gene identifiers were converted from gene symbols to Entrez gene ids using the R package

org.Hs.eg.db (genome-wide annotation for Human, v3.19.1). The processed matrix was used as input for the *classifyCMS* function with the option method "SSP".

Data description

The first simulation dataset was generated based on the H&E image of a mouse brain dataset MPBS-01 from the 10X Visium platform, while the second simulation dataset was generated from a human breast cancer ST dataset with an H&E image sequenced by 10X Xenium. The mouse brain datasets MBC-01, MBC-02, MBC-03, MPBS-01 and MPBS-02 were sequenced by 10X Visium, with IHC images for MBC-01 and MBC-02, and H&E images for the other mouse brain datasets. The four SHH medulloblastoma PDOX datasets were sequenced by 10X Visium and accompanied with H&E images, with their tumor/normal/interface annotations from the original paper[39]. The human colorectal cancer samples CRC-01 and CRC-02 were sequenced by 10X Visium CytAssist. Sample CRC-03 was sequenced by Stereo-seq technology with a nearby slice stained by H&E image. See Supplementary Table 1 for details.

The region annotations for mouse brain coronal and sagittal sections were downloaded from the aligned slices (the 76th coronal section and the 9th sagittal section) in the Allen Reference Atlas – Mouse Brain[66] (atlas.brain-map.org). The mouse brain region marker genes were sourced from the Allen Mouse Brain Atlas[31] (https://mouse.brain-map.org/). The marker genes of major cell types in the adult mouse leptomeninges were collected from Pietila et al.[36]. The marker genes of mouse microglial cells, astrocytes, and endothelial cells were downloaded from the CellMarker 2.0 database (http://117.50.127.228/CellMarker/index.html). The gene signatures of SHH-A, SHH-B, SHH-C, E2F target genes, and neuronal differentiation were collected from Vo et al.[39]. Reference scRNA-seq of metastasized colorectal cancer samples were downloaded from the NCBI GEO database under accession code GSE183916.

Data availability

The ST datasets in the paper are publicly available at:

(1) 10X Visium mouse brain coronal section data.

MBC-01: https://www.10xgenomics.com/resources/datasets/adult-mouse-brain-section-2-coronal-stains-dapi-anti-gfap-anti-neu-n-1-standard-1-1-0

MBC-02: https://www.10xgenomics.com/resources/datasets/adult-mouse-brain-section-1-coronal-stains-dapi-anti-neu-n-1-standard-1-1-0

MBC-03: https://www.10xgenomics.com/resources/datasets/mouse-brain-section-coronal-1-standard-1-0-0

(2) 10X Visium mouse posterior brain sagittal section data.

MPBS-01: https://www.10xgenomics.com/resources/datasets/mouse-brain-serial-section-1-sagittal-posterior-1-standard-1-1-0

MPBS-02: https://www.10xgenomics.com/resources/datasets/mouse-brain-serial-section-2-sagittal-posterior-1-standard-1-1-0

(3) 10X Xenium human breast cancer data, replicate 1.

https://www.10xgenomics.com/products/xenium-in-situ/preview-dataset-human-breast

(4) 10X Visium sonic hedgehog medulloblastoma data.

https://genomemedicine.biomedcentral.com/articles/10.1186/s13073-023-01185-4#availability-of-data-and-materials

Raw and processed data for the colorectal cancer samples will be available at the time of publication. Details of the datasets analyzed in this paper are described in Supplementary Table 1.

Code availability

An open-source implementation of the DeepFuseNMF algorithm can be accessed at https://github.com/XiDsLab/DeepFuseNMF. A detailed documentation, including tutorials demonstrating the use of DeepFuseNMF on several example datasets, is available at

https://deepfusenmf.readthedocs.io/en/latest/. Codes to reproduce the analyses in this manuscript are available at Zenodo: https://doi.org/10.5281/zenodo.13690848.

Acknowledgments

This work was supported by the National Natural Science Foundation of China (12425110, 12371286 and 11971039 to R.X.), the National Key R&D Program of China (2020YFE0204200 to R.X.), Science and Technology Project of Tianjin Binhai New Area Health Commission (2022BWKY016 to Y.Z.), and the Sino-Russian Mathematics Center. Part of the analysis was performed on the high-performance computing platform of the Center for Life Sciences (Peking University). We thank Quan Nguyen and Laura A. Genovesi for sharing the 10X Visium mouse brain sonic hedgehog (SHH) medulloblastoma data. We also thank Yuanyuan He and Cheng Li for their helpful discussions.

Author contributions

R.X. conceived the study. R.X. and J.J.X. supervised the study. J.T. formulated the method. J.T. and K.Q. developed the software. J.T. and Z.C. performed bioinformatic analyses and prepared figures and tables in the manuscript. S.H. helped develop biological interpretations. S.Y., B.Y. and H.M. conducted pathological annotations. Y.Z. prepared the samples. Y.H. performed the spatial transcriptomics sequencing. J.T., Z.C., X.H. and R.X. wrote the manuscript.

Ethics declarations

All human tissue samples were obtained from Tianjin Medical University Cancer Institute & Hospital. Before surgery at the center, all patients provided written informed consent to allow any excess tissue to be used for research studies. The study was approved by the Ethics Committee (ID: bc2022189).

Competing interests

J.J.X. and R.X. hold stock in GeneX Health Co., Ltd. All other authors declare that they have no competing interests.

References

1. Chen, K.H., Boettiger, A.N., Moffitt, J.R., Wang, S. & Zhuang, X. Spatially resolved, highly multiplexed RNA profiling in single cells. *Science* **348**, aaa6090 (2015).

2. Chen, A. et al. Spatiotemporal transcriptomic atlas of mouse organogenesis using DNA nanoball-patterned arrays. *Cell* **185**, 1777-1792. e1721 (2022).

3. Janesick, A. et al. High resolution mapping of the tumor microenvironment using integrated single-cell, spatial and in situ analysis. *Nat. Commun.* **14**, 8353 (2023).

4. Zhu, J. et al. Custom microfluidic chip design enables cost-effective three-dimensional spatiotemporal transcriptomics with a wide field of view. *Nat. Genet.*, 1-12 (2024).

5. Schott, M. et al. Open-ST: High-resolution spatial transcriptomics in 3D. *Cell* **187**, 3953-3972. e3926 (2024).

6. Huang, S. et al. Spatial transcriptomics: a new frontier in cancer research. *Clin. Cancer Bull.* **3**, 13 (2024).

7. Erickson, A. et al. Spatially resolved clonal copy number alterations in benign and malignant tissue. *Nature* **608**, 360-367 (2022).

8. Carmona-Fontaine, C. et al. Metabolic origins of spatial organization in the tumor microenvironment. *Proc. Natl. Acad. Sci. USA* **114**, 2934-2939 (2017).

9. Vandereyken, K., Sifrim, A., Thienpont, B. & Voet, T. Methods and applications for single-cell and spatial multi-omics. *Nat. Rev. Genet.*, 1-22 (2023).

10. Soldatov, R. et al. Spatiotemporal structure of cell fate decisions in murine neural crest. *Science* **364**, eaas9536 (2019).

11. Li, H. et al. A comprehensive benchmarking with practical guidelines for cellular deconvolution of spatial transcriptomics. *Nat. Commun.* **14**, 1548 (2023).

12. Pham, D. et al. Robust mapping of spatiotemporal trajectories and cell–cell interactions in healthy and diseased tissues. *Nat. Commun.* **14**, 7739 (2023).

13. Shang, L. & Zhou, X. Spatially aware dimension reduction for spatial transcriptomics. *Nat. Commun.* **13**, 7203 (2022).

14. Velten, B. et al. Identifying temporal and spatial patterns of variation from multimodal data using MEFISTO. *Nat. Methods* **19**, 179-186 (2022).

15. Townes, F.W. & Engelhardt, B.E. Nonnegative spatial factorization applied to spatial genomics. *Nat. Methods* **20**, 229-238 (2023).

16. Chidester, B., Zhou, T., Alam, S. & Ma, J. SpiceMix enables integrative single-cell spatial modeling of cell identity. *Nat. Genet.*, 1-11 (2023).

17. Dries, R. et al. Giotto: a toolbox for integrative analysis and visualization of spatial expression data. *Genome Biol.* **22**, 1-31 (2021).

18. Chen, S. et al. Integration of spatial and single-cell data across modalities with weakly linked features. *Nat. Biotechnol.* **42**, 1096-1106 (2024).

19. Long, Y. et al. Spatially informed clustering, integration, and deconvolution of spatial transcriptomics with GraphST. *Nat. Commun.* **14**, 1155 (2023).

20. Zhou, X., Dong, K. & Zhang, S. Integrating spatial transcriptomics data across different conditions, technologies and developmental stages. *Nat. Comput. Sci.* **3**, 894-906 (2023).

21. Bao, F. et al. Integrative spatial analysis of cell morphologies and transcriptional states with MUSE. *Nat. Biotechnol.* **40**, 1200-1209 (2022).

22. Hu, J. et al. SpaGCN: Integrating gene expression, spatial location and histology to identify spatial domains and spatially variable genes by graph convolutional network. *Nat. Methods* **18**, 1342-1351 (2021).

23. Bergenstråhle, L. et al. Super-resolved spatial transcriptomics by deep data fusion. *Nat. Biotechnol.* **40**, 476-479 (2022).

24. He, B. et al. Integrating spatial gene expression and breast tumour morphology via deep learning. *Nat. Biomed. Eng.* **4**, 827-834 (2020).

25. Hu, J. et al. Deciphering tumor ecosystems at super resolution from spatial transcriptomics with TESLA. *Cell Syst.* **14**, 404-417. e404 (2023).

26. Zhang, D. et al. Inferring super-resolution tissue architecture by integrating spatial transcriptomics with histology. *Nat. Biotechnol.*, 1-6 (2024).

27. Wan, X. et al. Integrating spatial and single-cell transcriptomics data using deep generative models with SpatialScope. *Nat. Commun.* **14**, 7848 (2023).

28. Li, B. et al. Tissue characterization at an enhanced resolution across spatial omics platforms with deep generative model. *Nat. Commun.* **15**, 6541 (2024).

29. Lee, D.D. & Seung, H.S. Learning the parts of objects by non-negative matrix factorization.

Nature **401**, 788-791 (1999).

30. Lein, E.S. et al. Genome-wide atlas of gene expression in the adult mouse brain. *Nature* **445**, 168-176 (2007).

31. Lein, E.S. et al. Genome-wide atlas of gene expression in the adult mouse brain. *Nature* **445**, 168-176 (2007).

32. Batiuk, M.Y. et al. Identification of region-specific astrocyte subtypes at single cell resolution. *Nat. Commun.* **11**, 1220 (2020).

33. Zeng, H. et al. Spatially resolved single-cell translatomics at molecular resolution. *Science* **380**, eadd3067 (2023).

34. Decimo, I., Fumagalli, G., Berton, V., Krampera, M. & Bifari, F. Meninges: from protective membrane to stem cell niche. *Am. J. Stem Cells* **1**, 92 (2012).

35. Mapunda, J.A. et al. VE-cadherin in arachnoid and pia mater cells serves as a suitable landmark for in vivo imaging of CNS immune surveillance and inflammation. *Nat. Commun.* **14**, 5837 (2023).

36. Pietilä, R. et al. Molecular anatomy of adult mouse leptomeninges. *Neuron* **111**, 3745-3764. e3747 (2023).

37. Engelhardt, B., Vajkoczy, P. & Weller, R.O. The movers and shapers in immune privilege of the CNS. *Nat. Immunol.* **18**, 123-131 (2017).

38. Mastorakos, P. & McGavern, D. The anatomy and immunology of vasculature in the central nervous system. *Sci. Immunol.* **4**, eaav0492 (2019).

39. Vo, T. et al. Spatial transcriptomic analysis of Sonic hedgehog medulloblastoma identifies that the loss of heterogeneity and promotion of differentiation underlies the response to CDK4/6 inhibition. *Genome Med.* **15**, 29 (2023).

40. Hovestadt, V. et al. Resolving medulloblastoma cellular architecture by single-cell genomics. *Nature* **572**, 74-79 (2019).

41. Finn, R.S., Aleshin, A. & Slamon, D.J. Targeting the cyclin-dependent kinases (CDK) 4/6 in estrogen receptor-positive breast cancers. *Breast Cancer Res.* **18**, 1-11 (2016).

42. Guinney, J. et al. The consensus molecular subtypes of colorectal cancer. *Nat. Med.* **21**, 1350-1356 (2015).

43. Khaliq, A.M. et al. Refining colorectal cancer classification and clinical stratification through a single-cell atlas. *Genome Biol.* **23**, 113 (2022).

44. Cable, D.M. et al. Robust decomposition of cell type mixtures in spatial transcriptomics. *Nat. Biotechnol.* **40**, 517-526 (2022).

45. Chakravarthy, A., Khan, L., Bensler, N.P., Bose, P. & De Carvalho, D.D. TGF-β-associated extracellular matrix genes link cancer-associated fibroblasts to immune evasion and immunotherapy failure. *Nat. Commun.* **9**, 4692 (2018).

46. Hoadley, K.A. et al. Cell-of-origin patterns dominate the molecular classification of 10,000 tumors from 33 types of cancer. *Cell* **173**, 291-304. e296 (2018).

47. Zhang, L. et al. Single-cell analyses inform mechanisms of myeloid-targeted therapies in colon cancer. *Cell* **181**, 442-459. e429 (2020).

48. Dong, K. & Zhang, S. Deciphering spatial domains from spatially resolved transcriptomics with an adaptive graph attention auto-encoder. *Nat. Commun.* **13**, 1739 (2022).

49. Li, J., Chen, S., Pan, X., Yuan, Y. & Shen, H.-B. Cell clustering for spatial transcriptomics data with graph neural networks. *Nat. Comput. Sci.* **2**, 399-408 (2022).

50. Lopez, R., Regier, J., Cole, M.B., Jordan, M.I. & Yosef, N. Deep generative modeling for single-cell transcriptomics. *Nat. Methods* **15**, 1053-1058 (2018).

51. Tian, T., Wan, J., Song, Q. & Wei, Z. Clustering single-cell RNA-seq data with a model-based deep learning approach. *Nat. Mach. Intell.* **1**, 191-198 (2019).

52. Caligiuri, G. & Tuveson, D.A. Activated fibroblasts in cancer: Perspectives and challenges. *Cancer Cell* **41**, 434-449 (2023).

53. Smillie, C.S. et al. Intra-and inter-cellular rewiring of the human colon during ulcerative colitis. *Cell* **178**, 714-730. e722 (2019).

54. Moran, P.A. Notes on continuous stochastic phenomena. *Biometrika* **37**, 17-23 (1950).

55. Ronneberger, O., Fischer, P. & Brox, T. U-net: Convolutional networks for biomedical image segmentation. *Medical Image Computing and Computer-Assisted Intervention–MICCAI 2015: 18th International Conference, Munich, Germany, October 5-9, 2015, Proceedings, Part III 18*, 234-241 (2015).

56. Chen, L., Lu, X., Zhang, J., Chu, X. & Chen, C. Hinet: Half instance normalization network for image restoration. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 182-192 (2021).

57. Loshchilov, I. & Hutter, F. SGDR: Stochastic Gradient Descent with Warm Restarts. *International*

Conference on Learning Representations, 1-16 (2022).

58. Voronoï, G. Nouvelles applications des parametres continus a la theorie des forms quadratiques. Deuxieme memoire: Recheches sur les parallelloedres primitifs. *J. Reine Angew. Math.* **134**, 198-287 (1908).

59. Blondel, V.D., Guillaume, J.-L., Lambiotte, R. & Lefebvre, E. Fast unfolding of communities in large networks. *J. Stat. Mech.* **2008**, P10008 (2008).

60. Lenos, K.J. et al. Molecular characterization of colorectal cancer related peritoneal metastatic disease. *Nat. Commun.* **13**, 4443 (2022).

61. Yuan, H. et al. CancerSEA: a cancer single-cell state atlas. *Nucleic Acids Res.* **47**, D900-D908 (2019).

62. Cerami, E. et al. The cBio cancer genomics portal: an open platform for exploring multidimensional cancer genomics data. *Cancer Discov.* **2**, 401-404 (2012).

63. de Bruijn, I. et al. Analysis and visualization of longitudinal genomic and clinical data from the AACR project GENIE biopharma collaborative in cBioPortal. *Cancer Res.* **83**, 3861-3867 (2023).

64. Gao, J. et al. Integrative analysis of complex cancer genomics and clinical profiles using the cBioPortal. *Sci. Signal.* **6**, pl1 (2013).

65. Hafemeister, C. & Satija, R. Normalization and variance stabilization of single-cell RNA-seq data using regularized negative binomial regression. *Genome Biol.* **20**, 296 (2019).

66. Allen Institute for Brain Science. Allen Reference Atlas – Mouse Brain [brain atlas] (2011). Available from atlas.brain-map.org.

67. Zhang, M. et al. Molecularly defined and spatially resolved cell atlas of the whole mouse brain. *Nature* **624**, 343-354 (2023).

Fig. 1. Overview of DeepFuseNMF. DeepFuseNMF consists of two components: the feature representation and high-resolution embedding learning components. In the feature representation component, DeepFuseNMF independently learns a low-resolution embedding from the ST data and a pixel-wise feature representation from the histology image data. In the high-resolution embedding learning component, DeepFuseNMF integrates the low-resolution embedding and the pixel-wise image features to learn a high-resolution embedding. This is achieved by reconstructing both the gene expression data and the image data from the learned embedding using an encoder-decoder framework. With the learned embedding, DeepFuseNMF can perform various downstream analyses, including identification of genes associated with the learned embeddings, high-resolution spatial domain detection, and gene expression recovery. CNN: convolutional neural network. MLP: multilayer perceptron.

Fig. 2. Comparison of DeepFuseNMF with interpretable embedding learning methods using simulation.
a. Generation of the first simulation dataset. The H&E image of a mouse cerebellum sample is manually segmented into three brain regions and a background region. Spot locations are randomly generated on the non-background area of tissue. Each brain region is then associated with a specific embedding dimension, and spot-wise ST data are generated based on the location of sequenced spots and the embedding dimensions. Scale bar: 500 μm. **b-c**. Error bar plots showing (b) the MAEs between the true and inferred embeddings given by different methods under various simulation scenarios, and (c) the ARIs between clustering results given by different methods and the true spatial domains. Error bars represent the mean $\pm$ standard deviation (SD). **d-e.** Zoomed-in views of the red-box region highlighted in panel (a). Scale bar: 500 μm **d.** The local true embeddings E1 and E2 and corresponding embeddings estimated by different methods. Spatial intensities of each embedding dimension are linearly scaled to $[0,1]$ for visualization. **e.** The local clustering results given by different methods. The numbers on the top of the subfigures are the ARIs in this local region. Black color represents regions that are incorrectly clustered. **f.** Heatmaps showing examples of the second simulation data generated from a human breast carcinoma sample and the corresponding H&E stained image. Scale bar: 300 μm. **g.** Zoomed-in views of the inferred embedding dimensions learned by various methods from one of the second simulation datasets (spot radius: 30 pixels) in the three selected ROIs in panel (f). Scale bar of ROI 1-3: 100, 100, and 50 μm. The whole-spots scenario means that expression of all spots of the simulation dataset are used for embedding learning, and the spots-masking scenario means that the ST expressions in the light blue boxes are masked for embedding learning.

Fig. 3. Embeddings learned from the adult mouse brain coronal section data MBC-01. a. Anatomical annotations from the Allen Reference Atlas – Mouse Brain. **b**. Representative embedding dimensions identified by DeepFuseNMF including the isocortex-associated dimensions (E15, E18, E9) and hippocampal-formation-associated dimensions (E10, E14, E16). **c-d**. Embedding dimensions associated with NeuN or GFAP protein expressions inferred by DeepFuseNMF, TESLA+NMF, NMF and SpiceMix and their zoomed-in views in four selected ROIs. Scale bar of whole image: 1mm. Scale bar of ROI 1-4: 250, 200, 150 and 200 μm. **e**. A heatmap showing the mean rankings of brain-region marker genes in each embedding dimension. Gene rankings are normalized to [0,1]. In each embedding dimension, the genes are ranked increasingly by their corresponding values in the loading matrix. **f-g.** Error bar plots showing gene rankings of marker genes of subregions of isocortex and hippocampal formation in associated embedding dimensions. Error bars: median $\pm$ median absolute deviation (MAD, a robust SD). DG: dentate gyrus; CA: cornu ammonias; CA1sp: pyramidal layer of field CA1; CA2sp: pyramidal layer of field CA2; CA3sp: pyramidal layer of field CA3.

Fig. 4. Spatial domains detected from the adult mouse brain coronal section data MBC-01. a. Zoomed-in views of clusters identified by different methods in the hippocampal formation. The spatial clusters were generated by Louvain clustering with resolution 2.0 on the embeddings learned by different methods, except for iStar which used the same number of clusters as DeepFuseNMF. For spot-level methods, spot radii are enlarged 1.2-fold for visualization. Scale bar: 300 μm. **b**. Anatomical annotations from the Allen Reference Atlas – Mouse Brain hippocampal formation. DG: dentate gyrus; CA: cornu ammonias. **c**. The raw expression and high-resolution expression recovered by DeepFuseNMF for the marker genes of hippocampal formation subregions. Scale bar: 300 μm. **d**. A refined cluster C9 located around the meninges. Scale bar: 500 μm. Right panel: The zoomed-in view of an ROI showing that this cluster is often smaller than a spot. Scale bar: 50 μm. **e.** Violin plots showing the recovered high-resolution expression of marker genes of major cell types in glial limitans and leptomeninges across different spatial clusters. FB: meningeal fibroblasts subtype. VSMC: vascular smooth muscle cell. **f.** The IHC image of GFAP and 4',6-diamidino-2-phenylindole (DAPI). Blue: DAPI; Yellow: GFAP in cluster C9; Pink: GFAP in other clusters. Right panels: Zoomed-in views of two ROIs. Scale bar: 1 mm. **g.** Violin plots of the IHC intensity levels of GFAP in meninges-related clusters identified by different methods. **h.** Violin plots of mean expressions of FB1 marker genes in meninges-related clusters' spots identified by different methods. P-values are obtained using the two-sided Wilcoxon rank-sum test. *: p-value ≤ 0.05; ***: p-value ≤ 0.001.

Fig. 5. Embedding and clustering results of the four PDOX samples. a. Upper panel: The H&E images with annotated tumor regions. Lower panel: Spot locations along with their species classifications based on their expressions of human and mouse genes. Scale bar: 1mm. **b**. Rows 1-3 showing the 95th percentile of spot-level embedding intensity for different species and subsequent rows displaying the mean rankings of various gene signatures across each embedding dimension. Gene rankings were normalized to [0,1]. CBX: cerebellar cortex. **c.** The embedding dimensions (E6, E13, E5) associated with SHH transcriptional signatures. Scale bar: 1mm. **d**. Left panel: Anatomical annotations from the Allen Reference Atlas – Mouse Cerebellum Cortex. Right panel: Spatial clusters identified by DeepFuseNMF, iStar, and SpiceMix in the Palbociclib A section. For SpiceMix, its filtered low-quality spots are colored in grey, and spot radius is enlarged 1.3-fold for better visualization. Scale bar: 1mm. Bottom panels: Zoomed-in views of the ROI in the light blue box of the top panel. Scale bar: 200 μm. **e.** Violin plots of the mean normalized expressions of human genes, tumor invasion genes, and tumor proliferation genes across spots dominated by clusters identified by DeepFuseNMF. P-values are obtained using the two-sided Wilcoxon rank-sum test. ***: p-value ≤ 0.001.

Fig. 6. Analysis of colorectal cancer samples. a-e. Analysis of sample CRC-01. **a.** The H&E image of sample CRC-01 with annotation by our pathologist. Annotated tumor, stroma, muscle and necrosis regions are outlined in red, green, brown and grey, respectively. Scale bar: 500 μm. **b.** Spatial clusters identified by DeepFuseNMF. Spatial clusters are annotated by their marker genes (see Fig. S16a). Scale bar: 500 μm. **C.** Spatial clusters identified by iStar and NSFH. For NSFH, its filtered low-quality spots are colored in grey, and spot radius is enlarged 1.2-fold for better visualization. Scale bar: 500 μm. **d.** Zoomed-in views of H&E images and clusters identified by DeepFuseNMF, iStar and NSFH. ROIs correspond to black-box regions in (a). Scale bar: 100 μm. **e.** Violin plots of mean gene expression of fibroblast, extracellular matrix (ECM), cancer-invasion and cancer-associated ECM (C-ECM) signatures. **f-j.** Analysis of sample CRC-03. **f.** The H&E image of a nearby slice of sample CRC-03 with pathologist annotation. Annotated tumor regions are outlined in red. Other regions are all stroma regions. Scale bar: 500 μm. **g.** Spatial clusters identified by DeepFuseNMF. Scale bar: 500 μm. **i.** Spatial clusters identified by iStar and NSFH. For NSFH, low-quality spots are colored in grey, and spot radius is enlarged 1.2-fold for better visualization. Scale bar: 500 μm. **i.** Violin plots of mean gene expression of *C1QC*+ macrophage markers. P-values are obtained using the two-sided Wilcoxon rank-sum test. **j.** Gene set enrichment analysis (GSEA) on cluster S1-related genes for antigen processing and presentation. The enrichment plots contain profiles of the running enrichment scores (RES) and positions of gene set members on the rank ordered list in GSEA. ***: p-value ≤ 0.001; ****: p-value ≤ 0.0001.