Title: Egocentric anchoring-and-adjustment of social knowledge in the hippocampal formation
Authors: Marta Rodríguez Aramendía, Mariachiara Esposito, & Raphael Kaplan
Affiliation: Department of Basic Psychology, Clinical Psychology, and Psychobiology, Universitat Jaume I, Castelló de la Plana, Spain
Email correspondence: kaplan@uji.es

Abstract

Recent work suggests the hippocampal formation(HF) assimilates relational social knowledge similar to how it transforms egocentric spatial cues into map-like representations. Yet whether hippocampal map-like representations of social knowledge still represent lingering egocentric biases is unclear. We test if a prominent egocentric bias involving an implicit reliance on self-knowledge when rating others, anchoring-and-adjustment, is present when the relative attributes of different social entities are assimilated by the HF. Participants provided likelihood ratings of partaking in everyday activities for themselves, fictitious individuals, and familiar social groups. Adapting a functional neuroimaging task from Kaplan and Friston, participants then learned a stranger's preference for an activity relative to one of the fictitious individuals and inferred how the stranger's preference related to the groups' preferences. Egocentric anchoring-and-adjustment was present when participants rated the other entities. Isolating the neural representation of egocentric anchoring-and-adjustment when flexibly comparing different social entities, the HF and dorsomedial prefrontal cortex(dmPFC) represented group-self rating discrepancy. Furthermore, the HF also reflected how well group preferences were remembered, where memory for group preferences correlates with task performance. We found the HF selectively represented group identity over other learned entities, confirming that the HF was primarily engaged by social comparisons in a more ample frame of reference. Taken together, these results imply that self-knowledge influences how the HF assimilates map-like knowledge about others.

Introduction

Learning via cognitive maps permits an organism to relate their current state to an internal model of the world [1]. Cognitive maps have inspired a better understanding of how neurons in the hippocampal formation(HF), including entorhinal cortex (EC), transform egocentric spatial cues into purely environment-centered allocentric coordinates supporting spatial navigation [2]. Growing evidence suggests the HF assimilates abstract knowledge similar to how it transforms spatial cues [3-6], where social learning tasks have been particularly successful in isolating this new role [7-11; see 12 for review]. In particular, Kaplan & Friston(2019) investigated social learning beyond well-studied self versus other comparisons by testing how a stranger's preference was learned relative to one individual and then compared to other individuals. The transformation from learning preferences relative to one point of reference and relating that preference to others highlighted a role for the HF in social inferences in an absolute reference frame(i.e., flexibly comparing everyone in one's social environment). Although comparisons were made on a 1D number line of preferences, the authors viewed an absolute reference frame as analogous to map-like allocentric reference frames. The extension of allocentric/absolute coding principles to social learning raises the possibility that spatial and social perspective-taking could rely on the same neural computations in the HF and beyond[13]. However, whether this form of hippocampal social learning is supported by an isometric map-like representation, or an integrated model of relational knowledge via more imprecise subjective mechanisms is unknown[14-16]. On one hand, firing fields of spatially-modulated hippocampal neurons resemble cartesian coordinates on a map[5,17] , yet the self often serves as a reference point when making memory-guided inferences[18,19]. Moreover, previous work involving social reference frame transformations used the self as one of the explicit reference points in all conditions[8]. Consequently, it is unclear if subjective biases might inform HF map-like representations of abstract knowledge about others.

One well-characterized subjective bias that could distort map-like learning is anchoring-and-adjustment, where an individual starts with an initial idea and incompletely shifts away from their initial starting point to make an inference [20]. In egocentric anchoring-and-adjustment, people commonly begin by recruiting self-knowledge and then adjust away from this self anchor to make inferences about others(e.g., You judge someone else's preference for a food that you like to be closer to your own preference than it should be)[21,22]. Notably, the more divergent others' attributes are from a participant's, the more adjustment is needed and the longer it takes to make the inference [23,24]. These findings are consistent with the proposition that adjustment from self-generated anchors occurs serially over time [19]. Relating anchoring to neural processes, social anchoring biases, where dorsomedial prefrontal cortex(dmPFC) tracks the divergence between self and other preferences [25]. Although egocentric anchoring is well-described in social decision tasks[25], evidence of its influence on map-like knowledge representations of the social world are missing [8,13].

Clues about how self-knowledge implicitly influences map-like representations of abstract knowledge come from work by Kaplan & Friston(2019). The authors had participants learn a stranger's preference for an everyday activity—relative to previously provided ratings for either themselves, a close friend, or a typical person on that same activity—and subsequently decide how the stranger's preference relates to the other two individuals' preferences. Highlighting how the metric nature of these abstract distances influenced

behavior, they observed a steady increase in the quickness and accuracy of the participant's responses when the stranger's rating was closer to one option versus another. In parallel, they identified a HF region relating to the absolute distance between the stranger's rating and the choice options differently depending on whether a self-comparison was present in the absolute reference frame[8]. Still, due to self preferences always being needed in the transformation and/or comparison process, it is unclear whether egocentric anchoring may occur during the task. By removing the explicit need to use self-knowledge during the inference process, while keeping everything else the same, we can measure the implicit representation of self preferences during relative to absolute reference frame transformations involving different social entities.

Here, we investigate the implicit influence of the self on inferences in an absolute map-like reference frame, we adapted the Kaplan & Friston(2019) paradigm by collecting preference likelihood ratings on everyday activities(e.g., eat spicy food, read a book, cycle to work). Participants provided ratings for themselves, two fictitious individuals, and two societal groups (people from cities and rural areas) from 1 to 9 on a 0-10 (ranging from impossible to happening at this moment) scale to allow for strangers with higher or lower ratings than the entities in the subsequent fMRI task(Fig. 1). To expedite learning of the fictitious individuals, we made the two individuals congruent with one of the two rated groups(a rural or urban person). Subsequently for the transformation phase that occurred while participants underwent functional magnetic resonance imaging(fMRI), participants inferred a stranger's preference for an everyday activity—relative to previously provided ratings for one of the two individuals—and decided how a stranger's preference relates to a medium preference(normal group) and a preference of one of the two groups. More specifically, participants needed to decide whether the stranger's rating was closer to one of the two groups, or a normal group with a medium rating of 5(Fig. 1). After deciding without any feedback, a jittered intertrial interval period(mean 2.5s) featuring a black fixation point overlaid on a gray background appeared on the screen before moving onto a new trial. After the fMRI task, participants provided ratings for all entities, including the self, on the same scenarios to assess consistency/memory for ratings.

Including two different types of both individuals and groups ensured that the rated entities, the stranger, and the participant didn't have overlapping ratings too often(see Methods for more details). Furthermore, separating the groups and individuals in different stages of a transformation trial allowed us to test what task representations were most important to the HF and dmPFC(Fig. 1C). Crucially, self ratings weren't necessary to perform the transformation phase of the task and unlike the previous version of the task, no spatial number line cues of preferences were provided to remove potential spatial scaffolding effects that could enhance performance. This experimental design allows us to study how the absolute distance between the stranger's rating and the ratings of the groups that are being compared with the stranger(absolute distance, AD), the differences between self and others' preferences(rating discrepancy, RD, with either groups or individuals), the cognitive demand of how far the stranger's preference is away from the individual's rating(rescaling), and the memory for self and others' preferences(rating consistency, RC, for groups or individuals) are represented during reference frame transformations of social knowledge(see Methods and Table S1 for more information, and Figure S1 for example).

The motivations behind our experimental design were threefold: First, to replicate both the egocentric anchoring-and-adjustment rating response time(RT) and accuracy findings in the social domain[23,24]; Second, to replicate the linear relationship between accuracy and the absolute distance between the stranger's rating and the compared groups' in the transformation phase[8]; Third, to isolate the behavioral and neural representation of egocentric anchor biases during reference frame transformations of abstract knowledge. We predicted that egocentric anchoring-and-adjustment would bias map-like representations of abstract knowledge in the hippocampal-entorhinal system and dmPFC. We employed representational similarity analysis(RSA) here because we were interested if trial-level differences in self-other(group or individual) rating discrepancy, independent of preference type(i.e., food, transportation, music, etc.), would be represented in a common format in the aforementioned regions during our social inference task.

Results
Behavioral results

During the anchor phase, the average time that participants took to provide ratings of others was 3.12s(SEM=0.085). We ran a linear mixed effects model to test the influence of various factors on determining self versus other discrepancy for each participant. We observed that the anchor entity, individuals and groups, influenced how participants judged the target. A significant effect of entity was observed (b=0.077, t(19)=2.10, p=0.036), indicating that participants rated the preferences of individual entities closer to their own preferences than those of group targets. Examining the hypothesized positive linear relationship between RT and self versus other discrepancy, we found a significant effect of RT on self-other discrepancy scores (b=0.21, t(19)=2.18, p=0.030). This result suggests that increases in RT correspond to increases in the magnitude of correction away from a self-anchor—evidence of serial adjustment present in anchoring-and-adjustment (Fig.2A).

To test if serial adjustment from self-knowledge occurred exclusively when the target was an individual or a group, we explored whether the relationship between RT and self–other discrepancy depended on entity type(i.e., individuals or groups). There was no significant interaction of the target entity on RT (b=-0.07, t(19)=-0.68, p=0.49). These findings replicate prior social anchoring-and-adjustment studies[23,24], aligning with the idea that participants anchor on self-knowledge and serially adjust away from this anchor when evaluating both individuals and groups.

Following previous work[8], participants' ratings for groups and individuals were generally consistent before and after scanning(Fig. 2C) ; participants were on average within ±1 of their original ratings for 75.2% (SEM=1.84 %) of group rating trials and only made large deviations from their original ratings > = 3 on 11.8% (SEM= 1.28%) of trials. For individual rating trials, they were on average within ±1 of their original ratings for 61.9% (SEM = 1.94 %) and only made large deviations from their ratings >= ±3 on 21.6% (SEM= 2.56%). For self preferences, participants had high consistency in recalling their own preferences, with a 74.40% of trial consistency within 1 of their original ratings, and 5% (SEM= 1.17%) of trials displayed large deviations >= 3. When relating subjective self-confidence to self rating consistency, confidence ratings significantly correlated with rating consistency (t(19) = -5.09; p < 0.001), where higher confidence ratings yielded more consistent ratings.

During the fMRI experiment, participants made 70.9% of decisions correctly (SEM =2.98 %, n=20), after eliminating trials for which either answer was correct (i.e., same or equidistant ratings), while mean RT was 4.48s (SEM = 0.11). Replicating previous findings in Kaplan & Friston, 2019, there was a positive correlation between the absolute distance of the choice options from the stranger and task performance(group-level statistics: $t(19) = 12.54$, $p < 0.001$; Fig. 2B), and a negative correlation with RT (group-level statistics: $t(19) = -2.65$, $p = 0.01$). Notably, we identified a negative correlation between RT and accuracy (group-level statistics:$t(19) = -5.33$, $p < 0.001$), indicating quicker RTs for accurate choices.

Furthermore, our investigation focused on the impact of egocentric anchoring-and-adjustment during the transformation phase, particularly in the absolute reference frame. Examining the effect of rating discrepancy (RD) and entities on choice accuracy, we observed a significant interaction between RD and entities ($F(2,38) = 11.30$, $p=0.0015$, partial eta squared ($\eta^2 p$) =0.37), where significant differences on performance were observed in the medium and high levels of RD between individuals and groups (mean differences in the medium bin = 8.5%, $p = 0.004$; mean differences in high bin = 5.73%, $p= 0.007$) (Fig. 2E). Next, we examined the influence of rating discrepancy on accuracy separately for individuals and groups. For individuals, a one-way ANOVA with three levels of RD (low, medium and high) showed no significant differences in accuracy ($F(2,38)=1.08,p=0.34,\eta^2 p=0.054$, Fig.2E). Additionally, no significant quadratic relationship was found ($t(19)=-1.16,p=0.87$), indicating that self versus individual rating discrepancy ($RD_{individual}$) didn't significantly impact task performance. In contrast, a one-way ANOVA for performance by self-group rating discrepancy (RD_{group}) revealed significant differences in accuracy ($F(2,38)=10.8,p=<0.001$, $\eta^2 p$ =0.36, Fig.2E). Moreover, a significant quadratic effect was observed ($t(19)=3.39,p=0.0015$, and Fig. S2), suggesting that the relationship between RD_{group} and performance follows a non-linear pattern.

Exploring the effect of memory on choice accuracy, we observed a significant interaction between rated entities and RC ($F(3,57) = 6.59$, $p < 0.001$, $\eta^2 p= 0.25$). In a post-hoc analysis, we observed significant differences between individuals and groups for the very inconsistent ratings >=±3 bin (mean differences = 14.97%, $p= 0.004$) (Fig. 2D). Then, we examined the relationship between performance and rating consistency (including memory for individuals and groups). We observed a significant correlation between these two variables($\rho=-0.59$, $p=0.005$). Next, we separately analyzed the correlation between accuracy and RC_{group}($\rho= -0.54$, $p=0.013$) and $RC_{individual}$($\rho=-0.52$, $p= 0.017$). For both entities, we observe a significant negative correlation between accuracy and memory for the rating of others. In other words, the more consistent participants rated others' preferences, the better they performed the fMRI task.

fMRI analysis
RSA searchlight
To test which regions represented egocentric anchor biases and other social inference demands during the transformation fMRI task, we performed whole-brain searchlight representational similarity analysis (RSA). Neural representational dissimilarity matrices (RDMs) were computed in a sphere centered on each voxel of the brain, and their relationships to behavioral RDMs were investigated(Fig. 3A). This allowed us to determine whether the neural representation of anchor biases in both relative (self rating discrepancy with individual rating: $RD_{individual}$) and absolute(self rating discrepancy with compared groups:

RD_{group}) reference frames is different after explaining variance related to other important cognitive aspects in the transformation phase. The additional cognitive predictors were the absolute distance between the stranger and choice options(AD), rescaling of the relative position of the stranger's rating in relation to the individual to its absolute position on the rating scale, as well as rating consistency for groups(RC_{group}) and individuals($RC_{individual}$).

In a whole-brain general linear model (GLM) analysis, we observed a relationship between group rating discrepancy(RD_{group}) and the left hippocampus pattern dissimilarity($x = –22, y = -19, z =-19$; $t(19)=3.78$, bilateral hippocampus small-volume corrected peak-voxel $p=0.046$; Fig. 3B), and the left entorhinal cortex($x = -19, y =-25 , z=-22$; $t(19)=4.37$, bilateral entorhinal cortex small-volume corrected peak-voxel $p=0.015$; Fig. 3B). Testing whether egocentric anchoring to the group in the hippocampus and entorhinal cortex was also present in individuals, we observed no similar effect in this hippocampal region for $RD_{individual}$($t(19)=-0.37$, $p=0.71$), nor for entorhinal cortex($t(19)= 0.081$, $p=0.93$). In a subsequent t-test, we tested whether this effect was specific to RD_{group}, where there was no significant difference between hippocampal pattern dissimilarity for RD_{group} versus $RD_{individual}$($t(19)=1.4$, $p=0.16$), nor for entorhinal cortex pattern dissimilarity($t(19)=1.75$, $p=0.09$). We then tested whether the effect found in the hippocampus peak and entorhinal peak was exclusive to the RD_{group} predictor. Using a 10 mm sphere, we examined in a post-hoc ROI analysis if this effect was present in the beta maps of other predictors. We found a significant effect for RC_{group} in both the bilateral hippocampus peak($t(19)=-3.01$, and $p=0.007$) and the entorhinal peak($t(19)= -2.49$, $p=0.02$), but not for the other predictors(Fig.3B). HF representation of RC is consistent with its putative role in mnemonic function[3].

Given our previous hypothesis about the role of dmPFC in egocentric anchoring-and-adjustment, we investigated whether there were any significant effects there. Despite not finding a significant dmPFC cluster for representing any variable of interest, we checked whether any effects were present in an ROI of the dmPFC. In the ROI, we observed a significant effect for RD_{group}($t(19) = 2.92$, $p = 0.008$, Fig. 3C). There were no significant dmPFC results for the other predictors. Testing whether the dmPFC rating discrepancy effects were selective to RD_{group}, a subsequent t-test revealed that there was no significant difference between dmPFC RD_{group} and $RD_{individual}$ pattern dissimilarity($t(19) = 0.74$, $p = 0.46$). Checking whether any other brain region significantly represented any variables in our GLM, we observed a significant peak for RD_{group} in the left ventrolateral prefrontal cortex($x= -55$, $y=21 , z=3$; $t(19)=5.55$, peak-level FWE $p= 0.039$), but no other significant effects for any variables anywhere else in the brain.

Pattern dissimilarity and RD_{group}

We then tested whether the behavioral influence of egocentric anchoring on our task was also present in HF and dmPFC representations. To investigate whether pattern dissimilarity in the HF and dmPFC followed the u-shaped effect found in the behavioral results between group rating discrepancy and Accuracy (Fig.2E and Supplemental Fig.S2), we conducted quadratic regression analyses. These analyses let us determine if there was a linear or quadratic effect between pattern dissimilarity and RD_{group}. However, we didn't find a significant U-shape effect in any region examined (hippocampus peak $t(19)= -0.84$, $p=0.79$, entorhinal peak $t(19)= -1.42$, $p=0.91$ and dmPFC ($t(19) = -1.26$, $p = 0.88$). We also investigated the possibility of a linear effect between pattern dissimilarity and RD group.

However, no significant linear effects were found across the hippocampal peak(t(19)= -0.66, p=0.74), entorhinal peak (t(19)=-1.65, p=0.94), and the dmPFC ROI(t(19) = -0.44, p = 0.67).

RSA social entity model comparison
To examine whether the hippocampus, entorhinal cortex, and dmPFC preferentially represented group identity, individual identity, or trial congruence during transformation trials, we generated trial-by-trial correlation matrices and contrasted them with the three aforementioned conceptual matrices. A trial was considered congruent when the individual and the social group involved in the transformation trial generally aligned to the same social category(i.e., an individual with an urban or rural background being paired with a respective city or village dweller group in the condition). This analysis allowed us to explore the impact of various task features on the regions' pattern dissimilarity. We hypothesized that trials featuring the same groups would exhibit greater similarity in their hippocampal representation than trials featuring the same individuals or congruent individual-group entities. For all of the regions studied, we observe significant differences in model fits (hippocampus peak, $F_{(2,38)}$= 29.08 , $p<0.001$; entorhinal peak, $F_{(2,38)}$=15.04 ,$p<0.001$ and dmPFC $F_{(2,38)}$=12.88,$p<0.001$). Following a significant ANOVA for each brain region, a paired T-test was performed to test pairwise differences between the three models. In the hippocampus peak, there was a significant difference between the group vs congruence models(t(19)=5.46, $p<0.001$) and group vs individual models(t(19)=6.37, $p<0.001$). Lastly, for the entorhinal peak, we observed a significant difference between group versus congruence models(t(19)=2.30, p=0.03) and group versus individual models(t(19)=4.68, $p<0.001$). These results demonstrate a consistent pattern across the regions, where the group model consistently outperformed both the individual and consistency models, suggesting that the group model better captures the underlying neural representations. In slight contrast for the dmPFC, there was no significant difference between the group vs congruence models(t(19)=1.97, p=0.06), but there was still a significant difference between group vs individual models(t(19)=5.15, $p<0.001$).

We then ran a searchlight RSA to test if there were other brain regions that were significantly modulated by the difference between the three models. We observed two significant peaks: one in the thalamus (x=-7,y= -16,z= 9; $F_{(2,38)}$= 13.42,$p_{FWE}<0.001$) and another in the ventral striatum(x=27, y=18,z= 6; $F_{(2,38)}$= 12.38, $p_{FWE}<0.001$). For the thalamus, we observed significant differences for the individual versus congruence model(t(19)= 3.88,$p<0.001$) and group versus congruence model(p<0.001, t(19)=3.63), while not finding any significant difference between individual and group models(t(19)=-0.12, p=0.9). For the ventral striatum peak, we observed significant differences between the group versus individual models(t(19)=-2.58, p=0.018), individual versus congruent model(t(19)=3.35, p=0.0034), and group versus congruence models(t(19)=4.25, p=0.002).

Discussion
We tested whether map-like representations of abstract social knowledge are susceptible to egocentric anchoring-and-adjustment. Replicating findings from social anchoring[23,24], we observed egocentric anchoring-and-adjustment when participants rated entities(Fig. 2A) and map-like social inference behavioral performance effects from the Kaplan & Friston paradigm(Fig. 2B). Highlighting the presence of egocentric anchoring in the HF and dmPFC, hippocampal-entorhinal and dmPFC pattern similarity was related to self versus group rating discrepancy(Fig. 3). Notably, the hippocampus and entorhinal cortex also represented how

well group preferences were remembered, which was a key indicator of task performance(Fig. 3). Testing whether the HF and dmPFC preferentially represent group identity, individual identity, or trial congruence during transformation trials, we find that the HF selectively represents group identity(Fig.4). In what follows, we speculate on how egocentric anchoring potentially shapes abstract knowledge codes and relate our findings to the wider literature.

The generality of egocentric biases on allocentric coding

Our experiment doesn't test whether HF and dmPFC representations of egocentric anchor biases during map-like inferences are selective to the social domain [12], or are more generally applicable to abstract knowledge [26]. Comparable work has uncovered the co-existence of egocentric and allocentric representations in different brain structures for abstract knowledge[27], which allows for the possibility that these parallel representations could be flexibility modulated depending on task demands. The switch between egocentric and allocentric processing could be flexibly adapted depending on task demands, which is supported by recent evidence showing personal biases can facilitate emotion prediction [28] and learning more generally[29]. Future work can study the relationship between egocentric anchoring and hippocampal generalization to uncover when self-projection is beneficial or detrimental in spatial and non-spatial inference tasks[19,30].

Effects of social cognition and relationship with the hippocampal formation

Our findings add to a growing literature highlighting the importance of the HF in assimilating social knowledge[7-10,31,32], although an important caveat to these findings is that no study has demonstrated they are specific to cognitive map-like or non-isometric/cartesian representations of social knowledge. Further investigation of the effect of subjective biases on cognitive maps of social space[7,9,10] and assimilation of knowledge in social networks[33-36] could yield insights into whether there are differences in subjective and objective map-like coding. Moreover, investigating subjective confidence and its relationship to egocentric anchoring in the HF could be a promising avenue of investigation. Lastly, we don't specifically investigate spatial or social perspective switching computations that likely rely on regions like the retrosplenial cortex(RSc)[37]. Future work can address whether social and spatial perspective transformations require similar underlying computations and how they might differ in areas like dmPFC or RSc [13,38].

The specificity of anchoring to groups versus individuals in allocentric reference frames

For neural representations of rating discrepancy(egocentric anchoring) and consistency(i.e., memory strength), we find that our ROIs represent these behavioral variables for group, but not individual ratings. Moreover, these RSA effects are paralleled by behavioral performance results(Fig.2D-E), where the accuracy of social inferences is most strongly determined by self-group rating discrepancy and group rating consistency. Taken together, these results suggest that the most crucial aspects of flexible map-like social inferences are how well attributes of the social groups in our task are learned and remembered in the absolute reference frame. An important caveat to these HF and dmPFC findings is that we cannot determine whether our effect is specific to egocentric anchoring for groups, or more generally relevant to any social entity in the absolute reference frame. This is especially

important because groups or any collective minded thinking can be seen as more allocentric[39], independent of any explicit reference frame transformation. Moreover, rating consistency was much lower for individuals than groups. This was likely because the groups, city and village dwellers, were more familiar than specific fictive individuals to participants. To resolve this issue, future studies can alternate whether individuals or societal groups are in the initial relative position to the stranger in our task and test how that changes task performance. Notably, different individuals were interchangeably used as the initial reference point and choice options in Kaplan and Friston(2019), which had similar behavioral results as this study. Therefore, we predict that our fMRI results would hold if the stranger was learned relative to a group and subsequently compared to individuals in the absolute reference frame.

Relating dmPFC effects to the Social Anchoring Literature

Building on previous work by Tamir and Mitchell (2010), we observed a relationship between dmPFC representational similarity and social anchoring(self versus group rating discrepancy) in our task. Previous work isolated dmPFC fMRI signals that related to self-other discrepancy when inferring mental states of one individual[25]. In contrast, our dmPFC self-other discrepancy results extend to non-linear social inferences that involves learning a stranger's preference relative to an individual and then extrapolating whether the stranger's preference is more similar to one of two groups' preferences. Consequently, we show that dmPFC isn't limited to its putative role of guiding one to one self-other comparisons[25,40] and can extend to more complex social inference of relating multiple social entities to each other.

dmPFC versus Hippocampal-Entorhinal Contributions to Social Learning

Despite the dmPFC and HF being commonly linked to social [25,40] and spatial [17] learning respectively, we find that both regions represent egocentric anchor biases during social inference. One of the key differences between the dmPFC and hippocampal-entorhnal system in our task is that the HF also represented how consistently preferences were rated. Finding hippocampal-entorhinal representations of how well groups' preferences are remembered is consistent with the region's putative role in long-term memory[3]. Additionally, we find that the HF selectively represents group identity during transformation trials. In contrast, we observed that the dmPFC represented group identity over individual identity, but not individual-group identity congruence. These results are consistent with the idea that HF maintains a map-like representation of one's social network[13], while dmPFC has a more general role in integrating multiple sources of information[41]. Taken together with work showing that knowledge storage of these self preference ratings relies on ventral mPFC[42], our results imply that dmPFC is ideally positioned in the brain to interface self-knowledge with map-like knowledge of others in the hippocampal-entorhinal system.

Conclusion

We highlight how personal preferences are present in the HF and dmPFC when making inferences about how others relate to each other. Future work can determine whether similar egocentric biases are transferable to cognitive map-like representations in spatial and other non-spatial domains[15]. By further disentangling the role of the self in shaping hippocampal

models of the world, a better understanding of variability in allocentric representations will be formed.

Methods:

Ethics Statement

Study participants were compensated and gave informed written consent to participate. The study was approved by the local research ethics committee at Universitat Jaume I (ethics reference: CD/10/2022). The study was conducted in accordance with Declaration of Helsinki protocols.

Participants

Thirty participants (16 female, with a mean age of 21.16 years, SD=3.46) took part in an experiment conducted at Universitat Jaume I, using an online recruitment system. Four participants were excluded due to poor performance (<60%). A further four participants were excluded due to excessive movement during the experiment and two participants were omitted due to technical issues during image acquisition resulting in a final sample of 20 participants. All participants were right-handed, had normal or corrected-to-normal vision, and had no history of neurological or psychiatric disorders.

Task

Stimuli were presented using PsychoPy (v 2020.1.1) toolbox running in Python 3.9. The task comprised distinct phases: anchor phase, transformation phase fMRI task, and rating consistency phase (Fig. 1A).

Anchor phase

Participants first provided likelihood ratings for 105 everyday activities adapted from [8](listed in Supplementary Information) on a scale from 0 to 10 (0 indicating impossibility, 10 indicating extreme likelihood). Following each question, participants provided a confidence rating on a scale from 1 to 5(from no idea to very sure), reflecting their confidence regarding their own preferences. To achieve a more varied distribution of ratings, we excluded the 30 trials that were nearest to the mean of each participant's preference, resulting in 75 trials for the subsequent phase.

Participants were then introduced to two individuals with a brief paragraph description and the name of two stereotypical groups(city dwellers and village dwellers). To make the individuals easier to learn, each fictitious individual was created to have preferences either more compatible with city or rural village living and were gender matched to the participant. Participants were given as much time as they needed to read the full description of the two individuals. Subsequently, participants judged the entities' preferences. Using the same 0-10 scale for self rating, participants expressed what they felt was the likelihood of each entity partaking in a variety of everyday scenarios within a 10 second time limit [8]. Participants only provided preference ratings for a given scenario once before and after the fMRI task.

Transformation fMRI-phase

Participants then performed a brief practice version of the fMRI social decision-making task(adapted from Kaplan & Friston, 2019) outside of the scanner, until they achieved a performance level of at least 70%. During the transformation task, participants inferred a stranger's preference relative to one of the familiar individuals using their previous ratings for

the individual entities. Subsequently, in a two-alternative forced choice task (2AFC) they determined whether that stranger's preference is more similar to a normal group (always a 5), or one of the two groups they previously rated[8] within ten seconds. Participants estimated the stranger's preference using a scenario, and a cue of less or more related to the preferences of the previously presented individual (e.g: The stranger eats spicy food more/less than the individual). If the cue was "more", participants had to add half of the difference between the individual preference and the high extreme of the scale (10) to the individual entity's preference. If the cue was "less", participants had to subtracted half of the difference between individual preference and the low extreme of the scale (0 to the individual entity's preference). Participants were instructed that it was a different stranger on each trial. Crucially, participants never received any feedback during the task.

We had four conditions, each based on the individual entity used to infer the stranger's value and the group entity presented as a choice option in the 2AFC(Fig.1A). The four different conditions were used to control for different levels of similarity between the rated entities and the participant, as well as schematic congruence between individuals and groups(level of attribute similarity between an individual and group entity in a given trial). Given the different compatibility between each rated individual and group, there were two conditions with a congruent rated individual and group(e.g., the urban oriented individual with city dwellers; the rurally oriented individual with village dwellers) and two involving an incongruent rated individual and group(i.e., the rurally oriented individual with city dwellers; the urban oriented individual with village dwellers). Due to time constraints for fMRI scanning, we excluded an additional 15 scenarios from the remaining 75 scenarios for the fMRI task, specifically those where participants rated the group preferences as 5 to avoid overlap with the normal group. Participants were therefore tested on the same 60 scenarios for all four conditions during the transformation phase, resulting in a total of 240 trials. These trials were distributed over four fMRI runs, with each run consisting of 60 trials that were assigned completely randomly. Trials were self-paced, allowing participants to determine the time for each trial(mean=4.48s) with a maximum allowed RT of 10s. As in the Kaplan & Friston study[8], any transformation trial where both choice options were correct wasn't included in the analyses

All of the information needed to perform the task was presented at once on the screen, and the aspects of the task that varied from trial to trial were the egocentric reference frame(individual), the cue (that connects individuals preferences and stranger preferences), and the choice options(see Fig. 1A). Participants had a maximum of 10s to make a decision, followed by a jittered ITI period (mean = 2.5 s; range = 1-4s), where a white fixation cross on gray background was presented. After completing the fMRI task, participants were asked to give ratings for themselves and the four entities again to test the consistency/memory for their preferences.

Anchoring-and-adjustment analysis
To study the anchoring and adjustment effect during the anchor phase, we applied a linear mixed effect model(equation 1). Our focus was on studying the relationship between participant RTs and rating discrepancy(RD), calculated as the absolute differences between participants' self-preferences and others' preferences, when inferring others' preferences. To assess differences between egocentric anchoring and adjustment for individuals and groups, we included the anchor entity and the interaction with RT as predictive variables in the model.

$$RD \sim RT+ \text{ anchor entity} + RT*\text{anchor entity} + (1| \text{participant}) \text{ (equation 1)}$$

We tested for egocentric anchoring-and-adjustment by incorporating the fixed effect of RT, which is the positive correlation between RT and self–other discrepancy [23,24]. We added participants as nested variables in the model. Trials in which participants did not provide a response within the 10-second window during the self-rating or anchor phase were excluded from the analysis. This exclusion was necessary due to the impossibility to calculate the rating discrepancy variable in such instances. RTs were log-transformed to address their right-skewed distribution, and we excluded responses whose log RTs were >=2.5 SD from the grand mean[43].

fMRI acquisition
Whole-brain structural and functional MRI data were acquired using 3T General Electric Signa Architect magnetic resonance imaging (MRI) scanner using a 32-channel head coil. Four whole-brain functional runs were acquired using a multi-band multi-echo (MBME) EPI sequence (voxel size= 3 mm isotropic, TR = 2 s; TEs = 18.5, 34.16, and 49.82 ms,; flip angle θ = 80; resolution matrix = 80 × 80, and a multi-band acceleration factor = 2). We used a functional sequence that sets the slice angle of 30° relative to the anterior-posterior commissure line to minimize signal loss in the medial temporal and orbitofrontal regions [44]. Structural T1-weighted images were acquired using an MPRAGE sequence (TR = 2.5 s; flip angle = 8, and slice thickness = 1 mm).

fMRI data analysis

Calculation of behavioral dissimilarity matrices
For each participant and run, we calculated trial by trial dissimilarity matrices for each of the behavioral variables of interest: absolute distance between choices(AD), rescaling, self versus individual rating consistency($RC_{individual}$), self versus group rating consistency(RC_{group}), self versus group rating discrepancy(RD_{group}), and self versus individual rating discrepancy($RD_{individual}$). These matrices were constructed by computing the absolute differences between the values of these variables across trials.

Representational similarity analysis (RSA)
We performed a whole-brain searchlight-based multiple regression RSA to examine brain regions in which changes in dissimilarity between neural activity patterns in the trials is explained by the behavioral variables of interest. To create the neural representation dissimilarity matrix (nRDM) for each voxel, a spherical searchlight was run by defining a sphere with a radius of four voxels that was moved across the brain, capturing the dissimilarity of neural activity patterns across trials[45]. Next, we perform a single value decomposition analysis to reduce the dimensionality to ten dimensions, where these first ten dimensions capture 76.04% variance for all participants and searchlights. To investigate how changes in behavioral variables relate to neural fMRI signal patterns in different brain regions, we applied a voxel-wise GLM to predict the nRDM with six behavioral predictors (Fig. 3A). Behavioral matrices were standardized before performing regressions. For each participant, the multiple regression-based RSA provided a beta map for each of the six predictors. These beta maps indicate the relative influence of each predictor on the dissimilarity of neural activity patterns within the searchlight spheres. In a second-level

analysis, the resulting beta estimates for each participant and for each voxel were testing the regression coefficients against zero using one sample t-test.

In addition to the searchlight-based RSA, we ran a ROI-based RSA in dmPFC. We computed the trial by trial nRDM for each ROI and also applied the aforementioned dimensionality reduction. The resulting nRDM was then introduced as the independent variable in the same GLM(Fig. 3A) employed for the searchlight analysis.

Pattern dissimilarity by RD$_{group}$

We extracted the beta values within a 10mm radius sphere around the hippocampal peak, entorhinal peak, and dmPFC ROI for each participant from the corresponding beta image for each trial. Subsequently, we concatenated all trials from different runs and constructed correlation matrices for trials that share the same RD$_{group}$ value, resulting in nine representational dissimilarity matrices. Trials with a singular representation for an RD$_{group}$ category were excluded from the analysis. To quantify dissimilarity, we convert correlation values to dissimilarity using the 1 - correlation. Following this transformation, we calculated the mean pattern dissimilarity value for each nRDM.

To study the relationship between accuracy and pattern dissimilarity with RD$_{group}$, we calculate two regression models for each participant. We add a quadratic term $(RD_{group} - \underline{RD_{group}})^2$ to account for potential symmetrical quadratic relationships, where the β2 coefficient expresses the strength of the quadratic relationship between dependent variables and RD$_{group}$.

$$Accuracy = b + \beta1 * RD_{group} + \beta2 * (RD_{groups} - \underline{RD_{group}})^2 Pattern\ dissimilarity$$
$$= b + \beta1 * RD_{group} + \beta2 * (RD_{group} - \underline{RD_{group}})^2$$

For the group-level analysis, we test if the β2 coefficients were significantly different from zero, which allows us to study the quadratic relationship. To study the relationship between these two models, we correlated the beta values for each regression between them. This correlation between coefficients across participants helped us identify consistent patterns in the direction of the quadratic effects.

Model matrix comparisons
To test specific hypotheses about how groups, individuals, and trial congruency are represented, we compared trial by trial correlation matrices for pattern similarity data to model matrices(Fig. 4A). Beta images for each trial, resulting from the preprocessing step in the *Beta series modeling* section, were masked with a 10 mm radius spherical mask on significant peaks identified in the RSA searchlight analysis and in the ROI dmPFC. The beta values underwent pairwise comparisons resulting in a trial by trial nRDM, for each participant and run. We computed three model matrices: (1) congruent model, (2) group model, and (3) individual model.

For the congruence model, transformation trials were classified as congruent when the egocentric reference frames (individuals) and allocentric reference frames (groups) belong to

the same social category (i.e. trials involving city individual and city group). Conversely, trials were considered incongruent when the egocentric and allocentric reference frames belong to different categories(i.e., city individual and rural people group). To calculate congruence matrices, we hypothesize that trials within the same congruence condition will exhibit higher correlations with other trials sharing the same condition. To calculate the group model matrix and the individual model matrix, we hypothesized that trials that involves the same social groups or the same individuals will contain more similar representations. Model matrices were constructed assigning a value of 0 to trials with a hypothesized high correlation (similarity), and a value of 2 to those with a hypothesized low correlation (dissimilarity).

To evaluate model fit, we computed a partial correlation between participant average trial-wise pattern similarity data and each of the 3 model matrices using the lower half of the matrix (excluding comparisons involving the same trials) after eliminating the effect of condition. At the group-level, we computed one-way ANOVAs and a paired T-test. These statistical analyses allowed us to compare fits across models.

In addition to the model matrix comparison RSA, we performed a whole-brain searchlight-based multiple regression RSA to examine the brain areas in which the change in dissimilarity between neural activity patterns in the trials is explained by the different three models. Subsequently, we performed an ANOVA to compare the difference between the coefficients for each model and a paired t-test to determine which model was driving the observed effects.

fMRI statistical analysis
For the whole-brain results, the statistical analyses are performed using 10 mm radius spheres in Nilearn toolbox (v.0.10.2)[46] around the respective peak-voxel specified in the voxel-wise GLM analysis. We report peak-voxels in the hippocampus, dmPFC and entorhinal cortex that survive small-volume correction for multiple comparisons ($p<0.05$) based on bilateral hippocampal, dmPFC, and entorhinal cortex masks. We defined the bilateral hippocampal region using the Wake Forest University (WFU) PickAtlas, integrated with SPM [47,48]. The entorhinal cortex mask was created based on prior literature [8,49,50]. For the regions of interest (ROI) analysis, we define the dmPFC mask [51] as the medial wall of the prefrontal cortex that forms part of Brodmann areas 9 and 10. Additionally, medial parts of Brodmann area 8 adjacent to area 9, as well as the dorsomedial portion of area 32, have been included. For all analyses outside the regions of interest (ROIs), we report activations surviving an uncorrected statistical threshold of $p=0.001$ and correction for multiple comparisons at the whole-brain level (FWE $p<0.05$) either at the peak-voxel or cluster-level. Coordinates of brain regions are reported in MNI space. Analysis was performed using a Python open-source RSAtoolbox v.3.0 (https://github.com/rsagroup/rsatoolbox, [52]) and statsmodels toolbox v. 0.14.0 (https://github.com/statsmodels/statsmodels, [53]).

Acknowledgments
We thank María Baena Pérez and Esteban Villar Rodríguez for assisting with fMRI piloting, Maria Picó Pérez for fMRI preprocessing advice, and Ameer Ghouse for statistical and programming assistance. We thank Shahar Arzy and Maya Visser for feedback on a previous version of this manuscript. We thank General Electric for providing a pilot version of their multi-echo fMRI sequence package. This research is supported by grants awarded to

References

1- Tolman, E.C. 1948. Cognitive maps in rats and men. Psychol Rev

2- O'Keefe, J., & Nadel, L. 1978. The Hippocampus as a Cognitive Map. Oxford University Press

3- Schiller D., Eichenbaum, H, Buffalo, EA, Davachi L, Foster, DJ, Leutgeb S, Ranganath C. 2015. Memory and Space: Towards an Understanding of the Cognitive Map. J Neurosci. 35(41):13904-11.

4- Kaplan, R., Schuck, NW, & Doeller CF. 2017. The Role of Mental Maps in Decision-Making. Trends Neurosci 40(5):256-59.

5- Behrens, TEJ, Muller, TH, Whittington, JCR, Mark, S, Baram, AB, Stachenfeld, KL, Kurth-Nelson. Z. 2018. What is a Cognitive Map? Organizing Knowledge for Flexible Behaviour. Neuron. 100(2):490-509.

6- Bellmund, JLS, Gärdenfors P, Moser EI, Doeller CF. 2018. Navigating cognition: Spatial codes for human thinking. Science 362(6415)

7- Tavares R.M., Mendelsohn A., Grossman Y., et al. (2015). A map for social navigation in the human brain. Neuron, 87(1), 231–43.

8- Kaplan, R; Friston, KJ. 2019. Entorhinal transformations in abstract frames of reference. PLoS Biology. 17, pp. e3000230.

9- Park S.A., Miller D.S., Nili H., Ranganath C., Boorman E.D. (2020). Map making: constructing, combining, and inferring on abstract cognitive maps. Neuron, 107(6), 1226–38.e8.

10- Park S.A., Miller D.S., Boorman E.D. (2021). Novel inferences in a multidimensional social network use a grid-like code. Nature Neuroscience, 24(9), 1292–301.

11- Zhang, L., Chen, P., Schafer, M. et al. A specific brain network for a social map in the human brain. Sci Rep 12, 1773 (2022).

12- Schafer M., Schiller D. (2018). Navigating social space. Neuron, 100(2), 476–89.

13- Arzy, S; Kaplan, R. 2022. Transforming social perspectives with cognitive maps. Soc Cogn Affect Neurosci. 17(10): pp. 939-55.

14- Tversky, B. (1993) Cognitive maps, cognitive collages, and spatial mental models.

15- Tversky, B. (2019). Mind in motion: How action shapes thought. Hachette UK

16- Peer M., Hayman M, Tamir, B., Arzy S. (2021) Brain Coding of Social Network Structure. J Neurosci. 41(22):4897.

17- Buzsáki, G., Moser, E. 2013. Memory, navigation and theta rhythm in the hippocampal-entorhinal system. *Nat Neurosci* 16:130–138.

18- Sui J, Humphreys GW. 2017. The ubiquitous self: what the properties of self-bias tell us about the self. Ann N Y Acad Sci. 1396(1):222-235.

19-Todd, A.R. & Tamir D.I. (2024). Factors that amplify and attenuate egocentric mentalizing. Nature Reviews Psychology

20- Tversky, A., & Kahneman, D. (1974). Judgment under uncertainty: Heuristics and biases. Science, 185(4157), 1124–1131.

21- Epley, N., Keysar, B., Van Boven, L., & Gilovich, T. (2004). Perspective taking as egocentric anchoring and adjustment. Journal of Personality and Social Psychology, 87(3), 327–339.

22- Epley, N., & Gilovich, T. (2006). The anchoring-and-adjustment heuristic: Why the adjustments are insufficient. Psychological Science, 17(4), 311–318.

23-Tamir, D. I., & Mitchell, J. P. (2013). Anchoring and adjustment during social inferences. Journal of Experimental Psychology: General, 142(1), 151–162.

24- Wang, Y. A., Simpson, A. J., & Todd, A. R. (2023). Egocentric Anchoring-and-Adjustment Underlies Social Inferences About Known Others Varying in Similarity and Familiarity. Journal of Experimental Psychology: General.

25- Tamir, D. I., & Mitchell, J. P. (2010). Neural correlates of anchoring-and- adjustment during mentalizing. Proceedings of the National Academy of Sciences of the United States of America,107(24),10827–10832.

26- Boorman, E.D., Sweigart, S.C., Park, S.A. 2021. Cognitive maps and novel inferences: a flexibility hierarchy. Current Opinion in Behavioral Sciences. 38:141-49.

27- Viganò S, Bayramova R, Doeller CF, Bottini R. Mental search of concepts is supported by egocentric vector representations and restructured grid maps. Nat Commun. 2023 Dec 8;14(1):8132.

28- Zhao Z, Sened H, Tamir DI. 2023. Egocentric Projection is a Rational Strategy for Accurate Emotion Prediction. J Exp Soc Psychol 109:104521.

29- Tarantola, T., Kumaran, D., Dayan, P., & De Martino, B. 2017. Prior preferences beneficially influence social and non-social learning. Nat Commun. 8:817.

30- Sui J, Humphreys GW. 2015. The Integrative Self: How Self-Reference Integrates Perception and Memory. Trends Cogn Sci. 19(12):719-728.

31- Kumaran D, Melo HL, Duzel E. (2012). The emergence and representation of knowledge about social and nonsocial hierarchies. Neuron, 76(30:653-66.

32- Kumaran D, Banino A, Blundell C, Hassabis D, Dayan P. (2016). Computations Underlying Social Hierarchy Learning: Distinct Neural Mechanisms for Updating and Representing Self-Relevant Information. Neuron, 92(5):1135-47.

33-Peer M, Brunec I.K., Newcombe N.S., Epstein R.A. (2021). Structuring Knowledge with Cognitive Maps and Cognitive Graphs. Trends Cogn Sci, 25(1):37-54.

34- Du, M., Basyouni, R., & Parkinson C. (2021). How does the brain navigate knowledge of social relations? Testing for shared neural mechanisms for shifting attention in space and social knowledge. Neuroimage. 235:118019.

35- Son JY, Bhandari A, FeldmanHall O. (2021). Cognitive maps of social features enable flexible inference in social networks. Proceedings of the National Acad Sci, 118(39):e2021699118.

36- Son JY, Bhandari A, FeldmanHall O. (2023). Abstract cognitive maps of social network structure aid adaptive inference. Proceedings of the National Acad Sci, 120(47):e231080112

37- Bicanski, A, Burgess N. 2018. A neural-level model of spatial memory and imagery. Elife. 7:e33752.

38- Tversky, B. (2011). Spatial thought, social thought. In: Spatial Dimensions of Social Thought. Vol. 18, Berlin, Boston: De Gruyter Mouton. 17–38.

39- Triandis H.C., Leung K., Villareal M.J., Clack F.I. (1985). Allocentric versus idiocentric tendencies: convergent and discriminant validation. Journal of Research in Personality, 19(4), 395–415.doi:

40- Amodio DM, Frith CD. 2006. Meeting of minds: the medial frontal cortex and social cognition. Nat Rev Neurosci. 7(4):268-77.

41- Kolling N, O'Reilly JX. 2018. State-change decisions and dorsomedial prefrontal cortex: the importance of time. Current Opinion in Behavioral Sciences, 22:152-60.

42- Stendardi, D; Giordani, LG; Gambino, S; Kaplan, R; Ciaramelli, E; 2023. Who am I really? The ephemerality of the self-schema following vmPFC damage. Neuropsychologia. 188:108651.

43- Baayen, R. Harald, & Milin, Petar. "Analyzing reaction times." *International journal of psychological research* 3.2 (2010): 12-28.)

44- Weiskopf, N., Hutton, C., Josephs, O., Deichmann, R. (2006). Optimal EPI parameters for reduction of susceptibility-induced BOLD sensitivity losses: A whole-brain analysis at 3 T and 1.5 T. NeuroImage, 33:2, p.493-504,

45- Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis-connecting the branches of systems neuroscience. Frontiers in systems neuroscience, 4

46- Gorgolewski, K., C. D. Burns, C. Madison, D. Clark, Y. O. Halchenko, M. L. Waskom, and S. Ghosh. 2011. "Nipype: A Flexible, Lightweight and Extensible Neuroimaging Data Processing Framework in Python." Frontiers in Neuroinformatics 5: 13. https://doi.org/10.3389/fninf.2011.00013.

47-Maldjian, J. A., Laurienti, P. J., Kraft, R. A., & Burdette, J. H. (2003). An automated method for neuroanatomic and cytoarchitectonic atlas-based interrogation of fMRI data sets. Neuroimage, 19(3), 1233-1239.

48- Maldjian, JA, Laurienti, PJ, Burdette, JB, Kraft RA. An Automated Method for Neuroanatomic Precentral Gyrus Discrepancy in Electronic Versions of the Talairach Atlas. Neuroimage 2004; 21(1) 450-455.

49- Chadwick MJ, Jolly AE, Amos DP, Hassabis D, Spiers HJ. A goal direction signal in the human entorhinal/subicular region. Current Biology. 2015;25:87–92. doi: 10.1016/j.cub.2014.11.001.

50- Garvert, M. M., Dolan, R. J., & Behrens, T. E. (2017). A map of abstract relational knowledge in the human hippocampal–entorhinal cortex. *elife*, *6*, e17086.

51- Jenkinson, M., Beckmann, C. F., Behrens, T. E., Woolrich, M. W. & Smith, S. M. FSL. Neuroimage 62, 782–790 (2012).

52-Schütt H (2023) Representational Similarity Analysis 3.0, version swh:1:rev:01e767c432e77633fe31304201718afce6a6ff9c Software Heritage.

53- Seabold, S., & Perktold, J. (2010, June). Statsmodels: Econometric and statistical modeling with python. In Proceedings of the 9th Python in Science Conference (Vol. 57, No. 61, pp. 10-25080).

54- Kundu, P., Inati, S. J., Evans, J. W., Luh, W. M., & Bandettini, P. A. (2012). Differentiating BOLD and non-BOLD signals in fMRI time series using multi-echo EPI. Neuroimage, 60(3), 1759-1770.

55- Kundu, P., Brenowitz, N. D., Voon, V., Worbe, Y., Vértes, P. E., Inati, S. J., ... & Bullmore, E. T. (2013). Integrated strategy for improving functional connectivity mapping using multiecho fMRI. Proceedings of the National Academy of Sciences, 110(40), 16187-16192.

56- DuPre, E., Salo, T., Ahmed, Z., Bandettini, P. A., Bottenhorn, K. L., Caballero-Gaudes, C., ... & Handwerker, D. A. (2021). TE-dependent analysis of multi-echo fMRI with tedana. *Journal of Open Source Software*, *6*(66), 3669.

57-Whitaker, K., & Handwerker, D. A. (2021). TE-dependent analysis of multi-echo fMRI with tedana. Journal of Open Source Software, 6(66), 3669. doi:10.21105/joss.03669

58- Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., Kent, J. D., Goncalves, M., DuPre, E., Snyder, M., Oya, H., Ghosh, S. S., Wright, J., Durnez, J., Poldrack, R. A., & Gorgolewski, K. J. (2019). fMRIPrep: A robust preprocessing pipeline for functional MRI. Nature Methods, 16(1), 111–116. https://doi.org/10.1038/s41592-018-0235-4

59- Satterthwaite TD, Elliott MA, Gerraty RT, Ruparel K, Loughead J, Calkins ME, Eickhoff SB, Hakonarson H, Gur RC, Gur RE, Wolf DH, An improved framework for confound regression and filtering for control of motion artifact in the preprocessing of resting-state functional connectivity data. NeuroImage. 2013. doi:10.1016/j.neuroimage.2012.08.052

60- Murphy, K., Birn, R. M., Handwerker, D. A., Jones, T. B., & Bandettini, P. A. (2009). The impact of global signal regression on resting state correlations: are anti-correlated networks introduced?. Neuroimage, 44(3), 893-905.

Figure 1. Experimental paradigm. A. Anchor phase. Before and after fMRI scanning, participants provide a likelihood rating for themselves in different everyday scenarios, as well as confidence ratings about each preference. After reading a description of two different fictive individuals and being presented with two different social groups, participants rate the likelihood of these entities from 1-9(very unlikely to very likely) on a scale of 0 to 10 to partake in a given everyday scenario. B. Transformation phase. During fMRI scanning, participants infer a stranger's preference relative to one of the previously rated individuals in a particular scenario and in a two-alternative forced choice(2AFC) determine whether that stranger's preference is more similar to a normal group(participants were informed beforehand that this group always has a preference rating of 5), or one of the two groups they previously rated(using the preference rating provided by the participant for that entity). The 2AFC was self-paced(mean=4.48s) and intertrial interval duration lasted a mean of 2.5s(range 1-4s) over four runs. C. Relative versus absolute references frames in a transformation phase trial. In the relative reference frame, participants need to infer a stranger's preferences only relative to an individual's preference. In the absolute reference frame, the similarity of the stranger's preference(4 in this example) is then compared to one of the rated groups and a normal group. The discrepancy between the self rating(2 in this

example) and presented entities in both reference frames is also measurable(degree of egocentric anchoring).

Figure 2. Behavioral results: A. Positive relationship between self versus other entity rating discrepancy(RD) and reaction time(RT: centered by group mean). B. Significant relationship between accuracy and absolute distance between the stranger's rating and two choice options for each trial. C. Distribution of group and individual rating consistency (RC). D. Significant difference in accuracy for rating discrepancy for groups and individuals. E. Significant differences between individuals and group rating discrepancy and accuracy. All error bars showing mean ± SEM with dots representing individual participants. Asterisks showing significant differences: *= p<.05, ** = p<0.01 , *** =p<0.001.

Figure 3. Egocentric anchoring-and-adjustment in the hippocampus. A. Neural and behavioral representational dissimilarity matrices(RDMs) for the general linear model(GLM) searchlight analysis for one representative participant. The neural RDM was used as a dependent variable with six predictor behavioral variables. These six variables were the absolute distance between the stranger's rating and the ratings of the groups that are being compared with the stranger(absolute distance, AD), the differences between self and others' preferences(rating discrepancy, RD, with either groups or individuals), the cognitive demand of how far the stranger's preference is away from the individual's rating(rescaling), and the memory for self and others' preferences(rating consistency, RC, for groups or individuals). To construct the behavioral matrices, absolute differences between these variables on each trial pair comparison were computed. Matrices were standardized before performing regression. B. Top: Group activation maps for self versus group rating discrepancy(RD_{group}). Differences in RD_{group} were significantly associated with left entorhinal cortex (right) (small-volume corrected family-wise error (FWE) for bilateral entorhinal cortex mask, peak-voxel corrected p=0.015) and left hippocampus pattern dissimilarity(left: small-volume corrected FWE for bilateral hippocampus mask, peak-voxel corrected p=0.046). Bottom: Barplot showing coefficients(mean ± SEM) for a 10-mm sphere around significant entorhinal and hippocampal regions exhibiting for each behavioral variable of interest. C. Beta coefficients of RSA GLM in ROI of dmPFC. Bars showing beta coefficients resulting from the GLM for each behavioral variable in the dmPFC, where there is a significant dmPFC effect for RD_{group}(t(19) = 2.92, p = 0.008). Each dot represents an individual participant. **= p<0.01, *=p<.05

Figure 4. Neural representational model comparisons A. Model matrices based on hypothesized representational conditions: congruent versus incongruent individual and group entities(congruence), group trial identity(group), and individual trial identity(individual). B. Correlation between model RDMs and neural RDM in the left hippocampus peak(HC), left entorhinal peak(EC), and dmPFC, where group trial identity is the winning model. All error bars showing mean ± SEM with dots representing individual participants. ***= p<0.01, *=p<.05.