Creation of MLPA: A Multi-level Digital Twin Framework for Personalized Cancer Simulation and Treatment Optimization

James Gu[1], Jake Y Chen[*2]

[1]Basis Independent Fremont, CA, USA

[2]Informatics Institute, School of Medicine, The University of Alabama at Birmingham, AL, USA

*Correspondence: jakechen@uab.edu

Summary

This research proposes a new personalized cancer modeling and treatment strategy: the Multi-level Parameterized Automata (MLPA), an innovative digital twin framework. The MLPA framework fully integrates macroscopic electronic health records (EHR) and microscopic genomic data for the first time, employing stochastic cellular automata to model tumor progression and treatment efficacy dynamically.

The multi-scale strategy effectively enables MLPA to simulate complex cancer behaviors, including metastasis and pharmacological responses, with remarkable precision. The validation using bioluminescent imaging from mice demonstrates MLPA's exceptional predictive power, achieving a state-of-the-art R^2 value of 0.93, improvement over previously reported conventional models, and fitting within 95% confidence intervals.

The proposed MLPA framework accurately captures tumors' characteristic S-shaped growth curve and shows high fidelity in simulating various scenarios, from natural progression to aggressive growth and drug treatment responses. MLPA's ability to simulate drug effects through gene pathway perturbation, with predicted tumor cell counts being within a 2.5% equivalence margin interval, underscores its potential as a powerful method for precision oncology.

The proposed MLPA framework not only offers a more reliable platform for exploring personalized treatment strategies, but also potentially transforms patient outcomes by optimizing therapy based on individual human biological profiles. As clinically adopted technology progresses towards precision medicine, MLPA stands at the forefront, offering new possibilities in cancer simulation and treatment optimization. The code and imaging dataset used is available at https://github.com/alphamind-club/MLPA.

35   **Keywords**: Stochastic Cellular Automata, Cancer Growth, Gene Regulatory Pathways, Drug

36   Response, Simulation Model, Digital Twins.

Introduction

Based on the Center for Disease Control and Prevention's recent report, cancer is the second

leading cause of death in the United States, with 608,371 deaths recorded annually [1]. By 2040,

there will be a predicted 26.0 million cases of cancer in the United States alone, a massive

increase from the 18.1 million diagnoses in 2022. Cancer is particularly dangerous due to its

ability to evade the body's immune system, while spreading to other organs through a process

known as metastasis [2]. Its rapid and uncontrolled cell growth can overwhelm normal tissues,

disrupting vital functions and making treatment difficult, especially in advanced stages while

also being difficult to detect in preliminary stages. This staggering growth of cancer cases

highlights the urgent need for the development of more effective cancer prediction and treatment

methods in today's clinical workflows. Despite significant advancements in oncology, cancer's

inherent complexity and heterogeneity, marked by distinct genetic mutation patterns and diverse

clinical presentations [3-4], often render traditional drug treatment strategies ineffective, leading to

suboptimal patient outcomes [5-6]. The challenge lies in developing personalized treatment

approaches that account for the unique characteristics of each patient's cancer [7-8].

In recent years, advancements in cancer prediction—aimed at simulating disease progression and

optimizing treatment strategies—have primarily been driven by two key approaches: statistical

modeling and machine learning techniques. The work of Mascheroni et al. stands out as an early

effort to address data sparsity in personalized tumor growth prediction [9]. By combining Bayesian

and mechanistic modeling, they laid the groundwork for more robust cancer modeling, but their

method still struggled with feature selection—a recurring challenge even in recent models. Lai et

al. took a different route by using cellular automaton techniques for breast cancer therapy [10].

Their model is noteworthy for its scalability, but like many statistical approaches, it lacks

generalizability across different tumor types, restricting its broader clinical utility. More recent

research, such as Valentim et al., have continued to explore cellular automaton models. Although

Valentim's work offers an innovative way to simulate various tumor growth scenarios, the

absence of real-world data calibration still raises concerns about accuracy when translating these

simulations into clinical applications [11]. Velasquez et al. compares parametric models for

predicting overall survival in RET-altered solid tumors, showing superior accuracy for

mathematical models but highlighting the need for further validation across tumor types [12].

Additionally, Wang et al. developed a prostate cancer prediction model using parametric

statistical methods, though it lacks lifestyle and comorbidity data, limiting its overall utility [13].

Despite these contributions, statistical methods often struggle to integrate diverse and large-scale

datasets, which limits their predictive power.

On the other hand, it has been proven that the machine learning approach has an advantage over

this limitation by having the capability to process large, complex datasets in tandem with

multimodal data. Rabiei et al. and Tătaru et al. used Random Forest and Gradient Boosting Trees

for breast and prostate cancer prediction, respectively, achieving around 80% accuracy with high

sensitivity and specificity [14-15]. However, their models' lack of genomic or lifestyle data limits

their generalizability, a recurring problem in this domain. Groheux et al. also explored machine

learning in breast cancer prediction, yet similarly acknowledged that omitting genomic inputs

constrained their model's predictive power [16]. Interestingly, Steyaert et al. pushed the boundaries

of machine learning by incorporating both gene expression and histopathology data in their brain

tumor prognosis models [17]. This approach significantly enhanced survival predictions, offering a

glimpse into the future of integrating multiple data types to improve accuracy. In contrast, Vale-

Silva et al. integrated genomic data for long-term cancer survival prediction, but still faced

performance variability across cancer types, highlighting that even models with comprehensive

datasets need further refinement [18].

Moreover, very recent developments in digital twin technology, particularly from the Swedish

Digital Twin Consortium, have sparked considerable interest in their potential to revolutionize

personalized treatment strategies [19]. Their work emphasized patient-specific models that simulate

disease progression and treatment response, a marked shift from traditional predictive models.

Yet, the challenge remains in scaling this technology for broader healthcare applications. Benson

et al. have taken this a step further by developing high-resolution patient models capable of

computationally evaluating drug efficacy on an individual level, although achieving seamless

integration of such models into clinical practice remains an ongoing challenge [20]. Machado and

Berssaneti's review of digital twin applications reiterates the transformative potential in

healthcare, though realizing fully functional, whole-body digital twins is still not yet achieved [21].

Although some progress has been achieved as mentioned above, there were still some research

gaps that were identified through literature review. These research gaps are mainly highlighted as

follows: 1) Previous approaches in cancer prediction focus on detection rather than modeling

disease progression. While early detection is important, it is equally critical to forecast how

cancer will evolve, as this informs treatment strategies and improves patient outcomes; 2)

Despite achieving 80-90% accuracy levels, previously reported AI models function as black-

boxes. They focus on performance metrics without providing transparency into the mechanisms

driving cancer progression, limiting their clinical utility. Understanding key factors such as

tumor growth, metastasis, and drug response are crucial for developing personalized and

effective treatment plans; and 3) Currently reported studies heavily rely on a narrow set of data

inputs, often missing crucial genomic and spatial transcriptomic data. This restricts their

predictive power and limits their ability to offer personalized treatment strategies. Integrating

multiple data types is desirable to further improve both accuracy and the relevance of cancer

progression models, which would provide a more comprehensive and reliable view of the disease

and its behavior over time.

To address the research gaps, this research focuses on the following areas: 1) Propose a novel

computational MLPA framework. The proposed MLPA framework will fully integrate

macroscopic EHRs with microscopic genomic data, which is now more accessible, to create a

detailed, mechanism-based dynamic model of both the tumor microenvironment and the patient's

overall health profile; 2) Develop a strategic method utilizing stochastic cellular automata and

multiple data modalities to simulate timeseries cancer imaging data. While stochastic cellular

automata have been previously used to model tumor growth, the MLPA framework uniquely

combines them with genomic, EHR, and imaging data to offer a more comprehensive and

personalized view of cancer dynamics; and 3) Utilize Monte Carlo simulations to explore and

optimize cancer prediction model parameters to reduce simulation error, instead of relying on

traditional AI models which have black-box issues. By comprehensively incorporating a broader

range of data types than existing models, the MLPA framework aims to improve predictive

accuracy and provide a robust platform for optimizing individualized cancer treatment plans.

In summary, the proposed MLPA digital twin framework serves as a virtual testbed for

simulating disease progression and evaluating therapeutic responses under various treatment

regimens, providing an in-depth understanding of treatment outcomes, potential resistance

mechanisms, and the optimization of personalized treatment plans. This research proposes, for

the first time, the theoretical foundation of MLPA, its initial prototype, and its validation using a

bioluminescent imaging mice dataset. The simulation results demonstrate MLPA's ability to

accurately predict tumor dynamics and evaluate personalized treatment strategies. By

constructing this proof-of-concept cancer digital twin, this research aims to advance the frontier

of precision medicine, enhancing the specificity and efficacy of oncological therapies.

The paper is organized as follows: The "Results" section presents a thorough analysis of the

MLPA framework's fitting, validation, and drug effect simulation, utilizing a bioluminescent

imaging dataset of mice injected with MLL-rearranged leukemia and treated with DOT1L

histones. Following this, the "Discussion" section delves into the implications and interpretations

of these findings. The "Limitations" section openly addresses potential limitations and areas for

enhancement. Finally, the "STAR METHODS" section outlines the proposed methodology and

provides details on data and code availability.

Results

The results presented here highlight MLPA's versatility and predictive power in simulating tumor

growth under various conditions, predicting tumor progression with high accuracy, and validating

the effects of gene-targeted therapies. This section is organized into four subsections: 1) simulation

of tumor growth in different scenarios; 2) predictive accuracy of MLPA compared to mice data;

3) validation of drug treatment effects through gene pathway perturbation; and 4) assessment of

MLPA's reliability in predicting time points beyond the training dataset.

1. Simulating Tumor Growth Across Control, Aggressive, and Treatment Scenarios."

Figure 1 shows MLPA's capability to simulate various scenarios of tumor progression, providing

insights into various aspects of cancer growth and treatment responses. Importantly, it can simulate

tumor dynamics across multiple time points, allowing for a more comprehensive understanding of

disease progression and the evaluation of treatment efficacy over time.

In the control scenario ($P_{growth} = 5.5 \times 10^{-2}$ and $P_{metastasis} = 2.0 \times 10^{-4}$), the model simulated

the natural progression of a tumor without intervention. Initially at t_0, the tumor was localized with

limited spread. Over time, the tumor expanded steadily, showing increased density and area

coverage. By t_1 and t_2, the tumor had grown significantly, occupying a larger area of the simulated

tissue. This scenario validated the model's ability to replicate natural tumor growth patterns in

untreated conditions accurately.

The aggressive scenario ($P_{growth} = 6.5 \times 10^{-2}$ and $P_{metastasis} = 4.0 \times 10^{-4}$) simulated

conditions where factors enhanced tumor growth and metastasis, with gene pathways in the

PAGER3 database contributing to cancer advancement activated. By t_1 and t_2, there was rapid

and extensive tumor growth, with significantly increased density and area coverage compared to

the control scenario. The tumor size at t_2 in the aggressive scenario was approximately 1.26 times

larger than in the control scenario, demonstrating the model's ability to capture accelerated growth

patterns.

The drug treatment scenario ($P_{growth} = 2.5 \times 10^{-2}$ and $P_{metastasis} = 1.0 \times 10^{-4}$) evaluated the

efficacy of therapeutic interventions in controlling tumor growth, with gene pathways in the

PAGER3 database contributing to cancer advancement inhibited. As time progressed to t_1 and t_2,

the tumor growth was noticeably slower, and the density was reduced compared to both the Control

and Aggressive scenarios. At t_2, the tumor size in the drug treatment scenario was approximately

0.38 times the size of the control scenario, illustrating the model's capacity to simulate the effects

of therapeutic interventions.

2. Validating Predictive Accuracy Using Sigmoidal Approximations

Building on the previous simulations, we evaluated the accuracy of MLPA's predictions against

real-world data from bioluminescent imaging in mice, specifically on the four testing nontreated

mice subjects that were not used during the training phase. The MLPA framework was run four

times, with the tumor pixel and high-density tumor pixel counts averaged. It was found that the

results were able to be represented by a sigmoid function, with $N(t) = \frac{L}{1+e^{-k(t-t_0)}}$, where $N(t)$ is

the number of cancer cells at time t, L represents the carrying capacity of tumor cells, k controls

the growth of the cancer, and t_0 is the time of the inflection point of the growth. The R^2 value

obtained was 0.93, achieved by comparing the MLPA predicted outputs with the curves fit to the

bioluminescent mice imaging dataset. Other studies only achieved values of 0.80-0.90 [14, 15].

The sigmoid function is ideal for modeling tumor growth because it captures the initial slow

growth phase, rapid exponential growth, and eventual plateau as the tumor reaches its maximum

size, reflecting real-life conditions. The error bars in Figure 2A are the range of area values

obtained from the testing split of the mice imaging data. Both the tumor pixel and high-density

tumor predictions from MLPA fell within an acceptable range of error. MLPA predicted that the

total carrying capacity would be at 1,006,630 cells, with the inflection point of growth being

between 1 and 2 days. Notably, the model predicts a deceleration in cancer cell proliferation

beyond Day 5, as indicated by the approaching plateau in the graph. This deceleration can be

attributed to the tumor reaching spatial constraints within the host environment.

While other models such as the Gompertz or logistic functions also capture nonlinear growth, the

sigmoid model offers a balance between simplicity and precision, making it ideal for datasets with

limited time points. For example, the Gompertz model often requires finer temporal granularity to

estimate its asymmetric parameters reliably, while more complex models can risk overfitting or

instability when applied to datasets with sparse observations.

3. Gene Pathway Targeting for Drug Efficacy Simulation in MLPA

To validate the framework's treatment prediction using gene pathway perturbation, the MLPA

framework was compared with the four mice treated with a small-molecule inhibitor of DOT1L,

listed as the experimental group. The efficacy of this treatment was assessed by its ability to revert

gene perturbations caused by the disease. After fitting the default parameters of the MLPA model

to the experimental group ($P_{growth} = 3.2 \times 10^{-2}$ and $P_{growth} = 2.8 \times 10^{-4}$), specific gene

pathways known to be inhibited by DOT1L were selected, which were then used to perturb the

default model parameters as shown in Figure 2B. The following pathways from the CSV gene

pathway file which would be inhibited during treatment were chosen as follows: 1) Nonsense

Mediated Decay; 2) Chaperon Mediated Autophagy; 3) Regulation of TP53 Expression and

Degradation; 4) TP53 Activity through Methylation; and 5) Aggrephagy. These pathways were

inhibited so the result would counteract cancer progression, such as degrading potentially

oncogenic proteins, maintaining protein homeostasis, enhancing tumor suppressor functions, and

reducing proteotoxic stress.

A 95% confidence interval was created for the Day 5 experimental group predicted tumor pixel

counts, and was compared to the Day 5 pixel counts of the drug treated mice in the dataset. The

95% confidence interval from the mice dataset for tumor pixel count was determined to be

between 153,336 and 170,231 pixels when the predicted tumor pixel count was 158,125. The

95% confidence interval from the mice dataset for high-density tumor pixel count was

determined to be between 97,215 and 120,958 pixels when the predicted high-density tumor

pixel count was 110,807. Since the confidence intervals encapsulate the predicted values, they

indicate a precise prediction.

To further validate these results, equivalence tests were conducted using the Two One-Sided Test

procedure. For tumor pixels, the equivalence margin was set at ±3,953 pixels (2.5% of the

observed value), with a 95% simulated predictive interval of [143,124, 167,784]. The difference

between MLPA's and the imaging dataset means was 2,670 pixels. For high-density tumor

pixels, the equivalence margin was ±2,770 pixels (2.5% of the observed value), with a 95%

simulated predictive interval of [101,545, 118,347]. The difference between MLPA's and the

imaging dataset means was 860 pixels. In both cases, MLPA's predicted pixel counts fell within

the intervals from the actual imaging dataset and with differences well within the defined

equivalence margins. These findings indicate that the drug treatment significantly reduced tumor

size and density, aligning closely with the MLPA framework's predictions. The strong agreement

within the confidence intervals underscores the model's ability to accurately capture the effects

of activated gene pathways, thereby validating the proposed approach to simulating drug effects

through gene pathway perturbation. It was validated through experimental data that this

alignment not only reinforces the model's predictive accuracy, but also supports its potential

utility in personalized medicine applications where understanding the impact of gene-targeted

therapies is crucial.

In addition, when there is no gene pathway perturbation, as depicted in Figure 2B, we can clearly

observe a significant deviation from the actual results. For example, the tumor pixel count

predicted without pathway perturbation exceeded the observed value by 158,432 pixels (105%

error) for Day 5, and the high-density tumor pixel count overestimated the observed value by

89,193 pixels (180% error). This discrepancy highlights the critical role of incorporating gene

pathway perturbations in achieving accurate predictions. Without these perturbations, the MLPA

framework does not capture the biological effects of the treatment, leading to vast

overestimations of tumor progression and density.

4. Modeling Tumor Progression Through Time Point Prediction

Beyond validating drug effects, we also tested the framework's ability to predict tumor

progression across time points, even when some data points were withheld. Due to the specificity

of the dataset required for MLPA, the mice dataset was limited to only three data points, which

made it insufficient for this purpose, as hiding one point would leave too few for meaningful

predictions. To overcome this limitation, an initial testing MLPA model was used with the initial

parameters of $P_{growth} = 4.5 \times 10^{-2}$ and $P_{metastasis} = 3.0 \times 10^{-4}$ to generate simulated imaging

data for days 0, 2, 3, and 5. Then, the Day 2 cancer image was intentionally hidden, and a

separate MLPA model was used to see if it could accurately generate the missing image without

having access to the initial model's parameters, only using the other three days' imaging data to

develop its own parameters, shown in Figure 3A. By effectively predicting the missing data for

Day 2 on another model instance without knowing the initial parameters, MLPA shows its

capability to generate continuous, reliable data, even when only a few time points are available.

The second model adopted the parameters to $P_{growth} = 4.45 \times 10^{-2}$ and $P_{metastasis} =$

3.06×10^{-4} during the fitting process.

Then, the tumor cell density for Day 2 was analyzed using the newly calibrated parameters.

These predictions were compared with the original Day 2 observations. The 95% confidence

interval for the validation MLPA model's Day 2 tumor pixel count was determined to be between

239,413 and 281,988 pixels when the actual tumor pixel count was 258,758. The 95%

confidence interval for the validation MLPA model's Day 2 high-density tumor pixel count was

determined to be between 208,999 and 231,933 pixels when the actual high-density tumor pixel

count was 220,884. In both cases, the 95% confidence interval of the validation MLPA model

encapsulates the recorded testing MLPA model's pixel counts, indicating that predictions for

tumor cell density on Day 2 are statistically consistent with the testing data.

To further validate the model's predictive capabilities, the analysis was extended by simulating

tumor progression while hiding Day 5 data, using only the initial parameters trained from days 0,

2, and 3. In this scenario, a new validation MLPA model was trained using data from days 0, 2,

and 3 from the same testing MLPA model with the same testing model parameters as before,

optimizing the parameters to best fit the observed data. The training process yielded optimized

parameters in the validation MLPA model of $P_{growth} = 4.68 \times 10^{-2}$ and $P_{metastasis} =$

2.72×10^{-4}, as shown in Figure 4. The predicted parameters were consistent with those

obtained from the validation model predicting Day 2 imaging data, showing consistency when

using the same data.

The tumor cell density for Day 5 was predicted using the new validation MLPA model. These

predictions were compared with the original Day 5 observations. The 95% confidence interval

for the validation MLPA model's Day 5 tumor pixel count was determined to be between

324,173 and 375,250 pixels when the actual tumor pixel count was 358,011. The 95%

confidence interval for the validation MLPA model's Day 5 high-density tumor pixel count was

determined to be between 245,823 and 287,332 pixels when the actual high-density tumor pixel

count was 257,161. In both cases, the 95% confidence interval of the validation MLPA model

encapsulates the recorded testing MLPA model's pixel counts, indicating that the model's

predictions for tumor cell density on Day 5 are statistically consistent with the original model

data. This result displays the model's reliability in predicting future time points with a

predetermined set of data.

In addition, MLPA's performance was compared with a baseline linear regression, shown in

Figure 3B. These results demonstrate that MLPA's predictions for tumor and high-density cell

distributions are significantly more accurate than the baseline model, with an average tumor

residual of 666 compared to the baseline's 32,710, and an average high-density tumor residual of

7,466 compared to the baseline's 36,269, effectively capturing the processes of tumor

progression.

Discussion

The MLPA framework demonstrates robust predictive power in simulating cancer growth and

assessing treatment responses, validated with an R^2 value of 0.93 from bioluminescent imaging

data of mice with leukemia. The model achieved state-of-the-art accuracy in capturing tumor

behavior under untreated, aggressive, and drug-treated conditions, with DOT1L treatment

predictions consistently falling within 95% confidence intervals across multiple time points. This

strong validation underscores MLPA's capacity to simulate tumor dynamics accurately, providing

insights into cancer progression and treatment efficacy.

MLPA's approach sets it apart from traditional cancer prediction models by integrating multi-scale

data, including EHRs, genomic information, and imaging datasets, allowing for the simulation of

tumor behavior across multiple time points. Compared to conventional models, which often rely

on static data and lack real-world calibration, MLPA leverages stochastic cellular automata and

Monte Carlo simulations to explore the parameter space. This integration reduces simulation error,

resulting in more reliable predictions of cancer progression. Additionally, MLPA's capacity to

simulate cancer dynamics over time offers a more comprehensive view of tumor growth,

metastasis, and treatment responses.

Distinctively, MLPA incorporates gene pathway perturbations, enhancing its predictive accuracy

and allowing for the exploration of genomic data in cancer simulations. This feature distinguishes

it from other models, enabling the simulation of gene-targeted therapies and providing insights

into how specific pathways can influence cancer progression.

By using cellular automata and Monte Carlo simulations, MLPA offers transparency into the

mechanisms of tumor growth and treatment response—an advantage over black-box AI models

that focus primarily on predictive metrics without explaining underlying biological factors. The

framework's transparency in parameter influence provides valuable insights for optimizing

personalized treatment strategies, as shown in its virtual testbed simulations of therapeutic impacts

on individual patients in Figure 5. Compared to previous AI models, MLPA not only meets

predictive benchmarks but also offers clarity on how cancer progression mechanisms interact with

treatment variables, supporting more informed clinical decisions.

In its current form, MLPA represents a significant advancement in cancer modeling, merging

precision and transparency. The model's predictive capacity and Monte Carlo optimization set a

new standard in accuracy, crucial for personalized medicine. Moreover, its unique ability to

simulate the effects of gene-targeted therapies introduces a new level of insight into cancer

dynamics, with the potential to help clinicians test therapeutic scenarios virtually. Future

development to expand the model into 3D simulations and integrate human datasets could further

enhance its potential for advancing personalized cancer care and improving patient outcomes.

Limitations

Despite the strengths of the MLPA framework, there are several limitations in the current

research: 1) MLPA's validation was based on mouse data [22]. The absence of human-specific

data, especially paired human genomic and imaging data, limits the framework's capacity to

make accurate predictions for human patients. In addition, continuous cancer progression data

from human patients is unethical, as treatment is necessary. Instead, datasets with cancers that

grow similarly in humans and other animals could be used. Incorporating such datasets are

desirable to enhance the model's precision and reliability in a real clinical setting. For example,

transgenic mouse models such as MMTV-PyMT for breast cancer and KRAS-driven models for

lung and pancreatic cancers have demonstrated tumor growth dynamics closely resembling their

human counterparts, making them valuable for bridging the gap between murine and human data

in predictive frameworks like MLPA [23-25]; 2) While the MLPA framework is designed to

incorporate EHR data, the use of mice imaging data, which did not include EHR data, and the

incompatibility between animal EHR data and human EHR data, limited this research's ability to

validate the impact of these factors. Future research will focus on integrating and testing human

EHR data to explore how these additional physiological parameters influence the model's

predictions and overall effectiveness in a clinical setting; and 3) It should be mentioned that

although the current approach is implemented in 2D simulations due to being computationally

efficient, the MLPA framework can be further expanded into 3D simulations. Expanding the

model to 3D simulations will provide a more accurate representation of cancer growth, enabling

a deeper understanding of spatial tumor interactions and treatment effects.

Author contributions

Mr. James Gu was responsible for implementing the research work, coding the environment in

MATLAB, validating results, and drafting the manuscript. Dr. Jake Y. Chen provided the scientific

design, overall supervision, technical feedback, manuscript revision, and financial support to the

research.

Declaration of interests

There is no conflict of interest.

Declaration of Generative AI and AI-assisted technologies in the writing process

Statement: During the preparation of this work the author(s) used ChatGPT in order to improve

the language of the article. After using this tool/service, the author(s) reviewed and edited the

content as needed and take(s) full responsibility for the content of the publication.

Figure titles and legends

Figure 1: MLPA simulation of tumor growth under Control, Aggressive, and Drug Treatment

conditions from t_0 to t_2. The Aggressive scenario shows increased growth due to upregulated

cancer-promoting gene pathways, while the Drug Treatment scenario shows decreased growth

due to downregulation. Iterations are defined as each individual passes of the code and tumor

size is calculated by adding all the number of tumor cells grown.

Figure 2: Sigmoid Fit and Experimental Group Predictions: A) Sigmoid fit comparing MLPA

predicted tumor area (red) and high-density tumor area (blue) against observed tumor areas

from mice data (open circles with error bars), with equations provided for both fits; and B) MLPA

model predictions for the experimental group (4 treated mice subjects) treated with DOT1L

inhibitor over five days. Solid lines represent predicted tumor areas with parameter perturbation

from gene pathways enabled, while dotted lines show predictions without said perturbations.

Figure 3: MLPA Model Testing and Validation Predictions: A) MLPA testing model simulation for

tumor and high-density tumor areas over five days, with Day 2 data hidden to evaluate

accuracy. Solid lines show predictions, and asterisks mark observed data from the mice dataset;

and B) Validation model predictions trained on Day 0, 3, and 5 data from MLPA testing instance

are compared to baseline linear regression (dotted lines) to assess error.

Figure 4: Monte Carlo simulations for MLPA parameter optimization: A) Based on the mice

imaging dataset, $P_{growth} = 5.5 \times 10^{-2}$ and $P_{metastasis} = 2.0 \times 10^{-4}$; B) Based on hidden Day

2 trial, $P_{metastasis} = 2.0 \times 10^{-4}$ and $P_{metastasis} = 3.06 \times 10^{-4}$; and C) Based on the hidden

Day 5 trial, $P_{growth} = 4.68 \times 10^{-2}$ and $P_{metastasis} = 2.72 \times 10^{-4}$.

Figure 5: Illustration of multiscale data integration in healthcare using digital twins. Different

biological levels, from the body to the gene level, are integrated into a central data analysis

system. The system processes these layers of data to support diagnosis, prognosis, and therapy

optimization.

427 **STAR METHODS**

428 **Key Resource Table**

RESOURCE	SOURCE	IDENTIFIER
MATLAB Source Code	GitHub	https://github.com/alphamind-club/MLPA/tree/main
Bioluminescent Mice Imaging Data	Dr. Christopher R. Vakoc; Wang, E., Kawaoka, S., Yu, M., Shi, J., Ni, T., Yang, W., Zhu, J., Roeder, R.G., & Vakoc, C.R. (2013). *Histone H2B ubiquitin ligase RNF20 is required for MLL-rearranged leukemia.* Proceedings of the National Academy of Sciences, 110(10), 3901-3906. https://doi.org/10.1073/pnas.1301045110	https://pubmed.ncbi.nlm.nih.gov/23412334/
Gene Pathway Data	UAB PAGER3	https://discovery.informatics.uab.edu/PAGER/

431 **RESOURCE AVAILABILITY**

433 **Lead contact**

434 Mr. James Gu (jamesguru77@gmail.com), Dr. Jake Y. Chen (jakechen@uab.edu)

Material availability

With this article, we are providing a supplementary material file that provides information about

the following:

1. Untreated mice subjects, see Figure S1 in the supplementary materials.

2. Treated mice subjects, see Figure S2 in the supplementary materials.

3. Visualization of stochastic cellular automata simulated growth, see Figure S3 in the

    supplementary materials.

4. Table S1 lists the gene pathways used in the MLPA framework and their relationship to

    the stochastic cellular automata parameters.

Data and code availability

Data Availability

PAGER3 is an online repository developed by the University of Alabama at Birmingham that

provides access to pathways, annotated lists, and gene signatures (PAGs) related to human network

biology. It offers tools for analyzing and browsing PAGs, facilitating research into gene functions

and interactions. The bioluminescent imaging data was obtained from the study titled "Histone

H2B ubiquitin ligase RNF20 is required for MLL-rearranged leukemia", which investigated the

role of RNF20, an enzyme that modifies histone H2B, in the development of leukemia associated

with MLL gene rearrangements.

Code Availability

The code related to MLPA is provided through the GitHub repository. The resource contains the

main model script for cancer simulation, contour plots for data visualization, algorithms to find

458 residual errors from the simulation, and dataset CSV files. The code and experiment-related

459 materials can be obtained from the following GitHub link https://github.com/alphamind-

460 club/MLPA/tree/main.

462 **Acronyms**

Acronym	Definition
MLPA	Multi-level Parameterized Automata
EHR	Electronic Health Record
R2	R-Square Score
AI	Artificial Intelligence
VEGF	Vascular Endothelial Growth Factor
EMT	Epithelial-Mesenchymal Transition
CSV	Comma-separated Values
MLL	Mixed-lineage Leukemia
DOT1L	Disruptor of Telomeric Silencing 1-like
RGB	Red, Green, Blue
MAE	Mean Absolute Error
RMSE	Root Mean Square Error
PAG	Pathways, Annotated Lists, and Gene Signatures

464 **METHOD DETAILS**

466 **Novel MLPA Framework Overview**

Figure 6: An overview of the proposed novel MLPA strategy to simulate cancer growth and metastasis: A) The framework maps gene pathways G1-G5 to model parameters Q1-Q5; B) Model fitting process calibrated against bioluminescent imaging data; and C) Applications include cancer progression, drug metabolization, and treatment effects on survival. Mice images were from a dataset [22].

To simulate cancer progression and optimize treatment strategies, this research employs a dual-

level approach, creating a personalized cancer digital twin to obtain higher prediction accuracies.

At the physiological level, the MLPA framework focuses on simulating the physical aspects of

cancer progression within the patient's body using imaging and EHR data, such as sex, age, BMI,

weight, blood pressure, and other factors. This includes accurately mapping the spatial location

and growth dynamics of tumors, simulated using stochastic cellular automata where cells within

a defined neighborhood have probabilities of becoming tumor cells based on local conditions and

growth potentials. On the other hand, at the molecular level, the framework integrates genomic

data to simulate critical gene pathways affecting tumor behavior, including growth, mutation,

and metastasis. As shown in Figure 6A, the molecular data enables bi-directional communication

with the physiological level, influencing parameters such as tumor growth probabilities and

metastasis rates.

Framework calibration is achieved by fitting the simulation outputs to real bioluminescent mice

imaging data, captured over multiple time points. Bioluminescent imaging, a powerful tool in

preclinical cancer studies, enables real-time, non-invasive visualization of tumor dynamics by

detecting light emitted from luciferase-tagged cancer cells [26]. This technique provides critical

metrics such as cancer area and high-density tumor regions, making it invaluable for validating

the MLPA framework. Monte Carlo simulations are then used to explore the parameter space,

identifying optimal values that minimize error between simulated and observed data. Figure 6B

shows the process that enhances the accuracy of the digital twin. Framework validation is done

by comparing the continuous tumor growth predictions from the Monte Carlo simulation with

the observed data from bioluminescent cancer imaging, as this imaging closely resembles the

visual output of MLPA.

The digital twin strategy serves as a novel virtual platform for personalized medicine

applications, facilitating the evaluation of treatment efficacies and the prediction of

individualized patient responses to various therapies. The proposed MLPA approach provides

valuable insight into the future progression of the disease under various treatment scenarios.

Depicted in Figure 6C, the advantage of MLPA is providing a better understanding of how

different therapies may impact tumor growth, patient survival, and drug metabolization over

time.

500 **Proposed MLPA Architecture**

Figure 7: The proposed MLPA architecture integrating EHR, genomic, and imaging data mapped to model cancer progression. This multiscale approach personalizes growth predictions and simulates drug effects on tumor dynamics while considering mathematical models. Mice images were taken from a dataset [22].

501 Figure 7 shows the construction of the MLPA architecture, which involves three core

502 components besides the base imaging component: the physiological level, the molecular level,

503 and the AI mapping module. Each of these components plays a crucial role in simulating cancer

504 progression and treatment responses. At the physiological level, the architecture simulates the

505 physical aspects of cancer within the patient's body, such as tumor growth and spread. It

506 integrates EHR data, including variables like patient age, gender, BMI, and other relevant health

507 metrics. The physiological component is designed to reflect how these macroscopic factors

508 influence cancer progression, providing a broader context for the simulation. At the molecular

509 level, MLPA focuses on simulating molecular and cellular processes, including gene pathway

510 activity that influences tumor behavior, such as growth, mutation, and metastasis. The molecular

511 component leverages genomic data to simulate the microscopic environment of the tumor,

512 providing a detailed view of the internal mechanisms driving cancer progression. Due to the lack

513 of public data correlating certain gene pathways to cancer progression, the AI mapping module

serves as the bridge between the molecular level and model parameters, using ChatGPT 4o to

map gene pathway relationships [27-29].

The MLPA framework utilizes a stochastic cellular automata model to simulate cancer

progression. The model, built inside the programming language MATLAB, captures the complex

dynamics of tumor growth, mutation, and metastasis. The simulation environment is represented

by a lattice defined as $L = \{(x, y) \mid 1 \leq x \leq 200, 1 \leq y \leq 200\}$,initialized with a circular

tumor located at the center of the lattice. Because a two-dimensional lattice is used, a type of

search called Moore's neighborhood, defined by $N^M(x_0, y_0) = \{(x, y): |x - x_0| \leq r, |y - y_0| \leq$

$r\}$, can be employed to model tumor growth dynamics. Tumor cells grow based on probabilistic

rules within Moore's neighborhood of within a distance $r(u, v) := \max(|u_i - v_i|)$. A snapshot of

the stochastic cellular automata's simulated growth is provided in Figure S1.

Figure 8: Simulation initialization and results using MLPA: A) P_{growth} is influenced by a Gaussian-filtered map which models tumor microenvironment nutrient heterogeneity; B) Blood vessel heatmap showing angiogenesis; and C) Heatmap of tumor cells expressing VEGF signaling.

Adjacent cells within the Moore's neighborhood can become tumor cells, with a defined

probability P_{growth}. P_{growth} is also influenced by a growth rate map generated using a Gaussian-

filtered random map with a standard deviation of 1.00. This map is normalized and polarized to

create areas with varying growth potentials, effectively modeling the heterogeneous nature of the

tumor microenvironment. Growth rate values range from 0.02 to 1.00, with higher growth rates

assigned to regions with lower polarized map values and vice versa, as shown in Figure 8A.

Blood vessels have a chance P_{break} to grow towards nearby cancer cells. Blood vessels start as

rectangular regions from one lattice end. Vessel growth is directed toward Vascular Endothelial

Growth Factor (VEGF) signals from tumor cells, simulating angiogenesis, highlighted in Figures

8B and 8C. The blood vessel growth follows a probabilistic rule, with potential Epithelial-

Mesenchymal Transition (EMT) breaks dictated by a decreasing probability P_{break} as breaks

accumulate. To enhance nutrient delivery, the new EMT breaks grow toward the nearest tumor

cell, guided by VEGF signals. Cells near blood vessels have their growth probability increased

by 50% due to nutrient availability.

Table 1: Summary of representative algorithms used in MLPA framework

Algorithm 1 Simple cancer algorithm for **MLPA**	**Algorithm 2** Reading macroparameters for **MLPA**	**Algorithm 3** Reading microparameters for **MLPA**
for $(x_i, y_i) \in L$ **do**	**Input:** EHR	**Input:** Gene Pathway Database
if (x_i, y_i) is empty **and** $N^M(x_i, y_i)$ contains cancer	**For** attribute $A_i \in$ EHR **do**	**For** $Q_i \in$ Gene Pathway Database **do**
if $N^M(x_i, y_i)$ contains blood vessel	**If** $A_i > \bar{A}$	**If** $Q_i =$ activated
$P_{growth} * 1.5$	P_{growth} += correlation(A_i, P_{growth})	P_{growth} += correlation(Q_i, P_{growth})
else	$P_{mutation}$ += correlation$(A_i, P_{mutation})$	$P_{mutation}$ += correlation$(Q_i, P_{mutation})$
P_{growth}	P_{break} += correlation(A_i, P_{break})	P_{break} += correlation(Q_i, P_{break})
if (x_i, y_i) is blood vessel	$P_{metastasis}$ += correlation$(A_i, P_{metastasis})$	$P_{metastasis}$ += correlation$(Q_i, P_{metastasis})$
P_{break}	**Else if** $A_i > \bar{A}$	**Else if** $P_i =$ inhibited
if (x_i, y_i) is cancer **and** $N_{cancer} > N_{threshold}$	P_{growth} -= correlation(A_i, P_{growth})	P_{growth} -= correlation(Q_i, P_{growth})
$P_{metastasis}$	$P_{mutation}$ -= correlation$(A_i, P_{mutation})$	$P_{mutation}$ -= correlation$(Q_i, P_{mutation})$
if (x_i, y_i) is cancer **and** $P_{mutation}$	P_{break} -= correlation(A_i, P_{break})	P_{break} -= correlation(Q_i, P_{break})
P_{growth} — **and** $P_{metastasis}$++	$P_{metastasis}$ -= correlation$(A_i, P_{metastasis})$	$P_{metastasis}$ -= correlation$(Q_i, P_{metastasis})$

Metastasis, defined as $P_{metastasis}$, starts when cancer cells N_{cancer} surpass a defined threshold

$N_{threshold}$. The metastasis process results in new tumor sites near blood vessels, simulating

cancer's vascular spread. Additionally, tumor cells can also mutate with a probability $P_{mutation}$,

changing the cell's P_{growth} and $P_{metastasis}$. An example of how the parameters is used is shown

in Algorithm 1 under Table 1.

To personalize these model parameters to each individual patient, the incorporation of digital

twin technology integrates macroscopic patient EHR and microscopic patient genomic data to

create a highly individualized disease progression system. The macroscopic aspect of MLPA

utilizes simulated EHR data. Blood pressure can be continuously monitored to assess the

patient's cardiovascular health, influencing tumor growth, and treatment response [30]. Patient age

and gender specific differences are factored to account for their roles in cancer progression and

treatment effectiveness [31-32]. Other EHR parameters, such as BMI and medical history, are

included to comprehensively view the patient's health status. The macroscopic data can directly

perturb the stochastic cellular automata parameters such as P_{growth}, P_{break}, $P_{metastasis}$, and

$P_{mutation}$, as shown in Algorithm 2 on Table 1.

On the molecular level, the genomic pathway data then perturbs the model parameters to tailor

the framework to individual patients, effectively customizing the simulation based on each

patient's specific genomic profile [33-35]. The perturbation process is guided by the PAGER3

database, which includes pathways scientifically validated to affect metastasis, growth, mutation,

and angiogenesis [36-39]. The extracted pathway data was placed into a CSV file that lists gene

pathway names and their interactions to the model parameters. Pathway expression is controlled

via a graphical user interface, allowing adjustments based on activation, absence, or inhibition of

specific gene pathways. These adjustments directly influence the stochastic cellular automata

parameters, as described by their correlation in the CSV file. For instance, an expressed gene

pathway associated with increased P_{growth} will adjust the growth rate parameter accordingly,

while pathways involved in inhibiting P_{growth} will decrease it, as shown in Algorithm 3 in Table

1.

The AI mapping module was crucial in identifying relationships between specific gene pathways

and the four key model parameters, as there are no datasets available to describe the relation

between specific pathways to the model parameters that we defined in MLPA. To accomplish

this, ChatGPT 4o was utilized, leveraging its capabilities in natural language processing and data

interpretation to evaluate potential interactions between gene pathways and model parameters

while minimizing risks of AI hallucination. ChatGPT 4o was prompted with clear, pathway-

specific details to determine whether each pathway had a positive, negative, or neutral effect on

the parameters. Recent studies into ChatGPT's application in biomedical contexts further

underscore its effectiveness in identifying gaps within gene pathway annotations and enriching

pathway data, enhancing the accuracy of this mapping process [27-29]. Given the absence of

genomic data in the dataset, a standardized approach was applied by assigning a 10% change to

the parameters for any pathway relationship identified by ChatGPT, ensuring MLPA could

reflect gene pathway influences on tumor behavior even without direct genomic data. A list of

gene pathways implemented is available in Table S1.

Data Acquisition and Preprocessing

The imaging dataset was sourced from the study [22]. The dataset focuses on Mixed-lineage

leukemia (MLL) fusions, potent oncogenes that initiate aggressive forms of acute leukemia.

MLL-fusion proteins, as aberrant transcriptional regulators, alter gene expression in

hematopoietic cells by interacting with the histone H3 lysine 79 methyltransferase DOT1L.

Notably, treating leukemia using a DOT1L treatment decreased the spread of the cancer.

Table 2: Summary of untreated and treated mice imaging data split into training and testing category

Mice Group	Number of Mice	Time Points	Imaging Type	Treatment Type
Untreated (Training)	8	Days 0, 3, 5	Bioluminescent	Untreated
Untreated (Testing)	4	Days 0, 3, 5	Bioluminescent	Untreated
Treated (Testing)	4	Days 0, 3, 5	Bioluminescent	DOT1L Inhibitor

As described in Table 2, the dataset includes bioluminescent imaging data from 16 mice, each

recorded at three time points: days 0, 3, and 5. Among these, four mice were treated with a

small-molecule inhibitor of DOT1L. A 50/50 training/testing split was employed, using data

from 8 untreated mice for framework training and data from the remaining 8 mice for testing (4

treated and 4 untreated). In total, 48 images were processed, each tagged with metadata

corresponding to the original mouse subject. The images were standardized in size and

underwent segmentation based on RGB values to distinguish different regions of the

bioluminescent imaging heatmap. For each image, two critical variables were extracted: tumor

pixel count (all color values) and high-density tumor pixel count (red color values only).

Examples of the data are given in Figure S2 and S3.

Training Using Monte Carlo Simulations

From the bioluminescent imaging dataset, third-degree polynomials were fitted to the tumor

pixel count and high-density tumor pixel count. Harshe et al. states that three tumor volume

measurements are sufficient to estimate model parameters when noise is absent [40]. As such, Day

0, Day 3, and Day 5 imaging data were used to fit the polynomial curves. These curves provided

a mathematical comparison of the observed growth patterns in the bioluminescent images. Monte

Carlo simulations, which are computational techniques that use repeated random sampling to

estimate numerical results, were utilized [41]. In the context of MLPA, a Monte Carlo simulation

helps explore the range of possible tumor growth scenarios by varying P_{growth} and $P_{metastasis}$ to

find which parameter pair most closely represents the cancer growth in the mice dataset. A

systematic approach using Monte Carlo simulations identified these ranges as optimal for

minimizing residual errors in tumor pixel predictions. These ranges consistently captured the

tumor growth and metastasis dynamics across control, aggressive, and treatment scenarios.

Random values for P_{growth} and $P_{metastasis}$ were chosen from their respective distributions and

fed into the stochastic automata model. P_{break} and $P_{mutation}$ were held constant with $P_{break} =$

1.0×10^{-3} and $P_{mutation} = 1.0 \times 10^{-2}$, as the bioluminescent imaging dataset did not include

blood vessel mapping or genomic data to indicate mutations. The pathways from the CSV file,

such as mRNA splicing, Processing of Capped Intron Containing Pre mRNA, mRNA

Processing, Nonsense Mediated Decay, Chaperon Mediated Autophagy, Regulation of TP53

Expression and Degradation, and others, were assigned their typical expression in cancerous

conditions, with each pathway being assigned a value of 1, -1, or 0. In this context, a value of 1

indicates that the pathway is activated, meaning it is upregulated or more active in the cancerous

state. A value of -1 signifies that the pathway is inhibited, reflecting downregulation or reduced

activity in the cancerous state. Lastly, a value of 0 indicates that the pathway is not expressed or

has no relationship to the parameters in the stochastic cellular automata model. The AI mapping

module remained active throughout this process, ensuring that these values were accurately

perturbing the model parameters.

Figure 9: Fitting MLPA to bioluminescent imaging data and optimizing model parameters. A) Time series data consisting of day 0, day 3, and day 5; B) Segmentations of original image into tumor pixels and high-density tumor pixel segmentations; and C) Contour plot of prediction error used to fine-tune model parameters, with $P_{growth} = 5.5 \times 10^{-2}$ and $P_{metastasis} = 2.0 \times 10^{-4}$ set as default. Mice images were obtained from a dataset [22].

The automata's output was segmented to match the mice images, providing pixel counts for

tumor and high-density areas. Simulated pixel counts (derived from MLPA) were compared to

observed pixel counts (derived from mice dataset), calculating residuals for each simulation, with

errors quantified using Mean Absolute Error and Root Mean Squared Error. Error values were

mapped to their respective P_{growth} and $P_{metastasis}$ values, with the optimal values determined to

be $P_{growth} = 5.5 \times 10^{-2}$ and $P_{metastasis} = 2.0 \times 10^{-4}$ by identifying the region with the lowest

error values, as shown in Figure 9. These optimal values became MLPA's default parameters,

ensuring accurate tumor growth modeled after the mice dataset. By fitting the parameters of

MLPA to the observed data, the system is optimized to accurately reflect the tumor growth

dynamics observed in the imaging dataset.

References

1. Centers for Disease Control and Prevention. (2022). FastStats - Leading causes of death.\ National Center for Health Statistics. Retrieved from https://www.cdc.gov/nchs/fastats/leading-causes-of-death.htm

2. Vogelstein, B., & Kinzler, K. W. (2004). Cancer genes and the pathways they control. *Nature Medicine*, 10(8), 789-799

3. Stratton, M. R., Campbell, P. J., & Futreal, P. A. (2009). *The cancer genome. Nature*, 458(7239), 719-724

4. Caldas, C., & Brenton, J. D. (2005). Sizing up miRNAs as cancer genes. *Nature Medicine*, 11(7), 712-714

5. I. Dagogo-Jack, & A. T. Shaw, 2018. Tumour heterogeneity and resistance to cancer therapies. *Nature Reviews Clinical Oncolog*y, 15(2), 81-94

6. D. Hanahan, & R. A. Weinberg, 2011. *Hallmarks of cancer: the next generation. Cell*, 144(5), 646-674

7. A. Conde-Rodríguez, C. Sarabia-Cobo, & A. González-Vidal, 2022. Digital twins in healthcare: A systematic literature review. *Journal of Medical Systems*, 46(8), 1-14

8. Altrock, P. M., Liu, L. L., & Michor, F. (2015). The mathematics of cancer: integrating quantitative models. *Nature Reviews Cancer*, 15(12), 730-745

9. P. Mascheroni, S. Savvopoulos, J. C. L. Alfonso, M. Meyer-Hermann, & H. Hatzikirou (2021). Improving personalized tumor growth predictions using a Bayesian combination of mechanistic modeling and machine learning. *Communications Medicine*, 1(20)

10. Lai, X., Taskén, H. A., Mo, T., Funke, S. W., Frigessi, A., Rognes, M. E., & Köhn-Luque, A. (2021). A scalable solver for a stochastic, hybrid cellular automaton model of personalized breast cancer therapy. *Numerical Methods in Biomedical Engineering*, 37(11), e03542

11. Valentim, C. A., Rabi, J. A., & David, S. A. (2023). Cellular-automaton model for tumor growth dynamics: Virtualization of different scenarios. *Computers in Biology and Medicine*, 153, 106150

12. Velasquez, E., Kassir, N., Cheeti, S., Kuruvilla, D., Sane, R., Dang, S., Miles, D., & Lu, J. (2024). Predicting overall survival from tumor dynamics metrics using parametric statistical and machine learning models: Application to patients with RET-altered solid tumors. *Frontiers in Artificial Intelligence*, 7

13. Wang, W., & Jin, X. (2023). Prostate cancer prediction model: A retrospective analysis based on machine learning using the MIMIC-IV database. *Intelligent Pharmacy*, 1, 100010

14. Rabiei, R., Ayyoubzadeh, S. M., Sohrabei, S., Esmaeili, M., & Atashi, A. (2022). Prediction of breast cancer using machine learning approaches. *Journal of Biomedical Physics and Engineering*, 12(3), 297–308

15. Tătaru, O. S., Vartolomei, M. D., Rassweiler, J. J., Virgil, O., Lucarelli, G., Porpiglia, F., Amparore, D., Manfredi, M., Carrieri, G., Falagario, U., Terracciano, D., de Cobelli, O., Busetto, G. M., Del Giudice, F., & Ferro, M. (2021). Artificial intelligence and machine learning in prostate cancer patient management—Current trends and future perspectives. *Diagnostics (Basel)*, 11(2), 354

16. Groheux, D., Ferrer, L., Vargas, J., Martineau, A., Teixeira, L., Menu, P., Bertheau, P., Gallinato, O., Colin, T., & Lehmann-Che, J. (2022). Multimodal machine learning model

prediction of complete pathological response to neoadjuvant chemotherapy in triple-
negative breast cancer. *Journal of Clinical Oncology*, 40(16_suppl), 601

17.   Steyaert, S., Qiu, Y. L., Zheng, Y., Mukherjee, P., Vogel, H., & Gevaert, O. (2023).
Multimodal deep learning to predict prognosis in adult and pediatric brain tumors.
Communications Medicine, 3, 44

18.   Vale-Silva, L. A., & Rohr, K. (2021). Long-term cancer survival prediction using
multimodal deep learning. *Scientific Reports*, 11, 13505

19.   Swedish Digital Twin Consortium. https://www.sdtc.se/. Accessed October 23, 2024

20.   Björnsson, B., Borrebaeck, C., Elander, N., et al. (2020). Digital twins to personalize
medicine. *Genome Medicine*, 12(4), 1–9

21.   Machado, T. M., & Berssaneti, F. T. (2023). Literature review of digital twin in
healthcare. *Heliyon*, 9(9), e19390

22.   Wang, E., Kawaoka, S., Yu, G., Xu, Y., Kurosu, T., & Tanaka, Y. (2013). Histone H2B
ubiquitin ligase RNF20 is required for MLL-rearranged leukemia. *Proceedings of the
National Academy of Sciences*, 110(11), 4758-4763

23.   Attalla, S., Taifour, T., Bui, T., & Muller, W. (2021). Insights from transgenic mouse
models of PyMT-induced breast cancer: Recapitulating human breast cancer progression
in vivo. *Oncogene, 40*(475–491)

24.   Singh, M., & Johnson, L. (2012). Genetically engineered mouse models: Closing the gap
between preclinical data and trial outcomes. *Cancer Research, 72*(11), 2695–2700

25.   Drosten, M., Guerra, C., & Barbacid, M. (2018). Genetically engineered mouse models of
K-Ras-driven lung and pancreatic tumors: Validation of therapeutic targets. *Cold Spring
Harbor Perspectives in Medicine, 8*(5), a031542

26.   Sun, H., Pisle, S., Gardner, E. R., & Figg, W. D. (2010). Bioluminescent imaging study:
FAK inhibitor PF-562271 preclinical study in PC3M-luc-C6 local implant and metastasis
xenograft models. Cancer Biology & Therapy, 10(3), 235-243

27.   Tiwari, K., Matthews, L., May, B., Shamovsky, V., Orlic-Milacic, M., Rothfels, K.,
Ragueneau, E., Gong, C., Stephan, R., Li, N., Wu, G., Stein, L., D'Eustachio, P., &
Hermjakob, H. (2023). ChatGPT usage in the Reactome curation process. bioRxiv

28.   Chen, Q., Sun, H., Liu, H., Jiang, Y., Ran, T., Jin, X., Xiao, X., Lin, Z., & Chen, H.
(2023). An extensive benchmark study on biomedical text generation and mining with
ChatGPT. Bioinformatics, 39(9), btad557

29.   Hamed, A. A., Lee, B. S., Crimi, A., & Misiak, M. M. (2022). Challenging the machinery
of generative AI with fact-checking: Ontology-driven biological graphs for verifying
human disease-gene links. Bioinformatics (In press)

30.   Lim, S. L., Tan, C. S., Chua, J. W., & Teo, C. (2015). Integrating physiological data into
personalized cancer management: Opportunities and challenges. Annals of the Academy
of Medicine Singapore, 44(10), 361-368

31.   Armitage, P., & Doll, R. (2004). The age distribution of cancer and a multi-stage theory of
carcinogenesis. British Journal of Cancer, 91(12), 1983-1989

32.   Li, T., Fan, J., & Wang, B. (2016). TIMER: a web server for comprehensive analysis of
tumor-infiltrating immune cells. Cancer Research, 77(21), e108-e110

33.   Sun, L., Li, H. M., Seufferheld, M. J., Walters Jr, K. R., Margam, V. M., Jannasch, A.,
Diaz, N., Riley, C. P., Sun, W., Li, Y. F., Muir, W. M., Xie, J., Wu, J., Zhang, F., Chen, J.
Y., Barker, E. L., Adamec, J., & Pittendrigh, B. R. (2011). *Systems-scale analysis reveals
pathways involved in cellular response to methamphetamine*. PLoS One, 6(4): e18215

34.   Wan, P., Wu, J., Zhou, Y., Xiao, J., Feng, J., Zhao, W., Xiang, S., Jiang, G., & Chen, J. Y.
(2011). *Computational analysis of drought stress-associated miRNAs and miRNA co-*
regulation network in Physcomitrella patens. Genomics Proteomics Bioinformatics, 9(1–
2), 37–44
35.   Chen, J. Y., Sun, Y., Nagrath, D., Dhawan, P., Mathew, M., & Adamec, J. (2010). *Multi-*
omic profiling for an integrative understanding of multidrug resistance in cancer. BMC
Genomics, 11(Suppl 2): S12
36.   Yue, Z., Zheng, Q., Neylon, M. T., Yoo, M., Shin, J., Zhao, Z., Tan, A. C., & Chen, J. Y.
(2018). *PAGER 2.0: an update to the pathway, annotated-list and gene-signature*
electronic repository for Human Network Biology. Nucleic Acids Research, 46(D1),
D668–D676
37.   Hu, J., Gao, Y., Li, J., Shang, X., & Wang, J. (2021). PAGER 3.0: an update of the
pathway annotated-list and gene-signature electronic repository for Human Network
Biology. Nucleic Acids Research, 49(D1), D1347-D1354
38.   Yue, Z., Slominski, R., Bharti, S., & Chen, J. Y. (2022). *PAGER Web APP: An*
Interactive, Online Gene Set and Network Interpretation Tool for Functional Genomics.
Frontiers in Genetics, 13, 820361
39.   Yue, Z., Kshirsagar, M. M., Nguyen, T., Suphavilai, C., Neylon, M. T., Zhu, L., Ratliff,
T., & Chen, J. Y. (2015). *PAGER: Constructing PAGs and New PAG-PAG Relationships*
for Network Biology. Bioinformatics, 31(12), i250–i257
40.   I. Harshe, H. Enderling, R. Brady-Nicholls, (2023). Predicting Patient-Specific Tumor
Dynamics: How Many Measurements Are Necessary? Cancers (Basel) 15(5):1368
41.   Harrison, R. L. (2010). Introduction To Monte Carlo Simulation. AIP Conference
Proceedings, 1204(1), 17-21
759